



TEST REPORT

Applicant: Shenzhen Enye Industrial Co., Ltd.
Address of Applicant: 3F,Factory Building 3,No.78,Huating Road, Shuiwei Community,Dalang Street, Longhua District, Shenzhen, China
Manufacturer: Shenzhen Enye Industrial Co., Ltd.
Address of Manufacturer: 3F,Factory Building 3,No.78,Huating Road, Shuiwei Community,Dalang Street, Longhua District, Shenzhen, China
Product Name: TABLET
Model No.: E10,F11,X12,X11,Y10,G10,H5,G16,T10,G15
Trade Mark: N/A
FCC ID: 2BG7D-E10
Applicable standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407
Date of Test: Jul.02, 2025-Jul.21, 2025
Date of report issued: Jul.22, 2025

Remark:

The results shown in this test report refer only to the sample(s) tested , this test report cannot be reproduced, except in full without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver

Prepared By

Shenzhen ETR Standard Technology Co., Ltd.

Address: No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Compiled by:

Reviewed by:

Approved by:

Project Engineer

Project Manager

Authorized Signature



Report Revision History		
Report No.	Description	Issue Date
ET-25072161E03	Original	Jul.22, 2025



Contents

Page

1	TEST SUMMARY	4
1.1	MEASUREMENT UNCERTAINTY	4
2	GENERAL INFORMATION	5
2.1	GENERAL DESCRIPTION OF EUT	5
2.2	TEST MODE	7
2.3	DESCRIPTION OF SUPPORT UNITS	8
2.4	TEST FACILITY	8
2.5	ADDITIONAL INSTRUCTIONS.....	8
3	TEST INSTRUMENTS LIST	9
4	TEST RESULTS AND MEASUREMENT DATA	10
4.1	ANTENNA REQUIREMENT	10
4.2	CONDUCTED EMISSIONS	11
4.3	DUTY CYCLE.....	14
4.4	CONDUCTED OUTPUT POWER.....	18
4.5	BANDWIDTH &99% OCCUPY BANDWIDTH.....	20
4.6	POWER SPECTRAL DENSITY	28
4.7	BAND EDGE.....	36
4.7.1	Conducted test Method	36
4.8	SPURIOUS EMISSION	43
4.8.1	Radiated Emission Method	43
4.9	FREQUENCY STABILITY	53
5	TEST SETUP PHOTO	59
6	EUT CONSTRUCTIONAL DETAILS.....	59

1 Test Summary

Test Item	Section in CFR 47	Result	Test by
Antenna requirement	47CRF part 15.203	Pass	/
AC Power Line Conducted Emission	47CRF part 15.207	Pass	Jason Huang
Conducted Output Power	47CRF part 15.407 (a)(1)/(a)(3)	Pass	Kara Wu
26dB Bandwidth and 99% Occupied Bandwidth	47CRF part 15.407 (a)(12)	Pass	Kara Wu
6dB Bandwidth	47CRF part 15.407 (e)	Pass	Kara Wu
Power Spectral Density	47CRF part 15.407(a)(1)/(a)(3)	Pass	Kara Wu
Band Edge	47CRF part 15.407(b)(1)/(b)(4)	Pass	Kara Wu
Spurious Emission	47CRF part 15.205/15.209 47CRF part 15.407(b)(1)/(b)(4)/(b)(8)	Pass	Jason Huang
Frequency Stability	47CRF part 15.407(g)	Pass	Kara Wu

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10:2013 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01
3. Note: Compliance determination rules
 - 1).The Compliance determination of test results does not take into account measurement uncertainty. Measurement results are determined based on regulatory limitations or requirements specified by the applicant/manufacturer. If measurement uncertainty is taken into account, the applicant/manufacturer will bear all possible risks of non-compliance.
 - 2).The measurement uncertainty please refer to each test result in the "Measurement Uncertainty"

1.1 Measurement Uncertainty

Test Item	Measurement Uncertainty	Notes
Occupied Channel Bandwidth	0.55%	(1)
RF output power, conducted	±0.57 dB	(1)
Power Spectral Density, conducted	±0.61 dB	(1)
Unwanted Emissions, conducted	±0.64 dB	(1)
AC Power Line Conducted Emission	± 2.55 dB	(1)
Radiated emissions 9K-30MHz	±3.79 dB	(1)
Radiated emissions 30M- 1GHz	± 4.24 dB	(1)
Radiated emissions 1GHz-18GHz	± 4.26 dB	(1)
Radiated emissions 18GHz-40GHz	±4.17 dB	(1)
Frequency error	Uc=1X10-7	(1)
Duty Cycle	0.03%	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

2 General Information

2.1 General Description of EUT

Product Name:	TABLET
Model No.:	E10,F11,X12,X11,Y10,G10,H5,G16,T10,G15
Difference of model(s)	All the model are the same circuit and RF module, except the model names
Test Model:	E10
Hardware Version:	P30-T616-V2.0-230801-GU
Software Version:	1.0
Sample(s) Status:	Engineer sample
Operation Frequency:	☒ 5180-5240MHz for 802.11a/n(HT20)/ac20(VHT20); 5190-5230MHz for 802.11n(HT40)/ac40(VHT40); 5210MHz for 802.11 ac80(VHT40); ☒ 5745-5825 MHz for 802.11a/n(HT20)/ac20(VHT20); 5755-5795 MHz for 802.11n(HT40)/ac40(VHT40); 5775MHz for 802.11 ac80(VHT40);
Channel numbers:	☒ 4 channels for 802.11a/n20(HT20)/ac20(VHT20) in the 5180-5240MHz band; 2 channels for 802.11 n40(HT40)/ac40(VHT40) in the 5190-5230MHz band ; 1 channels for 802.11 ac80 in the 5210(VHT80)MHz band ; ☒ 5 channels for 802.11802.11a/n20(HT20)/ac20(VHT20) in the 5745-5825MHz band ; 2 channels for 802.11 n40(HT40)/ac40(VHT40) in the 5755-5795MHz band ; 1 channels for 802.11 5210(VHT80) in the 5775MHz band
Channel bandwidth:	802.11a/802.11n(HT20)/ 802.11ac(VHT20): 20MHz 802.11n(HT40)/ 802.11ac(VHT40) : 40MHz 802.11ac(VHT80) : 80MHz
Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15; 802.11ac(VHT/20/40/80):NSS1, MCS0-MCS9
Modulation technology:	Orthogonal Frequency Division Multiplexing (OFDM) with BPSK/QPSK/16QAM/64QAM/256QAM
Antenna Type:	FPCB antenna
Antenna gain:	4.98dBi (Note: Antenna information is provided by applicant, Testing lab is not responsible for the accuracy of the information.)
Battery:	DC 3.7V 8000mAh
Power supply:	DC 5V From Adapter or DC 3.7V From Battery
Adapter Model:	N/A

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180MHz	38	5190MHz	40	5200MHz	42	5210MHz
44	5220MHz	46	5230MHz	48	5240MHz	/	/
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745MHz	151	5755MHz	153	5765MHz	155	5775MHz
157	5785MHz	159	5795MHz	161	5805MHz	/	/
165	5825MHz	/					

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)		
	802.11 a /n(HT20)/ac(VHT20)	802.11 n(HT40)/ac(VHT40)	802.11ac(VHT80)
Lowest channel	5180	5190	5210
Middle channel	5200	X	
Highest channel	5240		

Test channel	Frequency (MHz)		
	802.11 a /n(HT20)/ac(VHT20)	802.11 n(HT40)/ac(VHT40)	802.11ac(VHT80)
Lowest channel	5745	5755	5775
Middle channel	5785	X	
Highest channel	5825		

2.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: For battery operated equipment, the EUT was performed using a new DC 3.7V battery.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pretest Mode	Description
Mode 1	802.11a / n 20/ ac 20 CH36/ CH40/ CH 48 802.11a /n 20/ac 20 CH149/ CH157/ CH 165
Mode 2	802.11n 40/ac 40 CH38/ CH 46 802.11n 40/ac 40 CH 151 / CH 159
Mode 3	802.11 ac80 CH 42/CH 155
Mode 4	/
Mode 5	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11a / n 20/ ac 20 CH36/ CH40/ CH 48 802.11a /n 20/ac 20 CH149/ CH157/ CH 165
Mode 2	802.11n 40/ac 40 CH38/ CH 46 802.11n 40/ac 40 CH 151 / CH 159
Mode 3	802.11 ac80 CH 42/CH 155
Mode 4	/

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

2.3 Description of Support Units

No.	Description	Manufacturer	Model	Serial Number
1	ADAPTER	XIAOMI	MDY-11-EM	/
2	EARPHONE	FEILIDA	I6	/

2.4 Test Facility

Test laboratory:	Shenzhen ETR Standard Technology Co., Ltd.
CNAS Registration Number:	L11864
A2LA Certificate Number:	6640.01
FCC Designation Number:	CN1326
FCC Test Firm Registration:	183064
IC Company Number:	28440
IC CAB identifier:	CN0132
Laboratory location:	No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

2.5 Additional Instructions

Test Software	Engineering Mode *#*#83781#*#*
Power level setup	Default

3 Test Instruments list

Conducted Emission

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESC13	100605	2025.3.06	2026.3.05
2	Artificial power network	schwarabeck	NSLK8127	8127483	2025.3.06	2026.3.05
3	Artificial power network	ETS	3186/2NM	1132	2025.3.06	2026.3.05
4	10dB attenuator	HUBER+SUHNER	10dB	/	2025.3.06	2026.3.05
5	Cable 4	HUBER SUNNER	3M	/	2025.3.06	2026.3.05
6	Absorbing Clamp	schwarabeck	MDS21	D69250	2025.3.06	2026.3.05

Radiated Emission &RF Conducted test:

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESC17	101032	2025.3.06	2026.3.05
2	Broadband antenna	schwarabeck	VULB9168	1064	2024.3.26	2026.3.25
3	Horn antenna	schwarabeck	BBHA9120D	9120D-1145	2024.3.22	2026.3.21
4	Amplifier	EMtrace	RP01A	50117	2025.3.06	2026.3.05
5	Amplifier	Space-Dtronic	EWLAN0118G-P40	19113001	2025.3.06	2026.3.05
6	Spectrum analyzer	KEYSIGHT	N9020A	MY55370280	2025.3.06	2026.3.05
7	Power detector meter	MWRFtest	MW100-PSB	MW201020JYT	2025.3.06	2026.3.05
8	Signal generator	Agilent	N5182A	MY49060455	2025.3.06	2026.3.05
9	Spectrum analyzer	Rohde&schwarz	FSV-40N	101321	2025.3.06	2026.3.05
10	Amplifier	SKET	LNPA_1840-50	SK2019040302	2025.3.06	2026.3.05
11	Horn antenna	schwarabeck	BBHA 9170	946	2024.3.22	2026.3.21
12	Loop antenna	schwarabeck	FMZB 1519 B	1519	2024.3.22	2026.3.21
13	Cable 6	HUBER SUNNER	0.5M	/	2025.3.06	2026.3.05
14	Cable7	HUBER SUNNER	2.0M	/	2025.3.06	2026.3.05
15	Cable8	HUBER SUNNER	6.0M	/	2025.3.06	2026.3.05
16	Filter	Xin bo	XBLBQ-GTA29	210410-3-2	2025.3.06	2026.3.05
17	Power Sensor	Keysight	U2021XA	MY54111006	2025.3.06	2026.3.05
18	Temp. & Humidity Chamber	Jiecheng Instrument	QA-LP-80	20160705001	2025/3/07	2026/3/06

Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).

Software Name	Manufacturer	Model	Version
RF test software	MWRFtest	MTS 8310	V2.0.0.0
Conducted test software	EZ-EMC	Farad	Ver.EMC-CON 3A1.1
Radiated test software	EZ-EMC	Farad	Ver.FA-03A2 RE

4 Test results and Measurement Data

4.1 Antenna requirement

Standard requirement:	47CRF Part 15.203
<i>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i>	
E.U.T Antenna:	
<i>The antenna is fpcb antenna, the best case gain of the antenna is 4.98dBi, reference to the appendix II for details.</i>	

4.2 Conducted Emissions


Test Requirement:	47CRF Part 15.207						
Test Method:	ANSI C63.10:2013						
Test Frequency Range:	150KHz to 30MHz						
Class / Severity:	Class B						
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto						
Limit:	Frequency range (MHz)		Limit (dBuV)				
			Quasi-peak		Average		
	0.15-0.5		66 to 56*		56 to 46*		
	0.5-5		56		46		
	5-30		60		50		
* Decreases with the logarithm of the frequency.							
Test setup:	Reference Plane Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m						
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.						
Test Instruments:	Refer to section 3.0 for details						
Test mode:	Refer to section 2.2 for details						
Test environment:	Temp.:	27.1°C	Humid.:	54%	Press.:	1012mbar	
Test voltage:	AC 120V						
Test results:	Pass						

Remark:

1. Both high voltage and low voltage have been tested, and the report only shows the worst case data with AC 120V/60Hz.
2. All mode have been tested, the report only shows the worst mode (802.11n20 5180MHz)


Measurement Result

Line:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1545	27.00	9.80	36.80	65.75	-28.95	QP
2	0.1545	10.96	9.80	20.76	55.75	-34.99	AVG
3	0.1949	25.54	9.81	35.35	63.83	-28.48	QP
4	0.1949	9.93	9.81	19.74	53.83	-34.09	AVG
5	0.2355	27.29	9.82	37.11	62.25	-25.14	QP
6	0.2355	12.76	9.82	22.58	52.25	-29.67	AVG
7	0.4245	25.40	9.90	35.30	57.36	-22.06	QP
8	0.4245	10.53	9.90	20.43	47.36	-26.93	AVG
9	11.5080	19.82	9.82	29.64	60.00	-30.36	QP
10	11.5080	7.89	9.82	17.71	50.00	-32.29	AVG
11	15.6210	24.41	9.74	34.15	60.00	-25.85	QP
12	15.6210	10.19	9.74	19.93	50.00	-30.07	AVG

Neutral:




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1545	25.71	9.80	35.51	65.75	-30.24	QP
2	0.1545	12.29	9.80	22.09	55.75	-33.66	AVG
3	0.1949	25.23	9.81	35.04	63.83	-28.79	QP
4	0.1949	11.06	9.81	20.87	53.83	-32.96	AVG
5	0.2310	25.55	9.82	35.37	62.41	-27.04	QP
6	0.2310	10.30	9.82	20.12	52.41	-32.29	AVG
7	0.3525	24.22	9.88	34.10	58.90	-24.80	QP
8	0.3525	13.70	9.88	23.58	48.90	-25.32	AVG
9	0.4245	24.77	9.90	34.67	57.36	-22.69	QP
10	0.4245	11.17	9.90	21.07	47.36	-26.29	AVG
11	16.8945	26.29	9.72	36.01	60.00	-23.99	QP
12	16.8945	13.59	9.72	23.31	50.00	-26.69	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

4.3 Duty cycle

Test Method :	ANSI C63.10:2013	
Limit:	/	
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 25.0°C	Humid.: 57%RH
Test voltage:	DC 3.7V	
Test results:	Pass	

Measurement Result

5180-5240MHz

Mode	Duty cycle (%)	Correction Factor (dB)
TX 802.11a Mode	84.68	0.72
TX 802.11n20 Mode	84.89	0.71
TX 802.11ac20 Mode	84.71	0.72
TX 802.11n40 Mode	91.72	0.38
TX 802.11a40 Mode	91.72	0.38
TX 802.11ac80 Mode	90.78	0.42


5745-5825 MHz

Mode	Duty cycle (%)	Correction Factor (dB)
TX 802.11a Mode	84.44	0.73
TX 802.11n20 Mode	84.78	0.72
TX 802.11ac20 Mode	84.44	0.73
TX 802.11n40 Mode	96.77	0.14
TX 802.11a40 Mode	96.77	0.14
TX 802.11ac80 Mode	93.81	0.28


Test plot

5180-5240MHz


(802.11a) plot




(802.11 n20) plot




(802.11ac20) plot




(802.11 n40) plot



(802.11ac40) plot




(802.11ac80) plot




5745-5825 MHz


(802.11a) plot



(802.11 n20) plot



(802.11ac20) plot




(802.11 n40) plot




(802.11ac40) plot



(802.11ac80) plot



4.4 Conducted Output Power

Test Requirement:	47CRF Part 15.407 (a)(1)/(a)(3)	
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 ANSI C63.10-2013	
Limit:	5150-5250MHz : 250mW 5725~5850MHz : 1W	
Test setup:	 The diagram illustrates the test setup. A 'Power Sensor' is connected via red lines to an 'E.U.T.' (Equipment Under Test) and a 'PC'. Both the E.U.T. and the PC are placed on a 'Non-Conducted Table'. This table is supported by two vertical legs and sits on a 'Ground Reference Plane', which is represented by a thick grey horizontal bar at the bottom.	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 25.0°C	Humid.: 57%RH
Test voltage:	DC 3.7V	
Test results:	Pass	

Measurement Result


5180-5240MHz

Test Channel	Frequency	Correction Factor	Maximum output power	Total Power	LIMIT	Result
	(MHz)	(dB)	(dBm)	(dBm)	dBm	
TX 802.11a Mode						
CH36	5180	0.72	6.95	7.67	24	Pass
CH40	5200	0.72	7.12	7.84	24	Pass
CH48	5240	0.72	7.11	7.83	24	Pass
TX 802.11 n20 Mode						
CH36	5180	0.71	6.93	7.64	24	Pass
CH40	5200	0.71	6.61	7.32	24	Pass
CH48	5240	0.71	6.74	7.45	24	Pass
TX 802.11 ac20 Mode						
CH36	5180	0.72	6.45	7.17	24	Pass
CH40	5200	0.72	6.59	7.31	24	Pass
CH48	5240	0.72	6.55	7.27	24	Pass
TX 802.11 n40 Mode						
CH38	5190	0.38	6.01	6.39	24	Pass
CH46	5230	0.38	5.56	5.94	24	Pass
TX 802.11 ac40 Mode						
CH38	5190	0.38	5.96	6.34	24	Pass
CH46	5230	0.38	5.53	5.91	24	Pass
TX 802.11 ac80 Mode						
CH42	5210	0.42	4.74	5.16	24	Pass

5745-5825 MHz

Test Channel	Frequency	Correction Factor	Maximum output power	Total Power	LIMIT	Result
	(MHz)	(dB)	(dBm)	(dBm)	dBm	
TX 802.11a Mode						
CH149	5745	0.73	6.68	7.41	30	Pass
CH157	5785	0.73	6.75	7.48	30	Pass
CH165	5825	0.73	6.60	7.33	30	Pass
TX 802.11 n20 Mode						
CH149	5745	0.72	6.34	7.06	30	Pass
CH157	5785	0.72	6.42	7.14	30	Pass
CH165	5825	0.72	6.74	7.46	30	Pass
TX 802.11 ac20 Mode						
CH149	5745	0.73	6.37	7.10	30	Pass
CH157	5785	0.73	6.40	7.13	30	Pass
CH165	5825	0.73	6.73	7.46	30	Pass
TX 802.11 n40 Mode						
CH151	5755	0.14	5.69	5.83	30	Pass
CH159	5795	0.14	5.83	5.97	30	Pass
TX 802.11 ac40 Mode						
CH151	5755	0.14	5.17	5.31	30	Pass
CH159	5795	0.14	5.73	5.87	30	Pass
TX 802.11 ac80 Mode						
CH155	5775	0.28	5.23	5.51	30	Pass

4.5 Bandwidth & 99% Occupy Bandwidth

Test Requirement:	47CRF Part 15.407(a)(12)&15.407(e),	
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01, ANSI C63.10:2013	
Limit:	Measurements in the 5.725-5.85 GHz band, the minimum bandwidth 6 dB bandwidth of U-NII devices shall be at least 500KHz. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 25.0°C	Humid.: 57%RH
Test voltage:	DC 3.7V	
Test results:	Pass	


Measurement Result

5180-5240MHz


Test CH	-26dB Channel Bandwidth (MHz)						Result
	802.11a	802.11n (HT20)	802.11ac (HT20)	802.11n (HT40)	802.11ac (HT40)	802.11ac (HT80)	
Lowest	19.82	19.84	19.86	39.73	40.24	--	Pass
Middle	19.71	19.76	19.79	--	--	80.81	
Highest	19.75	19.74	19.67	39.49	39.57	--	

Test plot 99% Occupy Bandwidth


(802.11a) plot on channel 36




(802.11 n20) plot on channel 36




(802.11a) plot on channel 40




(802.11 n20) plot on channel 40



(802.11a) plot on channel 48




(802.11 n20) plot on channel 48




Test plot


(802.11ac20) plot on channel 36




(802.11 n40) plot on channel 38




(802.11ac20) plot on channel 40



(802.11 n40) plot on channel 46




(802.11ac20) plot on channel 48




Test plot


(802.11ac40) plot on channel 38



(802.11ac80) plot on channel 42



(802.11ac40) plot on channel 46




5745-5825MHz

Test CH	-6dB Channel Bandwidth (MHz)						Limit (KHz)	Result
	802.11a	802.11n (HT20)	802.11ac (HT20)	802.11n (HT40)	802.11ac (HT40)	802.11ac (HT80)		
Lowest	15.11	15.38	14.97	35.12	35.10	--	>500	Pass
Middle	15.05	15.68	15.70	--	--	75.10		
Highest	15.56	15.68	14.60	35.09	35.04	--		


Remark: "---" is not applicable

Test plot


(802.11a) plot on channel 149




(802.11 n20) plot on channel 149




(802.11a) plot on channel 157




(802.11 n20) plot on channel 157



(802.11a) plot on channel 165




(802.11 n20) plot on channel 165




Test plot


(802.11ac20) plot on channel 149




(802.11 n40) plot on channel 151




(802.11ac20) plot on channel 157



(802.11 n40) plot on channel 159




(802.11ac20) plot on channel 165




Test plot


(802.11 ac40) plot on channel 151




(802.11 ac80) plot on channel 155



(802.11 ac40) plot on channel 159



4.6 Power Spectral Density

Test Requirement:	47CRF Part 15.407(a)(1)/ (a)(3)	
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01, ANSI C63.10:2013	
Limit:	Frequency band (MHz)	Limit
	5150-5250	≤17dBm/1MHz for master device
		≤11dBm/1MHz for client device
	5250-5350	≤11dBm/1MHz for client device
	5470-5725	≤11dBm/1MHz for client device
	5725-5850	≤30dBm/500kHz
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 25.0°C	Humid.: 57%RH
Test voltage:	DC 3.7V	
Test results:	Pass	

Measurement Result

5180-5240MHz

Mode	Frequency	Measured Power Density (dBm/MHz)	Correction Factor (dB)	Total Measured Power Density (dBm/MHz)	Limit (dBm/MHz)
802.11 a	5180 MHz	-6.604	0.720	-5.884	11
	5200 MHz	-6.249	0.720	-5.529	11
	5240 MHz	-6.413	0.720	-5.693	11
802.11 n20	5180 MHz	-6.379	0.710	-5.669	11
	5200 MHz	-6.947	0.710	-6.237	11
	5240 MHz	-6.595	0.710	-5.885	11
802.11 ac20	5180 MHz	-7.675	0.720	-6.955	11
	5200 MHz	-7.377	0.720	-6.657	11
	5240 MHz	-7.610	0.720	-6.890	11
802.11 n40	5190 MHz	-9.173	0.380	-8.793	11
	5230 MHz	-10.500	0.380	-10.120	11
802.11 ac40	5190 MHz	-11.622	0.380	-11.242	11
	5230 MHz	-11.979	0.380	-11.599	11
802.11 ac80	5210 MHz	-15.842	0.420	-15.422	11

(802.11a) PSD plot on channel 36



(802.11n20) PSD plot on channel 36



(802.11a) PSD plot on channel 40



(802.11n20) PSD plot on channel 40



(802.11a) PSD plot on channel 48




(802.11n20) PSD plot on channel 48




(802.11ac20) PSD plot on channel 36



(802.11n40) PSD plot on channel 38



(802.11ac20) PSD plot on channel 40




(802.11n40) PSD plot on channel 46



(802.11ac20) PSD plot on channel 48




(802.11ac40) PSD plot on channel 38



(802.11ac80) PSD plot on channel 42



(802.11ac40) PSD plot on channel 46



Mode	Frequency	Measured Power Density (dBm/510KHz)	Measured Power Density (dBm/500KHz)	Correction Factor (dB)	Total Measured Power Density (dBm/500KHz)	Limit (dBm/MHz)
802.11 a	5745 MHz	-9.553	-9.639	0.730	-8.909	30
	5785 MHz	-9.169	-9.255	0.730	-8.525	30
	5825 MHz	-9.264	-9.350	0.730	-8.620	30
802.11 n20	5745 MHz	-10.109	-10.195	0.720	-9.475	30
	5785 MHz	-10.127	-10.213	0.720	-9.493	30
	5825 MHz	-9.448	-9.534	0.720	-8.814	30
802.11ac20	5745 MHz	-10.549	-10.635	0.730	-9.905	30
	5785 MHz	-10.362	-10.448	0.730	-9.718	30
	5825 MHz	-9.871	-9.957	0.730	-9.227	30
802.11 n40	5755 MHz	-14.322	-14.408	0.140	-14.268	30
	5795 MHz	-13.971	-14.057	0.140	-13.917	30
802.11ac40	5755 MHz	-14.840	-14.926	0.140	-14.786	30
	5795 MHz	-13.942	-14.028	0.140	-13.888	30
802.11ac80	5775 MHz	-17.963	-18.049	0.280	-17.769	30

Note: 1. If the measurement is X dBm/510kHz, thus $X \text{ dBm/510kHz} = (10^{X/10}) * (500 / 510) \text{ dBm/500kHz}$

2. Correction Factor (dB)= duty cycle factor

(802.11a) PSD plot on channel 149



(802.11n20) PSD plot on channel 149



(802.11a) PSD plot on channel 157



(802.11n20) PSD plot on channel 157



(802.11a) PSD plot on channel 165



(802.11n20) PSD plot on channel 165



(802.11ac20) PSD plot on channel 149



(802.11n40) PSD plot on channel 151



(802.11ac20) PSD plot on channel 157



(802.11n40) PSD plot on channel 159



(802.11ac20) PSD plot on channel 165




(802.11ac40) PSD plot on channel 151



(802.11ac80) PSD plot on channel 155




(802.11ac40) PSD plot on channel 159



4.7 Band edge


4.7.1 Conducted test Method

Test Requirement:	47CRF Part 15.209 and 15.205	
Test Method:	ANSI C63.10: 2013	
Limit:	All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.	
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.	
Test Procedure:	1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range. 3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span. 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. 5. Repeat above procedures until all measured frequencies were complete..	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 25.0°C	Humid.: 57%RH
Test voltage:	DC 3.7V	
Test results:	Pass	


Remark: Due to the margin value of the sideband test being greater than the antenna gain value, the test meets the requirements

5.180~5.240 GHz

(802.11a) Band Edge, Left Side



(802.11n20) Band Edge, Left Side



(802.11a) Band Edge, Right Side




(802.11n20) Band Edge, Right Side




Remark: The antenna gain and cable loss were not compensated in the test data, and the margin value of the Band Edge test was greater than the sum of the antenna gain and cable loss, so the test met the requirements


(802.11ac20) Band Edge, Left Side



(802.11n40) Band Edge, Left Side



(802.11ac20) Band Edge, Right Side




(802.11n40) Band Edge, Right Side



Remark: The antenna gain and cable loss were not compensated in the test data, and the margin value of the Band Edge test was greater than the sum of the antenna gain and cable loss, so the test met the requirements


(802.11ac40) Band Edge, Left Side



(802.11ac80) Band Edge




(802.11ac40) Band Edge, Right Side




Remark: The antenna gain and cable loss were not compensated in the test data, and the margin value of the Band Edge test was greater than the sum of the antenna gain and cable loss, so the test met the requirements

5.745~5.825 GHz


(802.11a) Band Edge, Left Side



(802.11n20) Band Edge, Left Side



(802.11a) Band Edge, Right Side




(802.11n20) Band Edge, Right Side



Remark: Antenna gain and cable loss data included in Offset.


(802.11ac20) Band Edge, Left Side



(802.11n40) Band Edge, Left Side



(802.11ac20) Band Edge, Right Side




(802.11n40) Band Edge, Right Side



Remark: Antenna gain and cable loss data included in Offset.


(802.11ac40) Band Edge, Left Side



(802.11ac80) Band Edge





(802.11ac40) Band Edge, Right Side




Remark: Antenna gain and cable loss data included in Offset.

4.8 Spurious Emission

4.8.1 Radiated Emission Method

Test Requirement:	47CRF Part 15.209, Part 15E Section 15.407(b)(4)					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	9kHz to 40GHz					
Test site:	Measurement Distance: 3m					
Receiver setup:	Frequency	Detector	RBW	VBW	Value	
	9kHz-150KHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	
	150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value	
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value	
	Above 1GHz	Peak	1MHz	3MHz	Peak Value	
		AV	1MHz	3MHz	Average Value	
Limit:	Frequency		Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz		2400/F(KHz)	QP	300m	
	0.490MHz-1.705MHz		24000/F(KHz)	QP	300m	
	1.705MHz-30MHz		30	QP	30m	
	30MHz-88MHz		100	QP	3m	
	88MHz-216MHz		150	QP		
	216MHz-960MHz		200	QP		
	960MHz-1GHz		500	QP		
	Frequency		Limit (dBm/MHz)	Remark		
	Above 1GHz		-27.0	Peak Value		
	Test setup:	For radiated emissions from 9kHz to 30MHz				
						
		For radiated emissions from 30MHz to 1GHz				
						
	For radiated emissions above 1GHz					

	
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Remarks:

1. The report only shows the worst mode.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Measurement Data:

9 kHz ~ 30 MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Below 1GHz

Remark: The test data shows only the worst case 802.11n20 mode.


Temperature:	25.0°C	Relative Humidity:	57%
Pressure:	101.2kPa	Test Voltage :	DC 3.7V From Battery
Test Mode :	5.8G TX- 802.11n20 (5180MHz)		

Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	46.1779	39.44	-20.95	18.49	40.00	-21.51	QP
2	86.5027	46.23	-20.34	25.89	40.00	-14.11	QP
3	205.6750	52.21	-18.60	33.61	43.50	-9.89	QP
4	250.3009	49.18	-18.25	30.93	46.00	-15.07	QP
5	383.9318	41.55	-16.83	24.72	46.00	-21.28	QP
6	790.6186	36.66	-7.64	29.02	46.00	-16.98	QP

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	50.5859	41.83	-20.97	20.86	40.00	-19.14	QP
2	86.5027	44.40	-20.16	24.24	40.00	-15.76	QP
3	152.6640	46.38	-18.96	27.42	43.50	-16.08	QP
4	208.5801	45.70	-18.65	27.05	43.50	-16.45	QP
5	250.3010	53.22	-18.25	34.97	46.00	-11.03	QP
6	790.6186	37.09	-7.64	29.45	46.00	-16.55	QP

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The test data shows only the worst case 802.11a mode

Above 1GHz:

Remark: The test data shows only the worst case 802.11n20 mode.

Temperature:	25.0°C	Relative Humidity:	57%
Pressure:	101.2kPa	Test Voltage :	DC 3.7V From Battery
Test Mode :	5.2G TX- 802.11n20		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
Low Channel:5180MHz							
V	10360.00	42.20	1.77	43.97	68.20	-24.23	PK
V	10360.00	37.54	1.77	39.31	54.00	-14.69	AV
V	15540.00	46.84	7.72	54.56	74.00	-19.44	PK
V	15540.00	36.10	7.72	43.82	54.00	-10.18	AV
V	20720.00	52.41	-5.73	46.68	68.20	-21.52	PK
V	20720.00	47.85	-5.73	42.12	54.00	-11.88	AV
V	25900.00	49.01	-2.89	46.12	68.20	-22.08	PK
V	25900.00	43.71	-2.89	40.82	54.00	-13.18	AV
V	31080.00	45.96	1.66	47.62	68.20	-20.58	PK
V	31080.00	41.18	1.66	42.84	54.00	-11.16	AV
V	36260.00	43.01	4.63	47.64	68.20	-20.56	PK
V	36260.00	38.18	4.63	42.81	54.00	-11.19	AV
H	10360.00	41.66	1.77	43.43	68.20	-24.77	PK
H	10360.00	37.02	1.77	38.79	54.00	-15.21	AV
H	15540.00	46.63	7.72	54.35	74.00	-19.65	PK
H	15540.00	36.49	7.72	44.21	54.00	-9.79	AV
H	20720.00	52.18	-5.73	46.45	68.20	-21.75	PK
H	20720.00	46.95	-5.73	41.22	54.00	-12.78	AV
H	25900.00	49.00	-2.89	46.11	68.20	-22.09	PK
H	25900.00	44.11	-2.89	41.22	54.00	-12.78	AV
H	31080.00	45.21	1.66	46.87	68.20	-21.33	PK
H	31080.00	40.01	1.66	41.67	54.00	-12.33	AV
H	36260.00	42.88	4.63	47.51	68.20	-20.69	PK
H	36260.00	38.66	4.63	43.29	54.00	-10.71	AV

Remark:

1. Emission Level = Meter Reading + Factor,
Factor=Antenna Factor + Cable Loss – Pre-amplifier
Margin= Emission Level – Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
Middle Channel:5200Hz							
V	10400.00	41.65	1.85	43.50	68.20	-24.70	PK
V	10400.00	37.39	1.85	39.24	54.00	-14.76	AV
V	15600.00	46.34	7.64	53.98	74.00	-20.02	PK
V	15600.00	35.75	7.64	43.39	54.00	-10.61	AV
V	20800.00	52.17	-5.67	46.50	68.20	-21.70	PK
V	20800.00	47.14	-5.67	41.47	54.00	-12.53	AV
V	26000.00	49.16	-2.85	46.31	68.20	-21.89	PK
V	26000.00	43.90	-2.85	41.05	54.00	-12.95	AV
V	31200.00	45.33	1.57	46.90	68.20	-21.30	PK
V	31200.00	40.37	1.57	41.94	54.00	-12.06	AV
V	36400.00	43.01	4.93	47.94	68.20	-20.26	PK
V	36400.00	38.67	4.93	43.60	54.00	-10.40	AV
H	10400.00	42.12	1.85	43.97	68.20	-24.23	PK
H	10400.00	38.07	1.85	39.92	54.00	-14.08	AV
H	15600.00	48.02	7.64	55.66	74.00	-18.34	PK
H	15600.00	37.56	7.64	45.20	54.00	-8.80	AV
H	20800.00	53.16	-5.67	47.49	68.20	-20.71	PK
H	20800.00	47.83	-5.67	42.16	54.00	-11.84	AV
H	26000.00	47.02	-2.85	44.17	68.20	-24.03	PK
H	26000.00	34.59	-2.85	31.74	54.00	-22.26	AV
H	31200.00	45.18	1.57	46.75	68.20	-21.45	PK
H	31200.00	39.99	1.57	41.56	54.00	-12.44	AV
H	36400.00	42.74	4.93	47.67	68.20	-20.53	PK
H	36400.00	37.79	4.93	42.72	54.00	-11.28	AV

Remark:

1. Emission Level = Meter Reading + Factor,
Factor=Antenna Factor + Cable Loss – Pre-amplifier
Margin= Emission Level – Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
High Channel:5240MHz							
V	10480.00	43.28	2.02	45.30	68.20	-22.90	PK
V	10480.00	38.48	2.02	40.50	54.00	-13.50	AV
V	15720.00	45.39	7.46	52.85	74.00	-21.15	PK
V	15720.00	35.31	7.46	42.77	54.00	-11.23	AV
V	20960.00	52.49	-5.56	46.93	68.20	-21.27	PK
V	20960.00	47.44	-5.56	41.88	54.00	-12.12	AV
V	26200.00	48.37	-2.50	45.87	68.20	-22.33	PK
V	26200.00	44.08	-2.50	41.58	54.00	-12.42	AV
V	31440.00	45.48	1.39	46.87	68.20	-21.33	PK
V	31440.00	40.54	1.39	41.93	54.00	-12.07	AV
V	36680.00	42.47	5.25	47.72	68.20	-20.48	PK
V	36680.00	38.22	5.25	43.47	54.00	-10.53	AV
H	10480.00	42.45	2.02	44.47	68.20	-23.73	PK
H	10480.00	37.51	2.02	39.53	54.00	-14.47	AV
H	15720.00	46.76	7.46	54.22	74.00	-19.78	PK
H	15720.00	36.30	7.46	43.76	54.00	-10.24	AV
H	20960.00	53.25	-5.56	47.69	68.20	-20.51	PK
H	20960.00	47.78	-5.56	42.22	54.00	-11.78	AV
H	26200.00	48.82	-2.50	46.32	68.20	-21.88	PK
H	26200.00	44.78	-2.50	42.28	54.00	-11.72	AV
H	31440.00	45.73	1.39	47.12	68.20	-21.08	PK
H	31440.00	41.60	1.39	42.99	54.00	-11.01	AV
H	36680.00	43.50	5.15	48.65	68.20	-19.55	PK
H	36680.00	43.28	5.15	48.43	54.00	-5.57	AV

Remark:

1. Emission Level = Meter Reading + Factor,
Factor=Antenna Factor + Cable Loss – Pre-amplifier
Margin= Emission Level – Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Temperature:	25.0℃	Relative Humidity:	57%
Pressure:	101.2kPa	Test Voltage :	DC 3.7V From Battery
Test Mode :	5.8G TX- 802.11a		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
Low Channel:5745MHz							
V	11490.00	46.06	3.31	49.37	74.00	-24.63	PK
V	11490.00	36.72	3.31	40.03	54.00	-13.97	AV
V	17235.00	42.48	10.10	52.58	68.20	-15.62	PK
V	17235.00	37.29	10.10	47.39	54.00	-6.61	AV
V	22980.00	54.36	-4.61	49.75	74.00	-24.25	PK
V	22980.00	45.04	-4.61	40.43	54.00	-13.57	AV
V	28725.00	46.96	0.87	47.83	68.20	-20.37	PK
V	28725.00	41.87	0.87	42.74	54.00	-11.26	AV
V	34470.00	43.15	3.82	46.97	68.20	-21.23	PK
V	34470.00	38.61	3.82	42.43	54.00	-11.57	AV
H	11490.00	46.35	3.31	49.66	74.00	-24.34	PK
H	11490.00	36.06	3.31	39.37	54.00	-14.63	AV
H	17235.00	41.02	10.10	51.12	68.20	-17.08	PK
H	17235.00	35.98	10.10	46.08	54.00	-7.92	AV
H	22980.00	56.62	-4.61	52.01	74.00	-21.99	PK
H	22980.00	45.93	-4.61	41.32	54.00	-12.68	AV
H	28725.00	46.94	0.87	47.81	68.20	-20.39	PK
H	28725.00	42.67	0.87	43.54	54.00	-10.46	AV
H	34470.00	43.54	3.82	47.36	68.20	-20.84	PK
H	34470.00	39.38	3.82	43.20	54.00	-10.80	AV

Remark:

- Emission Level = Meter Reading + Factor,
Factor=Antenna Factor + Cable Loss – Pre-amplifier
Margin= Emission Level – Limit
- If peak below the average limit, the average emission was no test.
- The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
Low Channel:5785MHz							
V	11570.00	46.72	3.34	50.06	74.00	-23.94	PK
V	11570.00	36.46	3.34	39.80	54.00	-14.20	AV
V	17355.00	42.45	10.52	52.97	68.20	-15.23	PK
V	17355.00	37.85	10.52	48.37	54.00	-5.63	AV
V	23140.00	54.02	-4.66	49.36	74.00	-24.64	PK
V	23140.00	44.38	-4.66	39.72	54.00	-14.28	AV
V	28925.00	46.46	1.36	47.82	68.20	-20.38	PK
V	28925.00	42.78	1.36	44.14	54.00	-9.86	AV
V	34710.00	42.94	3.95	46.89	68.20	-21.31	PK
V	34710.00	38.23	3.95	42.18	54.00	-11.82	AV
H	11570.00	47.51	3.34	50.85	74.00	-23.15	PK
H	11570.00	37.41	3.34	40.75	54.00	-13.25	AV
H	17355.00	40.83	10.52	51.35	68.20	-16.85	PK
H	17355.00	33.97	10.52	44.49	54.00	-9.51	AV
H	23140.00	53.40	-4.66	48.74	74.00	-25.26	PK
H	23140.00	42.27	-4.66	37.61	54.00	-16.39	AV
H	28925.00	52.18	1.36	53.54	68.20	-14.66	PK
H	28925.00	46.75	1.36	48.11	54.00	-5.89	AV
H	34710.00	52.45	3.95	56.40	68.20	-11.80	PK
H	34710.00	41.53	3.95	45.48	54.00	-8.52	AV

Remark:


1. Emission Level = Meter Reading + Factor,
Factor=Antenna Factor + Cable Loss – Pre-amplifier
Margin= Emission Level – Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
Low Channel:5825MHz							
V	11650.00	45.12	3.36	48.48	74.00	-25.52	PK
V	11650.00	35.84	3.36	39.20	54.00	-14.80	AV
V	17475.00	41.77	10.93	52.70	68.20	-15.50	PK
V	17475.00	37.35	10.93	48.28	54.00	-5.72	AV
V	23300.00	52.27	-4.77	47.50	68.20	-20.70	PK
V	23300.00	47.02	-4.77	42.25	54.00	-11.75	AV
V	29125.00	46.92	1.65	48.57	68.20	-19.63	PK
V	29125.00	41.53	1.65	43.18	54.00	-10.82	AV
V	34950.00	41.51	4.09	45.60	68.20	-22.60	PK
V	34950.00	37.83	4.09	41.92	54.00	-12.08	AV
H	11650.00	47.95	3.36	51.31	74.00	-22.69	PK
H	11650.00	37.26	3.36	40.62	54.00	-13.38	AV
H	17475.00	39.94	10.93	50.87	68.20	-17.33	PK
H	17475.00	36.26	10.93	47.19	54.00	-6.81	AV
H	23300.00	51.26	-4.77	46.49	68.20	-21.71	PK
H	23300.00	47.85	-4.77	43.08	54.00	-10.92	AV
H	29125.00	47.78	1.65	49.43	68.20	-18.77	PK
H	29125.00	43.36	1.65	45.01	54.00	-8.99	AV
H	34950.00	45.12	4.09	49.21	68.20	-18.99	PK
H	34950.00	35.84	4.09	39.93	54.00	-14.07	AV

Remark:

1. Emission Level = Meter Reading + Factor,
Factor=Antenna Factor + Cable Loss – Pre-amplifier
Margin= Emission Level – Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

4.9 Frequency stability

Test Requirement:	47CRF Part 15.407(g)
Test Method:	ANSI C63.10:2013, FCC Part 2.1055
Limit:	Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified
Test Procedure:	a. The EUT was placed inside the environmental test chamber and powered by nominal DC voltage. b. Turn the EUT on and couple its output to a spectrum analyzer. c. Turn the EUT off and set the chamber to the highest temperature specified. d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 Minutes. e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 Minute s. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Remark: Set the EUT transmits at un-modulation mode to test frequency stability.

Measurement data:

Frequency stability versus Temp.					
Power Supply: DC 3.7V					
Temp. (°C)	Operating Frequency (MHz)	0 minute	2 minute	5 minute	10 minute
		Measured Frequency (MHz)	Measured Frequency (MHz)	Measured Frequency (MHz)	Measured Frequency (MHz)
-30	5180	5179.985	5179.952	5179.992	5180.000
	5190	5189.976	5189.982	5189.993	5189.999
	5200	5199.984	5200.007	5199.984	5199.993
	5210	5209.976	5209.991	5299.992	5209.983
	5220	5219.997	5219.982	5219.984	5219.993
	5230	5229.975	5230.010	5230.005	5299.991
	5240	5239.993	5239.998	5239.983	5239.995
-20	5180	5179.994	5179.990	5179.993	5179.952
	5190	5189.990	5189.991	5189.984	5189.982
	5200	5199.985	5199.982	5199.992	5200.007
	5210	5209.991	5299.990	5209.984	5209.991
	5220	5219.986	5219.982	5220.005	5219.982
	5230	5229.984	5230.003	5229.983	5230.010
	5240	5239.957	5239.981	5240.001	5239.998
-10	5180	5179.946	5179.990	5179.993	5180.000
	5190	5189.976	5189.991	5189.984	5189.996
	5200	5200.001	5199.982	5199.992	5199.991
	5210	5209.985	5299.990	5209.984	5209.997
	5220	5219.976	5219.982	5220.005	5219.992
	5230	5230.004	5230.003	5229.983	5229.990
	5240	5239.992	5239.981	5240.001	5239.963
0	5180	5179.985	5179.952	5179.992	5180.000
	5190	5189.976	5189.982	5189.993	5189.999
	5200	5199.984	5200.007	5199.984	5199.993
	5210	5209.976	5209.991	5299.992	5209.983
	5220	5219.997	5219.982	5219.984	5219.993
	5230	5229.975	5230.010	5230.005	5299.991
	5240	5239.993	5239.998	5239.983	5239.995
10	5180	5179.973	5179.991	5179.993	5180.000
	5190	5189.984	5189.982	5189.984	5180.000
	5200	5199.975	5199.990	5199.992	5189.996
	5210	5209.976	5209.982	5209.984	5199.991
	5220	5219.983	5220.003	5220.005	5209.997
	5230	5230.001	5229.981	5229.983	5219.992
	5240	5239.973	5239.999	5240.001	5229.990
20	5180	5179.994	5179.990	5179.993	5179.952
	5190	5189.990	5189.991	5189.984	5189.982

	5200	5199.985	5199.982	5199.992	5200.007
	5210	5209.991	5299.990	5209.984	5209.991
	5220	5219.986	5219.982	5220.005	5219.982
	5230	5229.984	5230.003	5229.983	5230.010
	5240	5239.957	5239.981	5240.001	5239.998
30	5180	5179.994	5179.990	5179.993	5179.952
	5190	5189.990	5189.991	5189.984	5189.982
	5200	5199.985	5199.982	5199.992	5200.007
	5210	5209.991	5299.990	5209.984	5209.991
	5220	5219.986	5219.982	5220.005	5219.982
	5230	5229.984	5230.003	5229.983	5230.010
	5240	5239.957	5239.981	5240.001	5239.998
40	5180	5179.984	5179.979	5179.993	5179.990
	5190	5189.985	5189.990	5189.984	5189.991
	5200	5199.976	5199.981	5199.992	5199.982
	5210	5299.984	5209.982	5209.984	5299.990
	5220	5219.976	5219.989	5220.005	5219.982
	5230	5229.997	5230.007	5229.983	5230.003
	5240	5239.975	5239.979	5240.001	5239.981
50	5180	5179.946	5179.990	5179.981	5180.115
	5190	5189.976	5189.991	5189.992	5199.990
	5200	5200.001	5199.982	5199.983	5200.015
	5210	5209.985	5299.990	5209.984	5209.993
	5220	5219.976	5219.982	5219.991	5220.008
	5230	5230.004	5230.003	5230.009	5230.001
	5240	5239.992	5239.981	5239.981	5240.009

Frequency stability versus Voltage					
Temperature: 25°C					
Power Supply (VAC)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)
DC 4.25V	5180	5179.979	5179.979	5180.002	5179.996
	5190	5189.973	5189.990	5189.998	5189.982
	5200	5199.986	5199.981	5199.993	5199.983
	5210	5209.990	5209.982	5209.999	5210.005
	5220	5219.976	5219.989	5219.994	5219.991
	5230	5229.969	5230.007	5229.992	5230.001
	5240	5180.109	5179.995	5179.993	5179.979
DC 3.7V	5180	5199.984	5189.989	5189.984	5189.990
	5190	5200.009	5199.989	5199.992	5199.981
	5200	5209.987	5210.001	5209.984	5209.982
	5210	5220.002	5219.992	5220.005	5219.989
	5220	5229.995	5299.995	5229.983	5230.007
	5230	5240.003	5239.992	5240.001	5239.992
	5240	5180.109	5179.995	5179.993	5179.979
DC 5.75V	5180	5179.994	5180.000	5179.981	5179.979
	5190	5189.990	5189.996	5189.992	5189.990
	5200	5199.985	5199.991	5199.983	5199.980
	5210	5209.991	5209.997	5209.984	5209.982
	5220	5219.986	5219.992	5219.991	5219.989
	5230	5229.984	5229.990	5230.009	5230.012
	5240	5239.957	5239.963	5239.981	5239.979

Frequency stability versus Temp.					
Power Supply: DC 3.7V					
Temp. (°C)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)
-30	5745	5745.007	5744.972	5744.614	5744.960
	5755	5744.955	5754.988	5754.998	5754.982
	5775	5754.977	5774.987	5774.999	5774.991
	5785	5774.986	5784.990	5785.002	5784.982
	5795	5784.977	5795.001	5794.985	5794.993
	5825	5794.988	5824.982	5824.981	5824.996
-20	5745	5744.972	5744.972	5744.995	5744.983
	5755	5754.997	5754.988	5754.997	5755.009
	5775	5774.978	5774.987	5775.000	5775.005
	5785	5784.987	5784.990	5784.992	5784.989
	5795	5794.985	5795.001	5794.983	5794.978
	5825	5824.995	5824.982	5824.992	5824.913
-10	5745	5744.977	5744.983	5744.979	5745.047
	5755	5754.984	5754.990	5755.004	5744.612
	5775	5774.976	5775.007	5774.985	5754.996
	5785	5784.968	5784.983	5784.994	5774.997
	5795	5794.975	5794.979	5794.992	5785.000
	5825	5824.904	5824.982	5825.002	5794.983
0	5745	5744.971	5744.982	5744.985	5744.982
	5755	5754.981	5754.989	5754.992	5754.971
	5775	5775.002	5774.981	5775.009	5774.982
	5785	5784.978	5784.973	5784.985	5784.989
	5795	5794.974	5794.980	5794.981	5795.007
	5825	5824.972	5824.909	5824.984	5824.999
10	5745	5744.968	5744.993	5744.979	5744.993
	5755	5754.983	5754.995	5755.004	5755.007
	5775	5774.982	5774.998	5774.985	5774.992
	5785	5784.985	5784.990	5784.994	5784.979
	5795	5794.995	5794.981	5794.992	5794.973
	5825	5824.977	5824.990	5825.002	5825.007
20	5745	5744.988	5745.007	5744.995	5744.982
	5755	5755.002	5754.979	5755.009	5755.001
	5775	5774.987	5775.002	5774.994	5774.981
	5785	5784.974	5785.002	5784.981	5785.008
	5795	5794.968	5794.993	5794.975	5795.000
	5825	5825.002	5825.008	5825.009	5825.009
30	5745	5744.967	5744.993	5744.979	5744.993
	5755	5754.983	5754.995	5755.004	5755.007
	5775	5774.982	5774.998	5774.985	5774.992
	5785	5784.985	5784.990	5784.994	5784.979
	5795	5794.996	5794.981	5794.992	5794.973
	5825	5824.977	5824.990	5825.002	5825.007
40	5745	5744.988	5744.982	5744.979	5744.977
	5755	5754.990	5754.999	5755.004	5755.002
	5775	5774.993	5775.000	5774.985	5774.983
	5785	5784.985	5784.982	5784.994	5784.992

50	5795	5794.976	5794.999	5794.992	5794.990
	5825	5824.985	5824.997	5825.002	5825.000
	5745	5744.972	5744.982	5744.984	5744.983
	5755	5754.997	5754.999	5754.991	5754.990
	5775	5774.978	5775.000	5774.983	5775.007
	5785	5784.987	5784.982	5784.975	5784.983
	5795	5794.985	5794.999	5794.982	5794.979
	5825	5824.995	5824.997	5824.911	5824.982

Frequency stability versus Voltage					
Temperature: 25°C					
Power Supply (VAC)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)
DC 4.25V	5745	5744.967	5744.982	5744.984	5744.977
	5755	5754.983	5754.989	5755.001	5755.002
	5775	5774.982	5774.981	5775.002	5774.983
	5785	5784.985	5784.973	5784.984	5784.992
	5795	5794.996	5794.980	5795.002	5794.990
	5825	5824.977	5824.909	5824.999	5825.000
DC 3.7V	5745	5744.967	5744.993	5744.979	5744.993
	5755	5754.983	5754.995	5755.004	5755.007
	5775	5774.982	5774.998	5774.985	5774.992
	5785	5784.985	5784.990	5784.994	5784.979
	5795	5794.992	5794.981	5794.992	5794.973
	5825	5824.977	5824.990	5825.002	5825.007
DC5.75V	5745	5744.988	5745.006	5744.995	5744.982
	5755	5755.002	5754.979	5755.009	5755.001
	5775	5774.987	5775.002	5774.994	5774.981
	5785	5784.974	5785.002	5784.981	5785.008
	5795	5794.968	5794.993	5794.975	5795.000
	5825	5825.002	5825.008	5825.009	5825.009

5 Test Setup Photo

Reference to the file No.: ET-25072161SP for details.

6 EUT Constructional Details

Reference to the file No.: ET-25072161EP and ET-25072161IP for details

-----END-----