RADIO TEST REPORT

Applicant	:	Dongguan Changxie Technology Co., Ltd.
Address of Applicant	:	Room 101, Building 1, No. 3, Nanya 1st Street, Daojiao Town, Dongguan City,Guangdong Province, China
Manufacturer	:	Dongguan Changxie Technology Co., Ltd.
Address of Manufacturer	:	Room 101, Building 1, No. 3, Nanya 1st Street, Daojiao Town, Dongguan City,Guangdong Province, China
Equipment under Test	:	Earphone
Model No.	:	X2 2X, X1 2X
FCC ID	:	2BG892025X12X
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10-2020+Cor 1-2023
Report No.	:	DDT-RE26012919-2E02
Issue Date	:	2026/04/18
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1. Summary of Test Results 7
2. General Test Information 8
2.1. Description of EUT 8
2.2. Accessories of EUT 9
2.3. Block diagram of EUT configuration for test 9
2.4. Decision of final test mode 9
2.5. Deviations of test standard 10
2.6. Test environment conditions 10
2.7. Test laboratory 10
2.8. Measurement uncertainty 11
3. Equipment Used During Conductive Test 12
4. 6 dB Bandwidth 13
4.1. Block diagram of test setup 13
4.2. Limits 13
4.3. Test procedure 13
4.4. Test result 14
4.5. Test graphs 15
5. 99% Bandwidth 17
5.1. Block diagram of test setup 17
5.2. Limits 17
5.3. Test procedure 17
5.4. Test result 18
5.5. Test graphs 19
6. Maximum Peak Output Power 21
6.1. Block diagram of test setup 21
6.2. Limits 21
6.3. Test procedure 21
6.4. Test result 22
6.5. Test graphs 23
7. Power Spectral Density 25
7.1. Block diagram of test setup 25
7.2. Limits 25
7.3. Test procedure 25
7.4. Test result 26
7.5. Test graphs 27
8. Band Edge Compliance (Conducted Method) 29

8.1. Block diagram of test setup 29
8.2. Limits 29
8.3. Test procedure 29
8.4. Test result 30
8.5. Test graphs 31
9. RF Conducted Spurious Emissions 33
9.1. Block diagram of test setup 33
9.2. Limits 33
9.3. Test procedure 33
9.4. Test result 34
9.5. Test graphs 35
10. Duty Cycle 41
10.1. Block diagram of test setup 41
10.2. Limit 41
10.3. Test procedure 41
10.4. Test result 42
10.5. Test graphs 43
11. Antenna Requirements 45
11.1. Limit 45
11.2. Result 45
12. Radiated Emission 46
12.1. Test equipment 46
12.2. Block diagram of test setup 47
12.3. Limits 48
12.4. Assistant equipment used for test 49
12.5. Test procedure 49
12.6. Test result 51
12.7. Test data 52
13. Band Edge Compliance 68
13.1. Test equipment 68
13.2. Block diagram of test setup 69
13.3. Limits 69
13.4. Assistant equipment used for test 69
13.5. Test procedure 69
13.6. Test result 69
13.7. Test data 70
14. Power Line Conducted Emissions 78
14.1. Test equipment 78

14.2. Block diagram of test setup 78
14.3. Limits 78
14.4. Assistant equipment used for test 79
14.5. Test procedure 79
14.6. Test result 79
14.7. Test data 80
15. Test Setup Photograph 84
16. Photos of the EUT 86

Test Report Declare

Applicant	:	Dongguan Changxie Technology Co., Ltd.
Address of Applicant	:	Room 101, Building 1, No. 3, Nanya 1st Street, Daojiao Town, Dongguan City,Guangdong Province, China
Equipment under Test	:	Earphone
Model No.	:	X2 2X, X1 2X
Manufacturer	:	Dongguan Changxie Technology Co., Ltd.
Address of Manufacturer	:	Room 101, Building 1, No. 3, Nanya 1st Street, Daojiao Town, Dongguan City,Guangdong Province, China

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10-2020+Cor 1-2023

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE26012919-2E02		
Date of Receipt:	2026/02/04	**Date of Test:**	2026/02/04 - 2026/04/01

Created: Chen Ziqin	Reviewed: Zoe Peng	Approved: Ella Gong
Chen Ziqin	Zoe peng	Ella Gong
2026/03/31	2026/04/18	2026/04/18

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
V0	Initial issue	2026/04/18	Ella Gong

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	6 dB Bandwidth and 99% Bandwidth	47 CFR Part 15 15.247(a)(2)	/	Pass
2	Peak Output Power	47 CFR Part 15 15.247(b)(3)	/	Pass
3	Power Spectral Density	47 CFR Part 15 15.247(e)	/	Pass
4	RF Conducted Spurious Emissions	47 CFR Part 15 15.247(d)	/	Pass
5	Radiated Emission	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d)	/	Pass
6	Band Edge Compliance	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d)	/	Pass
7	Antenna Requirement	47 CFR Part 15 15.203	/	Pass
8	Power Line Conducted Emissions	47 CFR Part 15 15.207(a)	/	Pass
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

EUT Name	:	Earphone
Model Number	:	X2 2X, X1 2X
Difference of model number	:	The above model is exactly the same in terms of its schematic diagram and structure, except for the differences in model number and the position of the buttons. Therefore, the tests we conducted on the model with the number X2 2X
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	DC 5V from USB cable or DC 3.7V built-in battery
Antenna Type	:	SMD CERAMIC ANTENNA
Max Antenna Gain(dBi)	:	2.67

Radio Specification	:	Bluetooth LE
Operation Frequency	:	2402 MHz to 2480 MHz
Modulation	:	GFSK

Bluetooth LE 1Mbps Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		
Bluetooth LE 2Mbps Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464

4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	/	
13	2428	27	2456	/	
The channels denoted with the grey background are excluded, because they are primary advertising channel only for the Bluetooth LE 1Mbps according to the Bluetooth Core Specification.					

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☒” means to be chosen or applicable; “□” means don’t to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
Loudspeaker microphone	/	/	/
Type-C charging cable	/	/	/

2.3. Block diagram of EUT configuration for test

EUT

2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:
Test software: FCC_Assist_1.0.4.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table:

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, Tx Power Setting, Channel, and Frequency			
Mode	Setting Tx Power	Channel	Frequency (MHz)
GFSK 1M	Default	CH0	2402
	Default	CH19	2440
	Default	CH39	2480
GFSK 2M	Default	CH1	2404
	Default	CH19	2440
	Default	CH38	2478

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15℃ to +35 ℃
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.9%
Peak Output Power (Conducted) (Spectrum analyzer)	0.98 dB
Peak Output Power (Conducted) (Power Sensor)	1.18 dB
Power Spectral Density (Base EIRP)	1.51 dB
Power Spectral Density (Spectrum analyzer)	0.98 dB
Frequencies Stability	1.9 kHz
Conducted spurious emissions	1.21 dB (9 kHz ≤ f < 7 GHz);
	3.31 dB (7 GHz ≤ f < 40 GHz)
Uncertainty for radio frequency (RBW < 20 kHz)	5.5×10^{-8}
Time	0.11%
Temperature	0.3 ℃
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.28 dB (Antenna Polarize: V)
	4.14 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.22 dB (1 - 6 GHz)
	4.52 dB (6 GHz - 18 GHz)
	4.58 dB (18 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.32dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☒RF Connected Test (RF Measurement System 3#)				
SIGNAL ANALYZER	R&S	FSV40	101407	2026/07/06
Wideband Radio Communication Tester	R&S	CMW500	117491	2027/03/28
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY62153058	2026/07/06
MXG Vector Signal Generator	Agilent	N5182A	MY48180912	2027/03/28
RF Control Unit	Tonscend	JS0806-2	20C8060230	2027/03/28
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2027/03/28
Test Software	Tonscend	JS1120-3	V3.6.21	N/A

4. 6 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

(1) The test according to ANSI C63.10 clause 11.8.
(2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
(3) Set the EUT as maximum power setting and enable the EUT transmit continuously
(4) Use the following spectrum analyzer settings for 6 dB Bandwidth:

RBW:	100 kHz
VBW:	≥ [3 × RBW]
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(5) Allow the trace to stabilize, measure the 6 dB bandwidth of signal, and record the results in the report.

4.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,41.7%RH	Test Date:	2026.03.26
Test Power Supply:	Battery	Sample Number:	S26012919-032

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	0.76	2401.63	2402.40	0.5	PASS
		2440	0.78	2439.62	2440.40	0.5	PASS
		2480	0.78	2479.62	2480.40	0.5	PASS
BLE_2M	Ant1	2404	1.27	2403.35	2404.62	0.5	PASS
		2440	1.25	2439.35	2440.61	0.5	PASS
		2478	1.24	2477.36	2478.60	0.5	PASS

4.5. Test graphs

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



BLE_2M_Ant1_2404



BLE_2M_Ant1_2440



BLE_2M_Ant1_2478



5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

(1) The test according to ANSI C63.10 clause 6.9.3.
(2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
(3) Set the EUT as maximum power setting and enable the EUT transmit continuously
(4) Use the following spectrum analyzer settings for the 99% Bandwidth:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(5) Allow the trace to stabilize, measure the 99% bandwidth of signal, and record the results in the report.

5.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,41.7%RH	Test Date:	2026.03.26
Test Power Supply:	Battery	Sample Number:	S26012919-032

Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	1.1548	2401.4446	2402.5994	---	---
		2440	1.1988	2439.4206	2440.6194	---	---
		2480	1.2428	2479.4046	2480.6474	---	---
BLE_2M	Ant1	2404	2.0799	2402.9870	2405.0669	---	---
		2440	2.0859	2438.9870	2441.0729	---	---
		2478	2.0919	2476.9870	2479.0789	---	---

5.5. Test graphs

BLE_1M_Ant1_2402



Date: 25.MAR.2026 11:29:32

BLE_1M_Ant1_2440



Date: 25.MAR.2026 11:31:47

BLE_1M_Ant1_2480



Date: 25.MAR.2026 11:33:38

BLE_2M_Ant1_2404



BLE_2M_Ant1_2440



BLE_2M_Ant1_2478



6. Maximum Peak Output Power

6.1. Block diagram of test setup



6.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi, the e.i.r.p shall not exceed 4W.

6.3. Test procedure

(1) The test according to ANSI C63.10 clause 11.9.1.1.
(2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
(3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
(4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW:	≥DTS bandwidth
VBW:	≥3 x RBW
Span	≥3 x RBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use peak marker function to determine the peak amplitude level.

6.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,41.7%RH	Test Date:	2026.03.26
Test Power Supply:	Battery	Sample Number:	S26012919-032

Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-1.91	≤30	PASS
		2440	-0.91	≤30	PASS
		2480	-1.28	≤30	PASS
BLE_2M	Ant1	2404	-1.97	≤30	PASS
		2440	-0.90	≤30	PASS
		2478	-1.46	≤30	PASS

6.5. Test graphs

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



BLE_2M_Ant1_2404



BLE_2M_Ant1_2440



BLE_2M_Ant1_2478



7. Power Spectral Density

7.1. Block diagram of test setup



7.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. Test procedure

(1) The test according to ANSI C63.10 clause 11.10.2.
(2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
(3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
(4) Use the following spectrum analyzer settings for Power Spectral Density measurement:

Center frequency	DTS Channel center frequency
RBW:	3 kHz ≤ RBW ≤ 100 kHz
VBW:	≥ 3RBW
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,41.7%RH	Test Date:	2026.03.26
Test Power Supply:	Battery	Sample Number:	S26012919-032

Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-18.13	≤8.00	PASS
		2440	-16.68	≤8.00	PASS
		2480	-17.08	≤8.00	PASS
BLE_2M	Ant1	2404	-21.09	≤8.00	PASS
		2440	-19.57	≤8.00	PASS
		2478	-19.93	≤8.00	PASS

7.5. Test graphs

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



BLE_2M_Ant1_2404



BLE_2M_Ant1_2440



BLE_2M_Ant1_2478



8. Band Edge Compliance (Conducted Method)

8.1. Block diagram of test setup



8.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

8.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.

8.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,41.7%RH	Test Date:	2026.03.26
Test Power Supply:	Battery	Sample Number:	S26012919-032

Mode	Frequency [MHz]	Measured Range	Verdict
GFSK 1M	2402	2.310 GHz - 2.410 GHz	Pass
	2480	2.470 GHz - 2.500 GHz	Pass
GFSK 2M	2404	2.310 GHz - 2.410 GHz	Pass
	2478	2.470 GHz - 2.500 GHz	Pass

8.5. Test graphs

BLE_1M_Ant1_Low_2402



BLE_1M_Ant1_High_2480



BLE_2M_Ant1_Low_2404



BLE_2M_Ant1_High_2478


Spectrum
Ref Level 20.00 dBm Offset 10.00 dB RBW 100 kHz
Att 20 dB SWT 1 ms VBW 300 kHz Mode Sweep
1Pk View
M1[1] -2.27 dBm 2.4780100 GHz
M2[1] -54.04 dBm 2.4835000 GHz
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
D1 -22.270 dBm
M1
M4
Start 2.47 GHz 691 pts Stop 2.5 GHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.47801 GHz -2.27 dBm
M2 1 2.4835 GHz -54.04 dBm
M3 1 2.5 GHz -56.36 dBm
M4 1 2.4836522 GHz -52.89 dBm
Date: 25.MAR.2026 11:40:34

9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup



9.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	≥Span/RBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

9.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,41.7%RH	Test Date:	2026.03.26
Test Power Supply:	Battery	Sample Number:	S26012919-032

Mode	Frequency [MHz]	Verdict
GFSK 1M	2402	Pass
	2440	Pass
	2480	Pass
GFSK 2M	2404	Pass
	2440	Pass
	2478	Pass

9.5. Test graphs

BLE_1M_Ant1_2402_0~Reference



BLE_1M_Ant1_2402_30~1000



BLE_1M_Ant1_2402_1000~26500



BLE_1M_Ant1_2440_0~Reference



BLE_1M_Ant1_2440_30~1000



BLE_1M_Ant1_2440_1000~26500



BLE_1M_Ant1_2480_0~Reference



BLE_1M_Ant1_2480_30~1000



BLE_1M_Ant1_2480_1000~26500



BLE_2M_Ant1_2404_0~Reference



BLE_2M_Ant1_2404_30~1000



BLE_2M_Ant1_2404_1000~26500



BLE_2M_Ant1_2440_0~Reference



BLE_2M_Ant1_2440_30~1000



BLE_2M_Ant1_2440_1000~26500



BLE_2M_Ant1_2478_0~Reference



BLE_2M_Ant1_2478_30~1000



BLE_2M_Ant1_2478_1000~26500



10. Duty Cycle

10.1. Block diagram of test setup



10.2. Limit

Just for Report.

10.3. Test procedure

(1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.
set the Spectrum Analyzer as below:
Centre Frequency: The centre frequency of the middle hopping channel.
Resolution BW: 10 MHz.
Video BW: 10 MHz.
Span: Zero span.
Detector: Peak.
Trace Mode: Clear Write.
Sweep: Video Trigger

(2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.

(3) Calculate dwell time follow below formula:
Duty cycle= Pulse's on time / Burst cycle

10.4. Test result

Test Engineer:	Zeng Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,41.7%RH	Test Date:	2026.03.26
Test Power Supply:	Battery	Sample Number:	S26012919-032

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
BLE_1M	Ant1	2402	1.24	1.88	65.96	1.81
		2440	1.24	1.88	65.96	1.81
		2480	1.24	1.88	65.96	1.81
BLE_2M	Ant1	2404	0.63	1.87	33.69	4.72
		2440	0.63	1.87	33.69	4.72
		2478	0.63	1.87	33.69	4.72

10.5. Test graphs

BLE_1M_Ant1_2402



Date: 25.MAR.2026 11:29:04

BLE_1M_Ant1_2440



Date: 25.MAR.2026 11:31:19

BLE_1M_Ant1_2480



Date: 25.MAR.2026 11:33:11

BLE_2M_Ant1_2404



BLE_2M_Ant1_2440



BLE_2M_Ant1_2478



11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2. Result

The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.

12. Radiated Emission

12.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2027/02/27
Radiation disturbance fully automated test software	Tonscend	JS32-RE	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2026/07/06
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/10/10
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/10/10
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	/
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/10/10
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2027/02/27
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2027/02/27
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2027/02/27
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2026/08/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27

12.2. Block diagram of test setup







12.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

(2) FCC 15.209 Limit

FREQUENCY	DISTANCE	FIELD STRENGTHS LIMIT	
MHz	Meters	uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dBuV/m(Peak) 54.0 dBuV/m(Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$Limit_{3m}(dBuV/m)= Limit_{30m}(dBuV/m) + 40Log(30m/3m)$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits.

12.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

12.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m

30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0°to 360°on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz,110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) For 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is reported)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.

12.6. Test result

PASS. (See below detailed test result)

12.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-25	**Tested By**:	Cao Jie
Test Mode:	TX BLE1M 2402MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC BELOW 1G\3		
Memo:	Sample Number:S26012919-028		



Final Data List									
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	30.000	34.62	10.50	3.78	16.60	40.00	23.40	QP	Horizontal
2	38.940	29.42	12.29	3.91	13.32	40.00	26.68	QP	Horizontal
3	54.828	27.5	12.82	4.02	12.04	40.00	27.96	QP	Horizontal
4	96.009	28.4	11.19	4.28	11.57	43.50	31.93	QP	Horizontal
5	119.991	30.52	9.70	4.42	12.32	43.50	31.18	QP	Horizontal
6	891.373	30.32	21.55	7.10	27.02	46.00	18.98	QP	Horizontal

Note:
1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-25	**Tested By**:	Cao Jie
Test Mode:	TX BLE1M 2402MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC BELOW 1G\4		
Memo:	Sample Number:S26012919-028		



Final Data List									
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	30.000	36.55	10.50	3.78	18.53	40.00	21.47	QP	Vertical
2	39.159	30.46	12.27	3.91	14.34	40.00	25.66	QP	Vertical
3	55.798	29.19	12.94	4.03	13.86	40.00	26.14	QP	Vertical
4	95.942	32.16	11.14	4.28	15.28	43.50	28.22	QP	Vertical
5	369.737	25.81	15.58	5.58	14.50	46.00	31.50	QP	Vertical
6	936.215	26.64	22.10	7.20	24.26	46.00	21.74	QP	Vertical

Note:
1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-25	**Tested By**:	Cao Jie
Test Mode:	TX BLE2M 2404MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC BELOW 1G\5		
Memo:	Sample Number:S26012919-028		



Final Data List									
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	30.296	33.95	10.44	3.78	15.87	40.00	24.13	QP	Horizontal
2	38.777	31.45	12.28	3.90	15.33	40.00	24.67	QP	Horizontal
3	48.736	27.89	13.49	3.97	13.05	40.00	26.95	QP	Horizontal
4	96.009	28.26	11.19	4.28	11.43	43.50	32.07	QP	Horizontal
5	119.991	29.6	9.70	4.42	11.40	43.50	32.10	QP	Horizontal
6	887.631	27.79	21.55	7.09	24.46	46.00	21.54	QP	Horizontal

Note:
1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-25	**Tested By**:	Cao Jie
Test Mode:	TX BLE2M 2404MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC BELOW 1G\6		
Memo:	Sample Number:S26012919-028		



Final Data List									
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	30.000	35.74	10.50	3.78	17.72	40.00	22.28	QP	Vertical
2	38.968	31.3	12.30	3.91	15.21	40.00	24.79	QP	Vertical
3	54.522	29.22	13.03	4.02	13.97	40.00	26.03	QP	Vertical
4	95.942	31.42	11.14	4.28	14.54	43.50	28.96	QP	Vertical
5	229.361	27.05	12.11	5.00	11.76	46.00	34.24	QP	Vertical
6	910.960	27.16	21.94	7.14	24.41	46.00	21.59	QP	Vertical

Note:
1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE1M 2402MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\1		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3822.000	45.75	30.64	4.55	-39.63	41.31	74.00	32.69	PK	Horizontal
2	4836.900	44.71	32.69	5.14	-39.78	42.76	74.00	31.24	PK	Horizontal
3	7526.300	42.69	36.53	5.80	-39.85	45.17	74.00	28.83	PK	Horizontal
4	9020.600	41.02	38.66	6.80	-38.62	47.86	74.00	26.14	PK	Horizontal
5	10841.300	40.90	39.25	7.29	-39.62	47.82	74.00	26.18	PK	Horizontal
6	11864.700	42.10	38.54	7.76	-39.60	48.80	74.00	25.20	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE1M 2402MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\2		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3811.800	45.83	30.76	4.55	-39.62	41.52	74.00	32.48	PK	Vertical
2	4898.100	43.97	33.09	5.18	-39.79	42.45	74.00	31.55	PK	Vertical
3	7504.200	43.15	36.84	5.80	-39.85	45.94	74.00	28.06	PK	Vertical
4	9137.900	41.84	38.76	6.78	-38.75	48.63	74.00	25.37	PK	Vertical
5	11414.200	41.78	39.66	7.58	-39.60	49.42	74.00	24.58	PK	Vertical
6	12344.100	41.26	39.27	7.81	-39.32	49.02	74.00	24.98	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE1M 2440MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\3		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3786.300	45.79	30.60	4.54	-39.61	41.32	74.00	32.68	PK	Horizontal
2	4904.900	44.03	33.10	5.19	-39.79	42.53	74.00	31.47	PK	Horizontal
3	7497.400	43.17	36.88	5.79	-39.85	45.99	74.00	28.01	PK	Horizontal
4	9110.700	41.99	38.21	6.79	-38.72	48.27	74.00	25.73	PK	Horizontal
5	10679.800	40.84	39.44	7.17	-39.63	47.82	74.00	26.18	PK	Horizontal
6	11398.900	41.77	39.79	7.57	-39.60	49.53	74.00	24.47	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE1M 2440MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\4		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4036.200	46.12	31.12	4.59	-39.70	42.13	74.00	31.87	PK	Vertical
2	5064.700	44.95	32.92	5.27	-39.79	43.35	74.00	30.65	PK	Vertical
3	7480.400	43.75	36.78	5.79	-39.85	46.47	74.00	27.53	PK	Vertical
4	9061.400	41.19	38.69	6.79	-38.67	48.00	74.00	26.00	PK	Vertical
5	10647.500	41.58	39.34	7.15	-39.64	48.43	74.00	25.57	PK	Vertical
6	11844.300	41.91	38.56	7.75	-39.60	48.62	74.00	25.38	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE1M 2480MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\5		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3998.800	46.17	30.89	4.57	-39.70	41.93	74.00	32.07	PK	Horizontal
2	4852.200	45.17	32.91	5.15	-39.79	43.44	74.00	30.56	PK	Horizontal
3	7517.800	43.54	36.65	5.80	-39.85	46.14	74.00	27.86	PK	Horizontal
4	9153.200	42.28	38.96	6.78	-38.77	49.25	74.00	24.75	PK	Horizontal
5	11154.100	41.98	38.85	7.47	-39.60	48.70	74.00	25.30	PK	Horizontal
6	12301.600	41.27	39.40	7.81	-39.36	49.12	74.00	24.88	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE1M 2480MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\6		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4068.500	46.60	31.16	4.62	-39.71	42.67	74.00	31.33	PK	Vertical
2	4991.600	45.01	33.02	5.24	-39.80	43.47	74.00	30.53	PK	Vertical
3	7351.200	42.82	36.99	5.74	-39.86	45.69	74.00	28.31	PK	Vertical
4	9054.600	41.05	38.82	6.79	-38.66	48.00	74.00	26.00	PK	Vertical
5	11383.600	41.15	39.60	7.56	-39.60	48.71	74.00	25.29	PK	Vertical
6	12291.400	40.39	39.38	7.81	-39.37	48.21	74.00	25.79	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE2M 2478MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\7		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3789.700	45.75	30.67	4.54	-39.62	41.34	74.00	32.66	PK	Horizontal
2	4921.900	45.60	33.10	5.20	-39.79	44.11	74.00	29.89	PK	Horizontal
3	7356.300	42.82	36.96	5.74	-39.86	45.66	74.00	28.34	PK	Horizontal
4	9119.200	41.98	38.38	6.78	-38.73	48.41	74.00	25.59	PK	Horizontal
5	11414.200	41.29	39.66	7.58	-39.60	48.93	74.00	25.07	PK	Horizontal
6	12318.600	41.19	39.34	7.81	-39.35	48.99	74.00	25.01	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE2M 2478MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\8		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3779.500	46.32	30.45	4.54	-39.61	41.70	74.00	32.30	PK	Vertical
2	4870.900	44.65	32.98	5.16	-39.79	43.00	74.00	31.00	PK	Vertical
3	7495.700	42.67	36.87	5.79	-39.85	45.48	74.00	28.52	PK	Vertical
4	9054.600	41.74	38.82	6.79	-38.66	48.69	74.00	25.31	PK	Vertical
5	11237.400	42.22	38.73	7.50	-39.60	48.85	74.00	25.15	PK	Vertical
6	12214.900	40.42	39.23	7.81	-39.43	48.03	74.00	25.97	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE2M 2440MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\9		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3886.600	46.80	30.74	4.56	-39.65	42.45	74.00	31.55	PK	Horizontal
2	4847.100	44.83	32.85	5.15	-39.78	43.05	74.00	30.95	PK	Horizontal
3	7380.100	43.19	36.82	5.75	-39.86	45.90	74.00	28.10	PK	Horizontal
4	9153.200	41.28	38.96	6.78	-38.77	48.25	74.00	25.75	PK	Horizontal
5	10690.000	41.36	39.47	7.18	-39.63	48.38	74.00	25.62	PK	Horizontal
6	11852.800	41.79	38.55	7.75	-39.60	48.49	74.00	25.51	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE2M 2440MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\10		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3954.600	46.95	30.36	4.56	-39.68	42.19	74.00	31.81	PK	Vertical
2	4865.800	45.06	32.96	5.16	-39.79	43.39	74.00	30.61	PK	Vertical
3	7477.000	42.64	36.76	5.79	-39.85	45.34	74.00	28.66	PK	Vertical
4	9064.800	41.87	38.63	6.79	-38.67	48.62	74.00	25.38	PK	Vertical
5	10684.900	40.91	39.45	7.18	-39.63	47.91	74.00	26.09	PK	Vertical
6	11732.100	42.75	38.53	7.70	-39.60	49.38	74.00	24.62	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE2M 2404MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\11		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3866.200	46.52	30.49	4.55	-39.65	41.91	74.00	32.09	PK	Horizontal
2	4780.800	45.96	32.14	5.10	-39.78	43.42	74.00	30.58	PK	Horizontal
3	7516.100	43.59	36.67	5.80	-39.85	46.21	74.00	27.79	PK	Horizontal
4	9046.100	42.09	38.87	6.79	-38.65	49.10	74.00	24.90	PK	Horizontal
5	10690.000	40.46	39.47	7.18	-39.63	47.48	74.00	26.52	PK	Horizontal
6	12337.300	41.44	39.29	7.81	-39.33	49.21	74.00	24.79	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE2M 2404MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\12		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3767.600	45.72	30.19	4.54	-39.61	40.84	74.00	33.16	PK	Vertical
2	4876.000	45.08	33.00	5.17	-39.79	43.46	74.00	30.54	PK	Vertical
3	7410.700	43.61	36.68	5.76	-39.86	46.19	74.00	27.81	PK	Vertical
4	9030.800	41.69	38.75	6.80	-38.63	48.61	74.00	25.39	PK	Vertical
5	11431.200	41.27	39.49	7.58	-39.60	48.74	74.00	25.26	PK	Vertical
6	12322.000	41.15	39.33	7.81	-39.34	48.95	74.00	25.05	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

13. Band Edge Compliance

13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2027/02/27
Radiation disturbance fully automated test software	Tonscend	JS32-RE	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2026/07/06
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/10/10
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/10/10
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	/
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/10/10
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2027/02/27
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2027/02/27
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2027/02/27
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2026/08/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27

13.2. Block diagram of test setup



13.3. Limits

All restriction band should comply with 15.209 limits, other emission should be at least 20 dB below the fundamental.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

13.5. Test procedure

Same with Radiated Emission except change investigated frequency range.
Remark: All restriction band have been tested, and only the worst case is shown in report.

13.6. Test result

PASS. (See below detailed test result)

13.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE2M 2404MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\13		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2389.380	19.02	27.46	3.77	0.00	50.25	74.00	23.75	PK	Horizontal
2	2390.000	14.17	27.46	3.78	0.00	45.41	74.00	28.59	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE2M 2404MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\14		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2388.830	14.15	27.47	3.77	0.00	45.39	74.00	28.61	PK	Vertical
2	2390.000	11.30	27.46	3.78	0.00	42.54	74.00	31.46	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE1M 2402MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\15		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2385.280	18.52	27.49	3.77	0.00	49.78	74.00	24.22	PK	Horizontal
2	2390.000	16.33	27.46	3.78	0.00	47.57	74.00	26.43	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE1M 2402MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\16		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2386.230	13.23	27.48	3.77	0.00	44.48	74.00	29.52	PK	Vertical
2	2390.000	12.99	27.46	3.78	0.00	44.23	74.00	29.77	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE1M 2480MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\17		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2483.500	10.73	27.54	3.88	0.00	42.15	74.00	31.85	PK	Horizontal
2	2484.772	13.63	27.55	3.88	0.00	45.06	74.00	28.94	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE1M 2480MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\18		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2483.500	11.54	27.54	3.88	0.00	42.96	74.00	31.04	PK	Vertical
2	2487.505	14.96	27.58	3.88	0.00	46.42	74.00	27.58	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE2M 2478MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\19		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2483.500	13.24	27.54	3.88	0.00	44.66	74.00	29.34	PK	Horizontal
2	2484.145	14.40	27.54	3.88	0.00	45.82	74.00	28.18	PK	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2026-03-19	**Tested By**:	Cao Jie
Test Mode:	TX BLE2M 2478MHz Mode	**Power Supply**:	Battery
Condition:	Temp:23.0°C;Humi:59.5%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2026 report data\Q26012919-4E\FCC ABOVE 1G BLE\20		
Memo:	Sample Number:S26012919-028		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2483.500	11.84	27.54	3.88	0.00	43.26	74.00	30.74	PK	Vertical
2	2485.786	13.30	27.56	3.88	0.00	44.74	74.00	29.26	PK	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

14. Power Line Conducted Emissions

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
EMI Test Receiver	R&S	ESCI 3	DDT-ZC01972	2027/02/27
Two Line V-Network	R&S	ENV216	DDT-ZC00586	2026/07/06
Pulse Limiter	R&S	KH43101	DDT-ZC00747	2027/02/27
Coaxial signal signal cable	H&S	RG214-5	DDT-ZC01817	2027/02/27
Conducted Radiated Software	Audix	e3	DDT-ZC00562	/
Two Line V-Network	R&S	ENV216	DDT-ZC02058	2026/07/06

14.2. Block diagram of test setup



14.3. Limits

Frequency	Quasi-Peak Level dB(uV)	Average Level dB(uV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Adapter	Xiaomi	MOY-11-EX	Xiaomi fast charging 33W	Input: 100-240V~ 50/60Hz, Output: 5V/3A or 9V/3A or 12V/2.25A or 20V/1.35A or 11V/3A MAX

14.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

14.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: "-----" means Peak detection; "-----" means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

14.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 5# Shield Room	D:\2026 report data\Q26012919-4E\0319 CE.EM6	
Test Date	: 2026-03-19	**Tested By**	: Jiahao Yang
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX BLE1M 2402MHz Mode
Condition	: Temp:24.9°C,Humi:60.7%	**LISN**	: 2025 2# 216/LINE
Memo	: S26012919-040		

Data: 6



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBµV)	Limit Line (dBµV)	Margin (dB)	Detector	Phase
1	0.27	14.19	9.46	0.07	10.24	33.96	61.20	27.24	QP	LINE
2	0.27	9.21	9.46	0.07	10.24	28.98	51.20	22.22	Average	LINE
3	0.56	13.16	9.50	0.11	10.33	33.10	56.00	22.90	QP	LINE
4	0.56	7.59	9.50	0.11	10.33	27.53	46.00	18.47	Average	LINE
5	0.78	15.46	9.51	0.14	10.37	35.48	56.00	20.52	QP	LINE
6	0.78	11.00	9.51	0.14	10.37	31.02	46.00	14.98	Average	LINE
7	1.41	10.88	9.50	0.19	10.40	30.97	56.00	25.03	QP	LINE
8	1.41	5.89	9.50	0.19	10.40	25.98	46.00	20.02	Average	LINE
9	4.70	2.54	9.54	0.24	10.27	22.59	56.00	33.41	QP	LINE
10	4.70	-4.88	9.54	0.24	10.27	15.17	46.00	30.83	Average	LINE
11	14.75	-6.98	9.74	0.32	10.21	13.29	60.00	46.71	QP	LINE
12	14.75	-12.08	9.74	0.32	10.21	8.19	50.00	41.81	Average	LINE

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 5# Shield Room	D:\2026 report data\Q26012919-4E\0319 CE.EM6	
Test Date	: 2026-03-19	**Tested By**	: Jiahao Yang
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX BLE1M 2402MHz Mode
Condition	: Temp:24.9°C,Humi:60.7%	**LISN**	: 2025 2# 216/NEUTRAL
Memo	: S26012919-040		

Data: 8



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBµV)	Limit Line (dBµV)	Margin (dB)	Detector	Phase
1	0.15	17.84	9.49	0.05	10.21	37.59	65.96	28.37	QP	NEUTRAL
2	0.15	10.72	9.49	0.05	10.21	30.47	55.96	25.49	Average	NEUTRAL
3	0.31	14.14	9.48	0.07	10.26	33.95	60.10	26.15	QP	NEUTRAL
4	0.31	8.85	9.48	0.07	10.26	28.66	50.10	21.44	Average	NEUTRAL
5	0.77	13.81	9.48	0.14	10.37	33.80	56.00	22.20	QP	NEUTRAL
6	0.77	8.24	9.48	0.14	10.37	28.23	46.00	17.77	Average	NEUTRAL
7	1.54	10.90	9.50	0.20	10.39	30.99	56.00	25.01	QP	NEUTRAL
8	1.54	5.41	9.50	0.20	10.39	25.50	46.00	20.50	Average	NEUTRAL
9	4.90	1.95	9.54	0.24	10.26	21.99	56.00	34.01	QP	NEUTRAL
10	4.90	-4.96	9.54	0.24	10.26	15.08	46.00	30.92	Average	NEUTRAL
11	16.23	-4.92	9.84	0.33	10.24	15.49	60.00	44.51	QP	NEUTRAL
12	16.23	-9.98	9.84	0.33	10.24	10.43	50.00	39.57	Average	NEUTRAL

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 5# Shield Room	D:\2026 report data\Q26012919-4E\0319 CE.EM6	
Test Date	: 2026-03-19	**Tested By**	: Jiahao Yang
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX BLE2M 2404MHz Mode
Condition	: Temp:24.9°C,Humi:60.7%	**LISN**	: 2025 2# 216/NEUTRAL
Memo	: S26012919-040		

Data: 10



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBµV)	Limit Line (dBµV)	Margin (dB)	Detector	Phase
1	0.20	15.78	9.49	0.05	10.20	35.52	63.71	28.19	QP	NEUTRAL
2	0.20	10.03	9.49	0.05	10.20	29.77	53.71	23.94	Average	NEUTRAL
3	0.35	13.87	9.48	0.08	10.27	33.70	59.00	25.30	QP	NEUTRAL
4	0.35	8.33	9.48	0.08	10.27	28.16	49.00	20.84	Average	NEUTRAL
5	0.78	16.48	9.48	0.14	10.37	36.47	56.00	19.53	QP	NEUTRAL
6	0.78	11.80	9.48	0.14	10.37	31.79	46.00	14.21	Average	NEUTRAL
7	3.84	1.86	9.52	0.23	10.30	21.91	56.00	34.09	QP	NEUTRAL
8	3.84	-3.71	9.52	0.23	10.30	16.34	46.00	29.66	Average	NEUTRAL
9	4.75	1.96	9.54	0.24	10.27	22.01	56.00	33.99	QP	NEUTRAL
10	4.75	-5.54	9.54	0.24	10.27	14.51	46.00	31.49	Average	NEUTRAL
11	22.18	-6.86	9.94	0.36	10.31	13.75	60.00	46.25	QP	NEUTRAL
12	22.18	-11.82	9.94	0.36	10.31	8.79	50.00	41.21	Average	NEUTRAL

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 5# Shield Room	D:\2026 report data\Q26012919-4E\0319 CE.EM6	
Test Date	: 2026-03-19	**Tested By**	: Jiahao Yang
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX BLE2M 2404MHz Mode
Condition	: Temp:24.9°C,Humi:60.7%	**LISN**	: 2025 2# 216/LINE
Memo	: S26012919-040		

Data: 12



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBµV)	Limit Line (dBµV)	Margin (dB)	Detector	Phase
1	0.26	14.04	9.46	0.07	10.24	33.81	61.34	27.53	QP	LINE
2	0.26	8.76	9.46	0.07	10.24	28.53	51.34	22.81	Average	LINE
3	0.55	13.20	9.49	0.11	10.33	33.13	56.00	22.87	QP	LINE
4	0.55	7.98	9.49	0.11	10.33	27.91	46.00	18.09	Average	LINE
5	1.56	10.32	9.51	0.20	10.39	30.42	56.00	25.58	QP	LINE
6	1.56	5.09	9.51	0.20	10.39	25.19	46.00	20.81	Average	LINE
7	4.90	0.80	9.54	0.24	10.26	20.84	56.00	35.16	QP	LINE
8	4.90	-6.49	9.54	0.24	10.26	13.55	46.00	32.45	Average	LINE
9	11.26	-6.98	9.63	0.28	10.16	13.09	60.00	46.91	QP	LINE
10	11.26	-12.03	9.63	0.28	10.16	8.04	50.00	41.96	Average	LINE
11	21.26	-4.74	9.81	0.36	10.31	15.74	60.00	44.26	QP	LINE
12	21.26	-11.00	9.81	0.36	10.31	9.48	50.00	40.52	Average	LINE

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

16. Photos of the EUT

Please refer to DDT-Q26012919-2E appendix Ⅰ

----------End Report----------