



**Label
Location**

ULANDPOWER

Model:UN1-A80T

Specifications:BK/WF

Rated Voltage:208/240Vac

Rated Power:19.2KW

Rated Current:80A

Power Frequency:60Hz

Protection Level:NEMA3

Operating temperature:

-22°F(-30°C) to 122°F(50°C)

Conforms to:UL Std.2594

Certified to:CSA Std.C22.2#280

For use with Electric Vehicles

Ventilation Not Required

Production Date:24-20



SN: 0010021324270000



FCC ID:2BG8P-UN2A80TWF
Contains FCC ID:2AC7Z-ESPWROOM32UE



Q40G007N-236-34A XX P

ULANDPOWER

Model:UN2-A80T

Specifications:BK/WF

Rated Voltage:208/240Vac

Rated Power:19.2KW

Rated Current:80A

Power Frequency:60Hz

Protection Level:NEMA3

Operating temperature:

-22°F(-30°C) to 122°F(50°C)

Conforms to:UL Std.2594

Certified to:CSA Std.C22.2#280

For use with Electric Vehicles

Ventilation Not Required

Production Date:24-20



SN: 0010021324270000



FCC ID:2BG8P-UN2A80TWF
Contains FCC ID:2AC7Z-ESPWROOM32UE



Q40G007N-236-34A XX P