



Test Report No.:
FCC2025-0009-H

TEST REPORT

FCC ID : 2BG9T-TCLSMARTD2A
Applicant : Shenzhen TCL Smart Home Technology Co., Ltd
Product Name : TCL D2 Series Smart Door Lock
Model No. : D2 Plus,D2X Plus,D2XX Plus,D2 Plus X,D2,D2X,D2XX

CVC Testing Technology Co., Ltd.

Product Name	TCL D2 Series Smart Door Lock	Trade Mark	TCL
Type/Model	D2 Plus,D2X Plus,D2XX Plus,D2 Plus X,D2,D2X,D2XX	Sample Status	—
Applicant	Shenzhen TCL Smart Home Technology Co., Ltd		
Applicant Address	7/F,TCL G1 Building. TCL International E City, No.1001 Zhongshan Yuan Road, Nanshan		
Manufacturer	Shenzhen TCL Smart Home Technology Co., Ltd		
Manufacturer Address	7/F,TCL G1 Building. TCL International E City, No.1001 Zhongshan Yuan Road, Nanshan		
Producer	Guangdong Yongding Technology Co., Ltd		
Producer Address	No.10 Chenglong Road, Qianlong Village, Sanxiang Town, Zhongshan City, Guangdong Province		
Quantity of sample	1 pcs	Sample Identification	1-1
Tested According To	FCC Part 2 (Section 2.1091) KDB 447498 D04 Interim General RF Exposure Guidance v01 IEEE C95.1-2019	Test Item	RF Exposure
Receiving Date	2025-05-12	Date of Testing	2025-05-20
Test conclusion	The equipment under test was found to comply with the requirements of the standards applied. Final Verdict: Pass. Seal of CVC Date of issue:2025-05-26		
Note: This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.			

Approved by:

Chen Huawen



Reviewed by:

Xu Zhenfei



Tested by:

Lu Weiji



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1. GENERAL PRODUCT INFORMATION	5
1.1 GENERAL INFORMATION	5
2. HUMAN EXPOSURE ASSESSMENT	6
2.1 RF EXPOSURE TEST EXEMPTIONS FOR SINGLE SOURCE	6
2.1.1 1-MW TEST EXEMPTION	6
2.1.2 SAR-BASED EXEMPTION	6
2.1.3 MPE-BASED EXEMPTION	7
2.1.4 MPE EXPOSURE LIMITS	8
2.2 RF EXPOSURE TEST EXEMPTIONS FOR SIMULTANEOUS TRANSMISSION SOURCES	10
2.2.1 1-MW TEST EXEMPTION FOR MULTIPLE SOURCES	10
2.2.2 SIMULTANEOUS TRANSMISSION WITH BOTH SAR-BASED AND MPE-BASED TEST EXEMPTIONS	10
2.3 CLASSIFICATION	11
3. RF OUTPUT POWER	12
4. TEST RESULTS	14

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCC2025-0009-H	Original release	May.26,2025

1. General Product Information

1.1 General information

Product Name	TCL D2 Series Smart Door Lock
Model No.	D2 Plus
Additional model	D2X Plus,D2XX Plus,D2 Plus X,D2,D2X,D2XX
Power Supply	DC 6.0V
Serial Number(SN)	/
Antenna Type	Internal antenna
Antenna Gain	WIFI:3.7 dBi (provided by client) Bluetooth: 3.7 dBi (provided by client) RFID: 0.0 dBi (provided by client)
Beamforming gain	Unsupported (provided by client)
Frequency Range	Bluetooth(Low Energy 1MHz,2MHz): 2402~2480MHz IEEE 802.11b/g/n(HT20/ax(HE20): 2412~2462MHz IEEE 802.11n(HT40)/ax(HE40): 2422~2452MHz RFID: 13.110-14.010MHz
Operate Temp.Range	-20°C~+70°C

Note:

1. The information of the EUT is declared by the manufacturer.
2. The laboratory is not responsible for the product technical specification provided by the client.
3. EUT photo refer to report (Report NO.:FCC2025-0009-EUT).
4. The EUT have SISO function, provides 1 completed transmitter and 1 receiver.
5. All the models are electrical identical including the same software parameter and hardware design (i.e., circuit design, PCB Layout, RF module/circuit, antenna type(s) and antenna location, components on PCB, etc.), same mechanical structure and design (including product enclosure, materials, etc.), the only difference is the model name, color, package.

No.	Model	Difference	Remarks
1	D2 Plus	1. Only the appearance color difference is different, include Dark grey、Brushed Nickel、Obsidian Black、Aged Bronze. 2. Only the printing style/label on the surface of the package is different, the product inside the package is the same.	Inspection model
2	D2X Plus		Coverage model
3	D2XX Plus		Coverage model
4	D2 Plus X	3. D2X Plus ,D2XX Plus,D2 Plus X, the “X” is a number from 0~9,or is an alphabet in A~Z.	Coverage model
5	D2	1. The same with D2 Plus, only without fingerprint recognition module. 2. D2X ,D2XX, the “X” is a number from 0~9,or is an alphabet in A~Z.	Coverage model
6	D2X		Coverage model
7	D2XX		Coverage model

6. All the tests carried out on model D2 Plus.

2. Human Exposure Assessment

2.1 RF Exposure Test Exemptions for Single Source

2.1.1 1-mW Test Exemption

The 1 mW Test Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1 mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph § 1.1307(b)(3)(ii)(A).

The 1 mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

2.1.2 SAR-Based Exemption

A more comprehensive exemption, considering a variable power threshold that depends on both the *separation distance* and power, is provided in § 1.1307(b)(3)(i)(B). This exemption is applicable to the frequency range between 300 MHz and 6 GHz, with *test separation distances* between 0.5 cm and 40 cm, and for all RF sources in fixed, mobile, and portable device exposure conditions.

Accordingly, a RF source is considered an *RF exempt device* if its available maximum time averaged (matched conducted) power or its effective radiated power (ERP), whichever is greater, are below a specified threshold. This exemption threshold was derived based on general population 1-g SAR requirements.

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than $ERP_{20\text{cm}}$ in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)]

TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES
SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source Frequency			Minimum Distance			Threshold ERP
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	-	1.34	159m	-	35.6m	$1920R^2$
1.34	-	30	35.6m	-	1.6m	$3450R^2/f^2$
30	-	300	1.6m	-	159mm	$3.83R^2$
300	-	1500	159mm	-	31.8mm	$0.0128R^2/f^2$
1500	-	100000	31.8mm	-	0.5mm	$19.2R^2$
Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.						

2.1.3 MPE-Based Exemption

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.¹⁰ For this case, a RF source is an *RF exempt device* if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW). This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$ERP_{20cm}(mW) = \begin{cases} 2040f_{(GHz)} & 0.3GHz \leq f \leq 1.5GHz \\ 3060 & 1.5GHz \leq f \leq 6GHz \end{cases} \quad (B.1)$$

$$P_{th}(mW) = \begin{cases} ERP_{20cm} (d_{(cm)}/20cm)^x & d \leq 20cm \\ ERP_{20cm} & 20cm < d \leq 40cm \end{cases} \quad (B. 2)$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f_{(GHz)}}} \right)$$

and f is in GHz, d is the separation distance (cm), and ERP_{20cm} is per Formula (B.1).

2.1.4 MPE exposure limits

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. Mobile devices, as defined in § 2.1091 along with their applicable RF exposure limits, are characterized by the requirement of maintaining a minimum *test separation distance* ≥ 20 cm between any radiating structure of the device and nearby persons; to apply only mobile device (MPE) exposure limits. This *test separation distance* requirement must be defined for the most conservative exposure conditions, and must be fully supported for all the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2).

$$S = \frac{PG}{4\pi R^2}$$

Where

S: power density in mW/cm²

P: power input to the antenna in mW

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna in cm

Note:

1. Mobile or fixed location transmitters, minimum separation distance is 20 cm, even if calculations indicate MPE distance is less.
2. The Numeric Gain calculated by $10^{(ant.Gain*(dBi)/10)}$.
3. Each band max power which perform MPE of any configurations.

Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i)Limits for Occupational/Controlled Exposure				
0.3~3.0	614	1.63	*(100)	≤ 6
3.0~30	1842/f	4.89/f	*(900/f ²)	< 6
30~300	61.4	0.163	1.0	< 6
300~1500			f/300	< 6
1500~100000			5	< 6
(ii)Limits for General Population/Uncontrolled Exposure				
0.3~1.34	614	1.63	*(100)	< 30
1.34~30	824/f	2.19/f	*(180/f ²)	< 30
30~300	27.5	0.073	0.2	< 30
300~1500			F/1500	< 30
1500~100000			1.0	< 30
f=frequency in MHz; *=Plane wave equivalent power density.				

2.2 RF Exposure Test Exemptions for Simultaneous Transmission Sources

2.2.1 1-mW Test Exemption for Multiple Sources

As discussed in § 1.1307(b)(3)(ii)(A), the 1-mW exemption intended for single transmitters may be also applied to simultaneous transmission conditions, within the same host device, according one of the following criteria:

- a) When maximum available power each individual transmitting antenna within the same time averaging period is ≤ 1 mW, and the nearest parts of the antenna structures of the simultaneously operating transmitters are separated by at least 2 cm.
- b) When the aggregate maximum available power of all transmitting antennas is ≤ 1 mW in the same time-averaging period.

This exemption may not be combined with any other exemption.

2.2.2 Simultaneous Transmission with both SAR-based and MPE-Based Test Exemptions

This case is described in detail in § 1.1307(b)(3)(ii)(B) and covers the situations where both SAR-based and MPE-based exemption may be considered for test exemption in fixed, mobile, or portable device exposure conditions. For these cases, a device with multiple RF sources transmitting simultaneously will be considered an *RF exempt device* if the condition of Formula (1) is satisfied.

The sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE shall be less than 1, to determine simultaneous transmission exposure compliance.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{\text{Evaluated}_k}{\text{Exposure Limit}_k} \leq 1$$

Where

a is number of fixed, mobile, or portable RF sources claiming exemption using the §1.1307(b)(3)(i)(B) formula for P_{th} , including existing exempt transmitters and those being added.

b is number of fixed, mobile, or portable RF sources claiming exemption using the applicable § 1.1307(b)(3)(i)(C) Table 1 formula for Threshold ERP, including existing exempt transmitters and those being added.

c is number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance.

P_i is the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ is the exemption threshold power (P_{th}) according to the § 1.1307(b)(3)(i)(B) formula for fixed, mobile, or portable RF source i .

ERP_j is the available maximum time-averaged power or the ERP, whichever is greater, of fixed, mobile, or portable RF source j .

$ERP_{th,j}$ is exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$, according to the applicable § 1.1307(b)(3)(i)(C) Table 1 formula at the location in question.

Evaluated_k is the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation.

Exposure Limit_k is either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable sources, as applicable.

2.3 CLASSIFICATION

The antenna of this product, under normal use condition, is 20cm away from the body of the user. So, this device is classified as Mobile Device.

Method in name of	calculation method
Method 1	1-mW Test Exemption
Method 2	SAR-Based Exemption
Method 3	MPE-Based Exemption
Method 4	MPE exposure limits
Method 5	1-mW Test Exemption for Multiple Sources
Method 6	Simultaneous Transmission with both SAR-based and MPE-Based Test Exemptions

3. RF Output Power

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
11B	2412-2462MHz	16.5	±0.5	16.0	17.0
11G	2412-2462MHz	12.5	±0.5	12.0	13.0
11N20SISO	2412-2462MHz	12.5	±0.5	12.0	13.0
11N40SISO	2422-2452MHz	11.5	±0.5	11.0	12.0
11AX20SISO	2412-2462MHz	12.0	±1.0	11.0	13.0
11AX20SISO(RU26)	2412-2462MHz	13.0	±2.0	11	15.0
11AX20SISO(RU52)	2412-2462MHz	13.5	±1.5	12	15.0
11AX20SISO(RU106)	2412-2462MHz	13.5	±0.5	13	14.0
11AX40SISO	2422-2452MHz	11.5	±0.5	11.0	12.0
BLE_1M(front)	2402~2480MHz	6.0	±1.0	5.0	7.0
BLE_1M(rear)	2402~2480MHz	6.0	±1.0	5.0	7.0
RFID	13.56MHz	-47.5	±0.5	-48.0	-47.0

The conducted power turn-up tolerance reference manufacturer specification.

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	16.38	≤30.00	PASS
		2437	16.39	≤30.00	PASS
		2462	16.37	≤30.00	PASS
11G	Ant1	2412	12.91	≤30.00	PASS
		2437	12.97	≤30.00	PASS
		2462	12.67	≤30.00	PASS
11N20SISO	Ant1	2412	12.40	≤30.00	PASS
		2437	12.44	≤30.00	PASS
		2462	12.13	≤30.00	PASS
11N40SISO	Ant1	2422	11.59	≤30.00	PASS
		2437	11.63	≤30.00	PASS
		2452	11.54	≤30.00	PASS
11AX20SISO	Ant1	2412	12.09	≤30.00	PASS
		2437	12.15	≤30.00	PASS
		2462	11.80	≤30.00	PASS
11AX40SISO	Ant1	2422	11.58	≤30.00	PASS
		2437	11.69	≤30.00	PASS
		2452	11.62	≤30.00	PASS
BLE_1M	Ant1	2402	6.51	≤30.00	PASS
		2440	5.80	≤30.00	PASS
		2480	5.55	≤30.00	PASS
BLE_2M	Ant1	2402	6.51	≤30.00	PASS
		2440	5.82	≤30.00	PASS
		2480	5.55	≤30.00	PASS
RFID	Ant1	13.56	-46.18	---	PASS

Test Mode	Antenna	Channel	Ru Size	Ru Index	Result[dBm]	Conducted Limit[dBm]	Verdict
11AX20SIS O	Ant1	2412	26Tone	RU0	11.35	≤30.00	PASS
				RU4	13.75	≤30.00	PASS
				RU8	11.41	≤30.00	PASS
			52Tone	RU37	12.36	≤30.00	PASS
				RU39	14.07	≤30.00	PASS
				RU40	12.43	≤30.00	PASS
			106Tone	RU53	13.20	≤30.00	PASS
				RU54	13.19	≤30.00	PASS
		2437	26Tone	RU0	11.80	≤30.00	PASS
				RU4	14.03	≤30.00	PASS
				RU8	11.74	≤30.00	PASS
			52Tone	RU37	12.81	≤30.00	PASS
				RU39	14.34	≤30.00	PASS
				RU40	12.69	≤30.00	PASS
			106Tone	RU53	13.70	≤30.00	PASS
				RU54	13.73	≤30.00	PASS
		2462	26Tone	RU0	11.89	≤30.00	PASS
				RU4	14.10	≤30.00	PASS
				RU8	11.73	≤30.00	PASS
			52Tone	RU37	12.79	≤30.00	PASS
				RU39	14.34	≤30.00	PASS
				RU40	12.71	≤30.00	PASS
			106Tone	RU53	13.73	≤30.00	PASS
				RU54	13.72	≤30.00	PASS

Note1: The relevant measured result has the offset with cable loss already.

Note2: $\text{RFID(dBm)} = 49.02(\text{dBuV/m}) - 95.2 = -46.18(\text{dBm})$

4. Test Results

Mode	Maximum source-based time averaged conducted output power (dBm)	EIRP(dBm)	Minimum separation distance (cm)	power density[S] (mW/cm ²)	Select calculation method	Limit for Exemption (mW)	Verdict
WIFI2.4G Hz	17.00	20.7	20	0.02339	Method 4	1	Exempt from MPE
Bluetooth	7.00	10.7	20	0.00234	Method 4	1	Exempt from MPE
Mode	Fundamental Emission (dBμV/m)	Electric field strength (V/m)		Select calculation method		Limit for Electric field strength (V/m)	Verdict
RFID	49.02	0.000282		Method 4		60.77	Exempt from MPE
Mode		Calculation for Simultaneous Transmission		Select calculation method		Limit for Exemption	Verdict
Simultaneous Transmission		0.023		Method 6		1	Exempt from MPE

Note: This device has a Bluetooth transmission, a WIFI transmission and a RFID .

$$\text{Simultaneous Transmission} = (0.02339/1) + (0.000282/60.77) = 0.023$$

Therefore this device complies with FCC's RF radiation exposure limits for general population.

_____ No Body Text Below _____

Important

1. The test report is invalid without the official stamp of CVC;
2. Any part photocopies of the test report are forbidden without the written permission from CVC;
3. The test report is invalid without the signatures of Author and Reviewer;
4. The test report is invalid if altered;
5. Objections to the test report must be submitted to CVC within 15 days;
6. Generally, commission test is responsible for the tested samples only;
7. As for the test result, “—” or “ N/A” means “not applicable”, “ / ”means “not testing”, “P” means “pass” and “F” means “fail”.

Address: No.3,Tiantaiyi Road, Kaitai Avenue, Science City, Guangzhou, China (Test location)

Post Code: 510663 Tel: 020-32293888

FAX: 020 32293889 E-mail: office@cvc.org.cn