TEST REPORT

Report No.:	BCTC2406874806-1E
Applicant:	ShenZhen Loowoko Technology Limited Co.,Ltd
Product Name:	10K Qi2 MPP Wireless Power Bank
Test Model:	L-WP-10L6-Qi2
Tested Date:	2024-06-21 to 2024-07-03
Issued Date:	2024-07-03

Shenzhen BCTC Testing Co., Ltd.

FCC ID: 2BG9U-L-WP-10L6-QI2

Product Name:	10K Qi2 MPP Wireless Power Bank
Trademark:	Loowoko
Model/Type Reference:	L-WP-10L6-Qi2
Prepared For:	ShenZhen Loowoko Technology Limited Co.,Ltd
Address:	4F, 5F, Building E, NO.2 North District, Shangxue Science and Technology City, Xinxue Community, Bantian Street, Longgang District, Shenzhen, China
Manufacturer:	ShenZhen Loowoko Technology Limited Co.,Ltd
Address:	4F, 5F, Building E, NO.2 North District, Shangxue Science and Technology City, Xinxue Community, Bantian Street, Longgang District, Shenzhen, China
Prepared By:	Shenzhen BCTC Testing Co., Ltd.
Address:	1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China.
Sample Received Date:	2024-06-21
Sample Tested Date:	2024-06-21 to 2024-07-03
Issue Date:	2024-07-03
Report No.:	BCTC2406874806-1E
Test Standards:	FCC Part15.209 ANSI C63.10-2013
Test Results:	PASS

Tested by:

Shanshan. Zhang

Shanshan. Zhang / Project Handler

Approved by:

Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp.This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full.The tested sample(s) and the sample information are provided by the client.

Table Of Content

Test Report Declaration Page
1. Version 4
2. Test Summary 5
3. Measurement Uncertainty 6
4. Product Information And Test Setup 7
4.1 Product Information 7
4.2 Support Equipment 7
4.3 Test Setup Configuration 8
4.4 Test Mode 9
5. Test Facility And Test Instrument Used 10
5.1 Test Facility 10
5.2 Test Instrument Used 10
6. Conducted Emissions 12
6.1 Block Diagram Of Test Setup 12
6.2 Limit 12
6.3 Test procedure 12
6.4 EUT operating Conditions 12
6.5 Test Result 13
7. Radiated Emissions 15
7.1 Block Diagram Of Test Setup 15
7.2 Limit 16
7.3 Test procedure 16
7.4 Test Result 17
8. Bandwidth Test 23
8.1 Test Procedure 23
8.2 Test Setup 23
8.3 Test Result 24
9. Antenna Requirements 25
9.1 Limit 25
9.2 Test Result 25
10. EUT Photographs 26
11. EUT Test Setup Photographs 27

(Note: N/A Means Not Applicable)

1. Version

Report No.	Issue Date	Description	Approved
BCTC2406874806-1E	2024-07-03	Original	Valid

2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No.	Results
1	Conducted Emission	15.207	PASS
2	Radiated Emission	15.209	PASS
3	20dB Bandwidth	15.215	PASS
4	Antenna Requirement	15.203	PASS

3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
2	Conducted Emission (150kHz-30MHz)	U=3.2dB
3	humidity uncertainty	U=5.3%
4	Temperature uncertainty	U=0.59℃

4. Product Information And Test Setup

4.1 Product Information

Model/Type Reference: L-WP-10L6-Qi2
Model Differences: N/A
Hardware Version: V1.0
Software Version: V1.0
Modulation: ASK
Operation Frequency: 115kHz-205kHz, 360kHz
Antenna installation: loop coil antenna
Ratings: Input: DC 5V/3A, DC 9V/2.22A
USB output: DC 5V/2A, DC 9V/2.22A
Wireless charging: 5W/7.5W/10W/15W
Battery: DC 3.87V

4.2 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	10K Qi2 MPP Wireless Power Bank	Loowoko	L-WP-10L6-Qi2	N/A	EUT
E-2	ADAPTER	Hoco.	N18	N/A	Auxiliary
E-3	Load	N/A	N/A	N/A	Auxiliary

Notes:
1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.3 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.

Conducted Emission:

Test Mode 1, 2, 3



Radiated Spurious Emission:

Test Mode 1, 2, 3



Test Mode 4, 5, 6



4.4 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

AC Mode	Mode 1	Charging+Full Load(115-205kHz, 5W)
	Mode 2	Charging+Half Load(115-205kHz, 2.5W)
	Mode 3	Charging+Null Load(115-205kHz)
DC Mode	Mode 4	Full Load(360kHz, 15W)
	Mode 5	Half Load(115-205kHz, 7.5W)
	Mode 6	Null Load(115-205kHz)

Note: All test mode were tested and passed, only shows the worst case mode which were recorded in this report.

5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address:1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.
FCC Test Firm Registration Number: 712850
A2LA certificate registration number is: CN1212
ISED Registered No.: 23583
ISED CAB identifier: CN0017

5.2 Test Instrument Used

Conducted Emissions Test					
Equipment	**Manufacturer**	**Model#**	**Serial#**	**Last Cal.**	**Next Cal.**
Receiver	R&S	ESR3	102075	May 16, 2024	May 15, 2025
LISN	R&S	ENV216	101375	May 16, 2024	May 15, 2025
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\
Pulse limiter	Schwarzbeck	VTSD9561-F	01323	May 16, 2024	May 15, 2025

RF Conducted Test					
Equipment	**Manufacturer**	**Model#**	**Serial#**	**Last Cal.**	**Next Cal.**
Power Meter	Keysight	E4419	\	May 16, 2024	May 15, 2025
Power Sensor (AV)	Keysight	E9300A	\	May 16, 2024	May 15, 2025
Signal Analyzer 20kHz-26.5GHz	Keysight	N9020A	MY49100060	May 16, 2024	May 15, 2025
Spectrum Analyzer 9kHz-40GHz	R&S	FSP 40	\	May 16, 2024	May 15, 2025

Radiated Emissions Test (966 Chamber01)					
Equipment	**Manufacturer**	**Model#**	**Serial#**	**Last Cal.**	**Next Cal.**
966 chamber	ChengYu	966 Room	966	May 16, 2024	May 15, 2025
Receiver	R&S	ESR3	102075	May 16, 2024	May 15, 2025
Receiver	R&S	ESRP	101154	May 16, 2024	May 15, 2025
Amplifier	Schwarzbeck	BBV9744	9744-0037	May 16, 2024	May 15, 2025
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	May 21, 2024	May 20, 2025
Loop Antenna(9KHz -30MHz)	Schwarzbeck	FMZB1519B	00014	May 21, 2024	May 20, 2025
Amplifier	SKET	LAPA_01G18G-45dB	SK2021040901	May 16, 2024	May 15, 2025
Horn Antenna	Schwarzbeck	BBHA9120D	1541	May 21, 2024	May 20, 2025
Amplifier(18GHz-40GHz)	MITEQ	TTA1840-35-HG	2034381	May 16, 2024	May 15, 2025
Horn Antenn(18GHz-40GHz)	Schwarzbeck	BBHA9170	00822	May 21, 2024	May 20, 2025
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	100363	May 16, 2024	May 15, 2025
Software	Frad	EZ-EMC	FA-03A2 RE	\	\

6. Conducted Emissions

6.1 Block Diagram Of Test Setup



6.2 Limit

Frequency (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00
Notes: 1. *Decreasing linearly with logarithm of frequency. 2. The lower limit shall apply at the transition frequencies.		

6.3 Test procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

a. The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
b. The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
c. For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

6.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

6.5 Test Result

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	L
Test Mode:	Mode 2	Test Voltage:	AC 120V/60Hz



Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement = Reading Level + Correct Factor
4. Over = Measurement - Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz		dB	dBuV	dBuV	dB	Detector
1		0.1722	35.84	20.07	55.91	64.85	-8.94	QP
2		0.1722	22.29	20.07	42.36	54.85	-12.49	AVG
3		0.3731	23.21	20.08	43.29	58.43	-15.14	QP
4		0.3731	19.02	20.08	39.10	48.43	-9.33	AVG
5		1.0265	19.53	20.09	39.62	56.00	-16.38	QP
6		1.0265	16.77	20.09	36.86	46.00	-9.14	AVG
7		2.2015	21.14	20.10	41.24	56.00	-14.76	QP
8	*	2.2015	18.45	20.10	38.55	46.00	-7.45	AVG
9		9.1073	15.15	20.17	35.32	60.00	-24.68	QP
10		9.1073	12.02	20.17	32.19	50.00	-17.81	AVG
11		26.5581	14.76	20.29	35.05	60.00	-24.95	QP
12		26.5581	12.80	20.29	33.09	50.00	-16.91	AVG

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	N
Test Mode:	Mode 2	Test Voltage:	AC 120V/60Hz



Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement = Reading Level + Correct Factor
4. Over = Measurement - Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz		dB	dBuV	dBuV	dB	Detector
1		0.1725	35.51	20.07	55.58	64.84	-9.26	QP
2		0.1725	20.39	20.07	40.46	54.84	-14.38	AVG
3		0.5010	19.98	20.08	40.06	56.00	-15.94	QP
4		0.5010	15.59	20.08	35.67	46.00	-10.33	AVG
5		1.0274	18.12	20.09	38.21	56.00	-17.79	QP
6		1.0274	15.93	20.09	36.02	46.00	-9.98	AVG
7		2.2064	19.12	20.10	39.22	56.00	-16.78	QP
8	*	2.2064	17.64	20.10	37.74	46.00	-8.26	AVG
9		3.0885	18.01	20.12	38.13	56.00	-17.87	QP
10		3.0885	16.15	20.12	36.27	46.00	-9.73	AVG
11		9.1140	13.50	20.17	33.67	60.00	-26.33	QP
12		9.1140	11.94	20.17	32.11	50.00	-17.89	AVG

7. Radiated Emissions

7.1 Block Diagram Of Test Setup

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



7.2 Limit

FCC §15.209; §15.205.

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

7.3 Test procedure

Receiver Parameter	Setting
Attenuation	Auto
9kHz~150kHz	RBW 200Hz for QP
150kHz~30MHz	RBW 9kHz for QP
30MHz~1000MHz	RBW 120kHz for QP

Below 1GHz test procedure as below:
a.The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
b.The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d.For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e.The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f.If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Above 1GHz test procedure as below:
g.Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
h.Test the EUT in the lowest channel ,the middle channel ,the Highest channel.
Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

7.4 Test Result

9kHz-30MHz

Temperature:	26℃	Relative Humidity:	54%RH
Pressure:	101 kPa	Test Voltage:	AC 120V/60Hz
Test Mode:	Mode 1	Polarization:	Coaxial(Worst)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		0.0091	71.05	-7.97	63.08	128.40	-65.34	peak
2		0.0289	69.87	-7.43	62.44	118.39	-55.95	peak
3		0.0620	66.96	-7.53	59.43	111.76	-52.33	peak
4		0.1113	77.28	-7.51	69.77	106.67	-36.90	peak
5		0.3326	58.68	-7.69	50.99	97.17	-46.18	peak
6	*	0.8251	46.08	-7.36	38.72	69.29	-30.57	peak

Temperature:	26℃	Relative Humidity:	54%RH
Pressure:	101 kPa	Test Voltage:	DC 7.2V
Test Mode:	Mode 4	Polarization:	Coaxial(Worst)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		0.0631	64.03	-7.55	56.48	111.60	-55.12	peak
2		0.0946	56.12	-7.53	48.59	108.09	-59.50	peak
3		0.1216	55.04	-7.53	47.51	105.91	-58.40	peak
4		0.3607	78.32	-7.67	70.65	96.46	-25.81	peak
5		0.7188	52.53	-7.36	45.17	70.48	-25.31	peak
6	*	1.0783	53.05	-7.36	45.69	66.97	-21.28	peak

Between 30MHz – 1GHz

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase:	Horizontal
Test Mode:	Mode 1(the worst mode)	Test Voltage:	AC 120V/60Hz



Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement = Reading Level + Correct Factor
3. Over = Measurement - Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		42.1542	35.96	-14.54	21.42	40.00	-18.58	QP
2		72.3376	34.24	-18.41	15.83	40.00	-24.17	QP
3		105.2718	32.38	-16.30	16.08	43.50	-27.42	QP
4		143.8295	43.24	-19.00	24.24	43.50	-19.26	QP
5		216.0240	45.01	-15.26	29.75	46.00	-16.25	QP
6	*	360.4476	41.97	-11.35	30.62	46.00	-15.38	QP

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 1(the worst mode)	Test Voltage:	AC 120V/60Hz



Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement = Reading Level + Correct Factor
3. Over = Measurement - Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	36.3814	51.42	-15.42	36.00	40.00	-4.00	QP
2	!	42.1542	49.82	-14.54	35.28	40.00	-4.72	QP
3		73.6170	47.53	-18.63	28.90	40.00	-11.10	QP
4		95.0930	40.50	-16.65	23.85	43.50	-19.65	QP
5		143.8295	48.34	-19.00	29.34	43.50	-14.16	QP
6		199.9856	48.10	-15.72	32.38	43.50	-11.12	QP

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 4(the worst mode)	Test Voltage:	DC 3.87V



Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement = Reading Level + Correct Factor
3. Over = Measurement - Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		41.7129	29.33	-14.58	14.75	40.00	-25.25	QP
2		54.6429	26.89	-14.53	12.36	40.00	-27.64	QP
3		143.8295	33.09	-19.00	14.09	43.50	-29.41	QP
4	*	199.9856	34.93	-15.72	19.21	43.50	-24.29	QP
5		250.3012	35.92	-14.28	21.64	46.00	-24.36	QP
6		492.4685	30.26	-8.80	21.46	46.00	-24.54	QP

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 4(the worst mode)	Test Voltage:	DC 3.87V



Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement = Reading Level + Correct Factor
3. Over = Measurement - Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	40.9881	44.17	-14.64	29.53	40.00	-10.47	QP
2		73.3593	40.64	-18.59	22.05	40.00	-17.95	QP
3		88.3421	39.16	-17.79	21.37	43.50	-22.13	QP
4		143.8295	42.63	-19.00	23.63	43.50	-19.87	QP
5		199.9856	39.02	-15.72	23.30	43.50	-20.20	QP
6		492.4685	35.16	-8.80	26.36	46.00	-19.64	QP

8. Bandwidth Test

8.1 Test Procedure

1. Set RBW = 1%~5% OBW.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

8.2 Test Setup



8.3 Test Result

Frequency (kHz)	20dB bandwidth (kHz)	Result
147	0.003	Pass
360	0.017	Pass





9. Antenna Requirements

9.1 Limit

For intentional device, according to FCC 47 CFR Section 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2 Test Result

The antenna used for this product is Inductive Loop coil antenna.

10. EUT Photographs

EUT Photo 1

NOTE: Appendix-Photographs Of EUT Constructional Details

11. EUT Test Setup Photographs

Conducted emissions



Radiated Measurement Photos
30MHz-1GHz



9kHz-30MHz



STATEMENT

1. The equipment lists are traceable to the national reference standards.

2. The test report can not be partially copied unless prior written approval is issued from our lab.

3. The test report is invalid without the "special seal for inspection and testing".

4. The test report is invalid without the signature of the approver.

5. The test process and test result is only related to the Unit Under Test.

6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.

7. The quality system of our laboratory is in accordance with ISO/IEC17025.

8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:
1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: http://www.chnbctc.com

Consultation E-mail: bctc@bctc-lab.com.cn

Complaint/Advice E-mail: advice@bctc-lab.com.cn

※※※※※ END ※※※※※