

Prüfbericht-Nr.: <i>Test report no.:</i>	CN25X68F 002	Auftrags-Nr.: <i>Order no.:</i>	158304066	Seite 1 von 75 <i>Page 1 of 75</i>
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2025-02-18	
Auftraggeber: <i>Client:</i>	LEGAMI S.p.A. SB Via Stezzano 18, 24052 Azzano San Paolo BG, Italy			
Prüfgegenstand: <i>Test item:</i>	Singing in the shower – Wireless Speaker			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	SHOW0010, SHOW0011, SHOW0012			
Auftrags-Inhalt: <i>Order content:</i>	FCC and ISED Certification			
Prüfgrundlage: <i>Test specification:</i>	FCC Part 15 Subpart C, ANSI C63.10-2013, RSS-247 Issue 3 RSS-Gen Issue 5+Amendment 1+Amendment 2			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2025-02-18			
Prüfmuster-Nr.: <i>Test sample no.:</i>	A003934077-001			
Prüfzeitraum: <i>Testing period:</i>	2025-03-10 - 2025-03-25			
Ort der Prüfung: <i>Place of testing:</i>	Hong Kong			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland Hong Kong Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: <i>tested by / supervised by:</i>			genehmigt von: <i>authorized by:</i>	
Datum: <i>Date:</i>	2025-04-09	Ausstellungsdatum: <i>Issue date:</i>	2025-04-09	
Stellung / Position:	Assistant Test Engineer	Stellung / Position:	Laboratory Manager	
Sonstiges / <i>Other:</i>	"Decision Rule" document announced in our website (https://www.tuv.com/landingpage/en/qm-gcn/) describes the statement of conformity and its rule of enforcement for test results are applicable throughout this test report. FCC ID: 2BGCL-SHOW0003 IC ID: 32529-SHOW0003			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 2 von 75
Page 2 of 75

Anmerkungen Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Prüfbericht-Nr.: Test report no.:		CN25X68F 002		Seite 3 von 75 Page 3 of 75
Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result	

Table of Content

	Page
Cover Page.....	1
Table of Content	3
Product Information	5
Manufacturers declarations	5
Product function and intended use.....	5
Submitted documents	5
Independent Operation Modes	5
Related Submittal(s) Grants.....	5
Remark	5
Test Set-up and Operation Mode.....	6
Principle of Configuration Selection.....	6
Test Operation and Test Software	6
Special Accessories and Auxiliary Equipment	6
Countermeasures to achieve EMC Compliance	6
Test Methodology	7
Radiated Emission	7
Field Strength Calculation.....	7
Conducted Emission Calculation	7
Test Setup Diagram	8
Test Facility	10
Test Laboratory Information	10
List of Test and Measurement Instruments.....	11
Measurement Uncertainty	12
Results FCC Part 15 - Subpart C / RSS-247 Issue 3	13
FCC 15.203 – Antenna Requirement 1	Pass..... 13
FCC 15.204 – Antenna Requirement 2	Pass..... 13
RSS-Gen 6.3 – External Control	Pass..... 13
RSS-Gen 8.3 – Antenna Requirement.....	Pass..... 13
FCC 15.207/ RSS-Gen 8.8 – Conducted Emission on AC Mains	Pass..... 14
FCC 15.215(c) / RSS-247 5.1(a) – 20dB Bandwidth	Pass..... 15
FCC 15.247 (a)(1) / RSS-247 5.1(b) – Carrier Frequency Separation	Pass..... 15
FCC 15.247 (a)(1)(iii) / RSS-247 5.1(d) – Number of Hopping Frequency	Pass..... 16
FCC 15.247 (a)(1)(iii) / RSS-247 5.1(d) – Time of Occupancy	Pass..... 16
RSS-Gen 6.7 – Occupied Bandwidth.....	N/A..... 17
FCC 15.247(b)(1) / RSS-247 5.4(b) – Maximum Peak Conducted Output Power.....	Pass..... 18
FCC 15.247(d) / RSS-247 5.5 – Spurious Conducted Emissions.....	Pass..... 18
FCC 15.205/ RSS-Gen 8.10 – Radiated Emissions in Restricted Frequency Bands	Pass..... 19
Appendix 1 – Test Results	21

Prüfbericht-Nr.: <i>Test report no.:</i>		CN25X68F 002		Seite 4 von 75 Page 4 of 75
Absatz <i>Clause</i>	Anforderungen - Prüfungen / <i>Requirements - Tests</i>	Messergebnisse – Bemerkungen/ <i>Measuring results - Remarks</i>	Ergebnis <i>Result</i>	

Appendix 2 – Test Setup	51
Appendix 3 – EUT External Photos	55
Appendix 4 – EUT Internal Photos	59
Appendix 5 – RF Exposure information.....	65

Prüfbericht-Nr.: Test report no.:		CN25X68F 002	Seite 5 von 75 Page 5 of 75
Absatz <i>Clause</i>	Anforderungen - Prüfungen / <i>Requirements - Tests</i>	Messergebnisse – Bemerkungen/ <i>Measuring results - Remarks</i>	Ergebnis <i>Result</i>

Product Information

PMN: Singing in the shower – Wireless Speaker	HVIN: SHOW0010, SHOW0011, SHOW0012
FVIN: N/A	HMN: N/A

Manufacturers declarations

	Transmitter
Operating frequency range	2402 - 2480MHz
Type of modulation	GFSK, $\pi/4$ -DQPSK
Number of channels	79
Type of antenna	PCB antenna
Power level	fix
Connection to public utility power line	No
Nominal voltage	3.7 VDC
Rated transmitter power	Refer to Appendix 5
Occupied bandwidth	Not available
Channel bandwidth	1MHz
Emission designator	F1D, G1D
Frequency stability	Not available

Product function and intended use

The equipment under test (EUT) is a speaker with Bluetooth functionality. It is powered by 3.7VDC battery.
FCC ID: 2BGCL-SHOW0003 / IC ID: 32529-SHOW0003

Models	Product description
SHOW0010, SHOW0011, SHOW0012	Singing in the shower – Wireless Speaker

Submitted documents

Nil

Independent Operation Modes

The basic operation modes are:

- Transmitting mode.

For further information refer to User Manual

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Remark

The test results in this test report are only relevant to the tested sample and does not involve any assessment in the production.

Due to the manufacturer declaration of equivalence, construction of models SHOW0010, SHOW0011, SHOW0012 were identical except the housing.

Prüfbericht-Nr.: <i>Test report no.:</i>		CN25X68F 002		Seite 6 von 75 Page 6 of 75
Absatz <i>Clause</i>	Anforderungen - Prüfungen / <i>Requirements - Tests</i>	Messergebnisse – Bemerkungen/ <i>Measuring results - Remarks</i>	Ergebnis <i>Result</i>	

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level.
The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- Test mode samples with maximum RF output power and duty cycle and capable to transmit continuously at the lowest, middle and highest frequency channels is provided by the applicant for the testing.
-

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- 1. AC-DC adapter
Brand: in&out Super Si
Model: io-30DF
Input: 100-240V~50/60Hz 0.8A
Output: 5V $\Rightarrow$ 3A 15.0W

Countermeasures to achieve EMC Compliance

- None

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 7 von 75
Page 7 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

Test Methodology

Radiated Emission

The radiated emission measurements of the transmitter part were performed according to the procedures in ANSI C63.10-2013.

For measurement below 1GHz - the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For measurement above 1GHz - the EUT was placed at the middle of the 1.5 m height turntable and RF absorbing material was placed on ground plane between turntable and measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where

- FS = Field Strength in dBuV/m at 3 meters.
- R = Reading of Spectrum Analyzer in dBuV.
- AF = Antenna Factor in dB.
- CF = Cable Attenuation Factor in dB.
- FA = Filter Attenuation Factor in dB.
- PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Conducted Emission Calculation

Receiver reading R_r (dB μ V)
LISN insertion loss L_I (dB)
Cable loss C_I (dB)

$$\text{Result (dB}\mu\text{V)} = R_r + L_I + C_I$$

Sample: $R_r = 40.2$ dB μ V
 $L_I = 10.2$ dB
 $C_I = 0.3$ dB

$$\text{Result} = 40.2 + 10.2 + 0.3 = 50.7 \text{ dB}\mu\text{V}$$

Prüfbericht-Nr.:
Test report no.:


CN25X68F 002

Seite 8 von 75
Page 8 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------


Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test




Note: Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)



Prüfbericht-Nr.: Test report no.:		CN25X68F 002		Seite 9 von 75 Page 9 of 75
Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result	

Diagram of Equipment Configuration for Antenna-port Conducted Measurement (if applicable)



Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 10 von 75
Page 10 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

Test Facility

Test Laboratory Information

TÜV Rheinland Hong Kong Ltd.

Address: 3-4/F, Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong

Tel.: +852 2192 1000

Fax: +852 2192 1001

Email: service-gc@tuv.com

The test facility is recognized or accredited by the following organizations:

FCC

Designation Number : HK0013

ISED/IC

Company Number : 26152

Hong Kong Productivity Council

Address: LG1/F, HKPC Building 78 Tat Chee Avenue, Kowloon, Hong Kong

Tel.: +852 2788 6396

Fax: +852 2788 5405

Email: emc@hkpc.org

The test facility is recognized or accredited by the following organizations:

FCC

Designation Number : HK0012

ISED/IC

Company Number : 4780A

Prüfbericht-Nr.: <i>Test report no.:</i>		CN25X68F 002		Seite 11 von 75 Page 11 of 75
Absatz <i>Clause</i>	Anforderungen - Prüfungen / <i>Requirements - Tests</i>	Messergebnisse – Bemerkungen/ <i>Measuring results - Remarks</i>	Ergebnis <i>Result</i>	

List of Test and Measurement Instruments

Hong Kong Productivity Council

Radiated Emission

Equipment	Manufacturer	Type	Cal. Date	Due Date
Multi-functional Anechoic Chamber (NSA)	Albatross	---	2025-01-06	2026-01-06
Multi-functional Anechoic Chamber (VSWR)	Albatross	---	2025-01-04	2026-01-04
Test Receiver	Rohde & Schwarz	ESU40	2024-03-21	2025-03-21
Double-Ridged Waveguide Horn	EMCO	3117	2022-11-21	2025-05-21
Bi-conical Antenna	Rohde & Schwarz	HK116	2022-10-24	2025-04-24
Log Periodic Antenna	Rohde & Schwarz	HL223	2022-10-25	2025-04-25
Cable	SF118/11N/11N /12000MM	Huber+Suhner	2025-01-06	2026-01-06
Microwave amplifier	COM-POWER Corporation	PAM-118A	2025-03-04	2026-03-04
High Pass Filter	Trilithic	23042	2023-10-29	2025-10-29

TÜV Rheinland Hong Kong Ltd.

Conducted Emission on AC mains port

Equipment	Manufacturer	Type	Cal. Date	Due Date
EMI Test Receiver	R & S	ESR 3	2024-09-09	2025-09-10
LISN	R & S	ENV216	2024-10-21	2025-10-22
RF Coaxial Cable	R & S	N/A	2024-08-06	2025-08-07

Radio Test

Equipment	Manufacturer	Type	Cal. Date	Due Date
Spectrum Analyzer	R & S	FSV40	2024-08-07	2025-08-06

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 12 von 75
Page 12 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

Measurement Uncertainty

The estimated combined standard uncertainty for powerline conducted emissions measurements is $\pm 3.22\text{dB}$.

The estimated combined standard uncertainty for radiated emissions measurements is $\pm 2.44\text{dB}$ (9kHz to 30MHz) and $\pm 5.92\text{dB}$ (30MHz to 1000MHz) and is $\pm 4.92\text{dB}$ (1GHz to 18GHz).

The estimated combined standard uncertainty for antenna conducted emission is $\pm 1.94\text{dB}$

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of $k=2$, which for the level of confidence is approximately 95%.

Absatz <i>Clause</i>	Anforderungen - Prüfungen / <i>Requirements - Tests</i>	Messergebnisse – Bemerkungen/ <i>Measuring results - Remarks</i>	Ergebnis <i>Result</i>
--------------------------------	---	--	----------------------------------

Results FCC Part 15 - Subpart C / RSS-247 Issue 3

FCC 15.203 – Antenna Requirement 1		Pass
FCC Requirements:	No antenna other than that furnished by the responsible party shall be used with the device	
Results:	a) Antenna type	PCB antenna
	b) Manufacturer and model no.:	N/A
	c) Peak Gain:	1.3 dBi
Verdict:	Pass	

FCC 15.204 – Antenna Requirement 2		Pass
FCC Requirements:	An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.	
Results:	Only one PCB antenna can be used.	
Verdict:	Pass	

RSS-Gen 6.3 – External Control		Pass
IC Requirements:	The device shall not have any external controls accessible to the user that enable it to be adjusted, selected or programmed to operate in violation of the limits prescribed in the applicable RSS.	
Results:	The device does not have any transmitter external controls accessible to the user that can be adjusted and operated in violation of the limits of this standard.	
Verdict:	Pass	

RSS-Gen 8.3 – Antenna Requirement		Pass
IC Requirements:	When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer.	
Results:	a) Antenna type	Fixed Integral wire antenna
	b) Manufacturer:	N/A
	c) Model no.:	N/A
	d) Peak Gain:	1.3 dBi
Verdict:	Pass	

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 14 von 75
Page 14 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

FCC 15.207/ RSS-Gen 8.8 – Conducted Emission on AC Mains

Pass

Test Specification : ANSI C63.10 – 2013
Test date : 2025-03-06
Mode of operation : BT mode
Port of testing : Temporary antenna port
Supply voltage : 120VAC/60Hz
Temperature : 20°C
Humidity : 55%

Requirement: Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Results: For test protocols please refer to Appendix 1.

Mode: Charging+BT linked+Song playing

Live

Frequency range (MHz)	Frequency (MHz)	Result (dBµV)	Limit (dBµV)	Margin (dB)	Remark	Verdict
0.15 - 30	No Peak Found	---	---	---	QP	Pass
	No Peak Found	---	---	---	Average	Pass

Neutral

Frequency range (MHz)	Frequency (MHz)	Result (dBµV)	Limit (dBµV)	Margin (dB)	Remark	Verdict
0.15 - 30	No Peak Found	---	---	---	QP	Pass
	No Peak Found	---	---	---	Average	Pass

Remark: If all emissions are below 20dBµV, the result column will mention no peak found.

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 15 von 75
Page 15 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

FCC 15.215(c) / RSS-247 5.1(a) – 20dB Bandwidth

Pass

Test Specification : ANSI C63.10 – 2013
Test date : 2025-03-10
Mode of operation : Tx mode
Port of testing : Temporary antenna port
Supply voltage : 3.7 VDC
Temperature : 20°C
Humidity : 55%

Requirement: The intentional radiators must be designed to ensure that the 20dB bandwidth of the emission, is contained within the frequency band designated in the rule section under which the equipment is operated.

Results: Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.
For test protocols refer to Appendix 1.

BDR

Frequency (MHz)	20 dB left (MHz)	Limit (MHz)	20 dB right (MHz)	Limit (MHz)	20dB bandwidth (kHz)
2402	2401.484	> 2400	2402.430	< 2483.5	945.50
2441	2440.515	> 2400	2441.428	< 2483.5	913.50
2480	2479.983	> 2400	2480.426	< 2483.5	845.40

EDR

Frequency (MHz)	20 dB left (MHz)	Limit (MHz)	20 dB right (MHz)	Limit (MHz)	20dB bandwidth (kHz)
2402	2401.301	> 2400	2402.621	< 2483.5	1320.30
2441	2440.305	> 2400	2441.622	< 2483.5	1316.80
2480	2479.329	> 2400	2480.611	< 2483.5	1281.90

FCC 15.247 (a)(1) / RSS-247 5.1(b) – Carrier Frequency Separation

Pass

Test Specification : ANSI C63.10 – 2013
Test date : 2025-03-10
Mode of operation : Tx mode
Port of testing : Temporary antenna port
Supply voltage : 3.7 VDC
Temperature : 20°C
Humidity : 55%

Requirement: Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.

Results: The centre frequencies of the hopping channels are separated by more than the 2/3*20dB bandwidth. For test protocols please refer to Appendix 1.

Note: The limit is maximum 2/3 of the 20dB bandwidth: 880.2 kHz

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 16 von 75
Page 16 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

FCC 15.247 (a)(1)(iii) / RSS-247 5.1(d) – Number of Hopping Frequency

Pass

Test Specification : ANSI C63.10 – 2013
Test date : 2025-03-10
Mode of operation : Tx mode
Port of testing : Temporary antenna port
Supply voltage : 3.7 VDC
Temperature : 20°C
Humidity : 55%

Requirement: Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

Results: Measured quantity of hopping channel is greater than 15 channels. For test protocols please refer to Appendix 1.

FCC 15.247 (a)(1)(iii) / RSS-247 5.1(d) – Time of Occupancy

Pass

Test Specification : ANSI C63.10 – 2013
Test date : 2025-03-10
Mode of operation : Tx mode
Port of testing : Temporary antenna port
Supply voltage : 3.7 VDC
Temperature : 20°C
Humidity : 55%

Requirement: The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Results: Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.
For test protocols please refer to Appendix 1.

BDR

Frequency (MHz)	Data packet	Pulse width (ms)	Measured dwell time (s)	Limit (s)	Verdict
Frequency Hopping	DH1	0.393	0.136	< 0.4	Pass
	DH3	1.654	0.255	< 0.4	Pass
	DH5	2.905	0.368	< 0.4	Pass

EDR

Frequency (MHz)	Data packet	Pulse width (ms)	Measured dwell time (s)	Limit (s)	Verdict
Frequency Hopping	2-DH1	0.404	0.146	< 0.4	Pass
	2-DH3	1.659	0.254	< 0.4	Pass
	2-DH5	2.910	0.317	< 0.4	Pass

Note:

Dwell Time = Pulse width x (Hopping rate / Number of channels) x Period

Period = 0.4 x 79 (channel) = 31.6 seconds

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 17 von 75
Page 17 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

RSS-Gen 6.7 – Occupied Bandwidth

N/A

Test Specification : RSS-Gen
Test date : 2025-03-10
Mode of operation : Tx mode
Port of testing : Antenna port
Supply voltage : 3.7 VDC
Temperature : 20°C
Humidity : 55%

Requirement : N/A

Results: Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.
For test protocols refer to Appendix 1.

BDR

Frequency (MHz)	Left (MHz)	Right (MHz)	99% bandwidth (kHz)
2402	2401.531	2402.454	923.33
2441	2440.541	2441.455	913.52
2480	2479.542	2480.443	901.30

EDR

Frequency (MHz)	Left (MHz)	Right (MHz)	99% bandwidth (kHz)
2402	2401.332	2402.659	1326.60
2441	2440.348	2441.637	1289.15
2480	2479.383	2480.585	1201.33

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 18 von 75
Page 18 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

FCC 15.247(b)(1) / RSS-247 5.4(b) – Maximum Peak Conducted Output Power

Pass

Test Specification : ANSI C63.10 – 2013
Test date : 2025-03-10
Mode of operation : Tx mode
Port of testing : Temporary antenna port
Supply voltage : 3.7 VDC
Temperature : 20°C
Humidity : 55%

Requirement: All frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

Results: For test protocols please refer to Appendix 1.

BDR

Frequency (MHz)	Measured output power (dBm)	Limit (W)	Limit (dBm)	Verdict
2402	-3.01	0.125	20.97	Pass
2441	-4.01	0.125	20.97	Pass
2480	-5.96	0.125	20.97	Pass

EDR

Frequency (MHz)	Measured output power (dBm)	Limit (W)	Limit (dBm)	Verdict
2402	-2.80	0.125	20.97	Pass
2441	-3.76	0.125	20.97	Pass
2480	-5.46	0.125	20.97	Pass

FCC 15.247(d) / RSS-247 5.5 – Spurious Conducted Emissions

Pass

Test Specification : ANSI C63.10 – 2013
Test date : 2025-03-10
Mode of operation : Tx mode
Port of testing : Temporary antenna port
Supply voltage : 3.7 VDC
Temperature : 20°C
Humidity : 55%

Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

Results: Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate.
Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method is compliance with the requirement. For test protocols refer to Appendix 1.

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 19 von 75
Page 19 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

FCC 15.205/ RSS-Gen 8.10 – Radiated Emissions in Restricted Frequency Bands

Pass

Test Specification : ANSI C63.10 – 2013
Test date : 2025-03-13
Mode of operation : Tx mode
Port of testing : Enclosure
Frequency range : 9kHz - 25GHz
Supply voltage : 3.7 VDC
Temperature : 21°C
Humidity : 59%

Requirement: In any 100kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission general limits.

Results: Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate.
All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.

Mode: 2402MHz TX

Vertical Polarization

Frequency MHz	Level dBuV/m	Limit / Detector dBuV/m
2390.000	45.2	74.0 / PK
2390.000	22.5	54.0 / AV
2400.000	57.1	74.0 / PK
2400.000	33.4	54.0 / AV
4803.641	60.2	74.0 / PK
4803.641	45.7	54.0 / AV
7205.463	62.8	74.0 / PK
7205.463	45.2	54.0 / AV

Mode: 2402MHz TX

Horizontal Polarization

Frequency MHz	Level dBuV/m	Limit / Detector dBuV/m
2390.000	45.6	74.0 / PK
2390.000	22.6	54.0 / AV
2400.000	63.3	74.0 / PK
2400.000	39.1	54.0 / AV
4803.641	58.4	74.0 / PK
4803.641	43.9	54.0 / AV
7205.464	68.9	74.0 / PK
7205.464	51.4	54.0 / AV

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 20 von 75
Page 20 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

Mode: 2441MHz TX			Vertical Polarization		
Frequency MHz	Level dBuV/m	Limit / Detector dBuV/m	Frequency MHz	Level dBuV/m	Limit / Detector dBuV/m
4881.639	60.3	74.0 / PK	4881.639	45.9	54.0 / AV
7322.456	61.7	74.0 / PK	7322.456	44.3	54.0 / AV
Mode: 2441MHz TX			Horizontal Polarization		
Frequency MHz	Level dBuV/m	Limit / Detector dBuV/m	Frequency MHz	Level dBuV/m	Limit / Detector dBuV/m
4882.225	57.3	74.0 / PK	4882.225	44.0	54.0 / AV
7322.464	65.7	74.0 / PK	7322.464	48.2	54.0 / AV
Mode: 2480MHz TX			Vertical Polarization		
Frequency MHz	Level dBuV/m	Limit / Detector dBuV/m	Frequency MHz	Level dBuV/m	Limit / Detector dBuV/m
2483.500	38.7	74.0 / PK	2483.500	21.0	54.0 / AV
4959.641	58.9	74.0 / PK	4959.641	44.1	54.0 / AV
7439.463	55.7	74.0 / PK	7439.463	38.6	54.0 / AV
Mode: 2480MHz TX			Horizontal Polarization		
Frequency MHz	Level dBuV/m	Limit / Detector dBuV/m	Frequency MHz	Level dBuV/m	Limit / Detector dBuV/m
2483.500	43.7	74.0 / PK	2483.500	22.0	54.0 / AV
4959.641	55.9	74.0 / PK	4959.641	41.1	54.0 / AV
7439.463	58.8	74.0 / PK	7439.463	41.2	54.0 / AV

Prüfbericht-Nr.: <i>Test report no.:</i>		CN25X68F 002		Seite 21 von 75 Page 21 of 75
Absatz <i>Clause</i>	Anforderungen - Prüfungen / <i>Requirements - Tests</i>	Messergebnisse – Bemerkungen/ <i>Measuring results - Remarks</i>	Ergebnis <i>Result</i>	

Appendix 1

Test Results

Prüfbericht-Nr.:
Test report no.:


CN25X68F 002

Seite 22 von 75
Page 22 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------


Conducted Emission on AC Mains

Conducted Emission (150 kHz - 30 MHz) - Cont TDS (QP+AV)



Live

Conducted Emission (150 kHz - 30 MHz) - Cont TDS (QP+AV)



Neutral


Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 23 von 75
Page 23 of 75


Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

20dB Bandwidth



Date: 10. MAR 2025 16:48:36

BDR, Tx frequency: 2402MHz



Date: 10. MAR 2025 17:04:59


BDR, Tx frequency: 2441MHz

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 24 von 75
Page 24 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 10. MAR 2025 17:11:21

BDR, Tx frequency: 2480MHz



Date: 10. MAR 2025 16:58:37


EDR, Tx frequency: 2402MHz

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 25 von 75
Page 25 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 10. MAR 2025 17:08:44

EDR, Tx frequency: 2441MHz



Date: 10. MAR 2025 17:15:39

EDR, Tx frequency: 2480MHz


Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 26 von 75
Page 26 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

Carrier Frequency Separation



BDR, Tx frequency: 2402MHz




BDR, Tx frequency: 2441MHz

Prüfbericht-Nr.:
Test report no.:


CN25X68F 002

Seite 27 von 75
Page 27 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



BDR, Tx frequency: 2480MHz




EDR, Tx frequency: 2402MHz

Prüfbericht-Nr.:
Test report no.:


CN25X68F 002

Seite 28 von 75
Page 28 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



EDR, Tx frequency: 2441MHz



EDR, Tx frequency: 2480MHz


Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 29 von 75
Page 29 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

Number of Hopping Frequency



BDR, Tx frequency: Frequency hopping



EDR, Tx frequency: Frequency hopping


Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 30 von 75
Page 30 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

Time of Occupancy



BDR, DH1, Pulse width




BDR, DH1, Tx frequency: Frequency hopping

Prüfbericht-Nr.:
Test report no.:


CN25X68F 002

Seite 31 von 75
Page 31 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



BDR, DH3, Pulse width




BDR, DH3, Tx frequency: Frequency hopping

Prüfbericht-Nr.:
Test report no.:


CN25X68F 002

Seite 32 von 75
Page 32 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



BDR, DH5, Pulse width




BDR, DH5, Tx frequency: Frequency hopping

Prüfbericht-Nr.:
Test report no.:


CN25X68F 002

Seite 33 von 75
Page 33 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



EDR, 2-DH1, Pulse width




EDR, 2-DH1, Tx frequency: Frequency hopping

Prüfbericht-Nr.:
Test report no.:


CN25X68F 002

Seite 34 von 75
Page 34 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



EDR, 2-DH3, Pulse width




EDR, 2-DH3, Tx frequency: Frequency hopping

Prüfbericht-Nr.:
Test report no.:


CN25X68F 002

Seite 35 von 75
Page 35 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



EDR, 2-DH5, Pulse width



EDR, 2-DH5, Tx frequency: Frequency hopping


Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 36 von 75
Page 36 of 75


Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

Occupied Bandwidth



Date: 10. MAR 2025 16:48:26

BDR, Tx frequency: 2402MHz



Date: 10. MAR 2025 17:04:48


BDR, Tx frequency: 2441MHz

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 37 von 75
Page 37 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 10. MAR 2025 17:11:10

BDR, Tx frequency: 2480MHz



Date: 10. MAR 2025 16:58:26


EDR, Tx frequency: 2402MHz

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 38 von 75
Page 38 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 10. MAR 2025 17:08:33

EDR, Tx frequency: 2441MHz



Date: 10. MAR 2025 17:15:28

EDR, Tx frequency: 2480MHz


Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 39 von 75
Page 39 of 75


Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

Maximum Peak Conducted Output Power



Date: 10. MAR 2025 16:48:12

BDR, Tx frequency: 2402MHz



Date: 10. MAR 2025 17:04:35


BDR, Tx frequency: 2441MHz

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 40 von 75
Page 40 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 10. MAR 2025 17:10:58

BDR, Tx frequency: 2480MHz



Date: 10. MAR 2025 16:58:12


EDR, Tx frequency: 2402MHz

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 41 von 75
Page 41 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 10. MAR 2025 17:08:19

EDR, Tx frequency: 2441MHz



Date: 10. MAR 2025 17:15:14

EDR, Tx frequency: 2480MHz


Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 42 von 75
Page 42 of 75


Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

Spurious Conducted Emissions



Date: 10. MAR 2025 16:49:34

BDR, Low Channel, Band Edge



Date: 10. MAR 2025 16:49:11


BDR, Low Channel, Band Edge, Frequency hopping

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 43 von 75
Page 43 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 10. MAR 2025 17:12:36

BDR, High Channel, Band Edge



Date: 10. MAR 2025 17:11:56


BDR, High Channel, Band Edge, Frequency hopping

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 44 von 75
Page 44 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 10. MAR 2025 16:57:34

EDR, Low Channel, Band Edge



Date: 10. MAR 2025 16:57:12


EDR, Low Channel, Band Edge, Frequency hopping

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 45 von 75
Page 45 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 10. MAR 2025 17:16:30

EDR, High Channel, Band Edge



Date: 10. MAR 2025 17:16:10

EDR, High Channel, Band Edge, Frequency hopping


Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 46 von 75
Page 46 of 75


Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

Prescan



Date: 10. MAR 2025 16:51:08

BDR, Tx frequency: 2402MHz



Date: 10. MAR 2025 17:08:19


BDR, Tx frequency: 2441MHz

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 47 von 75
Page 47 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 10. MAR 2025 17:14:10

BDR, Tx frequency: 2480MHz



Date: 10. MAR 2025 16:59:09


EDR, Tx frequency: 2402MHz

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 48 von 75
Page 48 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 10. MAR 2025 17:10:04

EDR, Tx frequency: 2440MHz



Date: 10. MAR 2025 17:18:04

EDR, Tx frequency: 2480MHz


Prüfbericht-Nr.:
Test report no.:

CN25X68F 002

Seite 49 von 75
Page 49 of 75


Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------

Worse Case



Date: 25.MAR.2025 13:34:57

EDR, Tx frequency: 2402MHz, 30MHz – 3GHz



Date: 25.MAR.2025 13:36:30


EDR, Tx frequency: 2402MHz, 3GHz – 6GHz

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 50 von 75
Page 50 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 25.MAR.2025 13:37:10

EDR, Tx frequency: 2402MHz, 6GHz – 9GHz



Date: 25.MAR.2025 13:41:09


EDR, Tx frequency: 2402MHz, 9GHz – 12GHz

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 51 von 75
Page 51 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 25.MAR.2025 13:41:55

EDR, Tx frequency: 2402MHz, 12GHz – 15GHz



Date: 25.MAR.2025 13:42:38


EDR, Tx frequency: 2402MHz, 15GHz – 18GHz

Prüfbericht-Nr.:
Test report no.:

CN25X68F 002


Seite 52 von 75
Page 52 of 75

Absatz Clause	Anforderungen - Prüfungen / Requirements - Tests	Messergebnisse – Bemerkungen/ Measuring results - Remarks	Ergebnis Result
------------------	---	--	--------------------



Date: 25.MAR.2025 13:43:16


EDR, Tx frequency: 2402MHz, 18GHz – 21GHz



Date: 25.MAR.2025 13:43:52

EDR, Tx frequency: 2402MHz, 21GHz – 24GHz

Prüfbericht-Nr.: <i>Test report no.:</i>	CN25X68F 002	Seite 53 von 75 Page 53 of 75	
Absatz <i>Clause</i>	Anforderungen - Prüfungen / <i>Requirements - Tests</i>	Messergebnisse – Bemerkungen/ <i>Measuring results - Remarks</i>	Ergebnis <i>Result</i>



Date: 25.MAR.2025 13:44:22

EDR, Tx frequency: 2402MHz, 24GHz – 26GHz