FCC TEST REPORT
FCC ID:2BGD3-EX01

Report Number.....:	**ZKT-241115L15521E**
Date of Test.....:	Oct. 17, 2024 to Oct. 29, 2024
Date of issue.....:	Oct. 29, 2024
Test Result .....:	PASS
Testing Laboratory.....:	**Shenzhen ZKT Technology Co., Ltd.**
Address .....:	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Applicant's name .....:	**Shuopu Electronics(Dongguan) Co., Ltd.**
Address .....:	4F, A Bldg, Hesheng Science Park, Nanshe Rd,Dongfeng Comm,Humen Tn,Duangguan, GD, CN (523932)
Manufacturer's name .....:	**Shuopu Electronics(Dongguan) Co., Ltd.**
Address .....:	4F, A Bldg, Hesheng Science Park, Nanshe Rd,Dongfeng Comm,Humen Tn,Duangguan, GD, CN (523932)
Test specification:	
Standard.....:	FCC CFR Title 47 Part 15 Subpart C
Test procedure.....:	/
Non-standard test method .....:	N/A

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name.....:	**SMARTCOBY Ex01 SLIM Qi2 & Cable**
Trademark .....:	CIO
Model/Type reference.....:	CIO-MB20W2C-5K-EX01
Model Difference.....:	/
Ratings.....:	Input 1: (USB-C): 5 V⎓3 A, 9 V⎓2.22 A, 12 V⎓1.67 A (Max 20W) Input 2:(USB-C Cable): 5 V⎓3 A, 9 V⎓2.22 A, 12 V⎓1.67 A (Max 20W) Output 1:(USB-C): 5 V⎓3 A, 9 V⎓2.22 A, 12 V⎓1.67 A (Max 20W) PPS 5-11 V⎓2 A (Max 22W) Output 2:(USB-C Cable): 5 V⎓3 A, 9 V⎓2.22 A, 12 V⎓1.67 A (Max 20W) PPS 5-11 V⎓2 A (Max 22W) Output 3:Qi2Wireless: Max 15W USB-C+USB-C Cable+Qi2 Wireless: 5 V⎓3 A, 15W Max

Testing procedure and testing location:

Testing Laboratory.....:	**Shenzhen ZKT Technology Co., Ltd.**
Address.....:	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Tested by (name + signature).....:	Alen He
Reviewer (name + signature).....:	Joe Liu
Approved (name + signature).....:	Lake Xie

TABLE OF CONTENTS

1. VERSION **4**
2. TEST SUMMARY **5**
2.1 TEST FACILITY 6
2.2 MEASUREMENT UNCERTAINTY 6
3. GENERAL INFORMATION **7**
3.1 GENERAL DESCRIPTION OF EUT 7
3.2 Test mode 7
3.3 Block Diagram of EUT Configuration 8
3.4 Test Conditions 8
3.5 Description Of Support Units (Conducted Mode) 9
3.6 EQUIPMENTS LIST FOR ALL TEST ITEMS 10
4. CONDUCTED EMISSION TEST **12**
4.1 CONDUCTED EMISSION MEASUREMENT 12
4.1.1 POWER LINE CONDUCTED EMISSION Limits 12
4.1.2 TEST PROCEDURE 12
4.1.3 DEVIATION FROM TEST STANDARD 12
4.1.4 TEST SETUP 13
4.1.5 EUT OPERATING CONDITIONS 13
4.1.6 Test Result 14
5. RADIATED EMISSION MEASUREMENT **16**
5.1 Radiated Emission Limits 16
5.2 Anechoic Chamber Test Setup Diagram 17
5.3 Test Procedure 17
5.4 DEVIATION FROM TEST STANDARD 17
5.5 Test Result 18
6. BANDWIDTH TEST **21**
ANTENNA REQUIREMENT **23**
7. TEST SETUP PHOTO **24**
8. EUT CONSTRUCTIONAL DETAILS **24**

1. VERSION

Report No.	Version	Description	Approved
ZKT-241115L15521E	Rev.01	Initial issue of report	Oct. 29, 2024

2. TEST SUMMARY

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Spurious Emission	15.209(a)(f)	Pass
20dB Bandwidth	15.215	Pass

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U，where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2，providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF conducted power	±0.16dB
3	Conducted spurious emissions	±0.21dB
4	All radiated emissions (9k-30MHz)	±4.68dB
5	All radiated emissions (<1G)	±4.68dB
6	All radiated emissions (>1G)	±4.89dB
7	Temperature	±0.5°C
8	Humidity	±2%
9	Occupied Bandwidth	±4.96%

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	SMARTCOBY Ex01 SLIM Qi2 & Cable
Test Model No.:	CIO-MB20W2C-5K-EX01
Hardware version:	V1.0
Software version:	V1.0
Operation Frequency:	110.2-205KHz
Modulation type:	MSK
Antenna Type:	Coil Antenna
Antenna gain:	0dBi
Remark:The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Shenzhen ZKT Technology Co., Ltd.. does not assume any responsibility.	

3.2 Test mode

Test Modes:	
Mode 1	Charging mode
Mode 2	Wireless charging(15W)
Mode 3	Wireless charging(10W)
Mode 4	Wireless charging(5W)
Mode 5	Charging+Wireless charging(15W)
Note: 1.All full load, half load, and no-load modes were tested, only the worst-case was recorded in the report. Mode 5 full load is the worst mode. 2.EUT support charging and discharging at the same time, Charging and discharging at the same time can only reach 15W.	

3.3 Block Diagram of EUT Configuration

Mode 1 :



Mode 2 & 3& 4:



Mode 5 :



3.4 Test Conditions

Temperature: 25.6℃

Relative Humidity: 54.3 %

3.5 Description Of Support Units (Conducted Mode)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	AC Adapter	N/A	HW-059200CHQ	N/A	AE
E-2	Wireless charging load	/	EESON	N/A	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.
(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

3.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation emissions& Radio Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	A.17.05	Nov. 02, 2023	Nov. 01, 2024
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Nov. 02, 2023	Nov. 01, 2024
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	100969	4.32	Nov. 02, 2023	Nov. 01, 2024
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	N/A	Nov. 13, 2023	Nov. 12, 2024
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	N/A	Nov. 13, 2023	Nov. 12, 2024
6	Horn Antenna (15GHz-40GHz)	A.H.System	SAS-574	588	N/A	Nov. 13, 2023	Nov. 12, 2024
7	Loop Antenna	TESEQ	HLA6121	58357	N/A	Nov. 16, 2023	Nov. 15, 2024
8	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	60747	N/A	Nov. 02, 2023	Nov. 01, 2024
9	Amplifier (1GHz-26.5GHz)	HuiPu	8449B	3008A00315	N/A	Nov. 02, 2023	Nov. 01, 2024
10	Amplifier (500MHz-40GHz)	QuanJuDa	DLE-161	097	N/A	Nov. 02, 2023	Nov. 01, 2024
11	Test Cable	N/A	R-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
12	Test Cable	N/A	R-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
13	Test Cable	N/A	R-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
14	Test Cable	N/A	RF-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
15	Test Cable	N/A	RF-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
16	Test Cable	N/A	RF-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
17	ESG Signal Generator	Agilent	E4421B	N/A	B.03.84	Nov. 02, 2023	Nov. 01, 2024
18	Signal Generator	Agilent	N5182A	N/A	A.01.87	Nov. 02, 2023	Nov. 01, 2024
19	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	N/A	Nov. 16, 2023	Nov. 15, 2024
20	Wideband Radio Communication Test	R&S	CMW500	106504	V 3.7.22	Nov. 02, 2023	Nov. 01, 2024
21	MWRF Power Meter Test system	MW	MW100-RF CB	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
22	D.C. Power Supply	LongWei	TPR-6405D	N/A	N/A	\	\
23	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	N/A	\	\
24	RF Software	MW	MTS8310	V2.0.0.0	N/A	\	\
25	Turntable	MF	MF-7802BS	N/A	N/A	\	\
26	Antenna tower	MF	MF-7802BS	N/A	N/A	\	\

Conducted emissions Test

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	N/A	Nov. 14, 2023	Nov. 13, 2024
2	LISN	CYBERTEK	EM5040A	E1850400149	N/A	Nov. 02, 2023	Nov. 01, 2024
3	Test Cable	N/A	C-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
4	Test Cable	N/A	C-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
5	Test Cable	N/A	C-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
6	EMI Test Receiver	R&S	ESCI3	101393	4.42 SP3	Nov. 02, 2023	Nov. 01, 2024
7	Triple-Loop Antenna	N/A	RF300	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
8	Absorbing Clamp	DZ	ZN23201	15034	N/A	Nov. 07, 2023	Nov. 06, 2024
9	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	N/A	\	\

Testing software

Project	**Software name**	**Edition**
RF Conducted	MTS 8310	2.0.0.0
Radiated Emission	EZ-EMC	FA-03A2 RE+

4. CONDUCTED EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	QP	AVG	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 Test Result

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.5234	21.35	10.02	31.37	56.00	-24.63	QP	P	
2	0.5234	11.66	10.02	21.68	46.00	-24.32	AVG	P	
3	0.5820	21.39	10.03	31.42	56.00	-24.58	QP	P	
4	0.5820	11.31	10.03	21.34	46.00	-24.66	AVG	P	
5 *	0.8655	23.39	10.05	33.44	56.00	-22.56	QP	P	
6	0.8655	9.96	10.05	20.01	46.00	-25.99	AVG	P	
7	0.9104	22.22	10.05	32.27	56.00	-23.73	QP	P	
8	0.9104	10.30	10.05	20.35	46.00	-25.65	AVG	P	
9	1.0410	22.04	10.06	32.10	56.00	-23.90	QP	P	
10	1.0410	9.11	10.06	19.17	46.00	-26.83	AVG	P	
11	1.1984	22.15	10.06	32.21	56.00	-23.79	QP	P	
12	1.1984	9.75	10.06	19.81	46.00	-26.19	AVG	P	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.8565	21.80	10.05	31.85	56.00	-24.15	QP	P	
2	0.8565	9.33	10.05	19.38	46.00	-26.62	AVG	P	
3	0.8925	21.17	10.05	31.22	56.00	-24.78	QP	P	
4	0.8925	9.77	10.05	19.82	46.00	-26.18	AVG	P	
5	1.0140	20.97	10.06	31.03	56.00	-24.97	QP	P	
6	1.0140	9.26	10.06	19.32	46.00	-26.68	AVG	P	
7	1.0680	21.26	10.06	31.32	56.00	-24.68	QP	P	
8	1.0680	9.88	10.06	19.94	46.00	-26.06	AVG	P	
9 *	1.1490	21.82	10.06	31.88	56.00	-24.12	QP	P	
10	1.1490	8.83	10.06	18.89	46.00	-27.11	AVG	P	
11	1.2480	21.34	10.06	31.40	56.00	-24.60	QP	P	
12	1.2480	9.32	10.06	19.38	46.00	-26.62	AVG	P	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

5. RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 1GHz
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Peak Value
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

5.1 Radiated Emission Limits

Limits for frequency below 30MHz

Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.490	2400/F(kHz)	300	Peak Value
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value

Limits for frequency Above 30MHz

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.00	Quasi-peak Value
88MHz-216MHz	43.50	Quasi-peak Value
216MHz-960MHz	46.00	Quasi-peak Value
960MHz-1GHz	54.00	Quasi-peak Value
Above 1GHz	54.00	Average Value
	74.00	Peak Value

5.2 Anechoic Chamber Test Setup Diagram

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.

5.3 Test Procedure

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna (calibrated by dipole antenna) are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on measurement.

5.4 DEVIATION FROM TEST STANDARD

No deviation

5.5 Test Result

Measurement data:

Note: Limit dBuV/m @3m = Limit dBuV/m @300m+ 80
Limit dBuV/m @3m = Limit dBuV/m @30m + 40

9 kHz~30 MHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	coaxial
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.127	72.02	0.16	72.18	105.53	-33.35	Peak
2	0.265	51.14	0.66	51.80	99.14	-47.34	Peak
3	0.411	47.11	0.93	48.04	95.33	-47.29	Peak
4 *	0.736	45.13	1.58	46.71	70.27	-23.56	QP
5	2.427	39.79	5.04	44.83	69.54	-24.71	QP
6	6.372	28.33	13.06	41.39	69.54	-28.15	QP

Note:
Pre-scan in the all of mode, the worst case in of was recorded.
Factor = antenna factor + cable loss – pre-amplifier.
Emission Level = Meter Reading - Factor
Margin = Emission Level- Limit.
The amplitude of emissions which are attenuated by more than 20db below the permissible value has no need to be reported.

30MHz-1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	78.500	31.12	-17.57	13.55	40.00	-26.45	QP
2	185.200	34.71	-18.37	16.34	43.50	-27.16	QP
3	193.930	35.31	-18.30	17.01	43.50	-26.49	QP
4	204.600	33.79	-18.10	15.69	43.50	-27.81	QP
5	258.920	30.86	-16.30	14.56	46.00	-31.44	QP
6	309.360	32.51	-14.71	17.80	46.00	-28.20	QP

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	52.310	32.89	-15.73	17.16	40.00	-22.84	QP
2	59.100	32.97	-16.23	16.74	40.00	-23.26	QP
3 *	76.560	38.30	-17.43	20.87	40.00	-19.13	QP
4	145.430	36.45	-18.69	17.76	43.50	-25.74	QP
5	176.470	36.90	-18.44	18.46	43.50	-25.04	QP
6	187.140	38.86	-18.36	20.50	43.50	-23.00	QP

Remarks:
1. Factor = Antenna Factor + Cable Loss – Preamplifier Factor
2. Level = Reading + Factor
3. Margin = Emission Level- Limit.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

6. BANDWIDTH TEST

1. Set RBW = 10 Hz for 1%-5%OBW.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP

Temperature:	25.7 ℃	Relative Humidity:	55%
Pressure:	101kPa		

Frequency (KHz)	20dB bandwidth (KHz)	Result
127.2	0.032	Pass

Wireless phone Antenna



ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is Coil Antenna, the best case gain of the antennas is 0dBi, reference to the appendix II for details	

7. TEST SETUP PHOTO

Reference to the appendix I for details.

8. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

※※※※※ END OF REPORT ※※※※※