TCT 通测检测
TESTING CENTRE TECHNOLOGY

TEST REPORT

FCC ID. ..... :	2BGDM-ECX1	
Test Report No..... :	TCT240509E049	
Date of issue..... :	May 24, 2024	
Testing laboratory ..... :	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name..... :	AEAI PTE.LTD.	
Address..... :	3 PHILLIP STREET, #09-02 ROYAL GROUP BUILDING SING, Singapore	
Manufacturer's name ... :	AEAI PTE.LTD.	
Address..... :	3 PHILLIP STREET, #09-02 ROYAL GROUP BUILDING SING, Singapore	
Standard(s) ..... :	FCC CFR Title 47 Part 15 Subpart E Section 15.407 KDB 662911 D01 Multiple Transmitter Output v02r01 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Product Name..... :	Aethir Edge Computing Server	
Trade Mark ..... :	N/A	
Model/Type reference..... :	ECX1, ECX2, ECX3, DN003, S-DN003	
Rating(s)..... :	Refer to EUT description of page 3	
Date of receipt of test item ..... :	May 09, 2024	
Date (s) of performance of test..... :	May 09, 2024 ~ May 24, 2024	
Tested by (+signature) ... :	Ronaldo LUO	Ronaldo Luo
Check by (+signature).... :	Beryl ZHAO	Beryl Zhao
Approved by (+signature):	Tomsin	Tomsin

SHENZHEN TONGCE TESTING LAB TCT

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. General Product Information 3
1.1. EUT description 3
1.2. Model(s) list 3
1.3. Test Frequency 4
2. Test Result Summary 5
3. General Information 6
3.1. Test environment and mode 6
3.2. Description of Support Units 7
4. Facilities and Accreditations 8
4.1. Facilities 8
4.2. Location 8
4.3. Measurement Uncertainty 8
5. Test Results and Measurement Data 9
5.1. Antenna requirement 9
5.2. Conducted Emission 10
5.3. Maximum Conducted Output Power 14
5.4. 6dB Emission Bandwidth 18
5.5. 26dB Bandwidth and 99% Occupied Bandwidth 19
5.6. Power Spectral Density 20
5.7. Band edge 23
5.8. Unwanted Emissions 36
5.9. Frequency Stability Measurement 52
Appendix A: Test Result of Conducted Test
Appendix B: Photographs of Test Setup
Appendix C: Photographs of EUT

1. General Product Information

1.1. EUT description

Product Name.....:	Aethir Edge Computing Server
Model/Type reference.....:	ECX1
Sample Number.....:	TCT240509E010-0101
Operation Frequency.....:	Band 1: 5180 MHz~5240 MHz Band 3: 5745 MHz~5825 MHz
Channel Bandwidth.....:	802.11a: 20MHz 802.11n: 20MHz, 40MHz 802.11ac: 20MHz, 40MHz, 80MHz 802.11ax: 20MHz, 40MHz, 80MHz
Modulation Technology .....:	Orthogonal Frequency Division Multiplexing(OFDM)
Modulation Type.....:	256QAM, 64QAM, 16QAM, BPSK, QPSK
Antenna Type.....:	Internal Antenna
Antenna Gain.....:	Band 1: Antenna 1: 2.58dBi, Antenna 2: 3.91dBi Band 3: Antenna 1: 4.64dBi, Antenna 2: 4.05dBi
Rating(s).....:	Adapter Information: Model: CS-1204000 Input: AC 100-240V, 50/60Hz, 2A Max. Output: DC 12.0V, 4.0A, 48.0W

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

No.	Model No.	Tested with
1	ECX1	☒
Other models	ECX2, ECX3, DN003, S-DN003	☐

Note: ECX1 is tested model, other models are derivative models. The models are identical in circuit and PCB layout, only different on the model names and appearance. So the test data of ECX1 can represent the remaining models.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

1.3. Test Frequency

Band 1

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180	38	5190	42	5210
40	5200	46	5230		
48	5240				

Band 3

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745	151	5755	155	5775
157	5785	159	5795		
165	5825				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Maximum Conducted Output Power	§15.407(a)	PASS
6dB Emission Bandwidth	§15.407(a)	PASS
26dB Emission Bandwidth& 99% Occupied Bandwidth	§15.407(a)	PASS
Power Spectral Density	§15.407(a)	PASS
Restricted Bands around fundamental frequency	§15.407(b)	PASS
Radiated Emission	§15.407(b)	PASS
Frequency Stability	§15.407(g)	PASS

Note:

1. PASS: Test item meets the requirement.

2. Fail: Test item does not meet the requirement.

3. N/A: Test case does not apply to the test object.

4. The test result judgment is decided by the limit of test standard.

5.For the band 5.15-5.25GHz,EUT meet the requirements of 15.407(a)(ii).

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

3. General Information

3.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Software:	
Software Information:	ADB Tool
Power Level:	10
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations with max. duty cycle.
The sample was placed 0.8m/1.5m for blow/above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11a(SISO)	6 Mbps
802.11n(HT20) (MIMO)	6.5 Mbps
802.11n(HT40) (MIMO)	13.5 Mbps
802.11ac(VHT20) (MIMO)	6.5 Mbps
802.11ac(VHT40) (MIMO)	13.5 Mbps
802.11ac(VHT80) (MIMO)	29.3 Mbps
802.11ax(VHT20) (MIMO)	6.5 Mbps

802.11ax(VHT40) (MIMO)	13.5 Mbps
802.11ax(VHT80) (MIMO)	29.3 Mbps
Final Test Mode:	
Operation mode:	Keep the EUT in continuous transmitting with modulation

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.

2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

3. For conducted measurements (Output Power, Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098
  SHENZHEN TONGCE TESTING LAB
  Designation Number: CN1205
  The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.
- IC - Registration No.: 10668A-1
  SHENZHEN TONGCE TESTING LAB
  CAB identifier: CN0031
  The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB
Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
TEL: +86-755-27673339

4.3. Measurement Uncertainty

The reported uncertainty of measurement y ± U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

5. Test Results and Measurement Data

5.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The EUT test with two Internal antennas for maximum gain which are detachable, and the gain is shown below.	
 Antenna 1 Antenna 2	
Refer to KDB 662911 D01 Multiple Transmitter Output v02r01: Unequal antenna gains, with equal transmit powers, if transmit signals are correlated, then Directional gain of B1= $10\log[(10^{2.58/20}+10^{3.91/20})^2/2]$ = 6.28dBi; Directional gain of B3 = $10\log[(10^{4.64/20}+10^{4.05/20})^2/2]$ = 7.36dBi.	
Note: Above directional gain not applicable to power measurements.	

5.2. Conducted Emission

5.2.1. Test Specification

<table>
<tr><td>Test Requirement:</td><td>FCC Part15 C Section 15.207</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10:2013</td></tr>
<tr><td>Frequency Range:</td><td>150 kHz to 30 MHz</td></tr>
<tr><td>Receiver setup:</td><td>RBW=9 kHz, VBW=30 kHz, Sweep time=auto</td></tr>
<tr><td>Limits:</td><td>
<table>
<tr><td rowspan="2">Frequency range (MHz)</td><td colspan="2">Limit (dBuV)</td></tr>
<tr><td>Quasi-peak</td><td>Average</td></tr>
<tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr>
<tr><td>0.5-5</td><td>56</td><td>46</td></tr>
<tr><td>5-30</td><td>60</td><td>50</td></tr>
</table>
</td></tr>
<tr><td>Test Setup:</td><td>


Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m
</td></tr>
<tr><td>Test Mode:</td><td>Transmitting Mode</td></tr>
<tr><td>Test Procedure:</td><td>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</td></tr>
<tr><td>Test Result:</td><td>PASS</td></tr>
</table>

5.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
EMI Test Receiver	R&S	ESCI3	100898	Jun. 29, 2024
Line Impedance Stabilisation Newtork(LISN)	Schwarzbeck	NSLK 8126	8126453	Jan. 31, 2025
Line-5	TCT	CE-05	/	Jul. 03, 2024
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room | Phase: *L1* | Temperature: 22.8 (℃) | Humidity: 49 %

Limit: FCC Part 15C Conduction(QP) | Power: AC 120 V/60 Hz

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1580	49.31	10.03	59.34	65.57	-6.23	QP	
2		0.1580	26.96	10.03	36.99	55.57	-18.58	AVG	
3		0.4259	38.80	9.41	48.21	57.33	-9.12	QP	
4		0.4259	28.26	9.41	37.67	47.33	-9.66	AVG	
5		2.1218	26.29	10.04	36.33	56.00	-19.67	QP	
6		2.1218	12.84	10.04	22.88	46.00	-23.12	AVG	
7		3.7660	37.18	10.27	47.45	56.00	-8.55	QP	
8		3.7660	23.33	10.27	33.60	46.00	-12.40	AVG	
9		6.9100	37.77	10.50	48.27	60.00	-11.73	QP	
10		6.9100	24.80	10.50	35.30	50.00	-14.70	AVG	
11		17.1660	33.51	10.61	44.12	60.00	-15.88	QP	
12		17.1660	21.60	10.61	32.21	50.00	-17.79	AVG	

Note:

Freq. = Emission frequency in MHz
Reading level (dBµV) = Receiver reading
Corr. Factor (dB) = LISN factor + Cable loss
Measurement (dBµV) = Reading level (dBµV) + Corr. Factor (dB)
Limit (dBµV) = Limit stated in standard
Margin (dB) = Measurement (dBµV) – Limits (dBµV)
Q.P. =Quasi-Peak
AVG =average
** is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.*

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room | Phase: N | Temperature: 22.8 (℃) | Humidity: 49 %

Limit: FCC Part 15C Conduction(QP) | Power: AC 120 V/60 Hz

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1660	48.66	10.01	58.67	65.16	-6.49	QP	
2		0.1660	28.45	10.01	38.46	55.16	-16.70	AVG	
3		0.4259	39.86	9.39	49.25	57.33	-8.08	QP	
4		0.4259	28.68	9.39	38.07	47.33	-9.26	AVG	
5		1.0420	22.51	8.82	31.33	56.00	-24.67	QP	
6		1.0420	9.41	8.82	18.23	46.00	-27.77	AVG	
7		4.0939	38.00	10.23	48.23	56.00	-7.77	QP	
8		4.0939	25.91	10.23	36.14	46.00	-9.86	AVG	
9		6.9820	38.82	10.48	49.30	60.00	-10.70	QP	
10		6.9820	25.75	10.48	36.23	50.00	-13.77	AVG	
11		15.4860	31.99	10.58	42.57	60.00	-17.43	QP	
12		15.4860	21.50	10.58	32.08	50.00	-17.92	AVG	

Note:

Freq. = Emission frequency in MHz
Reading level (dBµV) = Receiver reading
Corr. Factor (dB) = LISN factor + Cable loss
Measurement (dBµV) = Reading level (dBµV) + Corr. Factor (dB)
Limit (dBµV) = Limit stated in standard
Margin (dB) = Measurement (dBµV) – Limits (dBµV)
Q.P. =Quasi-Peak
AVG =average
** is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.*
Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80), 802.11ax(VHT20), 802.11ax(VHT40), 802.11ax(VHT80)) and the worst case Mode (Middle channel and 802.11ax(VHT20) transmit with antenna 2) was submitted only.

5.3. Maximum Conducted Output Power

5.3.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407(a)& Part 2 J Section 2.1046
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E
Limit:	Frequency Band (MHz) / Limit 5180 - 5240 / 24dBm(250mW) for client device 5260 - 5320 / 24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz 5470 - 5725 / 24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz 5745 - 5825 / 30dBm(1W)
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 5. Measure the conducted output power and record the results in the test report.
Test Result:	PASS
Remark:	Conducted output power= measurement power +10log(1/x), X is duty cycle=1, so 10log(1/1)=0 Conducted output power= measurement power

5.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Power Meter	Agilent	E4418B	MY45100357	Jun. 27, 2024
Power Sensor	Agilent	8481A	MY41091497	Jun. 27, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.3.3. Test Data

Configuration Band 1 (5180 - 5240 MHz) / Antenna 1+Antenna 2						
Mode	Test channel	Maximum Conducted (Average) Output Power (dBm)			Limit (dBm)	Result
		Ant1	Ant2	Total		
11a	CH36	12.74	13.46	/	23.72	PASS
11a	CH40	13.03	13.43	/	23.72	PASS
11a	CH48	14.03	15.05	/	23.72	PASS
11n(HT20)	CH36	13.31	13.84	16.59	23.72	PASS
11n(HT20)	CH40	13.35	13.71	16.54	23.72	PASS
11n(HT20)	CH48	14.37	15.45	17.95	23.72	PASS
11n(HT40)	CH38	13.28	13.65	16.48	23.72	PASS
11n(HT40)	CH46	14.27	15.23	17.79	23.72	PASS
11ac(VHT20)	CH36	13.22	13.69	16.47	23.72	PASS
11ac(VHT20)	CH40	13.27	13.58	16.44	23.72	PASS
11ac(VHT20)	CH48	14.33	15.29	17.85	23.72	PASS
11ac(VHT40)	CH38	13.12	12.88	16.01	23.72	PASS
11ac(VHT40)	CH46	14.10	14.46	17.29	23.72	PASS
11ac(VHT80)	CH42	13.45	13.73	16.60	23.72	PASS
11ax(VHT20)	CH36	13.13	13.40	16.28	23.72	PASS
11ax(VHT20)	CH40	13.21	13.37	16.30	23.72	PASS
11ax(VHT20)	CH48	14.20	14.93	17.59	23.72	PASS
11ax(VHT40)	CH38	13.02	13.15	16.10	23.72	PASS
11ax(VHT40)	CH46	14.02	14.61	17.34	23.72	PASS
11ax(VHT80)	CH42	13.15	13.45	16.31	23.72	PASS

Refer to KDB 662911 D01 Multiple Transmitter Output v02r01:
For power measurements on IEEE 802.11 devices,
Directional gain = 10 log[$(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}$] dBi =6.28>6, so power limit =23.72dBm.

Configuration Band 3 (5745 - 5825 MHz) / Antenna 1+Antenna 2						
Mode	Test channel	Maximum Conducted (Average) Output Power (dBm)			Limit (dBm)	Result
		Ant1	Ant2	Total		
11a	CH149	13.41	16.25	/	28.64	PASS
11a	CH157	13.81	16.58	/	28.64	PASS
11a	CH165	13.01	15.90	/	28.64	PASS
11n(HT20)	CH149	13.89	16.61	18.47	28.64	PASS
11n(HT20)	CH157	14.23	17.03	18.86	28.64	PASS
11n(HT20)	CH165	13.42	16.38	18.16	28.64	PASS
11n(HT40)	CH151	13.39	16.54	18.25	28.64	PASS
11n(HT40)	CH159	13.83	17.00	18.71	28.64	PASS
11ac(VHT20)	CH149	12.90	16.56	18.11	28.64	PASS
11ac(VHT20)	CH157	13.51	16.93	18.56	28.64	PASS
11ac(VHT20)	CH165	12.89	16.13	17.82	28.64	PASS
11ac(VHT40)	CH151	13.31	16.55	18.24	28.64	PASS
11ac(VHT40)	CH159	13.75	16.89	18.61	28.64	PASS
11ac(VHT80)	CH155	13.48	16.83	18.48	28.64	PASS
11ax(VHT20)	CH149	13.30	16.60	18.27	28.64	PASS
11ax(VHT20)	CH157	13.84	17.13	18.80	28.64	PASS
11ax(VHT20)	CH165	13.11	16.42	18.08	28.64	PASS
11ax(VHT40)	CH151	13.37	16.47	18.20	28.64	PASS
11ax(VHT40)	CH159	13.77	16.79	18.55	28.64	PASS
11ax(VHT80)	CH155	13.19	16.44	18.12	28.64	PASS

Refer to KDB 662911 D01 Multiple Transmitter Output v02r01:
For power measurements on IEEE 802.11 devices,
Directional gain = 10 log[$(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}$] dBi=7.36>6, power limit =28.64dBm.

5.4. 6dB Emission Bandwidth

5.4.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407(e)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Limit:	>500kHz
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS

5.4.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.5. 26dB Bandwidth and 99% Occupied Bandwidth

5.5.1. Test Specification

Test Requirement:	47 CFR Part 15C Section 15.407 (a)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D
Limit:	No restriction limits
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW. Set the Video bandwidth (VBW) = 3 *RBW. In order to make an accurate measurement. 4. Measure and record the results in the test report.
Test Result:	PASS

5.5.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.6. Power Spectral Density

5.6.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407 (a)
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F
Limit:	≤11.00dBm/MHz for Band 1 5150MHz-5250MHz(client device) ≤11.00dBm/MHz for Band 2A&2C 5250-5350&5470-5725 ≤30.00dBm/500KHz for Band 3 5725MHz-5850MHz The e.i,r,p spectral density for Band 1 5150MHz – 5250 MHz should not exceed 10dBm/MHz
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 1. Set RBW = 510 kHz/1 MHz, VBW ≥ 3*RBW, Sweep time = Auto, Detector = RMS. 2. Allow the sweeps to continue until the trace stabilizes. 3. Use the peak marker function to determine the maximum amplitude level. 4. The E.I.R.P spectral density used radiated test method. At a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment.
Test Result:	PASS

5.6.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.6.3. Test data

Configuration Band 1 (5180 - 5240 MHz) / Antenna 1+Antenna 2						
Mode	Test channel	Power Spectral Density(dBm/MHz)			Limit (dBm/MHz)	Result
		Ant1	Ant2	Total		
11a	CH36	1.89	2.59	/	10.72	PASS
11a	CH40	1.96	2.61	/	10.72	PASS
11a	CH48	3.02	4.01	/	10.72	PASS
11n(HT20)	CH36	1.79	2.24	5.03	10.72	PASS
11n(HT20)	CH40	1.62	2.10	4.88	10.72	PASS
11n(HT20)	CH48	2.70	3.85	6.32	10.72	PASS
11n(HT40)	CH38	-1.16	-0.65	2.11	10.72	PASS
11n(HT40)	CH46	-0.37	0.60	3.15	10.72	PASS
11ac(VHT20)	CH36	1.86	2.34	5.12	10.72	PASS
11ac(VHT20)	CH40	1.70	2.20	4.97	10.72	PASS
11ac(VHT20)	CH48	2.82	4.04	6.48	10.72	PASS
11ac(VHT40)	CH38	-1.09	-1.55	1.70	10.72	PASS
11ac(VHT40)	CH46	-0.04	0.21	3.10	10.72	PASS
11ac(VHT80)	CH42	-3.61	-3.47	-0.53	10.72	PASS
11ax(VHT20)	CH36	2.57	2.54	5.57	10.72	PASS
11ax(VHT20)	CH40	2.44	2.50	5.48	10.72	PASS
11ax(VHT20)	CH48	3.29	4.37	6.87	10.72	PASS
11ax(VHT40)	CH38	-0.40	-0.32	2.65	10.72	PASS
11ax(VHT40)	CH46	0.50	1.06	3.80	10.72	PASS
11ax(VHT80)	CH42	-2.97	-2.77	0.14	10.72	PASS

Refer to KDB 662911 D01 Multiple Transmitter Output v02r01:
For power spectral density (PSD) measurements when antenna gains are not equal,
Directional gain = 10 log[$(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}$] dBi =6.28>6,
So limit=10.72

Configuration Band 3(5745-5825MHz) / Antenna 1+Antenna 2						
Mode	Test channel	Power Spectral Density(dBm/MHz)			Limit (dBm/MHz)	Result
		Ant1	Ant2	Total		
11a	CH149	-0.02	2.90	/	28.64	PASS
11a	CH157	0.38	3.21	/	28.64	PASS
11a	CH165	-0.50	2.63	/	28.64	PASS
11n(HT20)	CH149	-0.47	2.2	4.08	28.64	PASS
11n(HT20)	CH157	-0.14	2.7	4.52	28.64	PASS
11n(HT20)	CH165	-0.97	1.99	3.77	28.64	PASS
11n(HT40)	CH151	-3.60	-0.58	1.18	28.64	PASS
11n(HT40)	CH159	-3.29	-0.13	1.58	28.64	PASS
11ac(VHT20)	CH149	-1.03	2.53	4.12	28.64	PASS
11ac(VHT20)	CH157	-0.44	3.00	4.62	28.64	PASS
11ac(VHT20)	CH165	-0.90	2.20	3.93	28.64	PASS
11ac(VHT40)	CH151	-3.31	0.20	1.80	28.64	PASS
11ac(VHT40)	CH159	-2.80	0.12	1.91	28.64	PASS
11ac(VHT80)	CH155	-6.31	-2.98	-1.32	28.64	PASS
11ax(VHT20)	CH149	0.40	3.24	5.06	28.64	PASS
11ax(VHT20)	CH157	0.56	3.68	5.40	28.64	PASS
11ax(VHT20)	CH165	-0.07	3.18	4.86	28.64	PASS
11ax(VHT40)	CH151	-2.91	0.14	1.89	28.64	PASS
11ax(VHT40)	CH159	-2.30	0.60	2.40	28.64	PASS
11ax(VHT80)	CH155	-5.52	-2.37	-0.66	28.64	PASS

Refer to KDB 662911 D01 Multiple Transmitter Output v02r01:
For power spectral density (PSD) measurements when antenna gains are not equal,
Directional gain = 10 log[$(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}$] dBi=7.36>6,
So limit=31.36

5.7. Band edge

5.7.1. Test Specification

<table>
<tr><td>Test Requirement:</td><td>FCC CFR47 Part 15E Section 15.407</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10 2013</td></tr>
<tr><td>Limit:</td><td>In un-restricted band:
For Band 1&2A&2C: -27dBm/MHz
For Band 3:
<table>
<tr><td>Frequency (MHz)</td><td>Limit (dBm/MHz)</td><td>Frequency (MHz)</td><td>Limit (dBm/MHz)</td></tr>
<tr><td>< 650</td><td>-27</td><td>5850~5855</td><td>27~15.6</td></tr>
<tr><td>5650~5700</td><td>-27~10</td><td>5855~5875</td><td>15.6~10</td></tr>
<tr><td>5700~5720</td><td>10~15.6</td><td>5875~5925</td><td>10~-27</td></tr>
<tr><td>5720~5725</td><td>15.6~27</td><td>> 5925</td><td>-27</td></tr>
</table>
E[dBμV/m] = EIRP[dBm] + 95.2 @3m
In restricted band:
<table>
<tr><td>Detector</td><td>Limit@3m</td></tr>
<tr><td>Peak</td><td>74dBμV/m</td></tr>
<tr><td>AVG</td><td>54dBμV/m</td></tr>
</table></td></tr>
<tr><td>Test Setup:</td><td> 
</td></tr>
<tr><td>Test Mode:</td><td>Transmitting mode with modulation</td></tr>
<tr><td>Test Procedure:</td><td>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold</td></tr>
</table>

	Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasipeak or average method as specified and then reported in a data sheet.
Test Result:	PASS

5.7.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
EMI Test Receiver	R&S	ESIB7	100197	Jun. 29, 2024
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 29, 2024
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Jan. 31, 2025
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Jan. 31, 2025
Pre-amplifier	HP	8447D	2727A05017	Jun. 27, 2024
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jul. 02, 2024
Broadband Antenna	Schwarzbeck	VULB9163	340	Jul. 01, 2024
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jul. 01, 2024
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Feb. 02, 2025
Coaxial cable	SKET	RC-18G-N-M	/	Jan. 31, 2025
Coaxial cable	SKET	RC_40G-K-M	/	Jan. 31, 2025
Antenna Mast	Keleto	CC-A-4M	/	/
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.7.3. Test Data

AX20-5180



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	59.79	-9.24	50.55	74.00	-23.45	peak	P	
2 *	5150.000	48.25	-9.24	39.01	54.00	-14.99	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	61.47	-9.24	52.23	74.00	-21.77	peak	P	
2 *	5150.000	51.19	-9.24	41.95	54.00	-12.05	AVG	P	

AX20-5240



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	49.15	-8.15	41.00	74.00	-33.00	peak	P	
2 *	5350.000	41.64	-8.15	33.49	54.00	-20.51	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	51.15	-8.15	43.00	74.00	-31.00	peak	P	
2 *	5350.000	41.87	-8.15	33.72	54.00	-20.28	AVG	P	

AX40-5190



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5147.411	62.78	-9.28	53.50	74.00	-20.50	peak	P	
2	5150.000	60.94	-9.24	51.70	74.00	-22.30	peak	P	
3 *	5150.000	53.50	-9.24	44.26	54.00	-9.74	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5147.279	70.72	-9.28	61.44	74.00	-12.56	peak	P	
2 *	5149.281	61.61	-9.26	52.35	54.00	-1.65	AVG	P	
3	5150.000	69.88	-9.24	60.64	74.00	-13.36	peak	P	
4	5150.000	60.95	-9.24	51.71	54.00	-2.29	AVG	P	

AX40-5230



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	50.38	-8.15	42.23	74.00	-31.77	peak	P	
2 *	5350.000	41.16	-8.15	33.01	54.00	-20.99	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	51.00	-8.15	42.85	74.00	-31.15	peak	P	
2 *	5350.000	43.45	-8.15	35.30	54.00	-18.70	AVG	P	

AX80-5210



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	69.20	-9.24	59.96	74.00	-14.04	peak	P	
2 *	5150.000	53.98	-9.24	44.74	54.00	-9.26	AVG	P	
3	5350.000	50.09	-8.15	41.94	74.00	-32.06	peak	P	
4	5350.000	42.46	-8.15	34.31	54.00	-19.69	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5119.025	76.06	-9.67	66.39	74.00	-7.61	peak	P	
2 *	5125.948	60.88	-9.58	51.30	54.00	-2.70	AVG	P	
3	5150.000	73.71	-9.24	64.47	74.00	-9.53	peak	P	
4	5150.000	58.53	-9.24	49.29	54.00	-4.71	AVG	P	
5	5350.000	52.86	-8.15	44.71	74.00	-29.29	peak	P	
6	5350.000	44.78	-8.15	36.63	54.00	-17.37	AVG	P	

AX20-5745



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge B3 (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5638.100	51.57	-7.44	44.13	68.20	-24.07	peak	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge B3 (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5612.860	52.95	-7.80	45.15	68.20	-23.05	peak	P	

AX20-5825



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge B3 (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5948.664	52.50	-6.80	45.70	68.20	-22.50	peak	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge B3 (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5974.656	52.70	-6.65	46.05	68.20	-22.15	peak	P	

AX40-5755



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge B3 (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5649.980	51.81	-7.27	44.54	68.20	-23.66	peak	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge B3 (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5650.280	52.50	-7.27	45.23	68.41	-23.18	peak	P	

AX40-5795



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge B3 (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5928.360	52.29	-6.88	45.41	68.20	-22.79	peak	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge B3 (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5974.776	52.52	-6.65	45.87	68.20	-22.33	peak	P	

AX80-5775



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge B3 (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5639.440	52.92	-7.43	45.49	68.20	-22.71	peak	P	
2	5928.680	52.13	-6.88	45.25	68.20	-22.95	peak	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 23.7(℃) Humidity: 57 %

Limit: FCC part 15.407 band edge B3 (PK) Power:AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5622.720	53.35	-7.66	45.69	68.20	-22.51	peak	P	
2	5948.600	52.15	-6.80	45.35	68.20	-22.85	peak	P	

Note: *All modulation (802.11a, 802.11n, 802.11ac, 802.11ax) have been tested, only the worst case in 802.11ax be reported.*

5.8. Unwanted Emissions

5.8.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407 & 15.209 & 15.205
Test Method:	KDB 789033 D02 v02r01
Frequency Range:	9kHz to 40GHz
Measurement Distance:	3 m
Antenna Polarization:	Horizontal & Vertical
Operation mode:	Transmitting mode with modulation
Receiver Setup:	

Frequency	Detector	RBW	VBW	Remark
9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
Above 1GHz	Peak	1MHz	3MHz	Peak Value
	Peak	1MHz	10Hz	Average Value

Limit:

Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

In restricted bands:

Frequency	Detector	Limit@3m
Above 1G	Peak	74dBμV/m
	AVG	54dBμV/m

Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(KHz)	300
0.490-1.705	24000/F(KHz)	3
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

In un-restricted bands: 68.2dBuV/m

Test setup:

For radiated emissions below 30MHz



30MHz to 1GHz

	 Above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the groundat a 3 meter camber. The table was rotated 360 degrees todetermine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, whichwas mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and thenthe antenna was tuned to heights from 1 meter to 4 meters and the rotatablewas turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and SpecifiedBandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limitspecified, then testing could be stopped and the peak values of the EUT wouldbe reported. Otherwise the emissions that did not have 10dB margin would bere-tested one by one using peak, quasi-peak or average method as specified andthen reported in a data sheet.
Test results:	PASS

5.8.2. Test Data

Please refer to following diagram for individual

Below 1GHz

Horizontal:



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 24.3(C) Humidity: 50 %

Limit: FCC Part 15C RE_3m Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	70.5836	36.11	-14.50	21.61	40.00	-18.39	QP	P	
2	183.2005	34.86	-13.47	21.39	43.50	-22.11	QP	P	
3	215.2678	36.11	-14.53	21.58	43.50	-21.92	QP	P	
4	229.2931	34.76	-13.84	20.92	46.00	-25.08	QP	P	
5 *	502.9395	34.34	-6.60	27.74	46.00	-18.26	QP	P	
6	993.0114	26.18	1.45	27.63	54.00	-26.37	QP	P	

Vertical:



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 24.3(C) Humidity: 50 %

Limit: FCC Part 15C RE_3m Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	31.2893	43.68	-13.54	30.14	40.00	-9.86	QP	P	
2	38.8878	42.20	-12.44	29.76	40.00	-10.24	QP	P	
3	43.8119	43.40	-12.54	30.86	40.00	-9.14	QP	P	
4	60.0691	44.15	-13.09	31.06	40.00	-8.94	QP	P	
5 *	70.5836	46.42	-14.50	31.92	40.00	-8.08	QP	P	
6	103.0800	45.14	-15.05	30.09	43.50	-13.41	QP	P	

Note: *1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported*

2. Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80), 802.11ax(VHT20), 802.11ax(VHT40), 802.11ax(VHT80)) and the worst case Mode (Channel 157 and 802.11ax(VHT20) transmit with antenna 1) was submitted only.

3.Measurement (dBµV) = Reading level + Correction Factor, correction Factor= Antenna Factor + Cable loss – Pre-amplifier.

Modulation Type: Band 1									
11a CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	38.79	---	8.02	46.81	---	68.2	---	-21.39
15540	H	37.01	---	9.87	46.88	---	74	54	-7.12
---	H	---	---	---	---	---	---	---	---
10360	V	38.43	---	8.02	46.45	---	68.2	---	-21.75
15540	V	37.51	---	9.87	47.38	---	74	54	-6.62
---	V	---	---	---	---	----	---	---	---
11a CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.61	---	7.97	47.58	---	68.2	---	-20.62
15600	H	38.15	---	9.83	47.98	---	74	54	-6.02
---	H	---	---	---	---	---	---	---	---
10400	V	40.31	---	7.97	48.28	---	68.2	---	-19.92
15600	V	38.68	---	9.83	48.51	---	74	54	-5.49
---	V	---	---	---	---	----	---	---	---
11a CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	38.16	---	7.97	46.13	---	68.2	---	-22.07
15720	H	37.19	---	9.83	47.02	---	74	54	-6.98
---	H	---	---	---	---	---	---	---	---
10480	V	38.06	---	7.97	46.03	---	68.2	---	-22.17
15720	V	36.42	---	9.83	46.25	---	74	54	-7.75
---	V	---	---	---	---	----	---	---	---
11n(HT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	41.76	---	8.02	49.78	---	68.2	---	-18.42
15540	H	37.55	---	9.87	47.42	---	74	54	-6.58
---	H	---	---	---	---	---	---	---	---
10360	V	42.11	---	8.02	50.13	---	68.2	---	-18.07
15540	V	37.87	---	9.87	47.74	---	74	54	-6.26
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	40.35	---	7.97	48.32	---	68.2	---	-19.88
15600	H	38.93	---	9.83	48.76	---	74	54	-5.24
---	H	---	---	---	---	---	---	---	---
10400	V	40.86	---	7.97	48.83	---	68.2	---	-19.37
15600	V	37.01	---	9.83	46.84	---	74	54	-7.16
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	41.12	---	7.97	49.09	---	68.2	---	-19.11
15720	H	37.65	---	9.83	47.48	---	74	54	-6.52
---	H	---	---	---	---	---	---	---	---
10480	V	40.31	---	7.97	48.28	---	68.2	---	-19.92
15720	V	38.23	---	9.83	48.06	---	74	54	-5.94
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH38: 5190MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	39.27	---	7.75	47.02	---	68.2	---	-21.18
15570	H	37.91	---	9.87	47.78	---	74	54	-6.22
---	H	---	---	---	---	---	---	---	---
10380	V	40.56	---	7.75	48.31	---	68.2	---	-19.89
15570	V	37.37	---	9.87	47.24	---	74	54	-6.76
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH46: 5230MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	41.45	---	7.97	49.42	---	68.2	---	-18.78
15690	H	38.36	---	9.83	48.19	---	74	54	-5.81
---	H	---	---	---	---	---	---	---	---
10460	V	41.22	---	7.97	49.19	---	68.2	---	-19.01
15690	V	38.63	---	9.83	48.46	---	74	54	-5.54
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	40.93	---	8.02	48.95	---	68.2	---	-19.25
15540	H	37.54	---	9.87	47.41	---	74	54	-6.59
---	H	---	---	---	---	---	---	---	---
10360	V	38.67	---	8.02	46.69	---	68.2	---	-21.51
15540	V	37.99	---	9.87	47.86	---	74	54	-6.14
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.45	---	7.97	47.42	---	68.2	---	-20.78
15600	H	38.39	---	9.83	48.22	---	74	54	-5.78
---	H	---	---	---	---	---	---	---	---
10400	V	39.52	---	7.97	47.49	---	68.2	---	-20.71
15600	V	38.84	---	9.83	48.67	---	74	54	-5.33
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH48:5240									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	37.71	---	7.97	45.68	---	68.2	---	-22.52
15720	H	37.65	---	9.83	47.48	---	74	54	-6.52
---	H	---	---	---	---	---	---	---	---
10480	V	38.83	---	7.97	46.8	---	68.2	---	-21.4
15720	V	38.01	---	9.83	47.84	---	74	54	-6.16
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH38:5190									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	40.19	---	7.75	47.94	---	68.2	---	-20.26
15570	H	39.38	---	9.87	49.25	---	74	54	-4.75
---	H	---	---	---	---	---	---	---	---
10380	V	38.49	---	7.75	46.24	---	68.2	---	-21.96
15570	V	38.26	---	9.87	48.13	---	74	54	-5.87
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH46:5230									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	38.21	---	7.97	46.18	---	68.2	---	-22.02
15690	H	38.66	---	9.83	48.49	---	74	54	-5.51
---	H	---	---	---	---	---	---	---	---
10460	V	39.87	---	7.97	47.84	---	68.2	---	-20.36
15690	V	37.33	---	9.83	47.16	---	74	54	-6.84
---	V	---	---	---	---	----	---	---	---

11ac(VHT80) CH42:5210									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10420	H	41.98	---	7.96	49.94	---	68.2	---	-18.26
15630	H	39.54	---	9.84	49.38	---	74	54	-4.62
---	H	---	---	---	---	---	---	---	---
10420	V	41.11	---	7.96	49.07	---	68.2	---	-19.13
15630	V	39.42	---	9.84	49.26	---	74	54	-4.74
---	V	---	---	---	---	----	---	---	---

11ax(VHT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	39.85	---	8.02	47.87	---	68.2	---	-20.33
15540	H	37.11	---	9.87	46.98	---	74	54	-7.02
---	H	---	---	---	---	---	---	---	---
10360	V	38.33	---	8.02	46.35	---	68.2	---	-21.85
15540	V	38.05	---	9.87	47.92	---	74	54	-6.08
---	V	---	---	---	---	----	---	---	---

11ax(VHT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.41	---	7.97	47.38	---	68.2	---	-20.82
15600	H	38.91	---	9.83	48.74	---	74	54	-5.26
---	H	---	---	---	---	---	---	---	---
10400	V	39.58	---	7.97	47.55	---	68.2	---	-20.65
15600	V	38.16	---	9.83	47.99	---	74	54	-6.01
---	V	---	---	---	---	----	---	---	---

11ax(VHT20) CH48:5240									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	37.64	---	7.97	45.61	---	68.2	---	-22.59
15720	H	37.35	---	9.83	47.18	---	74	54	-6.82
---	H	---	---	---	---	---	---	---	---
10480	V	38.24	---	7.97	46.21	---	68.2	---	-21.99
15720	V	38.19	---	9.83	48.02	---	74	54	-5.98
---	V	---	---	---	---	----	---	---	---

11ax(VHT40) CH38:5190									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	40.29	---	7.75	48.04	---	68.2	---	-20.16
15570	H	39.64	---	9.87	49.51	---	74	54	-4.49
---	H	---	---	---	---	---	---	---	---
10380	V	38.31	---	7.75	46.06	---	68.2	---	-22.14
15570	V	38.95	---	9.87	48.82	---	74	54	-5.18
---	V	---	---	---	---	----	---	---	---

11ax(VHT40) CH46:5230									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	38.52	---	7.97	46.49	---	68.2	---	-21.71
15690	H	38.92	---	9.83	48.75	---	74	54	-5.25
---	H	---	---	---	---	---	---	---	---
10460	V	39.91	---	7.97	47.88	---	68.2	---	-20.32
15690	V	37.42	---	9.83	47.25	---	74	54	-6.75
---	V	---	---	---	---	----	---	---	---

11ax(VHT80) CH42:5210									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10420	H	41.01	---	7.96	48.97	---	68.2	---	-19.23
15630	H	39.62	---	9.84	49.46	---	74	54	-4.54
---	H	---	---	---	---	---	---	---	---
10420	V	41.11	---	7.96	49.07	---	68.2	---	-19.13
15630	V	39.87	---	9.84	49.71	---	74	54	-4.29
---	V	---	---	---	---	----	---	---	---

Note:

1. *Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier*
2. *Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
4. *Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.*
5. *Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.*

Modulation Type: Band 3									
11a CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	37.18	---	8.09	45.27	---	74	54	-8.73
17235	H	37.62	---	9.67	47.29	---	68.2	---	-20.91
---	H	---	---	---	---	---	---	---	---
11490	V	40.01	---	8.09	48.1	---	74	54	-5.9
17235	V	38.65	---	9.67	48.32	---	68.2	---	-19.88
---	V	---	---	---	---	----	---	---	---
11a CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	39.52	---	8.10	47.62	---	74	54	-6.38
17355	H	38.46	---	9.65	48.11	---	68.2	---	-20.09
---	H	---	---	---	---	---	---	---	---
11570	V	38.75	---	8.10	46.85	---	74	54	-7.15
17355	V	39.18	---	9.65	48.83	---	68.2	---	-19.37
---	V	---	---	---	---	----	---	---	---
11a CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	37.55	---	8.12	45.67	---	74	54	-8.33
17475	H	36.46	---	9.62	46.08	---	68.2	---	-22.12
---	H	---	---	---	---	---	---	---	---
11650	V	38.28	---	8.12	46.4	---	74	54	-7.6
17475	V	38.19	---	9.62	47.81	---	68.2	---	-20.39
---	V	---	---	---	---	----	---	---	---
11n(HT20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	38.29	---	8.09	46.38	---	74	54	-7.62
17235	H	38.74	---	9.67	48.41	---	68.2	---	-19.79
---	H	---	---	---	---	---	---	---	---
11490	V	39.13	---	8.09	47.22	---	74	54	-6.78
17235	V	37.97	---	9.67	47.64	---	68.2	---	-20.56
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	38.41	---	8.10	46.51	---	74	54	-7.49
17355	H	39.22	---	9.65	48.87	---	68.2	---	-19.33
---	H	---	---	---	---	---	---	---	---
11570	V	38.09	---	8.10	46.19	---	74	54	-7.81
17355	V	39.34	---	9.65	48.99	---	68.2	---	-19.21
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	38.41	---	8.12	46.53	---	74	54	-7.47
17475	H	37.33	---	9.62	46.95	---	68.2	---	-21.25
---	H	---	---	---	---	---	---	---	---
11650	V	38.71	---	8.12	46.83	---	74	54	-7.17
17475	V	37.59	---	9.62	47.21	---	68.2	---	-20.99
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	40.13	---	8.09	48.22	---	74	54	-5.78
17265	H	37.06	---	9.67	46.73	---	68.2	---	-21.47
---	H	---	---	---	---	---	---	---	---
11510	V	41.48	---	8.09	49.57	---	74	54	-4.43
17265	V	38.92	---	9.67	48.59	---	68.2	---	-19.61
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	38.51	---	8.10	46.61	---	74	54	-7.39
17385	H	38.26	---	9.65	47.91	---	68.2	---	-20.29
---	H	---	---	---	---	---	---	---	---
11590	V	38.74	---	8.10	46.84	---	74	54	-7.16
17385	V	37.62	---	9.65	47.27	---	68.2	---	-20.93
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	40.93	---	8.09	49.02	---	74	54	-4.98
17235	H	37.41	---	9.67	47.08	---	68.2	---	-21.12
---	H	---	---	---	---	---	---	---	---
11490	V	40.08	---	8.09	48.17	---	74	54	-5.83
17235	V	38.62	---	9.67	48.29	---	68.2	---	-19.91
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	38.85	---	8.10	46.95	---	74	54	-7.05
17355	H	36.02	---	9.65	45.67	---	68.2	---	-22.53
---	H	---	---	---	---	---	---	---	---
11570	V	37.43	---	8.10	45.53	---	74	54	-8.47
17355	V	38.01	---	9.65	47.66	---	68.2	---	-20.54
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	40.94	---	8.12	49.06	---	74	54	-4.94
17475	H	38.18	---	9.62	47.8	---	68.2	---	-20.4
---	H	---	---	---	---	---	---	---	---
11650	V	38.71	---	8.12	46.83	---	74	54	-7.17
17475	V	40.54	---	9.62	50.16	---	68.2	---	-18.04
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	39.03	---	8.09	47.12	---	74	54	-6.88
17265	H	37.89	---	9.67	47.56	---	68.2	---	-20.64
---	H	---	---	---	---	---	---	---	---
11510	V	40.31	---	8.09	48.4	---	74	54	-5.6
17265	V	36.18	---	9.67	45.85	---	68.2	---	-22.35
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	40.82	---	8.10	48.92	---	74	54	-5.08
17385	H	37.41	---	9.65	47.06	---	68.2	---	-21.14
---	H	---	---	---	---	---	---	---	---
11590	V	39.36	---	8.10	47.46	---	74	54	-6.54
17385	V	38.21	---	9.65	47.86	---	68.2	---	-20.34
---	V	---	---	---	---	----	---	---	---

11ac(VHT80) CH155: 5775MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11550	H	40.55	---	8.09	48.64	---	74	54	-5.36
17325	H	38.19	---	9.66	47.85	---	68.2	---	-20.35
---	H	---	---	---	---	---	---	---	---
11550	V	41.34	---	8.09	49.43	---	74	54	-4.57
17325	V	39.65	---	9.66	49.31	---	68.2	---	-18.89
---	V	---	---	---	---	----	---	---	---

11ax(VHT20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	40.03	---	8.09	48.12	---	74	54	-5.88
17235	H	37.69	---	9.67	47.36	---	68.2	---	-20.84
---	H	---	---	---	---	---	---	---	---
11490	V	40.72	---	8.09	48.81	---	74	54	-5.19
17235	V	38.47	---	9.67	48.14	---	68.2	---	-20.06
---	V	---	---	---	---	----	---	---	---

11ax(VHT20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	38.21	---	8.10	46.31	---	74	54	-7.69
17355	H	38.54	---	9.65	48.19	---	68.2	---	-20.01
---	H	---	---	---	---	---	---	---	---
11570	V	37.43	---	8.10	45.53	---	74	54	-8.47
17355	V	38.94	---	9.65	48.59	---	68.2	---	-19.61
---	V	---	---	---	---	----	---	---	---

11ax(VHT20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	40.19	---	8.12	48.31	---	74	54	-5.69
17475	H	38.52	---	9.62	48.14	---	68.2	---	-20.06
---	H	---	---	---	---	---	---	---	---
11650	V	38.61	---	8.12	46.73	---	74	54	-7.27
17475	V	40.48	---	9.62	50.1	---	68.2	---	-18.1
---	V	---	---	---	---	----	---	---	---

11ax(VHT40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	39.38	---	8.09	47.47	---	74	54	-6.53
17265	H	37.26	---	9.67	46.93	---	68.2	---	-21.27
---	H	---	---	---	---	---	---	---	---
11510	V	40.01	---	8.09	48.1	---	74	54	-5.9
17265	V	36.46	---	9.67	46.13	---	68.2	---	-22.07
---	V	---	---	---	---	----	---	---	---

11ax(VHT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	40.27	---	8.10	48.37	---	74	54	-5.63
17385	H	37.04	---	9.65	46.69	---	68.2	---	-21.51
---	H	---	---	---	---	---	---	---	---
11590	V	39.17	---	8.10	47.27	---	74	54	-6.73
17385	V	38.36	---	9.65	48.01	---	68.2	---	-20.19
---	V	---	---	---	---	----	---	---	---

11ax(VHT80) CH155: 5775MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11550	H	40.35	---	8.09	48.44	---	74	54	-5.56
17325	H	38.12	---	9.66	47.78	---	68.2	---	-20.42
---	H	---	---	---	---	---	---	---	---
11550	V	41.29	---	8.09	49.38	---	74	54	-4.62
17325	V	9	---	9.66	18.66	---	68.2	---	-49.54
---	V	---	---	---	---	----	---	---	---

Note:

1. *Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier*
2. *Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
4. *Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.*
5. *Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.*

5.9. Frequency Stability Measurement

5.9.1. Test Specification

Test Requirement:	FCC Part15 Section 15.407(g) &Part2 J Section 2.1055
Test Method:	ANSI C63.10: 2013
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 45 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.
Test Setup:	
Test Procedure:	The EUT was placed inside the environmental test chamber and powered by nominal AC/DC voltage. b. Turn the EUT on and couple its output to a spectrum analyzer. c. Turn the EUT off and set the chamber to the highest temperature specified. d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Test Result:	PASS
Remark:	Pre-scan was performed at Antenna 1 and Antenna 2, the worst case was found. Only the test data of Antenna 1 was shown in this report.

Test plots as follows:

Test mode:	802.11ax(HT20)	Frequency(MHz):	5180
Temperature (°C)	Voltage(V_{AC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5180.04	40000	PASS
35		5180.02	20000	PASS
25		5180.02	20000	PASS
15		5180.02	20000	PASS
5		5180.02	20000	PASS
0		5180.04	40000	PASS
20	100V	5180.06	60000	PASS
	120V	5180.04	40000	PASS
	240V	5180.04	40000	PASS

Test mode:	802.11ax(HT20)	Frequency(MHz):	5200
Temperature (°C)	Voltage(V_{AC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5200.04	40000	PASS
35		5200.04	40000	PASS
25		5200.04	40000	PASS
15		5200.04	40000	PASS
5		5200.04	40000	PASS
0		5200.02	20000	PASS
20	100V	5200.04	40000	PASS
	120V	5200.04	40000	PASS
	240V	5200.04	40000	PASS

Test mode:	802.11ax(HT20)	Frequency(MHz):	5240
Temperature (°C)	Voltage(V_{AC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5240.04	40000	PASS
35		5240.04	40000	PASS
25		5240.04	40000	PASS
15		5240.04	40000	PASS
5		5240.04	40000	PASS
0		5240.04	40000	PASS
20	100V	5240.04	40000	PASS
	120V	5240.04	40000	PASS
	240V	5240.04	40000	PASS

Test mode:	802.11ax(HT20)	Frequency(MHz):	5745	
Temperature (°C)	Voltage(V_{AC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5745.04	40000	PASS
35		5745.04	40000	PASS
25		5745.06	60000	PASS
15		5745.04	40000	PASS
5		5745.04	40000	PASS
0		5745.04	40000	PASS
20	100V	5745.04	40000	PASS
	120V	5745.06	60000	PASS
	240V	5745.04	40000	PASS

Test mode:	802.11ax(HT20)	Frequency(MHz):	5785	
Temperature (°C)	Voltage(V_{AC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5785.04	40000	PASS
35		5785.04	40000	PASS
25		5785.04	40000	PASS
15		5785.04	40000	PASS
5		5785.04	40000	PASS
0		5785.04	40000	PASS
20	100V	5785.04	40000	PASS
	120V	5785.04	40000	PASS
	240V	5785.04	40000	PASS

Test mode:	802.11ax(HT20)	Frequency(MHz):	5825	
Temperature (°C)	Voltage(V_{AC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5825.04	40000	PASS
35		5825.04	40000	PASS
25		5825.04	40000	PASS
15		5825.04	40000	PASS
5		5825.04	40000	PASS
0		5825.04	40000	PASS
20	100V	5825.04	40000	PASS
	120V	5825.04	40000	PASS
	240V	5825.04	40000	PASS

Test mode:	802.11ax(HT40)	Frequency(MHz):	5190
Temperature (°C)	Voltage(V_{AC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5190.04	40000	PASS
35		5190.00	0	PASS
25		5190.04	40000	PASS
15		5190.04	40000	PASS
5		5190.04	40000	PASS
0		5190.04	40000	PASS
20	100V	5190.04	40000	PASS
	120V	5190.04	40000	PASS
	240V	5190.04	40000	PASS

Test mode:	802.11ax(HT40)	Frequency(MHz):	5230
Temperature (°C)	Voltage(V_{AC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5230.08	80000	PASS
35		5230.08	80000	PASS
25		5230.08	80000	PASS
15		5230.08	80000	PASS
5		5230.08	80000	PASS
0		5230.08	80000	PASS
20	100V	5230.08	80000	PASS
	120V	5230.08	80000	PASS
	240V	5230.08	80000	PASS

Test mode:	802.11ax(HT40)	Frequency(MHz):	5755
Temperature (°C)	Voltage(V_{AC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5755.04	40000	PASS
35		5755.00	0	PASS
25		5755.04	40000	PASS
15		5755.04	40000	PASS
5		5755.00	0	PASS
0		5755.04	40000	PASS
20	100V	5755.04	40000	PASS
	120V	5755.04	40000	PASS
	240V	5755.00	0	PASS

Test mode:	802.11ax(HT40)	Frequency(MHz):	5795	
Temperature (°C)	Voltage(V_{AC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5795.08	80000	PASS
35		5795.08	80000	PASS
25		5795.08	80000	PASS
15		5795.08	80000	PASS
5		5795.08	80000	PASS
0		5795.08	80000	PASS
20	100V	5795.08	80000	PASS
	120V	5795.08	80000	PASS
	240V	5795.08	80000	PASS

Test mode:	802.11ax(VHT80)	Frequency(MHz):	5210	
Temperature (°C)	Voltage(V_{AC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5210.08	80000	PASS
35		5210.08	80000	PASS
25		5210.08	80000	PASS
15		5210.08	80000	PASS
5		5210.08	80000	PASS
0		5210.08	80000	PASS
20	100V	5210.00	0	PASS
	120V	5210.08	80000	PASS
	240V	5210.08	80000	PASS

Test mode:	802.11ax(VHT80)	Frequency(MHz):	5775	
Temperature (°C)	Voltage(V_{AC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5775.08	80000	PASS
35		5775.08	80000	PASS
25		5775.08	80000	PASS
15		5775.08	80000	PASS
5		5775.08	80000	PASS
0		5775.08	80000	PASS
20	100V	5775.08	80000	PASS
	120V	5775.00	0	PASS
	240V	5775.08	80000	PASS

Appendix A: Test Result of Conducted Test

Antenna 1

Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)
NVNT	a	5180	Ant1	100
NVNT	a	5200	Ant1	100
NVNT	a	5240	Ant1	100
NVNT	n20	5180	Ant1	100
NVNT	n20	5200	Ant1	100
NVNT	n20	5240	Ant1	100
NVNT	n40	5190	Ant1	100
NVNT	n40	5230	Ant1	100
NVNT	ac20	5180	Ant1	100
NVNT	ac20	5200	Ant1	100
NVNT	ac20	5240	Ant1	100
NVNT	ac40	5190	Ant1	100
NVNT	ac40	5230	Ant1	100
NVNT	ac80	5210	Ant1	100
NVNT	ax20	5180	Ant1	100
NVNT	ax20	5200	Ant1	100
NVNT	ax20	5240	Ant1	100
NVNT	ax40	5190	Ant1	100
NVNT	ax40	5230	Ant1	100
NVNT	ax80	5210	Ant1	100
NVNT	a	5745	Ant1	100
NVNT	a	5785	Ant1	100
NVNT	a	5825	Ant1	100
NVNT	n20	5745	Ant1	100
NVNT	n20	5785	Ant1	100
NVNT	n20	5825	Ant1	100
NVNT	n40	5755	Ant1	100
NVNT	n40	5795	Ant1	100
NVNT	ac20	5745	Ant1	100
NVNT	ac20	5785	Ant1	100
NVNT	ac20	5825	Ant1	100
NVNT	ac40	5755	Ant1	100
NVNT	ac40	5795	Ant1	100
NVNT	ac80	5775	Ant1	100
NVNT	ax20	5745	Ant1	100
NVNT	ax20	5785	Ant1	100
NVNT	ax20	5825	Ant1	100
NVNT	ax40	5755	Ant1	100
NVNT	ax40	5795	Ant1	100
NVNT	ax80	5775	Ant1	100

Test Graphs

Duty Cycle NVNT a 5180MHz Ant1



Duty Cycle NVNT a 5200MHz Ant1



Duty Cycle NVNT a 5240MHz Ant1



Duty Cycle NVNT n20 5180MHz Ant1



Duty Cycle NVNT n20 5200MHz Ant1



Duty Cycle NVNT n20 5240MHz Ant1



Duty Cycle NVNT n40 5190MHz Ant1



Duty Cycle NVNT n40 5230MHz Ant1



Duty Cycle NVNT ac20 5180MHz Ant1



Duty Cycle NVNT ac20 5200MHz Ant1



Duty Cycle NVNT ac20 5240MHz Ant1



Duty Cycle NVNT ac40 5190MHz Ant1



Duty Cycle NVNT ac40 5230MHz Ant1



Duty Cycle NVNT ac80 5210MHz Ant1



Duty Cycle NVNT ax20 5180MHz Ant1



Duty Cycle NVNT ax20 5200MHz Ant1



Duty Cycle NVNT ax20 5240MHz Ant1



Duty Cycle NVNT ax40 5190MHz Ant1



Duty Cycle NVNT ax40 5230MHz Ant1



Duty Cycle NVNT ax80 5210MHz Ant1



Test Graphs

Duty Cycle NVNT a 5745MHz Ant1



Duty Cycle NVNT a 5785MHz Ant1



Duty Cycle NVNT a 5825MHz Ant1



Duty Cycle NVNT n20 5745MHz Ant1



Duty Cycle NVNT n20 5785MHz Ant1



Duty Cycle NVNT n20 5825MHz Ant1



Duty Cycle NVNT n40 5755MHz Ant1



Duty Cycle NVNT n40 5795MHz Ant1



Duty Cycle NVNT ac20 5745MHz Ant1



Duty Cycle NVNT ac20 5785MHz Ant1



Duty Cycle NVNT ac20 5825MHz Ant1



Duty Cycle NVNT ac40 5755MHz Ant1



Duty Cycle NVNT ac40 5795MHz Ant1



Duty Cycle NVNT ac80 5775MHz Ant1



Duty Cycle NVNT ax20 5745MHz Ant1



Duty Cycle NVNT ax20 5785MHz Ant1



Duty Cycle NVNT ax20 5825MHz Ant1



Duty Cycle NVNT ax40 5755MHz Ant1



Duty Cycle NVNT ax40 5795MHz Ant1



Duty Cycle NVNT ax80 5775MHz Ant1



Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	Ant1	12.74	24	Pass
NVNT	a	5200	Ant1	13.03	24	Pass
NVNT	a	5240	Ant1	14.03	24	Pass
NVNT	n20	5180	Ant1	13.31	24	Pass
NVNT	n20	5200	Ant1	13.35	24	Pass
NVNT	n20	5240	Ant1	14.37	24	Pass
NVNT	n40	5190	Ant1	13.28	24	Pass
NVNT	n40	5230	Ant1	14.27	24	Pass
NVNT	ac20	5180	Ant1	13.22	24	Pass
NVNT	ac20	5200	Ant1	13.27	24	Pass
NVNT	ac20	5240	Ant1	14.33	24	Pass
NVNT	ac40	5190	Ant1	13.12	24	Pass
NVNT	ac40	5230	Ant1	14.10	24	Pass
NVNT	ac80	5210	Ant1	13.45	24	Pass
NVNT	ax20	5180	Ant1	13.13	24	Pass
NVNT	ax20	5200	Ant1	13.21	24	Pass
NVNT	ax20	5240	Ant1	14.20	24	Pass
NVNT	ax40	5190	Ant1	13.02	24	Pass
NVNT	ax40	5230	Ant1	14.02	24	Pass
NVNT	ax80	5210	Ant1	13.15	24	Pass
NVNT	a	5745	Ant1	13.41	30	Pass
NVNT	a	5785	Ant1	13.81	30	Pass
NVNT	a	5825	Ant1	13.01	30	Pass
NVNT	n20	5745	Ant1	13.89	30	Pass
NVNT	n20	5785	Ant1	14.23	30	Pass
NVNT	n20	5825	Ant1	13.42	30	Pass
NVNT	n40	5755	Ant1	13.39	30	Pass
NVNT	n40	5795	Ant1	13.83	30	Pass
NVNT	ac20	5745	Ant1	12.90	30	Pass
NVNT	ac20	5785	Ant1	13.51	30	Pass
NVNT	ac20	5825	Ant1	12.89	30	Pass
NVNT	ac40	5755	Ant1	13.31	30	Pass
NVNT	ac40	5795	Ant1	13.75	30	Pass
NVNT	ac80	5775	Ant1	13.48	30	Pass
NVNT	ax20	5745	Ant1	13.30	30	Pass
NVNT	ax20	5785	Ant1	13.84	30	Pass
NVNT	ax20	5825	Ant1	13.11	27	Pass
NVNT	ax40	5755	Ant1	13.37	30	Pass
NVNT	ax40	5795	Ant1	13.77	30	Pass
NVNT	ax80	5775	Ant1	13.19	30	Pass

Test Graphs

Power NVNT a 5180MHz Ant1



Power NVNT a 5200MHz Ant1



Power NVNT a 5240MHz Ant1



Power NVNT n20 5180MHz Ant1



Power NVNT n20 5200MHz Ant1



Power NVNT n20 5240MHz Ant1



Power NVNT n40 5190MHz Ant1



Power NVNT n40 5230MHz Ant1



Power NVNT ac20 5180MHz Ant1



Power NVNT ac20 5200MHz Ant1