



Appendix B

RF Test Data for BT (BLE) (Conducted Measurement)

Product Name: Smart Bathroom Fan With Light

Trade Mark: cinoton

Test Model: STR-HV-001

Environmental Conditions

Temperature:	24.6° C
Relative Humidity:	52.4%
ATM Pressure:	100.0 kPa
Test Engineer:	Emiya Lin
Supervised by:	Simba Huang



Contents

Page

COVER PAGE

1	Duty Cycle	3
1.1	Test Result	3
1.2	Test Graphs	4
2	Maximum Conducted Output Power	7
2.1	Test Result	7
2.2	Test Graphs	8
3	-6dB Bandwidth	11
3.1	Test Result	11
3.2	Test Graphs	12
4	Maximum Power Spectral Density Level	15
4.1	Test Result	15
4.2	Test Graphs	16
5	Band Edge	19
5.1	Test Result	19
5.2	Test Graphs	20
6	Conducted RF Spurious Emission	24
6.1	Test Result	24
6.2	Test Graphs	25
7	Restrict Band	31
7.1	Test Result	31
7.2	Test Graphs	32





1 Duty Cycle


1.1 Test Result

Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor	1/T (kHz)
BLE 1M	2402	63.99	1.94	2.56
BLE 1M	2440	64.12	1.93	2.5
BLE 1M	2480	64.75	1.89	2.56
BLE 2M	2402	35.2	4.54	4.76
BLE 2M	2440	34.61	4.61	5
BLE 2M	2480	35.19	4.54	5

1.2 Test Graphs









2 Maximum Conducted Output Power


2.1 Test Result

Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
BLE 1M	2402	1.47	30	Pass
BLE 1M	2440	2.16	30	Pass
BLE 1M	2480	2.32	30	Pass
BLE 2M	2402	1.47	30	Pass
BLE 2M	2440	2.18	30	Pass
BLE 2M	2480	2.29	30	Pass

2.2 Test Graphs











3 -6dB Bandwidth


3.1 Test Result

Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
BLE 1M	2402	0.654	0.5	Pass
BLE 1M	2440	0.757	0.5	Pass
BLE 1M	2480	0.676	0.5	Pass
BLE 2M	2402	0.954	0.5	Pass
BLE 2M	2440	1.062	0.5	Pass
BLE 2M	2480	1.15	0.5	Pass

3.2 Test Graphs









4 Maximum Power Spectral Density Level


4.1 Test Result

Mode	Frequency (MHz)	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
BLE 1M	2402	-13.9	≤ 8	Pass
BLE 1M	2440	-13.17	≤ 8	Pass
BLE 1M	2480	-13.46	≤ 8	Pass
BLE 2M	2402	-16.46	≤ 8	Pass
BLE 2M	2440	-15.74	≤ 8	Pass
BLE 2M	2480	-15.5	≤ 8	Pass

4.2 Test Graphs









5 Band Edge


5.1 Test Result

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
BLE 1M	2402	-56.7	-20	Pass
BLE 1M	2480	-49.79	-20	Pass
BLE 2M	2402	-56.7	-20	Pass
BLE 2M	2480	-48.08	-20	Pass

5.2 Test Graphs













6 Conducted RF Spurious Emission


6.1 Test Result


Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
BLE 1M	2402	-42.48	-20	Pass
BLE 1M	2440	-42.81	-20	Pass
BLE 1M	2480	-44.23	-20	Pass
BLE 2M	2402	-42.05	-20	Pass
BLE 2M	2440	-42.88	-20	Pass
BLE 2M	2480	-43.65	-20	Pass


6.2 Test Graphs



















7 Restrict Band


7.1 Test Result



Mode	Frequency (MHz)	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	Duty Factor	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
BLE 1M	2402	2310	-48.61	2	-	48.65	Peak	74	Pass
BLE 1M	2402	2310	-55.26	2	1.94	43.94	Average	54	Pass
BLE 1M	2402	2340.624	-45.61	2	-	51.65	Peak	74	Pass
BLE 1M	2402	2342.16	-53.59	2	1.94	45.61	Average	54	Pass
BLE 1M	2402	2390	-47.47	2	-	49.79	Peak	74	Pass
BLE 1M	2402	2390	-57.08	2	1.94	42.12	Average	54	Pass
BLE 1M	2480	2483.5	-49.29	2	-	47.97	Peak	74	Pass
BLE 1M	2480	2483.5	-55.33	2	1.89	43.82	Average	54	Pass
BLE 1M	2480	2487.424	-45.12	2	-	52.14	Peak	74	Pass
BLE 1M	2480	2487.856	-54.74	2	1.89	44.41	Average	54	Pass
BLE 1M	2480	2500	-49.25	2	-	48.01	Peak	74	Pass
BLE 1M	2480	2500	-56.32	2	1.89	42.83	Average	54	Pass
BLE 2M	2402	2310	-47.77	2	-	49.49	Peak	74	Pass
BLE 2M	2402	2310	-56.42	2	4.54	45.38	Average	54	Pass
BLE 2M	2402	2348.4	-45.79	2	-	51.47	Peak	74	Pass
BLE 2M	2402	2341.872	-53.59	2	4.54	48.21	Average	54	Pass
BLE 2M	2402	2390	-49.49	2	-	47.77	Peak	74	Pass
BLE 2M	2402	2390	-56.72	2	4.54	45.08	Average	54	Pass
BLE 2M	2480	2483.5	-44.86	2	-	52.4	Peak	74	Pass
BLE 2M	2480	2483.5	-54.04	2	4.54	47.76	Average	54	Pass
BLE 2M	2480	2487.424	-43.85	2	-	53.41	Peak	74	Pass
BLE 2M	2480	2483.512	-54.16	2	4.54	47.64	Average	54	Pass
BLE 2M	2480	2500	-47.69	2	-	49.57	Peak	74	Pass
BLE 2M	2480	2500	-56.06	2	4.54	45.74	Average	54	Pass

7.2 Test Graphs









---The End---