

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15 SUBPART E 15.407

Report Reference No...... : **MTEB26060104-R3**

FCC ID..... : **2BGGE-OH-8000M**

Compiled by

(position+printed name+signature)..: File administrators Alisa Luo




Supervised by

(position+printed name+signature)..: Test Engineer Sunny Deng



Approved by

(position+printed name+signature)..: Manager Yvette Zhou



Date of issue..... : **Jun.10,2026**

Representative Laboratory Name. : **Shenzhen Most Technology Service Co., Ltd.**

Address..... : No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,
Nanshan, Shenzhen, Guangdong, China.

Applicant's name..... : **FUJI MEDICAL INSTRUMENTS MFG.CO., LTD.**

Address..... : 14F Oe Building 1-1-22 Noninbashi, Chuo-ku, Osaka shi, 540-0011
Japan

Test specification..... :

Standard..... : **FCC Part 15 Subpart E 15.407**

Shenzhen Most Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description.....: Massage Chair

Trade Mark.....:



Model/Type reference..... : OH-8000

Listed Models : N/A

Modulation : OFDM

Frequency..... : From 5180MHz-5240MHz

Rating..... : 100-240V~, 50/60Hz, 100W

Hardware Version : 1.0~80.0

Software Version : 1.0~80.0

Result..... : **PASS**

TEST REPORT

Equipment under Test : Massage Chair

Model /Type : OH-8000

Listed Models : N/A

Remark : N/A

Applicant : FUJI MEDICAL INSTRUMENTS MFG.CO., LTD.

Address : 14F Oe Building 1-1-22 Noninbashi, Chuo-ku, Osaka shi, 540-0011 Japan

Manufacturer : FUJI MEDICAL INSTRUMENTS MFG.CO., LTD.

Address : 14F Oe Building 1-1-22 Noninbashi, Chuo-ku, Osaka shi, 540-0011 Japan

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1 REVISION HISTORY	4
2 TEST STANDARDS	5
3 SUMMARY	6
3.1 General Remarks	6
3.2 Product Description	6
3.3 Equipment Under Test	6
3.4 Short description of the Equipment under Test (EUT)	6
3.5 EUT operation mode	7
3.6 Block Diagram of Test Setup	7
3.1 Test Item (Equipment Under Test) Description	7
3.2 Auxiliary Equipment (AE) Description	7
3.3 Antenna Information*	7
3.4 Related Submittal(s) / Grant (s)	8
3.5 Modifications	8
3.6 EUT configuration	8
4 TEST ENVIRONMENT	9
4.1 Address of the test laboratory	9
4.2 Test Facility	9
4.3 Environmental conditions	9
4.4 Test Description	10
4.5 Statement of the measurement uncertainty	10
4.6 Equipments Used during the Test	11
5 TEST CONDITIONS AND RESULTS	12
5.1 AC Power Conducted Emission	12
5.2 Radiated Emissions	15
5.3 Conduction spurious emission	22
5.4 Maximum Conducted Average Output Power	23
5.5 Power Spectral Density	24
5.6 Emission Bandwidth (26dBm Bandwidth)	25
5.7 Minimum Emission Bandwidth (6dBm Bandwidth)	26
5.8 Frequency Stability	27
5.9 Duty Cycle Information	28
6 TEST SETUP PHOTOS OF THE EUT	29
7 PHOTOS OF THE EUT	30
APPENDIX I. Frequency Stability	31
APPENDIX II. Conducted Output Power	32
APPENDIX III. 99% Bandwidth	33
APPENDIX IV. 6dB Bandwidth	34
APPENDIX V. 26dB Bandwidth	35
APPENDIX VI. Conducted Spurious & Band Edge Emission	36
APPENDIX VII. Duty Cycle	38
APPENDIX VIII. Power Spectral Density	39

1 Revision History

Revision	Issue Date	Revisions	Revised By
00	2026.06.10	Initial Issue	Alisa Luo

2 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15 Subpart E](#)—Unlicensed National Information Infrastructure Devices

[ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB789033 D02](#): General UNII Test Procedures New Rules v01r02

3 SUMMARY

3.1 General Remarks

Date of receipt of test sample	:	2026.05.06
Testing commenced on	:	2026.05.07
Testing concluded on	:	2026.06.10

3.2 Product Description

Product Description:	Massage Chair			
Model:	OH-8000			
Power supply:	AC 120V/60Hz			
Testing sample ID:	MTYP12563			
WIFI				
Supported type:	20MHz system	40MHz system	80MHz system	160MHz system
	802.11a	802.11n 802.11ac 802.11ax	802.11ac	N/A
Operation frequency:	5180MHz-5240MHz	N/A	N/A	N/A
Modulation:	OFDM	N/A	N/A	N/A
Antenna type:	PCB Antenna			
Antenna gain:	3dBi			

3.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☒ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☐ Other (specified in blank below)	

3.4 Short description of the Equipment under Test (EUT)

This is a Massage Chair For more details, refer to the user's manual of the EUT.

3.5 EUT operation mode


The Applicant provides communication tools software (AT command) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing. All test performed at the low, middle and high of operational frequency range of each mode.

Operation Frequency List WIFI on 5G Band:

Operating band	20MHz	
	Channel	Frequency (MHz)
U-NII 1 (5150MHz-5250MHz)	36	5180
	40	5200
	44	5220
	48	5240

Note: The line display in grey is those Channels/Frequencies select to test in this report for each operation mode.

3.6 Block Diagram of Test Setup



3.1 Test Item (Equipment Under Test) Description

Short designation	EUT Name	EUT Description	Serial number	Hardware status	Software status
EUT A					
EUT B					

*: declared by the applicant. According to customers information EUTs A and B are the same devices.

3.2 Auxiliary Equipment (AE) Description

AE short designation	EUT Name (if available)	EUT Description	Serial number (if available)	Software (if used)
AE 1				
AE 2				

3.3 Antenna Information*

Short designation	Antenna Name	Antenna Type	Frequency Range	Serial number	Antenna Peak Gain
Antenna	---	PCB Antenna	5180MHz-5240MHz	---	3dBi

*: declared by the applicant.

3.4 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

3.5 Modifications

No modifications were implemented to meet testing criteria.

3.6 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

☐ - supplied by the manufacturer

☐ - Supplied by the lab

☒	ADAPTER	M/N:	
☐		Manufacturer:	

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

Shenzhen Most Technology Service Co., Ltd.

No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

4.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 0031192610

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 6343.01

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

4.3 Environmental conditions

Radiated Emission:

Temperature:	23 ° C
Humidity:	48 %
Atmospheric pressure:	950-1050mbar

AC Main Conducted testing:

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

4.4 Test Description

FCC Requirement		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.407(a)	Emission Bandwidth(26dBm Bandwidth)	PASS ^{Note1}
FCC Part 15.407(e)	Minimum Emission Bandwidth(6dBm Bandwidth)	N/A ^{Note2}
FCC Part 15.407(a)	Maximum Conducted Output Power	PASS
FCC Part 15.407(a)	Peak Power Spectral Density	PASS
FCC Part 15.407(g)	Frequency Stability	PASS
FCC Part 15.407(b)	Undesirable emission	PASS
FCC Part 15.407(b)/15.205/15.209	Radiated Emissions	PASS
FCC Part 15.407(h)	Dynamic Frequency Selection	N/A ^{Note 3}
FCC Part 15.203/15.247(b)	Antenna Requirement	PASS

Note 1: Apply to U-NII 1, U-NII 2A, and U-NII 2C band.

Note 2: Apply to U-NII 3 band only.

Note 3: DFS is a separate report.

Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Conducted Output Power Power Spectral Density Emission Bandwidth(26dBm Bandwidth) Minimum Emission Bandwidth(6dBm Bandwidth) Undesirable emission Frequency Stability	11a/OFDM	54 Mbps

4.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Most Technology Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Most Technology Service Co., Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)
20dB Bandwidth & 99% Bandwidth	/	5%	(1)
Maximum Conducted Output Power	/	0.80dB	(1)

Spurious RF Conducted Emission	/	1.6dB	(1)
--------------------------------	---	-------	-----

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.6 Equipments Used during the Test


Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware versions	Last Cal.
1.	L.I.S.N.	R&S	ENV216	100093	/	2026/02/28
2.	Three-phase artificial power network	Schwarzback Mess	NNLK8129	8129178	/	2026/02/28
3.	Receiver	R&S	ESCI	100492	V3.0-10-2	2026/02/28
4.	Receiver	R&S	ESPI	101202	V3.0-10-2	2026/02/28
5.	Spectrum analyzer	Agilent	9020A	/	A14.16	2026/02/28
6.	Bilong Antenna	Sunol Sciences	JB3	A121206	/	2025/11/22
7.	Horn antenna	HF Antenna	HF Antenna	/	/	2026/03/08
8.	Loop antenna	Beijing Daze	ZN30900B	/	/	2026/03/28
10.	Wireless Communication Test Set	R&S	CMW500	155873	V3.7.40	2026/02/28
11.	Preamplifier	Millitech	KA-LNA18-40-01	18050001	/	2026/02/28
12.	High gain antenna	A-INFOMW	LB-180400KF	J211060273	/	2026/02/28
13.	Spectrum analyzer	R&S	FSP	100019	V4.40 SP2	2026/02/28
14.	Pre-amplifier	lenscend	TAP011840	AP21C806124	/	2026/02/28
15.	RF Cable(below1GHz)	Times	9kHz-1GHz	/	/	2026/02/28
16.	RF Cable(above1GHz)	Times	1-18G	/	/	2026/02/28
17.	RF Cable(9KHz-40GHz)	Tonscend	170660	/	/	2026/02/28
18.	vector Signal Generator	ROHDE & SCHWARZ	SMBV100B		/	2026/02/28
19.	Signal Generator	Agilent	5181A		/	2026/02/28
20.	splitter	Mini-Circuits	ZAP-50W	NN256400424	/	2026/02/28
21.	Humid & Temp Programmable Tester	Haida	HD-2257	110807201	/	2026/02/28
22.	X-series USB Peak and Average Power Sensor	Agilent	U2021XA	MY54080019	/	2026/02/28
23.	4 Ch.Simultaneous Sampling 14 Bits 2 MS/s	Agilent	U2531A	TW54063507	/	2026/02/28
24.	splitter	Mini-Circuits	ZAP-50W	NN256400424	/	2026/02/28
25.	Power meter	R&S	NRVS	100444	/	2026/02/28
26.	Testing software	Fala	EZ-EMC(CE)	/	Ver.FA-03A1	/
27.	Testing software	Fala	EZ-EMC(RE)	/	Ver.FA-03A3	/
27.	Testing software	WCS	WCS	/	Ver.23.06.1401	/

Note: The Cal.Interval was one year.

5 TEST CONDITIONS AND RESULTS

5.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSIC63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
- 2 Support equipment, if needed, was placed as per ANSIC63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSIC63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
- 4 The EUT received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit


For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :


Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST RESULTS

WIFI 5G modes were test at 802.11a,
(Low, Middle, and High channel); only the worst result of 802.11a Middle Channel was reported as below:





5.2 Radiated Emissions

Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Undesirable emission limits

Requirement	Limit(EIRP)	Limit (Field strength at 3m) Note1
15.407(b)(1)	PK:-27(dBm/MHz)	PK:68.2(dBμV/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)		

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$

(5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209


(6) In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure

- Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed.
- Radiated emission test frequency band from 9KHz to 40GHz.
- The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

- Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

TEST RESULTS

Remark:

- This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
- Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
- Remark: Result=Reading value+Factor


For 30MHz-1GHz

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	30.1600	-3.45	25.48	22.03	40.00	-17.97	QP	200	51	P	
2	73.7600	8.29	10.31	18.60	40.00	-21.40	QP	200	104	P	
3	161.1600	3.76	17.26	21.02	43.50	-22.48	QP	200	178	P	
4	297.7200	10.88	16.42	27.30	46.00	-18.70	QP	200	246	P	
5	359.0799	7.07	17.62	24.69	46.00	-21.31	QP	200	299	P	
6 *	931.0000	-1.01	29.31	28.30	46.00	-17.70	QP	200	335	P	

*:Maximum data x:Over limit !:over margin



For 1GHz to 40GHz

U-NII 1

Polar (H/V)	Frequency	Meter Reading	Antenna Factor	Cable loss	Preamp factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
802.11a Mode -5180MHz									
V	3586	55.89	29.03	5.24	36.4	53.76	68.2	14.44	PK
V	3586	42.8	29.03	5.24	36.4	40.67	54	13.33	AV
H	3586	52.75	29.03	5.24	36.4	50.62	68.2	17.58	PK
H	3586	47.05	29.03	5.24	36.4	44.92	54	9.08	AV
V	10360	36.25	39.41	11.45	34.28	52.83	68.2	15.37	PK
V	10360	25.15	39.41	11.45	34.28	41.73	54	12.27	AV
H	10360	34.92	39.41	11.45	34.28	51.5	68.2	16.7	PK
H	10360	28.65	39.41	11.45	34.28	45.23	54	8.77	AV
802.11a Mode -5200MHz									
V	3586	52.75	29.03	5.24	36.4	50.62	68.2	17.58	PK
V	3586	42.38	29.03	5.24	36.4	40.25	54	13.75	AV
H	3586	52.48	29.03	5.24	36.4	50.35	68.2	17.85	PK
H	3586	46.25	29.03	5.24	36.4	44.12	54	9.88	AV
V	10400	35.08	39.42	11.47	34.28	51.69	68.2	16.51	PK
V	10400	26.46	39.42	11.47	34.28	43.07	54	10.93	AV
H	10400	37.3	39.42	11.47	34.28	53.91	68.2	14.29	PK
H	10400	27.06	39.42	11.47	34.28	43.67	54	10.33	AV
802.11a Mode -5240MHz									
V	3586	54.58	29.03	5.24	36.4	52.45	68.2	15.75	PK
V	3586	43.17	29.03	5.24	36.4	41.04	54	12.96	AV
H	3586	54.36	29.03	5.24	36.4	52.23	68.2	15.97	PK
H	3586	46.19	29.03	5.24	36.4	44.06	54	9.94	AV
V	10480	35.73	39.43	11.47	34.28	52.35	68.2	15.85	PK
V	10480	26.76	39.43	11.47	34.28	43.38	54	10.62	AV
H	10480	34.88	39.43	11.47	34.28	51.5	68.2	16.7	PK
H	10480	26.87	39.43	11.47	34.28	43.49	54	10.51	AV

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. -- Mean the other emission levels were very low against the limit.
5. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

Radiated Band Edge Test:

U-NII 1

Polar (H/V)	Frequency	Meter Reading	Antenna Factor	Cable loss	Preamp factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
802.11a									
V	5150	56.19	31.22	7.62	36.5	58.53	74	15.47	PK
V	5150	38.67	31.22	7.62	36.5	41.01	54	12.99	AV
H	5150	54.98	31.22	7.62	36.5	57.32	74	16.68	PK
H	5150	44.18	31.22	7.62	36.5	46.52	54	7.48	AV
V	5350	56.3	31.56	7.83	35.82	59.87	74	14.13	PK
V	5350	40	31.56	7.83	35.82	43.57	54	10.43	AV
H	5350	53.5	31.56	7.83	35.82	57.07	74	16.93	PK
H	5350	41.61	31.56	7.83	35.82	45.18	54	8.82	AV

5.3 Conduction spurious emission

Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

Test Configuration



TEST RESULTS

See Appendix VI

5.4 Maximum Conducted Average Output Power

Limit

For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.


For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration



Test Results

See Appendix II

5.5 Power Spectral Density

Limit

(1) For the band 5.15 - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.

(iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(2) For the 5.25 - 5.35 GHz and 5.47 - 5.725 GHz bands, the peak power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(3) For the band 5.725 - 5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band. ^{note1, note2}

Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note2: Fixed point - to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 1MHz for U-NII 1, U-NII 2A, U-NII C band and 510KHz for U-NII 3 band.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to encompass the entire EBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.

Test Configuration



Test Results

See Appendix VIII

5.6 Emission Bandwidth (26dBm Bandwidth)

Limit

N/A

Test Procedure

1. Set resolution bandwidth (RBW) = approximately 1 % of the EBW.
2. Set the video bandwidth (VBW) > RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW / EBW ratio is approximately 1 %.

Test Configuration



Test Results

See Appendix V

5.7 Minimum Emission Bandwidth (6dBm Bandwidth)

Limit

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth 3 x RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Configuration



Test Results


See Appendix IV

5.8 Frequency Stability

LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

TEST CONFIGURATION



TEST PROCEDURE

Frequency Stability under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

Frequency Stability under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS

See Appendix I

5.9 Duty Cycle Information

See Appendix VII

6 Test Setup Photos of the EUT




7 Photos of the EUT

see photo report.

APPENDIX I. Frequency Stability
Test Result

Condition	Mode	Ch.	Antenna	Center Frequency (MHz)	Calculated Value of Center Frequency(MHz)	Result (ppm)	Limit (ppm)	State
NT/NV	IEEE 802.11a	36	0	5180.0	5180.003656	0.71	Within authorized band	PASS
		40		5200.0	5199.997944	-0.4		PASS
		48		5240.0	5239.995519	-0.86		PASS

Test Graphs
NT/NV
IEEE 802.11a



APPENDIX II. Conducted Output Power


Conducted output power

Mode	Channel	Corr'd Value Ant. 0 (dBm)	Limit (dBm)	Result
IEEE 802.11a	36	9.69	≤24	PASS
	40	9.83	≤24	PASS
	48	10.53	≤24	PASS

APPENDIX III. 99% Bandwidth
Test Result

Mode	Channel	Ant.	Center Frequency (MHz)	99% BW (MHz)
IEEE 802.11a	36	0	5180	16.644
	40		5200	16.534
	48		5240	16.590

Test Graphs




APPENDIX IV. 6dB Bandwidth

Test Result

Mode	Channel	Ant.	Center Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
IEEE 802.11a	36	0	5180	16.41	≥0.5	PASS
	40		5200	16.46		PASS
	48		5240	16.34		PASS


Test Graphs



APPENDIX V. 26dB Bandwidth
Test Result

Mode	Channel	Ant.	Center Frequency (MHz)	26 dB Bandwidth (MHz)	RBW/EBW
IEEE 802.11a	36	0	5180	24.48	1.0
	40		5200	21.25	1.09
	48		5240	21.34	1.18

Test Graphs





APPENDIX VI. Conducted Spurious & Band Edge Emission

Test Result

Mode	Channel	Ant.	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
IEEE 802.11a	36	0	5131.95	-39.590	-27	-12.590	PASS
			5148.96	-36.977	-27	-10.000	PASS
			5150.00	-38.506	-27	-12.000	PASS
			5350.00	-36.327	-27	-9.000	PASS
			5460.00	-35.233	-27	-8.000	PASS
			25000.0	-39.811	-27	-12.810	PASS
	40		5113.26	-42.903	-27	-15.900	PASS
			5127.84	-36.166	-27	-9.000	PASS
			5150.00	-36.177	-27	-9.000	PASS
			5350.00	-35.201	-27	-8.000	PASS
			5429.28	-34.864	-27	-8.000	PASS
			24945.0	-40.116	-27	-13.120	PASS
	48		5148.59	-42.774	-27	-15.770	PASS
			5149.92	-36.904	-27	-10.000	PASS
			5150.00	-36.904	-27	-10.000	PASS
			5350.00	-36.357	-27	-9.000	PASS
			5457.12	-36.235	-27	-9.000	PASS
			24931.7	-39.462	-27	-12.460	PASS



Note: input compensation coefficient (dB)= Cable Loss (dB)

Test Graphs




Out Of Band Emission
IEEE 802.11a Channel 36 20MHz Antenna 0

Spurious Emission:30.0~5150 MHz
IEEE 802.11a Channel 36 20MHz Antenna 0




Spurious Emission:5350~25000.0 MHz
IEEE 802.11a Channel 36 20MHz Antenna 0


Out Of Band Emission
IEEE 802.11a Channel 40 20MHz Antenna 0




Spurious Emission:30.0~5150 MHz
IEEE 802.11a_Channel 40_20MHz_Antenna 0




Spurious Emission:5350~25000.0 MHz
IEEE 802.11a_Channel 40_20MHz_Antenna 0



Out Of Band Emission
IEEE 802.11a_Channel 48_20MHz_Antenna 0



Spurious Emission:30.0~5150 MHz
IEEE 802.11a_Channel 48_20MHz_Antenna 0




Spurious Emission:5350~25000.0 MHz
IEEE 802.11a_Channel 48_20MHz_Antenna 0

APPENDIX VII. Duty Cycle

Test Result

Mode	Data rates	Channel	Antenna	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle (linear)	Duty Cycle Factor (dB)	1/T
IEEE 802.11a	54	36	1	0.037	0.611	6.11	0.0611	12.1396	27.0270
		40		0.038	0.611	6.16	0.0616	12.1042	26.3158
		48		0.038	0.611	6.16	0.0616	12.1042	26.3158


Test Graphs



APPENDIX VIII. Power Spectral Density
Test Result

Mode	Channel	Ant. 0 Meas PSD (dBm/MHz)	Ant. 0 Corr'd PSD (dBm/MHz)	Limit (dBm/MHz)	Result
IEEE 802.11a	36	-10.206	1.898	11	PASS
	40	-10.353	1.751		PASS
	48	-9.067	3.037		PASS

Test Graphs



***** End of Report *****