

RF Exposure evaluation

FCC ID	2BGPD-ZMLH-K36
Product Name	AI Intelligent skin analyzer (K36)
Model/Type reference	ZMLH-K36
Listed Model(s)	N/A

1. Reference

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radio frequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radio frequency radiation exposure evaluation: mobile devices

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f2)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500–100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f2)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

-A module can only use antennas certificated as follows provided by manufacturer;

Antenna No.	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
2.4GWIFI	FPC Antenna	2.08dBi	2400-2500MHz
5.8GWIFI	FPC Antenna	3.03dBi	5725-5850MHz

5. Conducted Output Power

WiFi2.4G

Modulation	Channel	Output Power (dBm)	Output Power (mW)
802.11b	1	7.24	5.30
	6	6.64	4.61
	11	7.23	5.28
802.11g	1	5.86	3.85
	6	7.32	5.40
	11	6.80	4.79
802.11n (HT20)	1	6.86	4.85
	6	7.41	5.51
	11	6.87	4.86
802.11n (HT40)	3	8.96	7.87
	6	5.88	3.87
	9	6.33	4.30

WiFi5.8G

Modulation	Channel	Output Power (dBm)	Output Power (mW)
802.11a	149	-0.04	0.99
	157	-0.29	0.94
	165	-0.82	0.83
802.11n (HT20)	149	3.06	2.02
	157	3.72	2.36
	165	3.27	2.12
802.11n (HT40)	151	2.89	1.95
	159	3.46	2.22

6. Manufacturing Tolerance

WiFi2.4G			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	7	7	7
Tolerance $\pm$ (dB)	1.0	1.0	1.0
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	8	5	6
Tolerance $\pm$ (dB)	1.0	1.0	1.0
WiFi5.8G			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	3	3	3
Tolerance $\pm$ (dB)	1.0	1.0	1.0
Channel	Channel 151	Channel 159	
Target (dBm)	2	3	
Tolerance $\pm$ (dB)	1.0	1.0	

7. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is 2.08dBi and 3.03, the RF power density can be obtained.

Mode	Output power		Antenna Gain (dBi)	Antenna Gain(linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
2.4GWIFI	9	7.94	2.08	1.61	0.00255	1.0000
5GWIFI	4	2.51	3.03	2.01	0.00100	1.0000

Remark:

1. Output power including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----End of the report-----