



FCC TEST REPORT

FCC ID: 2BGPD-ZMLH-X1

On Behalf of

Shenzhen Zhimei Lihe Industrial Development Co., Ltd.

AI Intelligent skin analyzer(X1)

Model No.: ZMLH-X1

Prepared for : Shenzhen Zhimei Lihe Industrial Development Co., Ltd.
Floor 5,Building C, Hengshunyuan Industrial Park, 6th

Address : Road,Building1,Loucun Community,Xinhu Street, Guangming
District, Shenzhen

Prepared By : Shenzhen PSI Testing Co., Ltd.

Address : 1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road,
Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Report Number : psi2509219-C01-R03

Date of Receipt : September 27, 2025

Date of Test : September 27, 2025- October 14, 2025

Date of Report : October 14, 2025

Version Number : V0

TABLE OF CONTENTS

Description	Page
1. Summary Of Standards And Results	6
1.1. Description of Standards and Results	6
2. General Information	7
2.1. Description of Device (EUT)	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of Connection Between EUT and Simulators	8
2.5. Test Mode Description	9
2.6. Software test version and power setting information	10
2.7. Test Conditions	10
2.8. Test Facility	11
2.9. Measurement Uncertainty	11
2.10. Test Equipment List	12
3. Spurious Emission	13
3.1. Test Limits	13
3.2. Block Diagram of Test setup	16
3.3. Test Procedure	17
3.4. Test Results	18
4. Power Line Conducted Emission	27
4.1. Test Limits	27
4.2. Test Procedure	27
4.3. Test Setup	27
4.4. Test Results	28
5. Out-of-band Emissions	31
5.1. Test Limits	31
5.2. Test Procedure	31
5.3. Test Setup	31
5.4. Test Results	31
6. Conducted Maximum Output Power	53
6.1. Test limits	53
6.2. Test Procedure	53
6.3. Test Setup	53
6.4. Test Results	53
7. Peak Power Spectral Density	60
7.1. Test limits	60
7.2. Test Procedure	60
7.3. Test Setup	60
7.4. Test Results	61
8. Bandwidth	68
8.1. Test limits	68
8.2. Test Procedure	68
8.3. Test Setup	68
8.4. Test Results	68
9. Band Edge Test	82
9.1. Block Diagram of Test Setup	82
9.2. Test Limit	82
9.3. Test Procedure	82
9.4. Test Results	83
10. Frequency stability	87
10.1. Test limit	87
10.2. Test Procedure	87
10.3. Test Setup	87

10.4. Test Results -----	87
11. Antenna Requirement-----	88
11.1. Standard Requirement -----	88
11.2. Antenna Connected Construction -----	88
11.3. Results -----	88
12. Photos of test setup -----	89
13. Photos of EUT -----	89

TEST REPORT DECLARATION

Applicant : Shenzhen Zhimei Lihe Industrial Development Co., Ltd.
Address : Floor 5,Building C, Hengshunyuan Industrial Park, 6th Road,Building1,Loucun
Community,Xinhu Street, Guangming District, Shenzhen
Manufacturer : Shenzhen Zhimei Lihe Industrial Development Co., Ltd.
Address : Floor 5,Building C, Hengshunyuan Industrial Park, 6th Road,Building1,Loucun
Community,Xinhu Street, Guangming District, Shenzhen
EUT Description : AI Intelligent skin analyzer(X1)
(A) Model No. : ZMLH-X1
(B) Trademark : N/A

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10:2013

Test Result: PASS

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part 15C requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....:

Jensen Wang
Test Engineer

Jensen Wang

Approved by (name + signature).....:

Simple Guan
Project Manager

Simple Guan

Date of issue.....:

October 14, 2025

Revision History

Revision	Issue Date	Revisions	Revised By
V0	October 14, 2025	Initial released Issue	Jensen Wang

1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Conducted Emission	FCC Part 15: 15.207 RSS-GEN(8.8), ANSI C63.10 :2013	P
6dB Bandwidth	FCC PART 15:15.247(a)(2) RSS-247(5.2 a), ANSI C63.10 :2013	P
Output Power	FCC Part 15: 15.247(b)(3) RSS-247(5.4 d), ANSI C63.10 :2013	P
Radiated Spurious Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) RSS-Gen(8.9), RSS-247(5.5) ANSI C63.10 :2013	P
Conducted Spurious & Band Edge Emission	FCC Part 15: 15.247(d) RSS-Gen(8.9), RSS-247(5.5) ANSI C63.10 :2013	P
Power Spectral Density	FCC PART 15:15.247(e) RSS-247(5.2 b), ANSI C63.10 :2013	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d) RSS-GEN(6.13), ANSI C63.10 :2013	P
Frequency stability	RSS-GEN(6.11)	N/A
Antenna Requirement	FCC Part 15: 15.203 RSS-GEN(6.8)	P
Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable. 4. Conclusion determination rules of this report: Unless there are clear provisions on measurement uncertainty in the standard or customer requirements, decision by actual test data without considering measurement uncertainty. 5. Measurement method usage KDB 558074 D01 15.247 Meas Guidance v05r02.		

2. General Information

2.1. Description of Device (EUT)

Product Name : AI Intelligent skin analyzer(X1)
 Model : ZMLH-X1
 Diff : N/A
 Test Voltage : AC 120V/60Hz

Radio technology	: 2.4G WiFi
Operation frequency	: 2412MHz-2462MHz for IEEE 802.11 b, g, n/HT20 2422MHz-2452MHz for IEEE 802.11n/HT40
Channel No.	: 802.11b/802.11g/802.11n(HT20): 11CH 802.11n(HT40): 7CH
Modulation type	: IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)
Antenna Type	: Internal antenna, maximum gain is 2.08dBi.
PMN	: N/A
HVIN	: N/A
Software version	: N/A
Hardware version/FVIN	: N/A
Note	: Antenna information is provided by applicant. Testing lab is not responsible for the accuracy of the information.


2.2. Accessories of Device (EUT)

Accessories 1 : N/A
Manufacturer : N/A
Model : N/A
Rating : N/A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1	N/A	N/A	N/A	N/A

2.4. Block Diagram of Connection Between EUT and Simulators



2.5. Test Mode Description

Keeping TX			
Mode	Data rate (Mbps)	Channel	Frequency(MHz)
IEEE 802.11 b	1	Low :CH1	2412
	1	Middle: CH6	2437
	1	High: CH11	2462
IEEE 802.11 g	6	Low :CH1	2412
	6	Middle: CH6	2437
	6	High: CH11	2462
IEEE 802.11 n/HT20	6.5	Low :CH1	2412
	6.5	Middle: CH6	2437
	6.5	High: CH11	2462
IEEE 802.11 n/HT40	13.5	Low :CH1	2422
	13.5	Middle:CH4	2437
	13.5	High:CH7	2452
Note: According exploratory test, EUT will have maximum output power in those data rate. So those data rate were used for all test.			

Channel list:					
For IEEE 802.11b, g, n/HT20					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH1	2412	CH5	2432	CH9	2452
CH2	2417	CH6	2437	CH10	2457
CH3	2422	CH7	2442	CH11	2462
CH4	2427	CH8	2447		

For IEEE 802.11 n/HT40					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH1	2422	CH5	2442		
CH2	2427	CH6	2447		
CH3	2432	CH7	2452		
CH4	2437				

2.6. Software test version and power setting information

Software testing version	Android system, engineering mode		
Mode	The client 's preset testing software is used to control the operation of EUT in continuous transmission mode and select the testing channel, wireless mode:		
Power level setup by client			
Mode	Channel	Frequency (MHz)	Soft Set
IEEE 802.11b/g/n20	Low :CH1	2412	TX level is set as defaults value.
	Middle: CH6	2437	TX level is set as defaults value.
	High: CH11	2462	TX level is set as defaults value.
IEEE 802.11n40	Low :CH1	2422	TX level is set as defaults value.
	Middle:CH4	2437	TX level is set as defaults value.
	High:CH7	2452	TX level is set as defaults value.

2.7. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	26℃
Humidity range:	25-75%	54%
Pressure range:	86-106kPa	101kPa

2.8. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission

Registration Number: 916281

2.9. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.17dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	2.74dB(Polarize: V)
	2.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 18GHz)	4.29dB(Polarize: V)
	4.82dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V)
	4.30 dB(Polarize: H)
Uncertainty for radio frequency	48.24KHz
Uncertainty for conducted RF Power	0.41dB
Uncertainty for Power Spectral Density	0.39 dB

2.10.Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2022.12.20	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2024.12.18	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV216	102282	/	2024.12.18	1 Year
4.	L.I.S.N.#2	RFT	NNB111	13835240	/	2024.12.18	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2025.01.02	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2025.01.02	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2024.12.18	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2025.01.02	2 Year
9.	Amplifier	SKET	LAPA_01G1 8G-45dB	SK20220329 01	/	2024.12.18	1 Year
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2024.12.31	2 Year
11.	Amplifier	SKET	LNPA_0118 G-45	SK20200108 01	/	2024.12.18	1 Year
12	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.0 2-1111533-Fz	/	2024.12.18	1 Year
13	RF Sensor Unit	Tachoy	TR1029-2	20220428P0 08	/	2024.12.18	1 Year
14	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2024.12.18	1 Year
15	Temp. & Humid Chamber	Auchno	9606	/	/	2024.12.18	1 Year
16	Regulated DC Power Supply	Xinouhua	ADC120V10 A	2022112516 38		2024.12.18	1 Year
17	Power meter	Agilent	E4419B	GB40202121	/	2024.12.18	1 Year
For Test Software Information							
Item	Software Name	Manufacturer			Version		
RE	EZ EMC	Farad			PSI-3A1		
CE	EZ EMC	Farad			PSI-3A1		
RF	RTS	TACHOY			V1.0.0		

3. Spurious Emission

3.1. Test Limits

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

RSS-GEN Restricted frequency band

Table 7 – Restricted frequency bands^{Note 1}

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 – 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0

6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 – 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 – 8500	
108 – 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSS.

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009-0.490	300	$2400/F(\text{KHz})$	/
0.490-1.705	30	$24000/F(\text{KHz})$	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Note: The peak limit is 20 dB higher than the average limit

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength ($\mu\text{V}/\text{m}$ at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500


Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) ($\mu\text{A}/\text{m}$)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	$6.37/F$ (F in kHz)	300
490 - 1705 kHz	$63.7/F$ (F in kHz)	30
1.705 - 30 MHz	0.08	30


Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

3.2. Block Diagram of Test setup


3.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



3.2.2 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



3.2.3 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



3.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

Test setup information:


9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHz~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

3.4. Test Results

We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.
Detailed information please see the following page.


From 9KHz to 30MHz:	
Test Date : 2025.09.30	Temperature : 26℃
Test Engineer : Jensen Wang	Humidity : 54%
Test Mode : IEEE 802.11b mode	
Test Results : PASS	
Note:	The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz:	
Test Date : 2025.09.30	Temperature : 26℃
Test Engineer : Jensen Wang	Humidity : 54%
Test Mode : IEEE 802.11b mode	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. All modes have been tested, and only worst data of IEEE 802.11b mode, Channel 2412MHz was listed in this report.

Polarization: Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	76.7807	25.94	11.08	37.02	40.00	-2.98	QP
2	148.5061	25.49	15.05	40.54	43.50	-2.96	QP
3	212.4556	25.47	11.77	37.24	43.50	-6.26	QP
4	330.9193	27.24	15.75	42.99	46.00	-3.01	QP
5	445.6320	24.83	18.73	43.56	46.00	-2.44	QP
6 *	742.5841	19.35	24.88	44.23	46.00	-1.77	QP

Level = Reading + Factor Margin = Level - Limit

Polarization: Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.3040	22.20	13.92	36.12	40.00	-3.88	QP
2	76.7135	26.53	11.09	37.62	40.00	-2.38	QP
3 *	148.5061	27.74	15.05	42.79	43.50	-0.71	QP
4	296.9636	27.69	14.78	42.47	46.00	-3.53	QP
5	445.6320	24.52	18.73	43.25	46.00	-2.75	QP
6	594.0903	21.07	22.04	43.11	46.00	-2.89	QP

Level = Reading + Factor Margin = Level - Limit

From 1GHz to 25GHz:	
Test Date : 2025.09.30	Temperature : 26℃
Test Engineer : Jensen Wang	Humidity : 54%
Test Mode : WiFi mode	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

Test Mode : IEEE 802.11b TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4824	V	58.31	-13.18	45.13	74.00	-28.87	Peak
2	4824	V	47.51	-13.18	34.33	54.00	-19.67	Avg
3	7236	--	--	--	--	--	--	--
4	9648	--	--	--	--	--	--	--
5	4824	H	55.07	-13.18	41.89	74.00	-32.11	Peak
6	4824	H	45.71	-13.18	32.53	54.00	-21.47	Avg
7	7236	--	--	--	--	--	--	--
8	9648	--	--	--	--	--	--	--
Test Mode : IEEE 802.11b TX Mid								
1	4874	V	57.64	-13.00	44.64	74.00	-29.36	Peak
2	4874	V	47.50	-13.00	34.50	54.00	-19.50	Avg
3	7311	--	--	--	--	--	--	--
4	9748	--	--	--	--	--	--	--
5	4874	H	55.14	-13.00	42.14	74.00	-31.86	Peak
6	4874	H	44.95	-13.00	31.95	54.00	-22.05	Avg
7	7311	--	--	--	--	--	--	--
8	9748	--	--	--	--	--	--	--
Test Mode : IEEE 802.11b TX High								
1	4924	V	57.70	-12.83	44.87	74.00	-29.13	Peak
2	4924	V	47.75	-12.83	34.92	54.00	-19.08	Avg
3	7386	--	--	--	--	--	--	--
4	9848	--	--	--	--	--	--	--
5	4924	H	57.84	-12.83	45.01	74.00	-28.99	Peak
6	4924	H	45.01	-12.83	32.18	54.00	-21.82	Avg
7	7386	--	--	--	--	--	--	--
8	9848	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

Test Mode : IEEE 802.11g TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4824	V	59.77	-13.18	46.59	74.00	-27.41	Peak
2	4824	V	46.94	-13.18	33.76	54.00	-20.24	Avg
3	7236	--	--	--	--	--	--	--
4	9648	--	--	--	--	--	--	--
5	4824	H	55.47	-13.18	42.29	74.00	-31.71	Peak
6	4824	H	46.85	-13.18	33.67	54.00	-20.33	Avg
7	7236	--	--	--	--	--	--	--
8	9648	--	--	--	--	--	--	--
Test Mode : IEEE 802.11g TX Mid								
1	4874	V	59.16	-13.00	46.16	74.00	-27.84	Peak
2	4874	V	49.20	-13.00	36.20	54.00	-17.80	Avg
3	7311	--	--	--	--	--	--	--
4	9748	--	--	--	--	--	--	--
5	4874	H	56.11	-13.00	43.11	74.00	-30.89	Peak
6	4874	H	46.28	-13.00	33.28	54.00	-20.72	Avg
7	7311	--	--	--	--	--	--	--
8	9748	--	--	--	--	--	--	--
Test Mode : IEEE 802.11g TX High								
1	4924	V	57.61	-12.83	44.78	74.00	-29.22	Peak
2	4924	V	47.89	-12.83	35.06	54.00	-18.94	Avg
3	7386	--	--	--	--	--	--	--
4	9848	--	--	--	--	--	--	--
5	4924	H	56.88	-12.83	44.05	74.00	-29.95	Peak
6	4924	H	47.49	-12.83	34.66	54.00	-19.34	Avg
7	7386	--	--	--	--	--	--	--
8	9848	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

Test Mode : IEEE 802.11n/HT20 TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4824	V	56.37	-13.18	43.19	74.00	-30.81	Peak
2	4824	V	48.86	-13.18	35.68	54.00	-18.32	Avg
3	7236	--	--	--	--	--	--	--
4	9648	--	--	--	--	--	--	--
5	4824	H	57.12	-13.18	43.94	74.00	-30.06	Peak
6	4824	H	45.59	-13.18	32.41	54.00	-21.59	Avg
7	7236	--	--	--	--	--	--	--
8	9648	--	--	--	--	--	--	--
Test Mode : IEEE 802.11n/HT20 TX Mid								
1	4874	V	56.89	-13.00	43.89	74.00	-30.11	Peak
2	4874	V	49.08	-13.00	36.08	54.00	-17.92	Avg
3	7311	--	--	--	--	--	--	--
4	9748	--	--	--	--	--	--	--
5	4874	H	58.03	-13.00	45.03	74.00	-28.97	Peak
6	4874	H	46.32	-13.00	33.32	54.00	-20.68	Avg
7	7311	--	--	--	--	--	--	--
8	9748	--	--	--	--	--	--	--
Test Mode : IEEE 802.11n/HT20 TX High								
1	4924	V	56.93	-12.83	44.10	74.00	-29.90	Peak
2	4924	V	48.63	-12.83	35.80	54.00	-18.20	Avg
3	7386	--	--	--	--	--	--	--
4	9848	--	--	--	--	--	--	--
5	4924	H	55.27	-12.83	42.44	74.00	-31.56	Peak
6	4924	H	47.33	-12.83	34.50	54.00	-19.50	Avg
7	7386	--	--	--	--	--	--	--
8	9848	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

Test Mode : IEEE 802.11n/HT40 TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4844	V	59.23	-13.11	46.12	74.00	-27.88	Peak
2	4844	V	49.02	-13.11	35.91	54.00	-18.09	Avg
3	7266	--	--	--	--	--	--	--
4	9688	--	--	--	--	--	--	--
5	4844	H	54.57	-13.11	41.46	74.00	-32.54	Peak
6	4844	H	47.13	-13.11	34.02	54.00	-19.98	Avg
7	7266	--	--	--	--	--	--	--
8	9688	--	--	--	--	--	--	--
Test Mode : IEEE 802.11n/HT40 TX Mid								
1	4874	V	59.09	-13.00	46.09	74.00	-27.91	Peak
2	4874	V	49.63	-13.00	36.63	54.00	-17.37	Avg
3	7311	--	--	--	--	--	--	--
4	9748	--	--	--	--	--	--	--
5	4874	H	55.97	-13.00	42.97	74.00	-31.03	Peak
6	4874	H	45.10	-13.00	32.10	54.00	-21.90	Avg
7	7311	--	--	--	--	--	--	--
8	9748	--	--	--	--	--	--	--
Test Mode : IEEE 802.11n/HT40 TX High								
1	4904	V	57.22	-12.90	44.32	74.00	-29.68	Peak
2	4904	V	48.21	-12.90	35.31	54.00	-18.69	Avg
3	7356	--	--	--	--	--	--	--
4	9808	--	--	--	--	--	--	--
5	4904	H	58.30	-12.90	45.40	74.00	-28.60	Peak
6	4904	H	47.97	-12.90	35.07	54.00	-18.93	Avg
7	7356	--	--	--	--	--	--	--
8	9808	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor, Margin= Result-Limit.								

4. Power Line Conducted Emission

4.1. Test Limits

Frequency (MHz)	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.


2. The lower limit shall apply at the transition frequencies.

3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Measurement. The bandwidth of test receiver is set at 9 kHz.

4.3. Test Setup




4.4. Test Results

Test Date	: 2025.09.30	Temperature	: 26℃
Test Engineer	: Jensen Wang	Humidity	: 54%
Test Mode	: WIFI mode		
Test Results	: PASS		

Note: 1. The test results are listed in next pages.

2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out.
3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.
4. All modes have been tested, and only worst data of b mode, Channel 2412MHz (AC 120V/ 60Hz) was listed in this report.


Polarization: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1620	44.85	9.94	54.79	65.36	-10.57	QP
2	0.1780	35.10	9.95	45.05	54.58	-9.53	AVG
3	0.2180	37.96	9.96	47.92	62.89	-14.97	QP
4	0.2260	31.77	9.96	41.73	52.60	-10.87	AVG
5 *	0.5420	39.32	9.81	49.13	56.00	-6.87	QP
6	0.5500	29.03	9.79	38.82	46.00	-7.18	AVG
7	1.2380	20.68	9.41	30.09	46.00	-15.91	AVG
8	1.2579	31.19	9.40	40.59	56.00	-15.41	QP
9	2.4380	28.84	9.39	38.23	56.00	-17.77	QP
10	2.5300	18.67	9.38	28.05	46.00	-17.95	AVG
11	15.7100	21.55	9.58	31.13	50.00	-18.87	AVG
12	16.2780	31.80	9.59	41.39	60.00	-18.61	QP

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1780	44.99	9.93	54.92	64.58	-9.66	QP
2	0.1780	36.35	9.93	46.28	54.58	-8.30	AVG
3 *	0.5420	40.10	9.78	49.88	56.00	-6.12	QP
4	0.5460	29.79	9.78	39.57	46.00	-6.43	AVG
5	1.1820	20.35	9.46	29.81	46.00	-16.19	AVG
6	1.2059	33.55	9.46	43.01	56.00	-12.99	QP
7	2.5020	18.35	9.41	27.76	46.00	-18.24	AVG
8	2.5420	29.75	9.42	39.17	56.00	-16.83	QP
9	7.0820	17.36	9.50	26.86	50.00	-23.14	AVG
10	7.1260	28.43	9.49	37.92	60.00	-22.08	QP
11	15.2860	29.82	9.92	39.74	60.00	-20.26	QP
12	16.0500	19.24	9.94	29.18	50.00	-20.82	AVG

Note: Level = Reading + Factor Margin = Level - Limit

5. Out-of-band Emissions


5.1. Test Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in FCC Part 15.209(a) is not required. Please refer section RSS-GEN&15.247.

5.2. Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, band edge and out-of-band emissions.

5.3. Test Setup





5.4. Test Results


PASS.

The test results are listed in next pages.

Band Edge: Pass.

Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_freq(MHz)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	2399.936	-45.673	-16.250	Pass
NVNT	ANT1	802.11b	2462.00	2486.560	-53.075	-16.458	Pass
NVNT	ANT1	802.11g	2412.00	2399.712	-43.864	-21.408	Pass
NVNT	ANT1	802.11g	2462.00	2483.776	-56.418	-21.156	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	2399.824	-45.994	-22.920	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	2488.288	-55.907	-22.893	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	2399.232	-41.380	-25.355	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	2485.720	-52.575	-24.892	Pass

1 Reference_Level_NVNT_ANT1_802_11b_2412**2 Bandedge_NVNT_ANT1_802_11b_2412**




1 Reference Level NVNT ANT1 802 11g 2412





1 Reference Level NVNT_ANT1_802_11n(HT20)_2412





2. Bandedge NVNT_ANT1_802_11n(HT20)_2462



1. Reference Level NVNT_ANT1_802_11n(HT40)_2422




1. Reference Level NVNT_ANT1_802_11n(HT40)_2452





Conducted spurious emission: Pass.

Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_freq(MHz)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	24430.684	-43.102	-16.250	Pass
NVNT	ANT1	802.11b	2437.00	24403.217	-47.642	-15.594	Pass
NVNT	ANT1	802.11b	2462.00	23953.757	-43.240	-16.458	Pass
NVNT	ANT1	802.11g	2412.00	24373.253	-52.912	-21.408	Pass
NVNT	ANT1	802.11g	2437.00	23893.829	-52.974	-19.723	Pass
NVNT	ANT1	802.11g	2462.00	24360.768	-53.893	-21.156	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	24400.720	-55.266	-22.920	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	24338.295	-48.912	-22.183	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	24270.876	-52.904	-22.893	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	24735.318	-56.515	-25.355	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	24443.169	-50.697	-24.985	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	24183.481	-51.528	-24.892	Pass




1 Reference Level NVNT_ANT1_802_11b_2437







1. Reference Level NVNT_ANT1_802_11g_2412




1. Reference Level NVNT_ANT1_802_11g_2437




2. Spurious Emission NVNT_ANT1_802_11g_2437




1. Reference Level NVNT_ANT1_802_11g_2462




1. Reference Level NVNT_ANT1_802_11n(HT20)_2412




1 Reference Level NVNT_ANT1_802_11n(HT20)_2437




1 Reference Level NVNT_ANT1_802_11n(HT20)_2462




1 Reference Level NVNT_ANT1_802_11n(HT40)_2422



1. Reference Level NVNT_ANT1_802_11n(HT40)_2437



1 Reference Level NVNT_ANT1_802_11n(HT40)_2452



6. Conducted Maximum Output Power

6.1. Test limits

Please refer RSS-247 & FCC PART 15.247.

Regulation 15.247(b) The limit of Maximum Peak Output Power Measurement is 1 W(30dBm)


6.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

1. Place the EUT on the table and set it in transmitting mode.
2. Connected the EUT's antenna port to peak power meter by 20dB attenuator.
3. Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.



6.3. Test Setup





6.4. Test Results

Condition	Antenna	Modulation	Frequency (MHz)	Detector	Conducted Power(dBm)	Duty factor(dB)	Total Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	Peak	14.36	N/A	14.36	30	Pass
NVNT	ANT1	802.11b	2437.00	Peak	14.89	N/A	14.89	30	Pass
NVNT	ANT1	802.11b	2462.00	Peak	14.56	N/A	14.56	30	Pass
NVNT	ANT1	802.11g	2412.00	Peak	16.57	N/A	16.57	30	Pass
NVNT	ANT1	802.11g	2437.00	Peak	17.01	N/A	17.01	30	Pass
NVNT	ANT1	802.11g	2462.00	Peak	16.43	N/A	16.43	30	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	Peak	14.68	N/A	14.68	30	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	Peak	15.32	N/A	15.32	30	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	Peak	14.94	N/A	14.94	30	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	Peak	14.84	N/A	14.84	30	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	Peak	15.30	N/A	15.30	30	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	Peak	15.05	N/A	15.05	30	Pass



Condition	Antenna	Modulation	Frequency (MHz)	Duty cycle(%)	Duty factor(dB)
NVNT	ANT1	802.11b	2412.00	99.53	0.00
NVNT	ANT1	802.11b	2437.00	99.53	0.00
NVNT	ANT1	802.11b	2462.00	99.53	0.00
NVNT	ANT1	802.11g	2412.00	97.22	0.12
NVNT	ANT1	802.11g	2437.00	97.26	0.12
NVNT	ANT1	802.11g	2462.00	97.22	0.12
NVNT	ANT1	802.11n(HT20)	2412.00	97.06	0.13
NVNT	ANT1	802.11n(HT20)	2437.00	97.10	0.13
NVNT	ANT1	802.11n(HT20)	2462.00	97.06	0.13
NVNT	ANT1	802.11n(HT40)	2422.00	94.29	0.26
NVNT	ANT1	802.11n(HT40)	2437.00	94.29	0.26
NVNT	ANT1	802.11n(HT40)	2452.00	94.29	0.26





Duty Cycle NVNT_ANT1_802_11b_2462





Duty Cycle NVNT ANT1 802 11g 2437





Duty Cycle NVNT ANT1 802 11n(HT20) 2412



Duty Cycle NVNT_ANT1_802_11n(HT20)_2462



Duty Cycle NVNT_ANT1_802_11n(HT40)_2437



7. Peak Power Spectral Density

7.1. Test limits


1. Please refer RSS-247 & FCC PART 15.247.
2. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
3. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

7.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as $RBW = 30\text{kHz}$ (Set the RBW to: $3\text{ kHz} \leq RBW \leq 100\text{ kHz}$), $VBW = 300\text{kHz}$ (Set the $VBW \geq 3 \times RBW$), $\text{span} \geq 1.5 \times \text{DTS bandwidth}$., detail see the test plot.
4. Record the max reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.

7.3. Test Setup



7.4. Test Results

Condition	Antenna	Modulation	Frequency (MHz)	SA_PSD (dBm/30kHz)	Duty factor(dB)	RB factor (dB)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
NVNT	ANT1	802.11b	2412.00	-0.22	N/A	-10.00	-10.22	8	Pass
NVNT	ANT1	802.11b	2437.00	0.42	N/A	-10.00	-9.58	8	Pass
NVNT	ANT1	802.11b	2462.00	0.37	N/A	-10.00	-9.63	8	Pass
NVNT	ANT1	802.11g	2412.00	-5.45	N/A	-10.00	-15.45	8	Pass
NVNT	ANT1	802.11g	2437.00	-4.34	N/A	-10.00	-14.34	8	Pass
NVNT	ANT1	802.11g	2462.00	-4.85	N/A	-10.00	-14.85	8	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	-6.99	N/A	-10.00	-16.99	8	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	-6.11	N/A	-10.00	-16.11	8	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	-6.44	N/A	-10.00	-16.44	8	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	-10.36	N/A	-10.00	-20.36	8	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	-9.70	N/A	-10.00	-19.70	8	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	-9.83	N/A	-10.00	-19.83	8	Pass


RB factor (dB)= 10 lg(3kHz/30kHz);

PSD(dBm/3kHz)=SA PSD(dBm/30kHz)+ RB factor(dB)


Power Spectral Density NVNT ANT1 802 11b 2412





Power Spectral Density NVNT ANT1 802 11b 2437





Power Spectral Density NVNT ANT1 802 11b 2462





Power Spectral Density NVNT_ANT1_802_11g_2437





Power Spectral Density NVNT ANT1 802 11n(HT20) 2412



Power Spectral Density NVNT ANT1 802 11n(HT20) 2462



Power Spectral Density NVNT ANT1 802 11n(HT40) 2437



8. Bandwidth

8.1. Test limits

Please refer RSS-247 & FCC PART 15.247

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.


8.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

a) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.



b) The test receiver set RBW = 100kHz, VBW $\geq$ 3*RBW =300kHz, Peak Detector, Sweep time set auto, detail see the test plot.



8.3. Test Setup







8.4. Test Results



Condition	Antenna	Modulation	Frequency (MHz)	-6dB BW(MHz)	limit(kHz)	Result
NVNT	ANT1	802.11b	2412.00	8.21	500	Pass
NVNT	ANT1	802.11b	2437.00	8.21	500	Pass
NVNT	ANT1	802.11b	2462.00	8.21	500	Pass
NVNT	ANT1	802.11g	2412.00	16.40	500	Pass
NVNT	ANT1	802.11g	2437.00	16.39	500	Pass
NVNT	ANT1	802.11g	2462.00	16.32	500	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	17.70	500	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	17.53	500	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	17.58	500	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	35.74	500	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	35.87	500	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	35.83	500	Pass




















Condition	Antenna	Modulation	Frequency (MHz)	99%%BW(MHz)
NVNT	ANT1	802.11b	2412.00	12.777
NVNT	ANT1	802.11b	2437.00	12.760
NVNT	ANT1	802.11b	2462.00	12.744
NVNT	ANT1	802.11g	2412.00	17.682
NVNT	ANT1	802.11g	2437.00	18.075
NVNT	ANT1	802.11g	2462.00	17.944
NVNT	ANT1	802.11n(HT20)	2412.00	18.410
NVNT	ANT1	802.11n(HT20)	2437.00	18.940
NVNT	ANT1	802.11n(HT20)	2462.00	18.871
NVNT	ANT1	802.11n(HT40)	2422.00	36.780
NVNT	ANT1	802.11n(HT40)	2437.00	37.019
NVNT	ANT1	802.11n(HT40)	2452.00	36.929




99% Occupied Bandwidth NVNT_ANT1_802_11b_2462





99% Occupied Bandwidth NVNT_ANT1_802_11g_2437





99% Occupied Bandwidth NVNT_ANT1_802_11n(HT20)_2412




99% Occupied Bandwidth_NVNT_ANT1_802_11n(HT20)_2462





9. Band Edge Test

9.1. Block Diagram of Test Setup



9.2. Test Limit

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Please refer RSS-GEN & FCC PART 15.247

9.3. Test Procedure

Refer to ANSI C 63.10, Clause 6.10.

All restriction band and non- restriction band have been tested, only worse case is reported.

Details see the KDB558074 D01 Meas Guidance v05r02

1. Put the EUT on a 1.5m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission
2. Check the spurious emissions out of band.
3. RBW 1MHz, VBW 3MHz, peak detector for peak value, RBW 1MHz, VBW 10Hz, RMS detector for AV value.

9.4. Test Results

Test Date : 2025.09.30					Temperature : 26℃			
Test Engineer : Jensen Wang					Humidity : 54%			
Test Results : PASS								
Frequency Range : 2310MHz~2410MHz								
Test Mode : IEEE 802.11b TX 2412MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	58.00	-20.45	37.55	74.00	-36.45	Peak
2	2390	H	--	-20.45	37.55	54.00	-16.45	Avg
3	2400	H	60.94	-20.41	40.53	74.00	-33.47	Peak
4	2400	H	--	-20.41	40.53	54.00	-13.47	Avg
1	2390	V	58.24	-20.45	37.79	74.00	-36.21	Peak
2	2390	V	--	-20.45	37.79	54.00	-16.21	Avg
3	2400	V	63.24	-20.41	42.83	74.00	-31.17	Peak
4	2400	V	--	-20.41	42.83	54.00	-11.17	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : IEEE 802.11b TX 2462MHz								
1	2483.5	H	62.63	-20.15	42.48	74.00	-31.52	Peak
2	2483.5	H	--	-20.15	42.48	54.00	-11.52	Avg
1	2483.5	V	66.19	-20.15	46.04	74.00	-27.96	Peak
2	2483.5	V	--	-20.15	46.04	54.00	-7.96	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

Frequency Range : 2310MHz~2410MHz								
Test Mode : IEEE 802.11g TX 2412MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	57.42	-20.45	36.97	74.00	-37.03	Peak
2	2390	H	--	-20.45	36.97	54.00	-17.03	Avg
3	2400	H	63.90	-20.41	43.49	74.00	-30.51	Peak
4	2400	H	--	-20.41	43.49	54.00	-10.51	Avg
1	2390	V	60.56	-20.45	40.11	74.00	-33.89	Peak
2	2390	V	--	-20.45	40.11	54.00	-13.89	Avg
3	2400	V	63.78	-20.41	43.37	74.00	-30.63	Peak
4	2400	V	--	-20.41	43.37	54.00	-10.63	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : IEEE 802.11g TX 2462MHz								
1	2483.5	H	61.91	-20.15	41.76	74.00	-32.24	Peak
2	2483.5	H	--	-20.15	41.76	54.00	-12.24	Avg
1	2483.5	V	63.03	-20.15	42.88	74.00	-31.12	Peak
2	2483.5	V	--	-20.15	42.88	54.00	-11.12	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

Frequency Range : 2310MHz~2410MHz								
Test Mode : IEEE 802.11n/HT20 TX 2412MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	58.28	-20.45	37.83	74.00	-36.17	Peak
2	2390	H	--	-20.45	37.83	54.00	-16.17	Avg
3	2400	H	63.48	-20.41	43.07	74.00	-30.93	Peak
4	2400	H	--	-20.41	43.07	54.00	-10.93	Avg
1	2390	V	61.11	-20.45	40.66	74.00	-33.34	Peak
2	2390	V	--	-20.45	40.66	54.00	-13.34	Avg
3	2400	V	62.71	-20.41	42.30	74.00	-31.70	Peak
4	2400	V	--	-20.41	42.30	54.00	-11.70	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : IEEE 802.11n/HT20 TX 2462MHz								
1	2483.5	H	60.82	-20.15	40.67	74.00	-33.33	Peak
2	2483.5	H	--	-20.15	40.67	54.00	-13.33	Avg
1	2483.5	V	64.53	-20.15	44.38	74.00	-29.62	Peak
2	2483.5	V	--	-20.15	44.38	54.00	-9.62	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

Frequency Range : 2310MHz~2410MHz								
Test Mode : IEEE 802.11n/HT40 TX 2422MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	58.17	-20.45	37.72	74.00	-36.28	Peak
2	2390	H	--	-20.45	37.72	54.00	-16.28	Avg
3	2400	H	61.44	-20.41	41.03	74.00	-32.97	Peak
4	2400	H	--	-20.41	41.03	54.00	-12.97	Avg
1	2390	V	61.60	-20.45	41.15	74.00	-32.85	Peak
2	2390	V	--	-20.45	41.15	54.00	-12.85	Avg
3	2400	V	61.90	-20.41	41.49	74.00	-32.51	Peak
4	2400	V	--	-20.41	41.49	54.00	-12.51	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : IEEE 802.11n/HT40 TX 2452MHz								
1	2483.5	H	62.58	-20.15	42.43	74.00	-31.57	Peak
2	2483.5	H	--	-20.15	42.43	54.00	-11.57	Avg
1	2483.5	V	65.47	-20.15	45.32	74.00	-28.68	Peak
2	2483.5	V	--	-20.15	45.32	54.00	-8.68	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor, Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

10. Frequency stability

10.1. Test limit


Please refer section RSS-Gen.

Regulation RSS-Gen If the frequency stability of the licence-exempt radio apparatus is not specified in the applicable RSS, the fundamental emissions of the radio apparatus should be kept within at least the central 80% of its permitted operating frequency band in order to minimize the possibility of out-of-band operation. In addition, its occupied bandwidth shall be entirely outside the restricted bands and the prohibited TV bands of 54-72 MHz, 76-88 MHz, 174-216 MHz, and 470-602 MHz, unless otherwise indicated.

10.2. Test Procedure

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.3. Test Setup



10.4. Test Results

Not Applicable.

11. Antenna Requirement

11.1. Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

11.2. Antenna Connected Construction

The antenna connector is unique antenna and no consideration of replacement. Please see EUT photo for details.

11.3. Results

The EUT antenna is internal antenna. It complies with the standard requirement.

12. Photos of test setup

Reference to the **appendix I Test Setup Photo** for details.

13. Photos of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

----- END OF REPORT-----