



H.B. Compliance Solutions

RF Exposure MPE Report

For the

Aether RF LLC

KM100A

January 30, 2026

Prepared for:

Aether RF LLC

6020 N. 55th Avenue

Glendale, AZ 85301

Prepared By:

H.B. Compliance Solutions

5005 S. Ash Avenue, Suite # A-10

Tempe, Arizona 85282

Reviewed By:

A handwritten signature in black ink, appearing to read 'Hoosamuddin Bandukwala'.

Hoosamuddin Bandukwala



Cert # ATL-0062-E

1. Equipment Overview

Product Name:	KM100A
Model(s) Tested:	-
FCC ID:	2BGQ6KM100A
Supply Voltage Input:	Primary Power: 16-24 VAC/VDC
Frequency Range:	902-928 MHz
No. of Channels:	200 / 50 Channels
Type(s) of Modulation:	OQPSK
Range of Operation Power:	0.973W
Emission Designator:	N/A
Channel Spacing(s)	128 Khz (200 Channel) & 512kHz (50 Channel)
Test Item:	Pre-Production
Type of Equipment:	Mobile
Antenna Requirement (§15.203) :	Type of Antenna: External Whip Antenna Gain of Antenna: 2.7dBi
Environmental Test Conditions:	Temperature: 15-35°C Humidity: 30-60% Barometric Pressure: 860-1060 mbar
Modification to the EUT:	None

2. Applicable Standard

According to §1.1307 the criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter. Test Limits

Evaluated against exposure limits: General Use X or Controlled Use

Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	* 100	6
3.0–30	1842/f	4.89/f	* 900/f ²	6
30–300	61.4	0.163	1.0	6
300–1,500			f/300	6
1,500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	* 100	30
1.34–30	824/f	2.19/f	* 180/f ²	30
30–300	27.5	0.073	0.2	30
300–1,500			f/1500	30
1,500–100,000			1.0	30

f = frequency in MHz* = Plane-wave equivalent power density

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules.

The emissions should be within the limits at 300kHz in the above table. (Use 300kHz limits for 150kHz)

3. Test Results

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where,

S = power density (mW/cm²)

P = output power at the antenna terminal (mW)

G = gain of transmit antenna (numeric)

R = distance from transmitting antenna (cm)

For Transmitter

Maximum peak output power = 29.88 (dBm)

Maximum peak output power at antenna input terminal = 972.74 (mW)

Antenna gain (typical) = 2.7 (dBi)

Maximum antenna gain = 1.86 (numeric)

Prediction distance = 20 (cm)

Prediction frequency = 928 (MHz)

MPE limit for uncontrolled exposure at prediction frequency = 0.619 (mW/cm²)

Power density at prediction frequency = 0.35995 (mW/cm²)

To solve for the minimum mounting distance required;

$$R = \sqrt{PG/4\pi S}$$

$$R = \sqrt{0.972.74 \times 1.86 / 4\pi \times 0.35995} = \underline{20 \text{ cm}} \text{ (Based on continuous transmission)}$$

Therefore, at 20cm the spectral power density is less than **the 0.619 mW/cm²** limit for uncontrolled exposure.

END OF TEST REPORT