Product Name: Desktop server	**Report No:ITEZA2-202400184RF1**
Product Model: UT2, UT2A, UT2 Pro, UT2C, UT2 Max	**Security Classification: Open**
Version: V1.0	**Total Page:68**

TIRT Testing Report

Prepared By:	**Checked By:**	**Approved By:**	
Aaron Long	Stone Tang	Joky Wang	
Aaron Long	Stone Tang	Joky Wang	

FCC Radio Test Report

FCC ID: 2BGV2UT2

According to

47 CFR FCC Part 15, Subpart C(Section 15.247)

ANSI C63.10:2013

Applicant:	Unify Data Technology LLC
Address:	1013 Centre Road, Suite 403S.2Wilmington, DE 19805, County of New Castle
Manufacturer:	Beijing Zentreadi Intelligence Information Technology Co.,Ltd
Address:	Room1109, 10th Floor, Building A, No.2 Zhongguancun South Street, Haidian District, Beijing
Sample No:	1000035553
Product Name:	Desktop server
Brand Name:	N/A
Model No.:	UT2, UT2A, UT2 Pro, UT2C, UT2 Max
Test No.:	UT2

Date of Receipt:	2024/06/06
Date of Test:	2024/06/06~2024/06/27
Issued Date:	2024/06/30
Testing Lab:	TIRT

Note: This report shall not be reproduced except in full, without the written approval of Beijing TIRT Technology Service Co.,Ltd Shenzhen.Laboratory.
This document may be altered or revised by Beijing TIRT Technology Service Co.,Ltd Shenzhen. Laboratory.Personnel only, and shall be noted in the revision section of the document. The test results of this report relate only to the tested sample identified in this report.

Table of Contents

Page

REPORT ISSUED HISTORY 6

1 . SUMMARY OF TEST RESULTS 7

1.1 TEST FACILITY 8

1.2 MEASUREMENT UNCERTAINTY 8

1.3 TEST ENVIRONMENT CONDITIONS 9

2 . GENERAL INFORMATION 10

2.1 GENERAL DESCRIPTION OF EUT 10

2.2 DESCRIPTION OF TEST MODES 11

2.3 PARAMETERS OF TEST SOFTWARE 12

2.4. ACCESSORIES OF DEVICE (EUT) 12

2.5 BLOCKDIAGRAMSHOWINGTHECONFIGURATIONOFSYSTEMTESTED 12

2.6 SUPPORT UNITS 12

3 .AC POWER LINE CONDUCTED EMISSIONS 13

3.1 LIMIT 13

3.2 TEST PROCEDURE 13

3.3 DEVIATIONFROMTESTSTANDARD 13

3.4 TESTSETUP 14

3.5 EUT OPERATING CONDITIONS 14

3.6 TEST RESULTS 14

4 . RADIATED EMISSIONS 15

4.1 LIMIT 15

4.2 TEST PROCEDURE 16

4.3 DEVIATIONFROMTESTSTANDARD 17

4.4 TESTSETUP 17

4.5 EUT OPERATING CONDITIONS 19

4.6 TEST RESULT- 9KHZ TO 30MHZ 19

4.7 TEST RESULT- 30MHZ TO 1000MHZ 19

4.8 TEST RESULT- ABOVE 1000MHZ 19

5 .BANDWIDTH 20

5.1 LIMIT 20

5.2 TEST PROCEDURE 20

5.3 DEVIATION FROM STANDARD 20

5.4 TEST SETUP 20

5.5 EUT OPERATION CONDITIONS 20

Table of Contents

Page

5.6 TESTRESULTS 20

6 .MAXIMUM OUTPUT POWER 21

6.1 LIMIT 21

6.2 TEST PROCEDURE 21

6.3 DEVIATION FROM STANDARD 21

6.4 TEST SETUP 21

6.5 EUT OPERATION CONDITIONS 21

6.6 TESTRESULTS 21

7 .CONDUCTED SPURIOUS EMISSION 22

7.1 LIMIT 22

7.2 TEST PROCEDURE 22

7.3 DEVIATION FROM STANDARD 22

7.4 TEST SETUP 22

7.5 EUT OPERATION CONDITIONS 22

7.6 TEST RESULTS 22

8 .POWER SPECTRAL DENSITY 23

8.1 LIMIT 23

8.2 TEST PROCEDURE 23

8.3 DEVIATION FROM STANDARD 23

8.4 TEST SETUP 23

8.5 EUT OPERATION CONDITIONS 23

8.6 TEST RESULTS 23

9. ANTENNA REQUIREMENT 24

9.1STANDARD REQUIREMENT 24

9.2ANTENNA CONNECTED CONSTRUCTION 24

9.3RESULTS 24

10. MEASUREMENT INSTRUMENTS LIST 25

11. PHOTOS OF TEST SETUP 26

12. PHOTOS OF EUT 28

APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS 36

APPENDIX B - RADIATED EMISSION -9 KHZ TO 30 MHZ 38

APPENDIX C - RADIATED EMISSION-30 MHZ TO 1000 MHZ 39

APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ 41

Table of Contents

Page

APPENDIX E - BANDWIDTH	43
APPENDIX F - MAXIMUM OUTPUT POWER	49
APPENDIX G - CONDUCTED SPURIOUS EMISSION	52
APPENDIX H- POWER SPECTRAL DENSITY	63
APPENDIX I- DUTY CYCLE	66

REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
ITEZA2-202400184RF1	V1.0	Original Report.	2024.06.30	Valid

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC CFR Title 47, Part 15, Subpart C				
Standard(s) Section	**Test Item**	**Test Result**	**Judgment**	**Remark**
15.207	AC Power Line Conducted Emissions	APPENDIX A	PASS	------
15.247(d) 15.205(a) 15.209(a)	Radiated Emissions	APPENDIX B APPENDIX C APPENDIX D	PASS	------
15.247(a)(2)	Bandwidth	APPENDIX E	PASS	------
15.247(b)(3)	Maximum Output Power	APPENDIX F	PASS	------
15.247(d)	Conducted Spurious Emission	APPENDIX G	PASS	------
15.247(e)	Power Spectral Density	APPENDIX H	PASS	------
15.203	Antenna Requirement	------	PASS	Note(2)

Note:

(1) “N/A” denotes test is not applicable to this device.

(2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

1.1 TEST FACILITY

Company:	Beijing TIRT Technology Service Co.,Ltd Shenzhen
Address:	104 Building C, Xinmingsheng Industrial Park No.132, Zhangge Old Village East Zone, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, Guangdong, P. R. China
CNAS Registration Number:	CNAS L14158
A2LA Registration Number:	6049.01
FCC Accredited Lab.Designation Number:	CN1366
FCC Test Firm Registration Number:	820690
Telephone:	+86-0755-27087573

1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))
The BTL measurement uncertainty as below table:

Uncertainty	
Parameter	Uncertainty
Occupied Channel Bandwidth	±142.12 KHz
RF power conducted	±0.74 dB
RF power radiated	±3.25dB
Spurious emissions, conducted	±1.78dB
Spurious emissions, radiated (30MHz～1GHz)	±4.6dB
Spurious emissions, radiated (1GHz ~ 18GHz)	±4.9dB
Conduction Emissions(150kHz~30MHz)	±3.1 dB
Humidity	±4.6%
Temprature	±0.7°C
Time	±1.25%

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
AC Power Line Conducted Emissions	24.5°C	50%	DC 12V from adapter	Aaron Long
Radiated Emissions-9 kHz to 30 MHz	24.5°C	50%	DC 3.85V from battery or DC 12V from adapter	Aaron Long
Radiated Emissions-30 MHz to 1000 MHz	24°C	53%	DC 3.85V from battery or DC 12V from adapter	Aaron Long
Radiated Emissions-Above 1000 MHz	26°C	53%	DC 3.85V from battery or DC 12V from adapter	Aaron Long
Bandwidth	25°C	56%	DC 3.85V from battery or DC 12V from adapter	Aaron Long
Maximum Output Power	24°C	54%	AC 120V/60Hz from Adapter	Aaron Long
ConductedSpurious Emission	25°C	62%	DC 3.85V from battery or DC 12V from adapter	Aaron Long
Power Spectral Density	26°C	60%	DC 3.85V from battery or DC 12V from adapter	Aaron Long

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Desktop server
Brand Name	N/A
Test Model	UT2
Series Model	UT2, UT2A, UT2 Pro, UT2C, UT2 Max
Model Difference(s)	There is no difference except the name of the model
Software Version	V1.0
Hardware Version	V1.0
Power Rating	DC 3.85V from battery or DC 12V from adapter
Operation Frequency	2402 MHz ~ 2480 MHz
Modulation Type	GFSK
Bit Rate of Transmitter	1Mbps, 2Mbps
Max. Output Power	2Mbps: -4.00dBm (0.000398W)

Note:

1. For a more detailed features description, please refer to the manufacturer’s specifications or the user's manual.

2.2 DESCRIPTION OF TEST MODES

The test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
GFSK (1M/2M)	Low :CH00	2402
	Middle: CH19	2440
	High: CH39	2480

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

Table for Filed Antenna:

Ant.	Manufactured	Model Name	Antenna Type	Connector	Gain (dBi)
1	Beijing Maxfatel Technology	UT2	FPC	N/A	0.14

Note: Antenna information is provided by applicant.
The antenna is for testing purposes only.

2.3 PARAMETERS OF TEST SOFTWARE

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test Software Version	Debug Engineering mode		
Frequency (MHz)	2402	2440	2480
1Mbps, 2 Mbps	default	default	default

2.4. ACCESSORIES OF DEVICE (EUT)

Accessories	Gallium Nitride Quick Charger
Manufacturer	/
Model	RY-C33
Ratings	Input: 100-240V~ 50/60Hz 0.8A
	Output: 5V⎓3A/9V⎓3A/12V⎓2.75A/15V⎓2.2A/20V⎓1.65A

2.5 BLOCKDIAGRAMSHOWINGTHECONFIGURATIONOFSYSTEMTESTED

EUT

2.6 SUPPORT UNITS

No.	Description	Manufacturer	Model	Note
1	N/A	N/A	N/A	N/A

3.AC POWER LINE CONDUCTED EMISSIONS

3.1LIMIT

Frequency of Emission (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 -0.5	66 to 56*	56 to 46*
0.5-5.0	56	6
5.0 -30.0	60	50

Note:

(1) The tighter limit applies at the band edges.
(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

3.2TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipmentpowered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the groundplane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

The following table is the setting of the receiver:

Receiver Parameters	Setting
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.3DEVIATIONFROMTESTSTANDARD

No deviation.

3.4TESTSETUP



The LISN edge is arranged parallel to the edge of the test table
The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT

3.5EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it).The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.6 TEST RESULTS

Please refer to the APPENDIX-A

4. RADIATED EMISSIONS

4.1LIMIT

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a)limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m at 3 m)	
	Peak	Average
Above 1000	74	54

Note:

(1) The limit for radiated test was performed according to FCC CFR Title 47, Part 15, Subpart C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2TEST PROCEDURE

a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn‘t perform. (below 1GHz)
h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn‘t perform. (above 1GHz)
i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

The following table is the setting of the receiver:

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~150 kHz for RBW 200 Hz
Start ~ Stop Frequency	0.15 MHz~30 MHz for RBW 9 kHz
Start ~ Stop Frequency	30 MHz~1000 MHz for RBW 100 kHz

Spectrum Parameters	Setting
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for PK value 1MHz / 1/THz for AVG value

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~90 kHz for PK/AVG detector
Start ~ Stop Frequency	90 kHz~110 kHz for QP detector
Start ~ Stop Frequency	110 kHz~490 kHz for PK/AVG detector
Start ~ Stop Frequency	490 kHz~30 MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector
Start ~ Stop Frequency	1 GHz~26.5GHz for PK/AVG detector

4.3DEVIATIONFROMTESTSTANDARD

No deviation.

4.4TESTSETUP

9 kHz to 30 MHz



30 MHz to 1 GHz



Above 1 GHz


Absorbers
3 m
1-4 m
EUT
1.5 m
1 m
Absorbers
0.3 m
Ground Plane
Receiver
Amp.

4.5EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.6 TEST RESULT- 9kHz TO 30MHz

Please refer to the APPENDIX-B

Remark:

(1) Distance extrapolation factor = 40 log (specific distance / test distance) (dB).
(2) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.7 TEST RESULT- 30MHz TO 1000MHz

Please refer to the APPENDIX-C

4.8 TEST RESULT- ABOVE 1000MHz

Please refer to the APPENDIX-D

Remark:

(1) No limit:This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5.BANDWIDTH

5.1LIMIT

Section	Test Item	Limit
FCC 15.247(a)(2)	6dB Bandwidth	>= 500 kHz
	99% Emission Bandwidth	-

5.2TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

b. The following table is the setting of the spectrum analyzer:

For 6 dB Bandwidth:

Spectrum Parameters	Setting
Span Frequency	> Measurement Bandwidth
RBW	100 kHz
VBW	300kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For 99% Emission Bandwidth:

Spectrum Parameters	Setting
Span Frequency	Between 1.5 times and 5.0 times the OBW
RBW	30 kHz
VBW	100kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.3DEVIATION FROM STANDARD

No deviation.

5.4TEST SETUP



5.5EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.6TESTRESULTS

Please refer to the APPENDIX-E

6.MAXIMUM OUTPUT POWER

6.1LIMIT

Section	Test Item	Limit
FCC 15.247(b)(3)	Maximum Output Power	1.0000 watt or 30.00dBm

6.2TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

b. The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span Frequency	≥ 3×RBW
RBW	3 MHz
VBW	3 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.3DEVIATION FROM STANDARD

No deviation.

6.4TEST SETUP



6.5EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.6TESTRESULTS

Please refer to the APPENDIX-F

7.CONDUCTED SPURIOUS EMISSION

7.1LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

7.2TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Start Frequency	30 MHz
Stop Frequency	26.5 GHz
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.3DEVIATION FROM STANDARD

No deviation.

7.4TEST SETUP

7.5EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.6 TEST RESULTS

Please refer to the APPENDIX-G

8.POWER SPECTRAL DENSITY

8.1LIMIT

Section	Test Item	Limit
FCC 15.247(e)	Power Spectral Density	8 dBm (in any 3 kHz)

8.2TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

b. The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span Frequency	2 MHz (1 Mbps) / 4 MHz (2 Mbps)
RBW	3 kHz
VBW	10 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.3DEVIATION FROM STANDARD

No deviation.

8.4TEST SETUP



8.5EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

8.6 TEST RESULTS

Please refer to the APPENDIX-H

9. ANTENNA REQUIREMENT

9.1STANDARD REQUIREMENT

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2ANTENNA CONNECTED CONSTRUCTION

The antenna connector is unique antenna and no consideration of replacement. Please see EUT photo for details.

9.3RESULTS

The EUT antenna is FPC antenna. It complies with the standard requirement.

10. MEASUREMENT INSTRUMENTS LIST

Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Receiver	Rohde&Schwarz	ESIB 40	YH-TIRT-SAC-966-20220911	2024/01/05	2025/01/04
Integral Antenna	Schwarzbeck	VULB 9163	01314	2022.12.11	2024.12.10
Integral Antenna	Rohde&Schwarz	HF907	RSM2991424	2022.12.11	2024.12.10
Preamplifier	Emtrace	RP01A	'02017	2024/01/05	2025/01/04
Preamplifier	Schwarzbeck	BBV9744	00143	2024/01/05	2025/01/04
Loop Antenna	ZHINAN	ZN30900A	12024	2024/01/05	2025/01/04
Horn Antenna	Schwarzbeck	BBHA9170	00956	2024/01/05	2025/01/04
RF Cable	/	LMR400UF-NMNM-7.0M	/	2024/01/05	2025/01/04
RF Cable	/	SFT2050PUR-NMNM-7.0M	/	2024/01/05	2025/01/04
EMI Receiver	Rohde&Schwarz	ESR7	1316.3003K07-102611-mk	2023/11/02	2024/11/01
LISN	Rohde&Schwarz	ENV216	3560.655.12-102915-Bp	2023/11/02	2024/11/01
RF Cable	\	SFT2050PUR-NMNM-2.0M	\	2024/01/05	2025/01/04
Spectrum analyzer	ROHDE&SCHWARZ	FSU26	200732	2024/01/05	2025/01/04
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	101722	2024/01/05	2025/01/04
Filter	HEWLETT PACKARD	JS0806-F	19K8060209	2024/01/05	2025/01/04

11. PHOTOS OF TEST SETUP

AC Power Line Conducted Emissions Test Photos



Radiated Emissions Test Photos

30 MHz to 1 GHz



Radiated Emissions Test Photos

Above 1 GHz



Conducted Test Photos

12. PHOTOS OF EUT




















CON6401
D22
U46
M10
Y5