

RF Test Report

For

Applicant name: Shenzhen Changxinghui Technology Co., Ltd
Address: Room1003, Building C, Lianjian Industrial Park, Huarong Road, Dalang, Longhua, Shenzhen, China
EUT name: GAMING POWER BANK
Brand name: N/A
Model number: XH001S
Series model number: Refer to section 2
FCC ID: 2BH4Z-XH001S

Issued By

Company name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China
Report number: BTF251105R00102
Test standards: 47 CFR Part 1 Subpart I Section 1.1310
Test conclusion: Pass
Date of sample receipt: 2025-11-05
Test date: 2025-11-06 to 2025-11-12
Date of issue: 2025-11-27

Prepared by:



Chris Liu / Project engineer

Approved by:



Ryan.CJ/EMC manager

Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd.. All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue date	Revisions content
R_V0	2025-11-27	Original

Table of Contents

1 Introduction	4
1.1 Laboratory Location	4
1.2 Laboratory Facility	4
1.3 Announcement	4
2 Product Information	5
2.1 Application Information	5
2.2 Manufacturer Information	5
2.3 Factory Information	5
2.4 General Description of Equipment under Test (EUT)	5
2.5 Technical Information	5
3 Test Equipment List	6
4 Applied Reference Documents	6
5 Test Auxiliary Equipment	6
6 Test Requirement	7
7 Test Settings	8
8 Exposure Assessment	9
8.1 E-Field Strength Test Date	9
8.2 H-Field Strength Test Date:	10
8.3 Estimated Model	12
8.4 Comparison of evaluation data and test data	14
9 Test Setup Photos	15

1 Introduction

1.1 Laboratory Location

Test location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China
Description:	All measurement facilities used to collect the measurement data are located at Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China
Phone number:	+86-0755-23146130
Fax number:	+86-0755-23146130

1.2 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1409**
BTF Testing Lab (Shenzhen) Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The test firm Registration No. is 695374.
- **CNAS - Registration No.: CNAS L17568**
BTF Testing Lab (Shenzhen) Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L17568.
- **A2LA - Registration No.: 6660.01**
BTF Testing Lab (Shenzhen) Co., Ltd. is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

1.3 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.
- (7) All entrusted information in this report is provided by the client and has been confirmed through consultation with the client; The testing items for this report have been discussed and confirmed with the client, and our company is only responsible for the content reflected in the report.

2 Product Information

2.1 Application Information

Company name:	Shenzhen Changxinghui Technology Co., Ltd
Address:	Room1003, Building C, Lianjian Industrial Park, Huarong Road, Dalang, Longhua, Shenzhen, China

2.2 Manufacturer Information

Company name:	Shenzhen Changxinghui Technology Co., Ltd
Address:	Room1003, Building C, Lianjian Industrial Park, Huarong Road, Dalang, Longhua, Shenzhen, China

2.3 Factory Information

Company name:	Shenzhen Changxinghui Technology Co., Ltd
Address:	Room1003, Building C, Lianjian Industrial Park, Huarong Road, Dalang, Longhua, Shenzhen, China

2.4 General Description of Equipment under Test (EUT)

EUT name	GAMING POWER BANK
Under test model name	XH001S
Series model name	XH001, Q8, Q8-A, SB - 501, B10
Description of model name differentiation	Only the model screen printing is different, everything else is the same
Hardware Version	N/A
Software Version	N/A
Rating:	Battery DC 3.7V 5000mAh 18.5Wh Type-C Input: 5.0V $\Rightarrow$ 3.1A, 9.0V $\Rightarrow$ 2.22A, 12.0V $\Rightarrow$ 1.67A MAX 20W Type-C Output: 5.0V $\Rightarrow$ 2.4A, 9.0V $\Rightarrow$ 2.22A, 12.0V $\Rightarrow$ 1.67A MAX 20W Wireless Transmitting: 15W MAX Lithium Battery Capacity: 5000mAh/3.7V/18.5Wh Rated Capacity: 3300mAh Total Output:5V $\Rightarrow$ 3A

2.5 Technical Information

Operation frequency:	110.677 kHz - 203.683 kHz
Modulation technology:	ASK
Antenna type:	Coil Antenna

3 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Electric and Magnetic Field Analyzer	Narda	EHP-200A	180ZX11001	2025/11/16	2026/11/15

4 Applied Reference Documents

Identity	Document Title
47 CFR Part 1 Subpart I Section 1.1310	Radio frequency radiation exposure limits.

5 Test Auxiliary Equipment

Description	Manufacturer	Model	Serial No.	Length	Description
Phone	HONOR	PGT-AN10	/	/	/

6 Test Requirement

KDB 680106 D01 RF Exposure Wireless Charging App v03

According to the item 5.2 of KDB 680106 D01v03:

Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.

a) Power transfer frequency is less than 1 MHz.

Yes, the device operate in the frequency range from 110-205KHz

b) Output power from each primary coil is less than or equal to 15 watts.

YES, the maximum output power of the primary coil is 5W.

c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils

Yes, the transfer system includes only single primary and secondary coils

d) Client device is placed directly in contact with the transmitter.

Yes, client device is placed directly in contact with the transmitter.

e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

Yes, the EUT is a Wireless Charging mobile.

f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Yes, the EUT field strength levels are 50% X MPE limit.


TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)


Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

7 Test Settings

Test Setup





Note1: The sensitive elements are located approximately 8mm below the exxternal surface

Note2: Measurements should be made from all sides and the top of the primary/client pair, with the 0/2/4/6/8/10/12/14/16/18/20cm measured from the center of the probe(s) to the edge of the device.

The RF exposure test was performed in anechoic chamber.

The measurement probe was placed at test distance (0/2/4/6/8/10/12/14/16/18/20cm) which is between the edge of the charger and the geometric center of probe.

The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E, F) were completed.

The EUT was measured according to the dictates of KDB 680106 D01 v04.

8 Exposure Assessment

8.1 E-Field Strength Test Date

➤ E-Field Strength at 2/4/6/8/10/12/14/16/18/20cm from the edges surrounding the EUT:

Charging Battery Level	Measured E-Field Strength Values (V/m)							FCC E-Field Strength Limits (V/m)
	Measured Distance (cm)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position F	
99%	2	4.4335	4.8639	4.4294	4.5587	7.4652	7.3266	614
50%	2	4.3235	5.1234	4.7547	4.7649	7.8581	7.4976	614
1%	2	4.6347	5.1258	4.6243	4.4574	7.6877	7.6230	614
99%	4	4.0232	4.5476	4.1360	4.2211	7.2854	6.9464	614
50%	4	3.9119	4.7458	4.3097	4.2497	7.4937	7.1185	614
1%	4	4.2242	4.8795	4.3956	4.2531	7.5900	7.2887	614
99%	6	3.6633	4.4067	3.9508	3.9498	7.1465	6.7799	614
50%	6	3.7861	4.5450	4.1064	3.9964	7.3900	6.9510	614
1%	6	4.0124	4.7062	4.2155	4.1153	7.5211	7.1781	614
99%	8	3.5164	4.3570	3.8294	3.8288	7.0621	6.6660	614
50%	8	3.7044	4.4689	3.9799	3.9418	7.2868	6.8546	614
1%	8	3.8935	4.6209	4.0925	4.0543	7.5127	7.0819	614
99%	10	2.7624	3.7148	3.3004	3.2643	6.0806	5.7240	614
50%	10	2.9133	3.8667	3.4142	3.3759	6.3074	5.9113	614
1%	10	3.0638	3.9793	3.5276	3.4888	6.4964	6.1006	614
99%	12	2.0837	3.2264	2.8488	2.8100	5.2508	4.9325	614
50%	12	2.1968	3.3020	2.9238	2.8866	5.4395	5.0839	614
1%	12	2.3480	3.4155	3.0380	3.0000	5.5918	5.2347	614
99%	14	1.4807	2.7735	2.4335	2.4339	4.5352	4.2169	614
50%	14	1.5935	2.8484	2.5086	2.5093	4.6870	4.3669	614
1%	14	1.7078	2.9246	2.5847	2.5857	4.8371	4.5169	614
99%	16	0.9900	2.3592	2.0950	2.0939	3.9333	3.6496	614
50%	16	1.0655	2.4343	2.1707	2.1336	4.0446	3.7633	614
1%	16	1.1790	2.5095	2.2452	2.2075	4.1599	3.8755	614
99%	18	0.5390	2.0199	1.7943	1.7928	3.4052	3.1227	614
50%	18	0.6512	2.0956	1.8685	1.8314	3.4800	3.2345	614
1%	18	0.7261	2.1703	1.9068	1.9057	3.5927	3.3111	614
99%	20	0.1616	1.7561	1.5290	1.5290	2.9523	2.6697	614
50%	20	0.2368	1.7917	1.6036	1.5672	3.0270	2.7826	614
1%	20	0.3121	1.8697	1.6425	1.5941	3.1039	2.8596	614

Note: V/m= A/m *377

8.2 H-Field Strength Test Date:

➤ H-Field Strength at 2/4/6 8/10/12/14/16/18/20cm from the edges surrounding the EUT

Charging Battery Level	Measured E-Field Strength Values (V/m)								FCC H-Field Strength Limits (A/m)
	Measured Distance (cm)	Unit	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position F	
99%	2	uT	0.0404	0.0436	0.0342	0.0295	0.0616	0.0695	--
99%	2	A/m	0.0323	0.0349	0.0274	0.0236	0.0493	0.0556	1.63
50%	2	uT	0.0470	0.0392	0.0329	0.0308	0.0633	0.0736	--
50%	2	A/m	0.0376	0.0314	0.0263	0.0246	0.0506	0.0589	1.63
1%	2	uT	0.0429	0.0425	0.0333	0.0363	0.0587	0.0692	--
1%	2	A/m	0.0344	0.0340	0.0266	0.0290	0.0470	0.0553	1.63
99%	4	uT	0.0298	0.0264	0.0222	0.0259	0.0375	0.0427	--
99%	4	A/m	0.0238	0.0211	0.0177	0.0207	0.0300	0.0342	1.63
50%	4	uT	0.0348	0.0250	0.0236	0.0258	0.0371	0.0458	--
50%	4	A/m	0.0278	0.0200	0.0189	0.0206	0.0297	0.0367	1.63
1%	4	uT	0.0358	0.0296	0.0271	0.0255	0.0349	0.0459	--
1%	4	A/m	0.0286	0.0237	0.0217	0.0204	0.0279	0.0367	1.63
99%	6	uT	0.0248	0.0222	0.0181	0.0164	0.0342	0.0430	--
99%	6	A/m	0.0198	0.0178	0.0145	0.0131	0.0274	0.0344	1.63
50%	6	uT	0.0258	0.0219	0.0192	0.0190	0.0344	0.0450	--
50%	6	A/m	0.0207	0.0176	0.0154	0.0152	0.0275	0.0360	1.63
1%	6	uT	0.0250	0.0218	0.0201	0.0228	0.0334	0.0427	--
1%	6	A/m	0.0200	0.0175	0.0161	0.0183	0.0267	0.0342	1.63
99%	8	uT	0.0227	0.0174	0.0147	0.0162	0.0274	0.0267	--
99%	8	A/m	0.0182	0.0139	0.0117	0.0130	0.0219	0.0213	1.63
50%	8	uT	0.0233	0.0179	0.0147	0.0165	0.0284	0.0264	--
50%	8	A/m	0.0186	0.0143	0.0118	0.0132	0.0228	0.0211	1.63
1%	8	uT	0.0232	0.0187	0.0151	0.0166	0.0293	0.0279	--
1%	8	A/m	0.0186	0.0150	0.0121	0.0133	0.0234	0.0223	1.63
99%	10	uT	0.0195	0.0150	0.0117	0.0127	0.0236	0.0230	--
99%	10	A/m	0.0156	0.0120	0.0093	0.0102	0.0189	0.0184	1.63
50%	10	uT	0.0213	0.0166	0.0132	0.0138	0.0252	0.0235	--
50%	10	A/m	0.0170	0.0133	0.0106	0.0111	0.0202	0.0188	1.63
1%	10	uT	0.0206	0.0162	0.0133	0.0141	0.0257	0.0247	--

1%	10	A/m	0.0165	0.0129	0.0107	0.0112	0.0205	0.0198	1.63
99%	12	uT	0.0163	0.0126	0.0116	0.0116	0.0206	0.0200	--
99%	12	A/m	0.0130	0.0101	0.0093	0.0093	0.0164	0.0160	1.63
50%	12	uT	0.0181	0.0124	0.0118	0.0119	0.0217	0.0203	--
50%	12	A/m	0.0145	0.0099	0.0095	0.0095	0.0174	0.0162	1.63
1%	12	uT	0.0185	0.0145	0.0110	0.0109	0.0217	0.0217	--
1%	12	A/m	0.0148	0.0116	0.0088	0.0087	0.0174	0.0174	1.63
99%	14	uT	0.0149	0.0121	0.0096	0.0100	0.0171	0.0170	--
99%	14	A/m	0.0119	0.0097	0.0077	0.0080	0.0137	0.0136	1.63
50%	14	uT	0.0161	0.0106	0.0106	0.0096	0.0189	0.0180	--
50%	14	A/m	0.0129	0.0085	0.0085	0.0077	0.0151	0.0144	1.63
1%	14	uT	0.0149	0.0127	0.0115	0.0122	0.0174	0.0187	--
1%	14	A/m	0.0119	0.0102	0.0092	0.0098	0.0139	0.0150	1.63
99%	16	uT	0.0130	0.0089	0.0085	0.0082	0.0153	0.0148	--
99%	16	A/m	0.0104	0.0071	0.0068	0.0066	0.0123	0.0119	1.63
50%	16	uT	0.0132	0.0100	0.0091	0.0093	0.0167	0.0156	--
50%	16	A/m	0.0106	0.0080	0.0072	0.0074	0.0134	0.0125	1.63
1%	16	uT	0.0134	0.0090	0.0101	0.0096	0.0170	0.0155	--
1%	16	A/m	0.0107	0.0072	0.0081	0.0077	0.0136	0.0124	1.63
99%	18	uT	0.0117	0.0091	0.0070	0.0093	0.0128	0.0128	--
99%	18	A/m	0.0093	0.0073	0.0056	0.0074	0.0103	0.0102	1.63
50%	18	uT	0.0121	0.0080	0.0074	0.0074	0.0135	0.0134	--
50%	18	A/m	0.0097	0.0064	0.0059	0.0059	0.0108	0.0107	1.63
1%	18	uT	0.0121	0.0095	0.0090	0.0083	0.0146	0.0134	--
1%	18	A/m	0.0096	0.0076	0.0072	0.0067	0.0117	0.0107	1.63
99%	20	uT	0.0102	0.0064	0.0058	0.0085	0.0122	0.0118	--
99%	20	A/m	0.0082	0.0051	0.0047	0.0068	0.0098	0.0095	1.63
50%	20	uT	0.0093	0.0083	0.0073	0.0082	0.0129	0.0121	--
50%	20	A/m	0.0074	0.0067	0.0058	0.0066	0.0103	0.0097	1.63
1%	20	uT	0.0094	0.0081	0.0071	0.0071	0.0125	0.0112	--
1%	20	A/m	0.0075	0.0064	0.0057	0.0057	0.0100	0.0090	1.63

Note: A/m=uT/1.25

8.3 Estimated Model

According to the formula:

The formula for the magnetic field strength at a distance r from the coil is

$$H = I / (2\pi r) * \mu$$

H is A/m

I is the current intensity

μ is the permeability, and its value depends on the medium.

The other parameters are fixed, so H is inversely proportional to r .




Therefore, From the measurement H_6 we can estimate the values of H_4, H_2, H_0 :

$$H_4 = H_6 * r_6 / r_4$$

$$H_2 = H_6 * r_6 / r_2$$

$$H_0 = H_6 * r_6 / r_0$$

The values of “ r ” are shown in the following table:

A:Rear.1.165cm 	B:Left.1.652cm 
C:Front.6.318cm 	D:Right.1.711cm 
E:Top.0.095cm 	F:Bottom.1.593cm 

➤ **ABCDEF direction The actual distance(r) to the antenna coil:**

measured distance(cm)	Actual distance r to the antenna (cm)					
	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position F
0	1.165	1.652	6.318	1.711	0.095	1.593
2	3.165	3.652	8.318	3.711	2.095	3.593
4	5.165	5.652	10.318	5.711	4.095	5.593
6	7.165	7.652	12.318	7.711	6.095	7.593
8	9.165	9.652	14.318	9.711	8.095	9.593
10	11.165	11.652	16.318	11.711	10.095	11.593
12	13.165	13.652	18.318	13.711	12.095	13.593
14	15.165	15.652	20.318	15.711	14.095	15.593
16	17.165	17.652	22.318	17.711	16.095	17.593
18	19.165	19.652	24.318	19.711	18.095	19.593
20	21.165	21.652	26.318	21.711	20.095	21.593

Note: The phone is 16.21mm thick.

➤ **The result is calculated by the above formula:**

H-Field Strength at 0/2/4cm from the edges surrounding the EUT

Charging Battery Level	Measured E-Field Strength Values (V/m)								FCC H-Field Strength Limits (A/m)
	Measured Distance (cm)	Unit	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position F	
99%	0	A/m	0.1219	0.1092	0.0890	0.0806	0.1683	0.2117	1.63
50%	0	A/m	0.1271	0.1080	0.0945	0.0933	0.1692	0.2216	1.63
1%	0	A/m	0.1232	0.1073	0.0988	0.1124	0.1645	0.2101	1.63
99%	2	A/m	0.0449	0.0402	0.0328	0.0297	0.0620	0.0779	1.63
50%	2	A/m	0.0468	0.0398	0.0348	0.0344	0.0623	0.0816	1.63
1%	2	A/m	0.0453	0.0395	0.0364	0.0414	0.0605	0.0773	1.63
99%	4	A/m	0.0275	0.0246	0.0201	0.0182	0.0380	0.0477	1.63
50%	4	A/m	0.0287	0.0244	0.0213	0.0211	0.0382	0.0500	1.63
1%	4	A/m	0.0278	0.0242	0.0223	0.0254	0.0371	0.0474	1.63

8.4 Comparison of evaluation data and test data

➤ We compare the test value of 4cm/2cm with the estimated value:

Test Value									
Charging Battery Level	Measured E-Field Strength Values (V/m)								FCC H-Field Strength Limits (A/m)
	Measured Distance (cm)	Unit	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position F	
99%	2	A/m	0.0323	0.0349	0.0274	0.0236	0.0493	0.0556	1.63
50%	2	A/m	0.0376	0.0314	0.0263	0.0246	0.0506	0.0589	1.63
1%	2	A/m	0.0344	0.0340	0.0266	0.0290	0.0470	0.0553	1.63
99%	4	A/m	0.0238	0.0211	0.0177	0.0207	0.0300	0.0342	1.63
50%	4	A/m	0.0278	0.0200	0.0189	0.0206	0.0297	0.0367	1.63
1%	4	A/m	0.0286	0.0237	0.0217	0.0204	0.0279	0.0367	1.63
Estimated Value									
Charging Battery Level	Measured E-Field Strength Values (V/m)								FCC H-Field Strength Limits (A/m)
	Measured Distance (cm)	Unit	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position F	
99%	2	A/m	0.0449	0.0402	0.0328	0.0297	0.0620	0.0779	1.63
50%	2	A/m	0.0468	0.0398	0.0348	0.0344	0.0623	0.0816	1.63
1%	2	A/m	0.0453	0.0395	0.0364	0.0414	0.0605	0.0773	1.63
99%	4	A/m	0.0275	0.0246	0.0201	0.0182	0.0380	0.0477	1.63
50%	4	A/m	0.0287	0.0244	0.0213	0.0211	0.0382	0.0500	1.63
1%	4	A/m	0.0278	0.0242	0.0223	0.0254	0.0371	0.0474	1.63

➤ The corresponding deviation value is calculated:

Charging Battery Level	Deviation value								Limits
	Measured Distance (cm)	Unit	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position F	
99%	2	A/m	-27.94%	-13.32%	-16.49%	-20.41%	-20.51%	-28.60%	30%
50%	2	A/m	-19.57%	-21.03%	-24.37%	-28.27%	-18.72%	-27.84%	30%
1%	2	A/m	-24.24%	-13.89%	-26.72%	-29.91%	-22.40%	-28.43%	30%
99%	4	A/m	-13.27%	-14.31%	-11.60%	13.76%	-21.03%	-28.45%	30%
50%	4	A/m	-2.93%	-17.77%	-11.49%	-1.98%	-22.14%	-26.63%	30%
1%	4	A/m	3.01%	-2.30%	-2.69%	-19.57%	-24.70%	-22.47%	30%

➤ Conclusion:

A minimum safety distance of 0 cm to the antenna is required when the device is charging a smart phone for mobile exposure. The detected emissions are below the limitations according FCC KDB 680106.

The model was established with a 30% agreement, so it was considered to be approved.

The estimated test distances of 0cm are reliable.

9 Test Setup Photos



Side(C)



Side(A)




Side(B)



Side(D)



Top(E)



Bottom(F)



BTF Testing Lab (Shenzhen) Co., Ltd.

Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street,
Bao'an District, Shenzhen, Guangdong, China

www.btf-lab.com

--END OF REPORT--