FCC TEST REPORT
FCC ID:2BH62-FOBM26AC3P32

Report Number.....:	**ZHT-240516024E**
Date of Test.....:	May 16, 2024 to Aug. 13, 2024
Date of issue.....:	Aug. 13, 2024
Test Result.....:	PASS
Testing Laboratory.....:	**Guangdong Zhonghan Testing Technology Co., Ltd.**
Address .....:	Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Applicant's name .....:	**Chengdu Dianzhu New Energy Technology Co., Ltd**
Address .....:	1st Floor, No. 22th, XinMa Road, Wuhou District, ChengDu City, SiChuan Province
Manufacturer's name .....:	**Chengdu Dianzhu New Energy Technology Co., Ltd**
Address .....:	1st Floor, No. 22th, XinMa Road, Wuhou District, ChengDu City, SiChuan Province
Test specification:	
Standard.....:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Test procedure.....:	KDB558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10:2013
Non-standard test method .....:	N/A

This device described above has been tested by ZHT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZHT, this document may be altered or revised by ZHT, personal only, and shall be noted in the revision of the document.

Product name.....:	**Portable Mode 2 Charger**
Trademark .....:	EVSOW
Model/Type reference.....:	F-OBM26-AC-3P32, F-OBM26-AC-1P32, F-OBM26-AC-3P16, F-MBM26-AC-1P32, F-MBM26-AC-1P40, F-MBM26-AC-1P50, F-GBM26-AC-1P32, F-GBM26-AC-3P16, F-GBM26-AC-3P32, F-TSM26-AC-1P32, F-TSM26-AC-1P40, F-TSM26-AC-1P50
Model Difference.....:	F-OBM26-AC-3P32 is tested model, other models are derivative models .The models are identical in circuit, only different on the model names. So the test data of F-OBM26-AC-3P32 can represent the remaining models.
Ratings.....:	Input: 100 - 240 V~, 50 / 60 Hz, 32 A Output: 100 - 240 V~, 50 / 60 Hz, 16 / 32 A / Input: 400 V~, 50 / 60 Hz Output: 400 V~, 50 / 60 Hz, 16 / 32 A

Testing procedure and testing location:

Testing Laboratory.....:	**Guangdong Zhonghan Testing Technology Co., Ltd.**
Address.....:	Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Tested by (name + signature).....:	Leon Li
Reviewer (name + signature).....:	Baret Wu
Approved (name + signature).....:	Levi Lee

Table of Contents

Page

1. VERSION 5
2. SUMMARY OF TEST RESULTS 6
2.1 TEST FACILITY 7
2.2 MEASUREMENT UNCERTAINTY 7
3. GENERAL INFORMATION 8
3.1 GENERAL DESCRIPTION OF EUT 8
3.2 DESCRIPTION OF TEST MODES 9
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 10
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 10
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS 11
4. EMC EMISSION TEST 13
4.1 CONDUCTED EMISSION MEASUREMENT 13
4.1.1 POWER LINE CONDUCTED EMISSION Limits 13
4.1.2 TEST PROCEDURE 13
4.1.3 DEVIATION FROM TEST STANDARD 13
4.1.4 TEST SETUP 14
4.1.5 EUT OPERATING CONDITIONS 14
4.2 RADIATED EMISSION MEASUREMENT 17
4.2.1 RADIATED EMISSION LIMITS 17
4.2.2 TEST PROCEDURE 17
4.2.3 DEVIATION FROM TEST STANDARD 18
4.2.4 TEST SETUP 18
4.2.5 EUT OPERATING CONDITIONS 19
4.2.6 TEST RESULTS 19
5. RADIATED BAND EMISSIONMEASUREMENT 24
5.1 TEST REQUIREMENT: 24
5.2 TEST PROCEDURE 24
5.3 DEVIATION FROM TEST STANDARD 24
5.4 TEST SETUP 25
5.5 EUT OPERATING CONDITIONS 25
5.6 TEST RESULT 26
6. POWER SPECTRAL DENSITY TEST 28
6.1 APPLIED PROCEDURES / LIMIT 28
6.2 TEST PROCEDURE 28
6.3 DEVIATION FROM STANDARD 28
6.4 TEST SETUP 28
6.5 EUT OPERATION CONDITIONS 29

6.6 TEST RESULT 29
7. CHANNEL BANDWIDTH 30
7.1 APPLIED PROCEDURES / LIMIT 30
7.2 TEST PROCEDURE 30
7.3 DEVIATION FROM STANDARD 30
7.4 TEST SETUP 30
7.5 EUT OPERATION CONDITIONS 30
7.6 TEST RESULT 31
8. AVERAGE OUTPUT POWER TEST 32
8.1 APPLIED PROCEDURES/LIMIT 32
8.2 TEST PROCEDURE 32
8.3 DEVIATION FROM STANDARD 32
8.4 TEST SETUP 32
8.5 EUT OPERATION CONDITIONS 32
8.6 TEST RESULT 32
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION 33
9.1 APPLICABLE STANDARD 33
9.2 TEST PROCEDURE 33
9.3 DEVIATION FROM STANDARD 33
9.4 TEST SETUP 33
9.5 EUT OPERATION CONDITIONS 33
9.6 TEST RESULTS 33
10. ANTENNA REQUIREMENT 34
11. TEST SETUP PHOTO 34
12. EUT CONSTRUCTIONAL DETAILS 34
13. APPENDIX 2.4G WIFI 35

1. VERSION

Report No.	Version	Description	Approved
ZHT-240516024E	Rev.01	Initial issue of report	Aug. 13, 2024

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (b)(4)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	Channel Bandwidth	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1) ” N/A” denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Guangdong Zhonghan Testing Technology Co., Ltd.
Add. : Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District Shenzhen, Guangdong, China

FCC Registration Number:255941
Designation Number: CN0325
IC Registered No.: 29832
CAB identifier: CN0143

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U · where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2 · providing a level of confidence of approximately 95 % 。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF conducted power	±0.16dB
3	Conducted spurious emissions	±0.21dB
4	All radiated emissions (9k-30MHz)	±4.68dB
5	All radiated emissions(<1G)	±4.68dB
6	All radiated emissions(>1G)	±4.89dB
7	Temperature	±0.5°C
8	Humidity	±2%
9	Occupied Bandwidth	±4.96%

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Portable Mode 2 Charger
Test Model No.:	F-OBM26-AC-3P32
Hardware Version:	V1.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Channel numbers:	802.11b/802.11g /802.11n(HT20):11
Operation Frequency:	802.11b/802.11g /802.11n(HT20): 2412-2462MHz
Channel separation:	5MHz
Modulation technology:	IEEE 802.11b: DQPSK/DBPSK/DSSS/CCK IEEE 802.11g: QPSK/BPSK/16QAM/64QAM/OFDM IEEE 802.11n: QPSK/BPSK/16QAM/64QAM/OFDM
Antenna Type:	PCB Antenna
Antenna gain:	2.5dBi
Ratings:	Input: AC 100-380V 50-60Hz

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
	802.11b/802.11g/802.11n(HT20)
Lowest channel	2412MHz
Middle channel	2437MHz
Highest channel	2462MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: EUT use new battery during the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11b	802.11g	802.11n(HT20)
Data rate	1Mbps	6Mbps	6.5Mbps

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

EUT

3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note

Item	Shielded Type	Ferrite Core	Length	Note

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
(3) The device does not have a voice recording function.

3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Model	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	May 10, 2024	May 09, 2025
2	Loop antenna	EMCI	LAP600	May 10, 2024	May 09, 2025
3	Amplifier	Schwarzbeck	BBV 9743 B	May 10, 2024	May 09, 2025
4	Amplifier	Schwarzbeck	BBV 9718 B	May 10, 2024	May 09, 2025
5	Bilog Antenna	Schwarzbeck	VULB9162	May 28, 2024	May 27, 2025
6	Horn Antenna	Schwarzbeck	BBHA9120D	May 16, 2024	May 15, 2025
7	Horn Antenna	A.H.SYSTEMS	SAS574	May 10, 2024	May 09, 2025
8	Amplifier	AEROFLEX	100KHz-40GHz	May 10, 2024	May 09, 2025
9	Spectrum Analyzer	R&S	FSV40	May 16, 2024	May 15, 2025
10	CDNE	Schwarzbeck	CDNE M2 + CDNE M3	May 10, 2024	May 09, 2025
11	966 Anechoic Chamber	EMToni	9m6m6m	Nov. 25, 2021	Nov. 24, 2024
12	Spectrum Analyzer	KEYSIGHT	N9020A	May 10, 2024	May 09, 2025
13	WIDBAND RADIO COMMUNICATION TESTER	R&S	CMW500	May 10, 2024	May 09, 2025
14	Single Generator	Agilent	N5182A	May 10, 2024	May 09, 2025
15	Power Sensor	MWRFtest	MW100-RFCB	May 10, 2024	May 09, 2025
16	Audio analyzer	R&S	UPL	May 10, 2024	May 09, 2025
17	Single Generator	R&S	SMB100A	May 10, 2024	May 09, 2025
18	Power Amplifier Shielding Room	EMToni	2m3m3m	Nov. 25, 2021	Nov. 24, 2024

Conduction Test equipment

Equipment	Manufacturer	Model	Last Cal.	Next Cal.
Receiver	R&S	ESCI	May 10, 2024	May 09, 2025
LISN	R&S	ENV216	May 10, 2024	May 09, 2025
ISN CAT 6	Schwarzbeck	NTFM 8158	May 10, 2024	May 09, 2025
ISN CAT 5	Schwarzbeck	CAT5 8158	May 10, 2024	May 09, 2025
Capacitive Voltage Probe	Schwarzbeck	CVP 9222 C	May 10, 2024	May 09, 2025
Current Transformer Clamp	Schwarzbeck	SW 9605	May 10, 2024	May 09, 2025
CE Shielding Room	EMToni	9m4m3m	Nov. 25, 2021	Nov. 24, 2024

Conducted Test equipment

Equipment	Manufacturer	Model	Last Cal.	Next Cal.
Spectrum Analyzer	KEYSIGHT	N9020A	May 10, 2024	May 09, 2025
Single Generator	Agilent	N5182A	May 10, 2024	May 09, 2025

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 test result

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1922	52.13	9.91	62.04	63.94	-1.90	QP	P	
2	0.1922	37.60	9.91	47.51	53.94	-6.43	AVG	P	
3	0.2625	49.11	9.94	59.05	61.35	-2.30	QP	P	
4	0.2625	30.44	9.94	40.38	51.35	-10.97	AVG	P	
5	0.3165	47.94	9.96	57.90	59.80	-1.90	QP	P	
6	0.3165	32.33	9.96	42.29	49.80	-7.51	AVG	P	
7 *	0.3930	46.40	9.99	56.39	58.00	-1.61	QP	P	
8	0.3930	29.18	9.99	39.17	48.00	-8.83	AVG	P	
9	0.5127	44.27	10.02	54.29	56.00	-1.71	QP	P	
10	0.5127	26.17	10.02	36.19	46.00	-9.81	AVG	P	
11	0.5792	43.72	10.03	53.75	56.00	-2.25	QP	P	
12	0.5792	28.85	10.03	38.88	46.00	-7.12	AVG	P	

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.1985	52.44	9.91	62.35	63.67	-1.32	QP	P	
2	0.1985	37.52	9.91	47.43	53.67	-6.24	AVG	P	
3	0.2600	49.55	9.93	59.48	61.43	-1.95	QP	P	
4	0.2600	34.85	9.93	44.78	51.43	-6.65	AVG	P	
5	0.3209	47.61	9.96	57.57	59.68	-2.11	QP	P	
6	0.3209	31.40	9.96	41.36	49.68	-8.32	AVG	P	
7	0.3840	45.82	9.98	55.80	58.19	-2.39	QP	P	
8	0.3840	32.49	9.98	42.47	48.19	-5.72	AVG	P	
9	0.4490	44.95	10.00	54.95	56.89	-1.94	QP	P	
10	0.4490	29.07	10.00	39.07	46.89	-7.82	AVG	P	
11	0.5685	44.08	10.03	54.11	56.00	-1.89	QP	P	
12	0.5685	32.86	10.03	42.89	46.00	-3.11	AVG	P	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor
4.The test data shows only the worst case 802.11b mode (Low Channel:2412MHz).

4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoiccamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of avariable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).
h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature :	25.1℃	Relative Humidity :	50%
Pressure :	101kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.3992	44.70	-11.21	33.49	40.00	-6.51	QP
2	52.9453	28.86	-9.06	19.80	40.00	-20.20	QP
3	82.9385	34.41	-14.02	20.39	40.00	-19.61	QP
4	103.0800	33.13	-11.24	21.89	43.50	-21.61	QP
5 *	872.1832	40.83	1.77	42.60	46.00	-3.40	QP
6	952.0937	31.89	2.66	34.55	46.00	-11.45	QP

Temperature :	25.1℃	Relative Humidity :	50%
Pressure :	101kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	32.9791	40.00	-10.92	29.08	40.00	-10.92	QP
2	47.4917	29.44	-8.97	20.47	40.00	-19.53	QP
3	84.1100	33.84	-13.77	20.07	40.00	-19.93	QP
4	96.7750	34.84	-11.45	23.39	43.50	-20.11	QP
5	872.1832	32.84	1.77	34.61	46.00	-11.39	QP
6 *	955.4380	33.30	2.70	36.00	46.00	-10.00	QP

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2.The emission levels of other frequencies are very lower than the limit and not show in test report.
3.The test data shows only the worst case 802.11b mode (Low Channel:2412MHz).

1GHz~25GHz

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
802.11b									
Low Channel:2412MHz									
V	4824.00	55.56	30.55	5.77	24.66	55.44	74	-18.56	PK
V	4824.00	43.31	30.55	5.77	24.66	43.19	54	-10.81	AV
H	4824.00	56.83	30.33	6.32	24.55	57.37	74	-16.63	PK
H	4824.00	44.12	30.33	6.32	24.55	44.66	54	-9.34	AV
Middle Channel:2437MHz									
V	4874.00	58.49	30.55	5.77	24.66	58.37	74	-15.63	PK
V	4874.00	41.48	30.55	5.77	24.66	41.36	54	-12.64	AV
H	4874.00	59.35	30.33	6.32	24.55	59.89	74	-14.11	PK
H	4874.00	43.27	30.33	6.32	24.55	43.81	54	-10.19	AV
High Channel:2462MHz									
V	4924.00	55.37	30.55	5.77	24.66	55.25	74	-18.75	PK
V	4924.00	42	30.55	5.77	24.66	41.88	54	-12.12	AV
H	4924.00	56.9	30.33	6.32	24.55	57.44	74	-16.56	PK
H	4924.00	43.64	30.33	6.32	24.55	44.18	54	-9.82	AV
802.11g									
Low Channel:2412MHz									
V	4824.00	59.35	30.55	5.77	24.66	59.23	74	-14.77	PK
V	4824.00	41.01	30.55	5.77	24.66	40.89	54	-13.11	AV
H	4824.00	55.7	30.33	6.32	24.55	56.24	74	-17.76	PK
H	4824.00	41.76	30.33	6.32	24.55	42.3	54	-11.7	AV
Middle Channel:2437MHz									
V	4874.00	57.29	30.55	5.77	24.66	57.17	74	-16.83	PK
V	4874.00	41.67	30.55	5.77	24.66	41.55	54	-12.45	AV
H	4874.00	55.76	30.33	6.32	24.55	56.3	74	-17.7	PK
H	4874.00	43.11	30.33	6.32	24.55	43.65	54	-10.35	AV
High Channel:2462MHz									
V	4924.00	58.36	30.55	5.77	24.66	58.24	74	-15.76	PK
V	4924.00	41.66	30.55	5.77	24.66	41.54	54	-12.46	AV
H	4924.00	59.88	30.33	6.32	24.55	60.42	74	-13.58	PK
H	4924.00	43.43	30.33	6.32	24.55	43.97	54	-10.03	AV
802.11n 20									
Low Channel:2412MHz									
V	4824.00	57.49	30.55	5.77	24.66	57.37	74	-16.63	PK
V	4824.00	41.85	30.55	5.77	24.66	41.73	54	-12.27	AV
H	4824.00	56.46	30.33	6.32	24.55	57	74	-17	PK
H	4824.00	43.48	30.33	6.32	24.55	44.02	54	-9.98	AV
Middle Channel:2437MHz									
V	4874.00	57.26	30.55	5.77	24.66	57.14	74	-16.86	PK
V	4874.00	43.47	30.55	5.77	24.66	43.35	54	-10.65	AV
H	4874.00	56.07	30.33	6.32	24.55	56.61	74	-17.39	PK
H	4874.00	44.1	30.33	6.32	24.55	44.64	54	-9.36	AV
High Channel:2462MHz									
V	4924.00	55.51	30.55	5.77	24.66	55.39	74	-18.61	PK
V	4924.00	41.58	30.55	5.77	24.66	41.46	54	-12.54	AV
H	4924.00	55.48	30.33	6.32	24.55	56.02	74	-17.98	PK
H	4924.00	42.79	30.33	6.32	24.55	43.33	54	-10.67	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4.For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.

5. RADIATED BAND EMISSIONMEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
802.11b	LowChannel 2412MHz										
	H	2390.00	61.33	30.22	4.85	23.98	59.94	74.00	-14.06	PK	PASS
	H	2390.00	48.43	30.22	4.85	23.98	47.04	54.00	-6.96	AV	PASS
	H	2400.00	59.49	30.22	4.85	23.98	58.10	74.00	-15.90	PK	PASS
	H	2400.00	46.97	30.22	4.85	23.98	45.58	54.00	-8.42	AV	PASS
	V	2390.00	60.56	30.22	4.85	23.98	59.17	74.00	-14.83	PK	PASS
	V	2390.00	46.12	30.22	4.85	23.98	44.73	54.00	-9.27	AV	PASS
	V	2400.00	62.02	30.22	4.85	23.98	60.63	74.00	-13.37	PK	PASS
	V	2400.00	46.97	30.22	4.85	23.98	45.58	54.00	-8.42	AV	PASS
	High Channel 2462MHz										
	H	2483.50	59.87	30.22	4.85	23.98	58.48	74.00	-15.52	PK	PASS
	H	2483.50	46.25	30.22	4.85	23.98	44.86	54.00	-9.14	AV	PASS
	H	2500.00	61.89	30.22	4.85	23.98	60.50	74.00	-13.50	PK	PASS
	H	2500.00	47.25	30.22	4.85	23.98	45.86	54.00	-8.14	AV	PASS
	V	2483.50	61.59	30.22	4.85	23.98	60.20	74.00	-13.80	PK	PASS
	V	2483.50	48.49	30.22	4.85	23.98	47.10	54.00	-6.90	AV	PASS
	V	2500.00	62.20	30.22	4.85	23.98	60.81	74.00	-13.19	PK	PASS
	V	2500.00	46.78	30.22	4.85	23.98	45.39	54.00	-8.61	AV	PASS
802.11g	Low Channel 2412MHz										
	H	2390.00	60.90	30.22	4.85	23.98	59.51	74.00	-14.49	PK	PASS
	H	2390.00	47.07	30.22	4.85	23.98	45.68	54.00	-8.32	AV	PASS
	H	2400.00	59.94	30.22	4.85	23.98	58.55	74.00	-15.45	PK	PASS
	H	2400.00	46.25	30.22	4.85	23.98	44.86	54.00	-9.14	AV	PASS
	V	2390.00	60.74	30.22	4.85	23.98	59.35	74.00	-14.65	PK	PASS
	V	2390.00	48.53	30.22	4.85	23.98	47.14	54.00	-6.86	AV	PASS
	V	2400.00	61.98	30.22	4.85	23.98	60.59	74.00	-13.41	PK	PASS
	V	2400.00	46.59	30.22	4.85	23.98	45.20	54.00	-8.80	AV	PASS
	High Channel 2462MHz										
	H	2483.50	61.28	30.22	4.85	23.98	59.89	74.00	-14.11	PK	PASS
	H	2483.50	46.50	30.22	4.85	23.98	45.11	54.00	-8.89	AV	PASS
	H	2500.00	59.32	30.22	4.85	23.98	57.93	74.00	-16.07	PK	PASS
	H	2500.00	47.30	30.22	4.85	23.98	45.91	54.00	-8.09	AV	PASS
	V	2483.50	59.64	30.22	4.85	23.98	58.25	74.00	-15.75	PK	PASS
	V	2483.50	48.33	30.22	4.85	23.98	46.94	54.00	-7.06	AV	PASS
	V	2500.00	62.30	30.22	4.85	23.98	60.91	74.00	-13.09	PK	PASS
	V	2500.00	46.57	30.22	4.85	23.98	45.18	54.00	-8.82	AV	PASS
802.11n20	Low Channel 2412MHz										
	H	2390.00	62.19	30.22	4.85	23.98	60.80	74.00	-13.20	PK	PASS
	H	2390.00	46.78	30.22	4.85	23.98	45.39	54.00	-8.61	AV	PASS
	H	2400.00	62.47	30.22	4.85	23.98	61.08	74.00	-12.92	PK	PASS
	H	2400.00	46.55	30.22	4.85	23.98	45.16	54.00	-8.84	AV	PASS
	V	2390.00	62.08	30.22	4.85	23.98	60.69	74.00	-13.31	PK	PASS
	V	2390.00	47.78	30.22	4.85	23.98	46.39	54.00	-7.61	AV	PASS
	V	2400.00	61.84	30.22	4.85	23.98	60.45	74.00	-13.55	PK	PASS
	V	2400.00	47.81	30.22	4.85	23.98	46.42	54.00	-7.58	AV	PASS
	High Channel 2462MHz										
	H	2483.50	61.87	30.22	4.85	23.98	60.48	74.00	-13.52	PK	PASS
	H	2483.50	47.70	30.22	4.85	23.98	46.31	54.00	-7.69	AV	PASS
	H	2500.00	62.98	30.22	4.85	23.98	61.59	74.00	-12.41	PK	PASS
	H	2500.00	46.94	30.22	4.85	23.98	45.55	54.00	-8.45	AV	PASS
	V	2483.50	62.84	30.22	4.85	23.98	61.45	74.00	-12.55	PK	PASS

	V	2483.50	46.19	30.22	4.85	23.98	44.80	54.00	-9.20	AV	PASS
	V	2500.00	60.54	30.22	4.85	23.98	59.15	74.00	-14.85	PK	PASS
	V	2500.00	47.98	30.22	4.85	23.98	46.59	54.00	-7.41	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6. POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = average
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULT

Temperature：	25.9℃	Relative Humidity：	52%
Pressure：	101kPa	Test Voltage ：	AC 120V/60Hz

Please refer to APPENDIX 2.4G WIFI

7. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 xRBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP

7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULT

Temperature :	25.8℃	Relative Humidity :	52%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Mode		

Please refer to APPENDIX 2.4G WIFI

8. AVERAGE OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

8.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Average Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

a. The EUT was directly connected to the Power Analyzer

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP

8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULT

Temperature :	25.3℃	Relative Humidity :	55%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz

Please refer to APPENDIX 2.4G WIFI

9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

A) Set the RBW = 100KHz.
B) Set the VBW = 300KHz.
C) Sweep time = auto couple.
D) Detector function = average
E) Trace mode = max hold.
F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

Please refer to APPENDIX 2.4G WIFI

10. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(b)(4)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is PCB Antenna, the best case gain of the antenna is 2.5dBi, reference to the appendix II for details	

11. TEST SETUP PHOTO

Reference to the appendix I for details.

12. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

13. APPENDIX 2.4G WIFI

Duty Cycle

Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
b	2412	99.28	0	0.08
b	2437	99.44	0	0.08
b	2462	99.2	0	0.08
g	2412	95.37	0.21	0.49
g	2437	93.21	0.31	0.49
g	2462	96.26	0.17	0.49
n20	2412	94.61	0.24	0.52
n20	2437	92.34	0.35	0.52
n20	2462	96.5	0.15	0.52

Test Graphs

Duty Cycle NVNT b 2412MHz Ant1



Duty Cycle NVNT b 2437MHz Ant1



Duty Cycle NVNT b 2462MHz Ant1



Duty Cycle NVNT g 2412MHz Ant1



Duty Cycle NVNT g 2437MHz Ant1



Duty Cycle NVNT g 2462MHz Ant1

Duty Cycle NVNT n20 2412MHz Ant1



Duty Cycle NVNT n20 2437MHz Ant1



Duty Cycle NVNT n20 2462MHz Ant1

Maximum Average Conducted Output Power

Mode	Frequency (MHz)	Total Power (dBm)	Correction Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
b	2412	11.75	0	11.75	30	Pass
b	2437	11.29	0	11.29	30	Pass
b	2462	11.57	0	11.57	30	Pass
g	2412	10.77	0.21	10.98	30	Pass
g	2437	11.03	0.31	11.34	30	Pass
g	2462	11.45	0.17	11.62	30	Pass
n20	2412	7.32	0.24	7.56	30	Pass
n20	2437	7.59	0.35	7.94	30	Pass
n20	2462	8.11	0.15	8.26	30	Pass

Test Graphs

Average Power NVNT b 2412MHz Ant1



Average Power NVNT b 2437MHz Ant1



Average Power NVNT b 2462MHz Ant1



Average Power NVNT g 2412MHz Ant1



Average Power NVNT g 2437MHz Ant1



Average Power NVNT g 2462MHz Ant1



Average Power NVNT n20 2412MHz Ant1



Average Power NVNT n20 2437MHz Ant1



Average Power NVNT n20 2462MHz Ant1



-6dB Bandwidth

Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
b	2412	8.507	0.5	Pass
b	2437	9.531	0.5	Pass
b	2462	8.601	0.5	Pass
g	2412	16.334	0.5	Pass
g	2437	16.348	0.5	Pass
g	2462	16.34	0.5	Pass
n20	2412	17.542	0.5	Pass
n20	2437	17.562	0.5	Pass
n20	2462	17.556	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT b 2412MHz Ant1



-6dB Bandwidth NVNT b 2437MHz Ant1



-6dB Bandwidth NVNT b 2462MHz Ant1



-6dB Bandwidth NVNT g 2412MHz Ant1



-6dB Bandwidth NVNT g 2437MHz Ant1



-6dB Bandwidth NVNT g 2462MHz Ant1



-6dB Bandwidth NVNT n20 2412MHz Ant1



-6dB Bandwidth NVNT n20 2437MHz Ant1



-6dB Bandwidth NVNT n20 2462MHz Ant1



Occupied Channel Bandwidth

Mode	Frequency (MHz)	99% OBW (MHz)
b	2412	14.044
b	2437	14.063
b	2462	14.052
g	2412	16.565
g	2437	16.676
g	2462	16.615
n20	2412	17.765
n20	2437	17.761
n20	2462	17.718

Test Graphs

OBW NVNT b 2412MHz Ant1



OBW NVNT b 2437MHz Ant1



OBW NVNT b 2462MHz Ant1



OBW NVNT g 2412MHz Ant1



OBW NVNT g 2437MHz Ant1



OBW NVNT g 2462MHz Ant1



OBW NVNT n20 2412MHz Ant1



OBW NVNT n20 2437MHz Ant1



OBW NVNT n20 2462MHz Ant1



Maximum Power Spectral Density Level

Mode	Frequency (MHz)	Total PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
b	2412	-8.6	0	-8.6	8	Pass
b	2437	-10.71	0	-10.71	8	Pass
b	2462	-9.59	0	-9.59	8	Pass
g	2412	-14.42	0.21	-14.21	8	Pass
g	2437	-14.31	0.31	-14	8	Pass
g	2462	-14.59	0.17	-14.42	8	Pass
n20	2412	-17.22	0.24	-16.98	8	Pass
n20	2437	-16.85	0.35	-16.5	8	Pass
n20	2462	-17.07	0.15	-16.92	8	Pass

Test Graphs

PSD NVNT b 2412MHz Ant1



PSD NVNT b 2437MHz Ant1



PSD NVNT b 2462MHz Ant1



PSD NVNT g 2412MHz Ant1



PSD NVNT g 2437MHz Ant1



PSD NVNT g 2462MHz Ant1



PSD NVNT n20 2412MHz Ant1



PSD NVNT n20 2437MHz Ant1



PSD NVNT n20 2462MHz Ant1



Band Edge

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
b	2412	-51.93	-30	Pass
b	2462	-58.35	-30	Pass
g	2412	-33.24	-30	Pass
g	2462	-51.24	-30	Pass
n20	2412	-34.6	-30	Pass
n20	2462	-50.49	-30	Pass

Test Graphs

Band Edge NVNT b 2412MHz Ant1 Ref



Band Edge NVNT b 2412MHz Ant1 Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.413 5 GHz	2.350 dBm			
2	N	1	f	2.400 0 GHz	-49.835 dBm			
3	N	1	f	2.400 0 GHz	-49.835 dBm			
4	N	1	f	2.399 9 GHz	-49.453 dBm			
5								
6								
7								
8								
9								
10								
11								

Band Edge NVNT b 2462MHz Ant1 Ref



Band Edge NVNT b 2462MHz Ant1 Emission



Band Edge NVNT g 2412MHz Ant1 Ref



Band Edge NVNT g 2412MHz Ant1 Emission



Band Edge NVNT g 2462MHz Ant1 Ref



Band Edge NVNT g 2462MHz Ant1 Emission

Band Edge NVNT n20 2412MHz Ant1 Ref



Band Edge NVNT n20 2412MHz Ant1 Emission



Band Edge NVNT n20 2462MHz Ant1 Ref



Band Edge NVNT n20 2462MHz Ant1 Emission



Conducted RF Spurious Emission

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
b	2412	-49.24	-30	Pass
b	2437	-49.26	-30	Pass
b	2462	-49.18	-30	Pass
g	2412	-46.54	-30	Pass
g	2437	-45.19	-30	Pass
g	2462	-46.03	-30	Pass
n20	2412	-42.78	-30	Pass
n20	2437	-42.33	-30	Pass
n20	2462	-42.48	-30	Pass

Test Graphs

Tx. Spurious NVNT b 2412MHz Ant1 Ref



Tx. Spurious NVNT b 2412MHz Ant1 Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.411 4 GHz	-0.093 dBm			
2	N	1	f	25.329 1 GHz	-46.560 dBm			
3	N	1	f	4.794 6 GHz	-56.029 dBm			
4	N	1	f	7.183 1 GHz	-55.271 dBm			
5	N	1	f	9.543 3 GHz	-56.735 dBm			
6								
7								
8								
9								
10								
11								

Tx. Spurious NVNT b 2437MHz Ant1 Ref



Tx. Spurious NVNT b 2437MHz Ant1 Emission



Tx. Spurious NVNT b 2462MHz Ant1 Ref



Tx. Spurious NVNT b 2462MHz Ant1 Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.460 8 GHz	2.171 dBm			
2	N	1	f	24.122 1 GHz	-46.443 dBm			
3	N	1	f	4.811 4 GHz	-56.141 dBm			
4	N	1	f	7.441 6 GHz	-55.748 dBm			
5	N	1	f	9.688 0 GHz	-57.292 dBm			
6								
7								
8								
9								
10								
11								

Tx. Spurious NVNT g 2412MHz Ant1 Ref



Tx. Spurious NVNT g 2412MHz Ant1 Emission



Tx. Spurious NVNT g 2437MHz Ant1 Ref



Tx. Spurious NVNT g 2437MHz Ant1 Emission

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.440 5 GHz	-2.279 dBm			
2	N	1	f	24.872 1 GHz	-46.184 dBm			
3	N	1	f	4.768 1 GHz	-55.586 dBm			
4	N	1	f	7.251 0 GHz	-55.544 dBm			
5	N	1	f	9.923 6 GHz	-57.318 dBm			
6								
7								
8								
9								
10								
11								

Tx. Spurious NVNT g 2462MHz Ant1 Ref



Tx. Spurious NVNT g 2462MHz Ant1 Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.465 2 GHz	-3.225 dBm			
2	N	1	f	24.747 7 GHz	-46.447 dBm			
3	N	1	f	4.916 4 GHz	-55.612 dBm			
4	N	1	f	7.254 5 GHz	-56.026 dBm			
5	N	1	f	9.751 5 GHz	-56.303 dBm			
6								
7								
8								
9								
10								
11								

Tx. Spurious NVNT n20 2412MHz Ant1 Ref



Tx. Spurious NVNT n20 2412MHz Ant1 Emission

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.410 5 GHz	-6.104 dBm			
2	N	1	f	25.228 6 GHz	-46.316 dBm			
3	N	1	f	4.754 0 GHz	-55.981 dBm			
4	N	1	f	7.053 4 GHz	-56.145 dBm			
5	N	1	f	9.570 7 GHz	-57.279 dBm			
6								
7								
8								
9								
10								
11								

Tx. Spurious NVNT n20 2437MHz Ant1 Ref



Tx. Spurious NVNT n20 2437MHz Ant1 Emission

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.436 1 GHz	-7.180 dBm			
2	N	1	f	24.665 6 GHz	-46.464 dBm			
3	N	1	f	4.830 8 GHz	-55.548 dBm			
4	N	1	f	7.311 0 GHz	-55.899 dBm			
5	N	1	f	9.613 0 GHz	-56.972 dBm			
6								
7								
8								
9								
10								
11								

Tx. Spurious NVNT n20 2462MHz Ant1 Ref



Tx. Spurious NVNT n20 2462MHz Ant1 Emission



※※※※※ **END OF REPORT** ※※※※※