FCC PART 15 SUBPART C TEST REPORT
FCC PART 15.247

Report Reference No.....:	**MAX25122612P01-R01**
FCC ID..... :	**2BH6K-A95XF9**
Compiled by (position+printed name+signature) .:	Engineer/ Cindy Zheng
Supervised by (position+printed name+signature) .:	Manager/Haley Wen
Approved by (position+printed name+signature) .:	RF Manager/ Vivian Jiang
Date of issue .....:	January 07, 2026
Testing Laboratory Name .....:	**MAXLAB Testing Co.,Ltd.**
Address .....:	1/F, Building B, Xinshidai GR Park,Shiyan Street, Bao'an District, Shenzhen,Guangdong, 518052, People's Republic of China
Applicant's name.....:	**Shenzhen Dimao Technology Co., LTD**
Address .....:	603 Conrui Times Square,Keyuan Business Building, No. 39,Huarong Road,Gaofeng Community,Dalang Street,Longhua District,Shenzhen
Test specification .....:	
Standard .....:	**FCC Part 15.247** **KDB558074 D01 15.247 Meas Guidance v05r02** **ANSI C63.10:2020**

MAXLAB Testing Co.,Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the MAXLAB Testing Co.,Ltd.is acknowledged as copyright owner and source of the material. MAXLAB Testing Co.,Ltd.takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description .....:	**Router TV Box**
Trade Mark .....:	N/A
Manufacturer .....:	**Shenzhen Dimao Technology Co., LTD**
Model/Type reference .....:	A95X F9
Listed Models .....:	A95X W2, A95X W3, A95X W5, A95X W6, A95X W7, A95X W8, A95X W9, A95X W10, A95X W11
Modulation Type .....:	DSSS/ OFDM
Operation Frequency.....:	From 2412 - 2462MHz
Rating .....:	DC5V 2A from adapter AC120V/60Hz
Result .....:	**PASS**

TEST REPORT

Equipment under Test	:	Router TV Box
Model /Type	:	A95X F9
Series Model No.		A95X W2, A95X W3, A95X W5, A95X W6, A95X W7, A95X W8, A95X W9, A95X W10, A95X W11
Model Declaration	:	All models covered in this report are the same with each other, except for different model No. for trading purpose.
Applicant	:	**Shenzhen Dimao Technology Co., LTD**
Address	:	603 Conrui Times Square,Keyuan Business Building, No. 39,Huarong Road,Gaofeng Community,Dalang Street,Longhua District,Shenzhen
Manufacturer	:	**Shenzhen Dimao Technology Co., LTD**
Address	:	603 Conrui Times Square,Keyuan Business Building, No. 39,Huarong Road,Gaofeng Community,Dalang Street,Longhua District,Shenzhen

Test Result:	**PASS**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1 TEST STANDARDS 4

2 SUMMARY 5

2.1 General Remarks 5
2.2 Product Description 5
2.3 Equipment Under Test 7
2.4 Short description of the Equipment under Test (EUT) 7
2.5 EUT operation mode 8
2.6 Block Diagram of Test Setup 8
2.7 Related Submittal(s) / Grant (s) 8
2.8 Modifications 8

3 TEST ENVIRONMENT 9

3.1 Address of the test laboratory 9
3.2 Test Facility 9
3.3 Environmental conditions 9
3.4 Test Description 10
3.5 Statement of the measurement uncertainty 10
3.6 Equipments Used during the Test 11

4 TEST CONDITIONS AND RESULTS 13

4.1 AC Power Conducted Emission 13
4.2 Radiated Emission 16
4.3 Maximum Peak Conducted Output Power 22
4.4 Power Spectral Density 26
4.5 6dB Bandwidth 32
4.6 Out-of-band Emissions 37
4.7 Antenna Requirement 46

5 TEST SETUP PHOTOS OF THE EUT 47

6 PHOTOS OF THE EUT 48

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.
ANSI C63.10-2020: American National Standard for Testing Unlicensed Wireless Devices
KDB558074 D01 v05r02: Guidance for Compliance Measurements on Digital Transmission Systems (DTS) ,Frequency Hopping Spread Spectrum System(HFSS), and Hybrid System Devices Operating Under §15.247 of The FCC rules.

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	December 23, 2025
Testing commenced on	:	December 23, 2025
Testing concluded on	:	January 07, 2026

2.2 Product Description

Product Name:	Router TV Box
Model/Type reference:	A95X F9, A95X W2, A95X W3, A95X W5, A95X W6, A95X W7, A95X W8, A95X W9, A95X W10, A95X W11
Power supply:	DC5V 2A from adapter AC120V/60Hz
Adapter information (Optional accessories)	Model: LD003-V1.0 Input: 100-240V~ 50/60Hz 0.4A Output: 5V⎓2.0A
Battery:	N/A
Testing sample ID:	MAX25122612P01-R01-1# (Engineer sample), MAX25122612P01-R01-2# (Normal sample)
Hardware version:	HV1.0
Software version:	SV1.0
WIFI :	
Supported type:	802.11b/802.11g/802.11n(H20)/ 802.11n(H40)
Modulation:	802.11b: DSSS 802.11g/802.11n(H20)/ 802.11n(H40): OFDM
Operation frequency:	802.11b/802.11g/802.11n(H20): 2412MHz~2462MHz 802.11n(H40): 2422MHz~2452MHz
Channel number:	802.11b/802.11g/802.11n(H20): 11 802.11n(H40):7
Channel separation:	5MHz
Antenna type:	PCB Antenna
Antenna gain:	Antenna 1: 4.08dBi Antenna 2: 4.08dBi
Note1: The EUT 802.11n (20) and 802.11n(40) is support MIMO mode.	
If all antennas have the same gain, Directional gain = G_{ANT} + Array Gain, • For power spectral density (PSD) measurements on all devices, Array Gain = 10 log(N_{ANT}/N_{SS}) dB. • For power measurements on IEEE 802.11 devices, 1,2 Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leqslant 4$; Array Gain = 0 dB (i.e., no array gain) for channel widths $\geqslant$ 40 MHz for any N_{ANT};	

Array Gain = 5 log(N_{ANT}/N_{SS}) dB or 3 dB, whichever is less, for 20-MHz channel widths with $N_{ANT} \geqslant 5$.
For power spectral density (PSD): Directional gain=4.08dBi+10×log(2/1)dB=7.09dBi Limit of Total power Spectral Density =8-(7.09-6)= 6.91 dBm/3kHz
For power measurements: Directional gain=4.08dBi+0dB=4.08dBi

2.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	○	230V / 50 Hz	●	120V / 60Hz
		○	5 V DC	○	24 V DC
		○	Other (specified in blank below)		

2.4 Short description of the Equipment under Test (EUT)

This is a Router TV Box.
For more details, refer to the user's manual of the EUT.

2.5 EUT operation mode

The application provider specific test software(MP_Kit_RTL11n_FTV_USB_v1.25) to control sample in continuous TX and RX (Duty Cycle >98%) for testing meet KDB558074 test requirement.
IEEE 802.11b/g/n: Thirteen channels are provided to the EUT.
IEEE 802.11n(H40): Seven channels are provided to the EUT.
IEEE 802.11b/g/n

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

IEEE 802.11n(H40)

Channel	Frequency(MHz)		
3	2422		
4	2427		
5	2432		
6	2437		
7	2442		
8	2447		
9	2452		

2.6 Block Diagram of Test Setup



2.7 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.8 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

MAXLAB Testing Co.,Ltd.
1/F, Building B, Xinshidai GR Park,Shiyan Street, Bao'an District, Shenzhen,Guangdong, 518052, People's Republic of China

3.2 Test Facility

FCC-Registration No.: 562200 Designation Number: CN1338
MAXLAB Testing Co.,Ltd.has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

Industry Canada Registration Number. Is: 11093A CAB identifier: CN0019
The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

A2LA-Lab Cert. No.: 4707.01
MAXLAB Testing Co.,Ltd.has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:
Radiated Emission:

Temperature:	25 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	25 ° C
Humidity:	44 %
Atmospheric pressure:	950-1050mbar

AC Power Conducted Emission

Temperature:	24 ° C
Humidity:	44 %
Atmospheric pressure:	950-1050mbar

3.4 Test Description

FCC PART 15.247		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(2)	6dB Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Peak Conducted Output Power	PASS
FCC Part 15.247(e)	Power Spectral Density	PASS
FCC Part 15.109/ 15.205/ 15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge	PASS
FCC Part 15.203/15.247 (b)	Antenna Requirement	PASS

Data Rate Used:
Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission Radiated Emission 9KHz~1GHz& Radiated Emission 1GHz~10th Harmonic	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(20MHz)/OFDM	6.5Mbps	1/6/11
	11n(40MHz)/OFDM	13.5Mbps	3/6/9
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(20MHz)/OFDM	6.5Mbps	1/11
	11n(40MHz)/OFDM	13.5Mbps	3/9

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01" Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the MAXLAB Testing Co.,Ltd.quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for MAXLAB Testing Co.,Ltd.

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6 Equipments Used during the Test

Conducted Emission					
Test Equipment	**Manufacturer**	**Model**	**Serial No.**	**Date of Cal.**	**Due Date**
Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	MAX252	2025-10-27	2026-10-26
EMI Test Receiver	R&S	ESCI 7	MAX552	2025-10-27	2026-10-26
Coaxial Switch	ANRITSU CORP	MP59B	MAX225	2025-10-27	2026-10-26
ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	MAX226	2025-10-27	2026-10-26
Coaxial Cable	MAX	N/A	MAX227	N/A	N/A
EMI Test Software	AUDIX	E3	N/A	N/A	N/A
Thermo meter	KTJ	TA328	MAX233	2025-10-27	2026-10-26
Absorbing clamp	Elektronik-Feinmechanik	MDS21	MAX229	2025-10-27	2026-10-26
LISN	R&S	ENV216	308	2025-10-27	2026-10-26
LISN	R&S	ENV216	314	2025-10-27	2026-10-26
Radiation Test equipment					
Test Equipment	**Manufacturer**	**Model**	**Serial No.**	**Date of Cal.**	**Due Date**
3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	MAX250	2025-10-27	2026-10-26
Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	MAX251	N/A	N/A
EMI Test Receiver	Rohde & Schwarz	ESU26	MAX203	2025-10-27	2026-10-26
BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	MAX214	2025-10-27	2026-10-26
Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	MAX208	2025-10-27	2026-10-26
Horn Antenna	ETS-LINDGREN	3160	MAX217	2025-10-27	2026-10-26
EMI Test Software	AUDIX	E3	N/A	N/A	N/A
Coaxial Cable	MAX	N/A	MAX213	2025-10-27	2026-10-26
Coaxial Cable	MAX	N/A	MAX211	2025-10-27	2026-10-26
Coaxial cable	MAX	N/A	MAX210	2025-10-27	2026-10-26
Coaxial Cable	MAX	N/A	MAX212	2025-10-27	2026-10-26
Amplifier(100kHz-3GHz)	HP	8347A	MAX204	2025-10-27	2026-10-26
Amplifier(2GHz-20GHz)	HP	84722A	MAX206	2025-10-27	2026-10-26
Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	MAX218	2025-10-27	2026-10-26
Band filter	Amindeon	82346	MAX219	2025-10-27	2026-10-26
Power Meter	Anritsu	ML2495A	MAX540	2025-10-27	2026-10-26
Power Sensor	Anritsu	MA2411B	MAX541	2025-10-27	2026-10-26
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	MAX575	2025-10-27	2026-10-26

Splitter	Agilent	11636B	MAX237	2025-10-27	2026-10-26
Loop Antenna	ZHINAN	ZN30900A	MAX534	2025-10-27	2026-10-26
Breitband hornantenne	SCHWARZBECK	BBHA 9170	MAX579	2025-10-27	2026-10-26
Amplifier	TDK	PA-02-02	MAX574	2025-10-27	2026-10-26
Amplifier	TDK	PA-02-03	MAX576	2025-10-27	2026-10-26
PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	MAX578	2025-10-27	2026-10-26

RF Conducted Test:

Test Equipment	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
MXA Signal Analyzer	Agilent	N9020A	MAX566	2025-10-27	2026-10-26
EMI Test Receiver	R&S	ESCI 7	MAX552	2025-10-27	2026-10-26
Spectrum Analyzer	Agilent	E4440A	MAX533	2025-10-27	2026-10-26
MXG vector Signal Generator	Agilent	N5182A	MAX567	2025-10-27	2026-10-26
ESG Analog Signal Generator	Agilent	E4428C	MAX568	2025-10-27	2026-10-26
USB RF Power Sensor	DARE	RPR3006W	MAX569	2025-10-27	2026-10-26
RF Switch Box	Shongyi	RFSW3003328	MAX571	2025-10-27	2026-10-26
Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	MAX572	2025-10-27	2026-10-26

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2020.
2 Support equipment, if needed, was placed as per ANSI C63.10-2020
3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020
4 The EUT received power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5 All support equipments received AC power from a second LISN, if any.
6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT.The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

TEST RESULTS

Note: 802.11b/802.11g/802.11n (H20)/ 802.11n (H40) Mode all have been tested, only worse case 802.11b mode is reported.

Power supply:	AC 120V/60Hz	Polarization	L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.186	26.69	10.15	36.84	64.21	-27.37	QP
2	0.186	14.14	10.15	24.29	54.21	-29.92	AVG
3	0.562	23.15	10.16	33.31	56.00	-22.69	QP
4 *	0.562	13.40	10.16	23.56	46.00	-22.44	AVG
5	1.142	9.65	10.17	19.82	46.00	-26.18	AVG
6	1.226	20.00	10.17	30.17	56.00	-25.83	QP
7	3.766	13.31	10.22	23.53	56.00	-32.47	QP
8	3.766	2.68	10.22	12.90	46.00	-33.10	AVG
9	9.690	-0.38	10.34	9.96	50.00	-40.04	AVG
10	10.142	10.77	10.35	21.12	60.00	-38.88	QP
11	22.642	8.94	10.64	19.58	60.00	-40.42	QP
12	23.354	-1.78	10.66	8.88	50.00	-41.12	AVG

Note:1).Level (dBμV)= Reading (dBμV)+ Factor (dB)
2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)
3). Margin(dB) = Limit (dBμV) - Level (dBμV)

Power supply:	AC 120V/60Hz	Polarization	N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.174	14.06	10.15	24.21	54.77	-30.56	AVG
2	0.178	27.68	10.15	37.83	64.58	-26.75	QP
3	0.314	15.70	10.15	25.85	49.86	-24.01	AVG
4	0.330	23.41	10.15	33.56	59.45	-25.89	QP
5	0.778	21.31	10.16	31.47	56.00	-24.53	QP
6 *	0.778	12.59	10.16	22.75	46.00	-23.25	AVG
7	2.506	2.46	10.20	12.66	46.00	-33.34	AVG
8	2.690	13.37	10.20	23.57	56.00	-32.43	QP
9	6.254	-1.11	10.26	9.15	50.00	-40.85	AVG
10	6.626	10.25	10.26	20.51	60.00	-39.49	QP
11	16.214	-1.81	10.48	8.67	50.00	-41.33	AVG
12	16.322	9.92	10.49	20.41	60.00	-39.59	QP

Note:1).Level (dBμV)= Reading (dBμV)+ Factor (dB)
2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)
3). Margin(dB) = Limit (dBμV) - Level (dBμV)

4.2 Radiated Emission

TEST CONFIGURATION

Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Anternna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

Transd=AF +CL-AG

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150

216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark:
1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. All three channels (lowest/middle/highest) of each mode were measured below 1GHz and recorded worst case at 802.11b low channel(ANT1).
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
4. The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

For 30MHz-1GHz

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	59.859	33.30	-15.13	18.17	40.00	-21.83	QP
2 *	85.598	43.68	-17.80	25.88	40.00	-14.12	QP
3	127.218	35.03	-13.98	21.05	43.50	-22.45	QP
4	216.024	48.04	-16.19	31.85	46.00	-14.15	QP
5	404.666	34.99	-9.40	25.59	46.00	-20.41	QP
6	704.226	34.10	-3.13	30.97	46.00	-15.03	QP

Note:1).Level (dBμV/m)= Reading (dBμV)+ Factor (dB/m)
2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)
3). Margin(dB) = Limit (dBμV/m) - Level (dBμV/m)

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	32.634	47.63	-14.73	32.90	40.00	-7.10	QP
2	38.212	44.55	-13.89	30.66	40.00	-9.34	QP
3	62.651	46.37	-15.51	30.86	40.00	-9.14	QP
4	169.005	46.37	-12.98	33.39	43.50	-10.11	QP
5	243.377	46.08	-14.40	31.68	46.00	-14.32	QP
6	297.224	42.53	-12.13	30.40	46.00	-15.60	QP

Note:1).Level (dBμV/m)= Reading (dBμV)+ Factor (dB/m)
2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)
3). Margin(dB) = Limit (dBμV/m) - Level (dBμV/m)

For 1GHz to 25GHz

Note: 802.11b/802.11g/802.11n (H20)/ 802.11n (H40) Mode all have been tested, only worse case 802.11b mode(ANT1) is reported ***(above 1GHz)***

Frequency(MHz):			2412		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	56.42	PK	74	17.58	60.78	32.40	5.11	41.87	-4.36
4824.00	46.00	AV	54	8.00	50.36	32.40	5.11	41.87	-4.36
7236.00	55.23	PK	74	18.77	55.86	36.58	6.43	43.64	-0.63
7236.00	45.07	AV	54	8.93	45.70	36.58	6.43	43.64	-0.63

Frequency(MHz):			2412		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	55.79	PK	74	18.21	60.15	32.40	5.11	41.87	-4.36
4824.00	45.43	AV	54	8.57	49.79	32.40	5.11	41.87	-4.36
7236.00	54.33	PK	74	19.67	54.96	36.58	6.43	43.64	-0.63
7236.00	44.41	AV	54	9.59	45.04	36.58	6.43	43.64	-0.63

Frequency(MHz):			2437		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	57.53	PK	74	16.47	61.48	32.56	5.34	41.85	-3.95
4874.00	47.79	AV	54	6.21	51.74	32.56	5.34	41.85	-3.95
7311.00	55.76	PK	74	18.24	56.12	36.54	6.81	43.71	-0.36
7311.00	46.17	AV	54	7.83	46.53	36.54	6.81	43.71	-0.36

Frequency(MHz):			2437		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	58.54	PK	74	15.46	62.49	32.56	5.34	41.85	-3.95
4874.00	46.57	AV	54	7.43	50.52	32.56	5.34	41.85	-3.95
7311.00	55.88	PK	74	18.12	56.24	36.54	6.81	43.71	-0.36
7311.00	47.37	AV	54	6.63	47.73	36.54	6.81	43.71	-0.36

Frequency(MHz):			2462		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4924.00	56.89	PK	74	17.11	60.35	32.73	5.64	41.83	-3.46
4924.00	46.91	AV	54	7.09	50.37	32.73	5.64	41.83	-3.46
7386.00	55.49	PK	74	18.51	55.55	36.50	7.23	43.79	-0.06
7386.00	45.47	PK	54	8.53	45.53	36.50	7.23	43.79	-0.06

Frequency(MHz):			2462		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4924.00	57.16	PK	74	16.84	60.62	32.73	5.64	41.83	-3.46
4924.00	46.02	AV	54	7.98	49.48	32.73	5.64	41.83	-3.46
7386.00	53.21	PK	74	20.79	53.27	36.50	7.23	43.79	-0.06
7386.00	45.03	PK	54	8.97	45.09	36.50	7.23	43.79	-0.06

1) Emission level (dBuV/m) = Meter Reading+ antenna Factor+ cable loss- preamp factor.
2) Margin value = Limits-Emission level.
3) -- Mean the PK detector measured value is below average limit.
4) The other emission levels were very low against the limit.
5) RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

Results of Band Edges Test (Radiated)

Note: 802.11b/802.11g/802.11n (H20)/ 802.11n (H40) Mode all have been tested, only worse case 802.11b mode_ANT1 is reported.

Test Frequency(MHz):			**Lowest channel**		**Polarity:**		**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2310.00	49.70	PK	74	24.30	59.89	27.42	4.31	42.15	-10.42
2310.00	40.51	AV	54	13.49	50.75	27.42	4.31	42.15	-10.42
2390.00	48.02	PK	74	25.98	58.02	27.55	4.35	42.19	-10.29
2390.00	38.53	AV	54	15.47	48.56	27.55	4.35	42.19	-10.29
2400.00	45.08	PK	74	28.92	54.94	27.70	4.39	42.28	-10.19
2400.00	35.30	AV	54	18.70	45.21	27.70	4.39	42.28	-10.19

Test Frequency(MHz):			**Lowest channel**		**Polarity:**		**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2310.00	47.66	PK	74	26.34	57.70	27.42	4.31	42.15	-10.42
2310.00	37.78	AV	54	16.22	47.84	27.42	4.31	42.15	-10.42
2390.00	44.67	PK	74	29.33	54.71	27.55	4.35	42.19	-10.29
2390.00	35.50	AV	54	18.50	45.43	27.55	4.35	42.19	-10.29
2400.00	42.65	PK	74	31.35	52.46	27.70	4.39	42.28	-10.19
2400.00	32.84	AV	54	21.16	42.68	27.70	4.39	42.28	-10.19

Test Frequency(MHz):			**Highest channel**		**Polarity:**		**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	44.02	PK	74	29.98	54.48	27.55	4.38	42.56	-10.63
2483.50	34.58	AV	54	19.42	45.43	27.55	4.38	42.56	-10.63
2500.00	41.94	PK	74	32.06	52.40	27.69	4.46	42.88	-10.73
2500.00	32.62	AV	54	21.38	43.27	27.69	4.46	42.88	-10.73

Test Frequency(MHz):			**Highest channel**		**Polarity:**		**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	42.01	PK	74	31.99	52.58	27.55	4.38	42.56	-10.63
2483.50	33.12	AV	54	20.88	43.72	27.55	4.38	42.56	-10.63
2500.00	38.72	PK	74	35.28	49.36	27.69	4.46	42.88	-10.73
2500.00	29.46	AV	54	24.54	40.06	27.69	4.46	42.88	-10.73

Note：

1) Emission level (dBuV/m) = Meter Reading+ antenna Factor+ cable loss- preamp factor.
2) Margin value = Limits-Emission level.
3) -- Mean the PK detector measured value is below average limit.
4) The other emission levels were very low against the limit.
5) RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

4.3 Maximum Peak Conducted Output Power

Limit

The Maximum Peak Output Power Measurement is 30dBm.

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration

Test Results

Test CH	Peak Output Power (dBm)				Limit(dBm)	Result
	802.11b		802.11g			
	ANT1	ANT2	ANT1	ANT2		
Lowest	10.197	10.217	10.335	10.360	30.00	Pass
Middle	10.265	10.313	10.373	10.405		
Highest	10.453	10.352	10.401	10.380		

Test CH	Peak Output Power (dBm)								Total power(dBm)		Limit (dBm)
	802.11n(HT20) (dBm)		802.11n(HT40) (dBm)		802.11n(HT20) (mW)		802.11n(HT40) (mW)		802.11n (HT20) (dBm)	802.11n (HT40) (dBm)	
/	ANT1	ANT2	ANT1	ANT2	ANT1	ANT2	ANT1	ANT2	/	/	30.00
Lowest	10.223	10.080	9.859	9.671	10.527	10.186	9.681	9.270	13.162	12.776	
Middle	10.612	10.571	9.737	9.656	11.513	11.405	9.412	9.238	13.602	12.707	
Highest	10.575	10.535	9.683	9.717	11.416	11.311	9.296	9.369	13.565	12.710	

Type	Frequency (MHz)	Output Power (dBm)	Antenna gain (dBi)	EIRP (dBm)
802.11b	Lowest	10.217	4.08	14.30
	Middle	10.313	4.08	14.39
	Highest	10.453	4.08	14.53
802.11g	Lowest	10.360	4.08	14.44
	Middle	10.405	4.08	14.49
	Highest	10.401	4.08	14.48
802.11n20	Lowest	13.162	4.08	17.24
	Middle	13.602	4.08	17.68
	Highest	13.565	4.08	17.65
802.11n40	Lowest	12.776	4.08	16.86
	Middle	12.707	4.08	16.79
	Highest	12.710	4.08	16.79

Note:

1) Measured output power at difference data rate for each mode and recorded worst case for each mode.
2) Test results including cable loss.
3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
4) If all antennas have the same gain, Directional gain = G_{ANT} + Array Gain,

   For power measurements on IEEE 802.11 devices, 1,2

   Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leqslant 4$;

   Array Gain = 0 dB (i.e., no array gain) for channel widths $\geqslant$ 40 MHz for any N_{ANT};

   Array Gain = 5 log(N_{ANT}/N_{SS}) dB or 3 dB, whichever is less, for 20-MHz channel widths with $N_{ANT} \geqslant 5$.

   Directional gain=4.08dBi+0dB=4.08dBi

N_{SS} = the number of independent spatial streams of data;
N_{ANT} = the total number of antennas;

Duty Cycly:

802.11b



Ton	Tp	Duty cycly(%)	Duty factor(dB)
100.00	100.00	100.00%	0.00

802.11g



Ton	Tp	Duty cycly(%)	Duty factor(dB)
100.00	100.00	100.00%	0.00

802.11n20



Ton	Tp	Duty cycly(%)	Duty factor(dB)
100.00	100.00	100.00%	0.00

802.11n40



Ton	Tp	Duty cycly(%)	Duty factor(dB)
100.00	100.00	100.00%	0.00

4.4 Power Spectral Density

Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW ≥ 3 kHz.
3. Set the VBW ≥ 3× RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be 8dBm.

Test Configuration

Test Results

Type	Channel	Power Spectral Density (dBm/3KHz)		Limit (dBm/3KHz)	Result
		ANT1	ANT2		
802.11b	01	-11.881	-13.423	8.00	Pass
	06	-13.755	-12.415		
	11	-13.272	-12.337		
802.11g	01	-18.677	-18.345		
	06	-18.267	-19.062		
	11	-18.791	-19.074		

Type	Channel	Power Spectral Density (dBm/3KHz)		Power Spectral Density (mW)		Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3KHz)	Result
		ANT1	ANT2	ANT1	ANT2			
802.11N20	01	-18.437	-18.457	0.014	0.014	-15.528	6.91	Pass
	06	-18.178	-19.464	0.015	0.011	-15.850		
	11	-19.651	-19.627	0.011	0.011	-16.576		
802.11N40	03	-22.009	-22.947	0.006	0.005	-19.586		
	06	-22.742	-22.823	0.005	0.005	-20.000		
	09	-21.854	-21.290	0.007	0.007	-18.539		

Note:
1) Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
2) Test results including cable loss;
3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;

4) If all antennas have the same gain, Directional gain = GANT + Array Gain,

For power spectral density (PSD) measurements on all devices,
Array Gain = 10 log(N_{ANT}/N_{SS}) dB.

So, Directional gain=4.08dBi+10×log(2/1)dB=7.09dBi

Limit of Total power Spectral Density =8-(7.09-6)=6.91 dBm/3kHz

N_{SS} = the number of independent spatial streams of data;
N_{ANT} = the total number of antennas;

Please refer to following plots;

ANT1

802.11b	802.11g
	
CH01	CH01
	
CH06	CH06
	
CH11	CH11

802.11n(HT20)



CH01

802.11n(HT40)



CH03



CH06



CH06



CH11



CH09