

FCC RF EXPOSURE REPORT

FCC ID: 2BH7FEAP727

Project No. : 2511C431
Equipment : BE5000 Ceiling Mount Wi-Fi 7 Access Point
Brand Name : Omada
Test Model : EAP727
Model Name : EAP727
Hardware Version : 1.0
Software Version : 1.0
Applicant : TP-Link Systems Inc.
Address : 10 Mauchly, Irvine, CA 92618
Manufacturer : TP-Link Systems Inc.
Address : 10 Mauchly, Irvine, CA 92618
Date of Receipt : Nov. 24, 2025
Date of Test : Nov. 24, 2025 ~ Jan. 06, 2026
Issued Date : Mar. 26, 2026
Test Sample : Engineering Sample No.: DG920251124512
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091 & KDB 447498 D01 v06

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc. (Dongguan)

Prepared by : 
Sheldon Ou

Approved by : 
Chay Cai

No.3, Jinshagang 1st Road, Dalang, Dongguan, Guangdong People's Republic of China.

Tel: +86-769-8318-3000 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. BTL assumes no responsibility for the data provided by the customer, any statements, inferences or generalizations drawn by the customer or others from the reports issued by BTL.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

REVISION HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-5-2511C431	R00	Original Report.	Mar. 26, 2026	Valid

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

2. ANTENNA SPECIFICATION

For LE:

Ant.	Manufacturer	P/N	Antenna Type	Connector	Gain (dBi)
1	TP-Link Systems Inc.	EAP727-ANT3	Dipole	N/A	3

Note: The antenna gain is provided by the manufacturer.

For 2.4GHz:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	 tp-link	EAP727	Dipole	ipex	3.38
2	 tp-link	EAP727	Dipole	ipex	3

Note:

- 1) This EUT supports CDD, all antenna gains are not equal, Directional gain = $G_{ANT} + \text{Array Gain}$.
For power measurements, Array Gain=0dB ($N_{ANT} \leq 4$), so the Directional gain=3.38.
- 2) Beamforming Gain is 3dB.
- 3) The antenna gain and beamforming gain are provided by the manufacturer.

For 5GHz:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Note
1	 tp-link	EAP727	Dipole	ipex	5.35	UNII-1
					5.77	UNII-2A
					7.07	UNII-2C
					7.46	UNII-3
2	 tp-link	EAP727	Dipole	ipex	4.94	UNII-1
					4.94	UNII-2A
					5.29	UNII-2C
					5.17	UNII-3
3	 tp-link	EAP727	Dipole	ipex	3.61	UNII-1
					3.61	UNII-2A
					3.95	UNII-2C
					4.04	UNII-3

Note:

- 1) This EUT supports CDD, and all antenna gains are not equal, Directional gain = $G_{ANT} + \text{Array Gain}$,
For power measurements, Array Gain=0dB ($N_{ANT} \leq 4$), so the Directional gain=7.46.
So, the UNII-1, UNII-3 output power limit is $30 - (7.46 - 6) = 28.54$, the UNII-2A, UNII-2C output power limit is $23.98 - (7.46 - 6) = 22.52$.
- 2) Beamforming Gain is 5dB.
- 3) The antenna gain and beamforming gain are provided by the manufacturer.

3. CALCULATED RESULT

For LE:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Max. Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.00	1.9953	16.98	49.8884	0.0117	1	Complies

For 2.4GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.38	2.1777	30.17	1039.9202	0.2666	1	Complies

For 5GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
7.46	5.5719	28.73	746.4488	0.4896	1	Complies

For the max simultaneous transmission MPE:

Ratio		Total	Limit of Ratio	Test Result
2.4GHz	5GHz			
0.2666	0.4896	0.7562	1	Complies

Note:

- (1) The calculated distance is 26 cm.
- (2) $\text{Ratio} = \text{Power Density (S) (mW/cm}^2\text{)} / \text{Limit of Power Density (S) (mW/cm}^2\text{)}$
- (3) Output power including tune up tolerance ($\pm 0.5\text{dB}$).
- (4) 2.4GHz and LE cannot simultaneous transmission.

End of Test Report