RF MEASUREMENT REPORT

FCC ID:	2BH7FWR1512X
Applicant:	TP-Link Systems Inc.
Product:	AX1500 Wi-Fi 6 Portable Router
Model No.:	TL-WR1512X
Brand Name:	tp-link
FCC Classification:	Unlicensed National Information Infrastructure (NII)
FCC Rule Part(s):	Part 15 Subpart E (Section 15.407)
Result:	Complies
Received Date:	2025-03-24
Test Date:	2025-03-28 ~ 2025-04-18

Reviewed By: Kevin Guo

Approved By: Robin Wu

ACCREDITED
TESTING LABORATORY
CERTIFICATE #3628.01

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB789033. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
R25S1052031-U202	V01	Initial Report	2025-07-15	Valid

CONTENTS

Description Page

1. General Information 6

1.1. Applicant 6
1.2. Manufacturer 6
1.3. Testing Facility 6
1.4. Product Information 7
1.5. Radio Specification under Test 7
1.6. Working Frequencies 8
1.7. Antenna Details 9

2. Test Configuration 10

2.1. Test Mode 10
2.2. Test System Connection Diagram 11
2.3. Test Software 11
2.4. Applied Standards 12
2.5. Test Environment Condition 12

3. Antenna Requirements 13

4. Measuring Instrument 14

5. Decision Rules and Measurement Uncertainty 15

5.1. Decision Rules 15
5.2. Measurement Uncertainty 15

6. Test Result 16

6.1. Summary 16
6.2. 26dB & 99% Bandwidth Measurement 17
6.2.1. Test Limit 17
6.2.2. Test Procedure 17
6.2.3. Test Setting 17
6.2.4. Test Setup 18
6.2.5. Test Result 18
6.3. 6dB Bandwidth Measurement 19
6.3.1. Test Limit 19
6.3.2. Test Procedure 19
6.3.3. Test Setting 19
6.3.4. Test Setup 19
6.3.5. Test Result 19
6.4. Output Power Measurement 20
6.4.1. Test Limit 20

6.4.2. Test Procedure 20
6.4.3. Test Setting 20
6.4.4. Test Setup 20
6.4.5. Test Result 20
6.5. Transmit Power Control Measurement 21
6.5.1. Test Limit 21
6.5.2. Test Procedure 21
6.5.3. Test Setting 21
6.5.4. Test Setup 21
6.5.5. Test Result 21
6.6. Power Spectral Density Measurement 22
6.6.1. Test Limit 22
6.6.2. Test Procedure 22
6.6.3. Test Setting 22
6.6.4. Test Setup 23
6.6.5. Test Result 23
6.7. Frequency Stability Measurement 24
6.7.1. Test Limit 24
6.7.2. Test Procedure 24
6.7.3. Test Setup 24
6.7.4. Test Result 25
6.8. Radiated Spurious Emission Measurement 26
6.8.1. Test Limit 26
6.8.2. Test Procedure 26
6.8.3. Test Setting 26
6.8.4. Test Setup 28
6.8.5. Test Result 29
6.9. Radiated Restricted Band Edge Measurement 30
6.9.1. Test Limit 30
6.9.2. Test Procedure 32
6.9.3. Test Setting 32
6.9.4. Test Setup 33
6.9.5. Test Result 33
6.10. AC Conducted Emissions Measurement 34
6.10.1. Test Limit 34
6.10.2. Test Setup 34
6.10.3. Test Result 34

Appendix A – Test Result 35

A.1 Duty Cycle Test Result 35

A.2 26dB Bandwidth Test Result 37
A.3 6dB Bandwidth Test Result 52
A.4 Output Power Test Result 58
A.5 Power Spectral Density Test Result 61
A.6 Radiated Spurious Emission Test Result 88
A.7 Radiated Restricted Band Edge Test Result 161
A.8 AC Conducted Emissions Test Result 287

Appendix B – Test Setup Photograph 291

Appendix C – EUT Photograph 292

1. General Information

1.1. Applicant

TP-Link Systems Inc.
10 Mauchly, Irvine, CA 92618

1.2. Manufacturer

TP-Link Systems Inc.
10 Mauchly, Irvine, CA 92618

1.3. Testing Facility

☒	**Test Site – MRT Suzhou Laboratory**				
	Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China **Laboratory Location (Suzhou - SIP)** 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China **Laboratory Location (Suzhou - Wujiang)** Building 1, No.1 Xingdong Road, Wujiang, Suzhou, Jiangsu, People's Republic of China				
	Laboratory Accreditations				
	A2LA: 3628.01		CNAS: L10551		
	FCC: CN1166		ISED: CN0001		
	VCCI:	☐R-20025	☐G-20034	☐C-20020	☐T-20020
		☐R-20141	☐G-20134	☐C-20103	☐T-20104
☐	**Test Site – MRT Shenzhen Laboratory**				
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China				
	Laboratory Accreditations				
	A2LA: 3628.02		CNAS: L10551		
	FCC: CN1284		ISED: CN0105		
☐	**Test Site – MRT Taiwan Laboratory**				
	Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)				
	Laboratory Accreditations				
	TAF: 3261				
	FCC: 291082, TW3261		ISED: TW3261		

1.4. Product Information

Product Name	AX1500 Wi-Fi 6 Portable Router
Model No.	TL-WR1512X
EUT Identification No.	20250324Sample#01(Conducted) 20250324Sample#02(Radiated)
Wi-Fi Specification	802.11a/b/g/n/ac/ax
Antenna Information	Refer to section 1.7
Operating Temperature	0 ~ 40°C
Power Type	By AC/DC Adapter
Accessory	
AC Adapter	Model: DSA-18QFB FUS A Input: 100-240V~50/60Hz,0.8A Output: 5.0VDC 3.0A 15.0W,9.0VDC 2.0A 18.0W,12.0VDC 1.5A 18.0W
Note: The information of the EUT (Equipment Under Test) was provided by the manufacturer. The accuracy, completeness, and validity of the information are solely the responsibility of the manufacturer.	

1.5. Radio Specification under Test

Frequency Range	UNII-1: 5150 ~ 5250 MHz UNII-2A: 5250 ~ 5350 MHz UNII-2C: 5470 ~ 5725 MHz UNII-3: 5725 ~ 5850 MHz	
Type of Modulation	802.11a/n/ac: OFDM 802.11ax: OFDMA	
Data Rate	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 300Mbps 802.11ac: up to 866.7Mbps 802.11ax: up to 1201Mbps	
Channel Puncturing Function	☐ Supported	☒ Unsupported
Support RU	☒ Full RU	☐ Partial RU

1.6. Working Frequencies

802.11a/n-HT20/ac-VHT20/ax-HE20

Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180 MHz	40	5200 MHz	44	5220 MHz
48	5240 MHz	52	5260 MHz	56	5280 MHz
60	5300 MHz	64	5320 MHz	100	5500 MHz
104	5520 MHz	108	5540 MHz	112	5560 MHz
116	5580 MHz	120	5600 MHz	124	5620 MHz
128	5640 MHz	132	5660 MHz	136	5680 MHz
140	5700 MHz	144	5720 MHz	149	5745 MHz
153	5765 MHz	157	5785 MHz	161	5805 MHz
165	5825 MHz	--	--	--	--

802.11n-HT40/ac-VHT40/ax-HE40

Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz	54	5270 MHz
62	5310 MHz	102	5510 MHz	110	5550MHz
118	5590 MHz	126	5630 MHz	134	5670 MHz
142	5710 MHz	151	5755 MHz	159	5795 MHz

802.11ac-VHT80/ax-HE80

Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210 MHz	58	5290 MHz	106	5530 MHz
122	5610 MHz	138	5690 MHz	155	5775 MHz

1.7. Antenna Details

Antenna Type	Frequency Band (MHz)	Antenna Gain (dBi)		CDD Directional Gain (dBi)		Beamforming Gain (dBi)
		Ant 0	Ant 1	For Power	For PSD	
Wi-Fi Antennas						
Dipole	2400 ~ 2500	2.52	2.88	2.88	5.89	5.89
	5150 ~ 5250	3.02	3.07	3.07	6.08	6.08
	5250 ~ 5350	2.92	3.00	3.00	6.01	6.01
	5470 ~ 5725	2.94	2.80	2.94	5.95	5.95
	5725 ~ 5895	3.38	3.92	3.92	6.93	6.93

Notes:

1. The EUT supports Cyclic Delay Diversity (CDD) mode., details refer to the table as below.
2. For CDD Mode, directional gain is calculated as follows.

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

• For power spectral density (PSD) measurements on all devices,

Array Gain = 10 log(N_{ANT}/ N_{SS}) dB

• For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB for $N_{ANT} \leq 4$;

3. The information as above is from the antenna report.
4. The EUT also supports Beam Forming mode, and the Beam Forming support 802.11n/ac/ax, not include 802.11a/b/g. Directional gain = G_{ANT} + BF Gain, BF Gain was declared by the applicant.

2. Test Configuration

2.1. Test Mode

CDD Mode
Mode 1: Transmit by 802.11a_N_{SS}=1 (6Mbps)
Mode 2: Transmit by 802.11ac-VHT20_N_{SS}=1 (MCS0)
Mode 3: Transmit by 802.11ac-VHT40_N_{SS}=1 (MCS0)
Mode 4: Transmit by 802.11ac-VHT80_N_{SS}=1 (MCS0)
Mode 5: Transmit by 802.11ax-HE20_N_{SS}=1 (MCS0)
Mode 6: Transmit by 802.11ax-HE40_N_{SS}=1 (MCS0)
Mode 7: Transmit by 802.11ax-HE80_N_{SS}=1 (MCS0)
Notes: 1. For Radiated emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. 2. For CDD mode, this device supports 2 N_{SS} and power level is the same of spatial multiplexing. The worst case is N_{SS}=1. 3. For beamforming operation, the manufacturer automatically reduces power based on a factor calculated as the difference between the beamforming directional gain and the CDD directional power gain. Thus, only the CDD mode was evaluated in this report. 4. All modes of operation and data rates were investigated, so all RF test requirements shall be executed at the worst data rate. 5. 802.11n and 802.11ac have same modulation type and same power value, so we only show 802.11ac test data in report.

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram



Cable Type		Cable Description	Length
A	Power Cable	Non shielded	3.0m
B	LAN Cable	Non shielded, Cat.5e	> 10m
Product		**Manufacturer**	**Model No.**
1	Notebook	Lenovo	E430C

2.3. Test Software

The EUT could transmit via engineer commands, and the commands were provided by the manufacturer.

2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.407
- KDB 789033 D02v02r01
- KDB 662911 D01v02r01
- ANSI C63.10-2013

2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the device is **permanently attached.**
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Active Loop Antenna	Schwarzbeck	FMZB 1519-60 D	MRTSUE07076	1 year	2025-11-19	WJ-AC1
TRILOG Broad Band Antenna	Schwarzbeck	VULB 9163	MRTSUE07096	1 year	2025-04-24 2026-04-16	WJ-AC1
Horn Antenna	ETS	3117	MRTSUE06257	1 year	2025-09-08	WJ-AC1
EMI Test Receiver	R&S	ESR3	MRTSUE07111	1 year	2026-03-24	WJ-AC1
Thermohygrometer	testo	608-H1	MRTSUE11333	1 year	2025-06-24	WJ-AC1
Thermohygrometer	testo	608-H1	MRTSUE11402	1 year	2025-12-01	WJ-AC1
Shielding Control Room	TDK	WJ-SCR1	MRTSUE07116	N/A	N/A	WJ-SCR1
Broadband Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE07100	1 year	2025-04-24 2026-04-10	WJ-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE07103	1 year	2025-04-14 2026-04-09	WJ-AC2
EXA Signal Analyzer	Keysight	N9010B	MRTSUE07148	1 year	2025-05-11	WJ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11315	1 year	2025-06-24	WJ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11332	1 year	2025-06-24	WJ-AC2
Shielding Control Room	TDK	WJ-SCR2	MRTSUE07118	N/A	N/A	WJ-SCR2
USB Power Sensor	Keysight	U2021XA	MRTSUE07141	1 year	2026-03-15	WJ-SR3
Thermohygrometer	testo	608-H1	MRTSUE11331	1 year	2025-06-24	WJ-SR3
Shielding Room	TDK	WJ-SR3	MRTSUE07125	N/A	N/A	WJ-SR3
Signal Analyzer	Keysight	N9020B	MRTSUE07037	1 year	2025-09-03	WJ-SR3
EMI Test Receiver	R&S	ESR3	MRTSUE07112	1 year	2025-04-21 2026-04-19	WJ-SR5
Two-Line V-Network	R&S	ENV216	MRTSUE07201	1 year	2025-05-26	WJ-SR5
Thermohygrometer	testo	608-H1	MRTSUE11317	1 year	2025-06-24	WJ-SR5
Shielding Room	TDK	WJ-SR5	MRTSUE07127	N/A	N/A	WJ-SR5

Software	Version	Function
e3	230711	EMI Test Software
maturo mcApp	9.3.0.5866	RE Antenna & Turntable
BenchVue Power Meter	v3.9	Power

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement
The maximum measurement uncertainty is evaluated as: 9kHz~150kHz: 3.58dB 150kHz~30MHz: 3.20dB
Radiated Emission Measurement
The maximum measurement uncertainty is evaluated as: Coaxial: 9kHz~30MHz: 2.35dB Coplanar: 9kHz~30MHz: 2.37dB Horizontal: 30MHz~200MHz: 3.47dB 200MHz~1GHz: 4.17dB 1GHz~40GHz: 4.97dB Vertical: 30MHz~200MHz: 4.07dB 200MHz~1GHz: 5.28dB 1GHz~40GHz: 4.84dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 2.5dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 1.5dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 2.5dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 3.2%

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.407(a)	26dB Bandwidth	Conducted	Pass
15.407(e)	6dB Bandwidth		Pass
15.407(a)(1)(ii), (2), (3)(i)	Maximum Conducted Output Power		Pass
15.407(h)(1)	Transmit Power Control		Pass
15.407(g)	Frequency Stability		N/A
15.407(a)(1)(ii), (2), (3)(i), (13)	Peak Power Spectral Density		Pass
15.407(h)(2)	Dynamic Frequency Selection (DFS)		Pass Remark 3
15.407(b)(1), (2), (3), (4)(i)	Undesirable Emissions	Radiated	Pass
15.205, 15.209 15.407(b)(8), (9), (10)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)		Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Remark:

1. The analyzer plots shown in this section were captured using a correction table to account for cable and attenuator losses in the system connecting the EUT to the analyzer across relevant frequencies.
2. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.
3. DFS report refers to R25S1052031-U203.
4. “N/A” means that the test item is not applicable, and the detailed information refers to relevant section.

6.2. 26dB & 99% Bandwidth Measurement

6.2.1. Test Limit

N/A

6.2.2. Test Procedure

KDB 789033 D02v02r01- Section II)C)1) (26dB Bandwidth)

KDB 789033 D02v02r01- Section II)D) (99% Bandwidth)

6.2.3. Test Setting

26dB Bandwidth

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth
2. RBW = approximately 1% of the emission bandwidth.
3. VBW > RBW
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

99% Bandwidth

1. Set center frequency to the nominal EUT channel center frequency.
2. RBW = 1% to 5% of the OBW
3. VBW ≥ 3 × RBW
4. Span = 1.5 times to 5 times the OBW
5. Detector = peak
6. Trace mode = max hold
7. Allow the trace to stabilize
8. Use the 99% power bandwidth function of the instrument.

6.2.4. Test Setup



6.2.5. Test Result

Refer to Appendix A.2.

6.3. 6dB Bandwidth Measurement

6.3.1. Test Limit

The minimum 6dBbandwidth shall be at least 500 kHz.

6.3.2. Test Procedure

KDB 789033 D02v02r01- Section II)C)2)

6.3.3. Test Setting

1. Set center frequency to the nominal EUT channel center frequency.
2. RBW = 100 kHz.
3. VBW ≥ 3 × RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.3.

6.4. Output Power Measurement

6.4.1. Test Limit

For the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm).

If transmitting antennas of directional gain greater than 6dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

6.4.2. Test Procedure

KDB 789033D02v02r01- Section Ⅱ)E)3)b) Method PM-G

6.4.3. Test Setting

<u>Average Power Measurement</u>

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. Transmit Power Control Measurement

6.5.1. Test Limit

The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30 dBm.

6.5.2. Test Procedure

KDB 789033 D02v02r01- Section Ⅱ)E)3)b) Method PM-G

6.5.3. Test Setting

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

6.5.4. Test Setup



6.5.5. Test Result

Device supports TPC mechanism, details refer to the operational description.

6.6. Power Spectral Density Measurement

6.6.1. Test Limit

For the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

6.6.2. Test Procedure

KDB 789033 D02v02r01-Section Ⅱ)F)

6.6.3. Test Setting

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire 26dB EBW of the signal.
3. RBW = 1MHz (510kHz, if measurement bandwidth of Maximum PSD is specified in 500 kHz)
4. VBW = 3 × RBW
5. Number of sweep points ≥ 2 × (span / RBW)
6. Detector = power averaging (Average)
7. Sweep time = auto
8. Trigger = free run
9. Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter.
10. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
11. Add 10*log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add 10*log(1/0.25) = 6 dB if the duty cycle is 25 percent.

6.6.4. Test Setup



6.6.5. Test Result

Refer to Appendix A.5.

6.7. Frequency Stability Measurement

6.7.1. Test Limit

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

6.7.2. Test Procedure

Frequency Stability Under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to highest. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C decreased per stage until the lowest temperature reached.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation (±15%) and endpoint, recordthe maximum frequency change.

6.7.3. Test Setup



6.7.4. Test Result

Grantee ensure that the product meets e-CFR Title 47 section 15.407(g) and KDB 789033 D02v02r01 frequency stability such that the emissions are maintained within the band of operation under all conditions of normal operation as specified in the user's manual. So this test item is not applicable.

6.8. Radiated Spurious Emission Measurement

6.8.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [μV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.8.2. Test Procedure

KDB 789033 D02v02r01- Section II)G)

6.8.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; if the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10Hz

   If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration.
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

6.8.4. Test Setup

Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.8.5. Test Result

Refer to Appendix A.6.

6.9. Radiated Restricted Band Edge Measurement

6.9.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1] 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])
13.36 - 13.41	--	--	--

For 15.407(b) requirement:

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Refer to KDB 789033 D02v02r01 G)2)c), as specified in § 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a maximum emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in § 15.407(b)(4)). However, an out-of-band emission that complies with both the peak and average limits of § 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz maximum emission limit.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [μV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.9.2. Test Procedure

KDB 789033 D02v02r01- Section II)G)

6.9.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10 Hz.

   If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration.
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

6.9.4. Test Setup



6.9.5. Test Result

Refer to Appendix A.7.

6.10. AC Conducted Emissions Measurement

6.10.1. Test Limit

FCC Part 15.207 Limits		
Frequency (MHz)	QP (dBμV)	AV (dBμV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50
Note 1: The lower limit shall apply at the transition frequencies. Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.		

6.10.2. Test Setup



6.10.3. Test Result

Refer to Appendix A.8.

Appendix A – Test Result

A.1 Duty Cycle Test Result

Test Site	WJ-SR3	Test Engineer	Jake Lan
Test Date	2025-03-28		

Test Mode	Duty Cycle	Test Mode	Duty Cycle
802.11a	92.83%	802.11ax-HE20	90.46%
802.11ac-VHT20	92.45%	802.11ax-HE40	83.33%
802.11ac-VHT40	85.93%	802.11ax-HE80	73.01%
802.11ac-VHT80	75.19%	--	--

Duty Cycle (T = Transmission Duration)

802.11a (T = 1.359ms)



802.11ac-VHT20 (T = 1.274ms)



802.11ac-VHT40 (T = 634.6μs)



802.11ac-VHT80 (T = 315.2μs)



Duty Cycle (T = Transmission Duration)	
802.11ax-HE20 (T = 986.0μs)	802.11ax-HE40 (T = 519.3μs)
	
802.11ax-HE80 (T = 279.2μs)	
	

A.2 26dB Bandwidth Test Result

Test Site	WJ-SR3	Test Engineer	Jake Lan
Test Date	2025-04-08 ~ 2025-04-18		

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
11a	6Mbps	36	5180	18.01	16.201
11a	6Mbps	44	5220	35.25	19.257
11a	6Mbps	48	5240	35.23	19.495
11a	6Mbps	52	5260	18.14	16.188
11a	6Mbps	60	5300	18.04	16.195
11a	6Mbps	64	5320	18.08	16.186
11a	6Mbps	100	5500	18.04	16.188
11a	6Mbps	116	5580	18.13	16.209
11a	6Mbps	140	5700	18.06	16.180
11a	6Mbps	144	5720	18.12	16.195
11a	6Mbps	149	5745	35.47	19.573
11a	6Mbps	157	5785	35.83	19.088
11a	6Mbps	165	5825	35.61	19.979
11ac-VHT20	MCS0	36	5180	18.85	17.343
11ac-VHT20	MCS0	44	5220	35.05	19.691
11ac-VHT20	MCS0	48	5240	35.67	18.507
11ac-VHT20	MCS0	52	5260	18.93	17.360
11ac-VHT20	MCS0	60	5300	18.85	17.374
11ac-VHT20	MCS0	64	5320	18.92	17.346
11ac-VHT20	MCS0	100	5500	18.92	17.341
11ac-VHT20	MCS0	116	5580	18.85	17.355
11ac-VHT20	MCS0	140	5700	18.68	17.397
11ac-VHT20	MCS0	144	5720	18.97	17.412
11ac-VHT20	MCS0	149	5745	37.19	19.539
11ac-VHT20	MCS0	157	5785	37.21	19.097
11ac-VHT20	MCS0	165	5825	37.25	19.875

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
11ac-VHT40	MCS0	38	5190	38.42	35.689
11ac-VHT40	MCS0	46	5230	75.98	36.756
11ac-VHT40	MCS0	54	5270	38.18	35.860
11ac-VHT40	MCS0	62	5310	38.14	35.744
11ac-VHT40	MCS0	102	5510	38.22	35.729
11ac-VHT40	MCS0	110	5550	38.06	35.886
11ac-VHT40	MCS0	134	5670	38.09	35.789
11ac-VHT40	MCS0	142	5710	38.03	35.857
11ac-VHT40	MCS0	151	5755	75.18	37.409
11ac-VHT40	MCS0	159	5795	76.81	37.380
11ac-VHT80	MCS0	42	5210	80.53	74.952
11ac-VHT80	MCS0	58	5290	81.06	74.914
11ac-VHT80	MCS0	106	5530	81.03	74.917
11ac-VHT80	MCS0	122	5610	81.14	75.016
11ac-VHT80	MCS0	138	5690	142.8	76.533
11ac-VHT80	MCS0	155	5775	81.48	75.168
11ax-HE20	MCS0	36	5180	19.82	18.706
11ax-HE20	MCS0	44	5220	35.80	19.243
11ax-HE20	MCS0	48	5240	34.53	19.572
11ax-HE20	MCS0	52	5260	19.93	18.714
11ax-HE20	MCS0	60	5300	19.80	18.762
11ax-HE20	MCS0	64	5320	19.98	18.718
11ax-HE20	MCS0	100	5500	19.67	18.754
11ax-HE20	MCS0	116	5580	19.97	18.688
11ax-HE20	MCS0	140	5700	19.94	18.688
11ax-HE20	MCS0	144	5720	19.98	18.704
11ax-HE20	MCS0	149	5745	37.41	19.154
11ax-HE20	MCS0	157	5785	38.93	19.615
11ax-HE20	MCS0	165	5825	38.37	19.402

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
11ax-HE40	MCS0	38	5190	39.53	37.185
11ax-HE40	MCS0	46	5230	73.88	39.515
11ax-HE40	MCS0	54	5270	39.69	37.294
11ax-HE40	MCS0	62	5310	39.57	37.213
11ax-HE40	MCS0	102	5510	39.39	37.375
11ax-HE40	MCS0	110	5550	39.38	37.355
11ax-HE40	MCS0	134	5670	39.58	37.221
11ax-HE40	MCS0	142	5710	39.70	37.250
11ax-HE40	MCS0	151	5755	73.35	39.363
11ax-HE40	MCS0	159	5795	72.58	37.998
11ax-HE80	MCS0	42	5210	80.41	76.618
11ax-HE80	MCS0	58	5290	80.15	76.339
11ax-HE80	MCS0	106	5530	80.41	76.596
11ax-HE80	MCS0	122	5610	80.41	76.483
11ax-HE80	MCS0	138	5690	110.8	76.995
11ax-HE80	MCS0	155	5775	81.32	76.710

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	F_H (MHz)	Limit (MHz)
802.11a	6Mbps	48	5240	5249.75	< 5250
802.11ac-VHT20	MCS0	48	5240	5249.25	< 5250
802.11ac-VHT40	MCS0	46	5230	5248.38	< 5250
802.11ac-VHT80	MCS0	42	5210	5247.48	< 5250
802.11ax-HE20	MCS0	48	5240	5249.79	< 5250
802.11ax-HE40	MCS0	46	5230	5249.76	< 5250
802.11ax-HE80	MCS0	42	5210	5248.31	< 5250

Note: F_H = Centre frequency + 99% OBW / 2.

For example, 802.11a 5240MHz, F_H = 5240 MHz + 19.495 MHz / 2 = 5249.75 MHz.

802.11a 26dB Bandwidth & 99% Bandwidth

Channel 36 (5180MHz)



Channel 44 (5220MHz)

Channel 48 (5240MHz)



Channel 52 (5260MHz)



Channel 60 (5300MHz)

Channel 64 (5320MHz)



Channel 100 (5500MHz)



Channel 116 (5580MHz)



802.11a 26dB Bandwidth & 99% Bandwidth	
Channel 140 (5700MHz)	Channel 144(5720MHz)
	
Channel 149 (5745MHz)	Channel 157 (5785MHz)
	
Channel 165 (5825MHz)	

802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth

Channel 36 (5180MHz)



Channel 44 (5220MHz)

Channel 48 (5240MHz)



Channel 52 (5260MHz)

Channel 60 (5300MHz)



Channel 64 (5320MHz)

Channel 100 (5500MHz)



Channel 116 (5580MHz)

802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth

Channel 140 (5700MHz)



Channel 144(5720MHz)



Channel 149 (5745MHz)



Channel 157 (5785MHz)

Channel 165 (5825MHz)

802.11ac-VHT40 26dB Bandwidth & 99% Bandwidth

Channel 38 (5190MHz)



Channel 46 (5230MHz)

Channel 54 (5270MHz)



Channel 62 (5310MHz)

Channel 102 (5510MHz)



Channel 110 (5550MHz)



Channel 134 (5670MHz)



Channel 142(5710MHz)



802.11ac-VHT40 26dB Bandwidth & 99% Bandwidth	
Channel 151 (5755MHz)	Channel 159 (5795MHz)

802.11ac-VHT80 26dB Bandwidth & 99% Bandwidth	
Channel 42 (5210MHz)	Channel 58 (5290MHz)
	
Channel 106 (5530MHz)	Channel 122 (5610MHz)
	
Channel 138 (5690MHz)	Channel 155 (5775MHz)
	

802.11ax-HE20 26dB Bandwidth & 99% Bandwidth

Channel 36 (5180MHz)



Channel 44 (5220MHz)

Channel 48 (5240MHz)

Channel 52 (5260MHz)

Channel 60 (5300MHz)



Channel 64 (5320MHz)

Channel 100 (5500MHz)



Channel 116 (5580MHz)

802.11ax-HE20 26dB Bandwidth & 99% Bandwidth	
Channel 140 (5700MHz)	Channel 144(5720MHz)
	
Channel 149 (5745MHz)	Channel 157 (5785MHz)
Channel 165 (5825MHz)	

802.11ax-HE40 26dB Bandwidth & 99% Bandwidth

Channel 38 (5190MHz)



Channel 46 (5230MHz)



Channel 54 (5270MHz)



Channel 62 (5310MHz)



Channel 102 (5510MHz)



Channel 110 (5550MHz)



Channel 134 (5670MHz)



Channel 142(5710MHz)