FCC TEST REPORT
FCC ID: 2BH85-NVG-A01

Report Number.....:	**ZKT-240820L10198E**
Date of Test.....:	July 26, 2024 to Aug. 20, 2024
Date of issue.....:	Aug. 23, 2024
Test Result..... :	PASS
Testing Laboratory.....:	**Shenzhen ZKT Technology Co., Ltd.**
Address ..... :	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Applicant's name .....:	**Shenzhen Bingyuan Technology Co.,LTD**
Address ..... :	No. 6 Shengdelan Electric Co. , Ltd. . Workshop 1403, Kukeng community, Guanlan Street, Longhua District, Shenzhen City
Manufacturer's name .....:	**Shenzhen Bingyuan Technology Co.,LTD**
Address ..... :	No. 6 Shengdelan Electric Co. , Ltd. . Workshop 1403, Kukeng community, Guanlan Street, Longhua District, Shenzhen City
Test specification:	
Standard.....:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Test procedure.....:	KDB558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10:2013
Non-standard test method .....:	N/A

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name.....:	**Night Vision Goggles**
Trademark .....:	/
Model/Type reference..... :	NVG-A01, NVG-A02, BY-01, BY-02, NV-B01, NV-B02, NV-A08, NV-A8, NV-B9, NV-C9, V-A80, NV-B90, NV-C90
Model Difference.....:	NVG-A01 is tested model, other models are derivative models . The models are identical in circuit, only different on the model names. So the test data of NVG-A01 can represent the remaining models.
Ratings..... :	Input: DC 5 V or DC 7.2 V by battery

Testing procedure and testing location:

Testing Laboratory.....:	**Shenzhen ZKT Technology Co., Ltd.**
Address.....:	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Tested by (name + signature).....:	Jim Liu
Reviewer (name + signature).....:	Tom Zou
Approved (name + signature).....:	Lake Xie

Table of Contents

Page

1. VERSION 5
2. SUMMARY OF TEST RESULTS 6
   2.1 TEST FACILITY 7
   2.2 MEASUREMENT UNCERTAINTY 7
3. GENERAL INFORMATION 8
   3.1 GENERAL DESCRIPTION OF EUT 8
   3.2 DESCRIPTION OF TEST MODES 9
   3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 10
   3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 10
   3.5EQUIPMENTS LIST FOR ALL TEST ITEMS 11
4. EMC EMISSION TEST 13
   4.1 CONDUCTED EMISSION MEASUREMENT 13
      4.1.1 POWER LINE CONDUCTED EMISSION Limits 13
      4.1.2 TEST PROCEDURE 13
      4.1.3 DEVIATION FROM TEST STANDARD 13
      4.1.4 TEST SETUP 14
      4.1.5 EUT OPERATING CONDITIONS 14
   4.2 RADIATED EMISSION MEASUREMENT 17
      4.2.1 RADIATED EMISSION LIMITS 17
      4.2.2 TEST PROCEDURE 17
      4.2.3 DEVIATION FROM TEST STANDARD 18
      4.2.4 TEST SETUP 18
      4.2.5 EUT OPERATING CONDITIONS 19
      4.2.6 TEST RESULTS 19
5. RADIATED BAND EMISSIONMEASUREMENT 24
   5.1 TEST REQUIREMENT: 24
   5.2 TEST PROCEDURE 24
   5.3 DEVIATION FROM TEST STANDARD 24
   5.4 TEST SETUP 25
   5.5 EUT OPERATING CONDITIONS 25
   5.6 TEST RESULT 26
6. POWER SPECTRAL DENSITY TEST 28
   6.1 APPLIED PROCEDURES / LIMIT 28
   6.2 TEST PROCEDURE 28
   6.3 DEVIATION FROM STANDARD 28
   6.4 TEST SETUP 28
   6.5 EUT OPERATION CONDITIONS 29

6.6 TEST RESULT 29
7. CHANNEL BANDWIDTH 30
7.1 APPLIED PROCEDURES / LIMIT 30
7.2 TEST PROCEDURE 30
7.3 DEVIATION FROM STANDARD 30
7.4 TEST SETUP 30
7.5 EUT OPERATION CONDITIONS 30
7.6 TEST RESULT 31
8. OUTPUT POWER TEST 32
8.1 APPLIED PROCEDURES/LIMIT 32
8.2 TEST PROCEDURE 32
8.3 DEVIATION FROM STANDARD 32
8.4 TEST SETUP 32
8.5 EUT OPERATION CONDITIONS 32
8.6 TEST RESULT 32
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION 33
9.1 APPLICABLE STANDARD 33
9.2 TEST PROCEDURE 33
9.3 DEVIATION FROM STANDARD 33
9.4 TEST SETUP 33
9.5 EUT OPERATION CONDITIONS 33
9.6 TEST RESULTS 33
10. ANTENNA REQUIREMENT 34
11. APPENDIX A 35
11.1 DUTY CYCLE 35
11.2 MAXIMUM AVERAGE CONDUCTED OUTPUT POWER 42
11.3 -6DB BANDWIDTH 49
11.4 OCCUPIED CHANNEL BANDWIDTH 56
11.5 MAXIMUM POWER SPECTRAL DENSITY LEVEL 63
11.6 BAND EDGE 70
11.7 CONDUCTED RF SPURIOUS EMISSION 79
12. TEST SETUP PHOTO 92
13. EUT CONSTRUCTIONAL DETAILS 92

1. VERSION

Report No.	Version	Description	Approved
ZKT-240820L10198E	Rev.01	Initial issue of report	Aug. 23, 2024

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (b)(4)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Output Power	PASS	
FCC part 15.247 (a)(2)	Channel Bandwidth	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1) ” N/A” denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U · where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2 · providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF conducted power	±0.16dB
3	Conducted spurious emissions	±0.21dB
4	All radiated emissions (9k-30MHz)	±4.68dB
5	All radiated emissions (<1G)	±4.68dB
6	All radiated emissions (>1G)	±4.89dB
7	Temperature	±0.5°C
8	Humidity	±2%
9	Occupied Bandwidth	±4.96%

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Night Vision Goggles
Test Model No.:	NVG-A01
Hardware Version:	V1.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Channel numbers:	802.11b/802.11g /802.11n(HT20):11, /802.11n(HT40):7
Operation Frequency:	802.11b/802.11g /802.11n(HT20): 2412-2462MHz/802.11n(HT40): 2422-2452MHz
Channel separation:	5MHz
Modulation technology:	IEEE 802.11b: DQPSK/DBPSK/DSSS/CCK IEEE 802.11g: QPSK/BPSK/16QAM/64QAM/OFDM IEEE 802.11n: QPSK/BPSK/16QAM/64QAM/OFDM
Antenna Type:	PCB Antenna
Antenna gain:	1.29dBi
Power supply:	Input: DC 5 V or DC 7.2 V by battery

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	**Frequency (MHz)**
	802.11b/802.11g/802.11n(HT20)
Lowest channel	2412MHz
Middle channel	2437MHz
Highest channel	2462MHz

Test channel	**Frequency (MHz)**
	802.11n(HT40)
Lowest channel	2422MHz
Middle channel	2437MHz
Highest channel	2452MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: EUT use new battery during the test,the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	13.5Mbps

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Emission



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Adapter	N/A	HW-059200CHQ	N/A	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	A.17.05	Nov. 02, 2023	Nov. 01, 2024
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Nov. 02, 2023	Nov. 01, 2024
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	100969	4.32	Nov. 02, 2023	Nov. 01, 2024
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	N/A	Nov. 13, 2023	Nov. 12, 2024
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	N/A	Nov. 13, 2023	Nov. 12, 2024
6	Horn Antenna (15GHz-40GHz)	A.H.System	SAS-574	588	N/A	Nov. 13, 2023	Nov. 12, 2024
7	Loop Antenna	TESEQ	HLA6121	58357	N/A	Nov. 16, 2023	Nov. 15, 2024
8	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	60747	N/A	Nov. 02, 2023	Nov. 01, 2024
9	Amplifier (1GHz-26.5GHz)	HuiPu	8449B	3008A00315	N/A	Nov. 02, 2023	Nov. 01, 2024
10	Amplifier (500MHz-40GHz)	QuanJuDa	DLE-161	097	N/A	Nov. 02, 2023	Nov. 01, 2024
11	Test Cable	N/A	R-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
12	Test Cable	N/A	R-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
13	Test Cable	N/A	R-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
14	Test Cable	N/A	RF-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
15	Test Cable	N/A	RF-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
16	Test Cable	N/A	RF-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
17	ESG Signal Generator	Agilent	E4421B	N/A	B.03.84	Nov. 02, 2023	Nov. 01, 2024
18	Signal Generator	Agilent	N5182A	N/A	A.01.87	Nov. 02, 2023	Nov. 01, 2024
19	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	N/A	Nov. 16, 2023	Nov. 15, 2024
20	Wideband Radio Communication Test	R&S	CMW500	106504	V 3.7.22	Nov. 02, 2023	Nov. 01, 2024
21	MWRF Power Meter Test system	MW	MW100-RF CB	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
22	D.C. Power Supply	LongWei	TPR-6405D	N/A	N/A	\	\
23	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	N/A	\	\
24	RF Software	MW	MTS8310	V2.0.0.0	N/A	\	\
25	Turntable	MF	MF-7802BS	N/A	N/A	\	\
26	Antenna tower	MF	MF-7802BS	N/A	N/A	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	N/A	Nov. 14, 2023	Nov. 13, 2024
2	LISN	CYBERTEK	EM5040A	E1850400149	N/A	Nov. 02, 2023	Nov. 01, 2024
3	Test Cable	N/A	C-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
4	Test Cable	N/A	C-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
5	Test Cable	N/A	C-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
6	EMI Test Receiver	R&S	ESCI3	101393	4.42 SP3	Nov. 02, 2023	Nov. 01, 2024
7	Triple-Loop Antenna	N/A	RF300	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
8	Absorbing Clamp	DZ	ZN23201	15034	N/A	Nov. 07, 2023	Nov. 06, 2024
9	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	N/A	\	\

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 Test result

Temperature:	24.3℃	Relative Humidity :	50%
Pressure:	101kPa	Phase :	L
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1635	33.87	9.90	43.77	65.28	-21.51	QP	P	
2	0.1635	19.50	9.90	29.40	55.28	-25.88	AVG	P	
3	0.1814	31.63	9.90	41.53	64.42	-22.89	QP	P	
4	0.1814	16.52	9.90	26.42	54.42	-28.00	AVG	P	
5	0.2353	28.54	9.92	38.46	62.26	-23.80	QP	P	
6	0.2353	13.61	9.92	23.53	52.26	-28.73	AVG	P	
7	0.4515	26.44	10.01	36.45	56.85	-20.40	QP	P	
8	0.4515	16.08	10.01	26.09	46.85	-20.76	AVG	P	
9	0.6225	21.46	10.03	31.49	56.00	-24.51	QP	P	
10	0.6225	6.74	10.03	16.77	46.00	-29.23	AVG	P	
11 *	15.1753	30.88	10.10	40.98	60.00	-19.02	QP	P	
12	15.1753	20.65	10.10	30.75	50.00	-19.25	AVG	P	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor
4.The test data shows only the worst case 802.11b mode (Low Channel:2412MHz).

Temperature:	24.3℃	Relative Humidity :	50%
Pressure:	101kPa	Phase :	N
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1590	35.37	9.89	45.26	65.52	-20.26	QP	P	
2	0.1590	22.22	9.89	32.11	55.52	-23.41	AVG	P	
3	0.1770	33.46	9.90	43.36	64.63	-21.27	QP	P	
4	0.1770	17.00	9.90	26.90	54.63	-27.73	AVG	P	
5	0.2040	30.98	9.91	40.89	63.45	-22.56	QP	P	
6	0.2040	16.64	9.91	26.55	53.45	-26.90	AVG	P	
7	0.3255	25.50	9.96	35.46	59.57	-24.11	QP	P	
8	0.3255	15.11	9.96	25.07	49.57	-24.50	AVG	P	
9	0.4290	25.38	9.99	35.37	57.27	-21.90	QP	P	
10	0.4290	22.49	9.99	32.48	47.27	-14.79	AVG	P	
11	0.4605	28.44	10.01	38.45	56.68	-18.23	QP	P	
12 *	0.4605	22.06	10.01	32.07	46.68	-14.61	AVG	P	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor
4.The test data shows only the worst case 802.11b mode (Low Channel:2412MHz).

4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoiccamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of avariable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).
h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature :	25.1℃	Relative Humidity :	50%
Pressure :	101kPa	Polarization :	Horizontal
Test Voltage :	DC 7.2V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	99.8777	39.14	-10.95	28.19	43.50	-15.31	QP
2	566.6221	41.91	-2.87	39.04	46.00	-6.96	QP
3 *	721.7258	41.71	-0.36	41.35	46.00	-4.65	QP
4	744.8660	39.47	-0.06	39.41	46.00	-6.59	QP
5	815.9678	36.76	0.92	37.68	46.00	-8.32	QP
6	929.0081	32.95	2.45	35.40	46.00	-10.60	QP

Temperature :	25.1℃	Relative Humidity :	50%
Pressure :	101kPa	Polarization :	Vertical
Test Voltage :	DC 7.2V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	99.8777	39.79	-10.95	28.84	43.50	-14.66	QP
2	300.3672	42.43	-8.03	34.40	46.00	-11.60	QP
3	566.6221	38.66	-2.87	35.79	46.00	-10.21	QP
4 *	625.0780	37.77	-1.85	35.92	46.00	-10.08	QP
5	721.7258	34.44	-0.36	34.08	46.00	-11.92	QP
6	912.8620	32.24	2.31	34.55	46.00	-11.45	QP

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2.The emission levels of other frequencies are very lower than the limit and not show in test report.
3.The test data shows only the worst case 802.11b mode (Low Channel:2412MHz).

1GHz~25GHz

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
802.11b									
Low Channel:2412MHz									
V	4824.00	57.82	30.55	5.77	24.66	57.7	74	-16.3	PK
V	4824.00	41.45	30.55	5.77	24.66	41.33	54	-12.67	AV
H	4824.00	56.67	30.33	6.32	24.55	57.21	74	-16.79	PK
H	4824.00	44.74	30.33	6.32	24.55	45.28	54	-8.72	AV
Middle Channel:2437MHz									
V	4874.00	57.24	30.55	5.77	24.66	57.12	74	-16.88	PK
V	4874.00	44.63	30.55	5.77	24.66	44.51	54	-9.49	AV
H	4874.00	58.75	30.33	6.32	24.55	59.29	74	-14.71	PK
H	4874.00	43.99	30.33	6.32	24.55	44.53	54	-9.47	AV
High Channel:2462MHz									
V	4924.00	58.81	30.55	5.77	24.66	58.69	74	-15.31	PK
V	4924.00	41.68	30.55	5.77	24.66	41.56	54	-12.44	AV
H	4924.00	58.35	30.33	6.32	24.55	58.89	74	-15.11	PK
H	4924.00	43.26	30.33	6.32	24.55	43.8	54	-10.2	AV
802.11g									
Low Channel:2412MHz									
V	4824.00	56.41	30.55	5.77	24.66	56.29	74	-17.71	PK
V	4824.00	41.38	30.55	5.77	24.66	41.26	54	-12.74	AV
H	4824.00	57.95	30.33	6.32	24.55	58.49	74	-15.51	PK
H	4824.00	41.65	30.33	6.32	24.55	42.19	54	-11.81	AV
Middle Channel:2437MHz									
V	4874.00	56.36	30.55	5.77	24.66	56.24	74	-17.76	PK
V	4874.00	41.48	30.55	5.77	24.66	41.36	54	-12.64	AV
H	4874.00	56.06	30.33	6.32	24.55	56.6	74	-17.4	PK
H	4874.00	42.82	30.33	6.32	24.55	43.36	54	-10.64	AV
High Channel:2462MHz									
V	4924.00	55.17	30.55	5.77	24.66	55.05	74	-18.95	PK
V	4924.00	43.8	30.55	5.77	24.66	43.68	54	-10.32	AV
H	4924.00	56.67	30.33	6.32	24.55	57.21	74	-16.79	PK
H	4924.00	42.76	30.33	6.32	24.55	43.3	54	-10.7	AV
802.11n 20									
Low Channel:2412MHz									
V	4824.00	56.29	30.55	5.77	24.66	56.17	74	-17.83	PK
V	4824.00	44.93	30.55	5.77	24.66	44.81	54	-9.19	AV
H	4824.00	58.2	30.33	6.32	24.55	58.74	74	-15.26	PK
H	4824.00	41.67	30.33	6.32	24.55	42.21	54	-11.79	AV
Middle Channel:2437MHz									
V	4874.00	58.56	30.55	5.77	24.66	58.44	74	-15.56	PK
V	4874.00	44.85	30.55	5.77	24.66	44.73	54	-9.27	AV
H	4874.00	59.28	30.33	6.32	24.55	59.82	74	-14.18	PK
H	4874.00	42.15	30.33	6.32	24.55	42.69	54	-11.31	AV
High Channel:2462MHz									
V	4924.00	59	30.55	5.77	24.66	58.88	74	-15.12	PK
V	4924.00	41.28	30.55	5.77	24.66	41.16	54	-12.84	AV
H	4924.00	58.72	30.33	6.32	24.55	59.26	74	-14.74	PK
H	4924.00	44.49	30.33	6.32	24.55	45.03	54	-8.97	AV
802.11n 40									
Low Channel:2422MHz									
V	4844.00	55.59	30.55	5.77	24.66	55.47	74	-18.53	PK

V	4924.00	41.78	30.55	5.77	24.66	41.66	54	-12.34	AV
H	4924.00	59.9	30.33	6.32	24.55	60.44	74	-13.56	PK
H	4924.00	41.86	30.33	6.32	24.55	42.4	54	-11.6	AV
Middle Channel:2437MHz									
V	4874.00	57.45	30.55	5.77	24.66	57.33	74	-16.67	PK
V	4874.00	41.45	30.55	5.77	24.66	41.33	54	-12.67	AV
H	4874.00	55.83	30.33	6.32	24.55	56.37	74	-17.63	PK
H	4874.00	43.58	30.33	6.32	24.55	44.12	54	-9.88	AV
High Channel:2452MHz									
V	4904.00	55.14	30.55	5.77	24.66	55.02	74	-18.98	PK
V	4904.00	43.6	30.55	5.77	24.66	43.48	54	-10.52	AV
H	4904.00	55.92	30.33	6.32	24.55	56.46	74	-17.54	PK
H	4904.00	42.23	30.33	6.32	24.55	42.77	54	-11.23	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4.For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.

5. RADIATED BAND EMISSIONMEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
802.11b	LowChannel 2412MHz										
	H	2390.00	60.21	30.22	4.85	23.98	58.82	74.00	-15.18	PK	PASS
	H	2390.00	48.61	30.22	4.85	23.98	47.22	54.00	-6.78	AV	PASS
	H	2400.00	59.05	30.22	4.85	23.98	57.66	74.00	-16.34	PK	PASS
	H	2400.00	47.50	30.22	4.85	23.98	46.11	54.00	-7.89	AV	PASS
	V	2390.00	62.10	30.22	4.85	23.98	60.71	74.00	-13.29	PK	PASS
	V	2390.00	47.83	30.22	4.85	23.98	46.44	54.00	-7.56	AV	PASS
	V	2400.00	60.24	30.22	4.85	23.98	58.85	74.00	-15.15	PK	PASS
	V	2400.00	46.06	30.22	4.85	23.98	44.67	54.00	-9.33	AV	PASS
	High Channel 2462MHz										
	H	2483.50	59.61	30.22	4.85	23.98	58.22	74.00	-15.78	PK	PASS
	H	2483.50	48.44	30.22	4.85	23.98	47.05	54.00	-6.95	AV	PASS
	H	2500.00	60.02	30.22	4.85	23.98	58.63	74.00	-15.37	PK	PASS
	H	2500.00	46.56	30.22	4.85	23.98	45.17	54.00	-8.83	AV	PASS
	V	2483.50	61.45	30.22	4.85	23.98	60.06	74.00	-13.94	PK	PASS
	V	2483.50	47.65	30.22	4.85	23.98	46.26	54.00	-7.74	AV	PASS
	V	2500.00	61.39	30.22	4.85	23.98	60.00	74.00	-14.00	PK	PASS
	V	2500.00	46.05	30.22	4.85	23.98	44.66	54.00	-9.34	AV	PASS
802.11g	Low Channel 2412MHz										
	H	2390.00	61.19	30.22	4.85	23.98	59.80	74.00	-14.20	PK	PASS
	H	2390.00	48.23	30.22	4.85	23.98	46.84	54.00	-7.16	AV	PASS
	H	2400.00	59.09	30.22	4.85	23.98	57.70	74.00	-16.30	PK	PASS
	H	2400.00	46.87	30.22	4.85	23.98	45.48	54.00	-8.52	AV	PASS
	V	2390.00	61.90	30.22	4.85	23.98	60.51	74.00	-13.49	PK	PASS
	V	2390.00	48.98	30.22	4.85	23.98	47.59	54.00	-6.41	AV	PASS
	V	2400.00	62.35	30.22	4.85	23.98	60.96	74.00	-13.04	PK	PASS
	V	2400.00	46.10	30.22	4.85	23.98	44.71	54.00	-9.29	AV	PASS
	High Channel 2462MHz										
	H	2483.50	61.66	30.22	4.85	23.98	60.27	74.00	-13.73	PK	PASS
	H	2483.50	48.92	30.22	4.85	23.98	47.53	54.00	-6.47	AV	PASS
	H	2500.00	61.00	30.22	4.85	23.98	59.61	74.00	-14.39	PK	PASS
	H	2500.00	47.52	30.22	4.85	23.98	46.13	54.00	-7.87	AV	PASS
	V	2483.50	60.23	30.22	4.85	23.98	58.84	74.00	-15.16	PK	PASS
	V	2483.50	48.97	30.22	4.85	23.98	47.58	54.00	-6.42	AV	PASS
	V	2500.00	62.71	30.22	4.85	23.98	61.32	74.00	-12.68	PK	PASS
	V	2500.00	48.65	30.22	4.85	23.98	47.26	54.00	-6.74	AV	PASS
802.11n20	Low Channel 2412MHz										
	H	2390.00	60.30	30.22	4.85	23.98	58.91	74.00	-15.09	PK	PASS
	H	2390.00	46.34	30.22	4.85	23.98	44.95	54.00	-9.05	AV	PASS
	H	2400.00	61.75	30.22	4.85	23.98	60.36	74.00	-13.64	PK	PASS
	H	2400.00	48.11	30.22	4.85	23.98	46.72	54.00	-7.28	AV	PASS
	V	2390.00	62.18	30.22	4.85	23.98	60.79	74.00	-13.21	PK	PASS
	V	2390.00	46.38	30.22	4.85	23.98	44.99	54.00	-9.01	AV	PASS
	V	2400.00	62.29	30.22	4.85	23.98	60.90	74.00	-13.10	PK	PASS
	V	2400.00	46.19	30.22	4.85	23.98	44.80	54.00	-9.20	AV	PASS
	High Channel 2462MHz										
	H	2483.50	60.40	30.22	4.85	23.98	59.01	74.00	-14.99	PK	PASS
	H	2483.50	47.65	30.22	4.85	23.98	46.26	54.00	-7.74	AV	PASS
	H	2500.00	59.94	30.22	4.85	23.98	58.55	74.00	-15.45	PK	PASS
	H	2500.00	48.66	30.22	4.85	23.98	47.27	54.00	-6.73	AV	PASS
	V	2483.50	59.78	30.22	4.85	23.98	58.39	74.00	-15.61	PK	PASS

	V	2483.50	46.91	30.22	4.85	23.98	45.52	54.00	-8.48	AV	PASS
	V	2500.00	61.20	30.22	4.85	23.98	59.81	74.00	-14.19	PK	PASS
	V	2500.00	48.73	30.22	4.85	23.98	47.34	54.00	-6.66	AV	PASS
802.11n 40	Low Channel 2422MHz										
	H	2390.00	61.73	30.22	4.85	23.98	60.34	74.00	-13.66	PK	PASS
	H	2390.00	46.01	30.22	4.85	23.98	44.62	54.00	-9.38	AV	PASS
	H	2400.00	60.34	30.22	4.85	23.98	58.95	74.00	-15.05	PK	PASS
	H	2400.00	47.97	30.22	4.85	23.98	46.58	54.00	-7.42	AV	PASS
	V	2390.00	59.05	30.22	4.85	23.98	57.66	74.00	-16.34	PK	PASS
	V	2390.00	48.11	30.22	4.85	23.98	46.72	54.00	-7.28	AV	PASS
	V	2400.00	59.51	30.22	4.85	23.98	58.12	74.00	-15.88	PK	PASS
	V	2400.00	47.10	30.22	4.85	23.98	45.71	54.00	-8.29	AV	PASS
	High Channel 2452MHz										
	H	2483.50	62.55	30.22	4.85	23.98	61.16	74.00	-12.84	PK	PASS
	H	2483.50	48.21	30.22	4.85	23.98	46.82	54.00	-7.18	AV	PASS
	H	2500.00	61.80	30.22	4.85	23.98	60.41	74.00	-13.59	PK	PASS
	H	2500.00	47.73	30.22	4.85	23.98	46.34	54.00	-7.66	AV	PASS
	V	2483.50	62.27	30.22	4.85	23.98	60.88	74.00	-13.12	PK	PASS
	V	2483.50	48.00	30.22	4.85	23.98	46.61	54.00	-7.39	AV	PASS
	V	2500.00	61.58	30.22	4.85	23.98	60.19	74.00	-13.81	PK	PASS
	V	2500.00	46.00	30.22	4.85	23.98	44.61	54.00	-9.39	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6. POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP

6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULT

Temperature：	25.9℃	Relative Humidity：	52%
Pressure：	101kPa	Test Voltage ：	DC 7.2V

Please refer to APPENDIX A

7. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 xRBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP

7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULT

Temperature :	25.8℃	Relative Humidity :	52%
Pressure :	101kPa	Test Voltage :	DC 7.2V
Test Mode :	TX Mode		

Please refer to APPENDIX A

8. OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

8.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

a. The EUT was directly connected to the Spectrum Analyzer

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULT

Temperature :	25.3℃	Relative Humidity :	55%
Pressure :	101kPa	Test Voltage :	DC 7.2V

Please refer to APPENDIX A

9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

A) Set the RBW = 100KHz.
B) Set the VBW = 300KHz.
C) Sweep time = auto couple.
D) Detector function = peak.
E) Trace mode = max hold.
F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

Please refer to APPENDIX A

10. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(b)(4)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is PCB Antenna, the best case gain of the antenna is 1.29dBi, reference to the appendix II for details	

11. APPENDIX A

11.1 DUTY CYCLE

Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
b	2412	Ant1	99.52	0	0.08
b	2437	Ant1	99.04	0	0.08
b	2462	Ant1	99.04	0	0.08
g	2412	Ant1	98.1	0	0.49
g	2437	Ant1	97.64	0.1	0.48
g	2462	Ant1	95.37	0.21	0.49
n20	2412	Ant1	95.54	0.2	0.52
n20	2437	Ant1	91.87	0.37	0.52
n20	2462	Ant1	97.46	0.11	0.52
n40	2422	Ant1	85.59	0.68	1.05
n40	2437	Ant1	88.79	0.52	1.05
n40	2452	Ant1	85.59	0.68	1.05

Test Graphs

Duty Cycle NVNT b 2412MHz Ant1



Duty Cycle NVNT b 2437MHz Ant1



Duty Cycle NVNT b 2462MHz Ant1



Duty Cycle NVNT g 2412MHz Ant1



Duty Cycle NVNT g 2437MHz Ant1



Duty Cycle NVNT g 2462MHz Ant1



Duty Cycle NVNT n20 2412MHz Ant1



Duty Cycle NVNT n20 2437MHz Ant1



Duty Cycle NVNT n20 2462MHz Ant1



Duty Cycle NVNT n40 2422MHz Ant1



Duty Cycle NVNT n40 2437MHz Ant1



Duty Cycle NVNT n40 2452MHz Ant1



11.2 MAXIMUM AVERAGE CONDUCTED OUTPUT POWER

Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
b	2412	Ant1	7.71	0	7.71	30	Pass
b	2437	Ant1	7.36	0	7.36	30	Pass
b	2462	Ant1	6.91	0	6.91	30	Pass
g	2412	Ant1	3.33	0	3.33	30	Pass
g	2437	Ant1	2.92	0.1	3.02	30	Pass
g	2462	Ant1	3.36	0.21	3.57	30	Pass
n20	2412	Ant1	2.74	0.2	2.94	30	Pass
n20	2437	Ant1	4.13	0.37	4.5	30	Pass
n20	2462	Ant1	4.65	0.11	4.76	30	Pass
n40	2422	Ant1	3.61	0.68	4.29	30	Pass
n40	2437	Ant1	3.07	0.52	3.59	30	Pass
n40	2452	Ant1	2.6	0.68	3.28	30	Pass

Test Graphs

Average Power NVNT b 2412MHz Ant1



Average Power NVNT b 2437MHz Ant1



Average Power NVNT b 2462MHz Ant1



Average Power NVNT g 2412MHz Ant1



Average Power NVNT g 2437MHz Ant1



Average Power NVNT g 2462MHz Ant1



Average Power NVNT n20 2412MHz Ant1



Average Power NVNT n20 2437MHz Ant1



Average Power NVNT n20 2462MHz Ant1



Average Power NVNT n40 2422MHz Ant1



Average Power NVNT n40 2437MHz Ant1



Average Power NVNT n40 2452MHz Ant1



11.3 -6DB BANDWIDTH

Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
b	2412	8.578	0.5	Pass
b	2437	8.598	0.5	Pass
b	2462	8.082	0.5	Pass
g	2412	16.335	0.5	Pass
g	2437	16.321	0.5	Pass
g	2462	16.345	0.5	Pass
n20	2412	17.569	0.5	Pass
n20	2437	17.336	0.5	Pass
n20	2462	17.542	0.5	Pass
n40	2422	35.581	0.5	Pass
n40	2437	35.322	0.5	Pass
n40	2452	35.915	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT b 2412MHz Ant1



-6dB Bandwidth NVNT b 2437MHz Ant1



-6dB Bandwidth NVNT b 2462MHz Ant1



-6dB Bandwidth NVNT g 2412MHz Ant1



-6dB Bandwidth NVNT g 2437MHz Ant1



-6dB Bandwidth NVNT g 2462MHz Ant1



-6dB Bandwidth NVNT n20 2412MHz Ant1



-6dB Bandwidth NVNT n20 2437MHz Ant1



-6dB Bandwidth NVNT n20 2462MHz Ant1



-6dB Bandwidth NVNT n40 2422MHz Ant1



-6dB Bandwidth NVNT n40 2437MHz Ant1



-6dB Bandwidth NVNT n40 2452MHz Ant1



11.4 OCCUPIED CHANNEL BANDWIDTH

Mode	Frequency (MHz)	99% OBW (MHz)
b	2412	13.439
b	2437	13.547
b	2462	13.539
g	2412	16.568
g	2437	16.559
g	2462	16.536
n20	2412	17.722
n20	2437	17.722
n20	2462	17.715
n40	2422	36.141
n40	2437	36.093
n40	2452	36.126

Test Graphs

OBW NVNT b 2412MHz Ant1



OBW NVNT b 2437MHz Ant1



OBW NVNT b 2462MHz Ant1



OBW NVNT g 2412MHz Ant1



OBW NVNT g 2437MHz Ant1



OBW NVNT g 2462MHz Ant1



OBW NVNT n20 2412MHz Ant1



OBW NVNT n20 2437MHz Ant1



OBW NVNT n20 2462MHz Ant1



OBW NVNT n40 2422MHz Ant1



OBW NVNT n40 2437MHz Ant1



OBW NVNT n40 2452MHz Ant1



11.5 MAXIMUM POWER SPECTRAL DENSITY LEVEL

Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
b	2412	Ant1	-7.51	0	-7.51	8	Pass
b	2437	Ant1	-6.87	0	-6.87	8	Pass
b	2462	Ant1	-7.49	0	-7.49	8	Pass
g	2412	Ant1	-22.89	0	-22.89	8	Pass
g	2437	Ant1	-22.92	0.1	-22.82	8	Pass
g	2462	Ant1	-23.23	0.21	-23.02	8	Pass
n20	2412	Ant1	-23.2	0.2	-23	8	Pass
n20	2437	Ant1	-21.05	0.37	-20.68	8	Pass
n20	2462	Ant1	-21.23	0.11	-21.12	8	Pass
n40	2422	Ant1	-24.07	0.68	-23.39	8	Pass
n40	2437	Ant1	-24.23	0.52	-23.71	8	Pass
n40	2452	Ant1	-24.7	0.68	-24.02	8	Pass

Test Graphs

PSD NVNT b 2412MHz Ant1



PSD NVNT b 2437MHz Ant1



PSD NVNT b 2462MHz Ant1



PSD NVNT g 2412MHz Ant1



PSD NVNT g 2437MHz Ant1



PSD NVNT g 2462MHz Ant1



PSD NVNT n20 2412MHz Ant1



PSD NVNT n20 2437MHz Ant1



PSD NVNT n20 2462MHz Ant1



PSD NVNT n40 2422MHz Ant1



PSD NVNT n40 2437MHz Ant1



PSD NVNT n40 2452MHz Ant1



11.6 BAND EDGE

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
b	2412	-47.69	-30	Pass
b	2462	-55.01	-30	Pass
g	2412	-39.69	-30	Pass
g	2462	-47.5	-30	Pass
n20	2412	-39.65	-30	Pass
n20	2462	-45.73	-30	Pass
n40	2422	-35.05	-30	Pass
n40	2452	-45.41	-30	Pass

Test Graphs

Band Edge NVNT b 2412MHz Ant1 Ref



Band Edge NVNT b 2412MHz Ant1 Emission



Band Edge NVNT b 2462MHz Ant1 Ref



Band Edge NVNT b 2462MHz Ant1 Emission



Band Edge NVNT g 2412MHz Ant1 Ref



Band Edge NVNT g 2412MHz Ant1 Emission



Band Edge NVNT g 2462MHz Ant1 Ref



Band Edge NVNT g 2462MHz Ant1 Emission

Band Edge NVNT n20 2412MHz Ant1 Ref



Band Edge NVNT n20 2412MHz Ant1 Emission



Band Edge NVNT n20 2462MHz Ant1 Ref



Band Edge NVNT n20 2462MHz Ant1 Emission

Band Edge NVNT n40 2422MHz Ant1 Ref



Band Edge NVNT n40 2422MHz Ant1 Emission

Band Edge NVNT n40 2452MHz Ant1 Ref



Band Edge NVNT n40 2452MHz Ant1 Emission

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.447 0 GHz	-11.057 dBm			
2	N	1	f	2.483 5 GHz	-58.661 dBm			
3	N	1	f	2.500 0 GHz	-57.540 dBm			
4	N	1	f	2.486 4 GHz	-56.113 dBm			
5								
6								
7								
8								
9								
10								
11								

11.7 CONDUCTED RF SPURIOUS EMISSION

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
b	2412	-40.68	-30	Pass
b	2437	-40.47	-30	Pass
b	2462	-38.56	-30	Pass
g	2412	-37.18	-30	Pass
g	2437	-33.95	-30	Pass
g	2462	-35.14	-30	Pass
n20	2412	-34.97	-30	Pass
n20	2437	-35.76	-30	Pass
n20	2462	-37.14	-30	Pass
n40	2422	-36.27	-30	Pass
n40	2437	-35.35	-30	Pass
n40	2452	-35.14	-30	Pass

Test Graphs

Tx. Spurious NVNT b 2412MHz Ant1 Ref



Tx. Spurious NVNT b 2412MHz Ant1 Emission



Tx. Spurious NVNT b 2437MHz Ant1 Ref



Tx. Spurious NVNT b 2437MHz Ant1 Emission

Tx. Spurious NVNT b 2462MHz Ant1 Ref



Tx. Spurious NVNT b 2462MHz Ant1 Emission



Tx. Spurious NVNT g 2412MHz Ant1 Ref



Tx. Spurious NVNT g 2412MHz Ant1 Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.416 7 GHz	-7.930 dBm			
2	N	1	f	3.409 3 GHz	-45.380 dBm			
3	N	1	f	4.871 4 GHz	-55.532 dBm			
4	N	1	f	7.124 8 GHz	-55.681 dBm			
5	N	1	f	9.468 3 GHz	-56.623 dBm			
6								
7								
8								
9								
10								
11								

Tx. Spurious NVNT g 2437MHz Ant1 Ref



Tx. Spurious NVNT g 2437MHz Ant1 Emission

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.438 8 GHz	-10.310 dBm			
2	N	1	f	3.502 0 GHz	-40.174 dBm			
3	N	1	f	4.821 1 GHz	-56.317 dBm			
4	N	1	f	7.345 4 GHz	-55.269 dBm			
5	N	1	f	9.877 7 GHz	-57.218 dBm			
6								
7								
8								
9								
10								
11								

Tx. Spurious NVNT g 2462MHz Ant1 Ref



Tx. Spurious NVNT g 2462MHz Ant1 Emission

Tx. Spurious NVNT n20 2412MHz Ant1 Ref



Tx. Spurious NVNT n20 2412MHz Ant1 Emission

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.419 4 GHz	-11.527 dBm			
2	N	1	f	351.2 MHz	-43.156 dBm			
3	N	1	f	4.823 7 GHz	-54.270 dBm			
4	N	1	f	7.100 1 GHz	-55.831 dBm			
5	N	1	f	9.566 3 GHz	-57.155 dBm			
6								
7								
8								
9								
10								
11								

Tx. Spurious NVNT n20 2437MHz Ant1 Ref



Tx. Spurious NVNT n20 2437MHz Ant1 Emission

Tx. Spurious NVNT n20 2462MHz Ant1 Ref



Tx. Spurious NVNT n20 2462MHz Ant1 Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.454 7 GHz	-7.362 dBm			
2	N	1	f	351.2 MHz	-43.408 dBm			
3	N	1	f	4.923 4 GHz	-52.111 dBm			
4	N	1	f	7.359 5 GHz	-56.251 dBm			
5	N	1	f	10.003 0 GHz	-57.249 dBm			
6								
7								
8								
9								
10								
11								

Tx. Spurious NVNT n40 2422MHz Ant1 Ref



Tx. Spurious NVNT n40 2422MHz Ant1 Emission

Tx. Spurious NVNT n40 2437MHz Ant1 Ref



Tx. Spurious NVNT n40 2437MHz Ant1 Emission

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.444 1 GHz	-12.122 dBm			
2	N	1	f	24.177 7 GHz	-46.102 dBm			
3	N	1	f	4.874 0 GHz	-53.915 dBm			
4	N	1	f	7.439 8 GHz	-56.451 dBm			
5	N	1	f	9.924 5 GHz	-56.748 dBm			
6								
7								
8								
9								
10								
11								

Tx. Spurious NVNT n40 2452MHz Ant1 Ref



Tx. Spurious NVNT n40 2452MHz Ant1 Emission

12. TEST SETUP PHOTO

Reference to the appendix I for details.

13. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

※※※※※ END OF REPORT ※※※※※