

FCC Appendix RF Test Data for BLE

FCC ID : 2BH95-AM350-X

Company : Shenzhen Aomosur Technology Co., Ltd

EUT : RV Leveling System

Model Number : AM350-X

Report No. : CTA26062200501


Reviewed By : Eric Wang


Appendix A: DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.628	2401.700	2402.328	0.5	PASS
		2440	0.648	2439.692	2440.340	0.5	PASS
		2480	0.644	2479.692	2480.336	0.5	PASS

Test Graphs







Appendix B: Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.0058	2401.5171	2402.5229	---	---
		2440	1.0111	2439.5172	2440.5283	---	---
		2480	1.0077	2479.5184	2480.5261	---	---

Test Graphs





Appendix C: Maximum conducted output power

Test Result Peak

TestMode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-3.45	≤30	PASS
		2440	-3.51	≤30	PASS
		2480	-3.79	≤30	PASS


Appendix D: Maximum power spectral density

Test Result


TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-19.24	≤8.00	PASS
		2440	-19.31	≤8.00	PASS
		2480	-19.50	≤8.00	PASS

Test Graphs


BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480




Appendix E: Band edge measurements

Test Result

TestMode	Antenna	Channel	Freq(MHz)	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-3.48	-55.21	≤-23.48	PASS
		High	2480	-3.93	-56.28	≤-23.93	PASS

Test Graphs





Appendix F: Conducted Spurious Emission

Test Result

TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	-5.58	-5.58	---	PASS
			30~1000	-5.58	-68.79	≤-25.58	PASS
			1000~26500	-5.58	-45.37	≤-25.58	PASS
		2440	Reference	-4.84	-4.84	---	PASS
			30~1000	-4.84	-69.13	≤-24.84	PASS
			1000~26500	-4.84	-45.33	≤-24.84	PASS
		2480	Reference	-6.57	-6.57	---	PASS
			30~1000	-6.57	-69.26	≤-26.57	PASS
			1000~26500	-6.57	-46.94	≤-26.57	PASS

Test Graphs







BLE_1M_Ant1_2440_0~Reference



BLE_1M_Ant1_2440_30~1000




BLE_1M_Ant1_2440_1000~26500




BLE_1M_Ant1_2480_0~Reference



BLE_1M_Ant1_2480_30~1000



BLE_1M_Ant1_2480_1000~26500





Appendix G: Duty Cycle

Test Result

TestMode	Antenna	Freq(MHz)	ON Time [ms]	Period [ms]	X	DC [%]	xFactor	Limit	Verdict
BLE_1M	Ant1	2402	0.41	0.62	0.6613	66.13	1.80	---	---
		2440	0.41	0.62	0.6613	66.13	1.80	---	---
		2480	0.41	0.62	0.6613	66.13	1.80	---	---

Test Graphs





Appendix H: Emissions in Restricted Bands


Test Result


TestMode	Antenna	Channel Name	Freq(MHz)	Detector	Freq [MHz]	Result [dBm]	Gain [dB]	DC Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Verdict
BLE_1M	Ant1	Low	2402	AV	2310.000	-60.98	2.00	1.80	38.02	≤54	PASS
				AV	2379.065	-59.25	2.00	1.80	39.75	≤54	PASS
				AV	2390.000	-60.38	2.00	1.80	38.62	≤54	PASS
				Peak	2310.000	-53.1	2.00	0.00	44.10	≤74	PASS
				Peak	2377.385	-48.74	2.00	0.00	48.46	≤74	PASS
				Peak	2390.000	-51.91	2.00	0.00	45.29	≤74	PASS
		High	2480	AV	2483.500	-58.86	2.00	1.80	40.14	≤54	PASS
				AV	2483.760	-58.6	2.00	1.80	40.40	≤54	PASS
				AV	2500.000	-59.66	2.00	1.80	39.34	≤54	PASS
				Peak	2483.500	-50.88	2.00	0.00	46.32	≤74	PASS
				Peak	2484.400	-48.69	2.00	0.00	48.51	≤74	PASS
				Peak	2500.000	-51.86	2.00	0.00	45.34	≤74	PASS

Note:

1. The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.

Test Graphs





BLE_1M_Ant1_High_2480_Peak

