


2.4G PE Antenna Spec



Product Specification

A. Electrical Characteristics

Frequency 2400MHz ~2500MHz

VSWR <1.5

Efficiency >20%

Impedance 50 Ohm

Polarizational: Vertical

Radiation: Omni

Gain 0DBi-0.6DBI

B. Material & Mechanical Characteristics

Material of Radiator Cu

Connector Type : NO

Dimension

C. Environmental

Operation Temperature - 30 °C ~ + 80 °C

Storage Temperature - 30 °C ~ + 85 °C

Test Equipment & Conditions



1. Network Analyzers :

Agilent 8753D 5071B

2. Communications Test Set:

Agilent E5515C

3. 3D Chamber Test System




Effiency &Gain


Freq (MHz)	Effi (%)	Gain (dBi)
2400	23.65	0.46
2415	23.19	0.38
2420	23.03	0.49
2430	22.41	0.42
2440	21.67	0.45
2450	20.24	0.52
2460	20.61	0.51
2465	21.41	0.59
2480	23.88	0.55
2500	25.72	0.45

Radiation Pattern


2400.000MHz




2400.000MHz H




2400.000MHz E1




2400.000MHz H E2




2450.000MHz




2450.000MHz H



2450.000MHz E1




2450.000MHz E2




2500.000MHz

2500.000MHz H





2500.000MHz E1



2500.000MHz E2

