



RF EXPOSURE REPORT

Report No.: 20240817G16885X-W4

Product Name: MT Series Thermal Dome Camera

Model No.: M6T25S, M6T25SNA

FCC ID: 2BHFB-9000

Applicant: Inlumen Technologies Co., Ltd.

Address: Building B3, NO.800 Wangjiang West Road, National High-tech
Industry Development District, Hefei, Anhui, China

Dates of Testing: 08/30/2024 - 09/29/2024

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No.43, Shahe Road, Xili Street,
Nanshan District, Shenzhen, Guangdong, China

Tel: 86-755-26627338

E-Mail: manager@ccic-set.com

This test report consists of 8 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product.....: MT Series Thermal Dome Camera

Trade Name: Nocpix

Applicant.....: Inlumen Technologies Co., Ltd.

Applicant Address.....: Building B3, NO.800 Wangjiang West Road, National
High-tech Industry Development District, Hefei, Anhui,
China

Manufacturer.....: Inlumen Technologies Co., Ltd.

Manufacturer Address.....: Building B3, NO.800 Wangjiang West Road, National
High-tech Industry Development District, Hefei, Anhui,
China

Test Standards.....: 47 CFR Part 2.1091

Test Result.....: Pass

Tested by: Kim Li 2024.09.29
Kim Li, Test Engineer

Reviewed by.....: Sun Jiaohui 2024.09.29
Sun Jiaohui, Senior Engineer

Approved by.....: Chris You 2024.09.29
Chris You, Manager



Table of Contents

1. GENERAL INFORMATION	5
1.1. EUT Description	5
1.2. EUT Description	6
1.3. Laboratory Facilities	6
1.4. Laboratory Location	6
2. TECHNICAL REQUIREMENTS SPECIFICATION IN CFR TITLE 47 PART 2.1091...	7
2.1. Evaluation method	7
2.2. Predication of MPE limit at a given distance	7
2.3. Evaluation Results	8
2.4. Conclusion	8



Change History		
Issue	Date	Reason for change
1.0	2024.09.29	First edition

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	MT Series Thermal Dome Camera
Model No.	M6T25S, M6T25SNA
Device Type	Fixed Devices
EUT supports Radios application	BLE/WIFI
Frequency Range	BLE: 2402MHz~2480MHz WIFI: 2412MHz~2462MHz
Modulation Type	BLE: GFSK WIFI: DSSS (802.11b), OFDM (802.11g/n)
Antenna gain	BLE/WIFI: 3.0dBi
Antenna Type	BLE/WIFI: External antenna

Note 1: The information of antenna gain and cable loss is provided by the manufacturer and our lab is not responsible for the accuracy of the antenna gain and cable loss information.

Note 2: The model M6T25S and the model M6T25SNA have the same technical structure, including circuit diagrams, wireless modules, and antenna positions, with the only difference being that the visible laser function of M6T25S cannot be turned on.

1.2. EUT Description

EUT has been tested according to the following standards.

No.	Identity	Document Title
1	47 CFR Part 1	Practice and Procedure
2	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
3	KDB 447498 D01 General RF Exposure Guidance v06	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
4	OET Bulletin 65 Edition 97-01	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields

1.3. Laboratory Facilities

FCC-Registration No.: CN1283

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until Jun. 30th, 2025.

ISED Registration: 11185A-1

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until Jun. 30th, 2025.

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

1.4. Laboratory Location

Company Name:	CCIC Southern Testing Co., Ltd.
Address:	Electronic Testing Building, No. 43, Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China

2. Technical Requirements Specification in CFR Title 47 Part 2.1091

2.1. Evaluation method

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	< 6
3.0-30	1824/f	4.89/f	*(900/f ²)	< 6
30-300	61.4	0.163	1.0	< 6
300-1500	/	/	f/300	< 6
1500-100,000	/	/	5	< 6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	< 30
1.34-30	824/f	2.19/f	*(180/f ²)	< 30
30-300	27.5	0.073	0.2	< 30
300-1500	/	/	f/1500	< 30
1500-100,000	/	/	1.0	< 30
Note: f = frequency in MHz. * = Plane-wave equivalent power density.				

2.2. Predication of MPE limit at a given distance

Refer to formulas on page 19 of OET Bulletin 65, Edition 97-01.

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna (appropriate units, e.g., cm)



2.3. Evaluation Results

Worst-Case mode Conducted Output Power Results

BLE(GFSK)			
Frequency (MHz)	2402	2440	2480
Test Results (dBm)	2.59	4.29	5.05
Target (dBm)	3.0	5.0	6.0
Tolerance (dB)	± 1	± 1	± 1

2.4G WIFI (IEEE 802.11b)			
Frequency (MHz)	2412	2437	2462
Test Results (dBm)	15.11	15.60	15.98
Target (dBm)	16.0	16.0	16.0
Tolerance (dB)	± 1	± 1	± 1

Calculation results: Worst-Case mode

Operation Mode	Output Power (dBm)	Ant. Gain		Distance (cm)	MPE (mW/cm ²)	MPE Limit (mW/cm ²)	Ratio
		(dBi)	(numeric)				
BLE	6.0	3.0	2.0	20	0.002	1.000	0.002
2.4G WIFI	16.0	3.0	2.0	20	0.016	1.000	0.016

Note: Output power including turn-up tolerance

Simultaneous Transmission Calculation (Worst-case mode)

No.	Transmitter Combinations	Scenario Supported or not
1	Bluetooth LE + 2.4G WLAN	Yes

Max Simultaneous Transmission Calculation (Worst-case mode)

No.	Worst Mode	MPE Ratio	Limit	Results
1	Bluetooth LE + 2.4G WLAN	0.018	≤ 1.0	Pass

Note: MPE Ratio = 0.002 + 0.016 = 0.018.

2.4. Conclusion

According to the KDB 447498 D01 General RF Exposure Guidance v06 section 7.2 determine the device is exclusion from SAR test.

**** END OF REPORT ****