

# TEST REPORT

**Application No.:** KSCR2508001892AT  
**FCC ID:** 2BHGF-0235CB1C  
**Applicant:** KeyLife International Technology Limited  
**Address of Applicant:** Workshop 7, 6th Floor Core 45, No. 43 Tsun Yip Street, Kowloon, HONG KONG  
**Manufacturer:** KeyLife International Technology Limited  
**Address of Manufacturer:** Workshop 7, 6th Floor Core 45, No. 43 Tsun Yip Street, Kowloon, HONG KONG  
**Equipment Under Test (EUT):**  
**EUT Name:** Solar-powered Security Camera  
**Model No.:** S420 Pro  
**Trade Mark:** youkey  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2025-08-27  
**Date of Test:** 2025-09-03 to 2025-09-15  
**Date of Issue:** 2025-09-18

|                     |              |
|---------------------|--------------|
| <b>Test Result:</b> | <b>Pass*</b> |
|---------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

| Revision Record |             |            |        |
|-----------------|-------------|------------|--------|
| Version         | Description | Date       | Remark |
| 00              | Original    | 2025-09-18 | /      |
|                 |             |            |        |
|                 |             |            |        |

|                          |  |                            |  |
|--------------------------|--|----------------------------|--|
| Authorized for issue by: |  |                            |  |
| Tested By                |  | Maker Qi                   |  |
|                          |  | Maker Qi /Project Engineer |  |
| Approved By              |  | Terry Hou                  |  |
|                          |  | Terry Hou /Reviewer        |  |

## 2 Test Summary

| Radio Spectrum Technical Requirement |                                  |        |                                                 |                      |
|--------------------------------------|----------------------------------|--------|-------------------------------------------------|----------------------|
| Item                                 | Standard                         | Method | Requirement                                     | Result               |
| Antenna Requirement                  | 47 CFR Part 15, Subpart C 15.247 | N/A    | 47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4) | Customer Declaration |

| Radio Spectrum Matter Part                            |                                  |                                    |                                           |        |
|-------------------------------------------------------|----------------------------------|------------------------------------|-------------------------------------------|--------|
| Item                                                  | Standard                         | Method                             | Requirement                               | Result |
| Conducted Emissions at AC Power Line (150kHz-30MHz)   | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2020) Section 6.2     | 47 CFR Part 15, Subpart C 15.207          | Pass   |
| Radiated Emissions which fall in the restricted bands |                                  | ANSI C63.10 (2020) Section 6.10.5  | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |
| Radiated Spurious Emissions Below 1GHz                |                                  | ANSI C63.10 (2020) Section 6.4,6.5 | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |
| Radiated Spurious Emissions Above 1GHz                |                                  | ANSI C63.10 (2020) Section 6.6     | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |
| Conducted Peak Output Power                           |                                  | ANSI C63.10 (2020) Section 11.9.2  | 47 CFR Part 15, Subpart C 15.247(b)(3)    | Pass   |
| Minimum 6dB Bandwidth                                 |                                  | ANSI C63.10 (2020) Section 11.8.1  | 47 CFR Part 15, Subpart C 15.247a(2)      | Pass   |
| Power Spectrum Density                                |                                  | ANSI C63.10 (2020) Section 11.10.2 | 47 CFR Part 15, Subpart C 15.247(e)       | Pass   |
| Conducted Band Edges Measurement                      |                                  | ANSI C63.10 (2020) Section 6.10.4  | 47 CFR Part 15, Subpart C 15.247(d)       | Pass   |
| Conducted Spurious Emissions                          |                                  | ANSI C63.10 (2020) Section 11.11   | 47 CFR Part 15, Subpart C 15.247(d)       | Pass   |

### 3 Contents

|                                                                 | Page      |
|-----------------------------------------------------------------|-----------|
| <b>1 COVER PAGE .....</b>                                       | <b>1</b>  |
| <b>2 Test Summary .....</b>                                     | <b>3</b>  |
| <b>3 Contents.....</b>                                          | <b>4</b>  |
| <b>4 General Information.....</b>                               | <b>5</b>  |
| 4.1 Details of E.U.T. ....                                      | 5         |
| 4.2 Description of Support Units .....                          | 5         |
| 4.3 Power level setting using in test.....                      | 5         |
| 4.4 Measurement Uncertainty .....                               | 6         |
| 4.5 Test Location.....                                          | 7         |
| 4.6 Test Facility .....                                         | 7         |
| 4.7 Deviation from Standards.....                               | 7         |
| 4.8 Abnormalities from Standard Conditions.....                 | 7         |
| <b>5 Equipment List .....</b>                                   | <b>8</b>  |
| <b>6 Radio Spectrum Technical Requirement.....</b>              | <b>9</b>  |
| 6.1 Antenna Requirement .....                                   | 9         |
| <b>7 Radio Spectrum Matter Test Results .....</b>               | <b>10</b> |
| 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz).....    | 10        |
| 7.2 Radiated Emissions which fall in the restricted bands ..... | 14        |
| 7.3 Radiated Spurious Emissions Below 1GHz .....                | 37        |
| 7.4 Radiated Spurious Emissions Above 1GHz.....                 | 41        |
| 7.5 Conducted Average Output Power .....                        | 61        |
| 7.6 Minimum 6dB Bandwidth .....                                 | 63        |
| 7.7 Power Spectrum Density.....                                 | 64        |
| 7.8 Conducted Band Edges Measurement .....                      | 65        |
| 7.9 Conducted Spurious Emissions .....                          | 67        |
| <b>8 Test Setup Photo .....</b>                                 | <b>69</b> |
| <b>9 EUT Constructional Details (EUT Photos).....</b>           | <b>69</b> |
| <b>10 Appendix.....</b>                                         | <b>70</b> |

## 4 General Information

### 4.1 Details of E.U.T.

|                      |                                                                                                                                         |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:        | DC 5V/2A<br>Battery Model: XL18650-2600-4P<br>3.7V 10400mAh 38.48Wh                                                                     |
| Test Voltage:        | AC 120V/60Hz(Pre-test AC 120V/50-60Hz&AC 240V/50-60Hz then choose the AC 120/60Hz as worst case)                                        |
| Operation Frequency: | 802.11b/g/n(HT20)/ax(HE20): 2412MHz to 2462MHz                                                                                          |
| Modulation Type:     | 802.11b: DSSS (DBPSK, DQPSK, CCK);<br>802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM);<br>802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM) |
| Number of Channels:  | 802.11b/g/n(HT20)/ax(HE20):11                                                                                                           |
| Channel Spacing:     | 5MHz                                                                                                                                    |
| Antenna Type:        | FPC Antenna                                                                                                                             |
| Antenna Gain:        | 1.42dBi (Provided by the manufacturer)                                                                                                  |

Note: The EUT is powered by two different methods: power adapter powered and battery powered, both pre-tested. The power adapter is identified as the worst-case scenario and only the worst-case outcome is reflected in the report.

### 4.2 Description of Support Units

| Description | Manufacturer | Model No.     | Serial No. |
|-------------|--------------|---------------|------------|
| AC Adapter  | DVE          | DSA-12G-12FEU | /          |
| Notebook    | LENOVO       | K27           | EB24537645 |

### 4.3 Power level setting using in test

| Channel | 802.11b | 802.11g | 802.11n(HT20) | 802.11ax(HE20) |
|---------|---------|---------|---------------|----------------|
|         | Ant 1   | Ant 1   | Ant 1         | Ant 1          |
| 1       | 14      | 13      | 13            | 13             |
| 6       | 15      | 14      | 14            | 15             |
| 11      | 17      | 16      | 16            | 16             |

#### 4.4 Measurement Uncertainty

| No.                                                                                                                                                      | Item                            | Measurement Uncertainty |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|-------------------------|
| 1                                                                                                                                                        | Radio Frequency                 | $8.4 \times 10^{-8}$    |
| 2                                                                                                                                                        | Timeout                         | 2s                      |
| 3                                                                                                                                                        | Duty Cycle                      | 0.37%                   |
| 4                                                                                                                                                        | Occupied Bandwidth              | 3%                      |
| 5                                                                                                                                                        | RF Conducted Power              | 0.6dB                   |
| 6                                                                                                                                                        | RF Power Density                | 2.9dB                   |
| 7                                                                                                                                                        | Conducted Spurious Emissions    | 0.75dB                  |
| 8                                                                                                                                                        | RF Radiated Power               | 5.2dB (Below 1GHz)      |
|                                                                                                                                                          |                                 | 5.9dB (Above 1GHz)      |
| 9                                                                                                                                                        | Radiated Spurious Emission Test | 4.2dB (Below 30MHz)     |
|                                                                                                                                                          |                                 | 4.5dB (30MHz-1GHz)      |
|                                                                                                                                                          |                                 | 5.1dB (1GHz-18GHz)      |
|                                                                                                                                                          |                                 | 5.4dB (Above 18GHz)     |
| 10                                                                                                                                                       | Temperature Test                | 1°C                     |
| 11                                                                                                                                                       | Humidity Test                   | 3%                      |
| 12                                                                                                                                                       | Supply Voltages                 | 1.5%                    |
| 13                                                                                                                                                       | Time                            | 3%                      |
| Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. |                                 |                         |

#### 4.5 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).
3. Sample source: sent by customer.

#### 4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

- **FCC**

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

- **ISED**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory. Company Number: 2324E

- **VCCI**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.

#### 4.7 Deviation from Standards

None

#### 4.8 Abnormalities from Standard Conditions

None

## 5 Equipment List

| Item                                         | Equipment                            | Manufacturer  | Model             | Inventory No          | Cal Date   | Cal. Due Date |
|----------------------------------------------|--------------------------------------|---------------|-------------------|-----------------------|------------|---------------|
| <b>Conducted Emission at Mains Terminals</b> |                                      |               |                   |                       |            |               |
| 1                                            | EMI Test Receive                     | R&S           | ESCI              | KS301196              | 07/09/2025 | 07/08/2026    |
| 2                                            | LISN                                 | R&S           | ENV216            | KS301197              | 01/15/2025 | 01/14/2026    |
| 3                                            | LISN                                 | Schwarzbeck   | NNLK 8129         | KS301091              | 01/15/2025 | 01/14/2026    |
| 4                                            | Pulse Limiter                        | R&S           | ESH3-Z2           | KUS1902E001           | 12/05/2024 | 12/04/2025    |
| 5                                            | CE test Cable                        | Thermax       | /                 | CZ301102              | 01/14/2025 | 01/13/2026    |
| 6                                            | Test Software                        | Farad         | EZ-EMC            | /                     | N.C.R      | N.C.R         |
| <b>RF Conducted Test</b>                     |                                      |               |                   |                       |            |               |
| 1                                            | Spectrum Analyzer                    | Keysight      | N9020A            | KUS1911E004-2         | 07/09/2025 | 07/08/2026    |
| 2                                            | Spectrum Analyzer                    | Keysight      | N9020A            | KUS2001M001-2         | 07/09/2025 | 07/08/2026    |
| 3                                            | Spectrum Analyzer                    | Keysight      | N9030B            | KSEM021-1             | 01/15/2025 | 01/14/2026    |
| 4                                            | Signal Generator                     | R&S           | SMBV100B          | KSEM032               | 02/19/2025 | 02/18/2026    |
| 5                                            | Signal Generator                     | R&S           | SMW200A           | KSEM020-1             | 07/09/2025 | 07/08/2026    |
| 6                                            | Signal Generator                     | Agilent       | N5182A            | KUS2001M001-1         | 07/08/2025 | 07/07/2026    |
| 7                                            | Signal Generator                     | Agilent       | E8257C            | KS301066              | 07/22/2025 | 07/21/2026    |
| 8                                            | Radio Communication Test Station     | Anritsu       | MT8000A           | KSEM001-1             | 07/09/2025 | 07/08/2026    |
| 9                                            | Radio Communication Analyzer         | Anritsu       | MT8821C           | KSEM002-1             | 02/19/2025 | 02/18/2026    |
| 10                                           | Universal Radio Communication Tester | R&S           | CMW500            | KUS1911E004-1         | 07/08/2025 | 07/07/2026    |
| 11                                           | Switcher                             | TST           | FY562             | KUS2001M001-4         | 01/15/2025 | 01/14/2026    |
| 12                                           | Conducted Test Cable                 | Thermax       | RF01-RF04         | CZ301111-<br>CZ301120 | 01/14/2025 | 01/13/2026    |
| 13                                           | Temp. / Humidity Chamber             | TERCHY        | MHK-120AK         | KS301190              | 07/15/2025 | 07/14/2026    |
| 14                                           | Temperature & Humidity Recorder      | Renke Control | RS-WS-N01-6J      | KSEM024-5             | 02/26/2025 | 02/25/2026    |
| 15                                           | Software                             | BST           | TST-PASS          | /                     | NCR        | NCR           |
| <b>RF Radiated Test</b>                      |                                      |               |                   |                       |            |               |
| 1                                            | Spectrum Analyzer                    | R&S           | FSV40             | KUS1806E003           | 07/09/2025 | 07/08/2026    |
| 2                                            | Universal Radio Communication Tester | R&S           | CMW500            | KSEM009-1             | 02/18/2025 | 02/17/2026    |
| 3                                            | Signal Generator                     | Agilent       | E8257C            | KS301066              | 07/22/2025 | 07/21/2026    |
| 4                                            | Loop Antenna (9KHz-30MHz)            | COM-POWER     | AL-130R           | KUS1806E001           | 07/11/2025 | 07/10/2026    |
| 5                                            | Bilog Antenna (30MHz-1GHz)           | TESEQ         | CBL 6112D         | KUS1806E005           | 07/12/2025 | 07/11/2026    |
| 6                                            | Horn-antenna(1-18GHz)                | Schwarzbeck   | BBHA9120D         | KS301079              | 03/23/2024 | 03/22/2026    |
| 7                                            | Horn Antenna(18-40GHz)               | Schwarzbeck   | BBHA9170          | CZ301058              | 01/07/2024 | 01/06/2026    |
| 8                                            | Amplifier(30MHz~1GHz)                | TST           | LNA009100G30      | KSEM061               | 01/15/2025 | 01/14/2026    |
| 9                                            | Amplifier(400MHz~8GHz)               | TST           | LNA004080G30      | KSEM062               | 01/15/2025 | 01/14/2026    |
| 10                                           | Amplifier(1GHz~18GHz)                | TST           | LNA010180G45      | KSEM039               | 07/09/2025 | 07/08/2026    |
| 11                                           | Amplifier(18~40GHz)                  | TST           | LNA180400G40      | KSEM038               | 07/09/2025 | 07/08/2026    |
| 12                                           | Temperature & Humidity Recorder      | Renke Control | RS-WS-N01-6J      | KSEM024-4             | 02/26/2025 | 02/25/2026    |
| 13                                           | Software                             | Faratronic    | EZ_EMC-v 3A1      | /                     | NCR        | NCR           |
| 14                                           | Software                             | ESE           | E3_V<br>6.111221a | /                     | NCR        | NCR           |

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is FPC on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.42 dBi.

Antenna location: Refer to internal photo.

## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2020) Section 6.2

Limit:

| Frequency of emission(MHz)                                             | Conducted limit(dBμV) |           |
|------------------------------------------------------------------------|-----------------------|-----------|
|                                                                        | Quasi-peak            | Average   |
| 0.15-0.5                                                               | 66 to 56*             | 56 to 46* |
| 0.5-5                                                                  | 56                    | 46        |
| 5-30                                                                   | 60                    | 50        |
| *Decreases with the logarithm of the frequency.                        |                       |           |
| Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz |                       |           |

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 26.5 °C


Humidity: 48.3 % RH

Atmospheric Pressure: 1010 mbar

#### 7.1.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                                                                                                                                                                                              |
|-----------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test            | 00        | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |

#### 7.1.3 Test Setup Diagram




#### 7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


Remark : Level=Read Level+ Cable Loss+ LISN Factor

Test Mode: 00; Line: Live line



| No. | Frequency<br>(MHz) | Reading<br>(dBUV) | Correct<br>Factor(dB) | Result<br>(dBUV) | Limit<br>(dBUV) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|-----------------------|------------------|-----------------|----------------|---------|
| 1   | 0.3620             | 18.05             | 19.68                 | 37.73            | 48.68           | -10.95         | Average |
| 2   | 0.3620             | 23.18             | 19.68                 | 42.86            | 58.68           | -15.82         | QP      |
| 3   | 0.4079             | 17.65             | 19.68                 | 37.33            | 47.69           | -10.36         | Average |
| 4   | 0.4079             | 22.83             | 19.68                 | 42.51            | 57.69           | -15.18         | QP      |
| 5   | 0.4627             | 7.60              | 19.66                 | 27.26            | 46.64           | -19.38         | Average |
| 6   | 0.4627             | 12.76             | 19.66                 | 32.42            | 56.64           | -24.22         | QP      |
| 7   | 0.5836             | 16.62             | 19.70                 | 36.32            | 46.00           | -9.68          | Average |
| 8   | 0.5836             | 21.81             | 19.70                 | 41.51            | 56.00           | -14.49         | QP      |
| 9   | 0.6982             | 6.31              | 19.75                 | 26.06            | 46.00           | -19.94         | Average |
| 10  | 0.6982             | 11.36             | 19.75                 | 31.11            | 56.00           | -24.89         | QP      |
| 11  | 1.0060             | 4.99              | 19.87                 | 24.86            | 46.00           | -21.14         | Average |
| 12  | 1.0060             | 10.24             | 19.87                 | 30.11            | 56.00           | -25.89         | QP      |

Test Mode: 00; Line: Neutral Line



| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>Factor(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|-----------------------|------------------|-----------------|----------------|---------|
| 1   | 0.4749             | 17.17             | 19.58                 | 36.75            | 46.43           | -9.68          | Average |
| 2   | 0.4749             | 22.39             | 19.58                 | 41.97            | 56.43           | -14.46         | QP      |
| 3   | 0.5270             | 16.96             | 19.59                 | 36.55            | 46.00           | -9.45          | Average |
| 4   | 0.5270             | 22.23             | 19.59                 | 41.82            | 56.00           | -14.18         | QP      |
| 5   | 0.6178             | 6.61              | 19.64                 | 26.25            | 46.00           | -19.75         | Average |
| 6   | 0.6178             | 11.81             | 19.64                 | 31.45            | 56.00           | -24.55         | QP      |
| 7   | 0.7761             | 6.74              | 19.71                 | 26.45            | 46.00           | -19.55         | Average |
| 8   | 0.7761             | 11.98             | 19.71                 | 31.69            | 56.00           | -24.31         | QP      |
| 9   | 0.9756             | 5.03              | 19.79                 | 24.82            | 46.00           | -21.18         | Average |
| 10  | 0.9756             | 10.17             | 19.79                 | 29.96            | 56.00           | -26.04         | QP      |
| 11  | 1.0460             | 4.73              | 19.80                 | 24.53            | 46.00           | -21.47         | Average |
| 12  | 1.0460             | 9.81              | 19.80                 | 29.61            | 56.00           | -26.39         | QP      |

## 7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.10.5

Measurement Distance: 3M

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 0.009-0.490    | 2400/F(kHz)                      | 300                          |
| 0.490-1.705    | 24000/F(kHz)                     | 30                           |
| 1.705-30.0     | 30                               | 30                           |
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| Above 960      | 500                              | 3                            |

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 45.2 % RH

Atmospheric Pressure: 1010 mbar

### 7.2.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test            | 00        | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |

## 7.2.3 Test Setup Diagram



#### 7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1:  $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.


Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle  $< 98\%$ ) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.

## 11b\_TX\_CH\_01\_Horizontal\_Peak




## 11b\_TX\_CH\_01\_Vertical\_Peak




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2387.000        | 54.12          | -2.14                   | 51.98           | 74.00          | -22.02      | peak   |
| 2   | 2390.000        | 53.76          | -2.13                   | 51.63           | 74.00          | -22.37      | peak   |
| 3   | 2413.320        | 104.51         | -2.01                   | 102.50          | 74.00          | 28.50       | peak   |

## 11b\_TX\_CH\_11\_Horizontal\_Peak




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2463.350        | 102.28         | -1.75                   | 100.53          | 74.00          | 26.53       | peak   |
| 2   | 2483.500        | 49.91          | -1.64                   | 48.27           | 74.00          | -25.73      | peak   |
| 3   | 2490.200        | 49.54          | -1.60                   | 47.94           | 74.00          | -26.06      | peak   |
| 4   | 2500.000        | 47.04          | -1.55                   | 45.49           | 74.00          | -28.51      | peak   |

11b\_TX\_CH\_11\_Vertical\_Peak




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2460.800        | 103.22         | -1.76                   | 101.46          | 74.00          | 27.46       | peak   |
| 2   | 2483.500        | 50.35          | -1.64                   | 48.71           | 74.00          | -25.29      | peak   |
| 3   | 2486.000        | 51.08          | -1.62                   | 49.46           | 74.00          | -24.54      | peak   |
| 4   | 2500.000        | 47.53          | -1.55                   | 45.98           | 74.00          | -28.02      | peak   |

11n(HT20)\_TX\_CH\_01\_Horizontal\_Peak




11n(HT20)\_TX\_CH\_01\_Horizontal\_Average




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2388.820        | 46.56          | -2.13                   | 44.43           | 54.00          | -9.57       | AVG    |
| 2   | 2390.000        | 48.84          | -2.13                   | 46.71           | 54.00          | -7.29       | AVG    |
| 3   | 2415.280        | 95.49          | -1.99                   | 93.50           | 54.00          | 39.50       | AVG    |

## 11n(HT20)\_TX\_CH\_01\_Vertical\_Peak




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2387.000        | 65.06          | -2.14                   | 62.92           | 74.00          | -11.08      | peak   |
| 2   | 2390.000        | 68.45          | -2.13                   | 66.32           | 74.00          | -7.68       | peak   |
| 3   | 2408.560        | 107.34         | -2.03                   | 105.31          | 74.00          | 31.31       | peak   |

11n(HT20)\_TX\_CH\_01\_Vertical\_Average




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2387.280        | 46.53          | -2.14                   | 44.39           | 54.00          | -9.61       | AVG    |
| 2   | 2390.000        | 51.64          | -2.13                   | 49.51           | 54.00          | -4.49       | AVG    |
| 3   | 2413.180        | 97.64          | -2.01                   | 95.63           | 54.00          | 41.63       | AVG    |

11n(HT20)\_TX\_CH\_11\_Horizontal\_Peak




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------|
| 1   | 2463.500        | 104.27         | -1.74                    | 102.53          | 74.00          | 28.53       | peak   |
| 2   | 2483.500        | 61.56          | -1.64                    | 59.92           | 74.00          | -14.08      | peak   |
| 3   | 2485.400        | 61.20          | -1.62                    | 59.58           | 74.00          | -14.42      | peak   |
| 4   | 2500.000        | 53.57          | -1.55                    | 52.02           | 74.00          | -21.98      | peak   |

11n(HT20)\_TX\_CH\_11\_Horizontal\_Average




11n(HT20)\_TX\_CH\_11\_Vertical\_Peak




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2458.550        | 105.16         | -1.77                   | 103.39          | 74.00          | 29.39       | peak   |
| 2   | 2483.500        | 64.65          | -1.64                   | 63.01           | 74.00          | -10.99      | peak   |
| 3   | 2485.250        | 63.56          | -1.62                   | 61.94           | 74.00          | -12.06      | peak   |
| 4   | 2500.000        | 52.95          | -1.55                   | 51.40           | 74.00          | -22.60      | peak   |

11n(HT20)\_TX\_CH\_11\_Vertical\_Average




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2457.200        | 95.56          | -1.77                   | 93.79           | 54.00          | 39.79       | AVG    |
| 2   | 2483.500        | 44.33          | -1.64                   | 42.69           | 54.00          | -11.31      | AVG    |
| 3   | 2485.550        | 42.26          | -1.62                   | 40.64           | 54.00          | -13.36      | AVG    |
| 4   | 2500.000        | 37.21          | -1.55                   | 35.66           | 54.00          | -18.34      | AVG    |

## 11(HE20)\_TX\_CH\_01\_Horizontal\_Peak




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2386.160        | 64.29          | -2.14                   | 62.15           | 74.00          | -11.85      | peak   |
| 2   | 2390.000        | 65.08          | -2.13                   | 62.95           | 74.00          | -11.05      | peak   |
| 3   | 2413.180        | 102.80         | -2.01                   | 100.79          | 74.00          | 26.79       | peak   |

## 11(HE20)\_TX\_CH\_01\_Horizontal\_Average




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2387.700        | 49.67          | -2.14                   | 47.53           | 54.00          | -6.47       | AVG    |
| 2   | 2390.000        | 52.58          | -2.13                   | 50.45           | 54.00          | -3.55       | AVG    |
| 3   | 2419.480        | 94.28          | -1.97                   | 92.31           | 54.00          | 38.31       | AVG    |

11(HE20)\_TX\_CH\_01\_Vertical\_Peak




11(HE20)\_TX\_CH\_01\_Vertical\_Average




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2387.420        | 51.86          | -2.14                   | 49.72           | 54.00          | -4.28       | AVG    |
| 2   | 2390.000        | 55.30          | -2.13                   | 53.17           | 54.00          | -0.83       | AVG    |
| 3   | 2409.400        | 96.30          | -2.02                   | 94.28           | 54.00          | 40.28       | AVG    |

11(HE20)\_TX\_CH\_11\_Horizontal\_Peak




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2467.250        | 105.42         | -1.72                   | 103.70          | 74.00          | 29.70       | peak   |
| 2   | 2483.500        | 61.36          | -1.64                   | 59.72           | 74.00          | -14.28      | peak   |
| 3   | 2485.250        | 61.91          | -1.62                   | 60.29           | 74.00          | -13.71      | peak   |
| 4   | 2500.000        | 51.46          | -1.55                   | 49.91           | 74.00          | -24.09      | peak   |

## 11(HE20)\_TX\_CH\_11\_Horizontal\_Average




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2459.150        | 92.50          | -1.76                   | 90.74           | 54.00          | 36.74       | AVG    |
| 2   | 2483.500        | 43.45          | -1.64                   | 41.81           | 54.00          | -12.19      | AVG    |
| 3   | 2486.150        | 41.72          | -1.62                   | 40.10           | 54.00          | -13.90      | AVG    |
| 4   | 2500.000        | 37.32          | -1.55                   | 35.77           | 54.00          | -18.23      | AVG    |

11(HE20)\_TX\_CH\_11\_Vertical\_Peak



11(HE20)\_TX\_CH\_11\_Vertical\_Average



| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 2459.150        | 93.51          | -1.76                   | 91.75           | 54.00          | 37.75       | AVG    |
| 2   | 2483.500        | 43.31          | -1.64                   | 41.67           | 54.00          | -12.33      | AVG    |
| 3   | 2484.500        | 43.03          | -1.64                   | 41.39           | 54.00          | -12.61      | AVG    |
| 4   | 2500.000        | 37.39          | -1.55                   | 35.84           | 54.00          | -18.16      | AVG    |

### 7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Measurement Distance: 3M

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 0.009-0.490    | 2400/F(kHz)                      | 300                          |
| 0.490-1.705    | 24000/F(kHz)                     | 30                           |
| 1.705-30.0     | 30                               | 30                           |
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| 960-1000       | 500                              | 3                            |

#### 7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 45.2 % RH

Atmospheric Pressure: 1010 mbar

#### 7.3.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                                                                                                                                                                                              |
|-----------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test            | 00        | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |

#### 7.3.3 Test Setup Diagram




#### 7.3.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1.  $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$
2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test Mode: 01; Polarity: Horizontal



| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>Factor(dB/m) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Height<br>(cm) | Degree<br>(deg.) | Remark |
|-----|--------------------|-------------------|-------------------------|--------------------|-------------------|----------------|----------------|------------------|--------|
| 1   | 31.73              | 2.52              | 23.60                   | 26.12              | 40.00             | -13.88         | 100            | 0                | QP     |
| 2   | 119.02             | 1.85              | 20.17                   | 22.02              | 43.50             | -21.48         | 200            | 47               | QP     |
| 3   | 227.69             | 9.62              | 18.59                   | 28.21              | 46.00             | -17.79         | 200            | 102              | QP     |
| 4   | 261.06             | 9.99              | 20.55                   | 30.54              | 46.00             | -15.46         | 100            | 123              | QP     |
| 5   | 744.87             | 2.74              | 29.67                   | 32.41              | 46.00             | -13.59         | 200            | 164              | QP     |
| 6   | 912.86             | 1.82              | 31.44                   | 33.26              | 46.00             | -12.74         | 100            | 295              | QP     |

Test Mode: 01; Polarity: Vertical



| No. | Frequency<br>(MHz) | Reading<br>(dBUV) | Correct<br>Factor(dB/m) | Result<br>(dBUV/m) | Limit<br>(dBUV/m) | Margin<br>(dB) | Height<br>(cm) | Degree<br>(deg.) | Remark |
|-----|--------------------|-------------------|-------------------------|--------------------|-------------------|----------------|----------------|------------------|--------|
| 1   | 30.85              | 2.10              | 24.44                   | 26.54              | 40.00             | -13.46         | 100            | 360              | QP     |
| 2   | 126.33             | 2.94              | 20.08                   | 23.02              | 43.50             | -20.48         | 100            | 341              | QP     |
| 3   | 224.52             | 11.28             | 18.57                   | 29.85              | 46.00             | -16.15         | 100            | 360              | QP     |
| 4   | 260.14             | 7.04              | 20.64                   | 27.68              | 46.00             | -18.32         | 100            | 29               | QP     |
| 5   | 779.61             | 1.54              | 30.48                   | 32.02              | 46.00             | -13.98         | 100            | 335              | QP     |
| 6   | 878.32             | 1.73              | 31.28                   | 33.01              | 46.00             | -12.99         | 100            | 29               | QP     |

## 7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.6

Measurement Distance: 3M

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| Above 1000     | 500                              | 3                            |

### 7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 45.2 % RH

Atmospheric Pressure: 1010 mbar

### 7.4.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-----------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test            | 00        | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |

### 7.4.3 Test Setup Diagram




#### 7.4.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle<98%) or 10Hz (Duty cycle $\geq$ 98%) for Average detection (AV) at frequency above 1GHz.

## 11b\_TX\_CH\_01\_Horizontal




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------|
| 1   | 4824.150        | 60.69          | -17.81                   | 42.88           | 74.00          | -31.12      | peak   |
| 2   | 7232.200        | 57.10          | -10.52                   | 46.58           | 74.00          | -27.42      | peak   |
| 3   | 9839.150        | 56.32          | -6.87                    | 49.45           | 74.00          | -24.55      | peak   |

## 11b\_TX\_CH\_01\_Vertical




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 4824.150        | 64.54          | -17.81                  | 46.73           | 74.00          | -27.27      | peak   |
| 2   | 8368.650        | 56.86          | -9.57                   | 47.29           | 74.00          | -26.71      | peak   |
| 3   | 10081.400       | 56.17          | -6.52                   | 49.65           | 74.00          | -24.35      | peak   |

## 11b\_TX\_CH\_06\_Horizontal




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 4873.450        | 61.08          | -17.59                  | 43.49           | 74.00          | -30.51      | peak   |
| 2   | 9006.150        | 57.44          | -8.18                   | 49.26           | 74.00          | -24.74      | peak   |
| 3   | 14052.600       | 55.57          | -3.39                   | 52.18           | 74.00          | -21.82      | peak   |

## 11b\_TX\_CH\_06\_Vertical




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 4874.300        | 61.70          | -17.59                  | 44.11           | 74.00          | -29.89      | peak   |
| 2   | 7243.250        | 56.54          | -10.49                  | 46.05           | 74.00          | -27.95      | peak   |
| 3   | 10537.850       | 55.78          | -6.09                   | 49.69           | 74.00          | -24.31      | peak   |

11b\_TX\_CH\_11\_Horizontal




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 4924.450        | 60.45          | -17.37                  | 43.08           | 74.00          | -30.92      | peak   |
| 2   | 7690.350        | 56.10          | -9.87                   | 46.23           | 74.00          | -27.77      | peak   |
| 3   | 9993.850        | 55.95          | -6.61                   | 49.34           | 74.00          | -24.66      | peak   |

11b\_TX\_CH\_11\_Vertical




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 4923.600        | 59.25          | -17.37                  | 41.88           | 74.00          | -32.12      | peak   |
| 2   | 7558.600        | 56.50          | -9.92                   | 46.58           | 74.00          | -27.42      | peak   |
| 3   | 9449.850        | 56.84          | -7.50                   | 49.34           | 74.00          | -24.66      | peak   |

## 11n(HT20)\_TX\_CH\_01\_Horizontal




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 7165.050        | 55.79          | -10.66                  | 45.13           | 74.00          | -28.87      | peak   |
| 2   | 9948.800        | 55.38          | -6.69                   | 48.69           | 74.00          | -25.31      | peak   |
| 3   | 11571.450       | 55.01          | -5.78                   | 49.23           | 74.00          | -24.77      | peak   |

11n(HT20)\_TX\_CH\_01\_Vertical




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 7681.000        | 58.19          | -9.87                   | 48.32           | 74.00          | -25.68      | peak   |
| 2   | 11079.300       | 56.02          | -6.02                   | 50.00           | 74.00          | -24.00      | peak   |
| 3   | 13298.650       | 55.54          | -4.29                   | 51.25           | 74.00          | -22.75      | peak   |

## 11n(HT20)\_TX\_CH\_06\_Horizontal




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 6756.200        | 54.36          | -11.95                  | 42.41           | 74.00          | -31.59      | peak   |
| 2   | 8970.450        | 55.18          | -8.26                   | 46.92           | 74.00          | -27.08      | peak   |
| 3   | 11585.050       | 54.94          | -5.78                   | 49.16           | 74.00          | -24.84      | peak   |

## 11n(HT20)\_TX\_CH\_06\_Vertical




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 6386.450        | 54.05          | -13.29                  | 40.76           | 74.00          | -33.24      | peak   |
| 2   | 8588.800        | 54.31          | -9.28                   | 45.03           | 74.00          | -28.97      | peak   |
| 3   | 11123.500       | 54.46          | -5.99                   | 48.47           | 74.00          | -25.53      | peak   |

## 11n(HT20)\_TX\_CH\_11\_Horizontal




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 7372.450        | 55.88          | -10.22                  | 45.66           | 74.00          | -28.34      | peak   |
| 2   | 9833.200        | 54.66          | -6.87                   | 47.79           | 74.00          | -26.21      | peak   |
| 3   | 11538.300       | 54.43          | -5.78                   | 48.65           | 74.00          | -25.35      | peak   |

## 11n(HT20)\_TX\_CH\_11\_Vertical




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 7141.250        | 55.36          | -10.71                  | 44.65           | 74.00          | -29.35      | peak   |
| 2   | 8032.900        | 55.21          | -9.73                   | 45.48           | 74.00          | -28.52      | peak   |
| 3   | 10707.850       | 54.12          | -6.08                   | 48.04           | 74.00          | -25.96      | peak   |

## 11ax(HE20)\_TX\_CH\_01\_Horizontal




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 5646.950        | 55.20          | -15.63                  | 39.57           | 74.00          | -34.43      | peak   |
| 2   | 7720.100        | 55.19          | -9.86                   | 45.33           | 74.00          | -28.67      | peak   |
| 3   | 10241.200       | 54.79          | -6.36                   | 48.43           | 74.00          | -25.57      | peak   |

## 11ax(HE20)\_TX\_CH\_01\_Verical




## 11ax(HE20)\_TX\_CH\_06\_Horizontal




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 6523.300        | 53.97          | -12.86                  | 41.11           | 74.00          | -32.89      | peak   |
| 2   | 8259.850        | 55.24          | -9.62                   | 45.62           | 74.00          | -28.38      | peak   |
| 3   | 10364.450       | 54.47          | -6.23                   | 48.24           | 74.00          | -25.76      | peak   |

## 11ax(HE20)\_TX\_CH\_06\_Vertical




| No. | Frequency (MHz) | Reading (dBuV) | Correction factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|-------------------------|-----------------|----------------|-------------|--------|
| 1   | 7245.800        | 55.74          | -10.49                  | 45.25           | 74.00          | -28.75      | peak   |
| 2   | 9480.450        | 55.06          | -7.45                   | 47.61           | 74.00          | -26.39      | peak   |
| 3   | 11405.700       | 54.66          | -5.83                   | 48.83           | 74.00          | -25.17      | peak   |

## 11ax(HE20)\_TX\_CH\_11\_Horizontal



## 11ax(HE20)\_TX\_CH\_11\_Vertical



## 7.5 Conducted Average Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2020) Section 11.9.2

Limit:

| Frequency range(MHz) | Output power of the intentional radiator(watt)         |
|----------------------|--------------------------------------------------------|
| 902-928              | 1 for $\geq 50$ hopping channels                       |
|                      | 0.25 for $25 \leq$ hopping channels $< 50$             |
|                      | 1 for digital modulation                               |
| 2400-2483.5          | 1 for $\geq 75$ non-overlapping hopping channels       |
|                      | 0.125 for all other frequency hopping systems          |
|                      | 1 for digital modulation                               |
| 5725-5850            | 1 for frequency hopping systems and digital modulation |

### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 25.1 °C


Humidity: 45.2 % RH

Atmospheric Pressure: 1010 mbar

### 7.5.2 Test Mode Description

| Pre-scan /<br>Final test | Mode<br>Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------------------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test               | 00           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11ax(HE20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |

### 7.5.3 Test Setup Diagram



### 7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details

## 7.6 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2020) Section 11.8.1

Limit:

≥500 kHz

### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 25.1 °C


Humidity: 45.2 % RH

Atmospheric Pressure: 1010 mbar

### 7.6.2 Test Mode Description

| Pre-scan /<br>Final test | Mode<br>Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------------------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test               | 00           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11ax(HE20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |

### 7.6.3 Test Setup Diagram



### 7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

## 7.7 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2020) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 25.1 °C


Humidity: 45.2 % RH

Atmospheric Pressure: 1010 mbar

### 7.7.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test            | 00        | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11ax(HE20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |

### 7.7.3 Test Setup Diagram



### 7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

## 7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 6.10.4

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 25.1 °C


Humidity: 45.2 % RH

Atmospheric Pressure: 1010 mbar

### 7.8.2 Test Mode Description

| Pre-scan /<br>Final test | Mode<br>Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------------------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test               | 00           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11ax(HE20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |

## 7.8.3 Test Setup Diagram



## 7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

## 7.9 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 25.1 °C


Humidity: 45.2 % RH

Atmospheric Pressure: 1010 mbar

### 7.9.2 Test Mode Description

| Pre-scan /<br>Final test | Mode<br>Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------------------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test               | 00           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11ax(HE20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |

## 7.9.3 Test Setup Diagram



## 7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Report No.: KSCR250800189202

Page: 69 of 120

## **8 Test Setup Photo**

Refer to Appendix - Test Setup Photo for KSCR2508001892AT

## **9 EUT Constructional Details (EUT Photos)**

Refer to Appendix\_Photographs of EUT Constructional Details for KSCR2508001892AT



## 10 Appendix

### 1. Duty Cycle


#### 1.1 Test Result

##### 1.1.1 Ant1


| Ant1            |         |                 |    |        |           |             |                |                                   |                       |
|-----------------|---------|-----------------|----|--------|-----------|-------------|----------------|-----------------------------------|-----------------------|
| Mode            | TX Type | Frequency (MHz) | RU | RU Pos | T_on (ms) | Period (ms) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) | Max. DC Variation (%) |
| 802.11b         | SISO    | 2412            | /  | /      | 12.437    | 12.510      | 99.42          | 0.03                              | 0.08                  |
|                 |         | 2437            | /  | /      | 12.437    | 12.520      | 99.34          | 0.03                              | 0.11                  |
|                 |         | 2462            | /  | /      | 12.437    | 12.517      | 99.36          | 0.03                              | 0.13                  |
| 802.11g         | SISO    | 2412            | /  | /      | 5.486     | 5.564       | 98.60          | 0.06                              | 0.18                  |
|                 |         | 2437            | /  | /      | 5.486     | 5.564       | 98.60          | 0.06                              | 0.18                  |
|                 |         | 2462            | /  | /      | 5.486     | 5.564       | 98.60          | 0.06                              | 0.18                  |
| 802.11n (HT20)  | SISO    | 2412            | /  | /      | 5.374     | 5.452       | 98.57          | 0.06                              | 0.18                  |
|                 |         | 2437            | /  | /      | 5.374     | 5.452       | 98.57          | 0.06                              | 0.20                  |
|                 |         | 2462            | /  | /      | 5.374     | 5.452       | 98.57          | 0.06                              | 0.17                  |
| 802.11ax (HE20) | SISO    | 2412            | SU | /      | 4.644     | 4.724       | 98.31          | 0.07                              | 0.20                  |
|                 |         | 2437            | SU | /      | 4.645     | 4.725       | 98.31          | 0.07                              | 0.21                  |
|                 |         | 2462            | SU | /      | 4.645     | 4.725       | 98.31          | 0.07                              | 0.21                  |

## 1.2 Test Graph


### 1.2.1 Ant1




## 802.11b HCH 2462MHz Ant1 (SISO) NTN




## 802.11g LCH 2412MHz Ant1 (SISO) NTN




## 802.11g\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




## 802.11g\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_LCH\_2412MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




## 802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




## 802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTN



## 802.11ax(HE20) MCH\_2437MHz\_SU / Ant1 (SISO) NTN



## 802.11ax(HE20) HCH\_2462MHz\_SU / Ant1 (SISO) NTN



## 2. Bandwidth

### 2.1 Test Result

#### 2.1.1 OBW

| Mode            | TX Type | Frequency (MHz) | RU | RU Pos | ANT | 99% Occupied Bandwidth (MHz) |       | Verdict |
|-----------------|---------|-----------------|----|--------|-----|------------------------------|-------|---------|
|                 |         |                 |    |        |     | Result                       | Limit |         |
| 802.11b         | SISO    | 2412            | /  | /      | 1   | 12.025                       | /     | Pass    |
|                 |         | 2437            | /  | /      | 1   | 12.079                       | /     | Pass    |
|                 |         | 2462            | /  | /      | 1   | 12.061                       | /     | Pass    |
| 802.11g         | SISO    | 2412            | /  | /      | 1   | 16.852                       | /     | Pass    |
|                 |         | 2437            | /  | /      | 1   | 16.946                       | /     | Pass    |
|                 |         | 2462            | /  | /      | 1   | 16.965                       | /     | Pass    |
| 802.11n (HT20)  | SISO    | 2412            | /  | /      | 1   | 17.730                       | /     | Pass    |
|                 |         | 2437            | /  | /      | 1   | 17.767                       | /     | Pass    |
|                 |         | 2462            | /  | /      | 1   | 17.735                       | /     | Pass    |
| 802.11ax (HE20) | SISO    | 2412            | SU | /      | 1   | 18.391                       | /     | Pass    |
|                 |         | 2437            | SU | /      | 1   | 18.450                       | /     | Pass    |
|                 |         | 2462            | SU | /      | 1   | 18.480                       | /     | Pass    |


#### 2.1.2 6dB BW

| Mode            | TX Type | Frequency (MHz) | RU | RU Pos | ANT | 6dB Bandwidth (MHz) |            | Verdict |
|-----------------|---------|-----------------|----|--------|-----|---------------------|------------|---------|
|                 |         |                 |    |        |     | Result              | Limit      |         |
| 802.11b         | SISO    | 2412            | /  | /      | 1   | 8.220               | $\geq 0.5$ | Pass    |
|                 |         | 2437            | /  | /      | 1   | 8.241               | $\geq 0.5$ | Pass    |
|                 |         | 2462            | /  | /      | 1   | 8.226               | $\geq 0.5$ | Pass    |
| 802.11g         | SISO    | 2412            | /  | /      | 1   | 16.335              | $\geq 0.5$ | Pass    |
|                 |         | 2437            | /  | /      | 1   | 16.425              | $\geq 0.5$ | Pass    |
|                 |         | 2462            | /  | /      | 1   | 16.452              | $\geq 0.5$ | Pass    |
| 802.11n (HT20)  | SISO    | 2412            | /  | /      | 1   | 17.258              | $\geq 0.5$ | Pass    |
|                 |         | 2437            | /  | /      | 1   | 17.283              | $\geq 0.5$ | Pass    |
|                 |         | 2462            | /  | /      | 1   | 17.098              | $\geq 0.5$ | Pass    |
| 802.11ax (HE20) | SISO    | 2412            | SU | /      | 1   | 17.145              | $\geq 0.5$ | Pass    |
|                 |         | 2437            | SU | /      | 1   | 17.392              | $\geq 0.5$ | Pass    |
|                 |         | 2462            | SU | /      | 1   | 17.176              | $\geq 0.5$ | Pass    |


## 2.2 Test Graph

### 2.2.1 OBW


802.11b LCH 2412MHz\_Ant1 (SISO)\_NTNV




802.11b MCH 2437MHz\_Ant1 (SISO)\_NTNV




802.11b HCH 2462MHz Ant1 (SISO) NTN




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




802.11g\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_LCH\_2412MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTNV




802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTNV



## 802.11ax(HE20) MCH\_2437MHz\_SU / Ant1 (SISO) NTN




## 802.11ax(HE20) HCH\_2462MHz\_SU / Ant1 (SISO) NTN




## 2.2.2 6dB BW


802.11b LCH 2412MHz\_Ant1 (SISO)\_NTNV




802.11b MCH 2437MHz\_Ant1 (SISO)\_NTNV




## 802.11b HCH 2462MHz Ant1 (SISO) NTN




## 802.11g LCH 2412MHz Ant1 (SISO) NTN




## 802.11g\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




## 802.11g\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20) LCH\_2412MHz\_Ant1 (SISO) NTN




802.11n(HT20) MCH\_2437MHz\_Ant1 (SISO) NTN




## 802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




## 802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTN



## 802.11ax(HE20) MCH 2437MHz SU / Ant1 (SISO) NTN



## 802.11ax(HE20) HCH 2462MHz SU / Ant1 (SISO) NTN



### 3. Maximum Conducted Output Power

#### 3.1 Test Result


##### 3.1.1 Power

| Mode            | TX Type | Frequency (MHz) | RU | RU Pos | Maximum Average Conducted Output Power (dBm) |       | Verdict |
|-----------------|---------|-----------------|----|--------|----------------------------------------------|-------|---------|
|                 |         |                 |    |        | ANT1                                         | Limit |         |
| 802.11b         | SISO    | 2412            | /  | /      | 15.27                                        | <=30  | Pass    |
|                 |         | 2437            | /  | /      | 14.35                                        | <=30  | Pass    |
|                 |         | 2462            | /  | /      | 15.28                                        | <=30  | Pass    |
| 802.11g         | SISO    | 2412            | /  | /      | 14.33                                        | <=30  | Pass    |
|                 |         | 2437            | /  | /      | 13.39                                        | <=30  | Pass    |
|                 |         | 2462            | /  | /      | 13.42                                        | <=30  | Pass    |
| 802.11n (HT20)  | SISO    | 2412            | /  | /      | 14.11                                        | <=30  | Pass    |
|                 |         | 2437            | /  | /      | 13.16                                        | <=30  | Pass    |
|                 |         | 2462            | /  | /      | 13.19                                        | <=30  | Pass    |
| 802.11ax (HE20) | SISO    | 2412            | SU | /      | 13.85                                        | <=30  | Pass    |
|                 |         | 2437            | SU | /      | 13.41                                        | <=30  | Pass    |
|                 |         | 2462            | SU | /      | 12.98                                        | <=30  | Pass    |


Note1: Antenna Gain: Ant1: 1.42dBi;

## 3.2 Test Graph


### 3.2.1 Power




## 802.11b HCH 2462MHz Ant1 (SISO) NTN




## 802.11g LCH 2412MHz Ant1 (SISO) NTN




## 802.11g\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




## 802.11g\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_LCH\_2412MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




## 802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




## 802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTN



## 802.11ax(HE20) MCH\_2437MHz\_SU / Ant1 (SISO) NTN



## 802.11ax(HE20) HCH\_2462MHz\_SU / Ant1 (SISO) NTN



## 4. Maximum Power Spectral Density

### 4.1 Test Result


#### 4.1.1 PSD

| Mode            | TX Type | Frequency (MHz) | RU | RU Pos | Maximum PSD (dBm) |       | Verdict |
|-----------------|---------|-----------------|----|--------|-------------------|-------|---------|
|                 |         |                 |    |        | ANT1              | Limit |         |
| 802.11b         | SISO    | 2412            | /  | /      | -1.38             | <=8   | Pass    |
|                 |         | 2437            | /  | /      | -2.14             | <=8   | Pass    |
|                 |         | 2462            | /  | /      | -1.23             | <=8   | Pass    |
| 802.11g         | SISO    | 2412            | /  | /      | -5.34             | <=8   | Pass    |
|                 |         | 2437            | /  | /      | -6.48             | <=8   | Pass    |
|                 |         | 2462            | /  | /      | -6.03             | <=8   | Pass    |
| 802.11n (HT20)  | SISO    | 2412            | /  | /      | -5.59             | <=8   | Pass    |
|                 |         | 2437            | /  | /      | -6.60             | <=8   | Pass    |
|                 |         | 2462            | /  | /      | -6.18             | <=8   | Pass    |
| 802.11ax (HE20) | SISO    | 2412            | SU | /      | -6.81             | <=8   | Pass    |
|                 |         | 2437            | SU | /      | -7.46             | <=8   | Pass    |
|                 |         | 2462            | SU | /      | -7.92             | <=8   | Pass    |


Note1: Antenna Gain: Ant1: 1.42dBi;

## 4.2 Test Graph


### 4.2.1 PSD




## 802.11b HCH 2462MHz Ant1 (SISO) NTNV




## 802.11g LCH 2412MHz Ant1 (SISO) NTNV




## 802.11g\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




## 802.11g\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_LCH\_2412MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTN



## 802.11ax(HE20) MCH\_2437MHz\_SU / Ant1 (SISO) NTN



## 802.11ax(HE20) HCH\_2462MHz\_SU / Ant1 (SISO) NTN



## 5. Unwanted Emissions In Non-restricted Frequency Bands

### 5.1 Test Result

#### 5.1.1 Ref

| Mode            | TX Type | Frequency (MHz) | RU | RU Pos | ANT | Level of Reference (dBm) |
|-----------------|---------|-----------------|----|--------|-----|--------------------------|
| 802.11b         | SISO    | 2412            | /  | /      | 1   | 7.59                     |
|                 |         | 2437            | /  | /      | 1   | 6.69                     |
|                 |         | 2462            | /  | /      | 1   | 7.60                     |
| 802.11g         | SISO    | 2412            | /  | /      | 1   | 3.72                     |
|                 |         | 2437            | /  | /      | 1   | 2.43                     |
|                 |         | 2462            | /  | /      | 1   | 2.95                     |
| 802.11n (HT20)  | SISO    | 2412            | /  | /      | 1   | 3.83                     |
|                 |         | 2437            | /  | /      | 1   | 2.94                     |
|                 |         | 2462            | /  | /      | 1   | 3.37                     |
| 802.11ax (HE20) | SISO    | 2412            | SU | /      | 1   | 3.43                     |
|                 |         | 2437            | SU | /      | 1   | 2.79                     |
|                 |         | 2462            | SU | /      | 1   | 2.88                     |

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.


#### 5.1.2 CSE

| Mode            | TX Type | Frequency (MHz) | RU | RU Pos | ANT | Level of Reference (dBm) | Limit (dBm) | Verdict |
|-----------------|---------|-----------------|----|--------|-----|--------------------------|-------------|---------|
| 802.11b         | SISO    | 2412            | /  | /      | 1   | 7.60                     | -22.40      | Pass    |
|                 |         | 2437            | /  | /      | 1   | 7.60                     | -22.40      | Pass    |
|                 |         | 2462            | /  | /      | 1   | 7.60                     | -22.40      | Pass    |
| 802.11g         | SISO    | 2412            | /  | /      | 1   | 3.72                     | -26.28      | Pass    |
|                 |         | 2437            | /  | /      | 1   | 3.72                     | -26.28      | Pass    |
|                 |         | 2462            | /  | /      | 1   | 3.72                     | -26.28      | Pass    |
| 802.11n (HT20)  | SISO    | 2412            | /  | /      | 1   | 3.83                     | -26.17      | Pass    |
|                 |         | 2437            | /  | /      | 1   | 3.83                     | -26.17      | Pass    |
|                 |         | 2462            | /  | /      | 1   | 3.83                     | -26.17      | Pass    |
| 802.11ax (HE20) | SISO    | 2412            | SU | /      | 1   | 3.43                     | -26.57      | Pass    |
|                 |         | 2437            | SU | /      | 1   | 3.43                     | -26.57      | Pass    |
|                 |         | 2462            | SU | /      | 1   | 3.43                     | -26.57      | Pass    |


Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.

## 5.2 Test Graph


### 5.2.1 Ref




## 802.11b HCH 2462MHz Ant1 (SISO) NTN




## 802.11g LCH 2412MHz Ant1 (SISO) NTN




## 802.11g\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




## 802.11g\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_LCH\_2412MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTN



## 802.11ax(HE20) MCH 2437MHz SU / Ant1 (SISO) NTN




## 802.11ax(HE20) HCH 2462MHz SU / Ant1 (SISO) NTN




## 5.2.2 CSE


802.11b LCH 2412MHz\_Ant1 (SISO)\_NTNV




802.11b LCH 2412MHz\_Ant1 (SISO)\_NTNV




## 802.11b MCH 2437MHz Ant1 (SISO) NTN




## 802.11b HCH 2462MHz Ant1 (SISO) NTN




## 802.11b HCH 2462MHz\_Ant1 (SISO)\_NTNV




## 802.11g LCH 2412MHz\_Ant1 (SISO)\_NTNV




## 802.11g LCH 2412MHz\_Ant1 (SISO) NTN




## 802.11g MCH 2437MHz\_Ant1 (SISO) NTN




## 802.11g\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




## 802.11g\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




802.11n(HT20) LCH\_2412MHz\_Ant1 (SISO) NTN




802.11n(HT20) LCH\_2412MHz\_Ant1 (SISO) NTN




## 802.11n(HT20)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




## 802.11n(HT20)\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




## 802.11n(HT20) HCH 2462MHz\_Ant1 (SISO) NTN




## 802.11ax(HE20) LCH 2412MHz\_SU / Ant1 (SISO) NTN




## 802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTN




## 802.11ax(HE20) MCH 2437MHz SU / Ant1 (SISO) NTN



## 802.11ax(HE20) HCH 2462MHz SU / Ant1 (SISO) NTN



## 802.11ax(HE20) HCH 2462MHz SU / Ant1 (SISO) NTN



- End of the Report -