TEST REPORT

KES Co., Ltd.
#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu,
Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

■ **FCC TEST REPORT**

1. Client

○ Name : JLU Co.,Ltd.
○ Address : 410-412, Busan Knowledge Industry Center 111, Hyoyeol-ro, Buk-gu, Busan, South Korea

2. Sample Description

○ Product item : Skin Care Device
○ Model name : JAH-P100A
○ Manufacturer etc. : JLU Co.,Ltd.

3. Date of test : 2026.09.04 ~ 2026.09.15

4. Location of Test : ☑ Permanent Testing Lab ☐ On Site Testing
○ Address : 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Rep. of Korea

5. FCC Rule part(s) : Part 15 Subpart C 15.247

6. Test result : PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
This test report cannot be reproduced and copied without permission without the written consent of KES Co., Ltd.
This laboratory is not accredited for the test results marked *.
This test report is not related to KOLAS accreditation.

Affirmation	Tested by Name : Myeong-Ho, Lee (Signature) [이명호]2026/10/07	Technical Manager Name : Yeong-Jun Cho (Signature) [조영준]2026/10/07

2026. 10. 07.

KES Co., Ltd.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

REPORT REVISION HISTORY

Date	Test Report No.	Revision History
2026.09.16	KES-RF260617	Initial
2026.10.07	KES-RF260617-R1	Correction of antenna gain value (page.4)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

TABLE OF CONTENTS

1. General information 4
1.1. EUT description 4
1.2. Test configuration 4
1.3. Information about derivative model 4
1.4. Accessory information 5
1.5. Device modifications 5
1.6. Sample calculation 5
1.7. Measurement Uncertainty 6
1.8. Frequency/channel operations 6
2. Summary of tests 7
3. Test results 8
3.1. 6 dB bandwidth 8
3.2. Output power 10
3.3. Power spectral density 12
3.4. Radiated restricted band and emissions 14
3.5. Conducted spurious emissions & band edge 27
3.6. AC conducted emissions 30
3.7. Antenna Requirement 33
Appendix A. Measurement equipment 34

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

1. General information

Applicant:	JLU Co.,Ltd.
Applicant address:	410-412, Busan Knowledge Industry Center 111, Hyoyeol-ro, Buk-gu, Busan, South Korea
Test site:	KES Co., Ltd.
Test site address:	☐ #3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Rep. of Korea ☒ 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Rep. of Korea
Test Facility	FCC Accreditation Designation No.: KR0100, Registration No.: 444148
FCC rule part(s):	15.247
FCC ID:	2BHHE-JAH-P100A
Test device serial No.:	☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test	Skin Care Device
Frequency range & Number of channels	2 402 ㎒ ~ 2 480 ㎒ (LE 1 Mbps) : 40 ch
Model	JAH-P100A
Modulation technique	GFSK
Antenna specification	PCB Antenna // Peak gain : -5.02 ㏈I
Power source	DC 7.4 V (Battery)
H/W version	0.12V
S/W version	227A

1.2. Test configuration

The **JLU Co.,Ltd. // Skin Care Device // JAH-P100A // FCC ID: 2BHHE-JAH-P100A** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15.247
KDB 558074 D01 v05 r02
ANSI C63.10-2020

1.3. Information about derivative model

N/A

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

1.4. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
Cradle	JLU Co.,Ltd.	-	-	DC 5 V (USB C-Type)
USB Cable	-	-	-	-

1.5. Device modifications

N/A

1.6. Sample calculation

Where relevant, the following sample calculation is provided
For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Offset(㏈) = RF cable loss(㏈) + attenuator factor(㏈).
= 1.08 + 20 = 21.08 (㏈)

For Radiation test :
Field strength level (㏈㎶/m) = Measured level (㏈㎶) + Antenna factor (㏈) + Cable loss (㏈) – Amplifier gain (㏈)

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

1.7. Measurement Uncertainty

Test Item		Uncertainty
Uncertainty for Radiation emission test (include Fundamental emission)	Below 1 ㎓	4.04 ㏈ (SAC #6)
	Above 1 ㎓	5.32 ㏈ (SAC #5)
Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of *k*=2.		

1.8. Frequency/channel operations

Ch.	Frequency (㎒)	Mode
00	2 402	LE 1 Mbps
⋮	⋮	⋮
19	2 440	LE 1 Mbps
⋮	⋮	⋮
39	2 480	LE 1 Mbps

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

2. Summary of tests

Section in FCC Part 15	Test description	Test results
15.247(a)(2)	6 dB bandwidth	Pass
15.247(b)(3)	Output power	Pass
15.247(e)	Power spectral density	Pass
15.205,15.209	Radiated restricted band and emission	Pass
15.247(d)	Conducted spurious emission and band edge	Pass
15.207(a)	AC Conducted emissions	Pass[note.1]
15.203	Antenna Requirement	Pass

Note.

1. The product can be charged by two methods: via a USB Type-C cable or a charging cradle. When the product is placed on the charging cradle for charging, the product cannot be operated or used, and therefore data communication is not performed during charging via the charging cradle.
2. By the request of applicant, test is performed with power setting value below :

Mode	Frequency (㎒)	Setting value
LE 1 Mbps	2 402 ~ 2 480	8

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

3. Test results

3.1. 6 dB bandwidth

Test procedure

ANSI C63.10-2020 - 11.8.2

Test setup



The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW ≥ 3 × RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate 902 ~ 928 MHz, 2 400 ~ 2 483.5 MHz, and 5 725 ~ 5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Results

Mode : LE 1 Mbps

Frequency(㎒)	6 ㏈ bandwidth(㎒)	Limit(㎒)
2 402	0.717	≥ 0.500
2 440	0.705	
2 480	0.697	

Test plots

LE 1 Mbps







Blank

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

3.2. Output power

Test procedure

ANSI C63.10-2020 - Section 11.9.1.2 and 11.9.2.3.2

Test setup



ANSI C63.10-2020 - Section 11.9.1.2

The maximum peak conducted output power may be measured using a broadband peak RF power m eter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwi dth and shall use a fast-responding diode detector.

ANSI C63.10-2020 - Section 11.9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 ㎒, 2 400~2 483.5 ㎒, and 5 725~5 850 ㎒ bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Test results

Mode	2 402 ㎒		2 440 ㎒		2 480 ㎒		Power Limit (dBm)
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	
LE 1 Mbps	7.69	8.13	7.83	8.18	7.80	8.16	30.00

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

3.3. Power spectral density

Test procedure

ANSI C63.10-2020 - Section 11.10.2

Test setup



a. Set analyzer center frequency to DTS channel center frequency.
b. Set the span to 1.5 times the DTS bandwidth.
c. Set the RBW to 3 ㎑ ≤ RBW ≤ 100 ㎑
d. Set the VBW ≥ [3 × RBW].
e. Detector = peak.
f. Sweep time = auto couple.
g. Trace mode = max hold.
h. Allow trace to fully stabilize.
i. Use the peak marker function to determine the maximum amplitude level within the RBW.
j. If measured value exceeds requirement, then reduce RBW (but no less than 3 ㎑) and repeat.

Limit

According to §15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 ㏈m in any 3 ㎑ band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Results

Mode : LE 1 Mbps

Frequency(㎒)	PSD (�dBm/3 ㎑)	Limit(㎑dBm/3 ㎑)
2 402	-8.56	≤ 8
2 440	-8.49	
2 480	-8.52	

Test plots

LE 1 Mbps







Blank

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

3.4. Radiated restricted band and emissions

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 ㎑ to 30 ㎒ Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 ㎒ to 1 ㎓ emissions.



You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

The diagram below shows the test setup that is utilized to make the measurements for emission from 1 ㎓ to the tenth harmonic of the highest fundamental frequency or to 40 ㎓ emissions, whichever is lower.



Test procedure

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2020

Test procedure below 30 ㎒

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that **parallel** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **parallel.**
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

Test procedure above 30 ㎒

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground for 30 ㎒-1 ㎓ and 1.5 meters for above 1 ㎓ at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

5. Spectrum analyzer settings for *f* < 1 ㎓:
   ① Span = wide enough to fully capture the emission being measured
   ② RBW = 120 ㎑
   ③ VBW ≥ RBW
   ④ Detector = quasi peak
   ⑤ Sweep time = auto
   ⑥ Trace = max hold
6. Spectrum analyzer settings for *f* ≥1 ㎓: Peak
   ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
   ② RBW = 1 ㎒
   ③ VBW ≥ 3 ㎒
   ④ Detector = peak
   ⑤ Sweep time = auto
   ⑥ Trace = max hold
   ⑦ Trace was allowed to stabilize

7. Spectrum analyzer settings for *f* ≥1 ㎓: Average
   ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
   ② RBW = 1 ㎒
   ③ VBW ≥ 3 × RBW
   ④ Detector = RMS, if span/(# of points in sweep) ≤ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
   ⑤ Averaging type = power(i.e., RMS)
      1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
      2) Some instruments require linear display mode in order to use linear voltage averaging. Log or ㏈ averaging shall not be used.
   ⑥ Sweep = auto
   ⑦ Trace = max hold
   ⑧ Perform a trace average of at least 100 traces.
   ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
      1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is 10 log(1/x), where x is the duty cycle.
      2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is 20 log(1/x), where x is the duty cycle.
      3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Note.

1. *f* <30 ㎒, extrapolation factor of 40 ㏈/decade of distance. F_d = 40log(D_m/Ds)
   f ≥30 ㎒, extrapolation factor of 20 ㏈/decade of distance. F_d = 20log(D_m/Ds)
   Where:
   F_d = Distance factor in ㏈
   D_m = Measurement distance in meters
   D_s = Specification distance in meters
2. Field strength(㏈㎶/m) = Level(㏈㎶) + CF (㏈) + or DCF(㏈)
3. Margin(㏈) = Limit(㏈㎶/m) - Field strength(㏈㎶/m)
4. Emissions below 18 ㎓ were measured at a 3 meter test distance while emissions above 18 ㎓ were measured at a 1 meter test distance with the application of a distance correction factor.
5. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation.**
6. The worst-case emissions are reported however emissions whose levels were not within 20 ㏈ of respective limits were not reported.
7. According to exploratory test no any obvious emission were detected from 9 ㎑ to 30 ㎒. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values：

Frequency (㎒)	Distance (Meters)	Radiated (㎶/m)
0.009 ~ 0.490	300	2400/F(㎑)
0.490 ~ 1.705	30	24000/F(㎑)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 ㎒, 76 ~ 88 ㎒, 174 ~ 216 ㎒ or 470 ~ 806 ㎒. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Duty cycle

Regarding to KDB 558074 D01_v05 r02, 6. Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

a) A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on- and off-times of the transmitted signal.

b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on- and off-times of the transmitted signal.

Mode	T_{on} time (㎳)	Period (㎳)	Duty cycle (Linear)	Duty cycle (%)	Duty cycle correction factor (㏈)
LE 1 Mbps	0.604	1.250	0.48	48.32	3.16

Duty cycle (Linear) = T_{on} time/Period

DCF(Duty cycle correction factor (㏈)) = 10log(1/duty cycle)

LE 1 Mbps



Note.

1. Tested with the maximum duty that can be set on the EUT.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Test results (Below 30 ㎒)

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	19 (Worst case)

Parallel



Note.
1. No spurious emission were detected under 30 ㎒.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Test results (Below 1 000 ㎒)

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	19 (Worst case)

Horizontal // Vertical



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	37.760	V	29.5	-14.7	14.8	40.0	25.2	165.0	7.5	
2	45.641	V	29.6	-12.2	17.4	40.0	22.6	114.0	37.6	
3	52.431	V	31.3	-12.2	19.1	40.0	20.9	163.0	16.7	
4	59.949	V	30.8	-13.1	17.7	40.0	22.3	129.0	14.0	
5	132.941	H	30.9	-16.9	14.0	43.5	29.5	211.0	350.6	
6	148.583	H	33.5	-17.3	16.2	43.5	27.3	230.0	356.6	
7	164.345	H	37.3	-16.7	20.6	43.5	22.9	218.0	202.3	
8	171.741	H	33.2	-16.2	17.0	43.5	26.5	167.0	355.6	
9	219.999	V	34.4	-12.6	21.8	46.0	24.2	113.0	2.4	
10	240.975	H	31.4	-12.1	19.3	46.0	26.7	107.0	71.0	
11	538.280	H	29.4	-6.2	23.2	46.0	22.8	185.0	177.7	
12	748.406	V	28.6	-2.0	26.6	46.0	19.4	166.0	26.4	

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Test results (Above 1 000 ㎒)

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	00

- **Spurious**

Frequency (㎒)	Level (dB㎛)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB㎛/m)	Limit (dB㎛/m)	Margin (dB)
1 008.10	44.56	Peak	H	-9.43	-	35.13	74.00	38.87
1 079.29	44.45	Peak	V	-9.01	-	35.44	74.00	38.56

- **Band edge**

Frequency (㎒)	Level (dB㎛)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB㎛/m)	Limit (dB㎛/m)	Margin (dB)
2 376.67	45.53	Peak	H	-1.13	-	44.40	74.00	29.60
2 377.76	45.49	Peak	V	-1.13	-	44.36	74.00	29.64

Restricted band // Horizontal // Peak



Restricted band // Vertical // Peak



You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Horizontal // Peak for 1 ㎓ to 3 ㎓	Vertical // Peak for 1 ㎓ to 3 ㎓
	
Horizontal // Peak for 3 ㎓ to 18 ㎓	**Vertical // Peak for 3 ㎓ to 18 ㎓**
	

Note.

1. Average test would be performed if the peak result were greater than the average limit.
2. No spurious emission were detected above 3 ㎓.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	19

- **Spurious**

Frequency (㎒)	Level (dB㎶)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
1 014.90	44.71	Peak	V	-9.39	-	35.32	74.00	38.68
1 025.70	44.04	Peak	H	-9.33	-	34.71	74.00	39.29

Horizontal // Peak for 1 ㎓ to 3 ㎓



Vertical // Peak for 1 ㎓ to 3 ㎓



Horizontal // Peak for 3 ㎓ to 18 ㎓



Vertical // Peak for 3 ㎓ to 18 ㎓



Note.
1. Average test would be performed if the peak result were greater than the average limit.
2. No spurious emission were detected above 3 ㎓.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	39

- **Spurious**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 034.10	44.16	Peak	V	-9.28	-	34.88	74.00	39.12
1 091.29	43.68	Peak	H	-8.93	-	34.75	74.00	39.25

- **Band edge**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 483.51	51.83	Peak	H	-0.88	-	50.95	74.00	23.05
2 483.96	47.19	Peak	V	-0.88	-	46.31	74.00	27.69

Restricted band // Horizontal // Peak



Restricted band // Vertical // Peak



You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Horizontal // Peak for 1 ㎓ to 3 ㎓



Vertical // Peak for 1 ㎓ to 3 ㎓



Horizontal // Peak for 3 ㎓ to 18 ㎓



Vertical // Peak for 3 ㎓ to 18 ㎓



Note.

1. Average test would be performed if the peak result were greater than the average limit.
2. No spurious emission were detected above 3 ㎓.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Test results (18 ㎓ to 30 ㎓) – Worst case

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	19

Horizontal // Peak	Vertical // Peak
	

Note.
1. No spurious emission were detected above 18 ㎓.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

3.5. Conducted spurious emissions & band edge

Test setup



Test procedure

Band edge

ANSI C63.10-2020 - Section 11.11

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Set the RBW = 100 ㎑
4. Set the VBW = [3 × RBW].
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow trace to fully stabilize.

Out of band emissions

ANSI C63.10-2020 - Section 11.11

1. Start frequency was set to 30 ㎒ and stop frequency was set to 25 ㎓ for 2.4 ㎓ frequencies and 40 ㎓ for 5 ㎓ frequencies
2. Set the RBW = 100 ㎑
3. Set the VBW = [3 × RBW].
4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Allow trace to fully stabilize.

Limit

According to 15.247(d), in any 100 ㎑ bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 ㏈ below that in the 100 ㎑ bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval , as permitted under paragraph(b)(3) of this section , the attenuation required under this paragraph shall be 30 ㏈ instead of 20 ㏈. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Test results

LE 1 Mbps	
2 402 MHz	**2 440 MHz**
	
	
	

LE 1 Mbps	
2 480 MHz	
	
	Blank

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

3.6. AC conducted emissions

Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 ㎑ to 30 ㎒, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (㎒)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Test results

Mode: LE 1 Mbps / USB Cable

Channel: 19 (Worst case)

Hot Line



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.210000	34.89	---	63.21	28.32	1000.0	9.000	L1	19.7
0.210000	---	29.48	53.21	23.73	1000.0	9.000	L1	19.7
0.366000	---	25.69	48.59	22.90	1000.0	9.000	L1	19.7
0.366000	36.27	---	58.59	22.32	1000.0	9.000	L1	19.7
0.790000	38.30	---	56.00	17.70	1000.0	9.000	L1	19.7
0.790000	---	28.68	46.00	17.32	1000.0	9.000	L1	19.7
0.882000	---	24.01	46.00	21.99	1000.0	9.000	L1	19.7
0.882000	31.88	---	56.00	24.12	1000.0	9.000	L1	19.7
5.190000	17.29	---	60.00	42.71	1000.0	9.000	L1	20.0
5.190000	---	13.47	50.00	36.53	1000.0	9.000	L1	20.0
12.718000	15.96	---	60.00	44.04	1000.0	9.000	L1	20.5
12.718000	---	6.73	50.00	43.27	1000.0	9.000	L1	20.5

Neutral Line



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.750000	---	28.53	46.00	17.47	1000.0	9.000	N	19.7
0.750000	37.40	---	56.00	18.60	1000.0	9.000	N	19.7
0.814000	---	29.83	46.00	16.17	1000.0	9.000	N	19.7
0.814000	37.87	---	56.00	18.13	1000.0	9.000	N	19.7
0.898000	---	21.36	46.00	24.64	1000.0	9.000	N	19.8
0.898000	28.80	---	56.00	27.20	1000.0	9.000	N	19.8
3.734000	---	24.02	46.00	21.98	1000.0	9.000	N	19.9
3.734000	28.53	---	56.00	27.47	1000.0	9.000	N	19.9
5.154000	---	13.75	50.00	36.25	1000.0	9.000	N	20.0
5.154000	17.38	---	60.00	42.62	1000.0	9.000	N	20.0
16.438000	---	5.28	50.00	44.72	1000.0	9.000	N	20.7
16.438000	8.60	---	60.00	51.40	1000.0	9.000	N	20.7

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Test results

Mode: LE 1 Mbps / Cradle

Channel: 19 (Worst case)

Hot Line



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.366000	36.27	---	58.59	22.32	1000.0	9.000	L1	19.7
0.366000	---	26.05	48.59	22.54	1000.0	9.000	L1	19.7
0.814000	---	29.65	46.00	16.35	1000.0	9.000	L1	19.7
0.814000	36.95	---	56.00	19.05	1000.0	9.000	L1	19.7
0.882000	---	24.19	46.00	21.81	1000.0	9.000	L1	19.7
0.882000	31.49	---	56.00	24.51	1000.0	9.000	L1	19.7
3.746000	---	25.97	46.00	20.03	1000.0	9.000	L1	19.9
3.746000	30.29	---	56.00	25.71	1000.0	9.000	L1	19.9
5.134000	---	20.88	50.00	29.12	1000.0	9.000	L1	20.0
5.134000	25.35	---	60.00	34.65	1000.0	9.000	L1	20.0
9.182000	---	13.53	50.00	36.47	1000.0	9.000	L1	20.3
9.182000	18.41	---	60.00	41.59	1000.0	9.000	L1	20.3

Neutral Line



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.362000	36.57	---	58.68	22.11	1000.0	9.000	N	19.7
0.362000	---	26.29	48.68	22.39	1000.0	9.000	N	19.7
0.774000	---	28.67	46.00	17.33	1000.0	9.000	N	19.7
0.774000	37.03	---	56.00	18.97	1000.0	9.000	N	19.7
0.834000	---	29.15	46.00	16.85	1000.0	9.000	N	19.7
0.834000	36.37	---	56.00	19.63	1000.0	9.000	N	19.7
0.882000	31.48	---	56.00	24.52	1000.0	9.000	N	19.8
0.882000	---	23.99	46.00	22.01	1000.0	9.000	N	19.8
3.746000	29.87	---	56.00	26.13	1000.0	9.000	N	19.9
3.746000	---	25.56	46.00	20.44	1000.0	9.000	N	19.9
5.134000	25.35	---	60.00	34.65	1000.0	9.000	N	20.0
5.134000	---	20.93	50.00	29.07	1000.0	9.000	N	20.0

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

3.7. Antenna Requirement

According to 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or toother intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Appendix A. Measurement equipment

Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
SPECTRUM ANALYZER	R&S	FSV40-N	102194	1 year	2027.08.04
SPECTRUM ANALYZER	R&S	FSV40	101002	1 year	2027.01.06
SIGNAL GENERATOR	KEYSIGHT	N5182B	MY59100115	1 year	2027.04.02
SIGNAL GENERATOR	Anritsu	68369B	002118	1 year	2027.04.02
Power Meter	Anritsu	ML2495A	2010001	1 year	2027.04.02
Pulse Power Sensor	Anritsu	MA2411B	1911111	1 year	2027.04.02
Attenuator	Mini-Circuits	BW-S10-2W263+	2	1 year	2027.01.12
LOOP ANTENNA	TESEQ	HLA6121	66547	2 years	2028.01.13
TRILOG-BROADBAND ANTENNA	Schwarzbeck	VULB 9163	714	2 years	2028.04.16
Horn Antenna	A.H.	SAS-571	414	1 year	2027.01.12
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA 9170550	1 year	2027.01.12
Amplifier	SONOMA INSTRUMENT	310N	401123	1 year	2027.02.12
PREAMPLIFIER	HP	8449B	3008A01742	1 year	2026.10.22
BROADBAND AMPLIFIER	SCHWARZBECK	BBV9721	PS9721-003	1 year	2027.01.12
DC POWER SUPPLY	AGILENT	6632B	MY43004090	1 year	2027.06.08
Cable	-	-	#5	1 year	2026.10.31
Cable (SAC #5)	SUCOFLEX106	HUBER_SUHNER	-	0.5 year	2027.02.05
	SUCOFLEX106	HUBER_SUHNER	-	0.5 year	2027.02.05
	LH21D/2xSMA	OSI Cable	-	0.5 year	2027.02.05
Cable (SAC #6)	TCLH21D-SMSM-2.5M 0222	OSI Cable	-	0.5 year	2027.02.05
	TCLH21D-NMNM-10.0M 0222	OSI Cable	-	0.5 year	2027.02.05
	TCLH21D-SMSM-7.0M 0222	OSI Cable	-	0.5 year	2027.02.05

* Statement of Traceability: KES Co., Ltd. attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Peripheral devices

Device	Manufacturer	Model No.	Serial No.
Notebook computer	Lenovo PC HK Limited	80XL	PF12GP

The End.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).