RF Test Data for 2.4G WiFi (Conducted Measurements)

General Description of EUT	
Product Name:	**Tablet PC**
Test Model:	**IRA T1030**
Sample ID:	**HC-C-202406-0309-01-02**
Environmental Conditions	
Temperature:	**22.0℃-25℃**
Relative Humidity:	**43%-55%**
Test Voltage:	**DC 3.8V**
Test Engineer:	**Mike Yan**
Note: For a more detailed features description, please refer to the report TBR-C-202406-0309-22 The report only show the worst case data.	

Contents

1.Duty Cycle....3
2.Maximum Conducted Output Power....10
3.-6dB Bandwidth....11
4.Occupied Channel Bandwidth....18
5.Maximum Power Spectral Density Level....25
6.Band Edge....32
7.Conducted RF Spurious Emission....41
8.Restrict Band....54

1.Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	Ant1	99.57	0.02	0.06
NVNT	b	2437	Ant1	99.69	0.01	0.06
NVNT	b	2462	Ant1	99.63	0.02	0.06
NVNT	g	2412	Ant1	97.83	0.1	0.37
NVNT	g	2437	Ant1	97.82	0.1	0.37
NVNT	g	2462	Ant1	97.83	0.1	0.37
NVNT	n(HT20)	2412	Ant1	97.41	0.11	0.44
NVNT	n(HT20)	2437	Ant1	97.41	0.11	0.44
NVNT	n(HT20)	2462	Ant1	97	0.13	0.44
NVNT	n(HT40)	2422	Ant1	94.87	0.23	0.9
NVNT	n(HT40)	2437	Ant1	94.87	0.23	0.9
NVNT	n(HT40)	2452	Ant1	94.87	0.23	0.9

Test Graphs

Duty Cycle NVNT b 2412MHz Ant1



Duty Cycle NVNT b 2437MHz Ant1



Duty Cycle NVNT b 2462MHz Ant1



Duty Cycle NVNT g 2412MHz Ant1



Duty Cycle NVNT g 2437MHz Ant1



Duty Cycle NVNT g 2462MHz Ant1



Duty Cycle NVNT n(HT20) 2412MHz Ant1



Duty Cycle NVNT n(HT20) 2437MHz Ant1



Duty Cycle NVNT n(HT20) 2462MHz Ant1



Duty Cycle NVNT n(HT40) 2422MHz Ant1



Duty Cycle NVNT n(HT40) 2437MHz Ant1



Duty Cycle NVNT n(HT40) 2452MHz Ant1



2.Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	Ant1	16.03	30	Pass
NVNT	b	2437	Ant1	16.76	30	Pass
NVNT	b	2462	Ant1	16.14	30	Pass
NVNT	g	2412	Ant1	15.78	30	Pass
NVNT	g	2437	Ant1	16.51	30	Pass
NVNT	g	2462	Ant1	14.73	30	Pass
NVNT	n(HT20)	2412	Ant1	14.48	30	Pass
NVNT	n(HT20)	2437	Ant1	15.68	30	Pass
NVNT	n(HT20)	2462	Ant1	13.29	30	Pass
NVNT	n(HT40)	2422	Ant1	13.2	30	Pass
NVNT	n(HT40)	2437	Ant1	15.03	30	Pass
NVNT	n(HT40)	2452	Ant1	12.52	30	Pass

Note: The duty factor has been compensated into the result.

3.-6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant1	8.1	0.5	Pass
NVNT	b	2437	Ant1	8.1	0.5	Pass
NVNT	b	2462	Ant1	9.01	0.5	Pass
NVNT	g	2412	Ant1	16.08	0.5	Pass
NVNT	g	2437	Ant1	16.33	0.5	Pass
NVNT	g	2462	Ant1	16.31	0.5	Pass
NVNT	n(HT20)	2412	Ant1	16.74	0.5	Pass
NVNT	n(HT20)	2437	Ant1	17.11	0.5	Pass
NVNT	n(HT20)	2462	Ant1	17.16	0.5	Pass
NVNT	n(HT40)	2422	Ant1	35.08	0.5	Pass
NVNT	n(HT40)	2437	Ant1	35.77	0.5	Pass
NVNT	n(HT40)	2452	Ant1	35.74	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT b 2412MHz Ant1



-6dB Bandwidth NVNT b 2437MHz Ant1



-6dB Bandwidth NVNT b 2462MHz Ant1



-6dB Bandwidth NVNT g 2412MHz Ant1



-6dB Bandwidth NVNT g 2437MHz Ant1



-6dB Bandwidth NVNT g 2462MHz Ant1



-6dB Bandwidth NVNT n(HT20) 2412MHz Ant1



-6dB Bandwidth NVNT n(HT20) 2437MHz Ant1



-6dB Bandwidth NVNT n(HT20) 2462MHz Ant1



-6dB Bandwidth NVNT n(HT40) 2422MHz Ant1



-6dB Bandwidth NVNT n(HT40) 2437MHz Ant1



-6dB Bandwidth NVNT n(HT40) 2452MHz Ant1



4.Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	b	2412	Ant1	11.764
NVNT	b	2437	Ant1	11.926
NVNT	b	2462	Ant1	11.956
NVNT	g	2412	Ant1	16.498
NVNT	g	2437	Ant1	16.59
NVNT	g	2462	Ant1	16.5
NVNT	n(HT20)	2412	Ant1	17.551
NVNT	n(HT20)	2437	Ant1	17.604
NVNT	n(HT20)	2462	Ant1	17.515
NVNT	n(HT40)	2422	Ant1	36.025
NVNT	n(HT40)	2437	Ant1	36.096
NVNT	n(HT40)	2452	Ant1	36.133

Test Graphs

OBW NVNT b 2412MHz Ant1



OBW NVNT b 2437MHz Ant1



OBW NVNT b 2462MHz Ant1



OBW NVNT g 2412MHz Ant1



OBW NVNT g 2437MHz Ant1



OBW NVNT g 2462MHz Ant1



OBW NVNT n(HT20) 2412MHz Ant1



OBW NVNT n(HT20) 2437MHz Ant1



OBW NVNT n(HT20) 2462MHz Ant1



OBW NVNT n(HT40) 2422MHz Ant1



OBW NVNT n(HT40) 2437MHz Ant1



OBW NVNT n(HT40) 2452MHz Ant1



5.Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	Ant1	-16.842	8	Pass
NVNT	b	2437	Ant1	-15.619	8	Pass
NVNT	b	2462	Ant1	-16.618	8	Pass
NVNT	g	2412	Ant1	-19.155	8	Pass
NVNT	g	2437	Ant1	-18.779	8	Pass
NVNT	g	2462	Ant1	-19.983	8	Pass
NVNT	n(HT20)	2412	Ant1	-21.393	8	Pass
NVNT	n(HT20)	2437	Ant1	-20.046	8	Pass
NVNT	n(HT20)	2462	Ant1	-22.636	8	Pass
NVNT	n(HT40)	2422	Ant1	-25.73	8	Pass
NVNT	n(HT40)	2437	Ant1	-23.906	8	Pass
NVNT	n(HT40)	2452	Ant1	-28.21	8	Pass

Note: The duty factor has been compensated into the result.

Test Graphs

PSD NVNT b 2412MHz Ant1



PSD NVNT b 2437MHz Ant1



PSD NVNT b 2462MHz Ant1



PSD NVNT g 2412MHz Ant1



PSD NVNT g 2437MHz Ant1



PSD NVNT g 2462MHz Ant1



PSD NVNT n(HT20) 2412MHz Ant1



PSD NVNT n(HT20) 2437MHz Ant1



PSD NVNT n(HT20) 2462MHz Ant1



PSD NVNT n(HT40) 2422MHz Ant1



PSD NVNT n(HT40) 2437MHz Ant1



PSD NVNT n(HT40) 2452MHz Ant1



6.Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-52.19	-30	Pass
NVNT	b	2462	Ant1	-51.54	-30	Pass
NVNT	g	2412	Ant1	-46.31	-30	Pass
NVNT	g	2462	Ant1	-45.89	-30	Pass
NVNT	n(HT20)	2412	Ant1	-43.89	-30	Pass
NVNT	n(HT20)	2462	Ant1	-43.43	-30	Pass
NVNT	n(HT40)	2422	Ant1	-38.89	-30	Pass
NVNT	n(HT40)	2452	Ant1	-37.76	-30	Pass

Test Graphs

Band Edge NVNT b 2412MHz Ant1 Ref



Band Edge NVNT b 2412MHz Ant1 Emission



Band Edge NVNT b 2462MHz Ant1 Ref



Band Edge NVNT b 2462MHz Ant1 Emission



Band Edge NVNT g 2412MHz Ant1 Ref



Band Edge NVNT g 2412MHz Ant1 Emission



Band Edge NVNT g 2462MHz Ant1 Ref



Band Edge NVNT g 2462MHz Ant1 Emission



Band Edge NVNT n(HT20) 2412MHz Ant1 Ref



Band Edge NVNT n(HT20) 2412MHz Ant1 Emission



Band Edge NVNT n(HT20) 2462MHz Ant1 Ref



Band Edge NVNT n(HT20) 2462MHz Ant1 Emission



Band Edge NVNT n(HT40) 2422MHz Ant1 Ref



Band Edge NVNT n(HT40) 2422MHz Ant1 Emission



Band Edge NVNT n(HT40) 2452MHz Ant1 Ref



Band Edge NVNT n(HT40) 2452MHz Ant1 Emission



7.Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-54.64	-30	Pass
NVNT	b	2437	Ant1	-54.91	-30	Pass
NVNT	b	2462	Ant1	-53.5	-30	Pass
NVNT	g	2412	Ant1	-52.34	-30	Pass
NVNT	g	2437	Ant1	-50.79	-30	Pass
NVNT	g	2462	Ant1	-50.65	-30	Pass
NVNT	n(HT20)	2412	Ant1	-50.26	-30	Pass
NVNT	n(HT20)	2437	Ant1	-51.88	-30	Pass
NVNT	n(HT20)	2462	Ant1	-47.74	-30	Pass
NVNT	n(HT40)	2422	Ant1	-46.19	-30	Pass
NVNT	n(HT40)	2437	Ant1	-46.9	-30	Pass
NVNT	n(HT40)	2452	Ant1	-43.82	-30	Pass

Test Graphs

Tx. Spurious NVNT b 2412MHz Ant1 Ref



Tx. Spurious NVNT b 2412MHz Ant1 Emission



Tx. Spurious NVNT b 2437MHz Ant1 Ref



Tx. Spurious NVNT b 2437MHz Ant1 Emission



Tx. Spurious NVNT b 2462MHz Ant1 Ref



Tx. Spurious NVNT b 2462MHz Ant1 Emission



Tx. Spurious NVNT g 2412MHz Ant1 Ref



Tx. Spurious NVNT g 2412MHz Ant1 Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.412 GHz	1.897 dBm			
2	N	1	f	25.124 GHz	-48.113 dBm			
3	N	1	f	5.006 GHz	-58.365 dBm			
4	N	1	f	7.045 GHz	-57.090 dBm			
5	N	1	f	9.665 GHz	-59.981 dBm			
6								
7								
8								
9								
10								
11								

Tx. Spurious NVNT g 2437MHz Ant1 Ref



Tx. Spurious NVNT g 2437MHz Ant1 Emission



Tx. Spurious NVNT g 2462MHz Ant1 Ref



Tx. Spurious NVNT g 2462MHz Ant1 Emission



Tx. Spurious NVNT n(HT20) 2412MHz Ant1 Ref



Tx. Spurious NVNT n(HT20) 2412MHz Ant1 Emission



Tx. Spurious NVNT n(HT20) 2437MHz Ant1 Ref



Tx. Spurious NVNT n(HT20) 2437MHz Ant1 Emission



Tx. Spurious NVNT n(HT20) 2462MHz Ant1 Ref



Tx. Spurious NVNT n(HT20) 2462MHz Ant1 Emission



Tx. Spurious NVNT n(HT40) 2422MHz Ant1 Ref



Tx. Spurious NVNT n(HT40) 2422MHz Ant1 Emission



Tx. Spurious NVNT n(HT40) 2437MHz Ant1 Ref



Tx. Spurious NVNT n(HT40) 2437MHz Ant1 Emission



Tx. Spurious NVNT n(HT40) 2452MHz Ant1 Ref



Tx. Spurious NVNT n(HT40) 2452MHz Ant1 Emission



MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.439 GHz	-4.210 dBm			
2	N	1	f	25.309 GHz	-47.553 dBm			
3	N	1	f	4.980 GHz	-58.201 dBm			
4	N	1	f	7.177 GHz	-57.056 dBm			
5	N	1	f	9.983 GHz	-59.577 dBm			
6								
7								
8								
9								
10								
11								

8.Restrict Band

Condition	Mode	Frequency (MHz)	Antenna	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	Duty Factor (dB)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
NVNT	b	2412	Ant1	2310	-53.24	2	-	44.02	Peak	74	Pass
NVNT	b	2412	Ant1	2310	-61.12	2	0.02	36.16	Average	54	Pass
NVNT	b	2412	Ant1	2388.156	-45.31	2	-	51.95	Peak	74	Pass
NVNT	b	2412	Ant1	2388.858	-52.69	2	0.02	44.59	Average	54	Pass
NVNT	b	2412	Ant1	2390	-47.13	2	-	50.13	Peak	74	Pass
NVNT	b	2412	Ant1	2390	-53.94	2	0.02	43.34	Average	54	Pass
NVNT	b	2462	Ant1	2483.5	-48.18	2	-	49.08	Peak	74	Pass
NVNT	b	2462	Ant1	2483.5	-56.59	2	0.02	40.69	Average	54	Pass
NVNT	b	2462	Ant1	2485.796	-46.37	2	-	50.89	Peak	74	Pass
NVNT	b	2462	Ant1	2485.107	-55.32	2	0.02	41.96	Average	54	Pass
NVNT	b	2462	Ant1	2500	-51.17	2	-	46.09	Peak	74	Pass
NVNT	b	2462	Ant1	2500	-59.78	2	0.02	37.5	Average	54	Pass
NVNT	g	2412	Ant1	2310	-52.25	2	-	45.01	Peak	74	Pass
NVNT	g	2412	Ant1	2310	-61.17	2	0.1	36.19	Average	54	Pass
NVNT	g	2412	Ant1	2389.443	-28.7	2	-	68.56	Peak	74	Pass
NVNT	g	2412	Ant1	2389.794	-44.34	2	0.1	53.02	Average	54	Pass
NVNT	g	2412	Ant1	2390	-32.36	2	-	64.9	Peak	74	Pass
NVNT	g	2412	Ant1	2390	-44.73	2	0.1	52.63	Average	54	Pass
NVNT	g	2462	Ant1	2483.5	-30.26	2	-	67	Peak	74	Pass
NVNT	g	2462	Ant1	2483.5	-45.18	2	0.1	52.18	Average	54	Pass
NVNT	g	2462	Ant1	2484.153	-29.36	2	-	67.9	Peak	74	Pass
NVNT	g	2462	Ant1	2483.623	-44.94	2	0.1	52.42	Average	54	Pass
NVNT	g	2462	Ant1	2500	-52.34	2	-	44.92	Peak	74	Pass
NVNT	g	2462	Ant1	2500	-60.2	2	0.1	37.16	Average	54	Pass
NVNT	n(HT20)	2412	Ant1	2310	-52.55	2	-	44.71	Peak	74	Pass
NVNT	n(HT20)	2412	Ant1	2310	-60.84	2	0.11	36.53	Average	54	Pass
NVNT	n(HT20)	2412	Ant1	2388.624	-29.89	2	-	67.37	Peak	74	Pass
NVNT	n(HT20)	2412	Ant1	2389.677	-43.68	2	0.11	53.69	Average	54	Pass
NVNT	n(HT20)	2412	Ant1	2390	-32.45	2	-	64.81	Peak	74	Pass
NVNT	n(HT20)	2412	Ant1	2390	-43.89	2	0.11	53.48	Average	54	Pass
NVNT	n(HT20)	2462	Ant1	2483.5	-31.34	2	-	65.92	Peak	74	Pass
NVNT	n(HT20)	2462	Ant1	2483.5	-47.09	2	0.13	50.3	Average	54	Pass
NVNT	n(HT20)	2462	Ant1	2484.418	-28.23	2	-	69.03	Peak	74	Pass
NVNT	n(HT20)	2462	Ant1	2483.57	-45.76	2	0.13	51.63	Average	54	Pass
NVNT	n(HT20)	2462	Ant1	2500	-51.82	2	-	45.44	Peak	74	Pass
NVNT	n(HT20)	2462	Ant1	2500	-60.33	2	0.13	37.06	Average	54	Pass
NVNT	n(HT40)	2422	Ant1	2310	-54.73	2	-	42.53	Peak	74	Pass
NVNT	n(HT40)	2422	Ant1	2310	-60.96	2	0.23	36.53	Average	54	Pass
NVNT	n(HT40)	2422	Ant1	2389.946	-26.84	2	-	70.42	Peak	74	Pass
NVNT	n(HT40)	2422	Ant1	2389.378	-43.82	2	0.23	53.67	Average	54	Pass
NVNT	n(HT40)	2422	Ant1	2390	-26.85	2	-	70.41	Peak	74	Pass

NVNT	n(HT40)	2422	Ant1	2390	-44.66	2	0.23	52.83	Average	54	Pass
NVNT	n(HT40)	2452	Ant1	2483.5	-32.61	2	-	64.65	Peak	74	Pass
NVNT	n(HT40)	2452	Ant1	2483.5	-45.87	2	0.23	51.62	Average	54	Pass
NVNT	n(HT40)	2452	Ant1	2483.698	-28.94	2	-	68.32	Peak	74	Pass
NVNT	n(HT40)	2452	Ant1	2484.088	-45.95	2	0.23	51.54	Average	54	Pass
NVNT	n(HT40)	2452	Ant1	2500	-52.23	2	-	45.03	Peak	74	Pass
NVNT	n(HT40)	2452	Ant1	2500	-59.97	2	0.23	37.52	Average	54	Pass

Test Graphs

Restrict Band NVNT b 2412MHz Ant1 Peak



Restrict Band NVNT b 2412MHz Ant1 Average



Restrict Band NVNT b 2462MHz Ant1 Peak



Restrict Band NVNT b 2462MHz Ant1 Average



Restrict Band NVNT g 2412MHz Ant1 Peak



Restrict Band NVNT g 2412MHz Ant1 Average



Restrict Band NVNT g 2462MHz Ant1 Peak



Restrict Band NVNT g 2462MHz Ant1 Average



Restrict Band NVNT n(HT20) 2412MHz Ant1 Peak



Restrict Band NVNT n(HT20) 2412MHz Ant1 Average



Restrict Band NVNT n(HT20) 2462MHz Ant1 Peak



Restrict Band NVNT n(HT20) 2462MHz Ant1 Average



Restrict Band NVNT n(HT40) 2422MHz Ant1 Peak



Restrict Band NVNT n(HT40) 2422MHz Ant1 Average



Restrict Band NVNT n(HT40) 2452MHz Ant1 Peak



Restrict Band NVNT n(HT40) 2452MHz Ant1 Average



-----END OF REPORT-----