

TEST REPORT

Applicant: EZ LYNK, SEZC
EUT Description: EZDISPLAY
Model: EZLYNKDISPLAY_7R1
Brand: EZ LYNK
FCC ID: 2BHJB-EZLD7
Standards: FCC CFR Title 47 Part 2
FCC CFR Title 47 Part 22
FCC CFR Title 47 Part 24
FCC CFR Title 47 Part 27
FCC CFR Title 47 Part 90
Date of Receipt: 2025/10/31
Date of Test: 2025/10/31 to 2025/12/09
Date of Issue: 2025/12/11

TOWE. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

the results documented in this report apply only the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility assure that additional production units of the model are manufactured with identical electrical and mechanical components. All sample tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise. without written approval of TOWE, the test report shall not be reproduced except in full.



Jim Huang
Approved By:



Carey Chen
Reviewed By:

Revision History

Rev.	Issue Date	Description	Revised by
01	2025/12/11	Original	Carey Chen

Summary of Test Results

FCC Part	Test Band	Test Item	Test Result
§2.1046 §22.913(a)(5) §27.50(b)(10) §27.50(c)(10) §90.542(a)	LTE Band 5/26(824 ~ 849MHz) LTE Band 13 LTE Band 12/17/71 LTE Band 14	Effective Radiated Power	Pass*
§2.1046 §24.232(c) §27.50(d)(4) §27.50(h)(2)	LTE Band 2/25 LTE Band 4/66 LTE Band 7/41	Effective Isotropic Radiated Power	
§2.1046 §90.635(b)	LTE Band 26(814 ~ 824MHz)	Transmitter Conducted Output Power	
§22.913(d) §24.232(d) §27.50(d)(5)	LTE Band 5/26(824 ~ 849MHz) LTE Band 2/25 Others Band	Peak-Average Ratio	Reference report FG2D2302A & FG2D2302B & FG2D2302C & FG2D2302D
§2.1049	All Band	Occupied Bandwidth	
§2.1051 §90.210(b) §90.691(a)	LTE Band 14 LTE Band 26(814 ~ 824MHz)	Emission Mask	
§2.1051 §22.917(a) §24.238(a) §27.53(c) §27.53(g) §27.53(h) §27.53(m) §90.543(e)(2)(3) §27.53(g)	LTE Band 5/26(824 ~ 849MHz) LTE Band 2/25 LTE Band 13 LTE Band 12/17 LTE Band 4/66 LTE Band 7/41 LTE Band 14 LTE Band 71	Band Edge	
§2.1051 §22.917(a) §24.238(a) §27.53(c) §27.53(g) §27.53(h) §27.53(m) §90.691 §90.543(c)(f) §27.53(g)	LTE Band 5/26(824 ~ 849MHz) LTE Band 2/25 LTE Band 13 LTE Band 12/17 LTE Band 4/66 LTE Band 7/41 LTE Band 26(814 ~ 824MHz) LTE Band 14 LTE Band 71	Spurious Emission at Antenna Terminals	
§2.1055 §22.355 §24.235 §27.54 §90.213	LTE Band 5/26(824 ~ 849MHz) LTE Band 2/25 Others Band LTE Band 26(814 ~ 824MHz)/14	Frequency Stability	
§2.1053 §22.917(a)	LTE Band 5/26(824 ~ 849MHz)	Field Strength of Spurious Radiation	Pass

FCC Part	Test Band	Test Item	Test Result
§24.238(a)	LTE Band 2/25		
§27.53(c)&(f)	LTE Band 13		
§27.53(g)	LTE Band 12/17		
§27.53(h)	LTE Band 4/66		
§27.53(m)	LTE Band 7/41		
§90.691	LTE Band 26(814 ~ 824MHz)		
§90.543(c)(f)	LTE Band 14		
§27.53(g)	LTE Band 71		
Remark: 1. Pass: Meet the requirement. 2. Pass*: The items of power data refer to the previous report, updated the ERP/EIRP and only the maximum power of all frequency bands displayed in this report.			

Remark: In this report Field Strength of Spurious Radiation was tested, and the other data please refer to the previous report with report number FG2D2302A & FG2D2302B & FG2D2302C & FG2D2302D (FCC ID: XMR2022SC680ANA) issued by Sporton International Inc. (Kunshan).

Table of Contents

1	General Description	6
1.1	Lab Information	6
1.1.1	Testing Location	6
1.1.2	Test Facility / Accreditations	6
1.2	Client Information	6
1.2.1	Applicant	6
1.2.2	Manufacturer	6
1.3	Product Information	7
2	Test Configuration	9
2.1	Test Channel	9
2.2	Test Mode	13
2.3	Support Unit used in test	13
2.4	Test Environment	13
2.5	Test RF Cable	13
2.6	Modifications	13
2.7	Test Setup Diagram	14
2.7.1	Radiated Configuration	14
3	Equipment and Measurement Uncertainty	15
3.1	Test Equipment List	15
3.2	Measurement Uncertainty	15
4	Test Results	16
4.1	Field Strength of Spurious Radiation	16
5	Test Setup Photos	18
	Appendix	19

1 General Description

1.1 Lab Information

1.1.1 Testing Location

These measurements tests were conducted at the Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. facility located at F401 and F101, Building E, Hongwei Industrial Zone, Liuxian 3rd Road, Bao'an District, Shenzhen, China. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014

Tel.: +86-755-27212361

Contact Email: info@towewireless.com

1.1.2 Test Facility / Accreditations

A2LA (Certificate Number: 7088.01)

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

FCC Designation No.: CN1353

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized as an accredited testing laboratory. Designation Number: CN1353.

ISED CAB identifier: CN0152

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0152

Company Number: 31000

1.2 Client Information

1.2.1 Applicant

Applicant:	EZ LYNK, SEZC
Address:	PO Box CEC-74, George Town KY1-9012, Cayman Islands

1.2.2 Manufacturer

Manufacturer:	EZ LYNK, SEZC
Address:	PO Box CEC-74, George Town KY1-9012, Cayman Islands

1.3 Product Information

EUT Description:	EZDISPLAY		
Model:	EZLYNKDISPLAY_7R1		
Brand:	EZ LYNK		
Hardware Version:	1.7		
Software Version:	Android 14		
IMEI:	867065080019727		
Device Capabilities:			
Modulation Type:	LTE:	☒ QPSK, ☒ 16QAM, ☐ 64QAM, ☐ 256QAM	
Operation Frequency Range:	Band	TX Frequency	RX Frequency
	LTE Band 2	1850 ~ 1910 MHz	1930 ~ 1990 MHz
	LTE Band 4	1710 ~ 1755 MHz	2110 ~ 2155 MHz
	LTE Band 5	824 ~ 849 MHz	869 ~ 894 MHz
	LTE Band 7	2500 ~ 2570 MHz	2620 ~ 2690 MHz
	LTE Band 12	699 ~ 716 MHz	729 ~ 746 MHz
	LTE Band 13	777 ~ 787 MHz	746 ~ 756 MHz
	LTE Band 14	788 ~ 798 MHz	758 ~ 768 MHz
	LTE Band 17	704 ~ 716 MHz	734 ~ 746 MHz
	LTE Band 25	1850 ~ 1915MHz	1930 ~ 1995 MHz
	LTE Band 26 (814 ~ 824 MHz)	814 ~ 824MHz	859 ~ 869 MHz
	LTE Band 26 (824 ~ 849 MHz)	824 ~ 849 MHz	869 ~ 894 MHz
	LTE Band 41	2496 ~ 2690MHz	2496 ~ 2690MHz
	LTE Band 66	1710 ~ 1780 MHz	2110 ~ 2200 MHz
	LTE Band 71	663 ~ 698 MHz	617 ~ 652 MHz
Power Class:	Class 3: All		
Antenna Type:	☐ External, ☒ Integrated		
Antenna Gain:	Band	Ant (dBi)	
	LTE Band 2	2.51	
	LTE Band 4	0.71	
	LTE Band 5	-1.44	
	LTE Band 7	0.49	
	LTE Band 12	-1.67	
	LTE Band 13	-1.61	
	LTE Band 14	-1.61	
	LTE Band 17	-1.67	
	LTE Band 25	2.75	
	LTE Band 26	-1.44	
	LTE Band 41	1.56	
	LTE Band 66	0.71	
LTE Band 71	-1.52		

Remark: The above EUT's information was declared by applicant, please refer to the specifications or user manual for more detailed description.

2 Test Configuration

2.1 Test Channel

Band	Bandwidth	TX Frequency			RX Frequency		
		Range	Channel	Frequency	Range	Channel	Frequency
LTE Band 2	1.4MHz	Low	18607	1850.7 MHz	Low	607	1930.7 MHz
		Middle	18900	1880 MHz	Middle	900	1960 MHz
		High	19193	1909.3 MHz	High	1193	1989.3 MHz
	3MHz	Low	18615	1851.5 MHz	Low	615	1931.5 MHz
		Middle	18900	1880 MHz	Middle	900	1960 MHz
		High	19185	1908.5 MHz	High	1185	1988.5 MHz
	5MHz	Low	18625	1852.5 MHz	Low	625	1932.5 MHz
		Middle	18900	1880 MHz	Middle	900	1960 MHz
		High	19175	1907.5 MHz	High	1175	1987.5 MHz
	10MHz	Low	18650	1855 MHz	Low	650	1935 MHz
		Middle	18900	1880 MHz	Middle	900	1960 MHz
		High	19150	1905 MHz	High	1150	1985 MHz
	15MHz	Low	18675	1857.5 MHz	Low	675	1937.5 MHz
		Middle	18900	1880 MHz	Middle	900	1960 MHz
		High	19125	1902.5 MHz	High	1125	1982.5 MHz
LTE Band 4	1.4MHz	Low	18700	1860 MHz	Low	700	1940 MHz
		Middle	18900	1880 MHz	Middle	900	1960 MHz
		High	19100	1900 MHz	High	1100	1980 MHz
	3MHz	Low	19957	1710.7 MHz	Low	1957	2110.7 MHz
		Middle	20175	1732.5 MHz	Middle	2175	2132.5MHz
		High	20393	1754.3 MHz	High	2393	2154.3 MHz
	5MHz	Low	19965	1711.5 MHz	Low	1965	2111.5 MHz
		Middle	20175	1732.5 MHz	Middle	2175	2132.5MHz
		High	20385	1753.5 MHz	High	2385	2153.5 MHz
	10MHz	Low	19975	1712.5 MHz	Low	1975	2112.5 MHz
		Middle	20175	1732.5 MHz	Middle	2175	2132.5MHz
		High	20375	1752.5 MHz	High	2375	2152.5 MHz
	15MHz	Low	20000	1715 MHz	Low	2115	2115 MHz
		Middle	20175	1732.5 MHz	Middle	2175	2132.5MHz
		High	20350	1750 MHz	High	2350	2150 MHz
LTE Band 5	1.4MHz	Low	20025	1717.5 MHz	Low	2025	2117.5 MHz
		Middle	20175	1732.5 MHz	Middle	2175	2132.5MHz
		High	20325	1747.5 MHz	High	2325	2147.5 MHz
	3MHz	Low	20050	1720 MHz	Low	2050	2120 MHz
		Middle	20175	1732.5 MHz	Middle	2175	2132.5MHz
		High	20300	1745 MHz	High	2300	2145 MHz
	5MHz	Low	20407	824.7 MHz	Low	2407	869.7 MHz
		Middle	20525	836.5 MHz	Middle	2525	881.5 MHz
		High	20643	848.3 MHz	High	2643	893.3 MHz
	10MHz	Low	20415	825.5 MHz	Low	2415	870.5 MHz
		Middle	20525	836.5 MHz	Middle	2525	881.5 MHz
		High	20635	847.5 MHz	High	2635	892.5 MHz
	15MHz	Low	20425	826.5 MHz	Low	2425	871.5 MHz
		Middle	20525	836.5 MHz	Middle	2525	881.5 MHz
		High	20625	846.5 MHz	High	2625	891.5 MHz
LTE Band 7	5MHz	Low	20450	829 MHz	Low	2450	874 MHz
		Middle	20525	836.5 MHz	Middle	2525	881.5 MHz
		High	20600	844 MHz	High	2600	889 MHz
	10MHz	Low	20775	2502.5 MHz	Low	2775	2622.5 MHz
		Middle	21100	2535 MHz	Middle	3100	2655 MHz
LTE Band 7	5MHz	Middle	21100	2535 MHz	Middle	3100	2655 MHz
		High	21425	2567.5 MHz	High	3425	2687.5 MHz
	10MHz	Low	20800	2505 MHz	Low	2800	2625 MHz
		Middle	21100	2535 MHz	Middle	3100	2655 MHz

Band	Bandwidth	TX Frequency			RX Frequency		
		Range	Channel	Frequency	Range	Channel	Frequency
	15MHz	High	21400	2565 MHz	High	3400	2685 MHz
		Low	20825	2507.5 MHz	Low	2825	2627.5 MHz
		Middle	21100	2535 MHz	Middle	3100	2655 MHz
	20MHz	High	21375	2562.5 MHz	High	3375	2682.5 MHz
		Low	20850	2510 MHz	Low	2850	2630 MHz
		Middle	21100	2535 MHz	Middle	3100	2655 MHz
LTE Band 12	1.4MHz	High	21350	2560 MHz	High	3350	2680 MHz
		Low	23017	699.7 MHz	Low	5017	729.7 MHz
		Middle	23095	707.5 MHz	Middle	5095	737.5 MHz
	3MHz	High	23173	715.3 MHz	High	5173	745.3 MHz
		Low	23025	700.5 MHz	Low	5025	730.5 MHz
		Middle	23095	707.5 MHz	Middle	5095	737.5 MHz
	5MHz	High	23165	714.5 MHz	High	5165	744.5 MHz
		Low	23035	701.5 MHz	Low	5035	731.5 MHz
		Middle	23095	707.5 MHz	Middle	5095	737.5 MHz
	10MHz	High	23155	713.5 MHz	High	5155	743.5 MHz
		Low	23060	704 MHz	Low	5060	734 MHz
		Middle	23095	707.5 MHz	Middle	5095	737.5 MHz
LTE Band 13	5MHz	High	23130	711 MHz	High	5130	741 MHz
		Low	23205	779.5 MHz	Low	5205	748.5 MHz
		Middle	23230	782 MHz	Middle	5230	751 MHz
	10MHz	High	23255	784.5 MHz	High	5255	753.5 MHz
		Low	23230	782 MHz	Low	5230	751 MHz
		Middle	23230	782 MHz	Middle	5230	751 MHz
LTE Band 14	5MHz	High	23230	782 MHz	High	5230	751 MHz
		Low	23305	790.5 MHz	Low	5305	760.5 MHz
		Middle	23330	793 MHz	Middle	5330	763 MHz
	10MHz	High	23355	795.5 MHz	High	5355	765.5 MHz
		Low	23330	793 MHz	Low	5330	763 MHz
		Middle	23330	793 MHz	Middle	5330	763 MHz
LTE Band 17	5MHz	High	23330	793 MHz	High	5330	763 MHz
		Low	23755	706.5 MHz	Low	5755	736.5 MHz
		Middle	23790	710 MHz	Middle	5790	740 MHz
	10MHz	High	23825	713.5 MHz	High	5825	743.5 MHz
		Low	23780	709 MHz	Low	5780	739 MHz
		Middle	23790	710 MHz	Middle	5790	740 MHz
LTE Band 25	1.4MHz	High	23800	711 MHz	High	5800	741 MHz
		Low	26047	1850.7 MHz	Low	8047	1930.7 MHz
		Middle	26365	1882.5 MHz	Middle	8365	1962.5 MHz
	3MHz	High	26683	1914.3 MHz	High	8683	1994.3 MHz
		Low	26055	1851.5 MHz	Low	8055	1931.5 MHz
		Middle	26365	1882.5 MHz	Middle	8365	1962.5 MHz
	5MHz	High	26675	1913.5 MHz	High	8675	1993.5 MHz
		Low	26065	1852.5 MHz	Low	8065	1932.5 MHz
		Middle	26365	1882.5 MHz	Middle	8365	1962.5 MHz
	10MHz	High	26665	1912.5 MHz	High	8665	1992.5 MHz
		Low	26090	1855 MHz	Low	8090	1935 MHz
		Middle	26365	1882.5 MHz	Middle	8365	1962.5 MHz
	15MHz	High	26640	1910 MHz	High	8640	1990 MHz
		Low	26115	1857.5 MHz	Low	8115	1937.5 MHz
		Middle	26365	1882.5 MHz	Middle	8365	1962.5 MHz
	20MHz	High	26615	1907.5 MHz	High	8615	1987.5 MHz
		Low	26140	1860 MHz	Low	8140	1940 MHz
		Middle	26365	1882.5 MHz	Middle	8365	1962.5 MHz
LTE Band 26	1.4MHz	High	26590	1905 MHz	High	8590	1985 MHz
		Low	26697	814.7 MHz	Low	8697	859.7 MHz

Band	Bandwidth	TX Frequency			RX Frequency		
		Range	Channel	Frequency	Range	Channel	Frequency
(814-824)	3MHz	Middle	26740	819 MHz	Middle	8740	864MHz
		High	26783	823.3 MHz	High	8783	868.3 MHz
		Low	26705	815.5 MHz	Low	8705	860.5 MHz
	5MHz	Middle	26740	819 MHz	Middle	8740	864MHz
		High	26775	822.5 MHz	High	8775	867.5 MHz
		Low	26715	816.5 MHz	Low	8715	861.5 MHz
	10MHz	Middle	26740	819 MHz	Middle	8740	864MHz
		High	26765	821.5 MHz	High	8765	866.5 MHz
		Low	26740	819 MHz	Low	8740	864MHz
	10MHz	Middle	26740	819 MHz	Middle	8740	864MHz
		High	26740	819 MHz	High	8740	864MHz
		Low	26740	819 MHz	Low	8740	864MHz
LTE Band 26 (824-849)	1.4MHz	Low	26797	824.7 MHz	Low	8797	869.7 MHz
		Middle	26915	836.5 MHz	Middle	8915	881.5 MHz
		High	27033	848.3 MHz	High	9033	893.3 MHz
	3MHz	Low	26805	825.5 MHz	Low	8805	870.5 MHz
		Middle	26915	836.5 MHz	Middle	8915	881.5 MHz
		High	27025	847.5 MHz	High	9025	892.5 MHz
	5MHz	Low	26815	826.5 MHz	Low	8815	871.5 MHz
		Middle	26915	836.5 MHz	Middle	8915	881.5 MHz
		High	27015	846.5 MHz	High	9015	891.5 MHz
	10MHz	Low	26840	829 MHz	Low	8840	844 MHz
		Middle	26915	836.5 MHz	Middle	8915	881.5 MHz
		High	26990	844 MHz	High	8990	889 MHz
	15MHz	Low	26865	831.5 MHz	Low	8865	876.5 MHz
		Middle	26915	836.5 MHz	Middle	8915	881.5 MHz
		High	26965	841.5 MHz	High	8965	886.5 MHz
LTE Band 41 (2496-2690)	5MHz	Low	39675	2498.5 MHz	Low	39675	2498.5 MHz
		Middle	40620	2593 MHz	Middle	40620	2593 MHz
		High	41565	2687.5 MHz	High	41565	2687.5 MHz
	10MHz	Low	39700	2501 MHz	Low	39700	2501 MHz
		Middle	40620	2593 MHz	Middle	40620	2593 MHz
		High	41540	2685 MHz	High	41540	2685 MHz
	15MHz	Low	39725	2503.5 MHz	Low	39725	2503.5 MHz
		Middle	40620	2593 MHz	Middle	40620	2593 MHz
		High	41515	2682.5 MHz	High	41515	2682.5 MHz
	20MHz	Low	39750	2506 MHz	Low	39750	2506 MHz
		Middle	40620	2593 MHz	Middle	40620	2593 MHz
		High	41490	2680 MHz	High	41490	2680 MHz
LTE Band 66	1.4MHz	Low	131979	1710.7 MHz	Low	66443	2110.7 MHz
		Middle	132322	1745 MHz	Middle	66786	2145MHz
		High	132665	1779.3 MHz	High	67329	2199.3 MHz
	3MHz	Low	131987	1711.5 MHz	Low	66451	2111.5 MHz
		Middle	132322	1745 MHz	Middle	66786	2145MHz
		High	132657	1778.5MHz	High	67321	2198.5MHz
	5MHz	Low	131997	1712.5 MHz	Low	66461	2112.5 MHz
		Middle	132322	1745 MHz	Middle	66786	2145MHz
		High	132647	1777.5 MHz	High	67311	2197.5 MHz
	10MHz	Low	132022	1715 MHz	Low	66486	2115 MHz
		Middle	132322	1745 MHz	Middle	66786	2145MHz
		High	132622	1775 MHz	High	67286	2195 MHz
	15MHz	Low	132047	1717.5 MHz	Low	66511	2117.5 MHz
		Middle	132322	1745 MHz	Middle	66786	2145MHz
		High	132597	1772.5 MHz	High	67261	2192.5 MHz
	20MHz	Low	132072	1720 MHz	Low	66536	2120 MHz
		Middle	132322	1745 MHz	Middle	66786	2145MHz
		High	132572	1770 MHz	High	67236	2190 MHz

Band	Bandwidth	TX Frequency			RX Frequency		
		Range	Channel	Frequency	Range	Channel	Frequency
LTE Band 71	5MHz	Low	133147	665.5 MHz	Low	68611	619.5 MHz
		Middle	133297	680.5 MHz	Middle	68761	634.5 MHz
		High	133447	695.5 MHz	High	68911	649.5 MHz
	10MHz	Low	133172	668 MHz	Low	68636	622 MHz
		Middle	133297	680.5 MHz	Middle	68761	634.5 MHz
		High	133422	693 MHz	High	68886	647 MHz
	15MHz	Low	133197	670.5 MHz	Low	68661	624.5 MHz
		Middle	133297	680.5 MHz	Middle	68761	634.5 MHz
		High	133397	690.5 MHz	High	68861	644.5 MHz
	20MHz	Low	133222	673 MHz	Low	68686	627 MHz
		Middle	133297	680.5 MHz	Middle	68761	634.5 MHz
		High	133372	688 MHz	High	68836	642 MHz

2.2 Test Mode

Test Mode	Description
TM 1	EUT communication with simulated station in LTE/QPSK mode
TM 2	EUT communication with simulated station in LTE/16QAM mode

2.3 Support Unit used in test

The EUT has been tested as an independent unit.

2.4 Test Environment

Temperature:	Normal: 15°C ~ 35°C
Relative Humidity	45 ~ 56 % RH Ambient
Voltage:	Nominal: 5Vdc

2.5 Test RF Cable

For all conducted test items: The offset level is set spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.


Offset = RF cable loss + attenuator factor.

2.6 Modifications

No modifications were made during testing.

2.7 Test Setup Diagram

2.7.1 Radiated Configuration



3 Equipment and Measurement Uncertainty

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, whichever is less, and where applicable is traceable recognized national standards.

3.1 Test Equipment List

Radiated Emission					
Description	Manufacturer	Model	S.N.	Last Due	Cal Due
Biconic Logarithmic Periodic Antennas	Schwarzbeck	VULB9163	1643	2023/06/25	2026/06/24
Double-Ridged Horn Antennas	Schwarzbeck	BBHA 9120D	2809	2023/06/25	2026/06/24
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	1290	2023/06/25	2026/06/24
Loop Antenna	Schwarzbeck	FMZB 1519C	1519C-028	2023/06/29	2026/06/28
Signal Analyzer	Keysight	N9020A	MY49100252	2025/03/11	2026/03/10
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY63440541	2025/05/29	2026/05/28
Wideband Radio Communication Tester	R&S	CMW500	150645	2025/03/11	2026/03/10
Low Noise Amplifier	Tonscend	TAP9K3G40	AP23A8060273	2025/03/11	2027/03/10
Low Noise Amplifier	Tonscend	TAP01018050	AP22G806258	2025/03/11	2027/03/10
Low Noise Amplifier	Tonscend	TAP18040048	AP22G806247	2025/03/11	2027/03/10
Hygrometer	BINGYU	HTC-1	N/A	2025/07/25	2026/07/24
Test Software	Tonscend	TS+	Version: 5.0.0	N/A	N/A

3.2 Measurement Uncertainty

Parameter	U _{lab}
Radiated Emissions(9kHz~30MHz)	2.40dB
Radiated Emissions(30MHz~1000MHz)	4.66dB
Radiated Emissions(1GHz~18GHz)	5.42dB
Radiated Emissions(18GHz~40GHz)	5.46dB

Uncertainty figures are valid to a confidence level of 95%

4 Test Results

4.1 Field Strength of Spurious Radiation

Limits

FCC part	Test Band	Limit
§2.1053 §22.917(a) §24.238(a) §27.53(g) §27.53(h)	LTE Band 5/26(824 ~ 849MHz) LTE Band 2/25 LTE Band 12/17/71 LTE Band 4/66	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.
§27.53(c)(f)	LTE Band 13	On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB; For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.
§90.543(e)(f)	LTE Band 14	least $43 + 10 \log(P)$ dB. For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals.
§27.53(m)	LTE Band 7/41	All frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz.
§90.691	LTE Band 26(814~824MHz)	The power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log(P)$ decibels or 80 decibels, whichever is the lesser attenuation.

Test Procedure

KDB 971168 D01 V03r01 Section 7

Test Settings

- For radiated emissions measurements performed at frequencies less than or equal to 1GHz, the EUT shall be placed on a RF-transparent table or support at a nominal height of 80cm above the reference ground plane.
- For radiated emissions measurements performed at frequencies above 1GHz, the EUT shall be placed on a RF-transparent table or support at a nominal height of 150cm above the ground plane.
- Radiated measurements shall be made with the measurement antenna positioned in both horizontal and vertical polarization. The measurement antenna shall be varied from 1m to 4m in height above the reference ground in a search for the relative positioning that produces the maximum radiated signal level (i.e, field strength or received power), when orienting the measurement antenna in vertical polarization, the minimum height of the lowest element of the antenna shall clear the site reference ground plane by at least 25cm.

4. For each suspected emission, the EUT was ranged its worst case and then tune the antenna tower(from 1~4m) and turntable(from 0~360°) find the maximum reading. Preamplifier and a high pass filter are used for the test in order get better signal level comply with the guidelines.
5. The simulated base station was set to force the EUT to its maximum transmitting power.
6. spectrum analyzer setting:
Measurements 9kHz ~150kHz: RBW = 300Hz; VBW ≥ 3kHz; Detector = RMS
Measurements 150kHz ~30MHz: RBW = 10kHz; VBW ≥ 30kHz; Detector = RMS
Measurements 30MHz~1000MHz: RBW = 100kHz or 1MHz; VBW ≥ 1MHz or 3MHz; Detector = RMS
Measurements Above 1000MHz: RBW = 1 MHz; VBW ≥ 3 MHz; Detector = RMS
7. The field strength is calculated by adding the Antenna Factor, Cable Factor. The basic equation with a sample calculation is as follows:
$$E(\text{dB}\mu\text{V/m}) = \text{Measured amplitude level (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}.$$
$$E(\text{dB}\mu\text{V/m}) = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}.$$
$$E(\text{dB}\mu\text{V/m}) = \text{EIRP(dBm)} - 20\log(D) + 104.8; \text{ where D is the measurement distance(in the far field region) in m.}$$
$$\text{EIRP(dBm)} = E(\text{dB}\mu\text{V/m}) + 20\log(D) - 104.8; \text{ where D is the measurement distance(in the far field region) in m.}$$

So, from d: The measuring distance is usually at 3m, then $20 \cdot \log(3) = 9.5424$

Then, $\text{EIRP (dBm)} = E(\text{dB}\mu\text{V/m}) + 9.5424 - 104.8 = E(\text{dB}\mu\text{V/m}) - 95.2576$
8. Repeat above procedures until all frequencies measured was complete.
9. Measure and record the results in the test report.

Test notes

1. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst-case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
2. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
3. Radiated spurious emissions were investigated from 9kHz to 30MHz, 30MHz-1GHz and above 1GHz. the disturbance between 9kHz to 30MHz, 30MHz-1GHz and 18GHz to 40GHz was very low. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be recorded, so only the harmonics had been displayed.
4. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

Test Setup

Refer to section 2.7.1 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result

The detailed test data see: **Appendix**.

5 Test Setup Photos

The detailed test data see: **Appendix-A WWAN Setup Photos**

Appendix

Maximum Power

Frequency Band	Frequency Range (MHz)		Emission Designator	Conducted Power dBm	Conducted Power (W)	Gain dBi	EIRP/ERP		Limit dBm
	Low	High					dBm	W	
B2	1860	1900	17M9G7D	23.32	0.2148	2.51	25.83	0.3828	33.00
B2	1860	1900	17M9W7D	23.21	0.2094	2.51	25.72	0.3733	33.00
B2	1857.5	1902.5	13M5W7D	23.32	0.2148	2.51	25.83	0.3828	33.00
B25	1860	1905	17M9G7D	23.44	0.2208	2.75	26.19	0.4159	33.00
B25	1860	1905	17M9W7D	23.11	0.2046	2.75	25.86	0.3855	33.00
B25	1857.5	1907.5	13M5W7D	23.38	0.2178	2.75	26.13	0.4102	33.00
B4	1720	1745	17M9G7D	23.15	0.2065	0.71	23.86	0.2432	30.00
B4	1720	1745	17M9W7D	22.64	0.1837	0.71	23.35	0.2163	30.00
B4	1715	1750	9M01W7D	22.96	0.1977	0.71	23.67	0.2328	30.00
B5	829	844	9M05G7D	22.91	0.1954	-1.44	19.32	0.0855	38.45
B5	829	844	9M03W7D	22.45	0.1758	-1.44	18.86	0.0769	38.45
B5	824.7	848.3	1M10W7D	22.53	0.1791	-1.44	18.94	0.0783	38.45
B26(824-849)	831.5	841.5	13M5G7D	23.34	0.2158	-1.44	19.75	0.0944	38.45
B26(824-849)	831.5	841.5	13M5W7D	23.28	0.2128	-1.44	19.69	0.0931	38.45
B66	1720	1770	17M9G7D	23.42	0.2198	0.71	24.13	0.2588	30.00
B66	1720	1770	17M9W7D	22.95	0.1972	0.71	23.66	0.2323	30.00
B66	1715	1775	9M01W7D	23.12	0.2051	0.71	23.83	0.2415	30.00
B7	2510	2560	17M9G7D	23.33	0.2153	0.49	23.82	0.2410	33.00
B7	2510	2560	17M9W7D	23.04	0.2014	0.49	23.53	0.2254	33.00
B12	704	711	9M11G7D	23.56	0.2270	-1.67	19.74	0.0942	34.77
B12	704	711	9M01W7D	23.48	0.2228	-1.67	19.66	0.0925	34.77
B13	782	782	9M03G7D	23.08	0.2032	-1.61	19.32	0.0855	34.77
B13	782	782	8M95W7D	22.98	0.1986	-1.61	19.22	0.0836	34.77
B17	709	711	9M11G7D	23.40	0.2188	-1.67	19.58	0.0908	34.77
B17	709	711	9M01W7D	23.25	0.2113	-1.67	19.43	0.0877	34.77
B41	2506	2680	18M0G7D	23.24	0.2109	1.56	24.80	0.3020	33.00
B41	2506	2680	18M0W7D	22.65	0.1841	1.56	24.21	0.2636	33.00
B41	2501	2685	9M05W7D	23.09	0.2037	1.56	24.65	0.2917	33.00
B71	673	688	17M9G7D	23.14	0.2061	-1.52	21.62	0.1452	34.77
B71	673	688	17M9W7D	22.19	0.1656	-1.52	20.67	0.1167	34.77
B26(814-824)	824	824	13M4G7D	23.29	0.2133	-1.44	/	/	50.00
B26(814-824)	824	824	13M5W7D	23.12	0.2051	-1.44	/	/	50.00
B26(814-824)	819	819	8M97W7D	23.13	0.2056	-1.44	/	/	50.00
B14	793	793	8M99G7D	23.35	0.2163	-1.61	19.59	0.0910	34.77


B14	793	793	9M03W7D	23.18	0.2080	-1.61	19.42	0.0875	34.77
-----	-----	-----	---------	-------	--------	-------	-------	--------	-------

Field Strength of Spurious Radiation

Test Result For LTE:

Project Information			
Mode:	LTE	Band:	B2
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List									
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1871.00	112.34	-95.06	17.28	-	-	150	Horizontal	NA
2	3742.00	50.23	-107.43	-57.20	-13.00	44.20	150	Horizontal	PASS
3	5613.50	40.69	-101.19	-60.50	-13.00	47.50	150	Horizontal	PASS
4	17342.50	33.78	-82.75	-48.97	-13.00	35.97	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B2
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1871.20	120.86	-95.06	25.80	-	-	150	Vertical	NA
2	3742.00	48.42	-107.43	-59.01	-13.00	46.01	150	Vertical	PASS
3	5613.50	40.31	-101.19	-60.88	-13.00	47.88	150	Vertical	PASS
4	17353.50	32.86	-82.54	-49.68	-13.00	36.68	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B4
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1723.60	102.55	-85.28	17.27	-	-	150	Horizontal	NA
2	2138.60	41.17	-84.57	-43.40	-	-	150	Horizontal	NA
3	3447.00	42.70	-107.30	-64.60	-13.00	51.60	150	Horizontal	PASS
4	8149.50	35.94	-94.55	-58.61	-13.00	45.61	150	Horizontal	PASS
5	17349.00	31.87	-82.44	-50.57	-13.00	37.57	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B4
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1723.60	108.59	-85.28	23.31	-	-	150	Vertical	NA
2	2138.20	41.75	-84.57	-42.82	-	-	150	Vertical	NA
3	3447.00	47.55	-107.30	-59.75	-13.00	46.75	150	Vertical	PASS
4	8878.50	37.28	-93.07	-55.79	-13.00	42.79	150	Vertical	PASS
5	17347.50	32.90	-82.51	-49.61	-13.00	36.61	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B5
Bandwidth:	10MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1664.27	80.55	-114.12	-33.57	-13.00	20.57	150	Horizontal	PASS
2	2496.27	72.76	-111.37	-38.61	-13.00	25.61	150	Horizontal	PASS
3	3328.53	56.35	-108.29	-51.94	-13.00	38.94	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B5
Bandwidth:	10MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1664.00	84.47	-114.12	-29.65	-13.00	16.65	150	Vertical	PASS
2	2496.27	68.30	-111.37	-43.07	-13.00	30.07	150	Vertical	PASS
3	3328.53	58.72	-108.29	-49.57	-13.00	36.57	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B7
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	2526.10	102.60	-83.04	19.56	-	-	150	Horizontal	NA
2	5052.00	41.86	-102.82	-60.96	-25.00	35.96	150	Horizontal	PASS
3	9580.50	35.66	-92.54	-56.88	-25.00	31.88	150	Horizontal	PASS
4	17356.00	32.65	-82.63	-49.98	-25.00	24.98	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B7
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	2526.10	110.87	-83.04	27.83	-	-	150	Vertical	NA
2	5052.50	43.45	-102.81	-59.36	-25.00	34.36	150	Vertical	PASS
3	9474.00	36.58	-93.07	-56.49	-25.00	31.49	150	Vertical	PASS
4	17353.00	32.20	-82.52	-50.32	-25.00	25.32	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B12
Bandwidth:	10MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1406.00	69.42	-114.33	-44.91	-13.00	31.91	150	Horizontal	PASS
2	2109.27	50.47	-113.21	-62.74	-13.00	49.74	150	Horizontal	PASS
3	2812.30	48.80	-109.81	-61.01	-13.00	48.01	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B12
Bandwidth:	10MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1406.00	62.84	-114.33	-51.49	-13.00	38.49	150	Vertical	PASS
2	2812.07	55.28	-109.81	-54.53	-13.00	41.53	150	Vertical	PASS
3	3515.33	54.83	-107.50	-52.67	-13.00	39.67	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B13
Bandwidth:	10MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1555.10	64.59	-114.07	-49.48	-13.00	36.48	150	Horizontal	PASS
2	2332.57	57.55	-112.39	-54.84	-13.00	41.84	150	Horizontal	PASS
3	6308.33	37.75	-98.90	-61.15	-13.00	48.15	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B13
Bandwidth:	10MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1555.10	67.90	-114.07	-46.17	-13.00	33.17	150	Vertical	PASS
2	2332.57	60.24	-112.39	-52.15	-13.00	39.15	150	Vertical	PASS
3	6909.87	37.53	-97.69	-60.16	-13.00	47.16	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B14
Bandwidth:	10MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1577.03	67.84	-114.18	-46.34	-40.00	6.34	150	Horizontal	PASS
2	2365.93	53.46	-112.42	-58.96	-13.00	45.96	150	Horizontal	PASS
3	5156.83	37.63	-101.93	-64.30	-13.00	51.30	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B14
Bandwidth:	10MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1577.03	67.82	-114.18	-46.36	-40.00	6.36	150	Vertical	PASS
2	2365.93	62.44	-112.42	-49.98	-13.00	36.98	150	Vertical	PASS
3	5110.63	37.50	-101.95	-64.45	-13.00	51.45	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B17
Bandwidth:	10MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1411.13	65.93	-114.35	-48.42	-13.00	35.42	150	Horizontal	PASS
2	2822.33	46.87	-109.72	-62.85	-13.00	49.85	150	Horizontal	PASS
3	3528.17	42.18	-107.60	-65.42	-13.00	52.42	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B17
Bandwidth:	10MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1411.37	61.12	-114.35	-53.23	-13.00	40.23	150	Vertical	PASS
2	2822.33	55.01	-109.72	-54.71	-13.00	41.71	150	Vertical	PASS
3	3527.70	52.94	-107.60	-54.66	-13.00	41.66	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B25
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1873.60	102.17	-84.97	17.20	-	-	150	Horizontal	NA
2	3747.50	45.00	-107.42	-62.42	-13.00	49.42	150	Horizontal	PASS
3	9473.00	37.79	-93.10	-55.31	-13.00	42.31	150	Horizontal	PASS
4	17348.50	32.85	-82.47	-49.62	-13.00	36.62	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B25
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1873.60	111.97	-84.97	27.00	-	-	150	Vertical	NA
2	3747.00	47.17	-107.43	-60.26	-13.00	47.26	150	Vertical	PASS
3	5620.50	40.48	-101.10	-60.62	-13.00	47.62	150	Vertical	PASS
4	9503.50	37.36	-92.60	-55.24	-13.00	42.24	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B26(814-824)
Bandwidth:	10MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1629.07	63.32	-114.17	-50.85	-13.00	37.85	150	Horizontal	PASS
2	2443.73	53.14	-111.26	-58.12	-13.00	45.12	150	Horizontal	PASS
3	3258.40	41.55	-108.46	-66.91	-13.00	53.91	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B26(814-824)
Bandwidth:	10MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1629.07	62.77	-114.17	-51.40	-13.00	38.40	150	Vertical	PASS
2	2444.00	58.20	-111.24	-53.04	-13.00	40.04	150	Vertical	PASS
3	3258.40	43.76	-108.46	-64.70	-13.00	51.70	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B26(824-849)
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1659.73	78.77	-114.11	-35.34	-13.00	22.34	150	Horizontal	PASS
2	2490.13	58.02	-111.34	-53.32	-13.00	40.32	150	Horizontal	PASS
3	3319.47	45.15	-108.25	-63.10	-13.00	50.10	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B26(824-849)
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1659.73	80.36	-114.11	-33.75	-13.00	20.75	150	Vertical	PASS
2	2489.33	62.56	-111.34	-48.78	-13.00	35.78	150	Vertical	PASS
3	3319.47	50.06	-108.25	-58.19	-13.00	45.19	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B66
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1736.20	102.40	-85.18	17.22	-	-	150	Horizontal	NA
2	2142.60	36.62	-84.61	-47.99	-	-	150	Horizontal	NA
3	4751.50	38.12	-103.22	-65.10	-13.00	52.10	150	Horizontal	PASS
4	10270.00	35.26	-91.59	-56.33	-13.00	43.33	150	Horizontal	PASS
5	17337.50	32.56	-82.97	-50.41	-13.00	37.41	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B66
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1736.00	108.17	-85.18	22.99	-	-	150	Vertical	NA
2	2147.40	41.85	-84.66	-42.81	-	-	150	Vertical	NA
3	4779.00	37.46	-102.97	-65.51	-13.00	52.51	150	Vertical	PASS
4	9576.50	36.05	-92.57	-56.52	-13.00	43.52	150	Vertical	PASS
5	17350.00	32.57	-82.40	-49.83	-13.00	36.83	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B71
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1343.00	70.98	-114.21	-43.23	-13.00	30.23	150	Horizontal	PASS
2	2686.07	60.49	-110.49	-50.00	-13.00	37.00	150	Horizontal	PASS
3	3358.30	58.85	-108.24	-49.39	-13.00	36.39	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B71
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	1343.00	71.76	-114.21	-42.45	-13.00	29.45	150	Vertical	PASS
2	2014.77	63.93	-113.51	-49.58	-13.00	36.58	150	Vertical	PASS
3	3357.83	57.66	-108.25	-50.59	-13.00	37.59	150	Vertical	PASS

Project Information

Mode:	LTE	Band:	B41(2496-2690)
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	2584.10	96.49	-82.40	14.09	-	-	150	Horizontal	NA
2	4786.00	37.75	-102.91	-65.16	-25.00	40.16	150	Horizontal	PASS
3	10076.50	35.23	-91.80	-56.57	-25.00	31.57	150	Horizontal	PASS
4	17349.00	32.02	-82.44	-50.42	-25.00	25.42	150	Horizontal	PASS

Project Information

Mode:	LTE	Band:	B41(2496-2690)
Bandwidth:	20MHz	Channel:	Mid
IMEI:	-	Engineer:	Tian Shuo
Remark:	EUT(M02)		

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Polarity	Verdict
1	2584.10	108.14	-82.40	25.74	-	-	150	Vertical	NA
2	5168.00	38.15	-102.04	-63.89	-25.00	38.89	150	Vertical	PASS
3	10300.00	35.09	-91.45	-56.36	-25.00	31.36	150	Vertical	PASS
4	17354.50	31.90	-82.58	-50.68	-25.00	25.68	150	Vertical	PASS

~The End~