




10 Carrier Frequency Separation Test

10.1 Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	>25KHz or >two-thirds of the 20 dB bandwidth

10.2 Test Setup



10.3 Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer settings:

1. Span= Wide enough to capture the peaks of two adjacent channels
2. Set the RBW = 300 kHz.
3. Set the VBW = 300 kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

10.4 Test Data

Test Item	:	Frequency Separation	Test Mode	:	CH Low ~ CH High
Test Voltage	:	DC 3.7V	Temperature	:	24.5°C
Test Result	:	PASS	Humidity	:	55%RH



L:


TestMode	Antenna	Frequency[MHz]	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	0.676	≥ 0.642	PASS
2DH5	Ant1	Hop	1.232	≥ 0.930	PASS

R:

TestMode	Antenna	Frequency[MHz]	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	0.95	≥ 0.688	PASS
2DH5	Ant1	Hop	1.166	≥ 0.884	PASS


Test Graphs:

L:





R:






11 Number of Hopping Channel Test

11.1 Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	>15 channels

11.2 Test Setup



11.3 Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer setting:

1. Span= the frequency band of operation
2. Set the RBW = 300kHz.
3. Set the VBW = 300kHz.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.



11.4 Test Data

Test Item	: Number of Hopping Frequency	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 3.7V	Temperature	: 24.5°C
Test Result	: PASS	Humidity	: 55%RH

L:


TestMode	Antenna	Frequency[MHz]	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS


R:

TestMode	Antenna	Frequency[MHz]	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS


Test Graphs:


L:





R:








12 Dwell Time Test

12.1 Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	0.4 sec

12.2 Test Setup



12.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span= zero span, centered on a hopping channel
2. Set the RBW = 1 MHz.
3. Set the VBW = 3 MHz.
4. Sweep time = as necessary to capture the entire dwell time per hopping channel.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.



12.4 Test Data

Test Item : Time of Occupancy
Test Voltage : DC 3.7V
Test Result : PASS

Test Mode : CH Low ~ CH High
Temperature : 24.5°C
Humidity : 55%RH

L:

TestMode	Antenna	Frequency[MHz]	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH5	Ant1	Hop	2.885	106.67	0.308	≤0.4	PASS
2DH5	Ant1	Hop	2.891	106.67	0.308	≤0.4	PASS
DH1	Ant1	Hop	0.381	320	0.122	≤0.4	PASS
2DH1	Ant1	Hop	0.390	320	0.125	≤0.4	PASS
DH3	Ant1	Hop	1.638	160	0.262	≤0.4	PASS
2DH3	Ant1	Hop	1.643	160	0.263	≤0.4	PASS

R:

TestMode	Antenna	Frequency[MHz]	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH5	Ant1	Hop	2.885	106.67	0.308	≤0.4	PASS
2DH5	Ant1	Hop	2.891	106.67	0.308	≤0.4	PASS
DH1	Ant1	Hop	0.383	320	0.123	≤0.4	PASS
2DH1	Ant1	Hop	0.391	320	0.125	≤0.4	PASS
DH3	Ant1	Hop	1.638	160	0.262	≤0.4	PASS
2DH3	Ant1	Hop	1.643	160	0.263	≤0.4	PASS


Note:

- 1.DH1/2DH1 Dwell Time: Reading * (1600/2)*31.6/(channel number).
- 2.DH3/2DH3 Dwell Time: Reading * (1600/4)*31.6/(channel number).
- 3.DH5/2DH5 Dwell Time: Reading * (1600/6)*31.6/(channel number).




Test Graphs:

L:





2DH1-Ant1-Hop-PASS



DH3-Ant1-Hop-PASS



2DH3-Ant1-Hop-PASS





R:

DH5-Ant1-Hop-PASS




2DH5-Ant1-Hop-PASS



DH1-Ant1-Hop-PASS



2DH1-Ant1-Hop-PASS



DH3-Ant1-Hop-PASS



2DH3-Ant1-Hop-PASS




13 100kHz Bandwidth of Frequency Band Edge Requirement

13.1 Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

13.2 Test Setup



13.3 Test Procedure

The EUT must have its hopping/Non-hopping function enabled. Using the following spectrum analyzer setting:

1. Set the RBW = 100kHz.
2. Set the VBW = 300kHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.



13.4 Test Data

Test Item : Band edge
Test Voltage : DC 3.7V
Test Result : PASS

Test Mode : CH Low ~ CH High
Temperature : 24.5°C
Humidity : 55%RH

L:

TestMode	Antenna	ChName	Frequency[MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	-0.10	-40.65	≤-20.1	PASS
DH5	Ant1	High	2480	0.90	-40.49	≤-19.1	PASS
DH5	Ant1	Low	Hop_2402	-0.51	-41.07	≤-20.51	PASS
DH5	Ant1	High	Hop_2480	0.92	-39.75	≤-19.09	PASS
2DH5	Ant1	Low	2402	-0.23	-40.72	≤-20.23	PASS
2DH5	Ant1	High	2480	1.10	-40.79	≤-18.9	PASS
2DH5	Ant1	Low	Hop_2402	-3.76	-41.34	≤-23.76	PASS
2DH5	Ant1	High	Hop_2480	0.07	-39.95	≤-19.93	PASS


R:


TestMode	Antenna	ChName	Frequency[MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	-0.04	-40.77	≤-20.04	PASS
DH5	Ant1	High	2480	0.90	-40.21	≤-19.1	PASS
DH5	Ant1	Low	Hop_2402	-1.11	-41.28	≤-21.11	PASS
DH5	Ant1	High	Hop_2480	0.52	-40.12	≤-19.48	PASS
2DH5	Ant1	Low	2402	-0.66	-40.53	≤-20.66	PASS
2DH5	Ant1	High	2480	0.94	-40.44	≤-19.06	PASS
2DH5	Ant1	Low	Hop_2402	-2.73	-41.42	≤-22.73	PASS
2DH5	Ant1	High	Hop_2480	0.23	-40.31	≤-19.77	PASS




Test Graphs:

L:







DH5-Ant1-Hop_2480-PASS




2DH5-Ant1-2402-PASS




2DH5-Ant1-2480-PASS



2DH5-Ant1-Hop_2402-PASS




2DH5-Ant1-Hop_2480-PASS






R:


DH5-Ant1-2402-PASS




DH5-Ant1-2480-PASS




DH5-Ant1-Hop_2402-PASS




DH5-Ant1-Hop_2480-PASS




2DH5-Ant1-2402-PASS




2DH5-Ant1-2480-PASS



2DH5-Ant1-Hop_2402-PASS



2DH5-Ant1-Hop_2480-PASS





Conducted Emission Method

Test Result

L:

TestMode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	0~Reference	-0.48	-0.48	---	PASS
DH5	Ant1	2402	30~1000	-0.48	-53.86	≤-20.48	PASS
DH5	Ant1	2402	1000~26500	-0.48	-41.92	≤-20.48	PASS
DH5	Ant1	2441	0~Reference	-0.17	-0.17	---	PASS
DH5	Ant1	2441	30~1000	-0.17	-53.55	≤-20.17	PASS
DH5	Ant1	2441	1000~26500	-0.17	-42.3	≤-20.17	PASS
DH5	Ant1	2480	0~Reference	1.03	1.03	---	PASS
DH5	Ant1	2480	30~1000	1.03	-54.18	≤-18.97	PASS
DH5	Ant1	2480	1000~26500	1.03	-41.76	≤-18.97	PASS
2DH5	Ant1	2402	0~Reference	-0.06	-0.06	---	PASS
2DH5	Ant1	2402	30~1000	-0.06	-54.15	≤-20.06	PASS
2DH5	Ant1	2402	1000~26500	-0.06	-41.3	≤-20.06	PASS
2DH5	Ant1	2441	0~Reference	-0.21	-0.21	---	PASS
2DH5	Ant1	2441	30~1000	-0.21	-54.13	≤-20.21	PASS
2DH5	Ant1	2441	1000~26500	-0.21	-41.81	≤-20.21	PASS
2DH5	Ant1	2480	0~Reference	1.08	1.08	---	PASS
2DH5	Ant1	2480	30~1000	1.08	-53.24	≤-18.92	PASS
2DH5	Ant1	2480	1000~26500	1.08	-42.63	≤-18.92	PASS

R:

TestMode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	0~Reference	-0.31	-0.31	---	PASS
DH5	Ant1	2402	30~1000	-0.31	-54.1	≤-20.31	PASS
DH5	Ant1	2402	1000~26500	-0.31	-41.55	≤-20.31	PASS
DH5	Ant1	2441	0~Reference	-0.28	-0.28	---	PASS
DH5	Ant1	2441	30~1000	-0.28	-54.33	≤-20.28	PASS
DH5	Ant1	2441	1000~26500	-0.28	-41.86	≤-20.28	PASS



Report No.: PTC25100920001E-FC01

DH5	Ant1	2480	0~Reference	0.91	0.91	---	PASS
DH5	Ant1	2480	30~1000	0.91	-54.43	≤ -19.09	PASS
DH5	Ant1	2480	1000~26500	0.91	-41.98	≤ -19.09	PASS
2DH5	Ant1	2402	0~Reference	-0.21	-0.21	---	PASS
2DH5	Ant1	2402	30~1000	-0.21	-54	≤ -20.21	PASS
2DH5	Ant1	2402	1000~26500	-0.21	-42.22	≤ -20.21	PASS
2DH5	Ant1	2441	0~Reference	-0.31	-0.31	---	PASS
2DH5	Ant1	2441	30~1000	-0.31	-53.14	≤ -20.31	PASS
2DH5	Ant1	2441	1000~26500	-0.31	-41.77	≤ -20.31	PASS
2DH5	Ant1	2480	0~Reference	0.91	0.91	---	PASS
2DH5	Ant1	2480	30~1000	0.91	-54.75	≤ -19.09	PASS
2DH5	Ant1	2480	1000~26500	0.91	-41.82	≤ -19.09	PASS




Test Graphs:

L:

DH5-Ant1-2402-0~Reference-PASS



DH5-Ant1-2402-30~1000-PASS




DH5-Ant1-2402-1000~26500-PASS




DH5-Ant1-2441-0~Reference-PASS



DH5-Ant1-2441-30~1000-PASS




DH5-Ant1-2441-1000~26500-PASS



DH5-Ant1-2480-0~Reference-PASS



DH5-Ant1-2480-30~1000-PASS



DH5-Ant1-2480-1000~26500-PASS