

Bluetooth Antenna For ISM 2.4 GHz Applications

◆ Part number : AHSBTF0402-L00

Specification


Frequency	2400 ~ 2485 MHz
VSWR	2.0 max
Peak Gain	1.9 dBi min
Radiation Pattern	Omni-directional
Input Impedance	50 ohm

<Typical Test Board>




- Ground size : 37 X 42 mm



VSWR on Evaluation Board



Gain on Evaluation Board (2D)




(unit : dBi)

Frequency (MHz)	Azimuth Plane(XY)	Elevation1 Plane(YZ)	Elevation2 Plane(ZX)
	Peak Gain	Peak Gain	Peak Gain
2400	-1.0	-0.7	-0.8
2450	1.4	1.3	1.0
2500	0.3	0.5	0.7




Gain on Evaluation Board (3D)



(unit : dBi)

Frequency (MHz)	3D Data	
	Peak Gain	Avg. Gain
2400	-0.4	-3.3
2450	1.9	-1.0
2500	1.0	-1.8

Typical Test Board



No ground area

1.2 mm gap



from ground

Matching circuit added in the feeding line

- T-type : series + shunt

- π -type : shunt + series + shunt

Recommended Pad Layout



- 1: Input Pad
- 2: Ground Pad
- 3: Ground Pad
- 4: Non-Contact (For SMT)

