

## RF Exposure Evaluation

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1091, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

| Frequency range<br>(MHz)                                | Electric field<br>strength<br>(V/m) | Magnetic field strength<br>(A/m) | Power density<br>(mW/cm <sup>2</sup> ) | Averaging time<br>(minutes) |
|---------------------------------------------------------|-------------------------------------|----------------------------------|----------------------------------------|-----------------------------|
| (A) Limits for Occupational/Controlled Exposures        |                                     |                                  |                                        |                             |
| 0.3–3.0                                                 | 614                                 | 1.63                             | *(100)                                 | 6                           |
| 3.0–30                                                  | 1842/f                              | 4.89/f                           | *(900/f <sup>2</sup> )                 | 6                           |
| 30–300                                                  | 61.4                                | 0.163                            | 1.0                                    | 6                           |
| 300–1500                                                |                                     |                                  | f/300                                  | 6                           |
| 1500–100,000                                            |                                     |                                  | 5                                      | 6                           |
| (B) Limits for General Population/Uncontrolled Exposure |                                     |                                  |                                        |                             |
| 0.3–1.34                                                | 614                                 | 1.63                             | *(100)                                 | 30                          |
| 1.34–30                                                 | 824/f                               | 2.19/f                           | *(180/f <sup>2</sup> )                 | 30                          |
| 30–300                                                  | 27.5                                | 0.073                            | 0.2                                    | 30                          |
| 300–1500                                                |                                     |                                  | f/1500                                 | 30                          |
| 1500–100,000                                            |                                     |                                  | 1.0                                    | 30                          |

f = frequency in MHz

Friis transmission formula:  $Pd = (P_{out} * G) / (4 * \pi * r^2)$

Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

**R** = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

**IC RF Exposure Evaluation**  
**Limits**

According to RSS-102 issue 6 December 2023

Transmitters are exempt from routine SAR and RF exposure evaluations provided that they comply with the requirements of sections 6.3 or 6.6.

**6.3. SAR exemption limits**

Devices operating at or below the applicable output power levels (adjusted for tune-up tolerance) specified in table 11, based on the separation distance, are exempt from SAR evaluation. The separation distance, defined as the distance between the user and/or bystander and the antenna and/or radiating element of the device or the outer surface of the device, shall be less than or equal to 20 cm for these exemption limits to apply.

**Table 11: Power limits for exemption from routine SAR evaluation based on the separation distance**

| Frequency (MHz) | ≤ 5 mm (mW) | 10 mm (mW) | 15 mm (mW) | 20 mm (mW) | 25 mm (mW) | 30 mm (mW) | 35 mm (mW) | 40 mm (mW) | 45 mm (mW) | > 50 mm (mW) |
|-----------------|-------------|------------|------------|------------|------------|------------|------------|------------|------------|--------------|
| ≤ 300           | 45          | 116        | 139        | 163        | 189        | 216        | 246        | 280        | 319        | 362          |
| 450             | 32          | 71         | 87         | 104        | 124        | 147        | 175        | 208        | 248        | 296          |
| 835             | 21          | 32         | 41         | 54         | 72         | 96         | 129        | 172        | 228        | 298          |
| 1900            | 6           | 10         | 18         | 33         | 57         | 92         | 138        | 194        | 257        | 323          |
| 2450            | 3           | 7          | 16         | 32         | 56         | 89         | 128        | 170        | 209        | 245          |
| 3500            | 2           | 6          | 15         | 29         | 50         | 72         | 94         | 114        | 134        | 158          |
| 5800            | 1           | 5          | 13         | 23         | 32         | 41         | 54         | 74         | 102        | 128          |

## 6.6. Field reference level exposure exemption limits

Field reference level (FRL) exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm (i.e. mobile devices), except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 1 W (adjusted for tune-up tolerance)
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance)
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz
- at or above 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 5 W (adjusted for tune-up tolerance)

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the EIRP was derived.

### Test Result of RF Exposure Evaluation

IC RF Exposure Evaluation

The following table data is calculated based on Chapter 6.6

### Test Result of RF Exposure Evaluation

BLE mode

FCC RF Exposure Evaluation

| Antenna Gain (dBi) | Antenna Gain (numeric) | Max conducted power | Output power to antenna (mW) | Power Density at R=20cm (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) | Result |
|--------------------|------------------------|---------------------|------------------------------|-----------------------------------------------|-----------------------------|--------|
| -0.58              | 0.875                  | 7.32                | 5.40                         | 0.000939                                      | 1                           | PASS   |

IC RF Exposure Evaluation

| Conducted output power(dBm) | Conducted Output power (mW) | EIRP (dBm) | EIRP (mW) | Frequency(MHz) | Limit (W) | Result |
|-----------------------------|-----------------------------|------------|-----------|----------------|-----------|--------|
| 7.32                        | 5.4                         | 6.74       | 4.72      | 2440           | 2.71      | PASS   |

Remark: 2.4G BLE antenna gain=-0.58dBi

EIRP=dBμV/m-95.2=101.94-95.2=6.74, conducted power=EIRP-ANT Gain=6.74-(-0.58)=7.32