



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20250400900E-03
Applicant: eMoMo Technology (Zhejiang) Co., LTD
Address of Applicant: eMoMo Industrial Park, 1158 Yuesi East Road Dipu Street, Anji County, Huzhou City, Zhejiang Province 313000 China
Equipment Under Test (EUT):
EUT Name: Multi-functional Audio System
Model No.: E309BLTV01
Test Model No.: E309BLTV01
Brand Name: eMoMo
FCC ID: 2BHM7-E309BLTV
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
447498 D04 Interim General RF Exposure Guidance v01
Date of Receipt: 2025-04-23
Date of Test: 2025-04-23 to 2025-05-08
Date of Issue: 2025-05-09
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Lewis Zhou

(Lewis Zhou)

Reviewed By:

Timo Lei

(Timo Lei)

Approved By:

Jack Ai

(Jack Ai)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20250400900E-03	Rev.01	Initial report	2025-05-09

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BT CLASSIC	4
3.4 GENERAL DESCRIPTION OF BLE	4
4 MPE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 Limits	6
4.1.2 Test Procedure	6
4.1.3 EUT RF Exposure	7

3 General Information

3.1 Client Information

Applicant:	eMoMo Technology (Zhejiang) Co., LTD
Address of Applicant:	eMoMo Industrial Park, 1158 Yuesi East Road Dipu Street, Anji County, Huzhou City, Zhejiang Province 313000 China
Manufacturer:	eMoMo Technology (Zhejiang) Co., LTD
Address of Manufacturer:	eMoMo Industrial Park, 1158 Yuesi East Road Dipu Street, Anji County, Huzhou City, Zhejiang Province 313000 China
Factory:	eMoMo Technology (Zhejiang) Co., LTD
Address of Factory:	eMoMo Industrial Park, 1158 Yuesi East Road Dipu Street, Anji County, Huzhou City, Zhejiang Province 313000 China

3.2 General Description of EUT

Product Name:	Multi-functional Audio System
Model No.:	E309BLTV01
Test Model No.:	E309BLTV01
Trade Mark:	eMoMo
Software Version:	SMD_YXR2388
Hardware Version:	REMO6_V1.0
EUT Power Supply:	Power supply AC120V

3.3 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	PCB antenna
Antenna Gain:	3.38dBi
Cable loss:	1.0 dB

3.4 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.0
Modulation Type:	GFSK
Number of Channel:	40
Transfer Rate:	1Mbps/2Mbps
Sample Type:	☒ Mobile ☐ Portable

Antenna Type:	PCB antenna
Antenna Gain:	3.38dBi
Cable loss:	1.0 dB

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave Dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For BT Classic

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	3.48	1.33	1.5±1	2.5	1.78
Middle(2441MHz)	4.11	1.96	2.0±1	3	2.00
Highest(2480MHz)	4.39	2.24	2.5±1	3.5	2.24
π/4DQPSK mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	3.92	1.77	2.0±1	3	2.00
Middle(2441MHz)	4.16	2.01	2.5±1	3.5	2.24
Highest(2480MHz)	4.73	2.58	3.0±1	4	2.51

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20250400900E-01 for EUT test Max Conducted Peak Output Power value.

2) EUT's module is more than 20cm away from the human body.

2) For BLE

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode(1Mbps)					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	3.34	1.19	1.5±1	2.5	1.78
Middle(2440MHz)	4.34	2.19	2.5±1	3.5	2.24
Highest(2480MHz)	4.36	2.21	2.5±1	3.5	2.24
GFSK mode(2Mbps)					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	3.64	1.49	1.5±1	2.5	1.78
Middle(2440MHz)	4.43	2.28	2.5±1	3.5	2.24
Highest(2480MHz)	4.56	2.41	2.5±1	3.5	2.24

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20250400900E-01 for EUT test Max Conducted Peak Output Power value.

2) EUT's module is more than 20cm away from the human body.

*** END OF REPORT ***