EMC TEST REPORT

Applicant	Shanghai Xin an Information and Technology Co. Ltd.
FCC ID	2BHQ6-MTAG
Product	Mtag
Brand	Mtag
Model	Mtag
Report No.	R2406A0747-E1
Issue Date	August 9, 2024

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2023)/ ANSI C63.4-2014**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Liu Wei	Fan Guangchang
Prepared by: Liu Wei	*Approved by: Fan Guangchang*

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
TEL: +86-021-50791141/2/3
FAX: +86-021-50791141/2/3-8000

Table of Contents

1 Test Laboratory 4
1.1 Notes of the Test Report 4
1.2 Test Facility 4
1.3 Testing Location 4
2 General Description of Equipment Under Test 5
2.1 Applicant and Manufacturer Information 5
2.2 General Information 5
2.3 Applied Standards 6
2.4 Test Mode 7
3 Test Case Results 8
3.1 Radiated Emission 8
3.2 Conducted Emission 13
4 Uncertainty Measurement 15
5 Main Test Instruments 16
ANNEX A: The EUT Appearance 17
ANNEX B: Test Setup Photos 18

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	NA Note 1
Date of Testing: October 16, 2023 ~ October 17, 2023 Date of Sample Received: October 11, 2023			
Note: 1. The equipment is not connected to the public network, so test items do not apply. 2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

This report change report number, all test values duplicated from the original report (Report No.: R2309A1013-E2).

This revised report (Report No.: R2406A0747-E1) supersedes and replaces the previously issued report (Report No.: R2309A1013-E2). Please discard or destroy the previously issued report and dispose of it accordingly.

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3 Testing Location

Company:	Eurofins TA Technology (Shanghai) Co., Ltd.
Address:	Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Fan Guangchang
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	https://www.eurofins.com/electrical-and-electronics
E-mail:	Jack.Fan@cpt.eurofinscn.com

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

2 General Description of Equipment Under Test

2.1 Applicant and Manufacturer Information

Applicant	Shanghai Xin an Information and Technology Co. Ltd.
Applicant address	1st Floor, Building 8, Lane 568, Tanglu Road, Pudong New Area, Shanghai, China
Manufacturer	Shanghai Xin an Information and Technology Co. Ltd.
Manufacturer address	1st Floor, Building 8, Lane 568, Tanglu Road, Pudong New Area, Shanghai, China

2.2 General Information

EUT Description			
Device Type	Portable Device		
Model	Mtag		
Lab internal SN	R2309A1013/S02		
HW Version	HW 1.0		
SW Version	1.2.0		
Power Rating	DC 3.3V		
Connecting I/O Port(s)	Please refer to the User's Manual.		
Antenna Type	Internal Antenna		
Frequency	Band	Tx (MHz)	Rx (MHz)
	Bluetooth LE	2400 ~ 2483.5	2400 ~ 2483.5
Auxiliary Test Equipment			
PC	PC Manufacturer: Dell Model: INSPIRON 5493 (SN: 12206714403)		
Note: The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.			

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards
FCC Code CFR47 Part15B (2023)
ANSI C63.4-2014

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

2.4 Test Mode

Test Mode	
Mode 1:	PC Power Supply + EUT + Receiver
Mode 2:	PC Power Supply + EUT + Standby

Test Type	Test Mode	Worst Mode
Radiated Emission	Mode 1, 2	Mode 1
Conducted Emission	/	/
During the test, the preliminary test was performed in all modes, the test data of the worst-case condition was recorded in this report.		

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

3 Test Case Results

3.1 Radiated Emission

Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	30% ~ 60%

Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.
The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.
Set the spectrum analyzer in the following:

Below 1GHz:
RBW=100 kHz / VBW=300 kHz / Sweep=AUTO
Above 1GHz:
(a) PEAK Detector: RBW=1MHz / VBW=3MHz/ Sweep=AUTO
(b) AVERAGE Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

During the test, EUT is connected to a laptop via a USB cable in the case of power supply.

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

Test Setup

Below 1GHz



Above 1GHz



Note: Area side: 2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

Limits

Class B

Frequency (MHz)	Field Strength (dBµV/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5th harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak

Frequency range of radiated measurements

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

Test Results

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier.

The following graphs display the maximum values of horizontal and vertical by software.
For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.
A symbol (dB礦/m) in the test plot below means (dBμV/m)



Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
34.32	21.82	40.00	18.18	188.0	V	204.00	18
54.74	23.85	40.00	16.15	207.0	H	245.00	20
106.80	21.63	43.50	21.87	178.0	H	30.00	18
192.80	26.36	43.50	17.14	100.0	H	1.00	18
327.99	26.22	46.00	19.78	178.0	V	166.00	22
722.18	33.72	46.00	12.28	122.0	V	336.00	29

Remark: 1. Correction Factor = Antenna factor + Insertion loss(cable loss)
2. Margin = Limit – Quasi-Peak

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.



Radiated Emission from 1GHz to 18GHz

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1414.38	---	30.57	54.00	23.43	500.00	100.0	H	261.00	-19
1599.25	43.29	---	74.00	30.71	500.00	200.0	H	0.00	-19
1858.50	43.57	---	74.00	30.43	500.00	100.0	V	60.00	-19
2128.38	---	30.64	54.00	23.36	500.00	100.0	H	350.00	-17
2655.38	54.94	---	74.00	19.06	500.00	100.0	H	357.00	-15
2655.38	---	37.76	54.00	16.24	500.00	100.0	H	357.00	-15
4091.88	---	32.56	54.00	21.44	500.00	100.0	V	184.00	-11
4249.13	43.96	---	74.00	30.04	500.00	100.0	H	355.00	-11
6650.38	48.40	---	74.00	25.60	500.00	100.0	H	290.00	-3
6663.13	---	37.14	54.00	16.86	500.00	200.0	V	178.00	-3
9725.25	---	39.54	54.00	14.46	500.00	200.0	H	51.00	0
13726.63	54.64	---	74.00	19.36	500.00	200.0	H	8.00	6

Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)
2. Margin = Limit –MAX Peak/ Average

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

3.2 Conducted Emission

Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	30% ~ 60%

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.
During the test, EUT is connected to a laptop via a USB cable in the case of power supply.

Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.

Limits

Frequency (MHz)	Class A (dBμV)		Class B (dBμV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 to 56 *	56 to 46*
0.5 - 5	73	60	56	46
5 - 30	73	60	60	50
*: Decreases with the logarithm of the frequency.				

Note: The EUT should meet CLASS B limit.

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

Test Results

The equipment doesn't connected to public network, therefore this requirement do not apply.

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

4 Uncertainty Measurement

Case	Uncertainty	Factor k
Radiated Emission 30MHz – 200MHz	4.17 dB	1.96
Radiated Emission 200MHz – 1GHz	4.84 dB	1.96
Radiated Emission 1GHz – 18GHz	4.35 dB	1.96

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

5 Main Test Instruments

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Expiration Time
Radiated Emission					
EMI Test Receiver	R&S	ESR	102389	2023-05-12	2024-05-11
Signal Analyzer	R&S	FSV40	101186	2023-05-12	2024-05-11
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	1023	2023-07-14	2026-07-13
Horn Antenna	R&S	HF907	102723	2021-07-24	2024-07-23
Software	R&S	EMC32	9.26.01	/	/

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.

ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.

******** END OF REPORT ********

This report shall not be reproduced except in full, without the written approval of Eurofins TA Technology (Shanghai) Co., Ltd.