FCC Part 15E Test Report
FCC ID: 2BHX3-TD8800M80

Applicant:	Shenzhen Trolink Technology Co.,Ltd
Address:	Floor 5, Block E, Fenda High-Tech Park, Sanwei Community, Hangcheng Street, Bao'an Distict, Shenzhen, Guangdong, China
Manufacturer:	Shenzhen Trolink Technology Co.,Ltd
Address:	Floor 5, Block E, Fenda High-Tech Park, Sanwei Community, Hangcheng Street, Bao'an Distict, Shenzhen, Guangdong, China
EUT:	network card
Trade Mark:	N/A
Model Number:	TD8800M80 TD8912
Date of Receipt:	Dec. 25, 2024
Test Date:	Dec. 25, 2024 - Mar. 03, 2025
Date of Report:	Mar. 03, 2025
Prepared By:	Shenzhen DL Testing Technology Co., Ltd.
Address:	101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China
Applicable Standards:	FCC PART 15 E 15.407 ANSI C63.10:2013
Test Result:	Pass
Report Number:	DL-241225024ER

Prepared (Test Engineer):	Alisa Song
Reviewer (Supervisor):	Jack Bu
Approved (Manager):	Jade Yang

This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.

Table of Contents **Page**

1 . SUMMARY OF TEST RESULTS 4
1.1 MEASUREMENT UNCERTAINTY 4
2 . GENERAL INFORMATION 5
2.1 GENERAL DESCRIPTION OF EUT 5
2.2 DESCRIPTION OF TEST MODES 7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 7
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 8
2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING 8
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS 9
3 . EMC EMISSION TEST 10
3.1 CONDUCTED EMISSION MEASUREMENT 10
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS 10
3.1.2 TEST PROCEDURE 10
3.1.3 DEVIATION FROM TEST STANDARD 10
3.1.4 TEST SETUP 11
3.1.5 EUT OPERATING CONDITIONS 11
3.1.6 TEST RESULTS 11
3.2 RADIATED EMISSION MEASUREMENT 12
3.2.1 RADIATED EMISSION LIMITS 12
3.2.2 TEST PROCEDURE 13
3.2.3 DEVIATION FROM TEST STANDARD 13
3.2.4 TEST SETUP 14
3.2.5 EUT OPERATING CONDITIONS 15
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ) 16
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ) 17
3.2.8 TEST RESULTS (1GHZ~40GHZ) 19
3.3 RADIATED BAND EMISSION MEASUREMENT 42
3.3.1 TEST REQUIREMENT: 42
3.3.2 TEST PROCEDURE 42
3.3.3 DEVIATION FROM TEST STANDARD 42
3.3.4 TEST SETUP 42
3.3.5 EUT OPERATING CONDITIONS 42
4 . PEAK OUTPUT POWER 49
4.1 APPLIED PROCEDURES / LIMIT 49
4.1.1 TEST PROCEDURE 49
4.1.2 DEVIATION FROM STANDARD 49
4.1.3 TEST SETUP 49
4.1.4 EUT OPERATION CONDITIONS 49
4.1.5 TEST RESULTS 50
5 . POWER SPECTRAL DENSITY TEST 59
5.1 APPLIED PROCEDURES / LIMIT 59
5.1.1 TEST PROCEDURE 59
5.1.2 DEVIATION FROM STANDARD 59
5.1.3 TEST SETUP 59
5.1.4 EUT OPERATION CONDITIONS 59
5.1.5 TEST RESULTS 60
6 . 6DB&26DB&99% BANDWIDTH TEST 69

Table of Contents **Page**

6.1 APPLIED PROCEDURES / LIMIT 69
6.1.1 TEST PROCEDURE 69
6.1.2 DEVIATION FROM STANDARD 69
6.1.3 TEST SETUP 69
6.1.4 EUT OPERATION CONDITIONS 70
6.1.5 TEST RESULTS 70
7 . DUTY CYCLE TEST SIGNAL 79
7.1 APPLIED PROCEDURES / LIMIT 79
7.1.1 TEST PROCEDURE 79
7.1.2 DEVIATION FROM STANDARD 79
7.1.3 TEST SETUP 79
7.1.4 EUT OPERATION CONDITIONS 79
7.1.5 TEST RESULTS 80
8 . FREQUENCY STABILITY 89
8.1 APPLIED PROCEDURES / LIMIT 89
8.1.1 TEST PROCEDURE 89
8.1.2 DEVIATION FROM STANDARD 89
8.1.3 TEST SETUP 89
8.1.4 EUT OPERATION CONDITIONS 89
8.1.5 TEST RESULTS 90
9 . TRANSMISSION IN THE ABSENCE OF DATA 94
9.1 STANDARD REQUIREMENT 94
9.2 TEST RESULT 94
10 . ANTENNA REQUIREMENT 94
10.1 STANDARD REQUIREMENT 94
10.2 EUT ANTENNA 94
11 . TEST SEUUP PHOTO 94
12 . EUT PHOTO 94

1.. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	
15.407(b), 15.209	Radiated Spurious Emission	PASS	
15.407 (b)	Band Edge Emission	PASS	
15.407 (a)	Averaging Output Power	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.407(a) (e)	26dB bandwidth and 99%dB Bandwidth 6dB bandwidth and 99%dB Bandwidth	PASS	
15.407(g)	Frequency Stability	PASS	
15.407(c)	Transmission in case of Absence of Information	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

Test lab: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

FCC Test Firm Registration Number: 854456
Designation Number: CN1307
IC Registered No.: 27485
CAB ID.: CN0118

1.1. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y** ± **U**, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**，providing a level of confidence of approximately **95** %。

No.	Item	Uncertainty
1	Conducted Emission Test	±2.56dB
2	RF power,conducted	±0.42dB
3	Spurious emissions,conducted	±2.76dB
4	All emissions,radiated(<30MHz)	±3.54dB
5	All emissions,radiated(<1G)	±3.65dB
6	All emissions,radiated(>1G)	±4.89dB
7	Occupied bandwidth	±1.28MHz
8	PSD	±0.69dB
9	Temperature	±0.5°C
10	Humidity	±2%

2.. GENERAL INFORMATION

2.1. GENERAL DESCRIPTION OF EUT

Product Name:	network card
Trademark	N/A
Model No.:	TD8800M80 TD8912
Model Difference	All models are same as the samples except model name and appearance color, they have the same structure and circuit.
Operation Frequency:	IEEE 802.11a/n(HT20)/ac/ax(HT20): 5180-5240, 5745-5825MHz IEEE 802.11n(HT40)/ac/ax(HT40): 5190-5230, 5755-5795MHz
Channel numbers:	See channel list
Channel separation:	20MHz/40MHz
Modulation technology:	802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM): BPSK,QPSK,16-QAM,64-QAM,256-QAM 802.11ax(OFDMA):BPSK,QPSK,16-QAM,64-QAM,256-QAM, 1024-QAM
Rate of Transmitter	802.11a: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps,54Mbps 802.11n/ac/ax: Up to 500Mbps
Antenna Type:	Internal Antenna
Antenna gain:	3.16dBi
Power Supply:	DC 5V

Note:

1.For a more detailed features description, please refer to the manufacturer’s specifications or the User's Manual.

2.The EUT’s all information provided by client.

3.802.11ax supports only full RU mode.

2. Channel List

Channel List for 802.11 a/n(HT20)/ac/ax(HT20)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
40	5200	48	5240

Channel List for 802.11 n(HT40)/ac/ax(HT40)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	46	5230

Channel List for 802.11 a/n(HT20)/ac/ax(HT20)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	161	5805
153	5765	165	5825
157	5785		

Channel List for 802.11 n(HT40)/ac/ax(HT40)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795

2.2. DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Description			
Pretest Mode	Channel	Band 1	Band 4
Mode 1	802.11a/n(HT20)/ac/ax(HT20)	CH36, CH44, CH48	CH149, CH157, CH165
Mode 2	802.11n(HT40)/ac/ax(HT40)	CH38, CH46	CH151, CH159
Mode 3	Link Mode		

For Radiated Emission			
Pretest Mode	Channel	Band 1	Band 4
Mode 1	802.11a/n(HT20)/ac/ax(HT20)	CH36, CH44, CH48	CH149, CH157, CH165
Mode 2	802.11n(HT40)/ac/ax(HT40)	CH38, CH46	CH151, CH159
Mode 3	Link Mode		

Note: 1. The measurements are performed at the highest, middle, lowest available channels.
2. During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

2.3. BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



2.4. DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	network card	TD8800M80	N/A	EUT
E-2	Notebook	310S-14AST	N/A	Notebook (Provide by test lab): Manufacturer: LENOVO Model: 310S-14AST I/P: AC 100-240V 50/60Hz

Item	Shielded Type	Ferrite Core	Length	Note

Note:

(1) For detachable type I/O cable should be specified the length in cm in『Length』column.

2.5. TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Max output power Setting				
Test software Version	Test program: sscom5.13.1			
Mode	802.11a	802.11n HT20	802.11n HT40	802.11ac/ax HT20/HT40
Data Rate	6Mbps	MSC0	MSC0	MSC0
Power Setting of Softwave	60	60	66	66

2.6. EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 01, 2024	Oct. 31, 2025
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 01, 2024	Oct. 31, 2025
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 01, 2024	Oct. 31, 2025
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 01, 2024	Oct. 31, 2025
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 01, 2024	Oct. 31, 2025
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 01, 2024	Oct. 31, 2025
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 01, 2024	Oct. 31, 2025
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 01, 2024	Oct. 31, 2025
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 01, 2024	Oct. 31, 2025
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 01, 2024	Oct. 31, 2025
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 01, 2024	Oct. 31, 2025
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 01, 2024	Oct. 31, 2025
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 01, 2024	Oct. 31, 2025
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 01, 2024	Oct. 31, 2025
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 01, 2024	Oct. 31, 2025
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 01, 2024	Oct. 31, 2025

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	YIHENG	843 Room	843	Nov. 05, 2023	Nov. 04, 2026
2	EMI Receiver	R&S	ESR	101421	Nov. 01, 2024	Oct. 31, 2025
3	LISN	R&S	ENV216	102417	Nov. 01, 2024	Oct. 31, 2025
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 01, 2024	Oct. 31, 2025

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0

3.. EMC EMISSION TEST

3.1. CONDUCTED EMISSION MEASUREMENT

3.1.1. POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.5 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2. TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

d. LISN at least 80 cm from nearest part of EUT chassis.

e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3. DEVIATION FROM TEST STANDARD

No deviation

3.1.4. TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5. EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.6. TEST RESULTS

The EUT is powered by DC, no requirements for this item.

3.2. RADIATED EMISSION MEASUREMENT

3.2.1. RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

15.407(b)Undesirable emission limits. Except as shown in paragraph (b) (10) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1)For transmitters operating in the 5.15-5.25GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2)For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3)For transmitters operating in the 5.47-5.725GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4)For transmitters operating solely in the 5.725-5.850GHz band:
All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to10dBm/MHzat25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2. TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre.
h. Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3. DEVIATION FROM TEST STANDARD

No deviation

3.2.4. TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



3.2.5. EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6. TEST RESULTS (Between 9KHz – 30 MHz)

Temperature:	20℃	Relative Humidtity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V
Test Mode :	Mode 4	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.

3.2.7. TEST RESULTS (Between 30MHz – 1GHz)

Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	DC 5V		
Test Mode :	Mode 4		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin	
		MHz	dBuV	dB	dBuV	dB	dB	Detector
1		44.7433	28.70	-13.18	15.52	40.00	-24.48	QP
2		102.7192	28.17	-14.86	13.31	43.50	-30.19	QP
3		278.0668	34.81	-12.40	22.41	46.00	-23.59	QP
4		334.8586	37.31	-11.20	26.11	46.00	-19.89	QP
5		839.1816	31.94	-1.84	30.10	46.00	-15.90	QP
6	*	948.7608	31.78	-0.27	31.51	46.00	-14.49	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;

Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
test voltage :	DC 5V		
Test Mode :	Mode 4		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin	
		MHz	dBuV	dB	dBuV	dB	dB	Detector
1		43.6584	29.92	-13.29	16.63	40.00	-23.37	QP
2		105.2716	29.15	-14.67	14.48	43.50	-29.02	QP
3		213.0149	30.52	-14.35	16.17	43.50	-27.33	QP
4		364.2595	30.43	-10.28	20.15	46.00	-25.85	QP
5		554.8251	33.10	-6.02	27.08	46.00	-18.92	QP
6	*	948.7608	30.00	-0.27	29.73	46.00	-16.27	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;

3.2.8. TEST RESULTS (1ghz~40ghZ)

802.11a band 1

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5180									
V	10360	56.25	49.05	15.3	37.39	59.89	74	-14.11	PK
V	10360	41.16	49.05	15.3	37.39	44.8	54	-9.20	AV
V	15540	52.41	49.16	15.27	40.45	58.97	68.2	-9.23	PK
V	15540	39.95	49.16	15.27	40.45	46.51	54	-7.49	AV
H	10360	56.52	49.05	15.3	37.39	60.16	74	-13.84	PK
H	10360	40.23	49.05	15.3	37.39	43.87	54	-10.13	AV
H	15540	51.38	49.16	15.27	40.45	57.94	68.2	-10.26	PK
H	15540	38.94	49.16	15.27	40.45	45.5	54	-8.50	AV
operation frequency:5200									
V	10400	57.63	49.09	15.34	37.42	61.3	74	-12.70	PK
V	10400	39.48	49.09	15.34	37.42	43.15	54	-10.85	AV
V	15600	52.83	49.18	15.29	40.47	59.41	68.2	-8.79	PK
V	15600	38.17	49.18	15.29	40.47	44.75	54	-9.25	AV
H	10400	56.26	49.09	15.34	37.42	59.93	74	-14.07	PK
H	10400	39.85	49.09	15.34	37.42	43.52	54	-10.48	AV
H	15600	53.36	49.18	15.29	40.47	59.94	68.2	-8.26	PK
H	15600	38.41	49.18	15.29	40.47	44.99	54	-9.01	AV
operation frequency:5240									
V	10480	58.63	49.11	15.37	37.46	62.35	74	-11.65	PK
V	10480	39.28	49.11	15.37	37.46	43	54	-11.00	AV
V	15720	53.92	49.21	15.34	40.51	60.56	68.2	-7.64	PK
V	15720	38.33	49.21	15.34	40.51	44.97	54	-9.03	AV
H	10480	57.85	49.11	15.37	31.31	55.42	74	-18.58	PK
H	10480	45.76	49.11	15.37	31.31	43.33	54	-10.67	AV
H	15720	54.18	49.21	15.34	40.51	60.82	68.2	-7.38	PK
H	15720	37.14	49.21	15.34	40.51	43.78	54	-10.22	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5180									
V	10360	56.25	49.05	15.3	37.39	59.89	74	-14.11	PK
V	10360	38.14	49.05	15.3	37.39	41.78	54	-12.22	AV
V	15540	52.63	49.16	15.27	40.45	59.19	68.2	-9.01	PK
V	15540	38.25	49.16	15.27	40.45	44.81	54	-9.19	AV
H	10360	56.63	49.05	15.3	37.39	60.27	74	-13.73	PK
H	10360	39.88	49.05	15.3	37.39	43.52	54	-10.48	AV
H	15540	51.94	49.16	15.27	40.45	58.5	68.2	-9.70	PK
H	15540	38.93	49.16	15.27	40.45	45.49	54	-8.51	AV
operation frequency:5200									
V	10400	56.35	49.09	15.34	37.42	60.02	74	-13.98	PK
V	10400	39.66	49.09	15.34	37.42	43.33	54	-10.67	AV
V	15600	52.58	49.18	15.29	40.47	59.16	68.2	-9.04	PK
V	15600	38.94	49.18	15.29	40.47	45.52	54	-8.48	AV
H	10400	55.57	49.09	15.34	37.42	59.24	74	-14.76	PK
H	10400	40.63	49.09	15.34	37.42	44.3	54	-9.70	AV
H	15600	53.54	49.18	15.29	40.47	60.12	68.2	-8.08	PK
H	15600	39.58	49.18	15.29	40.47	46.16	54	-7.84	AV
operation frequency:5240									
V	10480	57.63	49.11	15.37	37.46	61.35	74	-12.65	PK
V	10480	40.14	49.11	15.37	37.46	43.86	54	-10.14	AV
V	15720	52.36	49.21	15.34	40.51	59	68.2	-9.20	PK
V	15720	38.85	49.21	15.34	40.51	45.49	54	-8.51	AV
H	10480	57.22	49.11	15.37	31.31	54.79	74	-19.21	PK
H	10480	44.96	49.11	15.37	31.31	42.53	54	-11.47	AV
H	15720	51.16	49.21	15.34	40.51	57.8	68.2	-10.40	PK
H	15720	39.25	49.21	15.34	40.51	45.89	54	-8.11	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n HT40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5190									
V	10380	56.63	49.07	15.33	37.41	60.3	74	-13.70	PK
V	10380	39.52	49.07	15.33	37.41	43.19	54	-10.81	AV
V	15570	52.33	49.17	15.28	40.46	58.9	68.2	-9.30	PK
V	15570	38.68	49.17	15.28	40.46	45.25	54	-8.75	AV
H	10380	56.26	49.07	15.33	37.41	59.93	74	-14.07	PK
H	10380	40.41	49.07	15.33	37.41	44.08	54	-9.92	AV
H	15570	52.36	49.17	15.28	40.46	58.93	68.2	-9.27	PK
H	15570	38.27	49.17	15.28	40.46	44.84	54	-9.16	AV
operation frequency:5230									
V	10460	57.63	49.11	15.37	37.46	61.35	74	-12.65	PK
V	10460	39.54	49.11	15.37	37.46	43.26	54	-10.74	AV
V	15690	52.17	49.21	15.34	40.51	58.81	68.2	-9.39	PK
V	15690	38.24	49.21	15.34	40.51	44.88	54	-9.12	AV
H	10460	57.84	49.11	15.37	31.31	55.41	74	-18.59	PK
H	10460	44.63	49.11	15.37	31.31	42.2	54	-11.80	AV
H	15690	52.85	49.21	15.34	40.51	59.49	68.2	-8.71	PK
H	15690	39.11	49.21	15.34	40.51	45.75	54	-8.25	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ac HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5180									
V	10360	56.63	49.05	15.3	37.39	60.27	74	-13.73	PK
V	10360	39.17	49.05	15.3	37.39	42.81	54	-11.19	AV
V	15540	51.85	49.16	15.27	40.45	58.41	68.2	-9.79	PK
V	15540	38.36	49.16	15.27	40.45	44.92	54	-9.08	AV
H	10360	56.68	49.05	15.3	37.39	60.32	74	-13.68	PK
H	10360	38.33	49.05	15.3	37.39	41.97	54	-12.03	AV
H	15540	52.38	49.16	15.27	40.45	58.94	68.2	-9.26	PK
H	15540	39.41	49.16	15.27	40.45	45.97	54	-8.03	AV
operation frequency:5200									
V	10400	56.36	49.09	15.34	37.42	60.03	74	-13.97	PK
V	10400	41.58	49.09	15.34	37.42	45.25	54	-8.75	AV
V	15600	52.96	49.18	15.29	40.47	59.54	68.2	-8.66	PK
V	15600	40.54	49.18	15.29	40.47	47.12	54	-6.88	AV
H	10400	55.98	49.09	15.34	37.42	59.65	74	-14.35	PK
H	10400	40.56	49.09	15.34	37.42	44.23	54	-9.77	AV
H	15600	53.74	49.18	15.29	40.47	60.32	68.2	-7.88	PK
H	15600	41.26	49.18	15.29	40.47	47.84	54	-6.16	AV
operation frequency:5240									
V	10480	57.27	49.11	15.37	37.46	60.99	74	-13.01	PK
V	10480	40.63	49.11	15.37	37.46	44.35	54	-9.65	AV
V	15720	51.48	49.21	15.34	40.51	58.12	68.2	-10.08	PK
V	15720	39.65	49.21	15.34	40.51	46.29	54	-7.71	AV
H	10480	57.63	49.11	15.37	31.31	55.2	74	-18.80	PK
H	10480	44.24	49.11	15.37	31.31	41.81	54	-12.19	AV
H	15720	52.82	49.21	15.34	40.51	59.46	68.2	-8.74	PK
H	15720	40.66	49.21	15.34	40.51	47.3	54	-6.70	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ac HT40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5190									
V	10380	56.38	49.07	15.33	37.41	60.05	74	-13.95	PK
V	10380	40.43	49.07	15.33	37.41	44.1	54	-9.90	AV
V	15570	52.75	49.17	15.28	40.46	59.32	68.2	-8.88	PK
V	15570	39.85	49.17	15.28	40.46	46.42	54	-7.58	AV
H	10380	56.36	49.07	15.33	37.41	60.03	74	-13.97	PK
H	10380	40.54	49.07	15.33	37.41	44.21	54	-9.79	AV
H	15570	51.43	49.17	15.28	40.46	58	68.2	-10.20	PK
H	15570	39.17	49.17	15.28	40.46	45.74	54	-8.26	AV
operation frequency:5230									
V	10460	57.63	49.11	15.37	37.46	61.35	74	-12.65	PK
V	10460	41.52	49.11	15.37	37.46	45.24	54	-8.76	AV
V	15690	52.14	49.21	15.34	40.51	58.78	68.2	-9.42	PK
V	15690	39.26	49.21	15.34	40.51	45.9	54	-8.10	AV
H	10460	57.92	49.11	15.37	31.31	55.49	74	-18.51	PK
H	10460	44.46	49.11	15.37	31.31	42.03	54	-11.97	AV
H	15690	52.37	49.21	15.34	40.51	59.01	68.2	-9.19	PK
H	15690	40.52	49.21	15.34	40.51	47.16	54	-6.84	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ax HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5180									
V	10360	56.33	49.05	15.3	37.39	59.97	74	-14.03	PK
V	10360	39.18	49.05	15.3	37.39	42.82	54	-11.18	AV
V	15540	51.82	49.16	15.27	40.45	58.38	68.2	-9.82	PK
V	15540	38.34	49.16	15.27	40.45	44.9	54	-9.10	AV
H	10360	56.63	49.05	15.3	37.39	60.27	74	-13.73	PK
H	10360	38.35	49.05	15.3	37.39	41.99	54	-12.01	AV
H	15540	52.32	49.16	15.27	40.45	58.88	68.2	-9.32	PK
H	15540	39.63	49.16	15.27	40.45	46.19	54	-7.81	AV
operation frequency:5200									
V	10400	56.34	49.09	15.34	37.42	60.01	74	-13.99	PK
V	10400	41.57	49.09	15.34	37.42	45.24	54	-8.76	AV
V	15600	52.93	49.18	15.29	40.47	59.51	68.2	-8.69	PK
V	15600	40.55	49.18	15.29	40.47	47.13	54	-6.87	AV
H	10400	55.93	49.09	15.34	37.42	59.6	74	-14.40	PK
H	10400	40.55	49.09	15.34	37.42	44.22	54	-9.78	AV
H	15600	53.86	49.18	15.29	40.47	60.44	68.2	-7.76	PK
H	15600	41.27	49.18	15.29	40.47	47.85	54	-6.15	AV
operation frequency:5240									
V	10480	57.26	49.11	15.37	37.46	60.98	74	-13.02	PK
V	10480	40.54	49.11	15.37	37.46	44.26	54	-9.74	AV
V	15720	51.47	49.21	15.34	40.51	58.11	68.2	-10.09	PK
V	15720	39.63	49.21	15.34	40.51	46.27	54	-7.73	AV
H	10480	57.41	49.11	15.37	31.31	54.98	74	-19.02	PK
H	10480	44.23	49.11	15.37	31.31	41.8	54	-12.20	AV
H	15720	52.88	49.21	15.34	40.51	59.52	68.2	-8.68	PK
H	15720	40.62	49.21	15.34	40.51	47.26	54	-6.74	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ax HT40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5190									
V	10380	56.33	49.07	15.33	37.41	60	74	-14.00	PK
V	10380	40.48	49.07	15.33	37.41	44.15	54	-9.85	AV
V	15570	52.74	49.17	15.28	40.46	59.31	68.2	-8.89	PK
V	15570	39.62	49.17	15.28	40.46	46.19	54	-7.81	AV
H	10380	56.66	49.07	15.33	37.41	60.33	74	-13.67	PK
H	10380	40.84	49.07	15.33	37.41	44.51	54	-9.49	AV
H	15570	51.47	49.17	15.28	40.46	58.04	68.2	-10.16	PK
H	15570	39.16	49.17	15.28	40.46	45.73	54	-8.27	AV
operation frequency:5230									
V	10460	57.32	49.11	15.37	37.46	61.04	74	-12.96	PK
V	10460	41.56	49.11	15.37	37.46	45.28	54	-8.72	AV
V	15690	52.52	49.21	15.34	40.51	59.16	68.2	-9.04	PK
V	15690	39.21	49.21	15.34	40.51	45.85	54	-8.15	AV
H	10460	57.99	49.11	15.37	31.31	55.56	74	-18.44	PK
H	10460	44.41	49.11	15.37	31.31	41.98	54	-12.02	AV
H	15690	52.33	49.21	15.34	40.51	58.97	68.2	-9.23	PK
H	15690	40.17	49.21	15.34	40.51	46.81	54	-7.19	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11a band 4

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5745									
V	11490	54.25	49.05	15.3	37.39	57.89	74	-16.11	PK
V	11490	41.16	49.05	15.3	37.39	44.8	54	-9.20	AV
V	17235	55.58	49.16	15.27	40.45	62.14	68.2	-6.06	PK
V	17235	40.31	49.16	15.27	40.45	46.87	54	-7.13	AV
H	11490	52.66	49.05	15.3	37.39	56.3	74	-17.70	PK
H	11490	42.85	49.05	15.3	37.39	46.49	54	-7.51	AV
H	17235	51.83	49.16	15.27	40.45	58.39	68.2	-9.81	PK
H	17235	40.64	49.16	15.27	40.45	47.2	54	-6.80	AV
operation frequency:5785									
V	11570	51.21	49.09	15.34	37.42	54.88	74	-19.12	PK
V	11570	41.69	49.09	15.34	37.42	45.36	54	-8.64	AV
V	17355	50.55	49.18	15.29	40.47	57.13	68.2	-11.07	PK
V	17355	40.63	49.18	15.29	40.47	47.21	54	-6.79	AV
H	11570	50.72	49.09	15.34	37.42	54.39	74	-19.61	PK
H	11570	42.64	49.09	15.34	37.42	46.31	54	-7.69	AV
H	17355	48.18	49.18	15.29	40.47	54.76	68.2	-13.44	PK
H	17355	40.86	49.18	15.29	40.47	47.44	54	-6.56	AV
operation frequency:5825									
V	11650	52.21	49.11	15.37	37.46	55.93	74	-18.07	PK
V	11650	41.23	49.11	15.37	37.46	44.95	54	-9.05	AV
V	17475	49.58	49.21	15.34	40.51	56.22	68.2	-11.98	PK
V	17475	40.26	49.21	15.34	40.51	46.9	54	-7.10	AV
H	11650	57.58	49.11	15.37	31.31	55.15	74	-18.85	PK
H	11650	48.76	49.11	15.37	31.31	46.33	54	-7.67	AV
H	17475	49.34	49.21	15.34	40.51	55.98	68.2	-12.22	PK
H	17475	40.74	49.21	15.34	40.51	47.38	54	-6.62	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5745									
V	11490	49.56	49.05	15.3	37.39	53.2	74	-20.80	PK
V	11490	42.17	49.05	15.3	37.39	45.81	54	-8.19	AV
V	17235	48.21	49.16	15.27	40.45	54.77	68.2	-13.43	PK
V	17235	40.65	49.16	15.27	40.45	47.21	54	-6.79	AV
H	11490	49.25	49.05	15.3	37.39	52.89	74	-21.11	PK
H	11490	41.34	49.05	15.3	37.39	44.98	54	-9.02	AV
H	17235	48.17	49.16	15.27	40.45	54.73	68.2	-13.47	PK
H	17235	40.66	49.16	15.27	40.45	47.22	54	-6.78	AV
operation frequency:5785									
V	11570	52.21	49.09	15.34	37.42	55.88	74	-18.12	PK
V	11570	42.63	49.09	15.34	37.42	46.3	54	-7.70	AV
V	17355	49.85	49.18	15.29	40.47	56.43	68.2	-11.77	PK
V	17355	40.16	49.18	15.29	40.47	46.74	54	-7.26	AV
H	11570	49.28	49.09	15.34	37.42	52.95	74	-21.05	PK
H	11570	43.84	49.09	15.34	37.42	47.51	54	-6.49	AV
H	17355	49.63	49.18	15.29	40.47	56.21	68.2	-11.99	PK
H	17355	40.74	49.18	15.29	40.47	47.32	54	-6.68	AV
operation frequency:5825									
V	11650	51.63	49.11	15.37	37.46	55.35	74	-18.65	PK
V	11650	41.52	49.11	15.37	37.46	45.24	54	-8.76	AV
V	17475	48.63	49.21	15.34	40.51	55.27	68.2	-12.93	PK
V	17475	40.31	49.21	15.34	40.51	46.95	54	-7.05	AV
H	11650	57.68	49.11	15.37	31.31	55.25	74	-18.75	PK
H	11650	44.14	49.11	15.37	31.31	41.71	54	-12.29	AV
H	17475	49.72	49.21	15.34	40.51	56.36	68.2	-11.84	PK
H	17475	40.36	49.21	15.34	40.51	47	54	-7.00	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n HT40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5755									
V	11510	49.63	49.07	15.33	37.41	53.3	74	-20.70	PK
V	11510	41.31	49.07	15.33	37.41	44.98	54	-9.02	AV
V	17265	49.77	49.17	15.28	40.46	56.34	68.2	-11.86	PK
V	17265	40.61	49.17	15.28	40.46	47.18	54	-6.82	AV
H	11510	48.23	49.07	15.33	37.41	51.9	74	-22.10	PK
H	11510	41.18	49.07	15.33	37.41	44.85	54	-9.15	AV
H	17265	49.34	49.17	15.28	40.46	55.91	68.2	-12.29	PK
H	17265	40.39	49.17	15.28	40.46	46.96	54	-7.04	AV
operation frequency:5795									
V	11590	49.24	49.11	15.37	37.46	52.96	74	-21.04	PK
V	11590	41.46	49.11	15.37	37.46	45.18	54	-8.82	AV
V	17385	48.28	49.21	15.34	40.51	54.92	68.2	-13.28	PK
V	17385	40.73	49.21	15.34	40.51	47.37	54	-6.63	AV
H	11590	57.88	49.11	15.37	31.31	55.45	74	-18.55	PK
H	11590	44.32	49.11	15.37	31.31	41.89	54	-12.11	AV
H	17385	48.62	49.21	15.34	40.51	55.26	68.2	-12.94	PK
H	17385	40.61	49.21	15.34	40.51	47.25	54	-6.75	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ac HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5745									
V	11490	49.16	49.05	15.3	37.39	52.8	74	-21.20	PK
V	11490	42.57	49.05	15.3	37.39	46.21	54	-7.79	AV
V	17235	48.82	49.16	15.27	40.45	55.38	68.2	-12.82	PK
V	17235	40.33	49.16	15.27	40.45	46.89	54	-7.11	AV
H	11490	48.28	49.05	15.3	37.39	51.92	74	-22.08	PK
H	11490	41.51	49.05	15.3	37.39	45.15	54	-8.85	AV
H	17235	48.46	49.16	15.27	40.45	55.02	68.2	-13.18	PK
H	17235	40.85	49.16	15.27	40.45	47.41	54	-6.59	AV
operation frequency:5785									
V	11570	48.21	49.09	15.34	37.42	51.88	74	-22.12	PK
V	11570	41.43	49.09	15.34	37.42	45.1	54	-8.90	AV
V	17355	49.57	49.18	15.29	40.47	56.15	68.2	-12.05	PK
V	17355	40.62	49.18	15.29	40.47	47.2	54	-6.80	AV
H	11570	49.36	49.09	15.34	37.42	53.03	74	-20.97	PK
H	11570	43.85	49.09	15.34	37.42	47.52	54	-6.48	AV
H	17355	49.66	49.18	15.29	40.47	56.24	68.2	-11.96	PK
H	17355	40.82	49.18	15.29	40.47	47.4	54	-6.60	AV
operation frequency:5825									
V	11650	49.36	49.11	15.37	37.46	53.08	74	-20.92	PK
V	11650	41.68	49.11	15.37	37.46	45.4	54	-8.60	AV
V	17475	48.33	49.21	15.34	40.51	54.97	68.2	-13.23	PK
V	17475	40.21	49.21	15.34	40.51	46.85	54	-7.15	AV
H	11650	57.19	49.11	15.37	31.31	54.76	74	-19.24	PK
H	11650	44.64	49.11	15.37	31.31	42.21	54	-11.79	AV
H	17475	48.66	49.21	15.34	40.51	55.3	68.2	-12.90	PK
H	17475	40.47	49.21	15.34	40.51	47.11	54	-6.89	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ac HT40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5755									
V	11510	49.63	49.07	15.33	37.41	53.3	74	-20.70	PK
V	11510	42.54	49.07	15.33	37.41	46.21	54	-7.79	AV
V	17265	48.27	49.17	15.28	40.46	54.84	68.2	-13.36	PK
V	17265	41.66	49.17	15.28	40.46	48.23	54	-5.77	AV
H	11510	48.82	49.07	15.33	37.41	52.49	74	-21.51	PK
H	11510	42.16	49.07	15.33	37.41	45.83	54	-8.17	AV
H	17265	48.18	49.17	15.28	40.46	54.75	68.2	-13.45	PK
H	17265	40.36	49.17	15.28	40.46	46.93	54	-7.07	AV
operation frequency:5795									
V	11590	49.21	49.11	15.37	37.46	52.93	74	-21.07	PK
V	11590	41.23	49.11	15.37	37.46	44.95	54	-9.05	AV
V	17385	48.77	49.21	15.34	40.51	55.41	68.2	-12.79	PK
V	17385	40.16	49.21	15.34	40.51	46.8	54	-7.20	AV
H	11590	57.52	49.11	15.37	31.31	55.09	74	-18.91	PK
H	11590	44.66	49.11	15.37	31.31	42.23	54	-11.77	AV
H	17385	48.24	49.21	15.34	40.51	54.88	68.2	-13.32	PK
H	17385	40.18	49.21	15.34	40.51	46.82	54	-7.18	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ax HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5745									
V	11490	49.16	49.05	15.3	37.39	52.8	74	-21.20	PK
V	11490	42.54	49.05	15.3	37.39	46.18	54	-7.82	AV
V	17235	48.85	49.16	15.27	40.45	55.41	68.2	-12.79	PK
V	17235	40.35	49.16	15.27	40.45	46.91	54	-7.09	AV
H	11490	48.28	49.05	15.3	37.39	51.92	74	-22.08	PK
H	11490	41.55	49.05	15.3	37.39	45.19	54	-8.81	AV
H	17235	48.82	49.16	15.27	40.45	55.38	68.2	-12.82	PK
H	17235	40.66	49.16	15.27	40.45	47.22	54	-6.78	AV
operation frequency:5785									
V	11570	48.54	49.09	15.34	37.42	52.21	74	-21.79	PK
V	11570	41.49	49.09	15.34	37.42	45.16	54	-8.84	AV
V	17355	49.52	49.18	15.29	40.47	56.1	68.2	-12.10	PK
V	17355	40.64	49.18	15.29	40.47	47.22	54	-6.78	AV
H	11570	49.36	49.09	15.34	37.42	53.03	74	-20.97	PK
H	11570	43.38	49.09	15.34	37.42	47.05	54	-6.95	AV
H	17355	49.83	49.18	15.29	40.47	56.41	68.2	-11.79	PK
H	17355	40.74	49.18	15.29	40.47	47.32	54	-6.68	AV
operation frequency:5825									
V	11650	49.36	49.11	15.37	37.46	53.08	74	-20.92	PK
V	11650	41.92	49.11	15.37	37.46	45.64	54	-8.36	AV
V	17475	48.34	49.21	15.34	40.51	54.98	68.2	-13.22	PK
V	17475	40.18	49.21	15.34	40.51	46.82	54	-7.18	AV
H	11650	57.16	49.11	15.37	31.31	54.73	74	-19.27	PK
H	11650	44.62	49.11	15.37	31.31	42.19	54	-11.81	AV
H	17475	48.66	49.21	15.34	40.51	55.3	68.2	-12.90	PK
H	17475	40.41	49.21	15.34	40.51	47.05	54	-6.95	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ax HT40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5755									
V	11510	49.63	49.07	15.33	37.41	53.3	74	-20.70	PK
V	11510	42.57	49.07	15.33	37.41	46.24	54	-7.76	AV
V	17265	48.21	49.17	15.28	40.46	54.78	68.2	-13.42	PK
V	17265	41.66	49.17	15.28	40.46	48.23	54	-5.77	AV
H	11510	48.64	49.07	15.33	37.41	52.31	74	-21.69	PK
H	11510	42.18	49.07	15.33	37.41	45.85	54	-8.15	AV
H	17265	48.16	49.17	15.28	40.46	54.73	68.2	-13.47	PK
H	17265	40.38	49.17	15.28	40.46	46.95	54	-7.05	AV
operation frequency:5795									
V	11590	49.69	49.11	15.37	37.46	53.41	74	-20.59	PK
V	11590	41.21	49.11	15.37	37.46	44.93	54	-9.07	AV
V	17385	48.73	49.21	15.34	40.51	55.37	68.2	-12.83	PK
V	17385	40.48	49.21	15.34	40.51	47.12	54	-6.88	AV
H	11590	57.24	49.11	15.37	31.31	54.81	74	-19.19	PK
H	11590	44.66	49.11	15.37	31.31	42.23	54	-11.77	AV
H	17385	48.21	49.21	15.34	40.51	54.85	68.2	-13.35	PK
H	17385	40.16	49.21	15.34	40.51	46.8	54	-7.20	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

15.407 (b)

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	5000MHz
Stop Frequency	5420MHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULT

802.11a

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5180									
V	5150	53.24	49.12	15.6	37.34	57.06	74	-16.94	PK
V	5150	39.96	49.12	15.6	37.34	43.78	54	-10.22	AV
V	5145	54.37	49.19	15.24	40.43	60.85	74	-13.15	PK
V	5145	36.85	49.19	15.24	40.43	43.33	54	-10.67	AV
H	5150	52.52	49.12	15.6	37.34	56.34	74	-17.66	PK
H	5150	37.59	49.12	15.6	37.34	41.41	54	-12.59	AV
H	5145	54.52	49.19	15.24	40.43	61	74	-13	PK
H	5145	33.64	49.19	15.24	40.43	40.12	54	-13.88	AV
operation frequency:5240									
V	5350	53.13	49.13	15.32	37.46	56.78	74	-17.22	PK
V	5350	35.28	49.13	15.32	37.46	38.93	54	-15.07	AV
V	5370	53.16	49.24	15.36	40.51	59.79	74	-14.21	PK
V	5370	32.65	49.24	15.36	40.51	39.28	54	-14.72	AV
H	5350	52.66	49.13	15.32	31.31	50.16	74	-23.84	PK
H	5350	40.71	49.13	15.32	31.31	38.21	54	-15.79	AV
H	5370	52.48	49.24	15.36	40.51	59.11	74	-14.89	PK
H	5370	32.83	49.24	15.36	40.51	39.46	54	-14.54	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5180									
V	5150	51.21	49.12	15.6	37.34	55.03	74	-18.97	PK
V	5150	33.36	49.12	15.6	37.34	37.18	54	-16.82	AV
V	5145	51.85	49.19	15.24	40.43	58.33	74	-15.67	PK
V	5145	33.67	49.19	15.24	40.43	40.15	54	-13.85	AV
H	5150	51.21	49.12	15.6	37.34	55.03	74	-18.97	PK
H	5150	33.36	49.12	15.6	37.34	37.18	54	-16.82	AV
H	5145	50.37	49.19	15.24	40.43	56.85	74	-17.15	PK
H	5145	32.21	49.19	15.24	40.43	38.69	54	-15.31	AV
operation frequency:5240									
V	5350	53.63	49.13	15.32	37.46	57.28	74	-16.72	PK
V	5350	34.75	49.13	15.32	37.46	38.4	54	-15.6	AV
V	5370	50.88	49.24	15.36	40.51	57.51	74	-16.49	PK
V	5370	33.36	49.24	15.36	40.51	39.99	54	-14.01	AV
H	5350	54.27	49.13	15.32	31.31	51.77	74	-22.23	PK
H	5350	36.65	49.13	15.32	31.31	34.15	54	-19.85	AV
H	5370	51.32	49.24	15.36	40.51	57.95	74	-16.05	PK
H	5370	33.87	49.24	15.36	40.51	40.5	54	-13.5	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ac HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5180									
V	5150	52.36	49.12	15.33	37.41	55.98	74	-18.02	PK
V	5150	34.55	49.12	15.33	37.41	38.17	54	-15.83	AV
V	5145	51.85	49.19	15.28	40.46	58.4	74	-15.6	PK
V	5145	33.86	49.19	15.28	40.46	40.41	54	-13.59	AV
H	5150	52.14	49.12	15.33	37.41	55.76	74	-18.24	PK
H	5150	34.87	49.12	15.33	37.41	38.49	54	-15.51	AV
H	5145	50.56	49.19	15.28	40.46	57.11	74	-16.89	PK
H	5145	33.35	49.19	15.28	40.46	39.9	54	-14.1	AV
operation frequency:5240									
V	5350	53.21	49.13	15.32	37.46	56.86	74	-17.14	PK
V	5350	36.16	49.13	15.32	37.46	39.81	54	-14.19	AV
V	5370	50.18	49.24	15.36	40.51	56.81	74	-17.19	PK
V	5370	33.64	49.24	15.36	40.51	40.27	54	-13.73	AV
H	5350	53.76	49.13	15.32	31.31	51.26	74	-22.74	PK
H	5350	40.85	49.13	15.32	31.31	38.35	54	-15.65	AV
H	5370	51.13	49.24	15.36	40.51	57.76	74	-16.24	PK
H	5370	35.44	49.24	15.36	40.51	42.07	54	-11.93	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n HT40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5190									
V	5150	52.36	49.12	15.6	37.39	56.23	74	-17.77	PK
V	5150	35.52	49.12	15.6	37.39	39.39	54	-14.61	AV
V	5145	51.64	49.19	15.24	40.45	58.14	74	-15.86	PK
V	5145	34.69	49.19	15.24	40.45	41.19	54	-12.81	AV
H	5150	52.55	49.12	15.6	37.39	56.42	74	-17.58	PK
H	5150	34.66	49.12	15.6	37.39	38.53	54	-15.47	AV
H	5145	50.28	49.19	15.24	40.45	56.78	74	-17.22	PK
H	5145	35.23	49.19	15.24	40.45	41.73	54	-12.27	AV
operation frequency:5230									
V	5350	53.87	49.13	15.34	37.46	57.54	74	-16.46	PK
V	5350	37.35	49.13	15.34	37.46	41.02	54	-12.98	AV
V	5370	50.18	49.24	15.35	40.51	56.8	74	-17.2	PK
V	5370	36.83	49.24	15.35	40.51	43.45	54	-10.55	AV
H	5350	54.85	49.13	15.34	31.31	52.37	74	-21.63	PK
H	5350	41.86	49.13	15.34	31.31	39.38	54	-14.62	AV
H	5370	52.54	49.24	15.35	40.51	59.16	74	-14.84	PK
H	5370	36.68	49.24	15.35	40.51	43.3	54	-10.7	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ac HT40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5190									
V	5150	52.56	49.12	15.32	37.41	56.17	74	-17.83	PK
V	5150	37.21	49.12	15.32	37.41	40.82	54	-13.18	AV
V	5145	52.83	49.19	15.36	40.46	59.46	74	-14.54	PK
V	5145	36.36	49.19	15.36	40.46	42.99	54	-11.01	AV
H	5150	52.87	49.12	15.32	37.41	56.48	74	-17.52	PK
H	5150	37.36	49.12	15.32	37.41	40.97	54	-13.03	AV
H	5145	51.13	49.19	15.36	40.46	57.76	74	-16.24	PK
H	5145	36.35	49.19	15.36	40.46	42.98	54	-11.02	AV
operation frequency:5230									
V	5350	54.63	49.13	15.34	37.34	58.18	74	-15.82	PK
V	5350	36.52	49.13	15.34	37.34	40.07	54	-13.93	AV
V	5370	51.56	49.24	15.35	40.43	58.1	74	-15.9	PK
V	5370	36.74	49.24	15.35	40.43	43.28	54	-10.72	AV
H	5350	54.66	49.13	15.34	37.34	58.21	74	-15.79	PK
H	5350	41.24	49.13	15.34	37.34	44.79	54	-9.21	AV
H	5370	50.67	49.24	15.35	40.43	57.21	74	-16.79	PK
H	5370	35.63	49.24	15.35	40.43	42.17	54	-11.83	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ax HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5180									
V	5150	52.69	49.12	15.33	37.41	56.31	74	-17.69	PK
V	5150	34.52	49.12	15.33	37.41	38.14	54	-15.86	AV
V	5145	51.23	49.19	15.28	40.46	57.78	74	-16.22	PK
V	5145	33.84	49.19	15.28	40.46	40.39	54	-13.61	AV
H	5150	52.18	49.12	15.33	37.41	55.8	74	-18.2	PK
H	5150	34.86	49.12	15.33	37.41	38.48	54	-15.52	AV
H	5145	50.54	49.19	15.28	40.46	57.09	74	-16.91	PK
H	5145	33.68	49.19	15.28	40.46	40.23	54	-13.77	AV
operation frequency:5240									
V	5350	53.69	49.13	15.32	37.46	57.34	74	-16.66	PK
V	5350	36.15	49.13	15.32	37.46	39.8	54	-14.2	AV
V	5370	50.12	49.24	15.36	40.51	56.75	74	-17.25	PK
V	5370	33.66	49.24	15.36	40.51	40.29	54	-13.71	AV
H	5350	53.74	49.13	15.32	31.31	51.24	74	-22.76	PK
H	5350	40.62	49.13	15.32	31.31	38.12	54	-15.88	AV
H	5370	51.16	49.24	15.36	40.51	57.79	74	-16.21	PK
H	5370	35.48	49.24	15.36	40.51	42.11	54	-11.89	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ax HT40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:5190									
V	5150	52.54	49.12	15.32	37.41	56.15	74	-17.85	PK
V	5150	37.62	49.12	15.32	37.41	41.23	54	-12.77	AV
V	5145	52.88	49.19	15.36	40.46	59.51	74	-14.49	PK
V	5145	36.34	49.19	15.36	40.46	42.97	54	-11.03	AV
H	5150	52.86	49.12	15.32	37.41	56.47	74	-17.53	PK
H	5150	37.32	49.12	15.32	37.41	40.93	54	-13.07	AV
H	5145	51.16	49.19	15.36	40.46	57.79	74	-16.21	PK
H	5145	36.37	49.19	15.36	40.46	43	54	-11	AV
operation frequency:5230									
V	5350	54.21	49.13	15.34	37.34	57.76	74	-16.24	PK
V	5350	36.53	49.13	15.34	37.34	40.08	54	-13.92	AV
V	5370	51.57	49.24	15.35	40.43	58.11	74	-15.89	PK
V	5370	36.25	49.24	15.35	40.43	42.79	54	-11.21	AV
H	5350	54.64	49.13	15.34	37.34	58.19	74	-15.81	PK
H	5350	41.28	49.13	15.34	37.34	44.83	54	-9.17	AV
H	5370	50.66	49.24	15.35	40.43	57.2	74	-16.8	PK
H	5370	35.18	49.24	15.35	40.43	41.72	54	-12.28	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.3 CONDUCTED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.407

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Spectrum Parameter	Setting	
Attenuation	Auto	
Start Frequency	5150MHz	5725MHz
Stop Frequency	5250MHz	5850MHz
RB / VB (emission in restricted band)	1 MHz / 3 MHz for Peak, 1 MHz / 10Hz for Average	

3.3.2 TEST PROCEDURE

Test method: FCC KDB 789033 G)& Parts 15.407(b)(4) & 15.209(a)

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULT

The antenna gain is compensated in the test data.

802.11a



5180MHz



5240MHz

802.11ac HT20



5180MHz



5240MHz

802.11ac HT40



5190MHz



5230MHz

802.11ax HT20



5180MHz



5240MHz

802.11ax HT40



5190MHz



5230MHz

802.11n HT20



5180MHz



5240MHz

802.11n HT40	
	
5190MHz	5230MHz

802.11a



5745MHz



5825MHz

802.11ac HT20



5745MHz



5825MHz

802.11ac HT40



5755MHz



5795MHz

802.11ax HT20	
	
5745MHz	5825MHz
802.11ax HT40	
	
5755MHz	5795MHz

802.11n HT20	
	
5745MHz	5825MHz
802.11n HT40	
	
5755MHz	5795MHz

4.. AVERAGING OUTPUT POWER

4.1. APPLIED PROCEDURES / LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.
For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

4.1.1. TEST PROCEDURE

a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
b. Spectrum Setting : RBW = 1MHz
Span≥99%OBW(30MHz/60MHz/120MHz etc.)
VBW≥3*RBW
Sweep = auto
Detector function = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
Trace = max hold

4.1.2. DEVIATION FROM STANDARD

No deviation.

4.1.3. TEST SETUP



4.1.4. EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5. TEST RESULTS

Temperature:	25 ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 5V

Band	Mode	Test Channel	Average Output Power (dBm)	Duty factor (dB)	Total Output Power(dBm)	LIMIT (dBm)
Band 1	802.11a	Low	3.468	0.87	4.338	23.98
		Middle	3.643	1.12	4.763	23.98
		High	4.266	0.87	5.136	23.98
	802.11ac HT20	Low	4.125	0.16	4.285	23.98
		Middle	4.415	0.13	4.545	23.98
		High	3.515	0.16	3.675	23.98
	802.11ac HT40	Low	4.743	0.32	5.063	23.98
		High	4.287	0.26	4.547	23.98
	802.11ax HT20	Low	4.193	0.13	4.323	23.98
		Middle	3.466	0.16	3.626	23.98
		High	4.17	0.13	4.3	23.98
	802.11ax HT40	Low	4.084	0.32	4.404	23.98
		High	3.507	0.26	3.767	23.98
	802.11n HT20	Low	4.008	0.13	4.138	23.98
		Middle	4.417	0.13	4.547	23.98
		High	4.317	0.16	4.477	23.98
	802.11n HT40	Low	4.563	0.26	4.823	23.98
		High	3.923	0.32	4.243	23.98

Band	Mode	Test Channel	Average Output Power (dBm)	Duty factor (dB)	Total Output Power(dBm)	LIMIT (dBm)
Band 4	802.11a	Low	4.661	1.12	5.781	30
		Middle	4.262	0.87	5.132	30
		High	4.817	1.12	5.937	30
	802.11ac HT20	Low	4.1	0.13	4.23	30
		Middle	2.921	0.13	3.051	30
		High	4.518	0.16	4.678	30
	802.11ac HT40	Low	4.758	0.26	5.018	30
		High	4.376	0.26	4.636	30
	802.11ax HT20	Low	4.097	0.13	4.227	30
		Middle	3.582	0.16	3.742	30
		High	4.633	0.13	4.763	30
	802.11ax HT40	Low	4.745	0.32	5.065	30
		High	4.462	0.26	4.722	30
	802.11n HT20	Low	4.641	0.13	4.771	30
		Middle	4.211	0.13	4.341	30
		High	4.518	0.16	4.678	30
	802.11n HT40	Low	4.184	0.32	4.504	30
		High	4.475	0.26	4.735	30

802.11a	802.11ac HT20
	
5180MHz	5180MHz
	
5200MHz	5200MHz
	
5240MHz	5240MHz

802.11ac HT40	802.11ax HT20
	
5190MHz	5180MHz
	
5230MHz	5200MHz
	
	5240MHz

802.11ax HT40	802.11n HT20
	
5190MHz	5180MHz
	
5230MHz	5200MHz
	
	5240MHz

802.11n HT40



5190MHz



5230MHz

802.11a	802.11ac HT20
	
5745MHz	5745MHz
	
5785MHz	5785MHz
	
5825MHz	5825MHz

802.11ac HT40	802.11ax HT20
	
5755MHz	5745MHz
	
5795MHz	5785MHz
	
	5825MHz

802.11ax HT40	802.11n HT20
	
5755MHz	5745MHz
	
5795MHz	5785MHz
	
	5825MHz

802.11n HT40



5755MHz



5795MHz

5.. POWER SPECTRAL DENSITY TEST

5.1. APPLIED PROCEDURES / LIMIT

In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.
In addition, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW ≥ 1MHz for band 1 RBW ≥ 510KHz for band 4
VB	VBW ≥ 3RBW
Detector	RMS (i.e., power averaging).
Trace	Max Hold
Sweep Time	Auto

5.1.1. TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. The testing follows FCC KDB 789033 D02.
3. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to Spectrum.
4. For U-NII1, U-NII-2A, U-NII-2C Band:
Set RBW=1MHz, VBW=3MHz, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
For U-NII-3 Band:
Set RBW=510 kHz, VBW=3*RBW, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
5. User the cursor on spectrum to peak search the highest level of trace
6. Record the max. reading and add 10 log(1/duty cycle).
   we test all antennas, the antenna 1 was worst mode and the data recording in the report.
7. Duty factor Reference is made to the test results in Section 7.1.5.

5.1.2. DEVIATION FROM STANDARD

No deviation.

5.1.3. TEST SETUP



5.1.4. EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5. TEST RESULTS

	Mode	Test Channel	Reading Level (dBm/MHz)	Duty factor (dB)	PSD (dBm/MHz)	Limit (dBm)	Result
Band1	802.11a	Low	-5.234	0.87	-4.364	11.00	PASS
		Middle	-5.795	1.12	-4.675	11.00	PASS
		High	-4.669	0.87	-3.799	11.00	PASS
	802.11ac20	Low	-5.453	0.16	-5.293	11.00	PASS
		Middle	-5.429	0.13	-5.299	11.00	PASS
		High	-6.348	0.16	-6.188	11.00	PASS
	802.11ac40	Low	-7.95	0.32	-7.63	11.00	PASS
		High	-8.687	0.26	-8.427	11.00	PASS
	802.11ax20	Low	-5.791	0.13	-5.661	11.00	PASS
		Middle	-6.289	0.16	-6.129	11.00	PASS
		High	-5.622	0.13	-5.492	11.00	PASS
	802.11ax40	Low	-8.741	0.32	-8.421	11.00	PASS
		High	-9.305	0.26	-9.045	11.00	PASS
	802.11n20	Low	-5.963	0.13	-5.833	11.00	PASS
		Middle	-5.501	0.13	-5.371	11.00	PASS
		High	-5.546	0.16	-5.386	11.00	PASS
	802.11n40	Low	-8.445	0.26	-8.185	11.00	PASS
		High	-9.16	0.32	-8.84	11.00	PASS

	Mode	Test Channel	Reading Level (dBm/ 510kHz)	Duty factor (dB)	RB factor (dB)	PSD (dBm/ 500kHz)	Limit (dBm/ 500kHz)	Result
Band4	802.11a	Low	-7.749	1.12	-0.09	-6.539	30.00	PASS
		Middle	-7.838	0.87	-0.09	-6.878	30.00	PASS
		High	-7.488	1.12	-0.09	-6.278	30.00	PASS
	802.11ac20	Low	-8.882	0.13	-0.09	-8.662	30.00	PASS
		Middle	-10.078	0.13	-0.09	-9.858	30.00	PASS
		High	-8.358	0.16	-0.09	-8.108	30.00	PASS
	802.11ac40	Low	-10.481	0.26	-0.09	-10.131	30.00	PASS
		High	-11.21	0.26	-0.09	-10.86	30.00	PASS
	802.11ax20	Low	-8.566	0.13	-0.09	-8.346	30.00	PASS
		Middle	-9.087	0.16	-0.09	-8.837	30.00	PASS
		High	-8.05	0.13	-0.09	-7.83	30.00	PASS
	802.11ax40	Low	-10.388	0.32	-0.09	-9.978	30.00	PASS
		High	-11.437	0.26	-0.09	-11.087	30.00	PASS
	802.11n20	Low	-8.134	0.13	-0.09	-7.914	30.00	PASS
		Middle	-8.681	0.13	-0.09	-8.461	30.00	PASS
		High	-8.256	0.16	-0.09	-8.006	30.00	PASS
	802.11n40	Low	-11.15	0.32	-0.09	-10.74	30.00	PASS
		High	-11.487	0.26	-0.09	-11.137	30.00	PASS

Note: RB factor=10log(510/500k)

802.11a	802.11ac HT20
	
5180MHz	5180MHz
	
5200MHz	5200MHz
	
5240MHz	5240MHz

802.11ac HT40	802.11ax HT20
	
5190MHz	5180MHz
	
5230MHz	5200MHz
	
	5240MHz

802.11ax HT40	802.11n HT20
	
5190MHz	5180MHz
	
5230MHz	5200MHz
	
	5240MHz

802.11n HT40



5190MHz



5230MHz

802.11a	802.11ac HT20
	
5745MHz	5745MHz
	
5785MHz	5785MHz
	
5825MHz	5825MHz