



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20250100059E-02
Applicant: Shenzhen IVY IoT Technology Co., Ltd.
Address of Applicant: 904, 9th Floor, Building B, Shenzhen International Innovation Valley Phase 1, Xingke 1st Street, Xili Street, Nanshan District, Shenzhen, China
Equipment Under Test (EUT):
EUT Name: WiFi Camera
Model No.: A5M10, A5A10-A5Z10, A5A10-A5A99, A31A-A31Z
Test Model No.: A5M10
Brand Name: N/A
FCC ID: 2BHXE-A5M10
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
447498 D04 Interim General RF Exposure Guidance v01
Date of Receipt: 2025-1-8
Date of Test: 2025-1-8 to 2025-2-7
Date of Issue: 2025-2-10
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Jack Ai
(Jack Ai)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20250100059E-02	Rev.01	Initial report	2025-2-10

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC	5
4 MPE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 Limits	6
4.1.2 Test Procedure	6
4.1.3 EUT RF Exposure	7

3 General Information

3.1 Client Information

Applicant:	Shenzhen IVY IoT Technology Co., Ltd.
Address of Applicant:	904, 9th Floor, Building B, Shenzhen International Innovation Valley Phase 1, Xingke 1st Street, Xili Street, Nanshan District, Shenzhen, China
Manufacturer:	Shenzhen IVY IoT Technology Co., Ltd.
Address of Manufacturer:	904, 9th Floor, Building B, Shenzhen International Innovation Valley Phase 1, Xingke 1st Street, Xili Street, Nanshan District, Shenzhen, China
Factory:	Shenzhen IVY IoT Technology Co., Ltd.
Address of Factory:	904, 9th Floor, Building B, Shenzhen International Innovation Valley Phase 1, Xingke 1st Street, Xili Street, Nanshan District, Shenzhen, China

3.2 General Description of EUT

Product Name:	WiFi Camera
Model No.:	A5M10, A5A10-A5Z10, A5A10-A5A99, A31A-A31Z
Test Model No.:	A5M10
Trade Mark:	N/A
Software Version:	V1.0
Hardware Version:	V1.0
EUT Power Supply:	Power supply AC 120V

Note:

Model No.:A5M10, A5A10-A5Z10, A5A10-A5A99, A31A-A31Z.

The circuit design, layout, components used and internal wiring are all the same, except for the appearance difference.

3.3 General Description of 2.4G WIFI Classic

Operation Frequency:	2412MHz~2462MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps IEEE for 802.11n(HT40) : 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	FPC antenna
Antenna Gain:	2.5dBi

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave Dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For 2.4G WIFI Classic

Measurement Data

11B mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	13.85	11.7	11.5 ± 1	12.5	17.783
Middle(2437MHz)	13.33	11.18	11.0 ± 1	12.0	15.849
Highest(2462MHz)	13.1	10.95	11.0 ± 1	12.0	15.849
11G mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	11.33	9.18	9.0 ± 1	10.0	10.000
Middle(2437MHz)	10.79	8.64	8.5 ± 1	9.5	8.913
Highest(2462MHz)	10.52	8.37	8.5 ± 1	9.5	8.913
11N20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	11.09	8.94	9.0 ± 1	10.0	10.000
Middle(2437MHz)	10.51	8.36	8.5 ± 1	9.5	8.913
Highest(2462MHz)	10.3	8.15	8.0 ± 1	9.0	7.943
11N40 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2422MHz)	9.7	7.55	7.5 ± 1	8.5	7.079
Middle(2437MHz)	9.08	6.93	7.0 ± 1	8.0	6.310
Highest(2452MHz)	8.44	6.29	6.5 ± 1	7.5	5.623

The ERP of this product is less than 3060mW

EIRP=Conducted power+Gain

ERP=EIRP-2.15dB

Note: 1) Refer to report No. CQASZ20250100059E-01 for EUT test Max Conducted AV Output Power value.

2) EUT's module is more than 20cm away from the human body.

*** END OF REPORT ***