

FCC PART 15.247 TEST REPORT

For

SPACEWALKER PTE. LTD.
60 PAYA LEBAR ROAD SINGAPORE Singapore

FCC ID: 2BK3M-UT5ULTRAUS

Report Type: Original Report	Product Name: Electric Scooter
Report Number: RKSA251106001-00B	
Report Date: 2026-01-19	
Reviewed By:	Jenny Yang
Approved By:	Kyle Xu
Test Laboratory: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

TABLE OF CONTENTS

REPORT REVISION HISTORY.....	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
SPECIAL ACCESSORIES	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC §1.1307(b) & §2.1093 - RF EXPOSURE.....	13
APPLICABLE STANDARD	13
MEASUREMENT RESULT	13
FCC §15.203 – ANTENNA REQUIREMENT	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	16
APPLICABLE STANDARD	16
TEST SYSTEM SETUP.....	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	17
TEST RESULTS SUMMARY	17
TEST DATA: SEE APPENDIX	17
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	18
APPLICABLE STANDARD	18
TEST SYSTEM SETUP.....	18
EMI TEST RECEIVER SETUP.....	19
TEST PROCEDURE	19
TEST RESULTS SUMMARY	20
TEST DATA: SEE APPENDIX	20
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATD: SEE APPENDIX	21
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST DATD: SEE APPENDIX	22
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	23
APPLICABLE STANDARD	23

TEST PROCEDURE	23
TEST DATD: SEE APPENDIX	23
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST DATD: SEE APPENDIX	24
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	25
APPLICABLE STANDARD	25
TEST PROCEDURE	25
TEST DATD: SEE APPENDIX	25
FCC §15.247(d) - BAND EDGES & CONDUCTED SPURIOUS EMISSION	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST DATD: SEE APPENDIX	27
APPENDIX - TEST DATA.....	28
AC LINE CONDUCTED EMISSIONS	28
RADIATED EMISSIONS & RESTRICTED BANDS EMISSIONS	31
CHANNEL SEPARATION TEST	59
20 dB BANDWIDTH TEST	61
QUANTITY OF HOPPING CHANNEL TEST	64
TIME OF OCCUPANCY (DWELL TIME).....	66
PEAK OUTPUT POWER MEASUREMENT	72
BAND EDGES.....	75
CONDUCTED SPURIOUS EMISSION	78
EUT PHOTOGRAPHS	81
TEST SETUP PHOTOGRAPHS	82

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RKSA251106001-00B	R1V1	2026-01-19	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	SPACEWALKER PTE. LTD.
Tested Model:	UT5 Ultra X US
Product Name:	Electric Scooter
Power Supply:	DC 67.2V charging by adapter or DC 57.6V powered by battery
Maximum Output Power:	GFSK: 0.03 dBm $\pi/4$ -DQPSK: 0.74 dBm 8DPSK: 1.37 dBm
RF Function:	Classic BT
Operating Band/Frequency:	2402-2480 MHz
Channel Number:	79
Channel Separation:	1 MHz
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
★Maximum Antenna Gain:	0.31 dBi
Sample/EUT Status:	Good condition

Adapter Information:

Model: FY2476723750

Input: 100-240V, 50/60Hz, 3.5A

Output: 67.2V, 3.75A

Note: The maximum antenna gain was declared by the manufacturer.

All measurement and test data in this report was gathered from production sample serial number: RKSA251106001-1 (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2025-11-06.)

Objective

This test report is prepared for *SPACEWALKER PTE. LTD.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024[▲], American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and 558074 D01 15.247 Meas Guidance v05r02.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	9 kHz~150 kHz	3.8dB
	150 kHz~30 MHz	3.4dB
	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu Province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No.: CN5055.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

The system was configured for testing in an engineering mode, which was provided by manufacturer

RF test software: FCC Assist 1.0.4

★Power level: Default

Note: The power level was declared by the applicant.

Special Accessories

No special accessory.

Equipment Modifications


No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Lenovo	Notebook	Y700P	PF2B7PL5
/	Debug board	/	/


External I/O Cable

Cable Description	Length (m)	From Port	To Port
Power Cable 1	1.5	LISN/AC Source	Adapter
Power Cable 2	2.0	Adapter	EUT
Data Cable	0.1	EUT	Debug board
USB Cable	1.0	Debug board	Notebook

Block Diagram of Test Setup**For Conducted Emissions:**


For Radiated Emissions (Below 1GHz):

Turntable
2m Diameter



For Radiated Emissions (Above 1GHz):

Turntable
2m Diameter



Note: The EUT Antenna 1.5m above Ground Plane

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307(b)(1)& §2.1093	RF EXPOSURE	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges & Conducted Spurious Emission	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber #1)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2025-04-09	2026-04-08
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2024-11-08	2027-11-07
Narda	6dB Attenuator	773-6	10690812-2-1	2024-11-08	2027-11-07
BACL	Active Loop Antenna	1313-1A	4041511	2024-11-22	2027-11-21
Sonoma Instrument	Pre-amplifier	310N	171205	2025-04-09	2026-04-08
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-9	009	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-10	010	2025-04-09	2026-04-08
Radiated Emission Test (Chamber #2)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207/040	2025-04-09	2026-04-08
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2024-11-03	2027-11-02
ETS-LINDGREN	Horn Antenna	3116	2516	2024-12-12	2027-12-11
A.H.Systems, inc	Amplifier	PAM-0118P	512	2025-04-09	2026-04-08
SELECTOR	Amplifier	EM18G40G	060726	2025-04-09	2026-04-08
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2025-04-08	2026-04-07
Narda	Attenuator	10dB	010	2025-04-08	2026-04-07
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-11	011	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-12	012	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-13	013	2025-04-09	2026-04-08
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200103	2025-04-09	2026-04-08
Narda	Attenuator	10dB	010	2025-04-08	2026-04-07
XHFDZ	RG316 Coaxial Cable	SMA-316	XHF-1175	Each time	N/A

Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2025-04-08	2026-04-07
Rohde & Schwarz	LISN	ENV216	101115	2025-04-08	2026-04-07
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3-Z2	100552	2025-04-08	2026-04-07
MICRO-COAX	Coaxial Cable	Cable-15	015	2025-04-08	2026-04-07

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) & §2.1093 - RF EXPOSURE

Applicable Standard

According to §2.1093 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f \text{ (GHz)}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. f (GHz) is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

Standalone SAR test exclusion

Module 1(RB8762-35A2)

Mode	Frequency Range (MHz)	Max Tune-up Conducted Power		Calculated Distance (mm)	Calculated Value	Threshold (10-g SAR)	SAR Test Exclusion
		(dBm)	(mW)				
BLE 1M	2402-2480	7.0	5.01	5	1.6	7.5	Yes
BLE 2M	2404-2478	7.0	5.01	5	1.6	7.5	Yes

Module 2(IB727T1)

Mode	Frequency Range (MHz)	Max Tune-up Conducted Power		Calculated Distance (mm)	Calculated Value	Threshold (10-g SAR)	SAR Test Exclusion
		(dBm)	(mW)				
BLE 1M	2402-2480	0.5	1.12	5	0.4	7.5	Yes
BLE 2M	2402-2480	0.5	1.12	5	0.4	7.5	Yes
BT	2402-2480	1.5	1.41	5	0.4	7.5	Yes

Standalone SAR estimation:

Module 1(RB8762-35A2)

Mode	Frequency Range (MHz)	Max Tune-up Conducted Power		Calculated Distance (mm)	Calculated Value	Estimated10-g (W/kg)
		(dBm)	(mW)			
BLE 1M	2402-2480	7.0	5.01	5	1.6	0.085
BLE 2M	2404-2478	7.0	5.01	5	1.6	0.085

Module 2(IB727T1)

Mode	Frequency Range (MHz)	Max Tune-up Conducted Power		Calculated Distance (mm)	Calculated Value	Estimated10-g (W/kg)
		(dBm)	(mW)			
BLE 1M	2402-2480	0.5	1.12	5	0.4	0.021
BLE 2M	2402-2480	0.5	1.12	5	0.4	0.021
BT	2402-2480	1.5	1.41	5	0.4	0.021

The EUT is a limb-worn devices. When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}/x]$ W/kg for test separation distances ≤ 50 mm;
where $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Module 1 and module 2 can Simultaneous Transmit

Simultaneous SAR test exclusion considerations:

Mode	Reported SAR (W/kg)		Σ SAR < 4.0W/kg
	SAR 1	SAR 2	
Module 1+Module 2	0.085	0.021	0.106

Conclusion: Σ SAR < 4.0 W/kg therefore simultaneous transmission SAR is not required.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has a PCB antenna, which the antenna gain is 0.31 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

Test System Setup



The measurement procedure of EUT setup is according with ANSIC63.10-2020. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz - 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2020 clause 6.2

During the conducted emission test, the EUT or adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

If the maximum peak value of the emissions is below the average limit, the QP value and average value measurement will not need to be performed and only record the maximum peak measured value to meet the requirements.

Level & Over Limit Calculation

The Level is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

$$\begin{aligned}\text{Factor (dB)} &= \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)} \\ \text{Level (dB}\mu\text{V)} &= \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)}\end{aligned}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Level (dB}\mu\text{V)} - \text{Limit (dB}\mu\text{V)}$$



Test Results Summary


According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data: See Appendix

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

Test System Setup**9 kHz - 30 MHz:****30 MHz - 1 GHz:**

Above 1 GHz:

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	VBW	IF B/W	Measurement	Detector
9 kHz - 150 kHz	200 Hz	1 kHz	200 Hz	Peak/QP/Average	Peak/QP/Average
150 kHz - 30 MHz	9 kHz	30 kHz	9 kHz	Peak/QP/Average	Peak/QP/Average
30 MHz - 1000 MHz	100 kHz	300 kHz	/	Peak	Peak
	/	/	120 kHz	QP	QP
Above 1GHz	1MHz	3 MHz	/	Peak	Peak
	1MHz	3 MHz	/	Average	Average

Test Procedure

According to ANSI C63.10-2020 clause 6.4, 6.5 and 6.6.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

If the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is at least 6 dB below the QP emission limit, there's no need to record the measured QP level of the emissions in the report.

For 9 kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dBμV/m) = Meter Reading (dBμV) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Note: The QuasiPeak (dBμV/m), MaxPeak (dBμV/m), Average (dBμV/m) which shown in the data table are all Corrected Amplitude.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data: See Appendix

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.


Test Procedure

According to ANSI C63.10a-2024 sub-clause 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- Span: Wide enough to capture the peaks of two adjacent channels.
- RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- Video (or average) bandwidth (VBW) $\geq$ 1/10th the RBW.
- Sweep: Auto.
- Detector function: Peak.
- Trace: Max hold.
- Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Datd: See Appendix

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH


Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

According to ANSI C63.10-2020 sub-clause 6.9.2

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Datd: See Appendix

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.


Test Procedure

According to ANSI C63.10a-2024 sub-clause 7.8.3

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c. VBW) $\geq 1/10$ th the RBW
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Datd: See Appendix

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard


Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

According to ANSI C63.10-2020 sub-clause 7.8.4

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Zero span, centered on a hopping channel.
- b. RBW shall be $\leq$ channel spacing and where possible RBW should be set $\geq 1 / T$, where T is the expected dwell time per channel.
- c. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d. Detector function: Peak.
- e. Trace: Max hold.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Datd: See Appendix

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard


According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

According to ANSI C63.10-2020 sub-clause 7.8.5

a. Use the following spectrum analyzer settings:

- 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW $\geq$ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b. Allow trace to stabilize.
- c. Use the marker-to-peak function to set the marker to the peak of the emission.
- d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e. A plot of the test results and setup description shall be included in the test report.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Datd: See Appendix

FCC §15.247(d) - BAND EDGES & CONDUCTED SPURIOUS EMISSION

Band Edges


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2020 sub-clause 7.8.7

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Conducted Spurious Emission

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


Test Procedure

Test Method: ANSI C63.10-2020 Clause 7.8.7.1

To demonstrate compliance with the relative out-of-band emissions requirements conducted spurious emissions shall be measured for the transmit frequencies, per 5.5 and 5.6, and at the maximum transmit powers. Frequency hopping shall be disabled for this test with the exception of measurements at the allocated band-edges which shall be repeated with hopping enabled.

Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The frequency range of testing shall span 30 MHz to 10 times the operating frequency and this may be done in a single sweep or, to aid resolution, across a number of sweeps. The resolution bandwidth shall be 100 kHz, video bandwidth 300 kHz, and a coupled sweep time with a peak detector.

The limit is based on the highest in-band level across all channels measured using the same instrument settings (resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector). To help clearly demonstrate compliance a display line may be set at the required offset (typically 20 dB) below the highest in-band level. Where the highest in-band level is not clearly identified in the out-of-band measurements a separate spectral plot showing the in-band level shall be provided.



Note: Offset (11dB) = Attenuator (10dB) + Cable Loss (1.0dB)

Test Datd: See Appendix


APPENDIX - TEST DATA

AC LINE CONDUCTED EMISSIONS

Environmental Conditions & Test Information

Test Date:	2025-11-26
Temperature:	16.3 °C
Relative Humidity:	35 %
ATM Pressure:	102.9 kPa
Test Result:	Pass
Test Engineer:	Jack He


EUT operation mode: Transmitting in 8DPSK Mode low channel (maximum output power mode)



Trace: 1

Site : CE
 Condition : limit\FCC PART 15.207\FCC 15.207 QP.csv Line
 : DET:Peak
 Project No. : RKSA251106001
 Model : UT5 Ultra X US
 Phase : L
 Voltage : 120V/60Hz
 Mode : BT
 Test Equipment : ENV216,ESR3
 Receiver Setting : RBW: 9 kHz, Sweep Time: Auto
 Temperature : 16.3°C
 Humidity : 35%
 Atmospheric pressure: 102.9kPa
 Test Engineer : Jack He

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV		dB	dBuV	dB	
1	0.261	0.60	20.40	21.00	51.40	-30.40	Average
2	0.261	24.00	20.40	44.40	61.40	-17.00	QP
3	0.477	-4.40	20.22	15.82	46.40	-30.58	Average
4	0.477	16.10	20.22	36.32	56.40	-20.08	QP
5	0.618	-4.89	20.22	15.33	46.00	-30.67	Average
6	0.618	15.41	20.22	35.63	56.00	-20.37	QP
7	1.048	-1.29	20.17	18.88	46.00	-27.12	Average
8	1.048	23.61	20.17	43.78	56.00	-12.22	QP
9	1.478	-0.90	20.24	19.34	46.00	-26.66	Average
10	1.478	25.70	20.24	45.94	56.00	-10.06	QP
11	2.373	-9.99	20.27	10.28	46.00	-35.72	Average
12	2.373	9.91	20.27	30.18	56.00	-25.82	QP



Site : CE
 Condition : limit\FCC PART 15.207\FCC 15.207 QP.csv Neutral
 : DET:Peak
 Project No. : RKSA251106001
 Model : UT5 Ultra X US
 Phase : N
 Voltage : 120V/60Hz
 Mode : BT
 Test Equipment : ENV216,ESR3
 Receiver Setting : RBW: 9 kHz, Sweep Time: Auto
 Temperature : 16.3°C
 Humidity : 35%
 Atmospheric pressure: 102.9kPa
 Test Engineer : Jack He

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV		dB	dBuV	dB	
1	0.266	1.50	20.37	21.87	51.24	-29.37	Average
2	0.266	25.40	20.37	45.77	61.24	-15.47	QP
3	0.618	-7.49	20.22	12.73	46.00	-33.27	Average
4	0.618	18.11	20.22	38.33	56.00	-17.67	QP
5	1.048	-8.29	20.18	11.89	46.00	-34.11	Average
6	1.048	15.81	20.18	35.99	56.00	-20.01	QP
7	1.485	-2.60	20.23	17.63	46.00	-28.37	Average
8	1.485	24.00	20.23	44.23	56.00	-11.77	QP
9	1.934	-7.50	20.27	12.77	46.00	-33.23	Average
10	1.934	11.80	20.27	32.07	56.00	-23.93	QP
11	22.245	0.90	20.59	21.49	50.00	-28.51	Average
12	22.245	20.00	20.59	40.59	60.00	-19.41	QP

RADIATED EMISSIONS & RESTRICTED BANDS EMISSIONS**Environmental Conditions & Test Information**


Test Item:	SPURIOUS EMISSIONS			
	9kHz – 30MHz	30 MHz - 1 GHz	1 GHz - 18 GHz	18 GHz - 25 GHz
Test Date:	2025-12-02	2025-12-02	2025-11-23	2025-12-31
Temperature:	18.9 °C	18.9 °C	17.8 °C	20.7 °C
Relative Humidity:	42 %	42 %	44 %	48 %
ATM Pressure:	102.3 kPa	102.3 kPa	103.1 kPa	102.4 kPa
Test Result:	Pass	Pass	Pass	Pass
Test Engineer:	Scarf Yang	Scarf Yang	Destine Hu	Hugh Wu

EUT operation mode: Transmitting


9 kHz-30 MHz: (Transmitting maximum output power 8DPSK Mode low channel)

Parallel(worst case)

9kHz-150kHz



150kHz-30MHz



Project No.RKSA251106001
Date: 2.DEC.2025 12:36:12

Tester:Scarff Yang

Project No.RKSA251106001
Date: 2.DEC.2025 12:43:02

Tester:Scarff Yang

9kHz-150kHz


Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.01746	44.79	PK	-0.55	122.76	77.97
0.027612	45.22	PK	-0.6	118.78	73.56
0.033252	45.26	PK	-1.13	117.17	71.91
0.038046	44.26	PK	-1.9	116	71.74

150kHz-30MHz

Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.150000	48.30	PK	-11.34	104.08	55.78
1.224600	40.66	PK	-28.35	65.84	25.18
4.388700	38.93	PK	-31.97	69.54	30.61
6.418500	32.43	PK	-32.27	69.54	37.11

30 MHz - 1 GHz (Transmitting in maximum output power 8DPSKmode and low channel):**Low Channel: 2402 MHz****Common Information**


Project No: RKSA251106001
 EUT Model: UT5 Ultra X US
 Test Mode: Transmitting in BT mode
 Standard: FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.247
 Test Equipment: ESCI, JB3, 310N
 Receiver Setting: RBW: 100 kHz, VBW: 300 kHz, Sweep Time: Auto
 Temperature: 18.9°C
 Humidity: 42%
 Barometric Pressure: 102.3 kPa
 Test Engineer: Scarf Yang
 Test Date: 2025/12/2

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
32.182500	31.61	40.00	8.39	V	-6.2
108.691250	35.08	43.50	8.42	H	-12.8
143.490000	36.50	43.50	7.00	H	-11.4
150.765000	36.20	43.50	7.30	H	-11.7
212.117500	37.43	43.50	6.07	H	-12.9
927.613750	35.57	46.00	10.43	H	1.5

1 GHz - 10 GHz:**GFSK:****Low Channel: 2402 MHz****Common Information**


Project No.:	RKSA251106001
EUT Model:	UT5 Ultra X US
Test Mode:	Transmitting in BT_1DH5 mode Low channel
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	17.8°C
Humidity:	44%
Atmospheric Pressure:	103.1kPa
Test Engineer:	Destine Hu
Test Date:	2025/11/23

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1063.900000	---	35.00	54.00	19.00	V	-15.0
1063.900000	43.60	---	74.00	30.40	V	-15.0
2125.900000	43.91	---	74.00	30.09	V	-9.9
2125.900000	---	33.47	54.00	20.53	V	-9.9
3185.200000	---	32.23	54.00	21.77	V	-7.4
3185.200000	39.86	---	74.00	34.14	V	-7.4
4800.700000	45.41	---	74.00	28.59	V	-3.4
4800.700000	---	39.60	54.00	14.40	V	-3.4
7431.400000	---	40.68	54.00	13.32	H	2.8
7431.400000	50.48	---	74.00	23.52	H	2.8
9847.000000	53.56	---	74.00	20.44	V	5.9
9847.000000	---	43.97	54.00	10.03	V	5.9

Middle Channel: 2441 MHz**Common Information**


Project No.:	RKSA251106001
EUT Model:	UT5 Ultra X US
Test Mode:	Transmitting in BT_1DH5 mode Middle channel
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	17.8°C
Humidity:	44%
Atmospheric Pressure:	103.1kPa
Test Engineer:	Destine Hu
Test Date:	2025/11/23

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1066.600000	39.65	---	74.00	34.35	V	-15.0
1066.600000	---	28.25	54.00	25.75	V	-15.0
2125.000000	46.48	---	74.00	27.52	V	-9.9
2125.000000	---	35.15	54.00	18.85	V	-9.9
4879.000000	---	41.94	54.00	12.06	V	-3.2
4879.000000	45.78	---	74.00	28.22	V	-3.2
5914.000000	---	37.45	54.00	16.55	H	-0.8
5914.000000	46.48	---	74.00	27.52	H	-0.8
7662.700000	---	40.78	54.00	13.22	H	3.1
7662.700000	50.74	---	74.00	23.26	H	3.1
9846.100000	---	43.25	54.00	10.75	H	5.9
9846.100000	52.30	---	74.00	21.70	H	5.9

High Channel: 2480 MHz**Common Information**

Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_1DH5 mode High channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8°C
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23

**Critical Freqs**


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1063.900000	40.80	---	74.00	33.20	V	-15.0
1063.900000	---	30.01	54.00	23.99	V	-15.0
2132.200000	42.43	---	74.00	31.57	V	-9.9
2132.200000	---	34.01	54.00	19.99	V	-9.9
4956.400000	47.30	---	74.00	26.70	V	-3.0
4956.400000	---	39.16	54.00	14.84	V	-3.0
6345.100000	---	36.75	54.00	17.25	V	-0.8
6345.100000	46.84	---	74.00	27.16	V	-0.8
8430.400000	---	42.45	54.00	11.55	H	4.5
8430.400000	51.91	---	74.00	22.09	H	4.5
9838.000000	49.26	---	74.00	24.74	V	5.9
9838.000000	---	44.82	54.00	9.18	V	5.9

$\pi/4$ -DQPSK:

Low Channel: 2402 MHz

Common Information


Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_2DH5 mode Low channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8°C
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1061.200000	---	35.52	54.00	18.48	V	-15.0
1061.200000	44.03	---	74.00	29.97	V	-15.0
2126.800000	---	28.24	54.00	25.76	V	-9.9
2126.800000	41.43	---	74.00	32.57	V	-9.9
3196.900000	---	28.71	54.00	25.29	V	-7.4
3196.900000	40.67	---	74.00	33.33	V	-7.4
4800.700000	---	42.45	54.00	11.55	V	-3.4
4800.700000	48.19	---	74.00	25.81	V	-3.4
7875.100000	---	42.03	54.00	11.97	H	3.2
7875.100000	51.63	---	74.00	22.37	H	3.2
9953.200000	50.69	---	74.00	23.31	H	6.2
9953.200000	---	44.94	54.00	9.06	H	6.2

Middle Channel: 2441 MHz**Common Information**


Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_2DH5 mode Middle channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8°C
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1063.900000	37.99	---	74.00	36.01	V	-15.0
1063.900000	---	28.17	54.00	25.83	V	-15.0
2125.900000	42.45	---	74.00	31.55	V	-9.9
2125.900000	---	31.34	54.00	22.66	V	-9.9
3782.800000	---	30.72	54.00	23.28	H	-5.5
3782.800000	40.17	---	74.00	33.83	H	-5.5
4879.000000	46.12	---	74.00	27.88	V	-3.2
4879.000000	---	42.62	54.00	11.38	V	-3.2
8308.900000	51.58	---	74.00	22.42	H	4.2
8308.900000	---	41.59	54.00	12.41	H	4.2
9933.400000	49.79	---	74.00	24.21	H	6.2
9933.400000	---	44.29	54.00	9.71	H	6.2

High Channel: 2480 MHz**Common Information**


Project No.: RKSA251106001
 EUT Model: UT5 Ultra X US
 Test Mode: Transmitting in BT_2DH5 mode High channel
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 17.8°C
 Humidity: 44%
 Atmospheric Pressure: 103.1kPa
 Test Engineer: Destine Hu
 Test Date: 2025/11/23

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1064.800000	---	30.09	54.00	23.91	V	-15.0
1064.800000	40.72	---	74.00	33.28	V	-15.0
2124.100000	---	31.68	54.00	22.32	H	-9.9
2124.100000	43.29	---	74.00	30.71	H	-9.9
3527.200000	---	30.41	54.00	23.59	H	-6.2
3527.200000	39.76	---	74.00	34.24	H	-6.2
4957.300000	48.46	---	74.00	25.54	V	-3.0
4957.300000	---	45.71	54.00	8.29	V	-3.0
7704.100000	51.17	---	74.00	22.83	H	3.1
7704.100000	---	41.95	54.00	12.05	H	3.1
9744.400000	53.03	---	74.00	20.97	V	5.6
9744.400000	---	43.92	54.00	10.08	V	5.6

8DPSK:**Low Channel: 2402 MHz****Common Information**


Project No.:	RKSA251106001
EUT Model:	UT5 Ultra X US
Test Mode:	Transmitting in BT_3DH5 mode Low channel
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	17.8°C
Humidity:	44%
Atmospheric Pressure:	103.1kPa
Test Engineer:	Destine Hu
Test Date:	2025/11/23

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1062.100000	---	34.16	54.00	19.84	V	-15.0
1062.100000	43.79	---	74.00	30.21	V	-15.0
2129.500000	---	31.60	54.00	22.40	V	-9.9
2129.500000	43.41	---	74.00	30.59	V	-9.9
3195.100000	---	28.21	54.00	25.79	V	-7.4
3195.100000	38.94	---	74.00	35.06	V	-7.4
4800.700000	---	42.43	54.00	11.57	V	-3.4
4800.700000	49.38	---	74.00	24.62	V	-3.4
7496.200000	---	41.29	54.00	12.71	V	3.0
7496.200000	50.56	---	74.00	23.44	V	3.0
9852.400000	---	44.38	54.00	9.62	H	5.9
9852.400000	52.47	---	74.00	21.53	H	5.9

Middle Channel: 2441 MHz**Common Information**


Project No.:	RKSA251106001
EUT Model:	UT5 Ultra X US
Test Mode:	Transmitting in BT_3DH5 mode Middle channel
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	17.8°C
Humidity:	44%
Atmospheric Pressure:	103.1kPa
Test Engineer:	Destine Hu
Test Date:	2025/11/23

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1063.000000	38.60	---	74.00	35.40	V	-15.0
1063.000000	---	31.45	54.00	22.55	V	-15.0
2132.200000	45.42	---	74.00	28.58	V	-9.9
2132.200000	---	36.89	54.00	17.11	V	-9.9
4879.000000	47.08	---	74.00	26.92	V	-3.2
4879.000000	---	44.21	54.00	9.79	V	-3.2
6145.300000	---	36.72	54.00	17.28	H	-0.7
6145.300000	46.34	---	74.00	27.66	H	-0.7
7862.500000	---	41.14	54.00	12.86	V	3.2
7862.500000	50.75	---	74.00	23.25	V	3.2
9820.000000	49.95	---	74.00	24.05	H	5.8
9820.000000	---	44.46	54.00	9.54	H	5.8

High Channel: 2480 MHz**Common Information**

Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_3DH5 mode High channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8°C
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23

**Critical_Freqs**


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1062.100000	---	37.66	54.00	16.34	V	-15.0
1062.100000	43.16	---	74.00	30.84	V	-15.0
2123.200000	---	31.65	54.00	22.35	H	-9.9
2123.200000	42.99	---	74.00	31.01	H	-9.9
3188.800000	---	30.02	54.00	23.98	V	-7.4
3188.800000	42.17	---	74.00	31.83	V	-7.4
4956.400000	---	39.56	54.00	14.44	V	-3.0
4956.400000	47.63	---	74.00	26.37	V	-3.0
8713.900000	---	43.33	54.00	10.67	H	4.7
8713.900000	52.42	---	74.00	21.58	H	4.7
9913.600000	---	45.37	54.00	8.63	V	6.1
9913.600000	49.53	---	74.00	24.47	V	6.1

10 GHz - 18 GHz:**GFSK:****Low Channel: 2402 MHz**

Common Information

Project No.:	RKSA251106001
EUT Model:	UT5 Ultra X US
Test Mode:	Transmitting in BT_1DH5 mode Low channel
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	17.8℃
Humidity:	44%
Atmospheric Pressure:	103.1kPa
Test Engineer:	Destine Hu
Test Date:	2025/11/23

Full Spectrum




Critical Freqs

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
12283.200000	---	43.77	54.00	10.23	V	8.9
12283.200000	55.30	---	74.00	18.70	V	8.9
13024.000000	---	44.38	54.00	9.62	V	9.2
13024.000000	55.10	---	74.00	18.90	V	9.2
14080.000000	54.22	---	74.00	19.78	H	11.2
14080.000000	---	47.04	54.00	6.96	H	11.2
14633.600000	56.27	---	74.00	17.73	V	11.5
14633.600000	---	45.92	54.00	8.08	V	11.5
16918.400000	---	44.03	54.00	9.97	H	10.6
16918.400000	54.25	---	74.00	19.75	H	10.6
17966.400000	54.31	---	74.00	19.69	H	11.7
17966.400000	---	45.43	54.00	8.57	H	11.7

Middle Channel: 2441 MHz**Common Information**

Project No.: RKSA251106001
 EUT Model: UT5 Ultra X US
 Test Mode: Transmitting in BT_1DH5 mode Middle channel
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 17.8°C
 Humidity: 44%
 Atmospheric Pressure: 103.1kPa
 Test Engineer: Destine Hu
 Test Date: 2025/11/23

Full Spectrum


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
12155.200000	54.65	---	74.00	19.35	V	9.0
12155.200000	---	44.65	54.00	9.35	V	9.0
13579.200000	---	45.73	54.00	8.27	V	10.2
13579.200000	55.35	---	74.00	18.65	V	10.2
14630.400000	56.07	---	74.00	17.93	H	11.5
14630.400000	---	45.41	54.00	8.59	H	11.5
14918.400000	53.40	---	74.00	20.60	V	10.6
14918.400000	---	47.02	54.00	6.98	V	10.6
17160.000000	55.22	---	74.00	18.78	H	10.8
17160.000000	---	43.86	54.00	10.14	H	10.8
17977.600000	---	46.24	54.00	7.76	H	11.7
17977.600000	53.28	---	74.00	20.72	H	11.7

High Channel: 2480 MHz**Common Information**

Project No.: RKSA251106001
 EUT Model: UT5 Ultra X US
 Test Mode: Transmitting in BT_1DH5 mode High channel
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 17.8℃
 Humidity: 44%
 Atmospheric Pressure: 103.1kPa
 Test Engineer: Destine Hu
 Test Date: 2025/11/23

Full Spectrum

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
11924.800000	---	44.39	54.00	9.61	H	8.9
11924.800000	54.92	---	74.00	19.08	H	8.9
13476.800000	55.56	---	74.00	18.44	H	9.9
13476.800000	---	44.39	54.00	9.61	H	9.9
14016.000000	---	45.57	54.00	8.43	H	11.1
14016.000000	56.37	---	74.00	17.63	H	11.1
14817.600000	57.32	---	74.00	16.68	V	10.9
14817.600000	---	45.54	54.00	8.46	V	10.9
17040.000000	---	44.83	54.00	9.17	V	10.9
17040.000000	56.17	---	74.00	17.83	V	10.9
17948.800000	52.79	---	74.00	21.21	H	11.6
17948.800000	---	46.04	54.00	7.96	H	11.6


$\pi/4$ -DQPSK:

Low Channel: 2402 MHz

Common Information

Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_2DH5 mode Low channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8℃
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μV/m)	Average (dB μV/m)	Limit (dB μV/m)	Margin (dB)	Pol	Corr. (dB/m)
12092.800000	---	45.12	54.00	8.88	H	9.0
12092.800000	54.69	---	74.00	19.31	H	9.0
13067.200000	---	44.68	54.00	9.32	H	9.3
13067.200000	55.09	---	74.00	18.91	H	9.3
14017.600000	---	46.02	54.00	7.98	H	11.1
14017.600000	56.14	---	74.00	17.86	H	11.1
14796.800000	---	45.24	54.00	8.76	V	11.0
14796.800000	55.54	---	74.00	18.46	V	11.0
16998.400000	---	44.57	54.00	9.43	H	11.0
16998.400000	55.72	---	74.00	18.28	H	11.0
17972.800000	53.62	---	74.00	20.38	V	11.7
17972.800000	---	46.18	54.00	7.82	V	11.7

Middle Channel: 2441 MHz**Common Information**

Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_2DH5 mode Middle channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8°C
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
12177.600000	---	44.25	54.00	9.75	V	9.0
12177.600000	55.06	---	74.00	18.94	V	9.0
14017.600000	---	45.76	54.00	8.24	V	11.1
14017.600000	56.54	---	74.00	17.46	V	11.1
14312.000000	---	47.88	54.00	6.12	H	11.6
14312.000000	55.40	---	74.00	18.60	H	11.6
14926.400000	---	46.12	54.00	7.88	H	10.5
14926.400000	55.52	---	74.00	18.48	H	10.5
17040.000000	---	44.18	54.00	9.82	V	10.9
17040.000000	54.69	---	74.00	19.31	V	10.9
17971.200000	53.20	---	74.00	20.80	H	11.7
17971.200000	---	45.68	54.00	8.32	H	11.7

High Channel: 2480 MHz**Common Information**

Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_2DH5 mode High channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8°C
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
12099.200000	---	44.20	54.00	9.80	V	9.0
12099.200000	54.50	---	74.00	19.50	V	9.0
13548.800000	---	45.34	54.00	8.66	H	10.1
13548.800000	55.30	---	74.00	18.70	H	10.1
14052.800000	---	46.15	54.00	7.85	H	11.2
14052.800000	56.53	---	74.00	17.47	H	11.2
14990.400000	---	46.31	54.00	7.69	V	10.3
14990.400000	55.74	---	74.00	18.26	V	10.3
17076.800000	---	44.26	54.00	9.74	V	10.9
17076.800000	54.47	---	74.00	19.53	V	10.9
17939.200000	53.09	---	74.00	20.91	H	11.6
17939.200000	---	45.23	54.00	8.77	H	11.6

8DPSK:**Low Channel: 2402 MHz****Common Information**

Project No.: RKSA251106001
 EUT Model: UT5 Ultra X US
 Test Mode: Transmitting in BT_3DH5 mode Low channel
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 17.8℃
 Humidity: 44%
 Atmospheric Pressure: 103.1kPa
 Test Engineer: Destine Hu
 Test Date: 2025/11/23

Full Spectrum


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
12177.600000	---	43.86	54.00	10.14	H	9.0
12177.600000	54.46	---	74.00	19.54	H	9.0
13548.800000	---	44.80	54.00	9.20	H	10.1
13548.800000	55.84	---	74.00	18.16	H	10.1
14628.800000	---	45.77	54.00	8.23	V	11.5
14628.800000	56.15	---	74.00	17.85	V	11.5
14934.400000	---	46.80	54.00	7.20	H	10.5
14934.400000	54.13	---	74.00	19.87	H	10.5
17483.200000	---	43.35	54.00	10.65	H	10.4
17483.200000	55.04	---	74.00	18.96	H	10.4
17960.000000	53.32	---	74.00	20.68	H	11.7
17960.000000	---	46.23	54.00	7.77	H	11.7

Middle Channel: 2441 MHz**Common Information**

Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_3DH5 mode Middle channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8°C
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
11868.800000	---	44.04	54.00	9.96	V	8.8
11868.800000	55.54	---	74.00	18.46	V	8.8
13137.600000	---	44.50	54.00	9.50	V	9.4
13137.600000	54.90	---	74.00	19.10	V	9.4
13574.400000	---	45.93	54.00	8.07	H	10.1
13574.400000	55.46	---	74.00	18.54	H	10.1
14830.400000	---	45.75	54.00	8.25	H	10.9
14830.400000	56.12	---	74.00	17.88	H	10.9
17038.400000	---	44.63	54.00	9.37	H	10.9
17038.400000	54.98	---	74.00	19.02	H	10.9
17929.600000	53.25	---	74.00	20.75	V	11.6
17929.600000	---	45.98	54.00	8.02	V	11.6

High Channel: 2480 MHz**Common Information**

Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_3DH5 mode High channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8℃
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23


Full Spectrum

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
12292.800000	---	43.55	54.00	10.45	V	8.9
12292.800000	54.44	---	74.00	19.56	V	8.9
12934.400000	---	44.69	54.00	9.31	V	9.1
12934.400000	54.47	---	74.00	19.53	V	9.1
14078.400000	---	45.23	54.00	8.77	H	11.2
14078.400000	56.37	---	74.00	17.63	H	11.2
14571.200000	---	46.85	54.00	7.15	H	11.7
14571.200000	54.00	---	74.00	20.00	H	11.7
16787.200000	---	43.63	54.00	10.37	V	10.1
16787.200000	54.40	---	74.00	19.60	V	10.1
17924.800000	53.93	---	74.00	20.07	V	11.6
17924.800000	---	45.81	54.00	8.19	V	11.6

**Band Edge:
GFSK:****Left Side****Common Information**

Project No.:	RKSA251106001
EUT Model:	UT5 Ultra X US
Test Mode:	Transmitting in BT_1DH5 mode Low channel
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	17.8°C
Humidity:	44%
Atmospheric Pressure:	103.1kPa
Test Engineer:	Destine Hu
Test Date:	2025/11/23


Full Spectrum**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2334.024000	---	34.30	54.00	19.70	H	0.3
2334.024000	46.89	---	74.00	27.11	H	0.3
2377.984000	---	35.58	54.00	18.42	H	0.4
2377.984000	44.30	---	74.00	29.70	H	0.4

Right Side**Common Information**

Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_1DH5 mode High channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8℃
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23

Full Spectrum

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.512000	47.45	---	74.00	26.55	H	0.5
2483.512000	---	40.99	54.00	13.01	H	0.5
2483.608000	48.97	---	74.00	25.03	H	0.5
2483.608000	---	40.89	54.00	13.11	H	0.5


$\pi/4$ -DQPSK:

Left Side

Common Information

Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_2DH5 mode Low channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8℃
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23

Full Spectrum




Critical_Freqs

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2365.664000	44.98	---	74.00	29.02	V	0.3
2365.664000	---	35.72	54.00	18.28	V	0.3
2380.560000	46.49	---	74.00	27.51	V	0.4
2380.560000	---	34.63	54.00	19.37	V	0.4

Right Side**Common Information**

Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_2DH5 mode High channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8°C
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23


Full Spectrum

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.512000	47.24	---	74.00	26.76	V	0.5
2483.512000	---	41.22	54.00	12.78	V	0.5
2483.680000	48.79	---	74.00	25.21	V	0.5
2483.680000	---	38.94	54.00	15.06	V	0.5

8DPSK:**Left Side****Common Information**

Project No.:	RKSA251106001
EUT Model:	UT5 Ultra X US
Test Mode:	Transmitting in BT_3DH5 mode Low channel
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	17.8℃
Humidity:	44%
Atmospheric Pressure:	103.1kPa
Test Engineer:	Destine Hu
Test Date:	2025/11/23


Full Spectrum**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2362.248000	43.83	---	74.00	30.17	H	0.3
2362.248000	---	34.53	54.00	19.47	H	0.3
2375.744000	44.95	---	74.00	29.05	H	0.4
2375.744000	---	33.34	54.00	20.66	H	0.4

Right Side**Common Information**


Project No.: RKSA251106001
EUT Model: UT5 Ultra X US
Test Mode: Transmitting in BT_3DH5 mode High channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 17.8℃
Humidity: 44%
Atmospheric Pressure: 103.1kPa
Test Engineer: Destine Hu
Test Date: 2025/11/23

Full Spectrum

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.512000	---	39.67	54.00	14.33	V	0.5
2483.512000	47.83	---	74.00	26.17	V	0.5
2483.584000	---	39.83	54.00	14.17	V	0.5
2483.584000	47.35	---	74.00	26.65	V	0.5

18 GHz - 25 GHz (Transmitting maximum output power 8DPSK Mode low channel):



Frequency (GHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
20.19	---	38.95	54	15.05	H	12.45
19.63	50.06	---	74	23.94	H	11.95
20.21	---	39.1	54	14.9	V	12.47
20.21	49.87	---	74	24.13	V	12.47

Note: The test distance is 3m. The limit is 74dBμV/m(Peak) and 54dBμV/m(Average).

CHANNEL SEPARATION TEST**Environmental Conditions & Test Information**


Test Date:	2025-12-01
Temperature:	21.2 °C
Relative Humidity:	47 %
ATM Pressure:	102.2 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

EUT operation mode: Transmitting

Mode	Channel	Result (MHz)	Limit (MHz)	Result
GFSK	Low	1.002	0.876	Pass
	Middle	1.000	0.876	Pass
	High	1.000	0.876	Pass


Note: Only GFSK mode result is reported since EDR($\pi/4$ -DQPSK, 8DPSK) has the exact same channel plan.
Limit = 20 dB bandwidth*2/3

BDR (GFSK): Low Channel




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:36:49

BDR (GFSK): Middle Channel



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:44:31

BDR (GFSK): High Channel



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:54:39


20 dB BANDWIDTH TEST**Environmental Conditions & Test Information**

Test Date:	2025-12-01
Temperature:	21.2 °C
Relative Humidity:	47 %
ATM Pressure:	102.2 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

EUT operation mode: Transmitting


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	1.038
	Middle	2441	1.041
	High	2480	1.038
EDR ($\pi/4$-DQPSK)	Low	2402	1.299
	Middle	2441	1.290
	High	2480	1.314
EDR (8DPSK)	Low	2402	1.263
	Middle	2441	1.275
	High	2480	1.272

BDR (GFSK): Middle Channel




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 14:42:27

EDR ($\pi/4$ -DQPSK): Low Channel




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:03:43


EDR ($\pi/4$ -DQPSK): High Channel




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:23:01



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:31:42



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:40:45



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:49:57


QUANTITY OF HOPPING CHANNEL TEST**Environmental Conditions & Test Information**

Test Date:	2025-12-01
Temperature:	21.2 °C
Relative Humidity:	47 %
ATM Pressure:	102.2 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

EUT operation mode: Hopping


Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR ($\pi/4$ -DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15

BDR (GFSK): Number of Hopping Channels




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:59:49

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:03:37

EDR (8DPSK): Number of Hopping Channels



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:09:45

TIME OF OCCUPANCY (DWELL TIME)**Environmental Conditions & Test Information**

Test Date:	2025-12-01
Temperature:	21.2 °C
Relative Humidity:	47 %
ATM Pressure:	102.2 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou


EUT operation mode: Hopping

Mode		Channel	BurstWidth (ms)	TotalHops (Num)	Dwell time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Middle	0.385	320	0.123	0.4	Pass
	DH3		1.647	160	0.264	0.4	Pass
	DH5		2.915	130	0.379	0.4	Pass
EDR ($\pi/4$ -DQPSK)	2DH1		0.395	320	0.126	0.4	Pass
	2DH3		1.656	150	0.248	0.4	Pass
	2DH5		2.925	130	0.380	0.4	Pass
EDR (8DPSK)	3DH1		0.396	320	0.127	0.4	Pass
	3DH3		1.650	160	0.264	0.4	Pass
	3DH5		2.925	120	0.351	0.4	Pass

Note: Dwell time = BurstWidth (Pulse time) * TotalHops


TotalHops (31.6s) = hopping numbers (3.16s)*10

BDR (GFSK): Pulse time, Middle Channel, DH1




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:12:32

BDR (GFSK): Pulse time, Middle Channel, DH3




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:14:05

BDR (GFSK): Pulse time, Middle Channel, DH5




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:15:21

EDR ($\pi/4$ -DQPSK): Pulse time, Middle Channel, 2DH1




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:17:20

EDR ($\pi/4$ -DQPSK): Pulse time, Middle Channel, 2DH3




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:23:23


EDR ($\pi/4$ -DQPSK): Pulse time, Middle Channel, 2DH5




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:24:49



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:26:03




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:27:18




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:36:42


BDR Mode (GFSK):



ProjectNo.:RSA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:11:32




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:13:10



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:14:25


EDR Mode ($\pi/4$ -DQPSK):

Hopping Numbers-2DH1




ProjectNo.:RSA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:15:44

Hopping Numbers-2DH3



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:22:23


Hopping Numbers-2DH5



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:23:56


EDR Mode (8DPSK):

Hopping Numbers-3DH1




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:25:11

Hopping Numbers-3DH3



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:26:26

Hopping Numbers-3DH5



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 17:35:13


PEAK OUTPUT POWER MEASUREMENT**Environmental Conditions & Test Information**

Test Date:	2025-12-01
Temperature:	21.2 °C
Relative Humidity:	47 %
ATM Pressure:	102.2 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

EUT operation mode: Transmitting


Mode	Channel	Frequency (MHz)	Result (dBm)	Limit (dBm)
GFSK	Low	2402	0.03	21
	Middle	2441	-0.04	
	High	2480	0.00	
$\pi/4$ DQPSK	Low	2402	0.74	
	Middle	2441	0.64	
	High	2480	0.71	
8DPSK	Low	2402	1.37	
	Middle	2441	1.27	
	High	2480	1.30	

BDR (GFSK): 2402MHz




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 14:35:04

BDR (GFSK): 2441MHz




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 14:44:07

BDR (GFSK): 2480MHz




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 14:55:25

EDR($\pi/4$ -DQPSK): 2402MHz




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:05:34

EDR($\pi/4$ -DQPSK): 2441MHz




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:15:03

EDR($\pi/4$ -DQPSK): 2480MHz




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:24:40

EDR(8DPSK): 2402MHz




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:33:58

EDR(8DPSK):2441MHz



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:43:56

EDR(8DPSK): 2480MHz



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:51:27

BAND EDGES**Environmental Conditions & Test Information**

Test Date:	2025-12-01
Temperature:	21.2 °C
Relative Humidity:	47 %
ATM Pressure:	102.2 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou


EUT operation mode: Transmitting & Hopping

Test Result: Compliant.

Mode	Channel	Frequency (MHz)	Result (dBc)	Limit (dBc)
GFSK	Low	2402	42.90	20
	High	2480	42.95	
$\pi/4$ DQPSK	Low	2402	43.43	
	High	2480	43.08	
8DPSK	Low	2402	43.46	
	High	2480	42.78	
GFSK (Hopping)	Low	2402	43.35	
	High	2480	42.65	
$\pi/4$ DQPSK (Hopping)	Low	2402	42.52	
	High	2480	43.11	
8DPSK (Hopping)	Low	2402	43.52	
	High	2480	42.06	


Band Edge

BDR (GFSK): Left Side




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:03:36

BDR (GFSK): Right Side




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:07:02

EDR ($\pi/4$ -DQPSK): Left Side




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:14:29

EDR ($\pi/4$ -DQPSK): Right Side




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:16:59

EDR (8DPSK): Left Side




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:26:03


EDR (8DPSK): Right Side




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:28:45

BDR (GFSK): Left Side - Hopping


ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:58:57

BDR (GFSK): Right Side - Hopping


ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:01:06

EDR ($\pi/4$ -DQPSK): Left Side - Hopping


ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:09:25

EDR ($\pi/4$ -DQPSK): Right Side - Hopping

ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:11:31

EDR (8DPSK): Left Side - Hopping

ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:19:22

EDR (8DPSK): Right Side - Hopping

ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 16:23:33


CONDUCTED SPURIOUS EMISSION**Environmental Conditions & Test Information**

Test Date:	2025-12-01
Temperature:	21.2 °C
Relative Humidity:	47 %
ATM Pressure:	102.2 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

Mode	Channel	Result (dB)	Limit (dB)
GFSK	Low	39.83	20.00
	Middle	39.25	20.00
	High	39.20	20.00
$\pi/4$ DQPSK	Low	39.12	20.00
	Middle	38.91	20.00
	High	39.16	20.00
8DPSK	Low	40.02	20.00
	Middle	39.10	20.00
	High	38.18	20.00


Note: the maximum path attenuation of 30MHz~25GHz was added into the offset

GFSK_Low




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 14:41:14

GFSK_Middle




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 14:52:06

GFSK_High




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:02:06

$\pi/4$ DQPSK_Low




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:11:33

$\pi/4$ DQPSK_Middle




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:21:57


$\pi/4$ DQPSK_High




ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:30:02



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:39:41



ProjectNo.:RSHA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:48:55



ProjectNo.:RSA251106001 Tester:Neil Zhou
Date: 1.DEC.2025 15:56:26

EUT PHOTOGRAPHS

Please refer to the attachment EXHIBIT A - EUT EXTERNAL PHOTOGRAPHS and EXHIBIT B - EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment EXHIBIT C - TEST SETUP PHOTOGRAPHS.

Declarations

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with “★”.
2. The test data was only valid for the test sample(s).
3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95.45% confidence interval.
6. This report may contain standards and test items that are not covered by the accreditation scope and shall be marked with an asterisk “▲”.

******* END OF REPORT *******