Appendix B

RF Test Data for 2.4GWIFI (Conducted Measurement)

Product Name: Portable Power Station

Test Model: Singo2000Plus

Environmental Conditions

Temperature:	23.8°C
Relative Humidity:	52.1%
ATM Pressure:	100.0 kPa
Test Engineer:	Andre Tan
Supervised by:	Nick Peng

B.1 -6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant1	8.025	>=0.5	Pass
NVNT	b	2437	Ant1	8.528	>=0.5	Pass
NVNT	b	2462	Ant1	8.07	>=0.5	Pass
NVNT	g	2412	Ant1	16.346	>=0.5	Pass
NVNT	g	2437	Ant1	16.297	>=0.5	Pass
NVNT	g	2462	Ant1	16.318	>=0.5	Pass
NVNT	n20	2412	Ant1	17	>=0.5	Pass
NVNT	n20	2437	Ant1	17.093	>=0.5	Pass
NVNT	n20	2462	Ant1	17.119	>=0.5	Pass

Test Graphs

-6dB Bandwidth NVNT b 2412MHz Ant1



-6dB Bandwidth NVNT b 2437MHz Ant1



-6dB Bandwidth NVNT b 2462MHz Ant1



-6dB Bandwidth NVNT g 2412MHz Ant1



-6dB Bandwidth NVNT g 2437MHz Ant1



-6dB Bandwidth NVNT g 2462MHz Ant1



-6dB Bandwidth NVNT n20 2412MHz Ant1



-6dB Bandwidth NVNT n20 2437MHz Ant1



-6dB Bandwidth NVNT n20 2462MHz Ant1



B.2 Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	Ant1	15.01	30	Pass
NVNT	b	2437	Ant1	15.39	30	Pass
NVNT	b	2462	Ant1	15.70	30	Pass
NVNT	g	2412	Ant1	14.74	30	Pass
NVNT	g	2437	Ant1	14.62	30	Pass
NVNT	g	2462	Ant1	14.30	30	Pass
NVNT	n20	2412	Ant1	13.04	30	Pass
NVNT	n20	2437	Ant1	14.20	30	Pass
NVNT	n20	2462	Ant1	13.67	30	Pass

B.3 Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	Ant1	-9.12	8	Pass
NVNT	b	2437	Ant1	-5.49	8	Pass
NVNT	b	2462	Ant1	-8.57	8	Pass
NVNT	g	2412	Ant1	-15.85	8	Pass
NVNT	g	2437	Ant1	-16.00	8	Pass
NVNT	g	2462	Ant1	-16.77	8	Pass
NVNT	n20	2412	Ant1	-17.13	8	Pass
NVNT	n20	2437	Ant1	-16.91	8	Pass
NVNT	n20	2462	Ant1	-16.36	8	Pass

Test Graphs

PSD NVNT b 2412MHz Ant1



PSD NVNT b 2437MHz Ant1



PSD NVNT b 2462MHz Ant1



PSD NVNT g 2412MHz Ant1



PSD NVNT g 2437MHz Ant1



PSD NVNT g 2462MHz Ant1



PSD NVNT n20 2412MHz Ant1



PSD NVNT n20 2437MHz Ant1



PSD NVNT n20 2462MHz Ant1



B.4 Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-50.34	-20	Pass
NVNT	b	2462	Ant1	-58.97	-20	Pass
NVNT	g	2412	Ant1	-32.69	-20	Pass
NVNT	g	2462	Ant1	-42.84	-20	Pass
NVNT	n20	2412	Ant1	-31.99	-20	Pass
NVNT	n20	2462	Ant1	-38.74	-20	Pass

Test Graphs

Band Edge NVNT b 2412MHz Ant1 Ref



Band Edge NVNT b 2412MHz Ant1 Emission



Band Edge NVNT b 2462MHz Ant1 Ref



Band Edge NVNT b 2462MHz Ant1 Emission



Band Edge NVNT g 2412MHz Ant1 Ref



Band Edge NVNT g 2412MHz Ant1 Emission



Band Edge NVNT g 2462MHz Ant1 Ref



Band Edge NVNT g 2462MHz Ant1 Emission



Band Edge NVNT n20 2412MHz Ant1 Ref



Band Edge NVNT n20 2412MHz Ant1 Emission



Band Edge NVNT n20 2462MHz Ant1 Ref



Band Edge NVNT n20 2462MHz Ant1 Emission



B.5 Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-51.1	-20	Pass
NVNT	b	2437	Ant1	-50.22	-20	Pass
NVNT	b	2462	Ant1	-51.27	-20	Pass
NVNT	g	2412	Ant1	-43.8	-20	Pass
NVNT	g	2437	Ant1	-45.34	-20	Pass
NVNT	g	2462	Ant1	-42.99	-20	Pass
NVNT	n20	2412	Ant1	-42.7	-20	Pass
NVNT	n20	2437	Ant1	-43.19	-20	Pass
NVNT	n20	2462	Ant1	-43.17	-20	Pass

Test Graphs

Tx. Spurious NVNT b 2412MHz Ant1 Ref



Tx. Spurious NVNT b 2412MHz Ant1 Emission



Tx. Spurious NVNT b 2437MHz Ant1 Ref



Tx. Spurious NVNT b 2437MHz Ant1 Emission



Tx. Spurious NVNT b 2462MHz Ant1 Ref



Tx. Spurious NVNT b 2462MHz Ant1 Emission