

- | | | |
|-----------|-----------------|----------------|
| 1.手机夹/散热器 | 2.可调节摄像头 | 3.遥控器 |
| 4.七彩灯 | 5.手掌开始屏幕键 | 6.开机键 |
| 7.七彩灯按键 | 8.底座1/4接口 | 9.底座 |
| 10.散热器开关 | 11.散热器Type-c充电口 | 12.云台Type-c充电口 |

1. 长按开机/关机
2. 连接蓝牙名称: Self
3. 一按拍照

1. 长按开机/关机
 2. 连接蓝牙名称: Selfie
 3. 一按拍照
-
3. 遥控器
 6. 开关机键
 9. 底座
 12. 云台Type-C充电口



- 充电**
 - 在充满电需充电3小时左右
 - 充电器充满电(红色灯熄灭)即可快速充电
 - 充电器中指示灯显示绿色时
 - 充电器中指示灯显示红灯颜色不影响状况
 - 充电器中指示灯显示红灯颜色不影响状况
- 按键说明**
 - **开机键:**
 - 长按开/关机
 - 单击电源键(红灯熄灭)后旋转360°全黑
 - 长按至全黑前,恢复到巡航状态
 - **七档灯调:**
 - 单击电源键七次灯,双向向巡航状态
 - **手车锁:**
 - 单击电源键手车功能(P24下方)灯光熄灭 双向向巡航
 - **挂挡盒:**
 - 挂挡盒:轻碰挂挡上下两可控制档位距离固定约0.5-3米内使用
 - 手车识别距离约0.5-1.5米为最佳
 - **远端遥控无线蓝牙耳麦、无绳上网APP:**
 - 手机软件安装蓝牙,开启即可

型号	Q15
品名	散热器智能跟拍云台
材料	ABS+电子元件
产品净重	270g
产品尺寸	88*82*206mm(含底座)
云台供电参数	Type-C 5V 1A
散热器供电参数	Type-C 5V 3A
可控角度范围	左右(航向)360°无限制

360 Smart Shooting Gimbal

It follows the gimbal



Operating interface



1. Phone designated
2. Adjustable camera
3. Remote control
4. Control lights
5. Palm start locking key
6. Power on/off button
7. Rainbow light button
8. Base 1/4 interface
9. Base
10. Heat sink switch
11. Heat sink Type-c charging port
12. Gimbal Type-c charging port

Remote controller



1. Press and hold to power on/off
2. Connect Bluetooth name: Safe
3. Click to take a picture

Operating instruction



Charging

- It takes about 3 hours to fully charge the fundaw
- Low power warning (battery <10%) The red light is blinking rapidly/charging the indicator is red (the color of the indicator light does not affect the state in different states.)
- Fully charged: The indicator is off

Key description

- Power button: Press and hold to turn on/off. Click twice to follow (steady red) Double-click for panorama. Click Stop Cruise to return to cruise status. Click to turn off the seven lights and double-click to turn on the light.
- Palm key: Click the palm gesture function (blinking 4 times with blue light only) and double-click the direction Port cruising.
- Standing Angle: Wedge the lens up and down to follow the distance suggestion. Use within 0.5-1.5 meters.
- Gesture recognition distance: 0.5-1.5 meters is the best.
- No need to connect Bluetooth. Download APP for tracking starting.
- Mobile phone software is fully compatible. Just open it.
- Tracking the gameplay of photos, videos, live broadcasts, video calls, etc.

Product specifications and parameters

model	Q15
Product Name	Intelligent follow-up gimbal for radiator
material	ABS+electronic components
Net weight	270g
Product size	88 * 82 * 206mm (including base)
PTZ charging parameters	Type-C 5V 1A
Power supply parameters for radiator	Type-C 5V 3A
Controllable angle range	360° left and right (heading) without restrictions

FCC Warning Statement

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation. The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.