

FCC CERTIFICATION TEST REPORT

Applicant	:	Tiandy Technologies Co., Ltd.
Address	:	No.8,Haitai Huake Rd2 (outside ring road) Huayuan New Technology Industrial Park
Manufacturer	:	Tiandy Technologies Co., Ltd.
Address	:	No.8,Haitai Huake Rd2 (outside ring road) Huayuan New Technology Industrial Park
Equipment under Test	:	PT Camera
Model No.	:	TC-L2,TC-H322A,TC-H332A,TC-H342A,TC-H352A,TC-H362A,TC-H382A,TC-H3102A,TC-H3A2A,TC-H3B2A,TC-H3C2A,TC-H322C,TC-H332C,TC-H342C,TC-H352C,TC-H362C,TC-H382C,TC-H3102C,TC-H3A2C,TC-H3B2C,TC-H3C2C,TC-H322D,TC-H332D,TC-H342D,TC-H352D,TC-H362D,TC-H382D,TC-H3102D,TC-H3A2D,TC-H3B2D,TC-H3C2D,TC-H322E,TC-H332E,TC-H342E,TC-H352E,TC-H362E,TC-H382E,TC-H3102E,TC-H3A2E,TC-H3B2E,TC-H3C2E,TC-H322N,TC-H332N,TC-H342N,TC-H352N,TC-H362N,TC-H382N,TC-H3A2N,TD-H622N,TD-H632N,TD-H642N,TD-H652N,TD-H662N,TD-H672N,TD-H682N,TD-H692N,TD-H6A2N,TD-H6112N,TD-H6N2N,TD-H6B2N,TD-H672A,TD-H622A,TD-H632A,TD-H642A,TD-H652A,TD-H662A,TD-H672A,TD-H682A,TD-H692A,TD-H6112A,TD-H6A2A,TD-H6B2A,TD-H6C2A,TD-H672C,TD-H632C,TD-H642C,TD-H652C,TD-H662C,TD-H692C,TD-H6112C,TD-H6A2C,TD-H6B2C,TD-H6C2C,TD-H672D,TD-H632D,TD-H642D,TD-H652D,TD-H662D,TD-H692D,TD-H6112D,TD-H6A2D,TD-H6B2D,TD-H6C2D,TD-H672E,TD-H632E,TD-H642E,TD-H652E,TD-H662E,TD-H692E,TD-H6112E,TD-H6A2E,TD-H6B2E,TD-H6C2E
Trade Mark	:	Tiandy
FCC ID	:	2BKEDTC-H342A
IC	:	N/A
Report No.	:	LS-R26012006-3F01
Issue Date	:	Mar. 30, 2026

LabSure Testing Services (Tianjin) Co., Ltd.



TABLE OF CONTENTS

1.	Summary of Test Results	6
2.	General Test Information	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT	8
2.3.	Assistant equipment used for test	8
2.4.	Block diagram of EUT configuration for test	8
2.5.	Deviations of test standard	8
2.6.	Test environment conditions	9
2.7.	Test laboratory	9
2.8.	Measurement uncertainty	10
3.	Equipment Used During Test	11
4.	6 dB Bandwidth and 99% Bandwidth	12
4.1.	Block diagram of test setup	12
4.2.	Limits	12
4.3.	Test procedure	12
4.4.	Test result	12
5.	Duty Cycle	13
5.1.	Block diagram of test setup	13
5.2.	Limit	13
5.3.	Test procedure	13
5.4.	Test result	13
6.	Maximum Peak Output Power	14
6.1.	Block diagram of test setup	14
6.2.	Limits	14
6.3.	Test procedure	14
6.4.	Test result	14
7.	Power Spectral Density	15
7.1.	Block diagram of test setup	15
7.2.	Limits	15
7.3.	Test procedure	15
7.4.	Test result	15
8.	Band Edge Compliance (Conducted Method)	16
8.1.	Block diagram of test setup	16
8.2.	Limits	16
8.3.	Test procedure	16
8.4.	Test result	16
9.	Radiated Emission	17
9.1.	Block diagram of test setup	17
9.2.	Limit	18
9.3.	Test Procedure	19
9.4.	Test result	21
10.	RF Conducted Spurious Emissions	62
10.1.	Block diagram of test setup	62
10.2.	Limits	62
10.3.	Test procedure	62
10.4.	Test result	62
11.	Band Edge Compliance (Radiated Method)	63
11.1.	Block diagram of test setup	63
11.2.	Limit	63
11.3.	Test Procedure	63
11.4.	Test result	63
12.	Power Line Conducted Emission	76
12.1.	Block diagram of test setup	76
12.2.	Power line conducted emission limits	76
12.3.	Test procedure	76

12.4. Test result	77
13. Antenna Requirements	80
13.1. Limit	80
13.2. Result	80
14. Test Setup Photograph.....	81
15. Photos of the EUT	82

Test Report Declare

Applicant	:	Tiandy Technologies Co., Ltd.
Address	:	No.8,Haitai Huake Rd2 (outside ring road) Huayuan New Technology Industrial Park
Equipment under Test	:	PT Camera
Model No.	:	TC-L2,TC-H322A,TC-H332A,TC-H342A,TC-H352A,TC-H362A,TC-H382A,TC-H3102A,TC-H3A2A,TC-H3B2A,TC-H3C2A,TC-H322C,TC-H332C,TC-H342C,TC-H352C,TC-H362C,TC-H382C,TC-H3102C,TC-H3A2C,TC-H3B2C,TC-H3C2C,TC-H322D,TC-H332D,TC-H342D,TC-H352D,TC-H362D,TC-H382D,TC-H3102D,TC-H3A2D,TC-H3B2D,TC-H3C2D,TC-H322E,TC-H332E,TC-H342E,TC-H352E,TC-H362E,TC-H382E,TC-H3102E,TC-H3A2E,TC-H3B2E,TC-H3C2E,TC-H322N,TC-H332N,TC-H342N,TC-H352N,TC-H362N,TC-H382N,TC-H3A2N,TD-H622N,TD-H632N,TD-H642N,TD-H652N,TD-H662N,TD-H672N,TD-H682N,TD-H692N,TD-H6A2N,TD-H6112N,TD-H6N2N,TD-H6B2N,TD-H672A,TD-H622A,TD-H632A,TD-H642A,TD-H652A,TD-H662A,TD-H672A,TD-H682A,TD-H692A,TD-H6112A,TD-H6A2A,TD-H6B2A,TD-H6C2A,TD-H672C,TD-H632C,TD-H642C,TD-H652C,TD-H662C,TD-H692C,TD-H6112C,TD-H6A2C,TD-H6B2C,TD-H6C2C,TD-H672D,TD-H632D,TD-H642D,TD-H652D,TD-H662D,TD-H692D,TD-H6112D,TD-H6A2D,TD-H6B2D,TD-H6C2D,TD-H672E,TD-H632E,TD-H642E,TD-H652E,TD-H662E,TD-H692E,TD-H6112E,TD-H6A2E,TD-H6B2E,TD-H6C2E
Trade Mark	:	Tiandy
Manufacturer	:	Tiandy Technologies Co., Ltd.
Address	:	No.8,Haitai Huake Rd2 (outside ring road) Huayuan New Technology Industrial Park

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C.

Test Procedure Used:

ANSI C63.10:2020.

We Declare:

The equipment described above is tested and assessed by LabSure Testing Services (Tianjin) Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The tested and assessed results are contained in this test report and LabSure Testing Services (Tianjin) Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assessments.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No.:	LS-R26012006-3F01		
Date of Receipt:	Mar. 02, 2026	Date of Test:	Mar. 02, 2026

Prepared By:

Tom Liu

Tom Liu/Engineer

Reviewed By:

Ethan Bao

Ethan Bao/Engineer

Authorized By:

Aaron Zhang

Aaron Zhang/Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of LabSure Testing Services (Tianjin) Co., Ltd.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Mar. 30, 2026	

1. Summary of Test Results

Description of Test Item	Standard	Verdict
6dB Bandwidth and 99% Bandwidth	FCC 15.247 (a) (2)	Pass
Maximum Conducted Output Power	FCC 15.247 (b) (3)	Pass
Power Spectral Density	FCC 15.247 (e)	Pass
Band-edge and Spurious Emissions (Conducted)	FCC 15.247 (d)	Pass
Radiated Spurious Emissions	FCC 15.247 (d) FCC 15.209 FCC 15.205	Pass
Radiated Band Edge Compliance	FCC 15.247 (d) FCC 15.209 FCC 15.205	Pass
Power Line Conducted Emission	FCC 15.207	Pass
Antenna Requirement	FCC 15.203	Pass

2. General Test Information

2.1. Description of EUT

EUT Name	: PT Camera
Model Number	: TC-L2, TC-H322A, TC-H332A, TC-H342A, TC-H352A, TC-H362A, TC-H382A, TC-H3102A, TC-H3A2A, TC-H3B2A, TC-H3C2A, TC-H322C, TC-H332C, TC-H342C, TC-H352C, TC-H362C, TC-H382C, TC-H3102C, TC-H3A2C, TC-H3B2C, TC-H3C2C, TC-H322D, TC-H332D, TC-H342D, TC-H352D, TC-H362D, TC-H382D, TC-H3102D, TC-H3A2D, TC-H3B2D, TC-H3C2D, TC-H322E, TC-H332E, TC-H342E, TC-H352E, TC-H362E, TC-H382E, TC-H3102E, TC-H3A2E, TC-H3B2E, TC-H3C2E, TC-H322N, TC-H332N, TC-H342N, TC-H352N, TC-H362N, TC-H382N, TC-H3A2N, TD-H622N, TD-H632N, TD-H642N, TD-H652N, TD-H662N, TD-H672N, TD-H682N, TD-H692N, TD-H6A2N, TD-H6112N, TD-H6N2N, TD-H6B2N, TD-H672A, TD-H622A, TD-H632A, TD-H642A, TD-H652A, TD-H662A, TD-H672A, TD-H682A, TD-H692A, TD-H6112A, TD-H6A2A, TD-H6B2A, TD-H6C2A, TD-H672C, TD-H632C, TD-H642C, TD-H652C, TD-H662C, TD-H692C, TD-H6112C, TD-H6A2C, TD-H6B2C, TD-H6C2C, TD-H672D, TD-H632D, TD-H642D, TD-H652D, TD-H662D, TD-H692D, TD-H6112D, TD-H6A2D, TD-H6B2D, TD-H6C2D, TD-H672E, TD-H632E, TD-H642E, TD-H652E, TD-H662E, TD-H692E, TD-H6112E, TD-H6A2E, TD-H6B2E, TD-H6C2E
Model Difference	: Models applied for this application are the equipment color, sales area and sales man, which do not affect the material, electromagnetic compatibility and safety electrical performance of the product.
Test Model Number	: TC-H342A
EUT Function Description	: Please reference user manual of this device
Power Supply	: AC 120V/60Hz
Radio Specification	: IEEE 802.11b/g/n
Operation Frequency	: IEEE 802.11b: 2412MHz-2462MHz IEEE 802.11g: 2412MHz-2462MHz IEEE 802.11n HT20: 2412MHz-2462MHz
Modulation	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Transmitter Rate	: IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n: MCS0~MCS7
Antenna Type	: PCB antenna, maximum PK gain: 2.25 dBi
Sample Number	: Y26012006-03

Note: EUT is the ab. of equipment under test.

Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

Remark: The information in this section is provided by the applicant or manufacturer, the laboratory is not liable to the accuracy, suitability, reliability or/and integrity of the information.

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Description	Remark
N/A	N/A	N/A	N/A	N/A

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	SN
Notebook	Lenovo Beijing Co. Ltd.	ThinkPad E450c	N/A	TP00067A

2.4. Block diagram of EUT configuration for test



The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

Test software: MobaXterm_Personal_22.1

Tested mode, channel, setting Tx power and rand data rate information				
Mode	Setting Tx Power	Data rate (Mbps) (See Note)	Channel	Frequency (MHz)
IEEE 802.11b	Default	1	LCH: CH1	2412
	Default	1	MCH: CH6	2437
	Default	1	HCH: CH11	2462
IEEE 802.11g	Default	6	LCH: CH1	2412
	Default	6	MCH: CH6	2437
	Default	6	HCH: CH11	2462
IEEE 802.11n HT20	Default	MCS 0	LCH: CH1	2412
	Default	MCS 0	MCH: CH6	2437
	Default	MCS 0	HCH: CH11	2462

Note1: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25 °C
Humidity range:	25-75%
Pressure range:	86-106 kPa

2.7. Test laboratory

LabSure Testing Services (Tianjin) Co., Ltd.

Address: Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park Development Area, Tianjin, China.

Tel: +86-22-58038033, www.lab-sure.com, E-mail: labsure@lab-sure.com

NVLAP (National Voluntary Laboratory Accreditation Program) CODE: 500036-0

CNAS (China National Accreditation Service for Conformity Assessment) CODE: L13402

FCC Designation Number: CN5004; FCC Test Firm Registration Number: 368676

ISED (Innovation, Science and Economic Development Canada) Company Number: 27768

Conformity Assessment Body Identifier: CN0125

VCCI Facility Registration Number: C-20089, T-20093, R-20125, G-20122

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	0.14%
Peak Output Power (Conducted) (Spectrum Analyzer)	0.12 dB (10 MHz $\leq$ f < 3.6 GHz); 0.32 dB (3.6 GHz $\leq$ f < 8 GHz)
Peak Output Power (Conducted) (Power Sensor)	0.51 dB
Power Spectral Density	0.12 dB (10 MHz $\leq$ f < 3.6 GHz); 0.32 dB (3.6 GHz $\leq$ f < 8 GHz)
Frequencies Stability	6.7×10^{-8} (Antenna couple method) 3.4×10^{-8} (Conducted method)
Conducted Spurious Emissions	0.12 dB (10 MHz $\leq$ f < 3.6 GHz); 0.32 dB (3.6 GHz $\leq$ f < 8 GHz) 0.52 dB (8 GHz $\leq$ f < 22 GHz)
Uncertainty for Radio Frequency (RBW < 20 kHz)	3×10^{-7}
Temperature	$\pm 2^{\circ}\text{C}$
Humidity	$\pm 1\%$
Uncertainty for Radiation Emission Test (30 MHz - 1 GHz)	2.72 dB (Antenna Polarize: V) 2.72 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission Test (1 GHz - 40 GHz)	2.74 dB (1 - 6 GHz) 2.72 dB (6 GHz - 18 GHz) 3.54 dB (18 GHz - 26 GHz) 4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power Line Conduction Emission Test	3.40 dB (150 kHz - 30 MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test (MWRFTest system)					
EXG Analog Signal Generator	Keysight	N5173B	MY53270968	2026/02/11	1 Year
MXG Vector Signal Generator	Keysight	N5182A	MY50143288	2026/02/11	1 Year
PXA Signal Analyzer	Keysight	N9030B	MY56320639	2026/03/14	1 Year
PXA Signal Analyzer	Keysight	N9010A	MY53281492	2026/02/11	1 Year
Wideband Radio Communication Tester	R&S	CMW500	158800	2026/02/11	1 Year
Power Sensor	KEYSIGHT	U2021XA	MY59150007	2026/02/11	1 Year
Test Software	MWRFTest	MTS8310	V03	N/A	N/A
Radiated Emission -10m EMI Chamber					
Broadband Horn Antenna	TESEQ	BHA 9118	31754	2025/09/29	1 Year
Broad Band Horn Antenna	Com-Power	AHA-840	10100024	2025/10/10	2 Year
Active Loop Antenna	R&S	HFH2-Z2	100269	2024/08/25	2 Year
Amplifier	CMO-MW	DPA8 1000 1800	09211739	2026/02/11	1 Year
EMI Test Receiver	R&S	ESCI	101024	2026/02/11	1 Year
EMI Test Receiver	R&S	ESCI	101030	2026/02/11	1 Year
EMI Test Receiver	R&S	ESU26	100244	2026/02/11	1 Year
EXA Signal Analyzer	Keysight	N9010A	MY53281492	2026/02/11	1 Year
Bilog Antenna	TESEQ	CBL6112D	29068	2024/10/10	2 Year
Bilog Antenna	TESEQ	CBL6112D	29069	2024/10/10	2 Year
Amplifier	Sonoma	310N	300913	2026/02/11	1 Year
Amplifier	Sonoma	310N	334532	2026/02/11	1 Year
Ant Mast	Innco	MA4000	N/A	N/A	N/A
Ant Mast	Innco	MA4000	N/A	N/A	N/A
Mast Controller	Innco	CO2000	N/A	N/A	N/A
Mast Controller	Innco	CO2000	N/A	N/A	N/A
RF Selector 4CH	TOYO	NS4904N	Selector1	N/A	N/A
RF Selector 4CH	TOYO	NS4904N	Selector2	N/A	N/A
Test software	TOYO	EP5/RSE	Ver 1.9.1	N/A	N/A
Test software	Audix	E3	V 6.11111b	N/A	N/A
Power Line Conducted Emissions Test					
Test Receiver	R&S	ESCI	100375	2026/02/11	1 Year
LISN	R&S	ENV216	101122	2026/02/11	1 Year
Test software	TOYO	EP5/CE	V 5.4.40	N/A	N/A

4. 6 dB Bandwidth and 99% Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) 99% Bandwidth set the spectrum analyzer as follows:

RBW:	1% to 5% of the OBW
VBW:	Three times the RBW
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) 6 dB Bandwidth set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(4) Allow the trace to stabilize, measure the 6 dB and 99% bandwidth of signal.

4.4. Test result

Pass

Please find the detailed data in APPENDIXES-WLAN.

5. Duty Cycle

5.1. Block diagram of test setup

Same as section 4.1

5.2. Limit

Just for Report.

5.3. Test procedure

(1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.

set the Spectrum Analyzer as below:

Centre Frequency: The center frequency of the middle hopping channel.

Resolution BW: 1 MHz.

Video BW: 3 MHz.

Span: Zero span.

Detector: Peak.

Trace Mode: Free Run

Sweep: Single

(2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.

(3) Calculate dwell time follow below formula:

Duty cycle= Pulse's on time / Burst cycle

5.4. Test result

Please find the detailed data in APPENDIXES-WLAN

6. Maximum Peak Output Power

6.1. Block diagram of test setup

Same with 4.1

6.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3. Test procedure

- (1). The test according to ANSI C63.10-2020 clause 11.9.1.2
- (2). The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast responding diode detector.

6.4. Test result

Pass

Please find the detailed data in APPENDIXES-WLAN.

7. Power Spectral Density

7.1. Block diagram of test setup

Same with 4.1

7.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.

(4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

(5) Add $[10 \log (1 / D)]$, where D is the duty cycle measured in step a), to the measured PSD to compute the average PSD during the actual transmission time.

7.4. Test result

Pass

Please find the detailed data in APPENDIXES-WLAN.

8. Band Edge Compliance (Conducted Method)

8.1. Block diagram of test setup

Same with 4.1

8.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

8.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100 kHz
VBW:	300 kHz
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span/RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

8.4. Test result


Pass

Please find the detailed data in APPENDIXES-WLAN.


9. Radiated Emission

9.1. Block diagram of test setup


Anechoic Chamber, test setup diagram for 9 kHz - 30 MHz:



Anechoic Chamber, test setup diagram for 30 MHz - 1 GHz:



Anechoic Chamber, test setup diagram for frequency above 1 GHz:



Note: For harmonic emissions test an appropriate high pass filter was inserted in the input port of AMP.

9.2. Limit

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6

(3) FCC 15.209

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	$2400/\text{F}(\text{kHz})$	$67.6-20\log(\text{F})$
0.490 ~ 1.705	30	$24000/\text{F}(\text{kHz})$	$87.6-20\log(\text{F})$
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V}/\text{m}) + 40\log(30\text{m}/3\text{m})$$

(4) Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209 & RSS-GEN, all the other emissions shall be at least 20dB below the fundamental emissions or comply with 15.209 limits.

9.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.
- (2) Test antenna was located on an adjustable mast, the distance from test antenna to EUT and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna (1 GHz - 18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna (18 GHz - 40 GHz)	3 m

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for

maximum response at each azimuth position around the EUT. And the loop antenna also is positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2020 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2020 clause 4.1.4.2.2 procedure for average measure.

(8) X axis, Y axis, Z axis are tested, and worse setup X axis is reported.

9.4. Test result

Pass. (See below detailed test result)

All the emissions were comply with 15.209 limits.

Note1: For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in transmitting mode.

Note2: For emissions above 1 GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

Note3: Scan with all modes, the worst case was recorded in this report.

Radiated Emission test (9KHz-30M)

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-18-2026

Tested By : Tom


EUT : PT Camera

Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : TX

Memo : 11B 1M 2412MHz




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detect or	Polarization
1	0.091	30.12	19.70	0.03	49.85	108.43	-58.58	Peak	HORIZONTAL
2	0.192	23.15	19.61	0.04	42.80	101.95	-59.15	Peak	HORIZONTAL
3	0.674	28.60	19.83	0.06	48.49	71.03	-22.54	Peak	HORIZONTAL
4	1.052	28.65	19.99	0.07	48.71	67.16	-18.45	Peak	HORIZONTAL
5	3.384	23.33	19.96	0.15	43.44	69.54	-26.10	Peak	HORIZONTAL
6	15.934	18.46	19.98	0.26	38.70	69.54	-30.84	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: 9k-150kHz, RBW: 300Hz; 150k-30Mhz, RBW: 10kHz, Sweep time: auto.

Radiated Emission test (below 1 GHz)



Spectrum Selection

No.	Frequency [MHz]	(P)	Reading [dB (μV)]	c. f [dB(1/m)]	Result PK [dB (μV/m)]	Limit QP [dB (μV/m)]	Margin QP [dB]	Height [cm]	Angle [°]	System
1	53.886	V	45.3	-15.3	30.0	40.0	10.0	100.0	94.0	2
2	389.021	V	38.7	-2.4	36.3	46.0	9.7	100.0	69.0	2
3	454.011	V	34.8	-0.6	34.2	46.0	11.8	100.0	24.6	2
4	298.448	H	41.4	-7.3	34.1	46.0	11.9	100.0	37.3	1
5	392.053	H	37.2	-3.7	33.5	46.0	12.5	100.0	23.9	1
6	30.485	H	28.1	-4.8	23.3	40.0	16.7	100.0	23.9	1

Note) Receiving antenna polarization: Horizontal and/or Vertical

Test Distance: 10 m, Antenna Height: 1 m to 4 m

Level QP (Quasi-Peak) = Reading QP + Factor (Antenna Factor + Cable Loss - Amp. Gain)

Margin QP (Quasi-Peak) = Limit - Level QP

Radiated Emission test (above 1 GHz)

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2412MHz ANT1

Data: 51



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	1198.00	50.75	24.67	43.66	3.03	34.79	74.00	-39.21	Peak	HORIZONTAL
2	1764.00	50.87	27.07	43.83	3.54	37.65	74.00	-36.35	Peak	HORIZONTAL
3	2058.00	48.27	28.31	43.88	3.80	36.50	74.00	-37.50	Peak	HORIZONTAL
4	2256.00	51.90	28.35	43.82	3.98	40.41	74.00	-33.59	Peak	HORIZONTAL
5	2492.00	52.78	28.40	43.75	4.22	41.65	74.00	-32.35	Peak	HORIZONTAL
6	2856.00	48.18	29.40	43.64	4.55	38.49	74.00	-35.51	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2412MHz ANT1

Data: 52



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	1196.00	49.32	24.67	43.66	3.05	33.38	74.00	-40.62	Peak	VERTICAL
2	1382.00	48.59	25.30	43.71	3.13	33.31	74.00	-40.69	Peak	VERTICAL
3	1754.00	55.61	27.02	43.83	3.51	42.31	74.00	-31.69	Peak	VERTICAL
4	1958.00	47.38	28.08	43.89	3.66	35.23	74.00	-38.77	Peak	VERTICAL
5	2808.00	48.06	29.26	43.66	4.51	38.17	74.00	-35.83	Peak	VERTICAL
6	2962.00	48.23	29.69	43.61	4.65	38.96	74.00	-35.04	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2412MHz ANT1

Data: 53



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4830.00	54.15	33.29	42.68	6.86	51.62	74.00	-22.38	Peak	HORIZONTAL
2	7230.00	47.81	37.78	42.69	7.77	50.67	74.00	-23.33	Peak	HORIZONTAL
3	9570.00	43.44	38.54	42.84	10.04	49.18	74.00	-24.82	Peak	HORIZONTAL
4	13425.00	43.31	40.92	43.04	11.22	52.41	74.00	-21.59	Peak	HORIZONTAL
5	16695.00	41.39	41.42	42.60	12.11	52.32	74.00	-21.68	Peak	HORIZONTAL
6	17865.00	39.48	42.81	41.99	12.64	52.94	74.00	-21.06	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2412MHz ANT1

Data: 54



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4824.00	55.01	33.28	42.69	6.83	52.43	54.00	-1.57	Average	VERTICAL
2	4830.00	55.96	33.29	42.68	6.86	53.43	74.00	-20.57	Peak	VERTICAL
3	7230.00	49.56	37.78	42.69	7.77	52.42	74.00	-21.58	Peak	VERTICAL
4	10485.00	43.21	38.99	42.80	9.80	49.20	74.00	-24.80	Peak	VERTICAL
5	13035.00	43.06	40.53	43.00	11.13	51.72	74.00	-22.28	Peak	VERTICAL
6	17280.00	40.56	42.34	42.40	12.41	52.91	74.00	-21.09	Peak	VERTICAL
7	17880.00	39.82	42.83	41.98	12.60	53.27	74.00	-20.73	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342K

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2437MHz ANT1

Data: 55



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	1198.00	51.42	24.67	43.66	3.03	35.46	74.00	-38.54	Peak	HORIZONTAL
2	1754.00	62.25	27.02	43.83	3.51	48.95	74.00	-25.05	Peak	HORIZONTAL
3	1942.00	64.16	28.00	43.88	3.68	51.96	74.00	-22.04	Peak	HORIZONTAL
4	2240.00	51.88	28.35	43.83	3.96	40.36	74.00	-33.64	Peak	HORIZONTAL
5	2520.00	52.16	28.46	43.74	4.26	41.14	74.00	-32.86	Peak	HORIZONTAL
6	2846.00	48.33	29.37	43.65	4.52	38.57	74.00	-35.43	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342K

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2437MHz ANT1

Data: 56



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	1198.00	51.86	24.67	43.66	3.03	35.90	74.00	-38.10	Peak	VERTICAL
2	1752.00	61.71	27.01	43.83	3.50	48.39	74.00	-25.61	Peak	VERTICAL
3	2008.00	48.08	28.30	43.90	3.70	36.18	74.00	-37.82	Peak	VERTICAL
4	2354.00	55.27	28.37	43.79	4.11	43.96	74.00	-30.04	Peak	VERTICAL
5	2528.00	50.94	28.48	43.74	4.27	39.95	74.00	-34.05	Peak	VERTICAL
6	2792.00	47.56	29.22	43.66	4.53	37.65	74.00	-36.35	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2437MHz ANT1

Data: 57



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4875.00	54.25	33.38	42.66	7.45	52.42	74.00	-21.58	Peak	HORIZONTAL
2	7305.00	49.47	37.84	42.72	8.00	52.59	74.00	-21.41	Peak	HORIZONTAL
3	9255.00	44.32	38.35	42.87	9.68	49.48	74.00	-24.52	Peak	HORIZONTAL
4	12675.00	43.25	39.72	42.90	10.67	50.74	74.00	-23.26	Peak	HORIZONTAL
5	13440.00	42.37	40.94	43.04	11.20	51.47	74.00	-22.53	Peak	HORIZONTAL
6	17880.00	39.70	42.83	41.98	12.60	53.15	74.00	-20.85	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2437MHz ANT1

Data: 58



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4874.00	55.24	33.37	42.66	7.43	53.38	54.00	-0.62	Average	VERTICAL
2	4875.00	55.94	33.38	42.66	7.45	54.11	74.00	-19.89	Peak	VERTICAL
3	7305.00	49.98	37.84	42.72	8.00	53.10	74.00	-20.90	Peak	VERTICAL
4	9765.00	42.71	38.66	42.82	10.44	48.99	74.00	-25.01	Peak	VERTICAL
5	13395.00	41.62	40.90	43.04	10.98	50.46	74.00	-23.54	Peak	VERTICAL
6	14580.00	41.78	39.94	42.93	12.16	50.95	74.00	-23.05	Peak	VERTICAL
7	17925.00	39.30	42.90	41.95	12.69	52.94	74.00	-21.06	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2462MHz ANT1

Data: 61



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	1196.00	52.33	24.67	43.66	3.05	36.39	74.00	-37.61	Peak	HORIZONTAL
2	1544.00	47.79	25.93	43.76	3.25	33.21	74.00	-40.79	Peak	HORIZONTAL
3	2210.00	51.65	28.34	43.84	3.92	40.07	74.00	-33.93	Peak	HORIZONTAL
4	2326.00	52.54	28.37	43.80	4.05	41.16	74.00	-32.84	Peak	HORIZONTAL
5	2540.00	52.01	28.51	43.74	4.31	41.09	74.00	-32.91	Peak	HORIZONTAL
6	2902.00	48.69	29.53	43.63	4.64	39.23	74.00	-34.77	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2462MHz ANT1

Data: 62



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	1196.00	49.58	24.67	43.66	3.05	33.64	74.00	-40.36	Peak	VERTICAL
2	1616.00	47.60	26.30	43.78	3.37	33.49	74.00	-40.51	Peak	VERTICAL
3	2012.00	47.79	28.30	43.90	3.71	35.90	74.00	-38.10	Peak	VERTICAL
4	2240.00	52.32	28.35	43.83	3.96	40.80	74.00	-33.20	Peak	VERTICAL
5	2380.00	54.83	28.38	43.79	4.17	43.59	74.00	-30.41	Peak	VERTICAL
6	2880.00	48.25	29.46	43.64	4.62	38.69	74.00	-35.31	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2462MHz ANT1

Data: 63



Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2462MHz ANT1

Data: 64



Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2412MHz ANT1

Data: 67



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	1198.00	51.54	24.67	43.66	3.03	35.58	74.00	-38.42	Peak	HORIZONTAL
2	1506.00	48.38	25.73	43.75	3.28	33.64	74.00	-40.36	Peak	HORIZONTAL
3	1788.00	48.15	27.20	43.84	3.57	35.08	74.00	-38.92	Peak	HORIZONTAL
4	2254.00	52.67	28.35	43.82	3.98	41.18	74.00	-32.82	Peak	HORIZONTAL
5	2488.00	54.33	28.40	43.75	4.22	43.20	74.00	-30.80	Peak	HORIZONTAL
6	2980.00	48.32	29.74	43.61	4.64	39.09	74.00	-34.91	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2412MHz ANT1

Data: 68



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	1198.00	52.80	24.67	43.66	3.03	36.84	74.00	-37.16	Peak	VERTICAL
2	1596.00	50.03	26.20	43.78	3.24	35.69	74.00	-38.31	Peak	VERTICAL
3	1798.00	53.40	27.25	43.84	3.57	40.38	74.00	-33.62	Peak	VERTICAL
4	2258.00	53.75	28.35	43.82	3.98	42.26	74.00	-31.74	Peak	VERTICAL
5	2492.00	57.65	28.40	43.75	4.22	46.52	74.00	-27.48	Peak	VERTICAL
6	2844.00	48.86	29.36	43.65	4.52	39.09	74.00	-34.91	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2412MHz ANT1

Data: 69



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4830.00	45.38	33.29	42.68	6.86	42.85	74.00	-31.15	Peak	HORIZONTAL
2	7245.00	42.61	37.80	42.70	7.78	45.49	74.00	-28.51	Peak	HORIZONTAL
3	9045.00	43.95	38.23	42.90	9.87	49.15	74.00	-24.85	Peak	HORIZONTAL
4	10365.00	43.47	38.95	42.80	10.96	50.58	74.00	-23.42	Peak	HORIZONTAL
5	14010.00	42.90	40.79	43.10	11.21	51.80	74.00	-22.20	Peak	HORIZONTAL
6	17100.00	39.19	42.38	42.53	12.91	51.95	74.00	-22.05	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2412MHz ANT1

Data: 70



- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342K

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2437MHz ANT1

Data: 71



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	1198.00	51.66	24.67	43.66	3.03	35.70	74.00	-38.30	Peak	HORIZONTAL
2	1580.00	49.40	26.12	43.77	3.13	34.88	74.00	-39.12	Peak	HORIZONTAL
3	1764.00	58.02	27.07	43.83	3.54	44.80	74.00	-29.20	Peak	HORIZONTAL
4	2278.00	53.76	28.36	43.82	4.02	42.32	74.00	-31.68	Peak	HORIZONTAL
5	2516.00	58.87	28.44	43.75	4.25	47.81	74.00	-26.19	Peak	HORIZONTAL
6	2584.00	55.50	28.64	43.72	4.45	44.87	74.00	-29.13	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342K

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2437MHz ANT1

Data: 72



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	1196.00	54.95	24.67	43.66	3.05	39.01	74.00	-34.99	Peak	VERTICAL
2	1492.00	53.16	25.67	43.75	3.27	38.35	74.00	-35.65	Peak	VERTICAL
3	1702.00	53.89	26.75	43.81	3.36	40.19	74.00	-33.81	Peak	VERTICAL
4	2240.00	53.04	28.35	43.83	3.96	41.52	74.00	-32.48	Peak	VERTICAL
5	2638.00	48.81	28.79	43.71	4.35	38.24	74.00	-35.76	Peak	VERTICAL
6	2856.00	48.62	29.40	43.64	4.55	38.93	74.00	-35.07	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2437MHz ANT1

Data: 73



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4875.00	46.71	33.38	42.66	7.45	44.88	74.00	-29.12	Peak	HORIZONTAL
2	7305.00	46.68	37.84	42.72	8.00	49.80	74.00	-24.20	Peak	HORIZONTAL
3	9555.00	43.47	38.53	42.84	9.97	49.13	74.00	-24.87	Peak	HORIZONTAL
4	11655.00	41.91	38.77	42.73	10.47	48.42	74.00	-25.58	Peak	HORIZONTAL
5	13365.00	43.24	40.87	43.04	10.88	51.95	74.00	-22.05	Peak	HORIZONTAL
6	17085.00	40.26	42.38	42.54	13.02	53.12	74.00	-20.88	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2437MHz ANT1

Data: 74



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4875.00	48.46	33.38	42.66	7.45	46.63	74.00	-27.37	Peak	VERTICAL
2	7320.00	45.39	37.86	42.73	8.11	48.63	74.00	-25.37	Peak	VERTICAL
3	10335.00	42.24	38.93	42.80	10.51	48.88	74.00	-25.12	Peak	VERTICAL
4	11685.00	42.07	38.76	42.73	10.53	48.63	74.00	-25.37	Peak	VERTICAL
5	13575.00	42.74	40.97	43.06	10.95	51.60	74.00	-22.40	Peak	VERTICAL
6	16935.00	40.52	42.19	42.60	12.16	52.27	74.00	-21.73	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342K

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2462MHz ANT1

Data: 77



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	1198.00	51.64	24.67	43.66	3.03	35.68	74.00	-38.32	Peak	HORIZONTAL
2	1914.00	49.13	27.85	43.87	3.73	36.84	74.00	-37.16	Peak	HORIZONTAL
3	2240.00	51.98	28.35	43.83	3.96	40.46	74.00	-33.54	Peak	HORIZONTAL
4	2378.00	54.87	28.38	43.79	4.17	43.63	74.00	-30.37	Peak	HORIZONTAL
5	2540.00	51.78	28.51	43.74	4.31	40.86	74.00	-33.14	Peak	HORIZONTAL
6	2694.00	49.27	28.94	43.69	4.37	38.89	74.00	-35.11	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342K

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2462MHz ANT1

Data: 78



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	1196.00	51.27	24.67	43.66	3.05	35.33	74.00	-38.67	Peak	VERTICAL
2	1496.00	49.18	25.69	43.75	3.27	34.39	74.00	-39.61	Peak	VERTICAL
3	1796.00	52.65	27.24	43.84	3.57	39.62	74.00	-34.38	Peak	VERTICAL
4	2240.00	53.11	28.35	43.83	3.96	41.59	74.00	-32.41	Peak	VERTICAL
5	2694.00	48.96	28.94	43.69	4.37	38.58	74.00	-35.42	Peak	VERTICAL
6	2882.00	48.65	29.47	43.64	4.62	39.10	74.00	-34.90	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2462MHz ANT1

Data: 79



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4920.00	45.14	33.46	42.64	7.00	42.96	74.00	-31.04	Peak	HORIZONTAL
2	7380.00	46.48	37.90	42.75	7.98	49.61	74.00	-24.39	Peak	HORIZONTAL
3	9990.00	43.53	38.79	42.80	9.59	49.11	74.00	-24.89	Peak	HORIZONTAL
4	13410.00	42.36	40.91	43.04	11.10	51.33	74.00	-22.67	Peak	HORIZONTAL
5	16725.00	41.05	41.52	42.60	12.18	52.15	74.00	-21.85	Peak	HORIZONTAL
6	17910.00	39.03	42.87	41.96	12.66	52.60	74.00	-21.40	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2462MHz ANT1

Data: 80



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4920.00	50.00	33.46	42.64	7.00	47.82	74.00	-26.18	Peak	VERTICAL
2	8340.00	43.14	37.74	42.97	9.14	47.05	74.00	-26.95	Peak	VERTICAL
3	10785.00	44.50	38.94	42.80	9.76	50.40	74.00	-23.60	Peak	VERTICAL
4	13455.00	42.23	40.96	43.05	11.11	51.25	74.00	-22.75	Peak	VERTICAL
5	14595.00	41.33	39.91	42.92	11.93	50.25	74.00	-23.75	Peak	VERTICAL
6	17130.00	39.97	42.37	42.51	12.68	52.51	74.00	-21.49	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2412MHz ANT1

Data: 83



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	1198.00	52.73	24.67	43.66	3.03	36.77	74.00	-37.23	Peak	HORIZONTAL
2	1882.00	47.95	27.69	43.86	3.81	35.59	74.00	-38.41	Peak	HORIZONTAL
3	2250.00	53.76	28.35	43.83	3.97	42.25	74.00	-31.75	Peak	HORIZONTAL
4	2328.00	54.63	28.37	43.80	4.05	43.25	74.00	-30.75	Peak	HORIZONTAL
5	2494.00	56.13	28.40	43.75	4.23	45.01	74.00	-28.99	Peak	HORIZONTAL
6	2900.00	48.84	29.52	43.63	4.64	39.37	74.00	-34.63	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2412MHz ANT1

Data: 84



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	1198.00	50.42	24.67	43.66	3.03	34.46	74.00	-39.54	Peak	VERTICAL
2	1760.00	56.34	27.05	43.83	3.52	43.08	74.00	-30.92	Peak	VERTICAL
3	2250.00	52.86	28.35	43.83	3.97	41.35	74.00	-32.65	Peak	VERTICAL
4	2340.00	56.31	28.37	43.80	4.07	44.95	74.00	-29.05	Peak	VERTICAL
5	2488.00	57.55	28.40	43.75	4.22	46.42	74.00	-27.58	Peak	VERTICAL
6	2836.00	47.80	29.34	43.65	4.50	37.99	74.00	-36.01	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2412MHz ANT1

Data: 85



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4815.00	44.29	33.27	42.69	6.78	41.65	74.00	-32.35	Peak	HORIZONTAL
2	7230.00	44.68	37.78	42.69	7.77	47.54	74.00	-26.46	Peak	HORIZONTAL
3	9645.00	44.81	38.59	42.84	9.93	50.49	74.00	-23.51	Peak	HORIZONTAL
4	13440.00	42.38	40.94	43.04	11.20	51.48	74.00	-22.52	Peak	HORIZONTAL
5	14580.00	41.54	39.94	42.93	12.16	50.71	74.00	-23.29	Peak	HORIZONTAL
6	17100.00	39.61	42.38	42.53	12.91	52.37	74.00	-21.63	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2412MHz ANT1

Data: 86



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4830.00	49.54	33.29	42.68	6.86	47.01	74.00	-26.99	Peak	VERTICAL
2	7230.00	46.17	37.78	42.69	7.77	49.03	74.00	-24.97	Peak	VERTICAL
3	10365.00	41.95	38.95	42.80	10.96	49.06	74.00	-24.94	Peak	VERTICAL
4	13440.00	42.03	40.94	43.04	11.20	51.13	74.00	-22.87	Peak	VERTICAL
5	14580.00	41.11	39.94	42.93	12.16	50.28	74.00	-23.72	Peak	VERTICAL
6	17085.00	39.40	42.38	42.54	13.02	52.26	74.00	-21.74	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2437MHz ANT1

Data: 87



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	1198.00	54.31	24.67	43.66	3.03	38.35	74.00	-35.65	Peak	HORIZONTAL
2	1740.00	48.05	26.95	43.82	3.47	34.65	74.00	-39.35	Peak	HORIZONTAL
3	1990.00	48.20	28.25	43.90	3.65	36.20	74.00	-37.80	Peak	HORIZONTAL
4	2240.00	54.30	28.35	43.83	3.96	42.78	74.00	-31.22	Peak	HORIZONTAL
5	2596.00	50.98	28.67	43.72	4.42	40.35	74.00	-33.65	Peak	HORIZONTAL
6	2882.00	47.98	29.47	43.64	4.62	38.43	74.00	-35.57	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2437MHz ANT1

Data: 88



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	1198.00	50.09	24.67	43.66	3.03	34.13	74.00	-39.87	Peak	VERTICAL
2	1618.00	47.82	26.31	43.79	3.38	33.72	74.00	-40.28	Peak	VERTICAL
3	1782.00	47.60	27.17	43.83	3.58	34.52	74.00	-39.48	Peak	VERTICAL
4	1950.00	47.36	28.04	43.89	3.67	35.18	74.00	-38.82	Peak	VERTICAL
5	2212.00	54.01	28.34	43.84	3.92	42.43	74.00	-31.57	Peak	VERTICAL
6	2740.00	47.99	29.07	43.68	4.48	37.86	74.00	-36.14	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2437MHz ANT1

Data: 89



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4874.00	45.32	33.37	42.66	7.43	43.46	54.00	-10.54	Average	HORIZONTAL
2	4875.00	60.09	33.38	42.66	7.45	58.26	74.00	-15.74	Peak	HORIZONTAL
3	7311.00	45.28	37.85	42.72	8.04	48.45	54.00	-5.55	Average	HORIZONTAL
4	7320.00	56.28	37.86	42.73	8.11	59.52	74.00	-14.48	Peak	HORIZONTAL
5	10365.00	42.38	38.95	42.80	10.96	49.49	74.00	-24.51	Peak	HORIZONTAL
6	13200.00	42.63	40.70	43.02	10.88	51.19	74.00	-22.81	Peak	HORIZONTAL
7	14595.00	40.55	39.91	42.92	11.93	49.47	74.00	-24.53	Peak	HORIZONTAL
8	17085.00	40.06	42.38	42.54	13.02	52.92	74.00	-21.08	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2437MHz ANT1

Data: 90



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4874.00	47.57	33.37	42.66	7.43	45.71	54.00	-8.29	Average	VERTICAL
2	4875.00	61.11	33.38	42.66	7.45	59.28	74.00	-14.72	Peak	VERTICAL
3	7305.00	56.62	37.84	42.72	8.00	59.74	74.00	-14.26	Peak	VERTICAL
4	7311.00	43.61	37.85	42.72	8.04	46.78	54.00	-7.22	Average	VERTICAL
5	10350.00	41.86	38.94	42.80	10.74	48.74	74.00	-25.26	Peak	VERTICAL
6	13365.00	42.61	40.87	43.04	10.88	51.32	74.00	-22.68	Peak	VERTICAL
7	14880.00	41.75	39.34	42.84	11.36	49.61	74.00	-24.39	Peak	VERTICAL
8	17400.00	40.21	42.32	42.32	12.49	52.70	74.00	-21.30	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2462MHz ANT1

Data: 93



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	1196.00	54.84	24.67	43.66	3.05	38.90	74.00	-35.10	Peak	HORIZONTAL
2	1250.00	53.13	24.85	43.67	2.94	37.25	74.00	-36.75	Peak	HORIZONTAL
3	1752.00	59.14	27.01	43.83	3.50	45.82	74.00	-28.18	Peak	HORIZONTAL
4	2240.00	53.43	28.35	43.83	3.96	41.91	74.00	-32.09	Peak	HORIZONTAL
5	2538.00	53.08	28.51	43.74	4.30	42.15	74.00	-31.85	Peak	HORIZONTAL
6	2880.00	48.65	29.46	43.64	4.62	39.09	74.00	-34.91	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2462MHz ANT1

Data: 94



Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2462MHz ANT1

Data: 95



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4920.00	47.51	33.46	42.64	7.00	45.33	74.00	-28.67	Peak	HORIZONTAL
2	7395.00	45.01	37.92	42.76	8.02	48.19	74.00	-25.81	Peak	HORIZONTAL
3	10245.00	42.85	38.90	42.80	10.00	48.95	74.00	-25.05	Peak	HORIZONTAL
4	13590.00	42.23	40.96	43.06	11.00	51.13	74.00	-22.87	Peak	HORIZONTAL
5	14595.00	42.68	39.91	42.92	11.93	51.60	74.00	-22.40	Peak	HORIZONTAL
6	17085.00	39.83	42.38	42.54	13.02	52.69	74.00	-21.31	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2462MHz ANT1


Data: 96



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4920.00	49.67	33.46	42.64	7.00	47.49	74.00	-26.51	Peak	VERTICAL
2	7380.00	44.36	37.90	42.75	7.98	47.49	74.00	-26.51	Peak	VERTICAL
3	9600.00	43.56	38.56	42.84	10.02	49.30	74.00	-24.70	Peak	VERTICAL
4	11130.00	42.69	38.87	42.79	10.38	49.15	74.00	-24.85	Peak	VERTICAL
5	13590.00	42.11	40.96	43.06	11.00	51.01	74.00	-22.99	Peak	VERTICAL
6	17190.00	39.64	42.36	42.47	12.71	52.24	74.00	-21.76	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission test (18GHz-25GHz)




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	18000.00	42.46	-2.26	8.15	48.35	74.00	-25.65	Peak	HORIZONTAL
2	18703.30	42.14	-2.74	8.31	47.71	74.00	-26.29	Peak	HORIZONTAL
3	20683.00	42.35	-4.72	8.22	45.85	74.00	-28.15	Peak	HORIZONTAL
4	22047.36	42.46	-5.07	8.90	46.29	74.00	-27.71	Peak	HORIZONTAL
5	23166.34	41.83	-4.73	8.70	45.80	74.00	-28.20	Peak	HORIZONTAL
6	24013.90	42.13	-5.10	9.17	46.20	74.00	-27.80	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	18421.69	40.66	-2.26	8.47	46.87	74.00	-27.13	Peak	VERTICAL
2	19937.07	43.41	-4.46	8.95	47.90	74.00	-26.10	Peak	VERTICAL
3	21167.54	45.29	-5.11	8.68	48.86	74.00	-25.14	Peak	VERTICAL
4	21854.55	44.06	-5.12	8.90	47.84	74.00	-26.16	Peak	VERTICAL
5	22817.52	41.76	-4.69	8.49	45.56	74.00	-28.44	Peak	VERTICAL
6	24556.86	40.76	-5.45	9.60	44.91	74.00	-29.09	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

10. RF Conducted Spurious Emissions

10.1. Block diagram of test setup

Same as section 4.1

10.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

10.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span/RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


10.4. Test result

Pass

Please find the detailed data in APPENDIXES-WLAN.

11. Band Edge Compliance (Radiated Method)

11.1. Block diagram of test setup



11.2. Limit

All restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400 MHz to 2483.5 MHz shall be at least 20dB below the fundamental emissions or comply with RSS-Gen Issue 3 clause 7.2.5 (Same as FCC 15.209) limits.

11.3. Test Procedure

Same with clause 8.3 except change investigated frequency range.

Remark: All restriction band have been tested, and only the worst case is shown in report.

11.4. Test result

Pass. (See below detailed test result)

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2412MHz ANT1

Data: 49



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2377.50	12.56	28.38	0.00	3.91	44.85	54.00	-9.15	Average	HORIZONTAL
2	2377.50	23.75	28.38	0.00	3.91	56.04	74.00	-17.96	Peak	HORIZONTAL
3	2390.00	12.34	28.38	0.00	3.95	44.67	54.00	-9.33	Average	HORIZONTAL
4	2390.00	21.72	28.38	0.00	3.95	54.05	74.00	-19.95	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2412MHz ANT1

Data: 50



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2364.50	12.35	28.37	0.00	3.91	44.63	54.00	-9.37	Average	VERTICAL
2	2364.50	24.23	28.37	0.00	3.91	56.51	74.00	-17.49	Peak	VERTICAL
3	2390.00	12.67	28.38	0.00	3.95	45.00	54.00	-9.00	Average	VERTICAL
4	2390.00	21.26	28.38	0.00	3.95	53.59	74.00	-20.41	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2462MHz ANT1

Data: 59



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	12.44	28.40	0.00	4.07	44.91	54.00	-9.09	Average	HORIZONTAL
2	2483.50	22.44	28.40	0.00	4.07	54.91	74.00	-19.09	Peak	HORIZONTAL
3	2504.88	12.36	28.41	0.00	4.05	44.82	54.00	-9.18	Average	HORIZONTAL
4	2504.88	24.84	28.41	0.00	4.05	57.30	74.00	-16.70	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11B 1M 2462MHz ANT1

Data: 60



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	12.55	28.40	0.00	4.07	45.02	54.00	-8.98	Average	VERTICAL
2	2483.50	21.55	28.40	0.00	4.07	54.02	74.00	-19.98	Peak	VERTICAL
3	2528.28	12.27	28.48	0.00	4.03	44.78	54.00	-9.22	Average	VERTICAL
4	2528.28	24.42	28.48	0.00	4.03	56.93	74.00	-17.07	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2412MHz ANT1

Data: 65



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2344.75	12.38	28.37	0.00	3.92	44.67	54.00	-9.33	Average	HORIZONTAL
2	2344.75	24.10	28.37	0.00	3.92	56.39	74.00	-17.61	Peak	HORIZONTAL
3	2390.00	12.26	28.38	0.00	3.95	44.59	54.00	-9.41	Average	HORIZONTAL
4	2390.00	20.93	28.38	0.00	3.95	53.26	74.00	-20.74	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2412MHz ANT1

Data: 66



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2371.88	12.26	28.37	0.00	3.91	44.54	54.00	-9.46	Average	VERTICAL
2	2371.88	24.11	28.37	0.00	3.91	56.39	74.00	-17.61	Peak	VERTICAL
3	2390.00	12.21	28.38	0.00	3.95	44.54	54.00	-9.46	Average	VERTICAL
4	2390.00	21.88	28.38	0.00	3.95	54.21	74.00	-19.79	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2462MHz ANT1

Data: 75



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	12.72	28.40	0.00	4.07	45.19	54.00	-8.81	Average	HORIZONTAL
2	2483.50	21.73	28.40	0.00	4.07	54.20	74.00	-19.80	Peak	HORIZONTAL
3	2498.04	12.52	28.40	0.00	4.06	44.98	54.00	-9.02	Average	HORIZONTAL
4	2498.04	23.79	28.40	0.00	4.06	56.25	74.00	-17.75	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : 11G 6M 2462MHz ANT1

Data: 76



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	12.35	28.40	0.00	4.07	44.82	54.00	-9.18	Average	VERTICAL
2	2483.50	22.35	28.40	0.00	4.07	54.82	74.00	-19.18	Peak	VERTICAL
3	2506.44	12.46	28.42	0.00	4.05	44.93	54.00	-9.07	Average	VERTICAL
4	2506.44	24.46	28.42	0.00	4.05	56.93	74.00	-17.07	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2412MHz ANT1

Data: 81



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2383.38	12.25	28.38	0.00	4.18	44.81	54.00	-9.19	Average	HORIZONTAL
2	2383.38	23.69	28.38	0.00	4.18	56.25	74.00	-17.75	Peak	HORIZONTAL
3	2390.00	12.28	28.38	0.00	4.21	44.87	54.00	-9.13	Average	HORIZONTAL
4	2390.00	21.71	28.38	0.00	4.21	54.30	74.00	-19.70	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2412MHz ANT1

Data: 82



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2339.00	12.24	28.37	0.00	4.07	44.68	54.00	-9.32	Average	VERTICAL
2	2339.00	23.81	28.37	0.00	4.07	56.25	74.00	-17.75	Peak	VERTICAL
3	2390.00	12.38	28.38	0.00	4.21	44.97	54.00	-9.03	Average	VERTICAL
4	2390.00	22.81	28.38	0.00	4.21	55.40	74.00	-18.60	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2462MHz ANT1

Data: 91



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	12.28	28.40	0.00	4.07	44.75	54.00	-9.25	Average	HORIZONTAL
2	2483.50	22.29	28.40	0.00	4.07	54.76	74.00	-19.24	Peak	HORIZONTAL
3	2534.04	12.52	28.50	0.00	4.05	45.07	54.00	-8.93	Average	HORIZONTAL
4	2534.04	24.12	28.50	0.00	4.05	56.67	74.00	-17.33	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

Radiated Emission Test Result

Test Site : 10m Chamber

Test Date : 03-30-2026

Tested By : Zayn Chen

EUT : PT Camera


Model Number : TC-H342A

Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Memo : N20 MCS0 2462MHz ANT1

Data: 92




Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	12.28	28.40	0.00	4.07	44.75	54.00	-9.25	Average	VERTICAL
2	2483.50	23.59	28.40	0.00	4.07	56.06	74.00	-17.94	Peak	VERTICAL
3	2497.68	12.46	28.40	0.00	4.06	44.92	54.00	-9.08	Average	VERTICAL
4	2497.68	24.46	28.40	0.00	4.06	56.92	74.00	-17.08	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Margin = Result Level - Limit.

12. Power Line Conducted Emission

12.1. Block diagram of test setup



12.2. Power line conducted emission limits

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150 kHz ~ 500 kHz	66 ~ 56*	56 ~ 46*
500 kHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

12.3. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80 cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 3.0 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest

emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.


The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

12.4. Test result

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: Pre-test AC conducted emission at all mode, only the worst case was recorded in this report.



Final Result

--- N Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c. f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.17285	31.0	15.8	9.8	40.8	25.6	64.8	54.8	24.0	29.2
2	0.65748	29.5	19.3	9.8	39.3	29.1	56.0	46.0	16.7	16.9
3	13.55995	14.3	8.4	10.2	24.5	18.6	60.0	50.0	35.5	31.4

--- L1 Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c. f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.19083	28.6	11.3	9.8	38.4	21.1	64.0	54.0	25.6	32.9
2	0.63606	30.8	20.8	9.8	40.6	30.6	56.0	46.0	15.4	15.4
3	0.6809	27.6	20.8	9.8	37.4	30.6	56.0	46.0	18.6	15.4
4	9.41789	24.6	12.8	10.1	34.7	22.9	60.0	50.0	25.3	27.1

Note1) Level (Quasi-Peak and/or C/Average) = Meter Reading + Factor

Note2) Line = Polarity of input power (Live or Neutral)

N : Abbreviation of Neutral Polarity, L1 : Abbreviation of Live Polarity,

Note3) Factor = LISN Insertion Loss + Cable Loss

Note4) Margin = Limit – Level (Quasi-Peak and/or C/Average)

Note5) C/Average : Abbreviation of CISPR Average

13. Antenna Requirements

13.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

13.2. Result

The antenna used for this product is PCB antenna and no antenna other than that furnished by the responsible party shall be used with the device, maximum antenna gain is 2.25 dBi.

14. Test Setup Photograph

Please find the photos of EUT in Test Setup Photograph.

15. Photos of the EUT

Please find the photos of EUT in APPENDIXES-Photos.

END OF REPORT