





Test Report No.:
FCCSZ2024-0057-H

RF Test Report

FCC ID : 2BKFC-LSRCR3P0
EUT : Millimeter Wave Corner Radar Sensor
MODEL : SRR3.0
BRAND NAME : 
APPLICANT : Lisheng Intelligent Technology (Shanghai) Co.,Ltd.
Classification of Test : Commission Test

CVC Testing Technology (Shenzhen) Co., Ltd.



Applicant		Name : Lisheng Intelligent Technology (Shanghai) Co.,Ltd. Address : Room 702-5, No. 4811 Caoan Road, Anting Town, Jiading District, Shanghai	
Manufacturer		Name : Lisheng Intelligent Technology (Shanghai) Co.,Ltd. Address : Room 702-5, No. 4811 Caoan Road, Anting Town, Jiading District, Shanghai	
Equipment Under Test		Name : Millimeter Wave Corner Radar Sensor Model/Type:SRR3.0 Trade mark :  Serial NO.:N/A Sampe NO.:2-1	
Date of Receipt.	2024.07.24	Date of Testing	2024.07.25~2024.08.05
Test Specification		Test Result	
FCC Part 2 (Section 2.1091) KDB 447498 D04, IEEE C95.3		PASS	
Evaluation of Test Result	The equipment under test was found to comply with the requirements of the standards applied.  Issue Date: 2024-08-07		
Tested by:  Liang Jiatong Name Signature	Reviewed by:  Mo Xianbiao Name Signature	Approved by:  Dong Sanbi Name Signature	
Other Aspects: NONE.			
Abbreviations:OK, Pass= passed Fail = failed N/A= not applicable EUT= equipment, sample(s) under tested			

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 GENERAL PRODUCT INFORMATION	5
2 RF EXPOSURE LIMITGENERAL INFORMATION	6
2.1 CLASSIFICATION.....	6
2.2 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (FCC)	6
2.3 CALCULATION RESULT OF MAXIMUM POWER	7

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCCSZ2024-0057-H	Original release	2024.08.07

1 GENERAL PRODUCT INFORMATION

PRODUCT	Millimeter Wave Corner Radar Sensor
BRAND	 LUXSHARE ICT
TEST MODEL	SRR3.0
ADDITIONAL MODEL	N/A
POWER SUPPLY	DC 12V form host unit
STANDARDS	FCC Part 2 (Section 2.1091)
	KDB 447498 D04
	IEEE C95.3

Note:

1. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2 RF EXPOSURE LIMIT GENERAL INFORMATION

2.1 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.2 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (FCC)

(Option C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF SOURCE FREQUENCY (MHZ)	THRESHOLD ERP(W)
0.3 -1.34	$1,920 R^2$
1.34 - 30	$3,450 R^2 F^2$
30 -300	$3.83 R^2$
300-1500	$0.0128 R^2 F^2$
1500-100,000	$19.2 R^2$

2.3 CALCULATION RESULT OF MAXIMUM POWER

The measured PEAK EIRP Power

Mode	PEAK EIRP(dBm)
76GHz-78GHz	22.97

Note:conducted Average Power = EIRP - Antenna Gain

The tuned EIRP Power (declared by client)

Frequency Range (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
76GHz-79.3GHz	23	±1	22	24

MAXIMUM PERMISSIBLE EXPOSURE (FCC)

Frequency Range (MHz)	R (cm)	EIRP (dBm)	ERP (dBm)	ERP (W)	Threshold ERP(W)	Ratio
76GHz-78GHz	20	24	21.85	0.153	0.77	0.199

Note: ERP=EIRP-2.15dB

Conclusion:

This confirmed that the device compliance with FCC RF exposure requirements.

----- End of the Report -----

Important

- (1) The test report is invalid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of Approval and Reviewer;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

Address: No. 1301-14&16, Guanguang Road, Xinlan Community, Guanlan Subdistrict, Longhua District, Shenzhen, Guangdong, China

Post Code: 518110 Tel: 0755-23763060-8805

Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn

<http://www.cvc.org.cn>