



FCC TEST REPORT

FCC ID: 2BKN3-RC941

On Behalf of

Rocware Corporation

4K Dual-lens Presentation PTZ Camera

Model No.: RC941, CX310, CX310L

Prepared for : Rocware Corporation
Address : 3/F-1, No. 2, Honghui Industrial Park, Xin'an Street, Bao'an District,
Shenzhen, China

Prepared By : Shenzhen PSI Testing Co., Ltd.
1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West
Address : Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong,
China

Report Number : psi2502088-C01-R12
Date of Receipt : February 20, 2025
Date of Test : February 24, 2025 - April 8, 2025
Date of Report : April 9, 2025
Version Number : V0

TABLE OF CONTENTS

	Description	Page
1	TEST SUMMARY	5
1.1	MEASUREMENT UNCERTAINTY.....	5
2	GENERAL INFORMATION	6
2.1	GENERAL DESCRIPTION OF EUT	6
2.2	TEST MODE	7
2.3	TEST FACILITY	7
2.4	DESCRIPTION OF SUPPORT UNITS	7
2.5	DEVIATION FROM STANDARDS.....	8
2.6	ABNORMALITIES FROM STANDARD CONDITIONS.....	8
2.7	OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
2.8	ADDITIONAL INSTRUCTIONS	8
2.9	TEST CONDITIONS	8
3	TEST INSTRUMENTS LIST	9
4	TEST RESULTS AND MEASUREMENT DATA.....	10
4.1	ANTENNA REQUIREMENT:	10
4.2	CONDUCTED EMISSIONS	11
4.3	EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....	14
4.4	MAXIMUM CONDUCTED OUTPUT POWER.....	114
4.5	POWER SPECTRAL DENSITY	120
4.6	BAND EDGE.....	168
4.7	RADIATED EMISSION	207
4.8	FREQUENCY STABILITY	215
5	PHOTOS OF TEST SETUP.....	217
6	PHOTOS OF EUT	217

TEST REPORT DECLARATION

Applicant : Rocware Corporation
Address : 3/F-1, No. 2, Honghui Industrial Park, Xin'an Street, Bao'an District, Shenzhen, China
Manufacturer : Rocware Corporation
Address : 3/F-1, No. 2, Honghui Industrial Park, Xin'an Street, Bao'an District, Shenzhen, China
EUT Description : 4K Dual-lens Presentation PTZ Camera
(A) Model No. : RC941, CX310, CX310L
(B) Trademark : Rocware

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart E

ANSI C63.4:2014, ANSI C63.10:2013

Test Result: PASS

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart E limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....: Jensen Wang
Test Engineer 
Approved by (name + signature).....: Simple Guan
Project Manager 
Date of issue.....: April 9, 2025

Revision History

Revision	Issue Date	Revisions	Revised By
V0	April 9, 2025	Initial released Issue	Jensen Wang



1 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	Section 15.203 Section 7.1.4 RSS-Gen Issue 5	PASS
AC Power Line Conducted Emission	Section 15.207 Section 7.2.4 RSS-GEN(8.8), ANSI C63.10	PASS
Occupied bandwidth	Section 15.407 (e)	PASS
Maximum Conducted Output Power	Section 15.407(a), RSS-247 5.4(2)	PASS
Power Spectral Density	Section 15.407(a), RSS-247 5.2(2)	PASS
Undesirable Emission	Section 15.407(b), RSS-247 5.5	PASS
Radiated Emission	Section 15.407(b)&15.209 Section 5.5 RSS-Gen(8.9), RSS-247(5.5), ANSI C63.10	PASS
Band Edge	15.205, RSS-247 Issue 2, ANSI C63.10	PASS
Frequency Stability	15.407(f), RSS-GEN(6.11)	PASS

Remark:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Frequency Stability: The manufacturer stated in the user's manual.
3. The conclusion of this test report is judged by actual test data without considering measurement uncertainty.
4. Measurement-method usage KDB 789033 D02 General UNII Test Procedures New Rules v02r01

1.1 Measurement Uncertainty

Item	Uncertainty
Uncertainty for Power Line Conducted Emissions Test	2.17dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	2.74dB(Polarize: V)
	2.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 18GHz)	4.29dB(Polarize: V)
	4.82dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31dB(Polarize: V)
	4.30dB(Polarize: H)
Uncertainty for radio frequency	48.24KHz
Uncertainty for conducted RF Power	0.41dB
Uncertainty for Power Spectral Density	0.39 dB
Occupied-Bandwidth	968Hz
Conducted-Spurious Emission	1.26dB

2 General Information

2.1 General Description of EUT

EUT Name : 4K Dual-lens Presentation PTZ Camera
 Model : RC941, CX310, CX310L
 Diff : There is no difference except the name of the model. All tests are made with the RC941 model.
 Test Voltage : DC 12V from adapter

Radio Technology : 5G WIFI

Operation frequency : 802.11a/802.11ac20/802.11n(HT20)/802.11ax20: 5180-5240MHz, 5260-5320MHz, 5500-5700MHz, 5745-5825MHz
 802.11ac40/802.11n(HT40)/802.11ax40: 5190-5230MHz, 5270-5310MHz, 5510-5670MHz, 5755-5795MHz
 802.11ac80/802.11ax80: 5210MHz, 5290MHz, 5530MHz, 5775MHz
 Channel separation : 20MHz for 802.11a/802.11ac20/802.11n(HT20)/802.11ax20
 40MHz for 802.11ac40/ 802.11n(HT40)/802.11ax40
 80MHz for 802.11ac80/802.11ax80
 Modulation technology: : IEEE 802.11n: OFDM (64QAM,16QAM,QPSK,BPSK)
 IEEE 802.11a: OFDM (64QAM,16QAM,QPSK,BPSK)
 IEEE 802.11ac: OFDM (64QAM,16QAM, 256QAM,QPSK,BPSK)
 IEEE 802.11ax: OFDMA (64QAM,16QAM,QPSK,BPSK,256QAM,1024QAM)
 Antenna Type : Internal antenna, Maximum Gain is 1.60dBi.
 PMN : N/A
 HVIN : N/A
 Software version : N/A
 Hardware version : N/A
 FVIN : N/A
 Note : Antenna information is provided by applicant.
 Testing lab is not responsible for the accuracy of the information.

2.2 Test mode

Transmitting mode Keep the EUT in transmitting with modulation.
EUT was test with 99% duty cycle at its maximum power control level.

Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

2.3 Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission
Registration Number: 916281

September 21, 2023 Certificated by IC
Registration Number: 31123
CAB identifier: CN0158

2.4 Description of Support Units

- Accessories 1 : AC ADAPTER 1
Manufacturer : HUIZHOU FUJIA APPLIANCE TECH. CO., LTD.
Model : FJ-SW729S1205000N
Rating : Input: 100-240V~50/60Hz 1.5A
Output: DC 12.0V/5.0A
- Accessories 2 : AC ADAPTER 2
Manufacturer : SHEN ZHEN TRANSIN TECHNOLOGIES CO.,LTD
Model : TS-A054-1204503
Rating : Input: 100-240V~50/60Hz 1.5A
Output: DC 12.0V/4.5A
- Accessories 3 : AC ADAPTER 3
Manufacturer : SHEN ZHEN TRANSIN TECHNOLOGIES CO.,LTD
Model : TS-A036-120300M
Rating : Input: 100-240V~50/60Hz 1.2A
Output: DC 12.0V/3.0A

2.5 Deviation from Standards

None.

2.6 Abnormalities from Standard Conditions

None.

2.7 Other Information Requested by the Customer

None.

2.8 Additional instructions

Software (Used for test) from client

Channel	Power level
Lowest	Default
Middle	Default
Highest	Default

2.9 Test Conditions


Items	Required	Actual
Temperature range:	15-35℃	26℃
Humidity range:	25-75%	54%
Pressure range:	86-106kPa	101kPa

3 Test Instruments list


Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2022.12.20	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2024.12.18	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV216	102282	/	2024.12.18	1 Year
4.	L.I.S.N.#2	RFT	NNB111	13835240	/	2024.12.18	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2025.01.02	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2025.01.02	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2024.12.18	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2025.01.02	2 Year
9.	Amplifier	SKET	LAPA_01G1 8G-45dB	SK20220329 01	/	2024.12.18	1 Year
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2024.12.31	2 Year
11.	Amplifier	SKET	LNPA_0118 G-45	SK20200108 01	/	2024.12.18	1 Year
12.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02 -1111533-Fz	/	2024.12.18	1 Year
13.	RF Sensor Unit	Tachoy	TR1029-2	20220428P0 08	/	2024.12.18	1 Year
14.	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2024.12.18	1 Year
15.	Temp. & Humid Chamber	Auchno	9606	/	/	2024.12.18	1 Year
16.	Regulated DC Power Supply	Xinouhua	ADC120V10 A	20221125163 8	/	2024.12.18	1 Year
For Test Software Information							
Item	Software Name	Manufacturer			Version		
RE	EZ EMC	Farad			PSI-3A1		
CE	EZ EMC	Farad			PSI-3A1		
RF	RTS	TACHOY			V1.0.0		

4 Test results and Measurement Data

4.1 Antenna requirement:

Standard requirement:	FCC Part15 C Section 15.203, RSS-GEN(6.8)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
Internal antenna, Maximum Gain is 1.6dB for 5180-5240MHz, 5260-5320MHz, 5500-5700MHz, 5745-5845MHz 	


4.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207, RSS-Gen §8.8		
Test Method:	ANSI C63.10:2013		
Test Frequency Range:	150KHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9KHz, VBW=30KHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test procedure	The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.		
Test setup:	 Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test Instruments:	Refer to section 3.0 for details		
Test mode:	Refer to section 2.2 for details		
Test results:	Pass		

Measurement Data


An initial pre-scan was performed on the line and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Line:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1740	44.86	9.94	54.80	64.77	-9.97	QP
2	0.1740	29.12	9.94	39.06	54.77	-15.71	AVG
3	0.3700	37.19	9.73	46.92	58.50	-11.58	QP
4	0.3700	23.31	9.73	33.04	48.50	-15.46	AVG
5 *	0.5100	36.70	9.89	46.59	56.00	-9.41	QP
6	0.5100	25.31	9.89	35.20	46.00	-10.80	AVG
7	0.8059	30.86	9.42	40.28	56.00	-15.72	QP
8	0.8059	20.40	9.42	29.82	46.00	-16.18	AVG
9	1.3020	35.87	9.40	45.27	56.00	-10.73	QP
10	1.3020	22.52	9.40	31.92	46.00	-14.08	AVG
11	2.3340	27.51	9.39	36.90	56.00	-19.10	QP
12	2.3340	15.33	9.39	24.72	46.00	-21.28	AVG

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit


Neutral:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1539	46.65	9.79	56.44	65.79	-9.35	QP
2	0.1539	29.66	9.79	39.45	55.79	-16.34	AVG
3 *	0.1900	46.42	9.99	56.41	64.04	-7.63	QP
4	0.1900	31.42	9.99	41.41	54.04	-12.63	AVG
5	0.3379	35.65	9.69	45.34	59.25	-13.91	QP
6	0.3379	22.51	9.69	32.20	49.25	-17.05	AVG
7	0.5220	33.93	9.78	43.71	56.00	-12.29	QP
8	0.5220	20.96	9.78	30.74	46.00	-15.26	AVG
9	0.9780	34.01	9.53	43.54	56.00	-12.46	QP
10	0.9780	21.97	9.53	31.50	46.00	-14.50	AVG
11	1.3700	31.89	9.42	41.31	56.00	-14.69	QP
12	1.3700	19.22	9.42	28.64	46.00	-17.36	AVG

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

All modes and channels have been tested and only the A 5180MHz mode with the worst data is listed.

4.3 Emission Bandwidth and 99% Occupied Bandwidth

Test Requirement:	FCC Part15 E Section 15.407, RSS-Gen §6.7; RSS-247 §6.2
Test Method:	KDB 789033 D02 General UNII Test Procedures New Rules v02r01
Limit:	N/A
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test procedure:	According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass


Note: Note: Both antennas have been tested and only the worst data of antenna 1 is shown.

Measurement Data:


Band 1 (5150-5250 MHz):

Condition	Antenna	Modulation	Frequency(MHz)	26dB_Emission_Bandwidth(MHz)	Occupied Bandwidth(MHz)
NVNT	ANT1	802.11a	5180.00	32.51	16.82
NVNT	ANT1	802.11a	5200.00	37.99	17.58
NVNT	ANT1	802.11a	5240.00	33.43	17.24
NVNT	ANT1	802.11n(HT20)	5180.00	36.86	18.16
NVNT	ANT1	802.11n(HT20)	5200.00	36.67	18.14
NVNT	ANT1	802.11n(HT20)	5240.00	35.32	18.07
NVNT	ANT1	802.11ac(VHT20)	5180.00	38.19	18.24
NVNT	ANT1	802.11ac(VHT20)	5200.00	38.09	18.26
NVNT	ANT1	802.11ac(VHT20)	5240.00	35.49	18.16
NVNT	ANT1	802.11ax(HE20)	5180.00	39.50	18.13
NVNT	ANT1	802.11ax(HE20)	5200.00	36.50	18.24
NVNT	ANT1	802.11ax(HE20)	5240.00	35.97	18.14
NVNT	ANT1	802.11n(HT40)	5190.00	82.93	39.85
NVNT	ANT1	802.11n(HT40)	5230.00	83.33	37.76
NVNT	ANT1	802.11ac(VHT40)	5190.00	85.84	40.55
NVNT	ANT1	802.11ac(VHT40)	5230.00	84.97	38.28
NVNT	ANT1	802.11ax(HE40)	5190.00	83.27	40.25
NVNT	ANT1	802.11ax(HE40)	5230.00	81.70	37.91
NVNT	ANT1	802.11ac(VHT80)	5210.00	180.26	76.74
NVNT	ANT1	802.11ax(HE80)	5210.00	172.68	76.85

99% OCB NVNT_ANT1_802_11a_5180




-26BW_NVNT_ANT1_802_11a_5180




99%_OCB_NVNT_ANT1_802_11a_5200




-26BW_NVNT_ANT1_802_11a_5200




99%_OCB_NVNT_ANT1_802_11a_5240



-26BW_NVNT_ANT1_802_11a_5240




99% OCB NVNT ANT1_802_11n(HT20)_5180




-26BW_NVNT_ANT1_802_11n(HT20)_5180




99% OCB NVNT ANT1_802_11n(HT20)_5200




-26BW_NVNT_ANT1_802_11n(HT20)_5200




99% OCB NVNT ANT1_802_11n(HT20)_5240




-26BW_NVNT ANT1_802_11n(HT20)_5240




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5180



-26BW_NVNT_ANT1_802_11ac(VHT20)_5180




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5200




-26BW_NVNT_ANT1_802_11ac(VHT20)_5200




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5240




-26BW_NVNT_ANT1_802_11ac(VHT20)_5240




99% OCB_NVNT_ANT1_802_11ax(HE20)_5180




-26BW_NVNT_ANT1_802_11ax(HE20)_5180




99%_OCB_NVNT_ANT1_802_11ax(HE20)_5200



-26BW_NVNT_ANT1_802_11ax(HE20)_5200




99% OCB_NVNT_ANT1_802_11ax(HE20)_5240




-26BW_NVNT_ANT1_802_11ax(HE20)_5240




99% OCB NVNT ANT1_802_11n(HT40)_5190




-26BW_NVNT_ANT1_802_11n(HT40)_5190




99% OCB NVNT ANT1_802_11n(HT40)_5230




-26BW_NVNT ANT1_802_11n(HT40)_5230




99%_OCB_NVNT_ANT1_802_11ac(VHT40)_5190




-26BW_NVNT_ANT1_802_11ac(VHT40)_5190




99%_OCB_NVNT_ANT1_802_11ac(VHT40)_5230




-26BW_NVNT_ANT1_802_11ac(VHT40)_5230




99%_OCB_NVNT_ANT1_802_11ax(HE40)_5190




-26BW_NVNT_ANT1_802_11ax(HE40)_5190




99%_OCB_NVNT_ANT1_802_11ax(HE40)_5230




-26BW_NVNT_ANT1_802_11ax(HE40)_5230




99%_OCB_NVNT_ANT1_802_11ac(VHT80)_5210



-26BW_NVNT_ANT1_802_11ac(VHT80)_5210



99%_OCB_NVNT_ANT1_802_11ax(HE80)_5210




-26BW_NVNT_ANT1_802_11ax(HE80)_5210




Band 2 (5260-5320 MHz):

Condition	Antenna	Modulation	Frequency(MHz)	26dB_Emission_Bandwidth(MHz)	Occupied Bandwidth(MHz)
NVNT	ANT1	802.11a	5260.00	32.71	16.94
NVNT	ANT1	802.11a	5300.00	34.81	16.92
NVNT	ANT1	802.11a	5320.00	33.31	16.98
NVNT	ANT1	802.11n(HT20)	5260.00	34.27	17.98
NVNT	ANT1	802.11n(HT20)	5300.00	35.30	18.00
NVNT	ANT1	802.11n(HT20)	5320.00	35.67	17.97
NVNT	ANT1	802.11ac(VHT20)	5260.00	33.13	17.79
NVNT	ANT1	802.11ac(VHT20)	5300.00	34.62	17.86
NVNT	ANT1	802.11ac(VHT20)	5320.00	34.43	17.81
NVNT	ANT1	802.11n(HT40)	5270.00	70.31	36.38
NVNT	ANT1	802.11n(HT40)	5310.00	78.41	36.90
NVNT	ANT1	802.11ac(VHT40)	5270.00	73.45	36.40
NVNT	ANT1	802.11ac(VHT40)	5310.00	78.51	36.85
NVNT	ANT1	802.11ax(HE20)	5260.00	33.65	17.84
NVNT	ANT1	802.11ax(HE20)	5300.00	35.24	17.96
NVNT	ANT1	802.11ax(HE20)	5320.00	36.20	18.01
NVNT	ANT1	802.11ax(HE40)	5270.00	81.13	36.84
NVNT	ANT1	802.11ax(HE40)	5310.00	78.13	36.78
NVNT	ANT1	802.11ac(VHT80)	5290.00	152.40	76.30
NVNT	ANT1	802.11ax(HE80)	5290.00	183.22	76.31


99%_OCB_NVNT_ANT1_802_11a_5260




-26BW_NVNT_ANT1_802_11a_5260




99%_OCB_NVNT_ANT1_802_11a_5300




-26BW_NVNT_ANT1_802_11a_5300




99%_OCB_NVNT_ANT1_802_11a_5320




-26BW_NVNT_ANT1_802_11a_5320




99% OCB NVNT ANT1_802_11n(HT20)_5260




-26BW_NVNT_ANT1_802_11n(HT20)_5260




99% OCB NVNT ANT1_802_11n(HT20)_5300




-26BW_NVNT_ANT1_802_11n(HT20)_5300




99% OCB NVNT ANT1_802_11n(HT20)_5320




-26BW_NVNT ANT1_802_11n(HT20)_5320




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5260




-26BW_NVNT_ANT1_802_11ac(VHT20)_5260




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5300




-26BW_NVNT_ANT1_802_11ac(VHT20)_5300




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5320




-26BW_NVNT_ANT1_802_11ac(VHT20)_5320




99% OCB NVNT ANT1_802_11n(HT40)_5270




-26BW_NVNT_ANT1_802_11n(HT40)_5270




99% OCB NVNT ANT1_802_11n(HT40)_5310




-26BW_NVNT_ANT1_802_11n(HT40)_5310




99%_OCB_NVNT_ANT1_802_11ac(VHT40)_5270




-26BW_NVNT_ANT1_802_11ac(VHT40)_5270




99%_OCB_NVNT_ANT1_802_11ac(VHT40)_5310




-26BW_NVNT_ANT1_802_11ac(VHT40)_5310



99%_OCB_NVNT_ANT1_802_11ax(HE20)_5260



-26BW_NVNT_ANT1_802_11ax(HE20)_5260




99% OCB_NVNT_ANT1_802_11ax(HE20)_5300




-26BW_NVNT_ANT1_802_11ax(HE20)_5300




99%_OCB_NVNT_ANT1_802_11ax(HE20)_5320




-26BW_NVNT_ANT1_802_11ax(HE20)_5320




99%_OCB_NVNT_ANT1_802_11ax(HE40)_5270




-26BW_NVNT_ANT1_802_11ax(HE40)_5270




99%_OCB_NVNT_ANT1_802_11ax(HE40)_5310




-26BW_NVNT_ANT1_802_11ax(HE40)_5310




99%_OCB_NVNT_ANT1_802_11ac(VHT80)_5290




-26BW_NVNT_ANT1_802_11ac(VHT80)_5290



99%_OCB_NVNT_ANT1_802_11ax(HE80)_5290




-26BW_NVNT_ANT1_802_11ax(HE80)_5290




Band 3 (5500-5570 MHz):

Condition	Antenna	Modulation	Frequency(MHz)	26dB Emission Bandwidth(MHz)	Occupied Bandwidth(MHz)
NVNT	ANT1	802.11a	5500	36.86	18.28
NVNT	ANT1	802.11a	5600	38.36	18.14
NVNT	ANT1	802.11a	5700.00	36.72	17.99
NVNT	ANT1	802.11n(HT20)	5500	37.61	18.20
NVNT	ANT1	802.11n(HT20)	5600	38.30	18.78
NVNT	ANT1	802.11n(HT20)	5700.00	37.88	18.55
NVNT	ANT1	802.11ac(VHT20)	5500	38.75	18.98
NVNT	ANT1	802.11ac(VHT20)	5600	38.33	18.21
NVNT	ANT1	802.11ac(VHT20)	5700.00	38.33	18.66
NVNT	ANT1	802.11n(HT40)	5510	87.19	43.16
NVNT	ANT1	802.11n(HT40)	5590	87.02	45.61
NVNT	ANT1	802.11n(HT40)	5670	76.13	37.05
NVNT	ANT1	802.11ac(VHT40)	5510	88.64	43.61
NVNT	ANT1	802.11ac(VHT40)	5590	90.78	46.28
NVNT	ANT1	802.11ac(VHT40)	5670	81.57	36.93
NVNT	ANT1	802.11ax(HE20)	5500.00	38.10	18.28
NVNT	ANT1	802.11ax(HE20)	5600.00	40.38	18.84
NVNT	ANT1	802.11ax(HE20)	5700.00	39.54	18.55
NVNT	ANT1	802.11ax(HE40)	5510.00	86.76	43.93
NVNT	ANT1	802.11ax(HE40)	5590.00	89.66	44.34
NVNT	ANT1	802.11ax(HE40)	5670.00	88.91	39.75
NVNT	ANT1	802.11ac(VHT80)	5530	152.98	75.95
NVNT	ANT1	802.11ac(VHT80)	5610	171.06	76.45
NVNT	ANT1	802.11ax(HE80)	5530.00	149.98	75.98
NVNT	ANT1	802.11ax(HE80)	5610.00	174.67	76.39


99%_OCB_NVNT_ANT1_802_11a_5500




-26BW_NVNT_ANT1_802_11a_5500




99%_OCB_NVNT_ANT1_802_11a_5600




-26BW_NVNT_ANT1_802_11a_5600




99%_OCB_NVNT_ANT1_802_11a_5700




-26BW_NVNT_ANT1_802_11a_5700




99% OCB NVNT ANT1_802_11n(HT20)_5500




-26BW_NVNT_ANT1_802_11n(HT20)_5500




99% OCB NVNT ANT1_802_11n(HT20)_5600




-26BW_NVNT_ANT1_802_11n(HT20)_5600




99% OCB NVNT ANT1_802_11n(HT20)_5700



-26BW_NVNT_ANT1_802_11n(HT20)_5700




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5500




-26BW_NVNT_ANT1_802_11ac(VHT20)_5500




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5600



-26BW_NVNT_ANT1_802_11ac(VHT20)_5600




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5700




-26BW_NVNT_ANT1_802_11ac(VHT20)_5700




99% OCB NVNT ANT1_802_11n(HT40)_5510




-26BW_NVNT_ANT1_802_11n(HT40)_5510




99% OCB NVNT ANT1_802_11n(HT40)_5590




-26BW_NVNT_ANT1_802_11n(HT40)_5590




99% OCB NVNT ANT1_802_11n(HT40)_5670



-26BW_NVNT_ANT1_802_11n(HT40)_5670



99%_OCB_NVNT_ANT1_802_11ac(VHT40)_5510



-26BW_NVNT_ANT1_802_11ac(VHT40)_5510

