

TEST REPORT

Application No.: SZCR2508003787IT

Applicant: Shenzhen Viwoods Technology & Design Co., Ltd.

Address of Applicant: 705, W2-A Bldg, Hi-tech Ind. Village, No.025 Hi-tech S 4th Rd, Nanshan Dist, Shenzhen 518000 China

Manufacturer: Shenzhen Viwoods Technology & Design Co., Ltd.

Address of Manufacturer: Room 705, Building W2-A, High-tech Industrial Village, No. 025 High-tech South 4th Road, High-tech Community, Yuehai Subdistrict, Nanshan District, Shenzhen 518000 China

Factory: Dongguan Wisky Electronics Technology Co., Ltd.

Address of Factory: Room 401, 4th Floor, No. 47 Qilinling Road, Shahu Community, Tangxia Town, Dongguan, Guangdong, China 523710

Equipment Under Test (EUT):

EUT Name: AiPaper Reader

Model No.: AiPaper Reader, AiPaper Reader C ♣

♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.

Trade Mark: Viwoods

FCC ID: 2BKO6-SE08

Standard(s) : 47 CFR Part 15, Subpart C 15.247

Date of Receipt: 2025-08-28

Date of Test: 2025-09-10 to 2025-09-26

Date of Issue: 2025-10-01

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250800378704

Page: 2 of 162

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2025-10-01		Original

Authorized for issue by:				
				
		Leo Lai/Project Engineer		
				
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2020) Section 11.9.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2020) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Declaration of EUT Family Grouping:

Model No.: AiPaper Reader, AiPaper Reader C

Only the model AiPaper Reader was tested, since according to the declaration from the applicant, the electrical circuit design, PCB layout, components used and internal wiring and functions were identical for the above models, with only difference being of model No.



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	6
4.4 Test Location	7
4.5 Test Facility	7
4.6 Deviation from Standards	7
4.7 Abnormalities from Standard Conditions	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement	10
6.1 Antenna Requirement	10
6.1.1 Test Requirement:	10
6.1.2 Conclusion	10
7 Radio Spectrum Matter Test Results	11
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	11
7.1.1 E.U.T. Operation	11
7.1.2 Test Mode Description	11
7.1.3 Test Setup Diagram	12
7.1.4 Measurement Procedure and Data	12
7.2 Radiated Emissions which fall in the restricted bands	15
7.2.1 E.U.T. Operation	15
7.2.2 Test Mode Description	16
7.2.3 Test Setup Diagram	16
7.2.4 Measurement Procedure and Data	17
7.3 Radiated Spurious Emissions Below 1GHz	50
7.3.1 E.U.T. Operation	50
7.3.2 Test Mode Description	50
7.3.3 Test Setup Diagram	51
7.3.4 Measurement Procedure and Data	51
7.4 Radiated Spurious Emissions Above 1GHz	54
7.4.1 E.U.T. Operation	54
7.4.2 Test Mode Description	54
7.4.3 Test Setup Diagram	54
7.4.4 Measurement Procedure and Data	55
7.5 Conducted Peak Output Power	104
7.5.1 E.U.T. Operation	104



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250800378704

Page: 5 of 162

7.5.2	Test Mode Description	104
7.5.3	Test Setup Diagram	105
7.5.4	Measurement Procedure and Data.....	105
7.6	Minimum 6dB Bandwidth	106
7.6.1	E.U.T. Operation	106
7.6.2	Test Mode Description	106
7.6.3	Test Setup Diagram	106
7.6.4	Measurement Procedure and Data.....	106
7.7	Power Spectrum Density	107
7.7.1	E.U.T. Operation	107
7.7.2	Test Mode Description	107
7.7.3	Test Setup Diagram	107
7.7.4	Measurement Procedure and Data.....	107
7.8	Conducted Band Edges Measurement	108
7.8.1	E.U.T. Operation	108
7.8.2	Test Mode Description	108
7.8.3	Test Setup Diagram	109
7.8.4	Measurement Procedure and Data.....	109
7.9	Conducted Spurious Emissions	110
7.9.1	E.U.T. Operation	110
7.9.2	Test Mode Description	110
7.9.3	Test Setup Diagram	111
7.9.4	Measurement Procedure and Data.....	111
8	Test Setup Photo	112
9	EUT Constructional Details (EUT Photos)	112
10	Appendix.....	113



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3.85V from internal rechargeable battery which can be charge by AC/DC adapter
Cable(s):	Type C USB Cable: 50cm shielded & 100cm shielded
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz;802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (DBPSK, DQPSK, CCK); 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Number of Channels:	802.11b/g/n(HT20):11;802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	PIFA Antenna
Antenna Gain:	2.06dBi

Remark:The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.1\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results
 – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
 – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2025-05-07	2028-05-06
EMI Test Receiver	Rohde&Schwarz	ESR	SZ-WRG-M-047	2025-01-08	2026-01-07
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2025-07-05	2026-07-04
LISN	Rohde&Schwarz	ENV216	SEM007-01	2025-07-25	2026-07-24
LISN	ETS-LINDGREN	3816/2	SEM007-02	2025-03-03	2026-03-02

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2023-11-20	2025-11-19
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2025-07-25	2026-07-24
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2025-08-29	2027-08-28
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2025-03-04	2026-03-03
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2025-07-05	2026-07-04



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250800378704

Page: 9 of 162

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2025-03-04	2026-03-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2025-03-04	2026-03-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2025-03-04	2026-03-03
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2025-03-03	2026-03-02

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2025-03-03	2026-03-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.06dBi.

Antenna location: Refer to internal photo.



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2020) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25.3 °C

Humidity: 40.5 % RH


Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



Test Mode: 04; Line: Live line




Site : Shielding Room
Condition: Line
Job No. : 03787IT
Test mode: 04

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 *	0.1508	0.06	10.19	41.09	51.34	65.96	-14.62	QP
2 *	0.1508	0.06	10.19	33.30	43.55	55.96	-12.41	Average
3	0.1945	0.07	10.13	35.36	45.56	63.84	-18.28	QP
4	0.1945	0.07	10.13	30.98	41.18	53.84	-12.66	Average
5	0.2893	0.08	9.87	28.42	38.37	60.54	-22.17	QP
6	0.2893	0.08	9.87	20.38	30.33	50.54	-20.21	Average
7	0.5641	0.10	9.58	20.65	30.33	56.00	-25.67	QP
8	0.5641	0.10	9.58	15.06	24.74	46.00	-21.26	Average
9	7.4071	0.15	9.68	16.72	26.55	60.00	-33.45	QP
10	7.4071	0.15	9.68	11.44	21.27	50.00	-28.73	Average
11	11.3170	0.16	9.76	12.22	22.14	60.00	-37.86	QP
12	11.3170	0.16	9.76	6.15	16.07	50.00	-33.93	Average



Test Mode: 04; Line: Neutral Line



Site : Shielding Room
Condition: Neutral
Job No. : 03787IT
Test mode: 04

		Cable	LISN	Read	Limit	Over	
	Freq	Loss	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB
1 *	0.1516	0.06	10.15	39.84	50.05	65.91	-15.86 QP
2 *	0.1516	0.06	10.15	31.12	41.33	55.91	-14.58 Average
3	0.1924	0.07	10.09	34.07	44.23	63.93	-19.70 QP
4	0.1924	0.07	10.09	28.08	38.24	53.93	-15.69 Average
5	0.3003	0.08	9.77	28.86	38.71	60.24	-21.53 QP
6	0.3003	0.08	9.77	21.70	31.55	50.24	-18.69 Average
7	0.5701	0.10	9.69	25.42	35.21	56.00	-20.79 QP
8	0.5701	0.10	9.69	19.20	28.99	46.00	-17.01 Average
9	0.8174	0.10	9.60	19.06	28.76	56.00	-27.24 QP
10	0.8174	0.10	9.60	13.16	22.86	46.00	-23.14 Average
11	7.2518	0.15	9.64	17.37	27.16	60.00	-32.84 QP
12	7.2518	0.15	9.64	11.29	21.08	50.00	-28.92 Average



7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 56.3 % RH


Atmospheric Pressure: 1020 mbar



7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



Test Mode: 04; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2412 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.395	16.13	29.10	32.78	41.39	53.84	74.00	-20.16	peak
2	2390.000	16.13	29.10	32.78	39.76	52.21	74.00	-21.79	peak
3 p	2412.000	16.17	29.05	32.77	93.24	105.69	74.00	31.69	peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2412 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.032	16.13	29.10	32.78	28.76	41.21	54.00	-12.79	Average
2	2390.000	16.13	29.10	32.78	28.29	40.74	54.00	-13.26	Average
3 q	2412.000	16.17	29.05	32.77	90.28	102.73	54.00	48.73	Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2412 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2325.141	16.03	28.75	32.81	41.86	53.83	74.00	-20.17	peak
2	2390.000	16.13	29.10	32.78	39.69	52.14	74.00	-21.86	peak
3 p	2412.000	16.17	29.05	32.77	93.11	105.56	74.00	31.56	peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2412 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2361.454	16.09	29.10	32.80	28.27	40.66	54.00	-13.34	Average
2	2390.000	16.13	29.10	32.78	27.89	40.34	54.00	-13.66	Average
3 q	2412.000	16.17	29.05	32.77	71.80	84.25	54.00	30.25	Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2462 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.000	16.24	28.90	32.74	92.53	104.93	74.00	30.93	peak
2	2483.500	16.28	28.90	32.73	40.25	52.70	74.00	-21.30	peak
3	2487.305	16.28	28.90	32.73	41.83	54.28	74.00	-19.72	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 04; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2462 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	2462.000	16.24	28.90	32.74	88.79	101.19	54.00	47.19	Average
2	2483.500	16.28	28.90	32.73	29.03	41.48	54.00	-12.52	Average
3	2486.651	16.28	28.90	32.73	30.52	42.97	54.00	-11.03	Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2462 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.000	16.24	28.90	32.74	91.67	104.07	74.00	30.07	peak
2	2483.500	16.28	28.90	32.73	40.31	52.76	74.00	-21.24	peak
3	2487.656	16.28	28.90	32.73	41.92	54.37	74.00	-19.63	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 04; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2462 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	16.24	28.90	32.74	72.50	84.90	54.00	30.90 Average
2	2483.500	16.28	28.90	32.73	27.88	40.33	54.00	-13.67 Average
3	2495.963	16.29	28.90	32.73	28.44	40.90	54.00	-13.10 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2412 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.605	16.13	29.10	32.78	51.93	64.38	74.00	-9.62	peak
2	2390.000	16.13	29.10	32.78	49.40	61.85	74.00	-12.15	peak
3 p	2412.000	16.17	29.05	32.77	94.13	106.58	74.00	32.58	peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2412 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	16.13	29.10	32.78	32.10	44.55	54.00	-9.45	Average
2	2390.000	16.13	29.10	32.78	32.10	44.55	54.00	-9.45	Average
3 q	2412.000	16.17	29.05	32.77	84.48	96.93	54.00	42.93	Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2412 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2374.285	16.11	29.10	32.79	40.66	53.08	74.00	-20.92	peak
2	2390.000	16.13	29.10	32.78	38.43	50.88	74.00	-23.12	peak
3 p	2412.000	16.17	29.05	32.77	75.07	87.52	74.00	13.52	peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2412 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2384.649	16.13	29.10	32.78	28.18	40.63	54.00	-13.37	Average
2	2390.000	16.13	29.10	32.78	27.75	40.20	54.00	-13.80	Average
3 q	2412.000	16.17	29.05	32.77	67.60	80.05	54.00	26.05	Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2462 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	2462.000	16.24	28.90	32.74	94.37	106.77	74.00	32.77 peak
2	2483.500	16.28	28.90	32.73	56.48	68.93	74.00	-5.07 peak
3	2484.542	16.28	28.90	32.73	56.68	69.13	74.00	-4.87 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2462 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	16.24	28.90	32.74	84.86	97.26	54.00	43.26 Average
2	2483.500	16.28	28.90	32.73	36.41	48.86	54.00	-5.14 Average
3	2483.790	16.28	28.90	32.73	35.79	48.24	54.00	-5.76 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2462 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.000	16.24	28.90	32.74	75.82	88.22	74.00	14.22	peak
2	2483.500	16.28	28.90	32.73	39.55	52.00	74.00	-22.00	peak
3	2497.779	16.30	28.90	32.73	41.16	53.63	74.00	-20.37	peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2462 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	16.24	28.90	32.74	68.27	80.67	54.00	26.67 Average
2	2483.500	16.28	28.90	32.73	28.09	40.54	54.00	-13.46 Average
3	2486.752	16.28	28.90	32.73	28.41	40.86	54.00	-13.14 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2412 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.363	16.13	29.10	32.78	53.90	66.35	74.00	-7.65	peak
2	2390.000	16.13	29.10	32.78	52.84	65.29	74.00	-8.71	peak
3 p	2412.000	16.17	29.05	32.77	93.12	105.57	74.00	31.57	peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2412 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	16.13	29.10	32.78	33.30	45.75	54.00	-8.25	Average
2	2390.000	16.13	29.10	32.78	33.30	45.75	54.00	-8.25	Average
3 q	2412.000	16.17	29.05	32.77	84.21	96.66	54.00	42.66	Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2412 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.363	16.13	29.10	32.78	40.73	53.18	74.00	-20.82	peak
2	2390.000	16.13	29.10	32.78	38.60	51.05	74.00	-22.95	peak
3 p	2412.000	16.17	29.05	32.77	74.93	87.38	74.00	13.38	peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2412 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2378.497	16.12	29.10	32.79	28.25	40.68	54.00	-13.32	Average
2	2390.000	16.13	29.10	32.78	27.86	40.31	54.00	-13.69	Average
3 q	2412.000	16.17	29.05	32.77	67.81	80.26	54.00	26.26	Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2462 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.000	16.24	28.90	32.74	94.50	106.90	74.00	32.90	peak
2	2483.500	16.28	28.90	32.73	55.32	67.77	74.00	-6.23	peak
3	2483.840	16.28	28.90	32.73	58.15	70.60	74.00	-3.40	peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2462 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	16.24	28.90	32.74	85.33	97.73	54.00	43.73 Average
2	2483.500	16.28	28.90	32.73	38.06	50.51	54.00	-3.49 Average
3	2484.141	16.28	28.90	32.73	37.56	50.01	54.00	-3.99 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2462 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.000	16.24	28.90	32.74	74.95	87.35	74.00	13.35	peak
2	2483.500	16.28	28.90	32.73	41.28	53.73	74.00	-20.27	peak
3	2484.091	16.28	28.90	32.73	41.24	53.69	74.00	-20.31	peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2462 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	2462.000	16.24	28.90	32.74	68.11	80.51	54.00	26.51	Average
2	2483.500	16.28	28.90	32.73	28.60	41.05	54.00	-12.95	Average
3	2498.687	16.30	28.90	32.73	28.47	40.94	54.00	-13.06	Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2422 Band edge
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.075	16.13	29.10	32.78	56.24	68.69	74.00	-5.31	peak
2	2390.000	16.13	29.10	32.78	54.41	66.86	74.00	-7.14	peak
3 p	2422.000	16.18	29.01	32.76	91.56	103.99	74.00	29.99	peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2422 Band edge
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.827	16.13	29.10	32.78	37.00	49.45	54.00	-4.55 Average
2	2390.000	16.13	29.10	32.78	37.29	49.74	54.00	-4.26 Average
3 q	2422.000	16.18	29.01	32.76	81.80	94.23	54.00	40.23 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2422 Band edge
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.376	16.13	29.10	32.78	41.46	53.91	74.00	-20.09 peak
2	2390.000	16.13	29.10	32.78	39.64	52.09	74.00	-21.91 peak
3 p	2422.000	16.18	29.01	32.76	74.88	87.31	74.00	13.31 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2422 Band edge
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.677	16.13	29.10	32.78	28.97	41.42	54.00	-12.58 Average
2	2390.000	16.13	29.10	32.78	29.24	41.69	54.00	-12.31 Average
3 q	2422.000	16.18	29.01	32.76	65.50	77.93	54.00	23.93 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2452 Band edge
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2452.000	16.23	28.90	32.75	89.15	101.53	74.00	27.53	peak
2	2483.500	16.28	28.90	32.73	55.86	68.31	74.00	-5.69	peak
3	2484.570	16.28	28.90	32.73	57.01	69.46	74.00	-4.54	peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2452 Band edge
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	2452.000	16.23	28.90	32.75	78.67	91.05	54.00	37.05	Average
2	2483.500	16.28	28.90	32.73	36.85	49.30	54.00	-4.70	Average
3	2483.865	16.28	28.90	32.73	36.72	49.17	54.00	-4.83	Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2452 Band edge
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2452.000	16.23	28.90	32.75	73.43	85.81	74.00	11.81	peak
2	2483.500	16.28	28.90	32.73	40.55	53.00	74.00	-21.00	peak
3	2484.711	16.28	28.90	32.73	42.85	55.30	74.00	-18.70	peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2452 Band edge
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	2452.000	16.23	28.90	32.75	62.72	75.10	54.00	21.10	Average
2	2483.500	16.28	28.90	32.73	28.03	40.48	54.00	-13.52	Average
3	2487.112	16.28	28.90	32.73	28.69	41.14	54.00	-12.86	Average



7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.2 °C

Humidity: 47.5 % RH


Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Test Mode: 04; Polarity: Horizontal




Site : chamber
Condition: 3m HORIZONTAL
Job No. : 03787IT
Test Mode: 04

	Ant	Cable	Preamp	Read		Limit	Over	
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.000	21.20	0.74	27.65	23.52	17.81	40.00	-22.19 QP
2	50.409	12.69	0.90	27.63	25.09	11.05	40.00	-28.95 QP
3	196.510	14.10	1.69	27.79	35.58	23.58	43.50	-19.92 QP
4 q	278.067	16.97	2.03	27.56	40.45	31.89	46.00	-14.11 QP
5	694.417	25.82	3.39	27.85	25.05	26.41	46.00	-19.59 QP
6	952.094	28.17	4.08	26.66	24.29	29.88	46.00	-16.12 QP



Test Mode: 04; Polarity: Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : 03787IT
Test Mode: 04

	Ant	Cable	Preamp	Read		Limit	Over	
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	48.163	13.25	0.89	27.63	33.64	20.15	40.00	-19.85 QP
2	50.232	12.72	0.90	27.63	33.46	19.45	40.00	-20.55 QP
3	180.649	14.11	1.63	27.77	36.34	24.31	43.50	-19.19 QP
4	265.676	17.07	1.99	27.59	34.24	25.71	46.00	-20.29 QP
5	599.321	24.42	3.10	28.10	26.97	26.39	46.00	-19.61 QP
6 q	935.546	28.18	4.05	26.76	24.65	30.12	46.00	-15.88 QP



7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 56.3 % RH

Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram



Above 1GHz



7.4.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



Test Mode: 04; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 03787IT\03860IT
 Mode : 2412 TX RSE
 : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7.43	34.40	54.22	52.54	40.15	74.00	-33.85 peak
2	8.89	35.40	53.15	52.58	43.72	74.00	-30.28 peak
3 p	8.49	35.70	53.18	62.62	53.63	74.00	-20.37 peak
4	10.72	37.50	53.34	51.76	46.64	74.00	-27.36 peak
5	10.97	39.62	52.91	50.91	48.59	74.00	-25.41 peak
6	11.47	44.09	52.43	48.35	51.48	74.00	-22.52 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2412 TX RSE
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4824.000	7.43	34.40	54.22	45.30	32.91	54.00	-21.09 Average
2	6756.708	8.71	35.21	53.18	45.23	35.97	54.00	-18.03 Average
3	7236.000	8.49	35.70	53.18	61.47	52.48	54.00	-1.52 Average
4	9648.000	10.72	37.50	53.34	43.60	38.48	54.00	-15.52 Average
5	13957.530	10.97	39.62	52.91	44.05	41.73	54.00	-12.27 Average
6	17741.740	11.35	43.84	52.53	41.36	44.02	54.00	-9.98 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2412 TX RSE
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4824.000	7.43	34.40	54.22	52.97	40.58	74.00	-33.42 peak
2	6071.417	8.92	35.04	53.11	52.90	43.75	74.00	-30.25 peak
3 p	7236.000	8.49	35.70	53.18	62.07	53.08	74.00	-20.92 peak
4	9648.000	10.72	37.50	53.34	52.64	47.52	74.00	-26.48 peak
5	13957.530	10.97	39.62	52.91	50.45	48.13	74.00	-25.87 peak
6	17639.470	11.28	43.68	52.58	48.71	51.09	74.00	-22.91 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2412 TX RSE
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4824.000	7.43	34.40	54.22	44.02	31.63	54.00	-22.37 Average
2	6995.172	8.56	35.71	53.20	44.87	35.94	54.00	-18.06 Average
3 q	7236.000	8.49	35.70	53.18	60.25	51.26	54.00	-2.74 Average
4	9648.000	10.72	37.50	53.34	44.64	39.52	54.00	-14.48 Average
5	13957.530	10.97	39.62	52.91	43.24	40.92	54.00	-13.08 Average
6	17793.090	11.38	43.89	52.50	41.14	43.91	54.00	-10.09 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 03787IT\03860IT
 Mode : 2437 TX RSE
 : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4874.000	7.47	34.60	54.21	52.46	40.32	74.00 -33.68 peak
2	5949.811	8.86	34.70	53.15	53.27	43.68	74.00 -30.32 peak
3 p	7311.000	8.47	35.70	53.17	62.74	53.74	74.00 -20.26 peak
4	9748.000	10.69	37.40	53.30	50.82	45.61	74.00 -28.39 peak
5	13957.530	10.97	39.62	52.91	50.04	47.72	74.00 -26.28 peak
6	17639.470	11.28	43.68	52.58	49.17	51.55	74.00 -22.45 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2437 TX RSE
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4874.000	7.47	34.60	54.21	44.66	32.52	54.00	-21.48 Average
2	5424.184	8.07	34.65	53.71	47.42	36.43	54.00	-17.57 Average
3	7311.000	8.47	35.70	53.17	61.39	52.39	54.00	-1.61 Average
4	9748.000	10.69	37.40	53.30	44.64	39.43	54.00	-14.57 Average
5	13957.530	10.97	39.62	52.91	43.18	40.86	54.00	-13.14 Average
6	17844.590	11.41	43.90	52.48	40.49	43.32	54.00	-10.68 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2437 TX RSE
: 2.4G WIFI 11B

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4874.000	7.47	34.60	54.21	51.74	39.60	74.00 -34.40 peak
2	6470.026	8.88	35.54	53.15	52.35	43.62	74.00 -30.38 peak
3	7311.000	8.47	35.70	53.17	61.52	52.52	74.00 -21.48 peak
4	9748.000	10.69	37.40	53.30	51.01	45.80	74.00 -28.20 peak
5	13957.530	10.97	39.62	52.91	50.62	48.30	74.00 -25.70 peak
6	18000.000	11.50	44.30	52.40	48.47	51.87	74.00 -22.13 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2437 TX RSE
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	7.47	34.60	54.21	44.67	32.53	54.00	-21.47 Average
2	6088.991	8.92	35.08	53.11	45.66	36.55	54.00	-17.45 Average
3 q	7311.000	8.47	35.70	53.17	60.27	51.27	54.00	-2.73 Average
4	9748.000	10.69	37.40	53.30	43.15	37.94	54.00	-16.06 Average
5	13957.530	10.97	39.62	52.91	43.11	40.79	54.00	-13.21 Average
6	17844.590	11.41	43.90	52.48	41.27	44.10	54.00	-9.90 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2462 TX RSE
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4924.000	7.50	34.65	54.21	50.31	38.25	74.00	-35.75 peak
2	5697.365	8.47	34.31	53.41	54.81	44.18	74.00	-29.82 peak
3 p	7386.000	8.44	35.77	53.16	62.49	53.54	74.00	-20.46 peak
4	9848.000	10.66	37.20	53.26	51.32	45.92	74.00	-28.08 peak
5	13957.530	10.97	39.62	52.91	49.80	47.48	74.00	-26.52 peak
6	17741.740	11.35	43.84	52.53	49.46	52.12	74.00	-21.88 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2462 TX RSE
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4924.000	7.50	34.65	54.21	45.39	33.33	54.00	-20.67 Average
2	6071.417	8.92	35.04	53.11	45.41	36.26	54.00	-17.74 Average
3	7386.000	8.44	35.77	53.16	60.90	51.95	54.00	-2.05 Average
4	9848.000	10.66	37.20	53.26	43.65	38.25	54.00	-15.75 Average
5	13957.530	10.97	39.62	52.91	43.67	41.35	54.00	-12.65 Average
6	17639.470	11.28	43.68	52.58	41.97	44.35	54.00	-9.65 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2462 TX RSE
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4924.000	7.50	34.65	54.21	50.80	38.74	74.00	-35.26 peak
2	6583.209	8.83	35.37	53.16	52.59	43.63	74.00	-30.37 peak
3 p	7386.000	8.44	35.77	53.16	61.46	52.51	74.00	-21.49 peak
4	9848.000	10.66	37.20	53.26	51.40	46.00	74.00	-28.00 peak
5	13957.530	10.97	39.62	52.91	50.03	47.71	74.00	-26.29 peak
6	17948.050	11.47	44.09	52.43	47.82	50.95	74.00	-23.05 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2462 TX RSE
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4924.000	7.50	34.65	54.21	43.46	31.40	54.00	-22.60 Average
2	6432.732	8.89	35.40	53.15	44.84	35.98	54.00	-18.02 Average
3	7386.000	8.44	35.77	53.16	60.49	51.54	54.00	-2.46 Average
4	9848.000	10.66	37.20	53.26	44.74	39.34	54.00	-14.66 Average
5	13957.530	10.97	39.62	52.91	43.34	41.02	54.00	-12.98 Average
6	17793.090	11.38	43.89	52.50	41.15	43.92	54.00	-10.08 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2412 TX RSE
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4824.000	7.43	34.40	54.22	52.21	39.82	74.00	-34.18 peak
2	6974.982	8.58	35.75	53.20	52.53	43.66	74.00	-30.34 peak
3 p	7236.000	8.49	35.70	53.18	61.05	52.06	74.00	-21.94 peak
4	9648.000	10.72	37.50	53.34	50.99	45.87	74.00	-28.13 peak
5	13957.530	10.97	39.62	52.91	49.61	47.29	74.00	-26.71 peak
6	17793.090	11.38	43.89	52.50	48.51	51.28	74.00	-22.72 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2412 TX RSE
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4824.000	7.43	34.40	54.22	45.43	33.04	54.00	-20.96 Average
2	6995.172	8.56	35.71	53.20	44.62	35.69	54.00	-18.31 Average
3 q	7236.000	8.49	35.70	53.18	54.64	45.65	54.00	-8.35 Average
4	9648.000	10.72	37.50	53.34	44.59	39.47	54.00	-14.53 Average
5	13957.530	10.97	39.62	52.91	43.75	41.43	54.00	-12.57 Average
6	17948.050	11.47	44.09	52.43	40.24	43.37	54.00	-10.63 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 03787IT\03860IT
 Mode : 2412 TX RSE
 : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4824.000	7.43	34.40	54.22	52.55	40.16	74.00	-33.84 peak
2	6195.508	8.91	34.72	53.12	52.93	43.44	74.00	-30.56 peak
3 p	7236.000	8.49	35.70	53.18	61.96	52.97	74.00	-21.03 peak
4	9648.000	10.72	37.50	53.34	51.86	46.74	74.00	-27.26 peak
5	13957.530	10.97	39.62	52.91	49.78	47.46	74.00	-26.54 peak
6	17690.530	11.32	43.78	52.55	48.05	50.60	74.00	-23.40 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2412 TX RSE
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4824.000	7.43	34.40	54.22	44.54	32.15	54.00	-21.85 Average
2	6470.026	8.88	35.54	53.15	44.70	35.97	54.00	-18.03 Average
3	7236.000	8.49	35.70	53.18	53.55	44.56	54.00	-9.44 Average
4	9648.000	10.72	37.50	53.34	44.48	39.36	54.00	-14.64 Average
5	13957.530	10.97	39.62	52.91	42.90	40.58	54.00	-13.42 Average
6	17793.090	11.38	43.89	52.50	41.08	43.85	54.00	-10.15 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 03787IT\03860IT
 Mode : 2437 TX RSE
 : 2.4G WIFI 11G

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4874.000	7.47	34.60	54.21	52.30	40.16	74.00 -33.84 peak
2	6303.890	8.90	34.99	53.13	52.34	43.10	74.00 -30.90 peak
3 p	7311.000	8.47	35.70	53.17	66.93	57.93	74.00 -16.07 peak
4	9748.000	10.69	37.40	53.30	50.16	44.95	74.00 -29.05 peak
5	13957.530	10.97	39.62	52.91	51.71	49.39	74.00 -24.61 peak
6	17793.090	11.38	43.89	52.50	49.07	51.84	74.00 -22.16 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2437 TX RSE
: 2.4G WIFI 11G


	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 4874.000	7.47	34.60	54.21	47.08	34.94	54.00	-19.06	Average
2 6106.616	8.92	35.07	53.11	44.89	35.77	54.00	-18.23	Average
3 q 7311.000	8.47	35.70	53.17	57.46	48.46	54.00	-5.54	Average
4 9748.000	10.69	37.40	53.30	43.83	38.62	54.00	-15.38	Average
5 13957.530	10.97	39.62	52.91	42.94	40.62	54.00	-13.38	Average
6 17639.470	11.28	43.68	52.58	41.46	43.84	54.00	-10.16	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 04; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2437 TX RSE
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4874.000	7.47	34.60	54.21	52.59	40.45	74.00	-33.55 peak
2	6470.026	8.88	35.54	53.15	52.13	43.40	74.00	-30.60 peak
3 p	7311.000	8.47	35.70	53.17	64.18	55.18	74.00	-18.82 peak
4	9748.000	10.69	37.40	53.30	52.11	46.90	74.00	-27.10 peak
5	13957.530	10.97	39.62	52.91	50.44	48.12	74.00	-25.88 peak
6	17793.090	11.38	43.89	52.50	48.27	51.04	74.00	-22.96 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2437 TX RSE
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4874.000	7.47	34.60	54.21	45.55	33.41	54.00	-20.59 Average
2	6995.172	8.56	35.71	53.20	44.87	35.94	54.00	-18.06 Average
3	7311.000	8.47	35.70	53.17	55.26	46.26	54.00	-7.74 Average
4	9748.000	10.69	37.40	53.30	43.21	38.00	54.00	-16.00 Average
5	13957.530	10.97	39.62	52.91	43.64	41.32	54.00	-12.68 Average
6	17896.250	11.44	43.90	52.45	41.24	44.13	54.00	-9.87 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 03787IT\03860IT
 Mode : 2462 TX RSE
 : 2.4G WIFI 11G

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7.50	34.65	54.21	52.26	40.20	74.00	-33.80 peak
2	8.88	34.77	53.13	54.22	44.74	74.00	-29.26 peak
3 p	8.44	35.77	53.16	67.13	58.18	74.00	-15.82 peak
4	10.66	37.20	53.26	50.43	45.03	74.00	-28.97 peak
5	10.97	39.62	52.91	50.92	48.60	74.00	-25.40 peak
6	11.38	43.89	52.50	49.11	51.88	74.00	-22.12 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2462 TX RSE
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4924.000	7.50	34.65	54.21	43.54	31.48	54.00	-22.52 Average
2	6995.172	8.56	35.71	53.20	45.27	36.34	54.00	-17.66 Average
3 q	7386.000	8.44	35.77	53.16	57.11	48.16	54.00	-5.84 Average
4	9848.000	10.66	37.20	53.26	43.61	38.21	54.00	-15.79 Average
5	13957.530	10.97	39.62	52.91	43.48	41.16	54.00	-12.84 Average
6	17741.740	11.35	43.84	52.53	41.12	43.78	54.00	-10.22 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2462 TX RSE
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	7.50	34.65	54.21	50.97	38.91	74.00	-35.09 peak
2	6340.436	8.90	34.92	53.14	53.12	43.80	74.00	-30.20 peak
3 p	7386.000	8.44	35.77	53.16	63.89	54.94	74.00	-19.06 peak
4	9848.000	10.66	37.20	53.26	51.12	45.72	74.00	-28.28 peak
5	13957.530	10.97	39.62	52.91	50.72	48.40	74.00	-25.60 peak
6	17639.470	11.28	43.68	52.58	50.34	52.72	74.00	-21.28 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2462 TX RSE
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	7.50	34.65	54.21	44.34	32.28	54.00	-21.72 Average
2	5949.811	8.86	34.70	53.15	45.13	35.54	54.00	-18.46 Average
3	7386.000	8.44	35.77	53.16	54.67	45.72	54.00	-8.28 Average
4	9848.000	10.66	37.20	53.26	43.64	38.24	54.00	-15.76 Average
5	13957.530	10.97	39.62	52.91	42.44	40.12	54.00	-13.88 Average
6	17793.090	11.38	43.89	52.50	42.19	44.96	54.00	-9.04 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 03787IT\03860IT
 Mode : 2412 TX RSE
 : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4824.000	7.43	34.40	54.22	52.79	40.40	74.00 -33.60 peak
2	6071.417	8.92	35.04	53.11	52.98	43.83	74.00 -30.17 peak
3	7236.000	8.49	35.70	53.18	61.72	52.73	74.00 -21.27 peak
4	9648.000	10.72	37.50	53.34	52.84	47.72	74.00 -26.28 peak
5	13957.530	10.97	39.62	52.91	50.48	48.16	74.00 -25.84 peak
6	17639.470	11.28	43.68	52.58	48.94	51.32	74.00 -22.68 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2412 TX RSE
: 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 4824.000	7.43	34.40	54.22	45.41	33.02	54.00	-20.98 Average
2 6340.436	8.90	34.92	53.14	45.79	36.47	54.00	-17.53 Average
3 q 7236.000	8.49	35.70	53.18	54.61	45.62	54.00	-8.38 Average
4 9648.000	10.72	37.50	53.34	44.61	39.49	54.00	-14.51 Average
5 13957.530	10.97	39.62	52.91	42.58	40.26	54.00	-13.74 Average
6 17639.470	11.28	43.68	52.58	41.79	44.17	54.00	-9.83 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2412 TX RSE
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	7.43	34.40	54.22	53.04	40.65	74.00	-33.35 peak
2	5949.811	8.86	34.70	53.15	52.92	43.33	74.00	-30.67 peak
3 p	7236.000	8.49	35.70	53.18	60.77	51.78	74.00	-22.22 peak
4	9648.000	10.72	37.50	53.34	51.30	46.18	74.00	-27.82 peak
5	13957.530	10.97	39.62	52.91	49.92	47.60	74.00	-26.40 peak
6	17793.090	11.38	43.89	52.50	48.89	51.66	74.00	-22.34 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2412 TX RSE
: 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 4824.000	7.43	34.40	54.22	45.03	32.64	54.00	-21.36 Average
2 6995.172	8.56	35.71	53.20	44.86	35.93	54.00	-18.07 Average
3 q 7236.000	8.49	35.70	53.18	53.57	44.58	54.00	-9.42 Average
4 9648.000	10.72	37.50	53.34	43.62	38.50	54.00	-15.50 Average
5 13957.530	10.97	39.62	52.91	44.41	42.09	54.00	-11.91 Average
6 17639.470	11.28	43.68	52.58	41.19	43.57	54.00	-10.43 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 03787IT\03860IT
 Mode : 2437 TX RSE
 : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4874.000	7.47	34.60	54.21	51.84	39.70	74.00 -34.30 peak
2	6470.026	8.88	35.54	53.15	53.35	44.62	74.00 -29.38 peak
3	7311.000	8.47	35.70	53.17	68.08	59.08	74.00 -14.92 peak
4	9748.000	10.69	37.40	53.30	50.79	45.58	74.00 -28.42 peak
5	13957.530	10.97	39.62	52.91	49.35	47.03	74.00 -26.97 peak
6	17793.090	11.38	43.89	52.50	49.99	52.76	74.00 -21.24 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2437 TX RSE
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	7.47	34.60	54.21	45.17	33.03	54.00	-20.97 Average
2	5949.811	8.86	34.70	53.15	45.94	36.35	54.00	-17.65 Average
3	7311.000	8.47	35.70	53.17	57.73	48.73	54.00	-5.27 Average
4	9748.000	10.69	37.40	53.30	44.28	39.07	54.00	-14.93 Average
5	13957.530	10.97	39.62	52.91	43.55	41.23	54.00	-12.77 Average
6	17741.740	11.35	43.84	52.53	41.43	44.09	54.00	-9.91 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2437 TX RSE
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4874.000	7.47	34.60	54.21	52.28	40.14	74.00	-33.86 peak
2	5254.440	7.87	34.11	53.90	54.75	42.83	74.00	-31.17 peak
3 p	7311.000	8.47	35.70	53.17	64.02	55.02	74.00	-18.98 peak
4	9748.000	10.69	37.40	53.30	49.74	44.53	74.00	-29.47 peak
5	13957.530	10.97	39.62	52.91	50.58	48.26	74.00	-25.74 peak
6	17741.740	11.35	43.84	52.53	48.95	51.61	74.00	-22.39 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2437 TX RSE
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	7.47	34.60	54.21	44.47	32.33	54.00	-21.67 Average
2	5932.638	8.83	34.67	53.17	45.22	35.55	54.00	-18.45 Average
3	7311.000	8.47	35.70	53.17	54.76	45.76	54.00	-8.24 Average
4	9748.000	10.69	37.40	53.30	43.02	37.81	54.00	-16.19 Average
5	13957.530	10.97	39.62	52.91	43.09	40.77	54.00	-13.23 Average
6	17690.530	11.32	43.78	52.55	41.69	44.24	54.00	-9.76 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2462 TX RSE
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	7.50	34.65	54.21	52.06	40.00	74.00	-34.00 peak
2	6340.436	8.90	34.92	53.14	53.09	43.77	74.00	-30.23 peak
3 p	7386.000	8.44	35.77	53.16	66.73	57.78	74.00	-16.22 peak
4	9848.000	10.66	37.20	53.26	51.39	45.99	74.00	-28.01 peak
5	13957.530	10.97	39.62	52.91	50.02	47.70	74.00	-26.30 peak
6	17741.740	11.35	43.84	52.53	49.86	52.52	74.00	-21.48 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2462 TX RSE
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	7.50	34.65	54.21	44.17	32.11	54.00	-21.89 Average
2	5949.811	8.86	34.70	53.15	45.92	36.33	54.00	-17.67 Average
3	7386.000	8.44	35.77	53.16	56.02	47.07	54.00	-6.93 Average
4	9848.000	10.66	37.20	53.26	44.43	39.03	54.00	-14.97 Average
5	13957.530	10.97	39.62	52.91	43.41	41.09	54.00	-12.91 Average
6	17741.740	11.35	43.84	52.53	41.51	44.17	54.00	-9.83 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 03787IT\03860IT
 Mode : 2462 TX RSE
 : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7.50	34.65	54.21	51.42	39.36	74.00	-34.64 peak
2	8.88	35.50	53.15	51.96	43.19	74.00	-30.81 peak
3 p	8.44	35.77	53.16	64.98	56.03	74.00	-17.97 peak
4	10.66	37.20	53.26	51.44	46.04	74.00	-27.96 peak
5	10.97	39.62	52.91	49.89	47.57	74.00	-26.43 peak
6	11.47	44.09	52.43	49.47	52.60	74.00	-21.40 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2462 TX RSE
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4924.000	7.50	34.65	54.21	43.64	31.58	54.00	-22.42 Average
2	6995.172	8.56	35.71	53.20	44.53	35.60	54.00	-18.40 Average
3	7386.000	8.44	35.77	53.16	56.57	47.62	54.00	-6.38 Average
4	9848.000	10.66	37.20	53.26	43.38	37.98	54.00	-16.02 Average
5	13957.530	10.97	39.62	52.91	43.41	41.09	54.00	-12.91 Average
6	17793.090	11.38	43.89	52.50	41.85	44.62	54.00	-9.38 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2422 TX RSE
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4844.000	7.44	34.48	54.21	52.41	40.12	74.00	-33.88 peak
2	6124.292	8.92	35.00	53.11	52.41	43.22	74.00	-30.78 peak
3 p	7266.000	8.48	35.70	53.17	61.58	52.59	74.00	-21.41 peak
4	9688.000	10.71	37.50	53.32	49.75	44.64	74.00	-29.36 peak
5	13957.530	10.97	39.62	52.91	49.72	47.40	74.00	-26.60 peak
6	17639.470	11.28	43.68	52.58	49.23	51.61	74.00	-22.39 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2422 TX RSE
: 2.4G WIFI 11N40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 4844.000	7.44	34.48	54.21	46.01	33.72	54.00	-20.28 Average
2 6303.890	8.90	34.99	53.13	45.35	36.11	54.00	-17.89 Average
3 q 7266.000	8.48	35.70	53.17	54.34	45.35	54.00	-8.65 Average
4 9688.000	10.71	37.50	53.32	43.11	38.00	54.00	-16.00 Average
5 13957.530	10.97	39.62	52.91	42.64	40.32	54.00	-13.68 Average
6 17844.590	11.41	43.90	52.48	41.62	44.45	54.00	-9.55 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2422 TX RSE
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4844.000	7.44	34.48	54.21	52.26	39.97	74.00	-34.03 peak
2	6414.167	8.89	35.29	53.14	53.07	44.11	74.00	-29.89 peak
3	7266.000	8.48	35.70	53.17	60.59	51.60	74.00	-22.40 peak
4	9688.000	10.71	37.50	53.32	50.17	45.06	74.00	-28.94 peak
5	13957.530	10.97	39.62	52.91	50.39	48.07	74.00	-25.93 peak
6	p17793.090	11.38	43.89	52.50	48.94	51.71	74.00	-22.29 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2422 TX RSE
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4844.000	7.44	34.48	54.21	44.75	32.46	54.00	-21.54 Average
2	6106.616	8.92	35.07	53.11	44.87	35.75	54.00	-18.25 Average
3	7266.000	8.48	35.70	53.17	53.84	44.85	54.00	-9.15 Average
4	9688.000	10.71	37.50	53.32	43.36	38.25	54.00	-15.75 Average
5	13957.530	10.97	39.62	52.91	42.93	40.61	54.00	-13.39 Average
6	17948.050	11.47	44.09	52.43	40.99	44.12	54.00	-9.88 Average



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2437 TX RSE
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4874.000	7.47	34.60	54.21	52.83	40.69	74.00	-33.31 peak
2	6213.441	8.91	34.75	53.12	52.71	43.25	74.00	-30.75 peak
3 p	7311.000	8.47	35.70	53.17	67.87	58.87	74.00	-15.13 peak
4	9748.000	10.69	37.40	53.30	52.04	46.83	74.00	-27.17 peak
5	13957.530	10.97	39.62	52.91	50.29	47.97	74.00	-26.03 peak
6	17741.740	11.35	43.84	52.53	48.58	51.24	74.00	-22.76 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2437 TX RSE
: 2.4G WIFI 11N40

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	7.47	34.60	54.21	45.04	32.90	54.00	-21.10 Average
2	6995.172	8.56	35.71	53.20	45.53	36.60	54.00	-17.40 Average
3	7311.000	8.47	35.70	53.17	56.93	47.93	54.00	-6.07 Average
4	9748.000	10.69	37.40	53.30	43.85	38.64	54.00	-15.36 Average
5	13957.530	10.97	39.62	52.91	43.15	40.83	54.00	-13.17 Average
6	17690.530	11.32	43.78	52.55	41.32	43.87	54.00	-10.13 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2437 TX RSE
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	7.47	34.60	54.21	52.32	40.18	74.00	-33.82 peak
2	6974.982	8.58	35.75	53.20	52.02	43.15	74.00	-30.85 peak
3 p	7311.000	8.47	35.70	53.17	62.17	53.17	74.00	-20.83 peak
4	9748.000	10.69	37.40	53.30	51.58	46.37	74.00	-27.63 peak
5	13957.530	10.97	39.62	52.91	50.68	48.36	74.00	-25.64 peak
6	17741.740	11.35	43.84	52.53	48.88	51.54	74.00	-22.46 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle



Site : chamber
 Condition: 3m VERTICAL
 Job No : 03787IT\03860IT
 Mode : 2437 TX RSE
 : 2.4G WIFI 11N40


	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4874.000	7.47	34.60	54.21	46.19	34.05	54.00 -19.95 Average
2	6432.732	8.89	35.40	53.15	45.24	36.38	54.00 -17.62 Average
3	7311.000	8.47	35.70	53.17	54.28	45.28	54.00 -8.72 Average
4	9748.000	10.69	37.40	53.30	43.97	38.76	54.00 -15.24 Average
5	13957.530	10.97	39.62	52.91	43.32	41.00	54.00 -13.00 Average
6	17741.740	11.35	43.84	52.53	41.59	44.25	54.00 -9.75 Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2452 TX RSE
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4904.000	7.49	34.69	54.21	52.63	40.60	74.00	-33.40 peak
2	6432.732	8.89	35.40	53.15	52.91	44.05	74.00	-29.95 peak
3 p	7356.000	8.45	35.71	53.16	61.02	52.02	74.00	-21.98 peak
4	9808.000	10.68	37.28	53.27	50.50	45.19	74.00	-28.81 peak
5	13957.530	10.97	39.62	52.91	50.04	47.72	74.00	-26.28 peak
6	17844.590	11.41	43.90	52.48	48.81	51.64	74.00	-22.36 peak



Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03787IT\03860IT
Mode : 2452 TX RSE
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4904.000	7.49	34.69	54.21	46.41	34.38	54.00	-19.62 Average
2	6602.265	8.81	35.30	53.16	45.01	35.96	54.00	-18.04 Average
3 q	7356.000	8.45	35.71	53.16	54.61	45.61	54.00	-8.39 Average
4	9808.000	10.68	37.28	53.27	43.16	37.85	54.00	-16.15 Average
5	13957.530	10.97	39.62	52.91	44.09	41.77	54.00	-12.23 Average
6	17793.090	11.38	43.89	52.50	41.68	44.45	54.00	-9.55 Average



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2452 TX RSE
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4904.000	7.49	34.69	54.21	52.00	39.97	74.00	-34.03 peak
2	6071.417	8.92	35.04	53.11	52.54	43.39	74.00	-30.61 peak
3	7356.000	8.45	35.71	53.16	60.45	51.45	74.00	-22.55 peak
4	9808.000	10.68	37.28	53.27	50.03	44.72	74.00	-29.28 peak
5	13957.530	10.97	39.62	52.91	51.67	49.35	74.00	-24.65 peak
6	p17741.740	11.35	43.84	52.53	49.41	52.07	74.00	-21.93 peak



Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 03787IT\03860IT
Mode : 2452 TX RSE
: 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	4904.000	7.49	34.69	54.21	44.98	32.95	54.00	-21.05 Average
2	5439.885	8.09	34.68	53.69	47.01	36.09	54.00	-17.91 Average
3	7356.000	8.45	35.71	53.16	54.58	45.58	54.00	-8.42 Average
4	9808.000	10.68	37.28	53.27	43.61	38.30	54.00	-15.70 Average
5	13957.530	10.97	39.62	52.91	43.10	40.78	54.00	-13.22 Average
6	17793.090	11.38	43.89	52.50	41.15	43.92	54.00	-10.08 Average



7.5 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2020) Section 11.9.2

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 21.2 °C

Humidity: 69.0 % RH


Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



7.6 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2020) Section 11.8.1

Limit:

≥500 kHz

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 21.2 °C


Humidity: 69.0 % RH

Atmospheric Pressure: 1020 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.7 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2020) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 21.2 °C


Humidity: 69.0 % RH

Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 6.10.4

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 21.2 °C

Humidity: 69.0 % RH


Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.9 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 21.2 °C

Humidity: 69.0 % RH


Atmospheric Pressure: 1020 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2508003787IT

9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2508003787IT



10 Appendix

1. Duty Cycle

1.1 Test Result


1.1.1 Ant1


Ant1							
Mode	Tx Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	8.383	8.413	99.64	0.02	0.04
		2437	8.383	8.413	99.64	0.02	0.04
		2462	8.383	8.413	99.64	0.02	0.04
802.11g	SISO	2412	1.392	1.428	97.48	0.11	0.06
		2437	1.392	1.427	97.55	0.11	0.06
		2462	1.393	1.428	97.55	0.11	0.03
802.11n (HT20)	SISO	2412	1.300	1.336	97.31	0.12	0.03
		2437	1.300	1.336	97.31	0.12	0.03
		2462	1.300	1.336	97.31	0.12	0.07
802.11n (HT40)	SISO	2422	0.648	0.682	95.01	0.22	0.03
		2437	0.648	0.683	94.88	0.23	0.07
		2452	0.648	0.683	94.88	0.23	0.03




1.2 Test Graph

1.2.1 Ant1







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	13.609	/	Pass
		2437	1	13.354	/	Pass
		2462	1	13.848	/	Pass
802.11g	SISO	2412	1	19.897	/	Pass
		2437	1	17.867	/	Pass
		2462	1	17.750	/	Pass
802.11n (HT20)	SISO	2412	1	18.915	/	Pass
		2437	1	19.044	/	Pass
		2462	1	18.666	/	Pass
802.11n (HT40)	SISO	2422	1	37.202	/	Pass
		2437	1	42.020	/	Pass
		2452	1	36.863	/	Pass


2.1.2 6dB BW


Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	8.666	≥ 0.5	Pass
		2437	1	9.096	≥ 0.5	Pass
		2462	1	8.691	≥ 0.5	Pass
802.11g	SISO	2412	1	16.036	≥ 0.5	Pass
		2437	1	16.024	≥ 0.5	Pass
		2462	1	15.655	≥ 0.5	Pass
802.11n (HT20)	SISO	2412	1	16.571	≥ 0.5	Pass
		2437	1	17.424	≥ 0.5	Pass
		2462	1	16.665	≥ 0.5	Pass
802.11n (HT40)	SISO	2422	1	35.372	≥ 0.5	Pass
		2437	1	36.545	≥ 0.5	Pass
		2452	1	34.423	≥ 0.5	Pass




2.2 Test Graph

2.2.1 OBW







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV



2.2.2 6dB BW




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Average Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	19.80	<=30	Pass
		2437	19.78	<=30	Pass
		2462	19.40	<=30	Pass
802.11g	SISO	2412	14.75	<=30	Pass
		2437	17.86	<=30	Pass
		2462	17.44	<=30	Pass
802.11n (HT20)	SISO	2412	14.62	<=30	Pass
		2437	18.27	<=30	Pass
		2462	17.70	<=30	Pass
802.11n (HT40)	SISO	2422	15.92	<=30	Pass
		2437	18.74	<=30	Pass
		2452	13.10	<=30	Pass

Note1: Antenna Gain: Ant1: 2.06dBi;

4. Maximum Power Spectral Density

4.1 Test Result

4.1.1 PSD

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	-11.42	<=8	Pass
		2437	-11.03	<=8	Pass
		2462	-11.31	<=8	Pass
802.11g	SISO	2412	-18.07	<=8	Pass
		2437	-15.14	<=8	Pass
		2462	-14.97	<=8	Pass
802.11n (HT20)	SISO	2412	-18.18	<=8	Pass
		2437	-14.49	<=8	Pass
		2462	-14.23	<=8	Pass

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250800378704

Page: 136 of 162

802.11n (HT40)	SISO	2422	-17.78	<=8	Pass
		2437	-16.26	<=8	Pass
		2452	-18.81	<=8	Pass
Note1: Antenna Gain: Ant1: 2.06dBi;					



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,


or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZEMC) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


4.2 Test Graph

4.2.1 PSD







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
802.11b	SISO	2412	1	11.38
		2437	1	11.14
		2462	1	11.14
802.11g	SISO	2412	1	4.92
		2437	1	7.80
		2462	1	7.70
802.11n (HT20)	SISO	2412	1	4.59
		2437	1	8.23
		2462	1	8.04
802.11n (HT40)	SISO	2422	1	3.41
		2437	1	5.05
		2452	1	1.52

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.

5.1.2 CSE

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	SISO	2412	1	11.38	-18.62	Pass
		2437	1	11.38	-18.62	Pass
		2462	1	11.38	-18.62	Pass
802.11g	SISO	2412	1	7.80	-22.20	Pass
		2437	1	7.80	-22.20	Pass
		2462	1	7.80	-22.20	Pass
802.11n (HT20)	SISO	2412	1	8.23	-21.77	Pass
		2437	1	8.23	-21.77	Pass
		2462	1	8.23	-21.77	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250800378704

Page: 145 of 162

802.11n (HT40)	SISO	2422	1	5.05	-24.95	Pass
		2437	1	5.05	-24.95	Pass
		2452	1	5.05	-24.95	Pass

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Fujian) FCC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


5.2 Test Graph

5.2.1 Ref







802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV



5.2.2 CSE

