



RF Exposure Evaluation

For

Wacebo USA, Inc.

Interactive Flat Panel Display/Interactive LED Panel/Touch Screen

Monitor/Touch Screen/Touch Monitor/Interactive LED

Test Model: E1M-L159Y

Additional Model No.: Please Refer to Page 6

Prepared for : Wacebo USA, Inc.
Address : 8 The Green Ste R, Dover, DELAWARE, 19901 USA
Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,
Shajing Street, Baoan District, Shenzhen, 518000, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : June 24, 2025
Number of tested samples : 2
Sample No. : A250611008-1, A250611008-2
Serial number : Prototype
Date of Test : June 24, 2025 ~ September 17, 2025
Date of Report : September 18, 2025



**RF Exposure Evaluation****Report Reference No.** : **LCSA06195112EI****Date of Issue** : September 18, 2025**Testing Laboratory Name** : **Shenzhen LCS Compliance Testing Laboratory Ltd.****Address** : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China**Testing Location/ Procedure** : Full application of Harmonised standards ☒
Partial application of Harmonised standards ☐
Other standard testing method ☐**Applicant's Name** : **Wacebo USA, Inc.****Address** : 8 The Green Ste R, Dover, DELAWARE, 19901 USA**Test Specification****Standard** : FCC KDB publication 447498 D01 General RF Exposure Guidance v06
FCC CFR 47 part1 1.1310
FCC CFR 47 part2 2.1091**Test Report Form No.** : TRF-4-E-214 A/0**TRF Originator** : Shenzhen LCS Compliance Testing Laboratory Ltd.**Master TRF** : Dated 2011-03**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

EUT Description. : **Interactive Flat Panel Display/Interactive LED Panel/Touch Screen Monitor/Touch Screen/Touch Monitor/Interactive LED****Trade Mark** : DABLIU**Test Model** : E1M-L159Y**Ratings** : Please Refer to Page 6**Result** : **PASS****Compiled by:**

Martin Lee/ Administrator

Supervised by:

Jack Liu/ Technique principal

Approved by:

Gavin Liang/ Manager





RF Exposure Evaluation

Test Report No. :	LCSA06195112EI	<u>September 18, 2025</u> Date of issue
--------------------------	-----------------------	--

Test Model.....	: E1M-L159Y
EUT.....	: Interactive Flat Panel Display/Interactive LED Panel/Touch Screen Monitor/Touch Screen/Touch Monitor/Interactive LED
Applicant.....	: Wacebo USA, Inc.
Address.....	: 8 The Green Ste R, Dover, DELAWARE, 19901 USA
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Wacebo USA, Inc.
Address.....	: 8 The Green Ste R, Dover, DELAWARE, 19901 USA
Telephone.....	: /
Fax.....	: /
Factory.....	: Wacebo USA, Inc.
Address.....	: 8 The Green Ste R, Dover, DELAWARE, 19901 USA
Telephone.....	: /
Fax.....	: /

Test Result	PASS
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Report Version	Issue Date	Revision Content	Revised By
000	September 18, 2025	Initial Issue	---





TABLE OF CONTENTS

Description	Page
1. Product Information.....	6
2. Evaluation Method.....	8
3. Limit.....	9
4. MPE Calculation Method.....	9
5. Conducted Power.....	9
6. Manufacturing Tolerance.....	15
7. Measurement Results.....	29
8. Conclusion.....	34
9. Description of Test Facility.....	34
10. Measurement Uncertainty.....	34





1. Product Information

EUT	: Interactive Flat Panel Display/Interactive LED Panel/Touch Screen Monitor/Touch Screen/Touch Monitor/Interactive LED
Test Model	: E1M-L159Y
Additional Model No.	: E1M-L156Y, E1M-L157Y, E1M-L158Y
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested.
Ratings	: Input(E1M-L156Y): 100-240V~, 50/60Hz, 4.6-1.9A, Max 460W Input(E1M-L157Y): 100-240V~, 50/60Hz, 5.0-2.0A, Max 500W Input(E1M-L158Y): 100-240V~, 50/60Hz, 5.8-2.4A, Max 580W Input(E1M-L159Y): 100-240V~, 50/60Hz, 7.5-3.1A, Max 750W
Hardware Version	: /
Software Version	: /
Module model	: Module 1: DCT85N2001 Module 2: WXT14R2201
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.0 (DSS) 40 channels for Bluetooth V5.0 (DTS)
Channel Spacing	: 1MHz for Bluetooth V5.0 (DSS) 2MHz for Bluetooth V5.0 (DTS)
Modulation Type	: Module 1: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0 (DSS) GFSK for Bluetooth V5.0 (DTS)
Bluetooth Version	: V5.0
Antenna Description	: Please refer to the antenna description.
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2462MHz
Channel Spacing	: 5MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	: Module 1:802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK) Module 2: 802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ax: OFDM,OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Please refer to the antenna description.
WIFI(5.2G Band)	:
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)





Modulation Type	: Module 1:802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) Module 2: 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) 802.11ax: OFDM,OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Please refer to the antenna description.
WIFI(5.3G Band)	:
Frequency Range	: 5260MHz~5320MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5260MHz~5320MHz) 2 channels for 40MHz bandwidth(5270MHz~5310MHz) 1 channels for 80MHz bandwidth(5290MHz)
Modulation Type	: Module 1:802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) Module 2: 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) 802.11ax: OFDM,OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Please refer to the antenna description.
WIFI(5.5G Band)	:
Frequency Range	: 5500MHz~5700MHz
Channel Number	: Module 1 & 2: 11 Channels for 20MHz bandwidth(5500MHz~5700MHz) 5 Channels for 40MHz bandwidth(5510MHz~5670MHz) 2 Channels for 80MHz bandwidth(5530MHz, 5610MHz)
Modulation Type	: Module 1:802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) Module 2: 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) 802.11ax: OFDM,OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Please refer to the antenna description.
WIFI(5.8G Band)	:
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	: Module 1:802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) Module 2: 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) 802.11ax: OFDM,OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Please refer to the antenna description.
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit





Device Type	: Mobile Device
Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.	

Antenna Description

Model	Function	antenna gain
E1M-L156Y, E1M-L157Y, E1M-L158Y	BT	Module 1: Internal Antenna 1: PIFA Antenna, 1.72dBi(Max.)
	2.4GWIFI	Module 1: Internal Antenna 1: PIFA Antenna, 1.72dBi(Max.) Internal Antenna 2: PIFA Antenna, 1.72dBi(Max.) Module 2: External Antenna 3, 3.9dBi(Max.) External Antenna 4, 3.9dBi(Max.)
	5GWIFI	Module 1: Internal Antenna 1: PIFA Antenna, 2.57dBi(Max.) Internal Antenna 2: PIFA Antenna, 2.57dBi(Max.) Module 2: External Antenna 3: 5.1dBi(Max.) External Antenna 4: 5.1dBi(Max.)
E1M-L159Y	BT	Module 1: External Antenna 1: 3.9dBi(Max.)
	2.4GWIFI	Module 1: External Antenna 1, 3.9dBi(Max.) External Antenna 2, 3.9dBi(Max.) Module 2: External Antenna 3, 3.9dBi(Max.) External Antenna 4, 3.9dBi(Max.)
	5GWIFI	Module 1: External Antenna 1, 5.1dBi(Max.) External Antenna 2, 5.1dBi(Max.) Module 2: External Antenna 3, 5.1dBi(Max.) External Antenna 4, 5.1dBi(Max.)

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.





3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100)*	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Conducted Power

[BT]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-0.92
	39	2441	-0.45
	78	2480	-1.64
$\pi/4$ DQPSK	0	2402	1.1
	39	2441	1.31
	78	2480	0.18
8DPSK	0	2402	1.52
	39	2441	1.78
	78	2480	0.63





[BLE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BLE 1M	0	2402	0.4
	19	2440	1.04
	39	2480	0.07
BLE 2M	0	2402	0.27
	19	2440	0.86
	39	2480	-0.12

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Ant1 Max Conducted Power(dBm)	Ant2 Max Conducted Power(dBm)
11B	1	2412	15.28	15.15
	6	2437	14.55	14.37
	11	2462	14.59	14.43
11G	1	2412	14.21	13.96
	6	2437	14.62	14.28
	11	2462	14.41	14.4
11N20 SISO	1	2412	13.29	13.12
	6	2437	14.03	13.7
	11	2462	13.53	13.42
11N40 SISO	3	2422	13.73	13.65
	6	2437	14.11	13.85
	9	2452	13.52	13.36

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Ant3 Max Conducted Power(dBm)	Ant4 Max Conducted Power(dBm)
11B	1	2412	14.98	14.89
	6	2437	14.16	14.09
	11	2462	14.23	14.18
11G	1	2412	14.88	13.91
	6	2437	14.22	14.24
	11	2462	14.3	14.37
11N20 SISO	1	2412	14.26	13
	6	2437	13.59	13.66
	11	2462	13.4	13.39
11N40 SISO	3	2422	13.5	13.68
	6	2437	13.73	13.84
	9	2452	13.16	13.36
11AX20 SISO	1	2412	13.09	13.48
	6	2437	13.11	13.79
	11	2462	13.37	13.31
11AX40 SISO	3	2422	13.51	13.4
	6	2437	13.29	13.07
	9	2452	13.18	12.97





[5.2G WIFI]

Mode	Channel	Frequency (MHz)	Ant 51 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11A	36	5180	11.98	11.8
	40	5200	11.59	11.78
	48	5240	11.59	12.15
11N20 SISO	36	5180	11.33	11.42
	40	5200	11.49	11.12
	48	5240	11.45	11.37
11N40 SISO	38	5190	11.47	11.23
	46	5230	10.56	10.75
11AC20 SISO	36	5180	11.84	11.49
	40	5200	11.45	11.04
	48	5240	11.47	10.46
11AC40 SISO	38	5190	11.49	11.29
	46	5230	10.92	10.6
11AC80 SISO	42	5210	10.61	10.86

[5.2G WIFI]

Mode	Channel	Frequency (MHz)	Ant 3 Max Conducted Power(dBm)	Ant4 Max Conducted Power(dBm)
11A	36	5180	11.64	11.8
	40	5200	11.67	11.97
	48	5240	11.75	11.3
11N20 SISO	36	5180	11.4	11.53
	40	5200	11.04	11.22
	48	5240	11.12	11.18
11N40 SISO	38	5190	11.14	10.21
	46	5230	10.28	10.35
11AC20 SISO	36	5180	11.36	11.57
	40	5200	11.04	11.28
	48	5240	11.12	11.17
11AC40 SISO	38	5190	10.21	10.28
	46	5230	10.37	10.4
11AC80 SISO	42	5210	10.56	11.02
11AX20 SISO	36	5180	11.85	11.78
	40	5200	11.02	11.61
	48	5240	11.15	10.72
11AX40 SISO	38	5190	11.12	10.63
	46	5230	10.27	10.78
11AX80 SISO	42	5210	10.58	10.95





[5.3G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
IEEE 802.11a	52	5260	12.92	12.7
	60	5280	13.23	12.74
	64	5320	13.06	12.9
11N20 SISO	52	5260	11.25	11.87
	60	5280	11.6	11.1
	64	5320	11.39	11.35
11N40 SISO	54	5270	10.71	10.52
	62	5310	11.37	11.11
11AC20 SISO	52	5260	11.3	11.82
	60	5280	11.63	11.1
	64	5320	11.49	11.43
11AC40 SISO	54	5270	10.66	10.61
	62	5310	11.42	11.12
11AC80 SISO	58	5290	11.37	11.16

[5.3G WIFI]

Mode	Channel	Frequency (MHz)	Ant 3 Max Conducted Power(dBm)	Ant 4 Max Conducted Power(dBm)
IEEE 802.11a	52	5260	12.56	12.48
	60	5280	12.62	12.76
	64	5320	12.67	13.11
11N20 SISO	52	5260	11.89	11.61
	60	5280	11.23	11.11
	64	5320	10.99	11.48
11N40 SISO	54	5270	11.03	10.45
	62	5310	10.57	11.11
11AC20 SISO	52	5260	11.81	11.61
	60	5280	11.26	11.18
	64	5320	11.25	11.56
11AC40 SISO	54	5270	11.09	11.1
	62	5310	10.62	10.61
11AC80 SISO	58	5290	10.72	10.41
11AX20 SISO	52	5260	11.31	11.12
	60	5280	11.17	10.9
	64	5320	11.28	11.3
11AX40 SISO	54	5270	10.98	10.31
	62	5310	10.57	10.9
11AX80 SISO	58	5290	10.72	10.85





[5.5G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11A	100	5500	12.98	12.81
	116	5580	13.13	12.92
	140	5700	12.89	13.08
11N20 SISO	100	5500	11.43	11.25
	116	5580	11.42	11.39
	140	5700	11.41	11.47
11N40 SISO	102	5510	10.95	10.85
	110	5550	10.58	10.62
	134	5670	11.34	11.5
11AC20 SISO	100	5500	11.4	11.3
	116	5580	11.56	11.31
	140	5700	11.31	11.56
11AC40 SISO	102	5510	10.76	10.81
	110	5550	10.52	10.58
	134	5670	11.35	10.45
11AC80 SISO	106	5530	10.63	10.65
	122	5610	11.06	10.92

[5.5G WIFI]

Mode	Channel	Frequency (MHz)	Ant 3 Max Conducted Power(dBm)	Ant 4 Max Conducted Power(dBm)
11A	100	5500	12	12.62
	116	5580	12.15	12.67
	140	5700	12.56	12.77
11N20 SISO	100	5500	11.48	11.21
	116	5580	11.55	11.31
	140	5700	11.88	11.55
11N40 SISO	102	5510	11.15	10.83
	110	5550	10.63	10.53
	134	5670	11.73	11.57
11AC20 SISO	100	5500	11.59	11.15
	116	5580	11.52	11.31
	140	5700	12.03	11.56
11AC40 SISO	102	5510	11.02	10.84
	110	5550	10.67	10.46
	134	5670	11.38	10.43
11AC80 SISO	106	5530	10.66	10.63
	122	5610	11.21	11.02
11AX20 SISO	100	5500	11.67	11.83
	116	5580	11.49	11.99
	140	5700	12.09	11.23
11AX40 SISO	102	5510	11.16	10.59
	110	5550	10.77	10.44
	134	5670	10.47	11.24
11AX80 SISO	106	5530	10.72	10.63
	122	5610	11.14	11.02





[5.8G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11A	149	5745	12.66	12.41
	157	5785	11.99	12.28
	165	5825	12.06	12.17
11N20 SISO	149	5745	11.08	11.32
	157	5785	10.37	11.55
	165	5825	11.39	11.56
11N40 SISO	151	5755	11.71	10.9
	159	5795	10.85	11.14
11AC20 SISO	149	5745	12.1	11.25
	157	5785	11.36	11.52
	165	5825	11.41	11.6
11AC40 SISO	151	5755	10.76	11.94
	159	5795	10.96	11.17
11AC80 SISO	155	5775	10.96	11.15

[5.8G WIFI]

Mode	Channel	Frequency (MHz)	Ant 3 Max Conducted Power(dBm)	Ant 4 Max Conducted Power(dBm)
11A	149	5745	12.46	12.6
	157	5785	11.77	11.81
	165	5825	11.85	11.78
11N20 SISO	149	5745	11.71	11.77
	157	5785	11.14	11.56
	165	5825	11.31	11.61
11N40 SISO	151	5755	10.45	10.9
	159	5795	10.72	11.07
11AC20 SISO	149	5745	11.82	11.34
	157	5785	11.12	11.55
	165	5825	11.23	11.62
11AC40 SISO	151	5755	10.58	10.82
	159	5795	10.81	10.99
11AC80 SISO	155	5775	10.75	11.19
11AX20 SISO	149	5745	11.79	11.87
	157	5785	11.08	11.65
	165	5825	11.18	11.68
11AX40 SISO	151	5755	10.5	10.56
	159	5795	10.77	10.7
11AX80 SISO	155	5775	10.7	10.86

NFC

Test Procedure

TX frequency range: 13.56MHz, Limit: $824/13.56=60.77\text{V/m}$

Device category: Mobile device (Distance: 20cm)

Max. Field Strength: 41.30dBuV/m @3m

@20cm=@3m+40*log(3/0.2)= 88.34dBuV/m

For 13.56MHz: $88.34\text{dBuV/m}=10^{\wedge}(88.34/20)/10^{\wedge}6=0.026\text{V/m}<60.77\text{V/m}$





6. Manufacturing Tolerance

[BT]

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	-1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	1.0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	1.0	1.0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

BLE 1M (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	1.0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

BLE 2M (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI Ant1]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	14.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	14.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0





[2.4G WIFI Ant2]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI Ant3]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0





[2.4G WIFI Ant4]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	13.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[5.2G WIFI Ant1]

11A (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 42		





Target (dBm)	10.0
Tolerance $\pm$ (dB)	1.0

[5.2G WIFI Ant2]

11A (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 42		
Target (dBm)	10.0		
Tolerance $\pm$ (dB)	1.0		

[5.2G WIFI Ant3]

11A (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	10.0	





Tolerance ±(dB)	1.0		1.0	
11AC80 (Average)				
Channel	Channel 42			
Target (dBm)	10.0			
Tolerance ±(dB)	1.0			
11AX20 (Average)				
Channel	Channel 36	Channel 40		Channel 48
Target (dBm)	11.0	11.0		11.0
Tolerance ±(dB)	1.0	1.0		1.0
11AX40 (Average)				
Channel	Channel 38		Channel 46	
Target (dBm)	11.0		10.0	
Tolerance ±(dB)	1.0		1.0	
11AX80 (Average)				
Channel	Channel 42			
Target (dBm)	10.0			
Tolerance ±(dB)	1.0			

[5.2G WIFI Ant4]

11A (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	10.0	
Tolerance ±(dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	10.0	
Tolerance ±(dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 42		
Target (dBm)	11.0		
Tolerance ±(dB)	1.0		
11AX20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	10.0
Tolerance ±(dB)	1.0	1.0	1.0
11AX40 (Average)			





Channel	Channel 38	Channel 46
Target (dBm)	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0
11AX80 (Average)		
Channel	Channel 42	
Target (dBm)	10.0	
Tolerance $\pm$ (dB)	1.0	

[5.3G WIFI Ant1]

11A (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	12.0	13.0	13.0
Tolerance ± (dB)	1.0	1.0	1.0
11N HT20 (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
11N HT40 (Average)			
Channel	Channel 54	Channel 62	
Target (dBm)	10.0	11.0	
Tolerance ± (dB)	1.0	1.0	
11AC VHT20 (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
11AC VHT40 (Average)			
Channel	Channel 54	Channel 62	
Target (dBm)	10.0	11.0	
Tolerance ± (dB)	1.0	1.0	
11AC VHT80 (Average)			
Channel	Channel 58		
Target (dBm)	11.0		
Tolerance ± (dB)	1.0		





[5.3G WIFI Ant2]

11A (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N HT20 (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N HT40 (Average)			
Channel	Channel 54	Channel 62	
Target (dBm)	10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC VHT20 (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC VHT40 (Average)			
Channel	Channel 54	Channel 62	
Target (dBm)	10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC VHT80 (Average)			
Channel	Channel 58		
Target (dBm)	11.0		
Tolerance $\pm$ (dB)	1.0		

[5.3G WIFI Ant3]

11A (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N HT20 (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	11.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N HT40 (Average)			
Channel	Channel 54	Channel 62	
Target (dBm)	11.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC VHT20 (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC VHT40 (Average)			
Channel	Channel 54	Channel 62	
Target (dBm)	11.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	





11AC VHT80 (Average)			
Channel	Channel 58		
Target (dBm)	10.0		
Tolerance ± (dB)	1.0		
11AX VHT20 (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
11AX VHT40 (Average)			
Channel	Channel 54	Channel 62	
Target (dBm)	10.0	10.0	
Tolerance ± (dB)	1.0	1.0	
11AX VHT80 (Average)			
Channel	Channel 58		
Target (dBm)	10.0		
Tolerance ± (dB)	1.0		

[5.3G WIFI Ant4]

11A (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	12.0	12.0	13.0
Tolerance ± (dB)	1.0	1.0	1.0
11N HT20 (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
11N HT40 (Average)			
Channel	Channel 54	Channel 62	
Target (dBm)	10.0	11.0	
Tolerance ± (dB)	1.0	1.0	
11AC VHT20 (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
11AC VHT40 (Average)			
Channel	Channel 54	Channel 62	
Target (dBm)	11.0	10.0	
Tolerance ± (dB)	1.0	1.0	
11AC VHT80 (Average)			
Channel	Channel 58		
Target (dBm)	10.0		
Tolerance ± (dB)	1.0		
11AX VHT20 (Average)			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	10.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0





11AX VHT40 (Average)		
Channel	Channel 54	Channel 62
Target (dBm)	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0
11AX VHT80 (Average)		
Channel	Channel 58	
Target (dBm)	10.0	
Tolerance $\pm$ (dB)	1.0	

[5.5G WIFI Ant1]

11A (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	12.0	13.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N HT20 (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N HT40 (Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	10.0	10.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC VHT20 (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC HT40 (Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	10.0	10.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC VHT80 (Average)			
Channel	Channel 106	Channel 122	
Target (dBm)	10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	

[5.5G WIFI Ant2]

11A (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	12.0	12.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N HT20 (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N HT40 (Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	10.0	10.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC VHT20 (Average)			





Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC HT40 (Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC VHT80 (Average)			
Channel	Channel 106	Channel 122	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	

[5.5G WIFI Ant3]

11A (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N HT20 (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N HT40 (Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	11.0	10.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC VHT20 (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	11.0	11.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC HT40 (Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	11.0	10.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC VHT80 (Average)			
Channel	Channel 106	Channel 122	
Target (dBm)	10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AX VHT20 (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	11.0	11.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX HT40 (Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	11.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX VHT80 (Average)			
Channel	Channel 106	Channel 122	
Target (dBm)	10.0	11.0	





Tolerance $\pm$ (dB)	1.0	1.0
----------------------	-----	-----

[5.5G WIFI Ant4]

11A (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N HT20 (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N HT40 (Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	10.0	10.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC VHT20 (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC HT40 (Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC VHT80 (Average)			
Channel	Channel 106	Channel 122	
Target (dBm)	10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AX VHT20 (Average)			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX HT40 (Average)			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	10.0	10.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX VHT80 (Average)			
Channel	Channel 106	Channel 122	
Target (dBm)	10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	





[5.8G WIFI Ant1]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	11.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	10.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	11.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 155		
Target (dBm)	10.0		
Tolerance $\pm$ (dB)	1.0		

[5.8G WIFI Ant2]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	11.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 155		





Target (dBm)	11.0
Tolerance $\pm$ (dB)	1.0

[5.8G WIFI Ant3]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 155		
Target (dBm)	10.0		
Tolerance $\pm$ (dB)	1.0		
11AX20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AX80 (Average)			
Channel	Channel 155		
Target (dBm)	10.0		
Tolerance $\pm$ (dB)	1.0		





[5.8G WIFI Ant4]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 155		
Target (dBm)	11.0		
Tolerance $\pm$ (dB)	1.0		
11AX20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AX80 (Average)			
Channel	Channel 155		
Target (dBm)	10.0		
Tolerance $\pm$ (dB)	1.0		





7. Measurement Results

7.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK	1.0	1.2589	3.9	2.4547	0.0006	1.0000
$\pi/4$ -DQPSK	2.0	1.5849	3.9	2.4547	0.0008	1.0000
8-DPSK	2.0	1.5849	3.9	2.4547	0.0008	1.0000

[BLE 1M]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK	2.0	1.5849	3.9	2.4547	0.0008	1.0000

[BLE 2M]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK	1.0	1.2589	3.9	2.4547	0.0006	1.0000

[2.4G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	16.0	39.8107	3.9	2.4547	0.0194	1.0000
IEEE 802.11g	15.0	31.6228	3.9	2.4547	0.0155	1.0000
IEEE 802.11n HT20	15.0	31.6228	3.9	2.4547	0.0155	1.0000
IEEE 802.11n HT40	15.0	31.6228	3.9	2.4547	0.0155	1.0000

[2.4G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	16.0	39.8107	3.9	2.4547	0.0194	1.0000
IEEE 802.11g	15.0	31.6228	3.9	2.4547	0.0155	1.0000
IEEE 802.11n HT20	14.0	25.1189	3.9	2.4547	0.0123	1.0000
IEEE 802.11n HT40	14.0	25.1189	3.9	2.4547	0.0123	1.0000

[2.4G WIFI Ant3]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	15.0	31.6228	3.9	2.4547	0.0155	1.0000
IEEE 802.11g	15.0	31.6228	3.9	2.4547	0.0155	1.0000
IEEE 802.11n HT20	15.0	31.6228	3.9	2.4547	0.0155	1.0000
IEEE 802.11n HT40	14.0	25.1189	3.9	2.4547	0.0123	1.0000
IEEE 802.11ax VHT20	14.0	25.1189	3.9	2.4547	0.0123	1.0000
IEEE 802.11ax VHT40	14.0	25.1189	3.9	2.4547	0.0123	1.0000





[2.4G WIFI Ant4]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	15.0	31.6228	3.9	2.4547	0.0155	1.0000
IEEE 802.11g	15.0	31.6228	3.9	2.4547	0.0155	1.0000
IEEE 802.11n HT20	14.0	25.1189	3.9	2.4547	0.0123	1.0000
IEEE 802.11n HT40	14.0	25.1189	3.9	2.4547	0.0123	1.0000
IEEE 802.11ax VHT20	14.0	25.1189	3.9	2.4547	0.0123	1.0000
IEEE 802.11ax VHT40	14.0	25.1189	3.9	2.4547	0.0123	1.0000

[5.2G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000

[5.2G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	5.1	3.2359	0.0129	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000

[5.2G WIFI Ant3]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ac VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ax VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000

[5.2G WIFI Ant4]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ac VHT80	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ax VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000





[5.3G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	14.0	25.1189	5.1	3.2359	0.0162	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT80	12.0	15.8489	5.1	3.2359	0.0102	1.0000

[5.3G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	5.1	3.2359	0.0129	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT80	12.0	15.8489	5.1	3.2359	0.0102	1.0000

[5.3G WIFI Ant3]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	5.1	3.2359	0.0129	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ax VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ax VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000

[5.3G WIFI Ant4]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	14.0	25.1189	5.1	3.2359	0.0162	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ax VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ax VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000

[5.5G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	14.0	25.1189	5.1	3.2359	0.0162	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT80	12.0	15.8489	5.1	3.2359	0.0102	1.0000





[5.5G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	14.0	25.1189	5.1	3.2359	0.0162	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ac VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000

[5.5G WIFI Ant3]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	5.1	3.2359	0.0129	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT80	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT20	13.0	19.9526	5.1	3.2359	0.0129	1.0000
IEEE 802.11ax VHT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT80	12.0	15.8489	5.1	3.2359	0.0102	1.0000

[5.5G WIFI Ant4]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	5.1	3.2359	0.0129	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ac VHT80	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT80	12.0	15.8489	5.1	3.2359	0.0102	1.0000

[5.8G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	5.1	3.2359	0.0129	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0129	1.0000
IEEE 802.11ac VHT20	13.0	19.9526	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ac VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000

[5.8G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	5.1	3.2359	0.0129	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT80	12.0	15.8489	5.1	3.2359	0.0102	1.0000





[5.8G WIFI Ant3]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	5.1	3.2359	0.0129	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ac VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ax VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ax VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000

[5.8G WIFI Ant4]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	5.1	3.2359	0.0129	1.0000
IEEE 802.11n HT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11n HT40	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ac VHT80	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT20	12.0	15.8489	5.1	3.2359	0.0102	1.0000
IEEE 802.11ax VHT40	11.0	12.5893	5.1	3.2359	0.0081	1.0000
IEEE 802.11ax VHT80	11.0	12.5893	5.1	3.2359	0.0081	1.0000

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjusted to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8.2 Simultaneous Transmission MPE Evaluation

The sample support one BT & BLE and two 2.4GWLAN & 5.2G WLAN & 5.3G WLAN & 5.5G WLAN & 5.8G WLAN, another two 2.4GWLAN & 5.2G WLAN & 5.3G WLAN & 5.5G WLAN & 5.8G WLAN, another one NFC, so need consider simultaneous transmission;

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

Σ of MPE ratios ≤ 1.0

<the worst simultaneous transmission operations result-2.4GWIFI+NFC>

2.4GWIFI -Ant 1	2.4GWIFI -Ant 2	2.4GWIFI -Ant 3	2.4GWIFI -Ant 4	NFC Ant	Σ MPE ratios	Limit	Results
0.0155	0.0123	0.0155	0.0123	0.0008	0.0636	1.0	Pass

<the worst simultaneous transmission operations result-BT+5GWIFI+NFC >

BT	5GWIFI -Ant 1	5GWIFI -Ant 2	5GWIFI -Ant 3	5GWIFI -Ant 4	NFC Ant	Σ MPE ratios	Limit	Results
0.0008	0.0129	0.0102	0.0102	0.0102	0.0008	0.0523	1.0	Pass

Remark:

1. Output power including tune-up tolerance;
2. BT/BLE/2.4G WIFI output power is burst peak power;
3. 5G WIFI output power is burst average power;
4. MPE evaluate distance is 20cm from user manual provide by manufacturer;
5. MPE values = $PG/4\pi R^2$
6. Both Bluetooth and WIFI cannot be transmitter simultaneously.





8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

9. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

10. Measurement Uncertainty

BT/BT LE/2.4GWIFI/5.2GWIFI/5.3GWIFI/5.5GWIFI/5.8GWIFI/NFC:

Test Item		Frequency Range	Uncertainty	Note
Output power	:	1GHz-40GHz	$\pm 0.57\text{dB}$	(1)
Radiation Uncertainty	:	9KHz~30MHz	$\pm 3.10\text{dB}$	(1)
		30MHz~200MHz	$\pm 2.96\text{dB}$	(1)
		200MHz~1000MHz	$\pm 3.10\text{dB}$	(1)
		1GHz~26.5GHz	$\pm 3.80\text{dB}$	(1)
		26.5GHz~40GHz	$\pm 3.90\text{dB}$	(1)
Conduction Uncertainty	:	150kHz~30MHz	$\pm 1.63\text{dB}$	(1)
Power disturbance	:	30MHz~300MHz	$\pm 1.60\text{dB}$	(1)
Output power	:	1GHz-40GHz	$\pm 0.57\text{dB}$	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

-----THE END OF REPORT-----

