

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

RF Exposure evaluation**Report Reference No. : GTS20251225009-2-13****FCC ID. : 2BKPG-JNG14**

Compiled by


(position+printed name+signature): File administrators Peter Xiao

Supervised by

(position+printed name+signature): Test Engineer Evan Ouyang

Approved by

(position+printed name+signature) : Manager Jason Hu



Date of issue : Mar.11, 2026

Representative Laboratory Name**..... : Shenzhen Global Test Service Co.,Ltd.**

Address

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name.....**..... : Gogogo technology Co., LIMITED**

Address

FLAT/RM A, 9/F SILVERCORP INTERNATIONAL TOWER,707-713 NATHAN ROAD, MONGKOK, KOWLOON, HONG KONG, China

Test specification

Standard..... : 47CFR §1.1310 Basis and purpose

Standard..... : 47CFR §2.1091 Radiofrequency radiation exposure evaluation: mobile devices

TRF Originator : Shenzhen Global Test Service Co.,Ltd.

Master TRF : Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description**..... : Mini PC**

Trade Mark : QAZIPO

Manufacturer : Gogogo technology Co., LIMITED

Model/Type reference : JNG14

Listed Models : JND13, JNE10, JNE12, JNG10, JNG11, JNG13, JPK09, JPK10, JPK07, MINI PC 3500U, MINI PC N150, NINI PC N150 PRO, MINI PC 6500Y, JNC15, JPK08, JPE12

Hardware Version : N/A

Software Version..... : N/A

Rating : DC 19.0V/3.42A by Adapter

Result : **PASS**

TEST REPORT

Test Report No. : GTS20251225009-2-13	Mar.11, 2026 Date of issue
--	-------------------------------

Equipment under Test : Mini PC

Model /Type : JNG14

Listed model : JND13, JNE10, JNE12, JNG10, JNG11, JNG13, JPK09, JPK10, JPK07, MINI PC 3500U, MINI PC N150, NINI PC N150 PRO, MINI PC 6500Y, JNC15 , JPK08, JPE12

Applicant : **Gogogo technology Co., LIMITED**

Address : FLAT/RM A, 9/F SILVERCORP INTERNATIONAL TOWER,707-713
NATHAN ROAD, MONGKOK, KOWLOON, HONG KONG, China

Manufacturer : **Gogogo technology Co., LIMITED**

Address : FLAT/RM A, 9/F SILVERCORP INTERNATIONAL TOWER,707-713
NATHAN ROAD, MONGKOK, KOWLOON, HONG KONG, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY 4

1.1 EUT CONFIGURATION..... 4

1.2 PRODUCT DESCRIPTION 4

2. TEST ENVIRONMENT 6

2.1 ADDRESS OF THE TEST LABORATORY 6

2.2 TEST FACILITY 6

2.3 ENVIRONMENTAL CONDITIONS 6

2.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY 6

3. METHOD OF MEASUREMENT 7

3.1 APPLICABLE STANDARD..... 7

3.2 REQUIREMENT 7

3.3 LIMIT 7

3.4 MPE CALCULATION METHOD..... 8

3.5 ANTENNA INFORMATION 8

4. CONDUCTED POWER RESULTS..... 9

5. MANUFACTURING TOLERANCE 12

6. MEASUREMENT RESULTS 16

6.1 STANDALONE MPE EVALUATION..... 16

6.2 SIMULTANEOUS TRANSMISSION MPE 18

7. CONCLUSION 19

1. SUMMARY

1.1 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

●	Adapter	M/N:	JHD-AP066U-190342BA-A
		Manufacturer:	Shenzhen Jihongda Power Co.,Ltd.

1.2 Product Description

Product Name:	Mini PC
Trade Mark:	QAZIPO
Model/Type reference:	JNG14
List Model:	JND13, JNE10, JNE12, JNG10, JNG11, JNG13, JPK09, JPK10, JPK07, MINI PC 3500U, MINI PC N150, NINI PC N150 PRO, MINI PC 6500Y, JNC15, JPK08, JPE12
Model Declaration	PCB board, structure and internal of these model(s) are the same, Only the model name different, So no additional models were tested.
Power supply:	DC 19.0V/3.42A by Adapter
Hardware Version	N/A
Software Version	N/A
Sample ID	GTS20251225009-2-S001-1# GTS20251225009-2-S001-2#
Bluetooth	
Frequency Range	2402MHz ~ 2480MHz
Channel Number	79 channels for Bluetooth (DSS) 40 channels for Bluetooth (DTS)
Channel Spacing	1MHz for Bluetooth (DSS) 2MHz for Bluetooth (DTS)
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK for Bluetooth (DSS) GFSK for Bluetooth (DTS)
2.4GWLAN	
WLAN Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz IEEE 802.11n HT40:2422-2462MHz
WLAN Modulation Type	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK, BPSK)
Channel number:	11 Channel for IEEE 802.11b/g/n (HT20) 7 Channel for IEEE 802.11n (HT40)
Channel separation:	5MHz
WIFI(5.2G/5.8G Band)	
WLAN Operation frequency	5180-5240MHz/ 5745MHz to 5825MHz
WLAN Modulation Type	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11acVHT20: OFDM (256QAM,64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11acVHT40: OFDM (256QAM,64QAM, 16QAM, QPSK,BPSK)

	IEEE 802.11acVHT80: OFDM (256QAM,64QAM, 16QAM, QPSK,BPSK)
Channel number:	4 Channels for 20MHz bandwidth(5180-5240MHz) 5 channels for 20MHz bandwidth(5745-5825MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 2 channels for 40MHz bandwidth(5755~5795MHz) 1 channels for 80MHz bandwidth(5210MHz) 1 channels for 80MHz bandwidth(5775MHz)
Antenna Description	Two internal antennas respectively.WLAN not support 2*2MIMO technology. ANT1 used for Bluetooth andWIFI TX/RX, 2.0dBi(Max.) for 2.4G Band and 2.0dBi(Max.) for 5G Band ANT2 used for WIFI TX/RX,2.0dBi(Max.) for 2.4G Band and 2.0dBi (Max.) for 5G Band

2. TEST ENVIRONMENT

2.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1401.

FCC Registered Test Site Number is 684561.

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Global Test Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3. METHOD OF MEASUREMENT

3.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2 Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498 D01 General RF Exposure Guidance v06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3.3 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.4 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT's maximum duty cycle transmission based on the appendix, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is 2.00dBi for BT&WLAN, and the power drift from Turn-up Procedure provide by manufacturer as following states, the RF power density can be obtained.

3.5 Antenna Information

JNG14 can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna1	BT&WLAN ANT1	Internal antenna	2.4 – 2.5 GHz 5.0 – 6.0 GHz	2.00dBi(Max.) for 2.4G band 2.00dBi(Max.) for 5G band
Antenna2	WLAN ANT2	Internal antenna	2.4 – 2.5 GHz 5.0 – 6.0 GHz	2.00dBi(Max.) for 2.4G band 2.00dBi(Max.) for 5G band

4. Conducted Power Results

Antenna 1:

Bluetooth

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	6.72
	39	2441	7.04
	78	2480	6.93
$\pi/4$ DQPSK	0	2402	8.81
	39	2441	8.37
	78	2480	7.96
8DPSK	0	2402	8.36
	39	2440	8.90
	78	2480	8.32
GFSK(BT LE)	0	2402	7.09
	19	2440	8.68
	39	2480	7.35

2.4GWLAN

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	01	2412	15.90
	06	2437	15.24
	11	2462	15.65
802.11g	01	2412	16.91
	06	2437	18.79
	11	2462	17.94
802.11n(HT20)	01	2412	17.26
	06	2437	19.19
	11	2462	17.50
802.11n(HT40)	03	2422	17.01
	06	2437	19.14
	09	2452	17.69

5.2GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	36	5180	9.11
	40	5200	10.31
	48	5240	10.51
802.11n20	36	5180	10.08
	40	5200	10.65
	48	5240	11.20
802.11n40	38	5190	10.25
	46	5230	10.82
802.11ac20	36	5180	8.52
	40	5200	4.82
	48	5240	10.09
802.11ac40	38	5190	7.97
	46	5230	10.47
802.11ac80	42	5210	10.08

5.8GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	149	5745	5.98
	157	5785	9.92
	165	5825	10.10
802.11n20	149	5745	8.18
	157	5785	9.62
	165	5825	10.16
802.11n40	151	5755	8.56
	159	5795	9.61
802.11ac20	149	5745	8.06
	157	5785	9.71
	165	5825	10.04
802.11ac40	151	5755	8.40
	159	5795	10.01
802.11ac80	155	5775	8.67

Antenna 2:**2.4GWLAN**

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	01	2412	15.66
	06	2437	16.57
	11	2462	16.21
802.11g	01	2412	16.30
	06	2437	19.23
	11	2462	18.36
802.11n(HT20)	01	2412	16.78
	06	2437	19.61
	11	2462	18.08
802.11n(HT40)	03	2422	16.89
	06	2437	19.38
	09	2452	18.11

5.2GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	36	5180	8.59
	40	5200	8.90
	48	5240	9.53
802.11n20	36	5180	8.27
	40	5200	8.66
	48	5240	9.35
802.11n40	38	5190	8.48
	46	5230	9.74
802.11ac20	36	5180	8.03
	40	5200	8.49
	48	5240	9.59
802.11ac40	38	5190	8.29
	46	5230	9.45
802.11ac80	42	5210	8.30

5.8GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	149	5745	12.11
	157	5785	12.31
	165	5825	11.97
802.11n20	149	5745	11.90
	157	5785	12.31
	165	5825	11.90
802.11n40	151	5755	11.84
	159	5795	12.35
802.11ac20	149	5745	11.75
	157	5785	12.42
	165	5825	12.01
802.11ac40	151	5755	11.66
	159	5795	11.99
802.11ac80	155	5775	11.28

5. Manufacturing Tolerance

Antenna 1:

Bluetooth			
GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	6.00	7.00	6.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	8.00	8.00	7.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	8.00	8.00	8.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
GFSK BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	7.00	8.00	7.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

2.4GWLAN

IEEE 802.11b (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	15.00	15.00	15.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	16.00	18.00	17.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	17.00	19.00	17.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 03	Channel 06	Channel 09
Target (dBm)	17.00	19.00	17.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.2GWLAN

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	9.00	10.00	10.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	10.00	10.00	11.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n VHT40 (Average)			
Channel	Channel 38	Channel 46	/
Target (dBm)	10.00	10.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	8.00	4.00	10.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 38	Channel 46	/
Target (dBm)	7.00	10.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 42	/	/
Target (dBm)	10.00	/	/
Tolerance $\pm$ (dB)	1.0	/	/

5.8GWLAN

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	5.00	9.00	10.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	8.00	9.00	10.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n VHT40 (Average)			
Channel	Channel 151	Channel 159	/
Target (dBm)	8.00	9.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	8.00	9.00	10.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 151	Channel 159	/
Target (dBm)	8.00	10.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 155	/	/
Target (dBm)	8.00	/	/
Tolerance $\pm$ (dB)	1.0	/	/

Antenna 2:

2.4GWLAN

IEEE 802.11b (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	15.00	16.00	16.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	16.00	19.00	18.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	16.00	19.00	18.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 03	Channel 06	Channel 09
Target (dBm)	16.00	19.00	18.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.2GWLAN

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	8.00	8.00	9.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	8.00	8.00	9.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n VHT40 (Average)			
Channel	Channel 38	Channel 46	/
Target (dBm)	8.00	9.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	8.00	8.00	9.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 38	Channel 46	/
Target (dBm)	8.00	9.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 42	/	/
Target (dBm)	8.00	/	/
Tolerance $\pm$ (dB)	1.0	/	/

5.8GWLAN

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.00	12.00	11.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.00	12.00	11.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n VHT40 (Average)			
Channel	Channel 151	Channel 159	/
Target (dBm)	11.00	12.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.00	12.00	12.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 151	Channel 159	/
Target (dBm)	11.00	11.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ac VHT80 (Average)			
Channel	Channel 155	/	/
Target (dBm)	11.00	/	/
Tolerance $\pm$ (dB)	1.0	/	/

6. Measurement Results

6.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Antenna 1:

BT

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
GFSK	8.00	6.3096	2.00	1.5849	0.0020	1.0000
$\pi/4$ DQPSK	9.00	7.9433	2.00	1.5849	0.0025	1.0000
8DPSK	9.00	7.9433	2.00	1.5849	0.0025	1.0000
GFSK(BT LE)	9.00	7.9433	2.00	1.5849	0.0025	1.0000

2.4GWLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
802.11b	16.00	39.8107	2.00	1.5849	0.0126	1.0000
802.11g	19.00	79.4328	2.00	1.5849	0.0250	1.0000
802.11n(HT20)	20.00	100.0000	2.00	1.5849	0.0315	1.0000
802.11n(HT40)	20.00	100.0000	2.00	1.5849	0.0315	1.0000

5.2GWLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
802.11a	11.00	12.5893	2.00	1.5849	0.0040	1.0000
802.11n20	12.00	15.8489	2.00	1.5849	0.0050	1.0000
802.11n40	11.00	12.5893	2.00	1.5849	0.0040	1.0000
802.11ac20	11.00	12.5893	2.00	1.5849	0.0040	1.0000
802.11ac40	11.00	12.5893	2.00	1.5849	0.0040	1.0000
802.11ac80	11.00	12.5893	2.00	1.5849	0.0040	1.0000

5.8GWLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11a	11.00	12.5893	2.00	1.5849	0.0040	1.0000
802.11n20	11.00	12.5893	2.00	1.5849	0.0040	1.0000
802.11n40	10.00	10.0000	2.00	1.5849	0.0032	1.0000
802.11ac20	11.00	12.5893	2.00	1.5849	0.0040	1.0000
802.11ac40	11.00	12.5893	2.00	1.5849	0.0040	1.0000
802.11ac80	9.00	7.9433	2.00	1.5849	0.0025	1.0000

Antenna 2:**2.4GWLAN**

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11b	17.00	50.1187	2.00	1.5849	0.0158	1.0000
802.11g	20.00	100.0000	2.00	1.5849	0.0315	1.0000
802.11n(HT20)	20.00	100.0000	2.00	1.5849	0.0315	1.0000
802.11n(HT40)	20.00	100.0000	2.00	1.5849	0.0315	1.0000

5.2GWLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11a	10.00	10.0000	2.00	1.5849	0.0032	1.0000
802.11n20	10.00	10.0000	2.00	1.5849	0.0032	1.0000
802.11n40	10.00	10.0000	2.00	1.5849	0.0032	1.0000
802.11ac20	10.00	10.0000	2.00	1.5849	0.0032	1.0000
802.11ac40	10.00	10.0000	2.00	1.5849	0.0032	1.0000
802.11ac80	9.00	7.9433	2.00	1.5849	0.0025	1.0000

5.8GWLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11a	13.00	19.9526	2.00	1.5849	0.0063	1.0000
802.11n20	13.00	19.9526	2.00	1.5849	0.0063	1.0000
802.11n40	13.00	19.9526	2.00	1.5849	0.0063	1.0000
802.11ac20	13.00	19.9526	2.00	1.5849	0.0063	1.0000
802.11ac40	12.00	15.8489	2.00	1.5849	0.0050	1.0000
802.11ac80	12.00	15.8489	2.00	1.5849	0.0050	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

6.2 Simultaneous Transmission MPE

The sample support oneBT&WLAN modular ,one BT&WLAN antenna and one WLAN antenna, Need consider simultaneous transmission ;

According to KDB447498 D01 General RF Exposure Guidance v06 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;
 $\sum$ of MPE ratios ≤ 1.0

6.2.1Summary simultaneous transmission results

Maximum Simultaneous transmission MPE Ratios for**2.4GWLAN(ANT 1)**, **2.4GWLAN(ANT 2)**

Maximum MPE ratio 2.4GWLAN(ANT 1)	Maximum MPE ratio 2.4GWLAN(ANT 2)	$\sum$ MPE ratios	Limit	Results
0.0315	0.0315	0.0630	1.0	PASS

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06, No SAR is required.

.....End of Report.....