

承認書

SPECIFICATION FOR APPROVAL

客戶:	Hong Kong Gleeman Enterprises Company Limited
CUSTOMER:	
客戶料號:	
CUST P/N:	
音澤料號:	G43.5*0.8-20.5-0.08*48P-10TS-6.5UH-L28MM+BJ
FINE P/N:	
產品型號:	Φ43.5MMX0.8MM
DESC:	
日期:	2024/08/22
DATE:	
版本:	A.0
Version:	

擬制 PREPARED BY	審核 CHECKED BY	批准 APPROVED BY	客戶承認 CUSTOMER APPROVE
何立成	马莉	但可清	

Shenzhen Meigehong Technology Co., LTD

版本變更履歷


Version Change History

[illegible]

SPECIFICATION

產品型號: DESC	G43.5*0.8-20.5-0.08*48P-10T S-6.5UH-L28MM+BJ	版本 Rev: A.0	客戶 CUST: 客戶料号 CUST P/N:	
---------------	---	----------------	----------------------------	--

一、尺寸 DIMENSION:(mm)



A	43.5±0.5
B	38.3±0.5
C	20.5±0.5
D	28 ±2
E	3±2
F	5.3±0.2
G	0.8±0.05
H	1.65±0.1
I	
K	

注:
1.Cross outlet;
2.Coil attached double slot disk, disk size 43.5±0.5mm,, the thickness 0.8±0.05mm.
3.Tape the back of the magnetic disc

二、原理图 SCHEMATIC DIAGRAM:

三、绕线参数 Winding Specification:

序号 NO.	端子 TERMINAL	线径 WIRE	圈数 Turns	绕线方向 Winding Direction
1	S F	热风线 0.08*48P	10Ts	CCW

四、电气特性 ELECTRICAL CHARACTERISTICS:

温度 TEMPERATURE:25±10°C, 湿度 RELATIVE HUMIDITY:65±20%

序号 NO.	项目 ITEM	端子 TERMINAL	标准 SPECIFICATION	测试条件 TEST FREQUENCY	测试仪器 TEST EQUIPMENTS
1	IND.	S-F	3.7uH ±10%单独线圈	100KHz/1.0V	LCZ METER 1062B
2	IND.	S-F	6.5uH ±10%加磁片	100KHz/1.0V	LCZ METER 1062B
3	DCR	S-F	≤100m Ω		LCZ METER 502B

擬制/日期 PREPARED BY/DATE	審核/日期 CHECKED BY/DATE
何立成 2024.01.09	

