TEST REPORT

Product Name:	MINI PC
FCC ID:	2BL9P-EXR1
Trademark:	N/A
Model Number:	EXR1, MQi12, MQi13, MQi14, MQi15, MXi12, MXi13, MXi14, MXi15, MQi12PROMAX, MQi13PROMAX, MQi14PROMAX, MQi15PROMAX, MXi12PROMAX, MXi13PROMAX, MXi14PROMAX, MXi15PROMAX, EXR1PROMAX, EXR2, EXR3, EXR4, EXR5, MQR8PROMAX, MQR9PROMAX, MXR8PROMAX, MXR9PROMAX, G1000, G2000, G3000, GTi1 Ultra, GTR1 Ultra, MQR5, MQR6, MQR7, MQR8, MQR9, MXR6, MXR8, MXR9
Prepared For:	Shenzhen Hahappylife Innovations Electronics Technology Co., Ltd
Address:	103, Bldg1, Meicheng Ind Park, No.4, Xinhe St, Ma'antang Community, Bantian St, Longgang Dist, Shenzhen, Guangdong, China
Manufacturer:	Shenzhen Hahappylife Innovations Electronics Technology Co., Ltd
Address:	103, Bldg1, Meicheng Ind Park, No.4, Xinhe St, Ma'antang Community, Bantian St, Longgang Dist, Shenzhen, Guangdong, China
Prepared By:	Shenzhen CTB Testing Technology Co., Ltd.
Address:	1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date:	Aug. 30, 2025
Sample tested Date:	Aug. 30, 2025 to Oct. 31, 2025
Issue Date:	Oct. 31, 2025
Report No.:	CTB25083002708RF04
Test Standards	FCC CFR Title 47 Part 15 Subpart E Section 15.407
Test Results	PASS
Remark:	This is WIFI-5GHz band radio test report.

Compiled by:	Reviewed by:	Approved by:
Zhou Kui	Arron Liu	Bin Mei
Zhou Kui	Arron Liu	Bin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "*" indicates the testing items were fulfilled by subcontracted lab. "#" indicates the items are not in CNAS accreditation scope.

TABLE OF CONTENT

Test Report Declaration Page
1. VERSION 4
2. TEST SUMMARY 5
3. MEASUREMENT UNCERTAINTY 6
4. PRODUCT INFORMATION AND TEST SETUP 7
4.1 Product Information 7
4.2 Test Setup Configuration 8
4.3 Support Equipment 8
4.4 Channel List 9
4.5 Test Mode 9
4.6 Test Environment 10
5. TEST FACILITY AND TEST INSTRUMENT USED 11
5.1 Test Facility 11
5.2 Test Instrument Used 11
6. AC POWER LINE CONDUCTED EMISSION 14
6.1 Block Diagram Of Test Setup 14
6.2 Limit 14
6.3 Test procedure 14
6.4 Test Result 16
7. RADIATED SPURIOUS EMISSIONS 18
7.1 Block Diagram Of Test Setup 18
7.2 Limit 18
7.3 Test procedure 19
7.4 Test Result 20
8. BAND EDGE 25
8.1 Block Diagram Of Test Setup 25
8.2 Limit 25
8.3 Test procedure 25
8.4 Test Result 26
9. CONDUCTED OUTPUT POWER 38
9.1 Block Diagram Of Test Setup 38
9.2 Limit 38
9.3 Test procedure 39
9.4 Test Result 40
10. EMISSION BANDWIDTH& OCCUPIED BANDWIDTH 57
10.1 Block Diagram Of Test Setup 57
10.2 Limits 57
10.3 Test Procedure 57
10.4 Test Results 59
11. POWER SPECTRAL DENSITY 75
11.1 Block Diagram Of Test Setup 75
11.2 Limit 75
11.3 Test procedure 75
11.4 Test Result 77
12. FREQUENCY STABILITY 92
12.1 Block Diagram Of Test Setup 92
12.2 Limit 92
12.3 Test procedure 92
12.4 Test Result 92
13. OPERATION IN THE ABSENCE OF INFORMATION TO THE TRANSMIT 105
13.1 Requirement 105
13.2 Test Results 105
14. ANTENNA REQUIREMENT 106
15. EUT TEST SETUP PHOTOGRAPHS 107

(Note: N/A means not applicable)

1. VERSION

Report No.	Issue Date	Description	Approved
CTB25083002708RF04	Oct. 31, 2025	Original	Valid

2. TEST SUMMARY

The Product has been tested according to the following specifications:

Test Item	Test Requirement	Test method	Result
AC Power Line Conducted Emission	47 CFR Part 15 Subpart E Section 15.407 (b)(6)	ANSI C63.10-2020	PASS
Radiated Spurious emissions	47 CFR Part 15 Subpart E Section 15.205/15.407(b)	KDB789033	PASS
Band edge	47 CFR Part 15 Subpart E Section 15.205/15.407(b)	KDB789033	PASS
Conducted Peak Output Power	47 CFR Part 15 Subpart E Section 15.407 (a)	KDB789033	PASS
Emission Bandwidth & Occupied Bandwidth	47 CFR Part 15 Subpart E Section 15.407 (a)(e)	KDB789033	PASS
Power Spectral Density	47 CFR Part 15 Subpart E Section 15.407 (a)	KDB789033	PASS
Frequency stability	47 CFR Part 15 Subpart E Section 15.407 (g)	KDB789033	PASS
Operation in the absence of information to the transmit	47 CFR Part 15 Subpart E Section 15.407 (b)	47 CFR Part 15 Subpart E	PASS
Antenna Requirement	47 CFR Part 15 Subpart E Section 15.203	/	PASS

Remark:
Test according to ANSI C63.10-2020.

3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Item	Uncertainty
Occupancy bandwidth	U=±54.3Hz
Adjacent channel power	U=±1.3dB
Conducted Adjacent channel power	U=±1.38dB
Conducted output power above 1G	U=±1.0dB
Conducted output power below 1G	U=±0.9dB
Power Spectral Density, Conduction	U=±1.0dB
Conduction spurious emissions	U=±2.8dB
Out of band emission	U=±54Hz
3m camber Radiated spurious emission(9kHz-30MHz)	U=±4.8dB
3m camber Radiated spurious emission(30MHz-1GHz)	U=±4.3dB
3m chamber Radiated spurious emission(1GHz-18GHz)	U=±4.5dB
3m chamber Radiated spurious emission(18GHz-40GHz)	U=±3.4dB
Humidity uncertainty	U=±5.3%
Temperature uncertainty	U=±0.59℃
Supply voltages	U=±3%
Time	U=±5%
Conducted emission(150kHz-30MHz)	3.2dB

4. PRODUCT INFORMATION AND TEST SETUP

4.1 Product Information

Model(s):	EXR1, MQi12, MQi13, MQi14, MQi15, MXi12, MXi13, MXi14, MXi15, MQi12PROMAX, MQi13PROMAX, MQi14PROMAX, MQi15PROMAX, MXi12PROMAX, MXi13PROMAX, MXi14PROMAX, MXi15PROMAX, EXR1PROMAX, EXR2, EXR3, EXR4, EXR5, MQR8PROMAX, MQR9PROMAX, MXR8PROMAX, MXR9PROMAX, G1000, G2000, G3000, GTi1 Ultra, GTR1 Ultra, MQR5, MQR6, MQR7, MQR8, MQR9, MXR6, MXR8, MXR9
Model Description:	All the model are the same circuit and RF module, only the name is different. Test sample model: EXR1
Wi-Fi Specification:	IEEE 802.11a/n/ac/ax
Hardware Version:	HAHAPPYLIFE-EXR1-V10-OK
Software Version:	windows ver: windows11 Pro 24H2
Operation Frequency:	IEEE 802.11a/n/ac/ax(20M): 5150MHz ~5250MHz/ 4 channel IEEE 802.11n/ac/ax(40M): 5150MHz ~5250MHz/ 2 channel IEEE 802.11ac/ax(80M): 5150MHz ~5250MHz/ 1 channel IEEE 802.11a/n/ac/ax(20M): 5725MHz ~5850MHz/ 5 channel IEEE 802.11n/ac/ax(40M): 5725MHz ~5850MHz/ 2 channel IEEE 802.11ac/ax(80M): 5725MHz ~5850MHz/ 1 channel
Max. RF output power:	WiFi (5G): 16.017dBm
Type of Modulation:	WiFi (5G): OFDM, OFDMA
Antenna installation:	WiFi (5G): FPC antenna
Antenna Gain:	WiFi (5.2G): Ant1: 3.03dBi Ant2: 0.69dBi WiFi (5.8G): Ant1: 3.73dBi Ant2: 0.82dBi
Ratings:	For Adapter: Input: AC 100-240V~50/60Hz, 2A Max Output: DC 19V⎓6.32A 120.0W For MINI PC Input: DC 19V⎓6.32A

4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

4.3 Support Equipment

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Switching Power Adapter	Hyleton	Hyleton-120W-1906320	N/A	AE
2	Keyboard	DELL	KB216t	N/A	AE
3	Mouse	DELL	MS116c	N/A	AE
4	Monitor	DELL	SE2218HV	N/A	AE
5	Router	Huawei	AX2 Pro	N/A	AE

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

For 802.11a/n/ac/ax(20M) Operation in the 5180MHz ~5240 MHz band			
Channel	Frequency	Channel	Frequency
36	5180MHz	44	5220MHz
40	5200MHz	48	5240MHz
For 802.11a/n/ac/ax(20M) Operation in the 5745MHz ~5825 MHz band			
Channel	Frequency	Channel	Frequency
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz	NA	NA

For 802.11n/ac/ax(40M) Operation in the 5190MHz ~5230 MHz band			
Channel	Frequency	Channel	Frequency
38	5190MHz	46	5230MHz
For 802.11n/ac/ax(40M) Operation in the 5755MHz ~5795 MHz band			
Channel	Frequency	Channel	Frequency
151	5755MHz	159	5795MHz

For 802.11ac/ax(80M) Operation in the 5210 MHz band			
Channel	Frequency	Channel	Frequency
42	5210MHz	NA	NA
For 802.11ac/ax(80M) Operation in the 5775 MHz band			
Channel	Frequency	NA	NA
155	5775MHz	NA	NA

NOTE: Duty cycle>98%.

Test mode	Rate
802.11a	54M
802.11n	500M
802.11ac/ax	500M

4.5 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test Mode	Tx/Rx	RF Channel		
		Low(L)	Middle(M)	High(H)
802.11a/n/ac/ax(20M)	5180MHz ~5240 MHz	Channel 36	Channel 40	Channel 48
		5180MHz	5200MHz	5240MHz
802.11n/ac/ax(40M)		Channel 38	N/A	Channel 46
		5190MHz	N/A	5230MHz
802.11ac/ax(80M)		N/A	Channel 42	N/A
		N/A	5210MHz	N/A
802.11a/n/ac/ax(20M)	5745MHz ~5825MHz	Channel 149	Channel 157	Channel 165
		5745MHz	5785MHz	5825MHz
802.11n/ac/ax(40M)		Channel 151	N/A	Channel 159
		5755MHz	N/A	5795MHz
802.11ac/ax(80M)		N/A	Channel 155	N/A
		N/A	5775MHz	N/A

4.6 Test Environment

Humidity(%):	54
Atmospheric Pressure(kPa):	101
Normal Voltage(DC):NV	19V
Normal Temperature(℃):NT	23
Low Temperature(℃):LT	0
High Temperature(℃):HT	40

5. TEST FACILITY AND TEST INSTRUMENT USED

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at 1&2F., Building A, No. 26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: CN1276

5.2 Test Instrument Used

No.	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Calibrated Date	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	A.14.16	2025/5/23	2026/5/22
2	Power Sensor	Agilent	U2021XA	MY56120032	/	2025/5/23	2026/5/22
3	Power Sensor	Agilent	U2021XA	MY56120034	/	2025/5/23	2026/5/22
4	Communication test set	R&S	CMW500	108058	V3.5.80	2025/5/23	2026/5/22
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/5/23	2026/5/22
6	Signal Generator	Agilent	N5181A	MY50140365	A.01.60	2025/5/22	2026/5/21
7	Vector signal generator	Agilent	N5182A	MY47420195	A.01.87	2025/5/22	2026/5/21
8	Communication test set	Agilent	E5515C	MY50102567	B.19.07 （E1962B ）	2025/5/22	2026/5/21
9	2.4 GHz Filter	Shenxiang	MSF2400-2483. 5MS-1154	20181015001	/	2025/6/18	2026/6/17
10	5 GHz Filter	Shenxiang	MSF5150-5850 MS-1155	20181015001	/	2025/6/18	2026/6/17
11	Filter	Xingbo	XBLBQ-DZA120	190821-1-1	/	2025/5/24	2026/5/23
12	BT&WI-FI Automatic test software	Micowave	MTS8310	Ver. 2.0.0.0	/	/	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	/	2024/10/31	2025/10/30
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	/	2025/5/22	2026/5/21
15	234G Automatic test software	Micowave	MTS8200	Ver. 2.0.0.0	/	/	/
16	966 chamber	C.R.T.	966	/	/	2024/6/23	2027/6/22
17	Receiver	R&S	ESPI	100362	RF_ATTEN_7 （104489/003）	2025/5/23	2026/5/22

18	Amplifier	HP	8447E	2945A02747	/	2025/5/23	2026/5/22
19	Amplifier	Agilent	8449B	3008A01838	/	2025/6/2	2026/6/1
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2025/6/29	2026/6/28
21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	/	2025/6/1	2026/5/31
22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/	/	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/2	2026/6/1
24	loop antenna	ZHINAN	ZN30900A	GTS534	/	/	/
25	40G Horn antenna	A/H/System	SAS-574	588	/	2025/6/2	2026/6/1
26	Amplifier	AEROFLEX	Aeroflex	097	/	2025/6/2	2026/6/1
27	Power Meter	KEYSIGHT	N1912AP	N/A	A.05.00	2025/6/2	2026/6/1

Continuous disturbance							
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated Date	Calibrated until
1	843 Shield Room	C/ R/ T	843	/	/	2024/6/22	2027/6/21
2	LISN	ROHDE&SCHWARZ	ESH3-Z5	831551852	/	2025/5/22	2026/5/21
3	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428	V4.42.SP3	2025/5/22	2026/5/21
4	Coaxial cable	ZDECL	Z302S	18091904	/	2025/5/22	2026/5/21
5	ISN	Schwarzbeck	NTFM8158	183	/	2025/6/18	2026/6/17
6	Voltage sensor	Schwarzbeck	TK 9420	01189	/	2024/10/26	2025/10/25
7	EZ-EMC	Frad	EMC-con3A1.1	/	/	/	/
8	Current Probe	FCC	F-52B	199453	/	2025/5/24	2026/5/23
9	Communication test set	R&S	CMW500	108058	B.19.07 （E1962B ）	2025/5/23	2026/5/22
10	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/5/23	2026/5/22

Radiated emission(No.1 Chamber)							
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until	Calibrated until
1	966 Chamber	C/ R/ T	966	/	/	2024/6/23	2027/6/22
2	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	/	2025/6/1	2026/5/31
3	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2025/6/29	2026/6/28
4	Amplifier	Agilent	8449B	3008A01838	/	2025/6/3	2026/6/2

5	Amplifier	HP	8447E	2945A02747	/	2025/5/23	2026/5/22
6	loop antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/2	2026/6/1
7	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESPI	100362	RF_ATTEN_7 (104489/003)	2025/5/23	2026/5/22
8	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/5/23	2026/5/22
9	Coaxial cable	ETS	RFC-SNS-100-NMS-80	/	/	2025/5/24	2026/5/23
10	Coaxial cable	ETS	RFC-SN-100-NMS-20	/	/	2025/5/24	2026/5/23
11	Coaxial cable	ETS	RFC-SNS-100-SMS-20	/	/	2025/5/24	2026/5/23
12	Coaxial cable	ETS	RFC-NNS-100-NMS-300	/	/	2025/5/24	2026/5/23
13	EMI test software	Frad	EZ-EMC	Ver/ FA-03A2 RE	/	/	/
14	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/5/23	2026/5/22
15	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/5/23	2026/5/22

6. AC POWER LINE CONDUCTED EMISSION

6.1 Block Diagram Of Test Setup



6.2 Limit

Table 4 – AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56[Note 1]	56 to 46[Note 1]
0.5 – 5	56	46
5 – 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

* Decreasing linearly with the logarithm of the frequency

6.3 Test procedure

1) The mains terminal disturbance voltage test was conducted in a shielded room.

2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,

4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane.

This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.

5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

6.4 Test Result

Modulation: 802.11a (the worst data)

L:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.3149	40.28	10.08	50.36	59.84	-9.48	QP
2		0.3149	30.39	10.08	40.47	49.84	-9.37	AVG
3		0.5260	39.51	10.09	49.60	56.00	-6.40	QP
4		0.5260	28.87	10.09	38.96	46.00	-7.04	AVG
5		0.9377	38.64	10.13	48.77	56.00	-7.23	QP
6	*	0.9377	30.90	10.13	41.03	46.00	-4.97	AVG
7		1.3500	38.56	10.14	48.70	56.00	-7.30	QP
8		1.3500	28.99	10.14	39.13	46.00	-6.87	AVG
9		5.2300	39.58	10.29	49.87	60.00	-10.13	QP
10		5.2300	28.86	10.29	39.15	50.00	-10.85	AVG
11		17.6299	37.86	10.85	48.71	60.00	-11.29	QP
12		17.6299	28.65	10.85	39.50	50.00	-10.50	AVG

Remark:

Factor = Cable loss + LISN factor, Margin = Measurement – Limit

N:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.2162	39.26	10.08	49.34	62.96	-13.62	QP
2		0.2162	27.70	10.08	37.78	52.96	-15.18	AVG
3		0.5340	39.80	10.09	49.89	56.00	-6.11	QP
4	*	0.5340	30.23	10.09	40.32	46.00	-5.68	AVG
5		0.9538	37.83	10.13	47.96	56.00	-8.04	QP
6		0.9538	25.58	10.13	35.71	46.00	-10.29	AVG
7		2.1739	36.72	10.18	46.90	56.00	-9.10	QP
8		2.1739	25.03	10.18	35.21	46.00	-10.79	AVG
9		5.0019	40.56	10.28	50.84	60.00	-9.16	QP
10		5.0019	29.80	10.28	40.08	50.00	-9.92	AVG
11		14.5700	39.57	10.71	50.28	60.00	-9.72	QP
12		14.5700	27.34	10.71	38.05	50.00	-11.95	AVG

Remark:
1. Factor = Cable loss + LISN factor, Margin = Limit – Level
2. All modes were tested at AC 120V and 240V, only the worst result of AC 120V 60Hz was reported.
3. All the test modes completed for test. Only the worst result of was reported.

7. RADIATED SPURIOUS EMISSIONS

7.1 Block Diagram Of Test Setup



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1GHz

7.2 Limit

Spurious Emissions:

Frequency	Field strength (dBμV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	20log 2400/F (kHz) + 80	Quasi-peak	3
0.490MHz-1.705MHz	20log 24000/F (kHz) + 40	Quasi-peak	3
1.705MHz-30MHz	20log 30 + 40	Quasi-peak	3
30MHz-88MHz	40.0	Quasi-peak	3
88MHz-216MHz	43.5	Quasi-peak	3
216MHz-960MHz	46.0	Quasi-peak	3
960MHz-1GHz	54.0	Quasi-peak	3
Above 1GHz	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

If radiated measurements are performed, field strength is then converted to EIRP as follows:
(i) EIRP = ((E*d)^2) / 30
where:
• E is the field strength in V/m;
• d is the measurement distance in meters;
• EIRP is the equivalent isotropically radiated power in watts.
(ii) Working in dB units, the above equation is equivalent to:
EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77
(iii) Or, if d is 3 meters:
EIRP[dBm] = E[dBμV/m] - 95.2

7.3 Test procedure

Below 1GHz test procedure as below:
a.The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
b.The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c.The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d.For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
e.The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f.If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Above 1GHz test procedure as below:
g.Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).
h.Test the EUT in the lowest channel ,the middle channel ,the Highest channel
j.Repeat above procedures until all frequencies measured was complete.

Receiver set:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120 kHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

7.4 Test Result

30MHz-1GHzTest Results:
Modulation: 802.11a (the worst data)
Test Channel: 5780MHz
Antenna polarity: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		45.2959	33.88	-6.17	27.71	40.00	-12.29	QP
2	!	151.8632	41.94	-4.22	37.72	43.50	-5.78	QP
3	!	208.2143	44.81	-6.18	38.63	43.50	-4.87	QP
4	*	311.6324	45.03	-2.33	42.70	46.00	-3.30	QP
5	!	500.3009	39.07	0.95	40.02	46.00	-5.98	QP
6		768.7481	30.06	7.88	37.94	46.00	-8.06	QP

Antenna polarity: V

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	!	31.3442	40.63	-6.35	34.28	40.00	-5.72	QP
2		85.1486	42.28	-8.41	33.87	40.00	-6.13	QP
3		131.9889	40.91	-5.92	34.99	43.50	-8.51	QP
4	*	158.6673	41.62	-3.56	38.06	43.50	-5.44	QP
5		314.3763	40.27	-2.29	37.98	46.00	-8.02	QP
6		500.3009	37.46	0.95	38.41	46.00	-7.59	QP

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

Radiated Spurious Emission (Above 1GHz):

Modulation: 802.11(a) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5180MHz									
10360	41.67	16.39	58.06	74	-15.94	PK	1.20	90	H
10360	27.90	16.39	44.29	54	-9.71	AV	1.31	285	H
10360	40.11	16.39	56.50	74	-17.50	PK	1.59	297	V
10360	26.00	16.39	42.39	54	-11.61	AV	1.54	30	V
Channel:5240MHz									
10480	41.67	16.11	57.78	74	-16.22	PK	1.61	136	H
10480	25.31	16.11	41.42	54	-12.58	AV	1.17	125	H
10480	41.71	16.11	57.82	74	-16.18	PK	1.42	323	V
10480	25.14	16.11	41.25	54	-12.75	AV	1.85	82	V
Channel:5745MHz									
11490	40.01	17.46	57.47	74	-16.53	PK	1.12	210	H
11490	27.78	17.46	45.24	54	-8.76	AV	1.05	3	H
11490	41.25	17.46	58.71	74	-15.29	PK	1.67	87	V
11490	26.34	17.46	43.80	54	-10.20	AV	1.03	295	V
Channel:5825MHz									
11650	41.21	17.57	58.78	74	-15.22	PK	1.28	345	H
11650	26.45	17.57	44.02	54	-9.98	AV	1.54	292	H
11650	40.90	17.57	58.47	74	-15.53	PK	1.67	99	V
11650	26.34	17.57	43.91	54	-10.09	AV	1.27	79	V

Modulation: 802.11(n40) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5190MHz									
10380	41.26	16.34	57.60	74	-16.40	PK	1.84	204	H
10380	25.48	16.34	41.82	54	-12.18	AV	1.51	65	H
10380	41.39	16.34	57.73	74	-16.27	PK	1.78	198	V
10380	25.07	16.34	41.41	54	-12.59	AV	1.81	241	V
Channel:5230MHz									
10460	40.18	16.15	56.33	74	-17.67	PK	1.14	208	H
10460	27.98	16.15	44.13	54	-9.87	AV	1.84	190	H
10460	40.64	16.15	56.79	74	-17.21	PK	1.30	169	V
10460	26.38	16.15	42.53	54	-11.47	AV	1.44	17	V
Channel:5755MHz									
11510	40.11	17.49	57.60	74	-16.40	PK	1.20	184	H
11510	26.16	17.49	43.65	54	-10.35	AV	1.28	109	H
11510	40.45	17.49	57.94	74	-16.06	PK	1.54	135	V
11510	26.86	17.49	44.35	54	-9.65	AV	1.31	263	V
Channel:5795MHz									
11590	41.43	17.52	58.95	74	-17.23	PK	1.86	160	H
11590	26.10	17.52	43.62	54	-15.05	AV	1.79	265	H
11590	39.10	17.52	56.62	74	-17.38	PK	1.34	112	V
11590	25.27	17.52	42.79	54	-11.21	AV	1.38	335	V

Modulation: 802.11(VHT80) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5210MHz									
10420	40.52	16.25	56.77	74	-17.23	PK	1.14	167	H
10420	26.29	16.25	42.54	54	-11.46	AV	1.39	169	H
10420	41.57	16.25	57.82	74	-16.18	PK	1.17	278	V
10420	26.52	16.25	42.77	54	-11.23	AV	1.20	224	V
Channel:5775MHz									
11550	39.67	17.50	57.17	74	-16.83	PK	1.23	263	H
11550	25.66	17.50	43.16	54	-10.84	AV	1.59	48	H
11550	40.01	17.50	57.51	74	-16.49	PK	1.15	264	V
11550	26.26	17.50	43.76	54	-10.24	AV	1.44	44	V

Remark:
1.Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits
2.The EUT was tested in the low, high channel and the worst case position data was reported.
3.Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. BAND EDGE

8.1 Block Diagram Of Test Setup



8.2 Limit

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(4) For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of −17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of −27 dBm/MHz.
(5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
(6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

8.3 Test procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

8.4 Test Result

Test Graph

ANT 1

802.11a-5180



802.11a-5240



802.11ac(VHT20)-5180



802.11ac(VHT20)-5240



802.11ac(VHT40)-5190



802.11ac(VHT40)-5230



802.11ac(VH80)-5210

802.11n(HT20)-5180



802.11n(HT20)-5240



802.11n(HT40)-5190



802.11n(HT40)-5230



802.11ax(HE20)-5180

802.11ax(HE20)-5240



802.11ax(HE40)-5190



802.11ax(HE40)-5230



802.11ax(HE80)-5210





ANT1:

802.11a-5745



802.11a-5825

802.11ac(VHT20)-5745



802.11ac(VHT20)-5825

802.11ac(VHT40)-5755

802.11ac(VHT40)-5795



802.11ac(VHT80)-5775

802.11(n20)-5745



802.11(n20)-5825



802.11(n40)-5755



802.11(n40)-5795

802.11ax(HE20)-5745

802.11ax(HE20)-5825



802.11ax(HE40)-5755

802.11ax(HE40)-5795

802.11ax(HE80)-5775

ANT 2

802.11a-5180



802.11a-5240



802.11ac(VHT20)-5180



802.11ac(VHT20)-5240



802.11ac(VHT40)-5190

802.11ac(VHT40)-5230



802.11ac(VHT80)-5210

802.11n(HT20)-5180



802.11n(HT20)-5240



802.11n(HT40)-5190



802.11n(HT40)-5230



802.11ax(HE20)-5180

802.11ax(HE20)-5240



802.11ax(HE40)-5190



802.11ax(HE40)-5230



802.11ax(HE80)-5210





ANT2:

802.11a-5745

802.11a-5825

802.11ac(VHT20)-5745

802.11ac(VHT20)-5825

802.11ac(VHT40)-5755

802.11ac(VHT40)-5795

802.11ac(VHT80)-5775

802.11(n20)-5745



802.11(n20)-5825

802.11(n40)-5755

802.11(n40)-5795

802.11ax(HE20)-5745

802.11ax(HE20)-5825

802.11ax(HE40)-5755

802.11ax(HE40)-5795

802.11ax(HE80)-5775

9. CONDUCTED OUTPUT POWER

9.1 Block Diagram Of Test Setup



9.2 Limit

(1) For the band 5.15-5.25 GHz.
(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p.
at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition,the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.
(5) The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution

bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

(h) Transmit Power Control (TPC) and Dynamic Frequency Selection (DFS).
(1) Transmit power control (TPC). U-NII devices operating in the 5.25-5.35 GHz band and the 5.47-5.725 GHz band shall employ a TPC mechanism. The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30 dBm. A TPC mechanism is not required for systems with an e.i.r.p. of less than 500 mW.

9.3 Test procedure

According to KDB789033 D02v02r01 sectionE, the following is the measurement procedure.

(i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW ≥ 3 MHz.

(iv) Number of points in sweep ≥ 2 × span / RBW. (This ensures that bin-to-bin spacing is ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98%, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98%, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.”

(viii) Trace average at least 100 traces in power averaging (rms) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

9.4 Test Result

ANT 1+ANT 2

Test mode1	Test Channel (MHz)	Output Power dBm ANT1	Output Power dBm ANT2	Output Power dBm Total	Limit dBm
802.11a	5180	11.911	12.668	/	23.98
	5200	10.592	13.298	/	23.98
	5240	11.895	14.382	/	23.98
802.11ac(VHT20)	5180	11.579	12.498	15.073	23.98
	5200	11.211	12.777	15.075	23.98
	5240	11.234	13.151	15.308	23.98
802.11ac(VHT40)	5190	11.339	12.743	15.108	23.98
	5230	11.442	13.642	15.690	23.98
802.11ac(VHT80)	5210	11.238	13.246	15.367	23.98
802.11n(HT20)	5180	11.972	12.357	15.179	23.98
	5200	11.862	12.826	15.381	23.98
	5240	11.491	14.128	16.017	23.98
802.11n(HT40)	5190	11.753	12.745	15.288	23.98
	5230	11.522	12.625	15.119	23.98
802.11ax(HE20)	5180	11.485	12.108	14.818	23.98
	5200	11.376	12.732	15.117	23.98
	5240	11.340	14.111	15.953	23.98
802.11ax(HE40)	5190	11.688	13.184	15.510	23.98
	5230	10.641	14.033	15.670	23.98
802.11ax(HE80)	5210	11.119	13.231	15.312	23.98

ANT 1+ANT 2

Test mode1	Test Channel (MHz)	Output Power dBm ANT1	Output Power dBm ANT2	Output Power dBm Total	Limit dBm
802.11a	5745	13.328	11.313	/	30
	5785	12.342	12.262	/	30
	5825	12.678	12.608	/	30
802.11ac(VHT20)	5745	11.867	11.026	15.447	30
	5785	12.689	12.232	15.312	30
	5825	13.009	12.603	15.653	30
802.11ac(VHT40)	5755	11.758	11.168	14.477	30
	5795	11.560	11.700	15.477	30
802.11ac(VHT80)	5775	11.776	11.075	15.821	30
802.11n(HT20)	5745	11.018	11.025	14.483	30
	5785	12.365	11.982	14.641	30
	5825	12.542	12.402	14.450	30
802.11n(HT40)	5755	12.153	11.055	14.649	30
	5795	11.860	11.502	14.695	30
802.11ax(HE20)	5745	11.507	11.023	14.282	30
	5785	12.451	12.223	15.349	30
	5825	12.785	12.552	15.680	30
802.11ax(HE40)	5755	12.214	11.091	14.699	30
	5795	12.139	11.640	14.907	30
802.11ax(HE80)	5775	11.791	11.031	14.438	30

ANT 1

802.11a-5180

802.11a-5200

802.11a-5240

802.11ac(VHT20)-5180

802.11ac(VHT20)-5200

802.11ac(VHT20)-5240



802.11ac(VHT40)-5190

802.11ac(VHT40)-5230



802.11ac(VHT80)-5210



802.11n(HT20)-5180



802.11n(HT20)-5200



802.11n(HT20)-5240

802.11n(HT40)-5190



802.11n(HT40)-5230

802.11ax(HE20)-5180



802.11ax(HE20)-5200

802.11ax(HE20)-5240



802.11ax(HE40)-5190

802.11ax(HE40)-5230

802.11ax(HE80)-5210

Agilent Spectrum Analyzer - Channel Power
Center Freq 5.230000000 GHz
Center Freq: 5.230000000 GHz
Trig: Free Run
#Atten: 30 dB
Avg|Hold: 100/100
Radio Std: None
Radio Device: BTS
Ref Offset 8.96 dB
10 dB/div
Ref 28.96 dBm
Center 5.23 GHz
#Res BW 1 MHz
#VBW 3 MHz
Span 60 MHz
Sweep 1 ms
Channel Power
10.64 dBm / 40 MHz
Power Spectral Density
-65.38 dBm /Hz


Agilent Spectrum Analyzer - Channel Power
Center Freq 5.210000000 GHz
Center Freq: 5.210000000 GHz
Trig: Free Run
#Atten: 30 dB
Avg|Hold: 100/100
Radio Std: None
Radio Device: BTS
Ref Offset 9.03 dB
10 dB/div
Ref 29.03 dBm
Center 5.21 GHz
#Res BW 1 MHz
#VBW 3 MHz
Span 120 MHz
Sweep 1 ms
Channel Power
11.12 dBm / 80 MHz
Power Spectral Density
-67.91 dBm /Hz

ANT1:

802.11a-5745



802.11a-5785



802.11a-5825

802.11ac(VHT20)-5745



802.11ac(VHT20)-5785



802.11ac(VHT20)-5825



802.11ac(VHT40)-5755

802.11ac(VHT40)-5795

802.11ac(VHT80)-5775



802.11n(HT20)-5745



802.11n(HT20)-5785



802.11n(HT20)-5825

5802.11n(HT40)-5755



802.11n(HT40)-5795

802.11ax(HE20)-5745



802.11ax(HE20)-5785



802.11ax(HE20)-5825



802.11ax(HE40)-5755

802.11ax(HE40)-5795

802.11ax(HE80)-5775


Agilent Spectrum Analyzer - Channel Power
Center Freq 5.230000000 GHz
Center Freq: 5.230000000 GHz
Trig: Free Run
Avg|Hold: 100/100
#Atten: 30 dB
Radio Std: None
Radio Device: BTS
Ref Offset 8.96 dB
10 dB/div
Ref 28.96 dBm
Log
Center 5.23 GHz
#Res BW 1 MHz
#VBW 3 MHz
Span 60 MHz
Sweep 1 ms
Channel Power
14.03 dBm / 40 MHz
Power Spectral Density
-61.99 dBm /Hz


Agilent Spectrum Analyzer - Channel Power
Center Freq 5.210000000 GHz
Center Freq: 5.210000000 GHz
Trig: Free Run
Avg|Hold: 100/100
#Atten: 30 dB
Radio Std: None
Radio Device: BTS
Ref Offset 9.03 dB
10 dB/div
Ref 29.03 dBm
Log
Center 5.21 GHz
#Res BW 1 MHz
#VBW 3 MHz
Span 120 MHz
Sweep 1 ms
Channel Power
13.23 dBm / 80 MHz
Power Spectral Density
-65.80 dBm /Hz

ANT 2

802.11a-5180

802.11a-5200



802.11a-5240



802.11ac(VHT20)-5180



802.11ac(VHT20)-5200

802.11ac(VH20)-5240

802.11ac(VHT40)-5190

802.11ac(VH40)-5230



802.11ac(VHT80)-5210



802.11n(HT20)-5180



802.11n(HT20)-5200



802.11n(HT20)-5240

802.11n(HT40)-5190



802.11n(HT40)-5230

802.11ax(HE20)-5180



802.11ax(HE20)-5200



802.11ax(HE20)-5240



802.11ax(HE40)-5190

802.11ax(HE40)-5230



802.11ax(HE80)-5210


Agilent Spectrum Analyzer - Channel Power
Center Freq 5.795000000 GHz
Center Freq: 5.795000000 GHz
Trig: Free Run
Avg|Hold: 100/100
#Atten: 30 dB
Radio Std: None
Radio Device: BTS
Ref Offset 9.52 dB
10 dB/div
Ref 29.52 dBm
Center 5.795 GHz
#Res BW 1 MHz
#VBW 3 MHz
Span 60 MHz
Sweep 1 ms
Channel Power
12.14 dBm / 40 MHz
Power Spectral Density
-63.88 dBm /Hz


Agilent Spectrum Analyzer - Channel Power
Center Freq 5.775000000 GHz
Center Freq: 5.775000000 GHz
Trig: Free Run
Avg|Hold: 100/100
#Atten: 30 dB
Radio Std: None
Radio Device: BTS
Ref Offset 9.79 dB
10 dB/div
Ref 29.79 dBm
Center 5.775 GHz
#Res BW 1 MHz
#VBW 3 MHz
Span 120 MHz
Sweep 1 ms
Channel Power
11.79 dBm / 80 MHz
Power Spectral Density
-67.24 dBm /Hz

ANT2:

802.11a-5745

802.11a-5785



802.11a-5825

802.11ac(VHT20)-5745



802.11ac(VHT20)-5785

802.11ac(VHT20)-5825

802.11ac(VHT40)-5755

802.11ac(VHT40)-5795



802.11ac(VHT80)-5775



802.11n(HT20)-5745



802.11n(HT20)-5785

802.11n(HT20)-5825

5802.11n(HT40)-5755



802.11n(HT40)-5795