Appendix B

RF Test Data for BT LE(Conducted Measurement)

Product Name: Mini PC

Test Model: MN-N1

Environmental Conditions

Temperature:	24.8° C
Relative Humidity:	53.4%
ATM Pressure:	100.0 kPa
Test Engineer:	Jose Zhu
Supervised by:	Nick Peng

B.1 -6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant0	0.651	>=0.5	Pass
NVNT	BLE 1M	2440	Ant0	0.65	>=0.5	Pass
NVNT	BLE 1M	2480	Ant0	0.656	>=0.5	Pass
NVNT	BLE 2M	2402	Ant0	1.147	>=0.5	Pass
NVNT	BLE 2M	2440	Ant0	1.161	>=0.5	Pass
NVNT	BLE 2M	2480	Ant0	1.17	>=0.5	Pass

Test Graphs

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant0



-6dB Bandwidth NVNT BLE 1M 2440MHz Ant0



-6dB Bandwidth NVNT BLE 1M 2480MHz Ant0



-6dB Bandwidth NVNT BLE 2M 2402MHz Ant0



-6dB Bandwidth NVNT BLE 2M 2440MHz Ant0



-6dB Bandwidth NVNT BLE 2M 2480MHz Ant0



B.2 Maximum Peak Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant0	0.19	30	Pass
NVNT	BLE 1M	2440	Ant0	0.11	30	Pass
NVNT	BLE 1M	2480	Ant0	-0.99	30	Pass
NVNT	BLE 2M	2402	Ant0	0.1	30	Pass
NVNT	BLE 2M	2440	Ant0	-0.08	30	Pass
NVNT	BLE 2M	2480	Ant0	-1.14	30	Pass

Test Graphs

Power NVNT BLE 1M 2402MHz Ant0



Power NVNT BLE 1M 2440MHz Ant0



Power NVNT BLE 1M 2480MHz Ant0



Power NVNT BLE 2M 2402MHz Ant0



Power NVNT BLE 2M 2440MHz Ant0



Power NVNT BLE 2M 2480MHz Ant0



B.3 Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant0	-16.23	8	Pass
NVNT	BLE 1M	2440	Ant0	-16.76	8	Pass
NVNT	BLE 1M	2480	Ant0	-17.51	8	Pass
NVNT	BLE 2M	2402	Ant0	-19.79	8	Pass
NVNT	BLE 2M	2440	Ant0	-19.97	8	Pass
NVNT	BLE 2M	2480	Ant0	-21.02	8	Pass

Test Graphs

PSD NVNT BLE 1M 2402MHz Ant0



PSD NVNT BLE 1M 2440MHz Ant0



PSD NVNT BLE 1M 2480MHz Ant0



PSD NVNT BLE 2M 2402MHz Ant0



PSD NVNT BLE 2M 2440MHz Ant0



PSD NVNT BLE 2M 2480MHz Ant0



B.4 Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant0	-55.91	-20	Pass
NVNT	BLE 1M	2480	Ant0	-54.77	-20	Pass
NVNT	BLE 2M	2402	Ant0	-44.23	-20	Pass
NVNT	BLE 2M	2480	Ant0	-55.57	-20	Pass

Test Graphs

Band Edge NVNT BLE 1M 2402MHz Ant0 Ref



Band Edge NVNT BLE 1M 2402MHz Ant0 Emission



Band Edge NVNT BLE 1M 2480MHz Ant0 Ref



Band Edge NVNT BLE 1M 2480MHz Ant0 Emission



Band Edge NVNT BLE 2M 2402MHz Ant0 Ref



Band Edge NVNT BLE 2M 2402MHz Ant0 Emission



Band Edge NVNT BLE 2M 2480MHz Ant0 Ref



Band Edge NVNT BLE 2M 2480MHz Ant0 Emission



B.5 Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant0	-54.85	-20	Pass
NVNT	BLE 1M	2440	Ant0	-55.13	-20	Pass
NVNT	BLE 1M	2480	Ant0	-54.02	-20	Pass
NVNT	BLE 2M	2402	Ant0	-54.99	-20	Pass
NVNT	BLE 2M	2440	Ant0	-53.23	-20	Pass
NVNT	BLE 2M	2480	Ant0	-53.29	-20	Pass

Test Graphs

Tx. Spurious NVNT BLE 1M 2402MHz Ant0 Ref



Tx. Spurious NVNT BLE 1M 2402MHz Ant0 Emission



Tx. Spurious NVNT BLE 1M 2440MHz Ant0 Ref



Tx. Spurious NVNT BLE 1M 2440MHz Ant0 Emission



Tx. Spurious NVNT BLE 1M 2480MHz Ant0 Ref



Tx. Spurious NVNT BLE 1M 2480MHz Ant0 Emission



Tx. Spurious NVNT BLE 2M 2402MHz Ant0 Ref



Tx. Spurious NVNT BLE 2M 2402MHz Ant0 Emission



Tx. Spurious NVNT BLE 2M 2440MHz Ant0 Ref



Tx. Spurious NVNT BLE 2M 2440MHz Ant0 Emission



Tx. Spurious NVNT BLE 2M 2480MHz Ant0 Ref



Tx. Spurious NVNT BLE 2M 2480MHz Ant0 Emission



B.6 Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant0	87.39	0.59	0.61
NVNT	BLE 1M	2440	Ant0	87.39	0.59	0.61
NVNT	BLE 1M	2480	Ant0	87.39	0.59	0.61
NVNT	BLE 2M	2402	Ant0	65.93	1.81	1.21
NVNT	BLE 2M	2440	Ant0	65.96	1.81	1.21
NVNT	BLE 2M	2480	Ant0	65.96	1.81	1.21

Test Graphs

Duty Cycle NVNT BLE 1M 2402MHz Ant0



Duty Cycle NVNT BLE 1M 2440MHz Ant0



Duty Cycle NVNT BLE 1M 2480MHz Ant0



Duty Cycle NVNT BLE 2M 2402MHz Ant0



Duty Cycle NVNT BLE 2M 2440MHz Ant0



Duty Cycle NVNT BLE 2M 2480MHz Ant0



B.7 Restrict Band

Condition	Mode	Frequency (MHz)	Antenna	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	Duty Factor (dB)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
NVNT	BLE 1M	2402	Ant0	2310	-51.22	2.74	-	46.78	Peak	74	Pass
NVNT	BLE 1M	2402	Ant0	2310	-59.16	2.74	0.59	38.84	Average	54	Pass
NVNT	BLE 1M	2402	Ant0	2349.648	-46.93	2.74	-	51.07	Peak	74	Pass
NVNT	BLE 1M	2402	Ant0	2387.856	-57.49	2.74	0.59	40.51	Average	54	Pass
NVNT	BLE 1M	2402	Ant0	2390	-49.92	2.74	-	48.08	Peak	74	Pass
NVNT	BLE 1M	2402	Ant0	2390	-58.56	2.74	0.59	39.44	Average	54	Pass
NVNT	BLE 1M	2480	Ant0	2483.5	-48.93	2.74	-	49.07	Peak	74	Pass
NVNT	BLE 1M	2480	Ant0	2483.5	-57.12	2.74	0.59	40.88	Average	54	Pass
NVNT	BLE 1M	2480	Ant0	2496.976	-46.28	2.74	-	51.72	Peak	74	Pass
NVNT	BLE 1M	2480	Ant0	2486.368	-57.03	2.74	0.59	40.97	Average	54	Pass
NVNT	BLE 1M	2480	Ant0	2500	-50.8	2.74	-	47.20	Peak	74	Pass
NVNT	BLE 1M	2480	Ant0	2500	-57.63	2.74	0.59	40.37	Average	54	Pass
NVNT	BLE 2M	2402	Ant0	2310	-49.85	2.74	-	48.15	Peak	74	Pass
NVNT	BLE 2M	2402	Ant0	2310	-58.76	2.74	1.81	39.24	Average	54	Pass
NVNT	BLE 2M	2402	Ant0	2358	-47.87	2.74	-	50.13	Peak	74	Pass
NVNT	BLE 2M	2402	Ant0	2365.2	-57.5	2.74	1.81	40.50	Average	54	Pass
NVNT	BLE 2M	2402	Ant0	2390	-48.64	2.74	-	49.36	Peak	74	Pass
NVNT	BLE 2M	2402	Ant0	2390	-58.42	2.74	1.81	39.58	Average	54	Pass
NVNT	BLE 2M	2480	Ant0	2483.5	-48.75	2.74	-	49.25	Peak	74	Pass
NVNT	BLE 2M	2480	Ant0	2483.5	-57.45	2.74	1.81	40.55	Average	54	Pass
NVNT	BLE 2M	2480	Ant0	2491.12	-46.58	2.74	-	51.42	Peak	74	Pass
NVNT	BLE 2M	2480	Ant0	2486.296	-57.05	2.74	1.81	40.95	Average	54	Pass
NVNT	BLE 2M	2480	Ant0	2500	-49.21	2.74	-	48.79	Peak	74	Pass
NVNT	BLE 2M	2480	Ant0	2500	-57.97	2.74	1.81	40.03	Average	54	Pass

Test Graphs

Restrict Band NVNT BLE 1M 2402MHz Ant0 Peak



Restrict Band NVNT BLE 1M 2402MHz Ant0 Average



Restrict Band NVNT BLE 1M 2480MHz Ant0 Peak



Restrict Band NVNT BLE 1M 2480MHz Ant0 Average



Restrict Band NVNT BLE 2M 2402MHz Ant0 Peak



Restrict Band NVNT BLE 2M 2402MHz Ant0 Average



Restrict Band NVNT BLE 2M 2480MHz Ant0 Peak



Restrict Band NVNT BLE 2M 2480MHz Ant0 Average