



# RF TEST REPORT

Product Name: Control Box

Model Number: GC3001

FCC ID: 2BLA7-GC3001

Issued For : NINGBO GERWIN MECHANIC&ELECTRONICS  
TECHNOLOGY CO.,LTD

Tianhu Road, Luotuo Street, Ningbo, Zhejiang, China

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,  
No.177, Renmin West Road, Jinsha, Kengzi Street,  
Pingshan District, Shenzhen, Guangdong, China

Report Number: LGT26C154HA01

Received Date: Mar. 18, 2026

Date of Test: Mar. 18, 2026 ~ Apr. 02, 2026

Date of Issue: Apr. 02, 2026

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



## TEST REPORT CERTIFICATION

**Applicant:** NINGBO GERWIN MECHANIC&ELECTRONICS TECHNOLOGY CO.,LTD  
**Address:** Tianhu Road, Luotuo Street, Ningbo, Zhejiang, China

**Manufacturer:** NINGBO GERWIN MECHANIC&ELECTRONICS TECHNOLOGY CO.,LTD  
**Address:** Tianhu Road, Luotuo Street, Ningbo, Zhejiang, China

**Product Name:** Control Box

**Trademark:** 

**Model Number:** GC3001

**Sample Status:** Normal

| APPLICABLE STANDARDS                                                     |              |
|--------------------------------------------------------------------------|--------------|
| STANDARD                                                                 | TEST RESULTS |
| FCC 47 CFR §2.1091<br>KDB 447498 D01 General RF Exposure<br>Guidance v06 | PASS         |

Prepared by:

Zane Shan

Zane Shan  
Engineer

Approved by:

Vita Li

Vita Li  
Technical Director





## TABLE OF CONTENTS

|                                           |          |
|-------------------------------------------|----------|
| <b>1 . GENERAL INFORMATION</b>            | <b>5</b> |
| 1.1 GENERAL DESCRIPTION OF THE EUT        | 5        |
| 1.2 TEST LABORATORY                       | 5        |
| <b>2 . FCC 47CFR § 2.1091 REQUIREMENT</b> | <b>6</b> |
| 2.1 TEST STANDARDS                        | 6        |
| 2.2 LIMIT                                 | 6        |
| 2.3 EUT OPERATION CONDITION               | 7        |
| 2.4 CLASSIFICATION                        | 7        |
| 2.5 TEST RESULT                           | 8        |



### **Revision History**

| Rev. | Issue Date    | Revisions     |
|------|---------------|---------------|
| 00   | Apr. 02, 2026 | Initial Issue |
|      |               |               |



## 1. GENERAL INFORMATION

### 1.1 GENERAL DESCRIPTION OF THE EUT

|                    |             |
|--------------------|-------------|
| Product Name:      | Control Box |
| Test Model Number: | GC3001      |
| Series Number:     | N/A         |
| Model Difference:  | N/A         |
| Hardware version:  | V1.2        |
| Software version:  | V1.0.2      |

### 1.2 TEST LABORATORY

|                            |                                                                                                                                                          |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Company Name:              | Shenzhen LGT Test Service Co., Ltd.                                                                                                                      |
| Address:                   | Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China |
| Accreditation Certificate: | A2LA Certificate No.: 6727.01                                                                                                                            |
|                            | FCC Registration No.: 746540                                                                                                                             |
|                            | CAB ID: CN0136                                                                                                                                           |



## 2. FCC 47CFR §2.1091 REQUIREMENT

### 2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

### 2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

| Frequency Range<br>(MHz)                              | Electric Field<br>Strength (V/m) | Magnetic Field<br>Strength (A/m) | Power Density<br>(mW/cm <sup>2</sup> ) |
|-------------------------------------------------------|----------------------------------|----------------------------------|----------------------------------------|
| Limits for Occupational / controlled Exposures        |                                  |                                  |                                        |
| 0.3-3.0                                               | 614                              | 1.63                             | *(100)                                 |
| 3.0-30                                                | 1842/f                           | 4.89/f                           | *(900/f <sup>2</sup> )                 |
| 30-300                                                | 61.4                             | 0.163                            | 1.0                                    |
| 300 - 1500                                            | --                               | --                               | F/300                                  |
| 1500 – 100000                                         | --                               | --                               | 5.0                                    |
| Limits for General population / Uncontrolled Exposure |                                  |                                  |                                        |
| 0.3-1.34                                              | 614                              | 1.63                             | *(100)                                 |
| 1.34-30                                               | 824/f                            | 2.19/f                           | *(180/f <sup>2</sup> )                 |
| 30-300                                                | 27.5                             | 0.073                            | 0.2                                    |
| 300 - 1500                                            | --                               | --                               | F/1500                                 |
| 1500 – 100000                                         | --                               | --                               | 1.0                                    |

F= Frequency in MHz

\* = Plane-wave equivalent power density.

Friss Formula

Friss Transmission Formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.



## **2.3 EUT OPERATION CONDITION**

EUT was enabled to transmit and receive at lowest, middle and highest channels.

## **2.4 CLASSIFICATION**

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.



## 2.5 TEST RESULT

### The MPE result of worst mode:

| RF Function | Frequency (MHz) | Max Turn up Power (dBm) | Max Turn up Power (mW) | ANT Gain (dBi) | ANT Gain (gain of antenna in linear scale) | Power Density (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) | Ratio         | Result |
|-------------|-----------------|-------------------------|------------------------|----------------|--------------------------------------------|-------------------------------------|-----------------------------|---------------|--------|
| 433.92      | 433.92          | -63.50                  | 0.00000045             | 2              | 1.58                                       | 0.00000000014                       | 1                           | 0.00000000014 | Pass   |

Note: The maximum Equivalent Isotropic Radiated Power :  $31.26\text{dBuV/m} - 95.3 = -64.04\text{dBm}$  (refer to C63.10, section 10.3.9)

The 2.4GHz Wi-Fi max power density  $0.0301\text{ (mW/cm}^2\text{)}$ , Ratio: 0.0301.

The BLE max power density  $0.0011\text{ (mW/cm}^2\text{)}$ , Ratio: 0.0011.

433.92MHz+2.4GHz Wi-Fi or BLE Multiple transmission:  $0.0301 + 0.00000000014 = 0.03010000014 < 1$

### Note:

1. The RF Exposure is less than the limit, complies with the exemption requirements.
2. 2.4GHz Wi-Fi and BLE Worst MPE refer to Wi-Fi and Bluetooth Module FCC ID: 2ANDL-T1-3S, because the 2.4GHz Wi-Fi and BLE share the same antenna and can't transmit simultaneously.

\*\*\*\*\*END OF THE REPORT\*\*\*\*\*