FCC Part 15C Test Report
FCC ID:2BLFJ-F1036

Applicant:	Shenzhen Yingzhiying Electronic Technology Co., Ltd.
Address:	202-1, 2/F, Building 7, Longbi Industrial Zone, No. 27 Dafa Road, Dafapu Community, Bantian Street, Longgang District, Shenzhen, China
Manufacturer:	Shenzhen Yingzhiying Electronic Technology Co., Ltd.
Address:	202-1, 2/F, Building 7, Longbi Industrial Zone, No. 27 Dafa Road, Dafapu Community, Bantian Street, Longgang District, Shenzhen, China
EUT:	Tablet
Trade Mark:	N/A
Model Number:	F1036 E1036_EEA, M1036_EEA, M1036, S1036, S1036_EEA, Y1036, Y1036_EEA
Date of Receipt:	Oct. 17, 2024
Test Date:	Oct. 17, 2024 - Nov. 26, 2024
Date of Report:	Nov. 26, 2024
Prepared By:	Shenzhen DL Testing Technology Co., Ltd.
Address:	101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China
Applicable Standards:	FCC PART 15 C 15.247 ANSI C63.10:2013
Test Result:	Pass
Report Number:	DL-241017024-1ER

Prepared (Test Engineer):	Alisa Song
Reviewer (Supervisor):	Jack Bu
Approved (Manager):	Jade Yang

This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.

Table of Contents **Page**

1 . SUMMARY OF TEST RESULTS 4
1.1 MEASUREMENT UNCERTAINTY 4
2 . GENERAL INFORMATION 5
2.1 GENERAL DESCRIPTION OF EUT 5
2.2 DESCRIPTION OF TEST MODES 6
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 6
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 7
2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING 7
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS 8
3 . EMC EMISSION TEST 10
3.1 CONDUCTED EMISSION MEASUREMENT 10
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS 10
3.1.2 TEST PROCEDURE 10
3.1.3 DEVIATION FROM TEST STANDARD 10
3.1.4 TEST SETUP 11
3.1.5 EUT OPERATING CONDITIONS 11
3.1.6 TEST RESULTS 11
3.2 RADIATED EMISSION MEASUREMENT 14
3.2.1 RADIATED EMISSION LIMITS 14
3.2.2 TEST PROCEDURE 15
3.2.3 DEVIATION FROM TEST STANDARD 15
3.2.4 TEST SETUP 15
3.2.5 EUT OPERATING CONDITIONS 16
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ) 17
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ) 18
3.2.8 TEST RESULTS (1GHZ~25GHZ) 20
3.3 RADIATED BAND EMISSION MEASUREMENT 24
3.3.1 TEST REQUIREMENT: 24
3.3.2 TEST PROCEDURE 24
3.3.3 DEVIATION FROM TEST STANDARD 24
3.3.4 TEST SETUP 25
3.3.5 EUT OPERATING CONDITIONS 25
3.4 CONDUCTED BAND EDGE EMISSION&CONDUCTED SPURIOUS EMISSIONS MEASUREMENT 30
3.4.1 APPLICABLE STANDARD 30
3.4.2 TEST PROCEDURE 30
3.4.3 DEVIATION FROM STANDARD 30

Table of Contents **Page**

3.4.4 TEST SETUP 30
3.4.5 EUT OPERATION CONDITIONS 30
3.4.6 TEST RESULTS 30
4 . MAXIMUM PEAK CONDUCTED OUTPUT POWER MEASUREMENT 34
4.1 STANDARD APPLICABLE 34
4.1.1 TEST PROCEDURE 34
4.1.2 MEASURING INSTRUMENTS AND SETTING 34
4.1.3 TEST SETUP 34
4.1.4 EUT OPERATION DURING TEST 34
4.1.5 TEST RESULTS 35
5 . POWER SPECTRAL DENSITY TEST 36
5.1 APPLIED PROCEDURES / LIMIT 36
5.1.1 TEST PROCEDURE 36
5.1.2 DEVIATION FROM STANDARD 36
5.1.3 TEST SETUP 36
5.1.4 EUT OPERATION CONDITIONS 36
5.1.5 TEST RESULTS 37
6 . 6DB BANDWIDTH TEST 40
6.1 APPLIED PROCEDURES / LIMIT 40
6.1.1 TEST PROCEDURE 40
6.1.2 DEVIATION FROM STANDARD 40
6.1.3 TEST SETUP 40
6.1.4 EUT OPERATION CONDITIONS 40
6.1.5 TEST RESULTS 41
7 . ANTENNA REQUIREMENT 44
7.1 STANDARD REQUIREMENT 44
7.2 EUT ANTENNA 44
8 . TEST SETUP PHOTO 44
9 . EUT PHOTO 44

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.205, 15.209, 15.247(d)	Radiated Spurious Emission	PASS	
15.205, 15.247(d)	Band Edge Emission& Conducted Spurious Emissions	PASS	
15.247(b)	Peak output power	PASS	
15.247(a)(2)	6dB Bandwidth	PASS	
15.247(e)	Power Spectral Density	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

Test lab: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

FCC Test Firm Registration Number: 854456
Designation Number: CN1307
IC Registered No.: 27485
CAB ID.: CN0118

1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y** ± **U**, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**，providing a level of confidence of approximately **95** %。

No.	Item	Uncertainty
1	Conducted Emission Test	±2.56dB
2	RF power,conducted	±0.42dB
3	Spurious emissions,conducted	±2.76dB
4	All emissions,radiated(<1G)	±3.65dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%
8	6dB Bandwidth	±0.2MHz
9	Power Spectral Density	±2.45dBm

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	Tablet
Trademark	N/A
Model No.:	F1036 E1036_EEA, M1036_EEA, M1036, S1036, S1036_EEA, Y1036, Y1036_EEA
Model Difference	All models are same as the samples except model name and appearance color, they have the same structure and circuit.
Operation Frequency:	2412~2462 MHz for 802.11b/g/nHT20 2422~2452 MHz for 802.11nHT40
Channel numbers:	11 Channels for 802.11b/g/n(HT20) 7 channels for 802.11nHT40
Channel separation:	5MHz
Modulation technology:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n(20/40): OFDM(QPSK, BPSK, 16-QAM, 64-QAM)
Rate of Transmitter	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps 802.11n: up to 150Mbps
Antenna Type:	FPC antenna
Antenna gain:	0.69 dBi
Power Supply:	DC 5V from charger DC 3.8V from battery
Adapter:	MODEL: H-991 INPUT: 100-240VAC 50/60Hz Max 0.35A OUTPUT: 5V⎓2A

Note:
1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2.The EUT's all information provided by client.

2. Channel List(802.11b/g/nHT20)

Channel	Frequency (GHz)	Channel	Frequency (GHz)
01	2.412	07	2.442
02	2.417	08	2.447
03	2.422	09	2.452
04	2.427	10	2.457
05	2.432	11	2.462
06	2.437		

Channel List(802.11nHT40)

Channel	Frequency (GHz)	Channel	Frequency (GHz)
03	2.422	07	2.442
04	2.427	08	2.447
05	2.432	09	2.452
06	2.437		

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11nHT20 CH1/ CH6/ CH11
Mode 4	802.11nHT40 CH3/ CH6/ CH09
Mode 5	Link Mode
For Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode
For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11nHT20 CH1/ CH6/ CH11
Mode 4	802.11nHT40 CH3/ CH6/ CH09
Mode 5	Link Mode

Note: 1. The measurements are performed at the highest, middle, lowest available channels.
2. During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Power Line Conducted Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	Tablet	F1036	N/A	EUT
E-2	Adapter	H-991	N/A	Customer Provided

Item	Shielded Type	Ferrite Core	Length	Note

Note:

(1) For detachable type I/O cable should be specified the length in cm in『Length』column.

2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Max output power Setting				
Test software Version	Test program: SC2342B BT/WiFi			
Mode	802.11b	802.11g	802.11n HT20	802.11n HT40
Data Rate	1Mbps	6Mbps	MSC0	MSC0
Power Setting of Softwave	60	60	60	66

2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 04, 2023 Nov. 02, 2024	Nov. 03, 2024 Nov. 01, 2024
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 04, 2023 Nov. 02, 2024	Nov. 03, 2024 Nov. 01, 2024
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 04, 2023 Nov. 02, 2024	Nov. 03, 2024 Nov. 01, 2024
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
17	Power Sensor	Techoy	TR1029-2	512364	Nov. 05, 2023 Nov. 01, 2024	Nov. 04, 2024 Oct. 31, 2025
18	RF Swith	Techoy	TR1029-1	512364	Nov. 05, 2023 Nov. 01, 2024	Nov. 04, 2024 Oct. 31, 2025

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	YIHENG	843 Room	843	Nov. 04, 2023	Nov. 05, 2026
2	EMI Receiver	R&S	ESR	101421	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
3	LISN	R&S	ENV216	102417	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 04, 2023 Nov. 01, 2024	Nov. 03, 2024 Oct. 31, 2025

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.50	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

d. LISN at least 80 cm from nearest part of EUT chassis.

e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.
We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

3.1.6 TEST RESULTS

Temperature:	25 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 5



Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1590	32.33	10.05	42.38	65.52	-23.14	QP	P	
2	0.1590	17.52	10.05	27.57	55.52	-27.95	AVG	P	
3	0.3795	30.23	10.26	40.49	58.29	-17.80	QP	P	
4 *	0.3795	25.44	10.26	35.70	48.29	-12.59	AVG	P	
5	0.8655	27.68	10.06	37.74	56.00	-18.26	QP	P	
6	0.8655	14.81	10.06	24.87	46.00	-21.13	AVG	P	
7	2.1795	21.99	10.07	32.06	56.00	-23.94	QP	P	
8	2.1795	12.40	10.07	22.47	46.00	-23.53	AVG	P	
9	5.2800	19.53	10.44	29.97	60.00	-30.03	QP	P	
10	5.2800	5.85	10.44	16.29	50.00	-33.71	AVG	P	
11	10.1085	19.97	11.27	31.24	60.00	-28.76	QP	P	
12	10.1085	7.19	11.27	18.46	50.00	-31.54	AVG	P	

Temperature:	25 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 5



Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1770	29.65	10.15	39.80	64.63	-24.83	QP	P	
2	0.1770	18.60	10.15	28.75	54.63	-25.88	AVG	P	
3	0.4785	31.24	10.16	41.40	56.37	-14.97	QP	P	
4 *	0.4785	32.82	10.16	42.98	46.37	-3.39	AVG	P	
5	1.2975	31.21	10.09	41.30	56.00	-14.70	QP	P	
6	1.2975	23.05	10.09	33.14	46.00	-12.86	AVG	P	
7	2.4405	28.66	10.06	38.72	56.00	-17.28	QP	P	
8	2.4405	19.18	10.06	29.24	46.00	-16.76	AVG	P	
9	4.9875	25.73	10.32	36.05	56.00	-19.95	QP	P	
10	4.9875	16.61	10.32	26.93	46.00	-19.07	AVG	P	
11	9.6270	22.23	11.16	33.39	60.00	-26.61	QP	P	
12	9.6270	12.31	11.16	23.47	50.00	-26.53	AVG	P	

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to1.5 metre.
h. Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD

No deviation

3.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

Temperature:	20℃	Relative Humidtity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.8V
Test Mode :	Mode 5	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.

3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	DC 3.8V		
Test Mode :	Mode 5		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin	
		MHz	dBuV	dB	dBuV	dB	dB	Detector
1		41.1320	25.59	-13.70	11.89	40.00	-28.11	QP
2		57.7962	25.22	-13.53	11.69	40.00	-28.31	QP
3		103.8055	25.81	-14.56	11.25	43.50	-32.25	QP
4		257.4222	28.27	-13.21	15.06	46.00	-30.94	QP
5		595.1329	26.92	-5.44	21.48	46.00	-24.52	QP
6	*	744.8661	30.37	-3.25	27.12	46.00	-18.88	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;

Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
Test Voltage :	DC 3.8V		
Test Mode :	Mode 5		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin	
		MHz	dBuV	dB	dBuV	dB	dB	Detector
1		43.0505	26.01	-13.48	12.53	40.00	-27.47	QP
2		98.8326	26.12	-15.08	11.04	43.50	-32.46	QP
3		211.5265	25.76	-14.39	11.37	43.50	-32.13	QP
4		444.8514	27.16	-8.58	18.58	46.00	-27.42	QP
5		766.0571	26.13	-2.78	23.35	46.00	-22.65	QP
6	*	948.7610	28.41	-0.27	28.14	46.00	-17.86	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;

3.2.8 TEST RESULTS (1GHZ~25GHZ)

802.11b

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2412									
V	4824	67.46	50.65	6.88	31.29	54.98	74	-19.02	PK
V	4824	55.57	50.65	6.88	31.29	43.09	54	-10.91	AV
V	7236	66.62	49.98	7.16	36.63	60.43	74	-13.57	PK
V	7236	47.03	49.98	7.16	36.63	40.84	54	-13.16	AV
V	16087	48.81	51.53	11.34	41.52	50.14	74	-23.86	PK
H	4824	66.57	50.65	6.88	31.29	54.09	74	-19.91	PK
H	4824	55.72	50.65	6.88	31.29	43.24	54	-10.76	AV
H	7236	70.31	49.98	7.16	36.63	64.12	74	-9.88	PK
H	7236	45.40	49.98	7.16	36.63	39.21	54	-14.79	AV
H	16087	49.04	51.53	11.34	41.52	50.37	74	-23.63	PK
operation frequency:2437									
V	4874	68.19	50.67	6.89	31.38	55.79	74	-18.21	PK
V	4874	55.92	50.67	6.89	31.38	43.52	54	-10.48	AV
V	7311	69.74	50.02	7.24	36.63	63.59	74	-10.41	PK
V	7311	47.09	50.02	7.24	36.63	40.94	54	-13.06	AV
V	16087	48.47	51.53	11.34	41.52	49.8	74	-24.2	PK
H	4874	66.33	50.67	6.89	31.38	53.93	74	-20.07	PK
H	4874	55.97	50.67	6.89	31.38	43.57	54	-10.43	AV
H	7311	69.29	50.02	7.24	36.63	63.14	74	-10.86	PK
H	7311	47.76	50.02	7.24	36.63	41.61	54	-12.39	AV
H	16087	48.70	51.53	11.34	41.52	50.03	74	-23.97	PK
operation frequency:2462									
V	4924	67.52	50.79	6.83	31.36	54.92	74	-19.08	PK
V	4924	55.37	50.79	6.83	31.36	42.77	54	-11.23	AV
V	7386	68.05	50.11	7.25	36.58	61.77	74	-12.23	PK
V	7386	46.62	50.11	7.25	36.58	40.34	54	-13.66	AV
V	16087	47.99	51.53	11.34	41.52	49.32	74	-24.68	PK
H	4924	66.98	50.79	6.83	31.36	54.38	74	-19.62	PK
H	4924	56.52	50.79	6.83	31.36	43.92	54	-10.08	AV
H	7386	67.97	50.11	7.25	36.58	61.69	74	-12.31	PK
H	7386	48.23	50.11	7.25	36.58	41.95	54	-12.05	AV
H	16087	49.18	51.53	11.34	41.52	50.51	74	-23.49	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11g

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2412									
V	4824	67.10	50.65	6.88	31.29	54.62	74	-19.38	PK
V	4824	55.53	50.65	6.88	31.29	43.05	54	-10.95	AV
V	7236	66.36	49.98	7.16	36.63	60.17	74	-13.83	PK
V	7236	46.19	49.98	7.16	36.63	40	54	-14.00	AV
V	16087	49.69	51.53	11.34	41.52	51.02	74	-22.98	PK
H	4824	68.31	50.65	6.88	31.29	55.83	74	-18.17	PK
H	4824	51.34	50.65	6.88	31.29	38.86	54	-15.14	AV
H	7236	64.89	49.98	7.16	36.63	58.7	74	-15.3	PK
H	7236	46.62	49.98	7.16	36.63	40.43	54	-13.57	AV
H	16087	46.99	51.53	11.34	41.52	48.32	74	-25.68	PK
operation frequency:2437									
V	4874	66.96	50.67	6.89	31.38	54.56	74	-19.44	PK
V	4874	55.52	50.67	6.89	31.38	43.12	54	-10.88	AV
V	7311	66.12	50.02	7.24	36.63	59.97	74	-14.03	PK
V	7311	46.70	50.02	7.24	36.63	40.55	54	-13.45	AV
V	16087	48.47	51.53	11.34	41.52	49.8	74	-24.2	PK
H	4874	65.29	50.67	6.89	31.38	52.89	74	-21.11	PK
H	4874	54.49	50.67	6.89	31.38	42.09	54	-11.91	AV
H	7311	64.63	50.02	7.24	36.63	58.48	74	-15.52	PK
H	7311	46.39	50.02	7.24	36.63	40.24	54	-13.76	AV
H	16087	47.43	51.53	11.34	41.52	48.76	74	-25.24	PK
operation frequency:2462									
V	4924	67.34	50.79	6.83	31.36	54.74	74	-19.26	PK
V	4924	54.77	50.79	6.83	31.36	42.17	54	-11.83	AV
V	7386	66.05	50.11	7.25	36.58	59.77	74	-14.23	PK
V	7386	47.06	50.11	7.25	36.58	40.78	54	-13.22	AV
V	16087	46.22	51.53	11.34	41.52	47.55	74	-26.45	PK
H	4924	65.79	50.79	6.83	31.36	53.19	74	-20.81	PK
H	4924	53.77	50.79	6.83	31.36	41.17	54	-12.83	AV
H	7386	65.13	50.11	7.25	36.58	58.85	74	-15.15	PK
H	7386	44.97	50.11	7.25	36.58	38.69	54	-15.31	AV
H	16087	47.24	51.53	11.34	41.52	48.57	74	-25.43	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2412									
V	4824	67.19	50.65	6.88	31.29	54.71	74	-19.29	PK
V	4824	56.32	50.65	6.88	31.29	43.84	54	-10.16	AV
V	7236	67.39	49.98	7.16	36.63	61.2	74	-12.8	PK
V	7236	47.22	49.98	7.16	36.63	41.03	54	-12.97	AV
V	16087	47.58	51.53	11.34	41.52	48.91	74	-25.09	PK
H	4824	66.44	50.65	6.88	31.29	53.96	74	-20.04	PK
H	4824	55.44	50.65	6.88	31.29	42.96	54	-11.04	AV
H	7236	64.25	49.98	7.16	36.63	58.06	74	-15.94	PK
H	7236	47.28	49.98	7.16	36.63	41.09	54	-12.91	AV
H	16087	47.20	51.53	11.34	41.52	48.53	74	-25.47	PK
operation frequency:2437									
V	4874	67.45	50.67	6.89	31.38	55.05	74	-18.95	PK
V	4874	55.82	50.67	6.89	31.38	43.42	54	-10.58	AV
V	7311	66.52	50.02	7.24	36.63	60.37	74	-13.63	PK
V	7311	48.14	50.02	7.24	36.63	41.99	54	-12.01	AV
V	16087	48.19	51.53	11.34	41.52	49.52	74	-24.48	PK
H	4874	66.32	50.67	6.89	31.38	53.92	74	-20.08	PK
H	4874	54.22	50.67	6.89	31.38	41.82	54	-12.18	AV
H	7311	66.35	50.02	7.24	36.63	60.2	74	-13.8	PK
H	7311	47.44	50.02	7.24	36.63	41.29	54	-12.71	AV
H	16087	47.08	51.53	11.34	41.52	48.41	74	-25.59	PK
operation frequency:2462									
V	4924	66.25	50.79	6.83	31.36	53.65	74	-20.35	PK
V	4924	56.93	50.79	6.83	31.36	44.33	54	-9.67	AV
V	7386	63.37	50.11	7.25	36.58	57.09	74	-16.91	PK
V	7386	45.47	50.11	7.25	36.58	39.19	54	-14.81	AV
V	16087	47.28	51.53	11.34	41.52	48.61	74	-25.39	PK
H	4924	66.75	50.79	6.83	31.36	54.15	74	-19.85	PK
H	4924	54.73	50.79	6.83	31.36	42.13	54	-11.87	AV
H	7386	64.51	50.11	7.25	36.58	58.23	74	-15.77	PK
H	7386	47.09	50.11	7.25	36.58	40.81	54	-13.19	AV
H	16087	47.32	51.53	11.34	41.52	48.65	74	-25.35	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n HT40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2422									
V	4844	67.59	50.65	6.88	31.29	55.11	74	-18.89	PK
V	4844	56.73	50.65	6.88	31.29	44.25	54	-9.75	AV
V	7266	68.07	49.98	7.16	36.63	61.88	74	-12.12	PK
V	7266	47.17	49.98	7.16	36.63	40.98	54	-13.02	AV
V	16087	47.39	51.53	11.34	41.52	48.72	74	-25.28	PK
H	4844	68.14	50.65	6.88	31.29	55.66	74	-18.34	PK
H	4844	56.50	50.65	6.88	31.29	44.02	54	-9.98	AV
H	7266	66.09	49.98	7.16	36.63	59.9	74	-14.1	PK
H	7266	48.93	49.98	7.16	36.63	42.74	54	-11.26	AV
H	16087	48.19	51.53	11.34	41.52	49.52	74	-24.48	PK
operation frequency:2437									
V	4874	67.23	50.67	6.89	31.38	54.83	74	-19.17	PK
V	4874	55.18	50.67	6.89	31.38	42.78	54	-11.22	AV
V	7311	65.88	50.02	7.24	36.63	59.73	74	-14.27	PK
V	7311	47.23	50.02	7.24	36.63	41.08	54	-12.92	AV
V	16087	48.22	51.53	11.34	41.52	49.55	74	-24.45	PK
H	4874	66.18	50.67	6.89	31.38	53.78	74	-20.22	PK
H	4874	54.49	50.67	6.89	31.38	42.09	54	-11.91	AV
H	7311	66.45	50.02	7.24	36.63	60.3	74	-13.7	PK
H	7311	48.46	50.02	7.24	36.63	42.31	54	-11.69	AV
H	16087	47.23	51.53	11.34	41.52	48.56	74	-25.44	PK
operation frequency:2452									
V	4904	66.46	50.79	6.83	31.36	53.86	74	-20.14	PK
V	4904	55.42	50.79	6.83	31.36	42.82	54	-11.18	AV
V	7356	63.33	50.11	7.25	36.58	57.05	74	-16.95	PK
V	7356	46.86	50.11	7.25	36.58	40.58	54	-13.42	AV
V	16087	47.34	51.53	11.34	41.52	48.67	74	-25.33	PK
H	4904	66.16	50.79	6.83	31.36	53.56	74	-20.44	PK
H	4904	55.55	50.79	6.83	31.36	42.95	54	-11.05	AV
H	7356	64.63	50.11	7.25	36.58	58.35	74	-15.65	PK
H	7356	45.68	50.11	7.25	36.58	39.4	54	-14.60	AV
H	16087	46.97	51.53	11.34	41.52	48.3	74	-25.70	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULT

802.11b

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2412									
V	2390	76.07	52.12	2.73	27.38	54.06	74	-19.94	PK
V	2390	64.80	52.12	2.73	27.38	42.79	54	-11.21	AV
V	2400	76.38	52.16	2.78	27.41	54.41	74	-19.59	PK
V	2400	64.03	52.16	2.78	27.41	42.06	54	-11.94	AV
H	2390	75.66	52.12	2.73	27.38	53.65	74	-20.35	PK
H	2390	65.36	52.12	2.73	27.38	43.35	54	-10.65	AV
H	2400	76.07	52.16	2.78	27.41	54.1	74	-19.9	PK
H	2400	65.03	52.16	2.78	27.41	43.06	54	-10.94	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2462									
V	2483.5	76.75	52.23	2.86	27.44	54.82	74	-19.18	PK
V	2483.5	65.75	52.23	2.86	27.44	43.82	54	-10.18	AV
V	2500	76.64	52.26	2.88	27.49	54.75	74	-19.25	PK
V	2500	64.99	52.26	2.88	27.49	43.1	54	-10.9	AV
H	2483.5	76.32	52.23	2.86	27.44	54.39	74	-19.61	PK
H	2483.5	65.19	52.23	2.86	27.44	43.26	54	-10.74	AV
H	2500	76.29	52.26	2.88	27.49	54.4	74	-19.6	PK
H	2500	64.91	52.26	2.88	27.49	43.02	54	-10.98	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11g

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2412									
V	2390	75.32	52.12	2.73	27.38	53.31	74	-20.69	PK
V	2390	64.21	52.12	2.73	27.38	42.2	54	-11.8	AV
V	2400	75.36	52.16	2.78	27.41	53.39	74	-20.61	PK
V	2400	63.35	52.16	2.78	27.41	41.38	54	-12.62	AV
H	2390	76.52	52.12	2.73	27.38	54.51	74	-19.49	PK
H	2390	65.09	52.12	2.73	27.38	43.08	54	-10.92	AV
H	2400	76.52	52.16	2.78	27.41	54.55	74	-19.45	PK
H	2400	65.36	52.16	2.78	27.41	43.39	54	-10.61	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2462									
V	2483.5	75.31	52.23	2.86	27.44	53.38	74	-20.62	PK
V	2483.5	64.70	52.23	2.86	27.44	42.77	54	-11.23	AV
V	2500	75.14	52.26	2.88	27.49	53.25	74	-20.75	PK
V	2500	65.12	52.26	2.88	27.49	43.23	54	-10.77	AV
H	2483.5	76.44	52.23	2.86	27.44	54.51	74	-19.49	PK
H	2483.5	65.17	52.23	2.86	27.44	43.24	54	-10.76	AV
H	2500	76.09	52.26	2.88	27.49	54.2	74	-19.8	PK
H	2500	65.17	52.26	2.88	27.49	43.28	54	-10.72	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n HT20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2412									
V	2390	76.20	52.12	2.73	27.38	54.19	74	-19.81	PK
V	2390	65.36	52.12	2.73	27.38	43.35	54	-10.65	AV
V	2400	77.50	52.16	2.78	27.41	55.53	74	-18.47	PK
V	2400	65.33	52.16	2.78	27.41	43.36	54	-10.64	AV
H	2390	76.80	52.12	2.73	27.38	54.79	74	-19.21	PK
H	2390	64.73	52.12	2.73	27.38	42.72	54	-11.28	AV
H	2400	75.81	52.16	2.78	27.41	53.84	74	-20.16	PK
H	2400	65.08	52.16	2.78	27.41	43.11	54	-10.89	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2462									
V	2483.5	75.74	52.23	2.86	27.44	53.81	74	-20.19	PK
V	2483.5	64.56	52.23	2.86	27.44	42.63	54	-11.37	AV
V	2500	75.04	52.26	2.88	27.49	53.15	74	-20.85	PK
V	2500	64.02	52.26	2.88	27.49	42.13	54	-11.87	AV
H	2483.5	75.35	52.23	2.86	27.44	53.42	74	-20.58	PK
H	2483.5	64.01	52.23	2.86	27.44	42.08	54	-11.92	AV
H	2500	74.18	52.26	2.88	27.49	52.29	74	-21.71	PK
H	2500	64.99	52.26	2.88	27.49	43.1	54	-10.9	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n HT40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2422									
V	2390	75.53	52.12	2.73	27.38	53.52	74	-20.48	PK
V	2390	64.76	52.12	2.73	27.38	42.75	54	-11.25	AV
V	2400	77.05	52.16	2.78	27.41	55.08	74	-18.92	PK
V	2400	64.74	52.16	2.78	27.41	42.77	54	-11.23	AV
H	2390	75.37	52.12	2.73	27.38	53.36	74	-20.64	PK
H	2390	64.20	52.12	2.73	27.38	42.19	54	-11.81	AV
H	2400	74.11	52.16	2.78	27.41	52.14	74	-21.86	PK
H	2400	63.87	52.16	2.78	27.41	41.9	54	-12.10	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2452									
V	2483.5	76.69	52.23	2.86	27.44	54.76	74	-19.24	PK
V	2483.5	64.42	52.23	2.86	27.44	42.49	54	-11.51	AV
V	2500	75.68	52.26	2.88	27.49	53.79	74	-20.21	PK
V	2500	64.35	52.26	2.88	27.49	42.46	54	-11.54	AV
H	2483.5	75.37	52.23	2.86	27.44	53.44	74	-20.56	PK
H	2483.5	63.62	52.23	2.86	27.44	41.69	54	-12.31	AV
H	2500	74.24	52.26	2.88	27.49	52.35	74	-21.65	PK
H	2500	64.70	52.26	2.88	27.49	42.81	54	-11.19	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.4 CONDUCTED BAND EDGE EMISSION&CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

3.4.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).
If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

3.4.2 TEST PROCEDURE

Using the following spectrum analyzer setting:
Set the RBW = 100KHz.
Set the VBW = 300KHz.
Sweep time = auto couple.
Detector function = peak.
Trace mode = max hold.
Allow trace to fully stabilize.

3.4.3 DEVIATION FROM STANDARD

No deviation.

3.4.4 TEST SETUP



3.4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.4.6 TEST RESULTS

For Conducted

802.11b





802.11g





802.11n HT20





802.11n HT40


Keysight Spectrum Analyzer - Swept SA
Center Freq 2.402000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 100/100
04:47:10 PM Oct 29, 2024
Ref Offset 7.46 dB
10 dB/div
Ref 20.00 dBm
Mkr1 2.434 5 GHz
2.716 dBm
Start 2.35200 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.45200 GHz
Sweep 9.600 ms (1001 pts)
1 N 1 f 2.434 5 GHz 2.716 dBm
2 N 1 f 2.400 0 GHz -31.791 dBm
3 N 1 f 2.400 0 GHz -31.791 dBm
4 N 1 f 2.384 5 GHz -31.199 dBm


Keysight Spectrum Analyzer - Swept SA
Center Freq 2.472000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 100/100
05:17:15 PM Oct 29, 2024
Ref Offset 7 dB
10 dB/div
Ref 20.00 dBm
Mkr1 2.459 5 GHz
1.477 dBm
Start 2.42200 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.52200 GHz
Sweep 9.600 ms (1001 pts)
1 N 1 f 2.459 5 GHz 1.477 dBm
2 N 1 f 2.483 5 GHz -40.290 dBm
3 N 1 f 2.500 0 GHz -53.916 dBm
4 N 1 f 2.483 8 GHz -38.832 dBm

For Conducted
During the test, pre-scan the all modulation, and found the 802.11b mode which it is worse case.

Test channel:	Lowest channel



0.03GHz~26.5GHz

Test channel:	Middle channel



0.03GHz~26.5GHz

Test channel:	Highest channel



0.03GHz~26.5GHz

4. MAXIMUM PEAK CONDUCTED OUTPUT POWER MEASUREMENT

4.1 STANDARD APPLICABLE

According to §15.247(b): For systems using digital modulation in the 2400-2483.5 MHz and 5725-5850 MHz band, the limit for maximum peak conducted output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.
Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter peak output power.

4.1.1 TEST PROCEDURE

According to C63.10-2013 clause 11.9.1.3 Maximum peak conducted output power, 9.1.3 the maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

4.1.2 MEASURING INSTRUMENTS AND SETTING

Please refer to equipment's list in this report. The following table is the setting of the power meter.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION DURING TEST

1) The EUT is configured to transmit continuously.
2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

4.1 TEST RESULTS

Temperature:	25 ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.8V

Mode	Test Channel	Peak Output Power (dBm)	LIMIT (dBm)
802.11b	Low	7.380	30.00
	Middle	7.413	30.00
	High	7.572	30.00
802.11g	Low	6.833	30.00
	Middle	6.545	30.00
	High	6.807	30.00
802.11n HT20	Low	6.651	30.00
	Middle	6.410	30.00
	High	6.313	30.00
802.11n HT40	Low	5.955	30.00
	Middle	5.496	30.00
	High	5.380	30.00

5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW ≥ 100kHz
VB	VBW ≥ 3RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP

5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

Mode	Test Channel	Reading Level (dBm/100KHz)	Correct Factor (100KHz/3KHz) (dB)	Test Result (dBm/3kHz)	Limit (dBm/3kHz)	Result
802.11b	Low	-1.160	15.23	-16.390	8	PASS
	Middle	-1.144	15.23	-16.374	8	PASS
	High	-0.963	15.23	-16.193	8	PASS
802.11g	Low	-2.083	15.23	-17.313	8	PASS
	Middle	-2.692	15.23	-17.922	8	PASS
	High	-2.180	15.23	-17.410	8	PASS
802.11n20	Low	-2.303	15.23	-17.533	8	PASS
	Middle	-2.674	15.23	-17.904	8	PASS
	High	-3.082	15.23	-18.312	8	PASS
802.11n40	Low	-4.041	15.23	-19.271	8	PASS
	Middle	-5.557	15.23	-20.787	8	PASS
	High	-4.925	15.23	-20.155	8	PASS

Correct Factor=10log(100KHz/3KHz)=15.23dB

802.11b	802.11g
	
2412MHz	2412MHz
	
2437MHz	2437MHz
	
2462MHz	2462MHz

802.11n HT20	802.11n HT40
	
2412MHz	2422MHz
	
2437MHz	2437MHz
	
2462MHz	2452MHz

6. 6DB BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range(MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

	Test Channel	6dB Bandwidth (MHz)	Limit (MHz)	Result
802.11b	Low	9.302	0.5	Pass
	Middle	9.591	0.5	Pass
	High	8.952	0.5	Pass
802.11g	Low	16.426	0.5	Pass
	Middle	16.405	0.5	Pass
	High	16.45	0.5	Pass
802.11n HT20	Low	17.489	0.5	Pass
	Middle	17.184	0.5	Pass
	High	17.543	0.5	Pass
802.11n HT40	Low	34.354	0.5	Pass
	Middle	34.563	0.5	Pass
	High	35.605	0.5	Pass

802.11b	802.11g
	
2412MHz	2412MHz
	
2437MHz	2437MHz
	
2462MHz	2462MHz

802.11n HT20	802.11n HT40
	
2412MHz	2422MHz
	
2437MHz	2437MHz
	
2462MHz	2452MHz

7. ANTENNA REQUIREMENT

7.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.2 EUT ANTENNA

The EUT antenna is FPC antenna, It comply with the standard requirement.

8. TEST SETUP PHOTO

Reference to the appendix I for details.

9. EUT PHOTO

Reference to the appendix II for details.

※※※※※ **END OF REPORT** ※※※※※