FCC TEST REPORT

For

Dongguan Sile Crafts Co., Ltd.

Children's walkie-talkie

Test Model: DJ-002

Prepared for	:	Dongguan Sile Crafts Co., Ltd.
Address	:	No.1 Xinxing South Road, Xiansha, Gaobu Town, Dongguan City, China
Prepared by	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel	:	(+86)755-82591330
Fax	:	(+86)755-82591332
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	November 19, 2024
Number of tested samples	:	2
Sample No.	:	A241118039-1, A241118039-2
Serial number	:	Prototype
Date of Test	:	November 19, 2024 ~ December 18, 2024
Date of Report	:	December 19, 2024

FCC TEST REPORT
FCC CFR 47 PART 95

Report Reference No.	:	**LCSA11014018EA**
Date of Issue	:	December 19, 2024
Testing Laboratory Name.....	:	**Shenzhen LCS Compliance Testing Laboratory Ltd.**
Address	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Testing Location/ Procedure	:	Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □
Applicant's Name	:	**Dongguan Sile Crafts Co., Ltd.**
Address	:	No.1 Xinxing South Road, Xiansha, Gaobu Town, Dongguan City, China
Test Specification		
Standard	:	FCC CFR 47 PART 95
Test Report Form No.....	:	TRF-4-E-175 A/0
TRF Originator.....	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF.....	:	Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

EUT Description.	:	**Children's walkie-talkie**
Trade Mark	:	N/A
Test Model.....	:	DJ-002
Ratings	:	DC 4.5V by 3pcs 1.5V*AA Battery
Result	:	**Positive**

Compiled by:	**Supervised by:**	**Approved by:**
Nadia Zhou	Cary Luo	Gavin Liang
Nadia Zhou/ Administrator	Cary Luo/ Technique principal	Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No. : LCSA11014018EA	December 19, 2024 Date of issue

Test Model.....	: DJ-002
EUT.....	: Children's walkie-talkie
Applicant.....	**: Dongguan Sile Crafts Co., Ltd.**
Address.....	: No.1 Xinxing South Road, Xiansha, Gaobu Town, Dongguan City, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	**: Dongguan Sile Crafts Co., Ltd.**
Address.....	: No.1 Xinxing South Road, Xiansha, Gaobu Town, Dongguan City, China
Telephone.....	: /
Fax.....	: /
Factory.....	**: Dongguan Sile Crafts Co., Ltd.**
Address.....	: No.1 Xinxing South Road, Xiansha, Gaobu Town, Dongguan City, China
Telephone.....	: /
Fax.....	: /

Test Result	**Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	December 19, 2024	Initial Issue	---

TABLE OF CONTENTS

Description ..... Page

1. GENERAL INFORMATION 6
1.1. DESCRIPTION OF DEVICE (EUT) 6
1.2. SUPPORT EQUIPMENT LIST 7
1.3. EXTERNAL I/O CABLE 7
1.4. DESCRIPTION OF TEST FACILITY 7
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY 7
1.6. MEASUREMENT UNCERTAINTY 7
1.7. DESCRIPTION OF TEST MODES 8

2. TEST METHODOLOGY 9
2.1. TEST STANDARDS 9
2.2. EUT CONFIGURATION 9
2.3. EUT EXERCISE 9
2.4. GENERAL TEST PROCEDURES 9
2.5. TEST SAMPLE 9

3. SYSTEM TEST CONFIGURATION 10
3.1. JUSTIFICATION 10
3.2. EUT EXERCISE SOFTWARE 10
3.3. SPECIAL ACCESSORIES 10
3.4. BLOCK DIAGRAM/SCHEMATICS 10
3.5. EQUIPMENT MODIFICATIONS 10
3.6. TEST SETUP 10

4. SUMMARY OF TEST RESULTS 11

5. MEASUREMENT RESULTS 12
5.1. MAXIMUM TRANSMITTER POWER 12
5.2. OCCUPIED BANDWIDTH AND EMISSION MASK 14
5.3. MODULATION CHARACTERISTIC 16
5.4. FREQUENCY STABILITY 19
5.5. TRANSMITTER RADIATED SPURIOUS EMISSION 20
5.6. ANTENNA REQUIREMENTS 22

6. SUMMARY OF TEST EQUIPMENT 23

7. TEST SETUP PHOTOGRAPHS OF EUT 24

8. EXTERIOR PHOTOGRAPHS OF THE EUT 24

9. INTERIOR PHOTOGRAPHS OF THE EUT 24

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	: Children's walkie-talkie
Test Model	: DJ-002
Ratings	: DC 4.5V by 3pcs 1.5V*AA Battery
Hardware Version	: DR-2310
Software Version	: DR-2310-V4
Children's walkie-talkie	
Frequency Range	: 462.5625MHz
Channel Number	: 1 Channels
Test Channel	: Channel 1
Channel Spacing	: 12.5KHz
Modulation Type	: FM
Emission Type	: F3E
Rate Power	: 5mW(It was fixed by the manufacturer, any individual can't arbitrarily change it.)
Antenna Description	: Spring Antenna, -2.16dBi (Max.)

1.2. Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
--	--	--	--	--

1.3. External I/O Cable

I/O Port Description	Quantity	Cable
--	--	--

1.4. Description of Test Facility

NVLAP Accreditation Code is 600167-0.
FCC Designation Number is CN5024.
CAB identifier is CN0071.
CNAS Registration Number is L4595.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6. Measurement Uncertainty

Test Item	Uncertainty	Note
Frequency error	30 Hz	(1)
Transmitter power conducted	0.62 dB	(1)
Transmitter power Radiated	2.67 dB	(1)
Conducted spurious emission 9KHz-12.75 GHz	1.88 dB	(1)
Conducted Emission 9KHz-30MHz	1.63 dB	(1)
Radiated spurious emission 30~1000MHz	4.65 dB	(1)
Radiated spurious emission 1~18GHz	3.89 dB	(1)
Radiated spurious emission 18-40GHz	3.90 dB	(1)
Occupied Bandwidth	N/A	N/A
Emission Mask	N/A	N/A
Modulation Characteristic	N/A	N/A
Transmitter Frequency Behavior	N/A	N/A

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7. Description of Test Modes

The EUT has been tested under typical operating condition. As, test modes selected as below by the technical parameters of the EUT:

Operation Mode	Modulation	Channel Separation	Condition
TM1	FM	12.5KHz	TX

Frequency list:

Channel	Frequency(MHz)	Type	Rate Power
1	**462.5625**	FRS	5mW

Note1: In section 15.31(m), regards to the operating frequency range less than 1MHz, only one point centered in the frequency range of operation selected to measure.
Note2: The line display in grey was the channel selected for test. The tests for frequencies 462.5625MHz are manufacturer's requirements.

2. TEST METHODOLOGY

2.1. TEST STANDARDS

The tests were performed according to following standards:
FCC Rules Part 95: PERSONAL RADIO SERVICES.
ANSI/TIA-603-E-2016: Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.
FCC Part 2: FREQUENCY ALLOCA-TIONS AND RADIO TREATY MAT-TERS; GENERAL RULES AND REG-ULATIONS
ANSI C63.26: 2015: American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
ANSI C63.4: 2014: American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz

2.2. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.3. EUT Exercise

The EUT has been tested under typical operating condition and The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.4. General Test Procedures

2.4.1 Conducted Emissions

N/A

2.4.2 Radiated Emissions

The EUT is placed on a turntable, which is directly placed on the ground. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013

2.5. Test Sample

The application provides 1 samples to meet requirement;

Sample Number	Description
Sample 1	continuous transmit

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition.

3.2. EUT Exercise Software

N/ A

3.3. Special Accessories

N/ A

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 95				
FCC Rules	Description of Test	Test Sample	Result	Remark
FCC Part 2.1046 FCC Part 95.567	Maximum Transmitter Power	Sample 1	Compliant	Note 1
FCC Part 2.1047 FCC Part 95.575	Modulation Characteristic	Sample 1	Compliant	Note 1
FCC Part 2.1049 FCC Part 95.573 FCC Part 95.579	Occupied Bandwidth and Emission Mask	Sample 1	Compliant	Note 1
FCC Part 2.1053 FCC Part 95.579	Radiated Spurious Emission	Sample 1	Compliant	Note 1
FCC Part 2.1055（d） FCC Part 95.565	Frequency Stability	Sample 1	Compliant	Note 1
FCC Part 2.1093	RF Exposure	Sample 1	Compliant	Note 2
FCC Part 95.587	Antenna Requirements	Sample 1	Compliant	Note 1

Remark:
1. Note 1 – Test results inside test report;
2. Note 2 –Test results in other test report (SAR Report);

5. MEASUREMENT RESULTS

5.1. Maximum Transmitter Power

5.1.1 Block Diagram of Test Setup





5.1.2 Limit

According to FCC Part 95.567:
Each FRS transmitter type must be designed such that the effective radiated power (ERP) on channels 8 through 14 does not exceed 0.5 Watts and the ERP on channels 1 through 7 and 15 through 22 does not exceed 2.0 Watts.

5.1.3 Test Procedure

1. EUT was placed on a 1.5meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization.
   The radiated emission measurements of all test transmit frequencies were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be

calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, and the maximum value of the receiver should be recorded as (P_r).
4. The EUT shall be replaced by a substitution antenna. In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. An amplifier may be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.
   The measurement results are obtained as described below:
   Power (EIRP) = $P_{Mea} + P_{Ag} - P_{cl} + G_a$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.

5.1.4 Test Results

Temperature	23.5℃	Humidity	53.7%
Test Engineer	Paddi Chen	Test Voltage	Normal Voltage

Test Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain (dBi)	Correction (dB)	P_{Ag} (dB)	ERP (dBm)	ERP (W)	Polarization	Limit (W)
462.5625	-31.42	2.08	7.69	2.15	34.59	6.63	0.0053	V	2.0
462.5625	-31.51	2.08	7.69	2.15	34.59	6.54	0.0050	H	2.0

Remark:

1. *EIRP=P_{Mea}(dBm) +P_{Ag}(dB) -P_{cl}(dB) +G_a(dBi)*
2. *ERP = EIRP – 2.15dBi as EIRP by subtracting the gain of the dipole.*
3. *The field strength of radiation emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The data show in this report only with the worst case setup. After exploratory measurement the worst case of Z axis and receiver antenna at vertical polarization was reported.*
4. *Test only was performed at high power level*

5.2. Occupied Bandwidth and Emission Mask

5.2.1 Limit

According to FCC 95.573:
Each FRS transmitter type must be designed such that the occupied bandwidth does not exceed 12.5kHz.

According to FCC 95.579:
Attenuation requirements. The power of unwanted emissions must be attenuated below the carrier power output in Watts (P) by at least:
(1) 25 dB (decibels) in the frequency band 6.25 kHz to 12.5 kHz removed from the channel center frequency.
(2) 35 dB in the frequency band 12.5 kHz to 31.25 kHz removed from the channel center frequency.
(3) 43 + 10 log (P) dB in any frequency band removed from the channel center frequency by more than 31.25 kHz.

5.2.2 Block Diagram of Test Setup



5.2.3 Test Procedure

1. The EUT was modulated by 2.5 KHz Sine wave audio signal; the level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz (12.5 kHz channel spacing) and 5 kHz (25 kHz channel spacing).
2. Set SPA Center Frequency = fundamental frequency, RBW=300Hz, VBW= 3 KHz, span =50 KHz.
3. Set SPA Max hold. Mark peak, Set 99% Occupied Bandwidth and 26dB Occupied Bandwidth.
4. Test only was performed at high power level

5.2.4 Test Results

Temperature	23.5℃	Humidity	54.1%
Test Engineer	Paddi Chen	Test Voltage	Normal Voltage

Occupied Bandwidth:

Emission Type	Frequency (MHz)	99% OBW (kHz)	26dB bandwidth (kHz)	Limit (KHz)	Result
F3E	462.5625	5.977	6.089	12.5	Pass

Emission Designator
Per CFR 47 §2.201& §2.202, BW = 2M + 2D for FM Mode (Channel Spacing: 12.5 kHz)
Emission Designator 11K0F3E
In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.
BW = 2(M+D) = 2*(3.0 kHz + 2.5 kHz) = 11 kHz = 11K0
F3E portion of the designator represents an FM voice transmission
Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

Please refer to following page.

Test Plot of Occupied Bandwidth and Emission Mask	
Occupied Bandwidth	Emission Mask
	
Channel 1: 462.5625MHz	

5.3. Modulation Characteristic

5.3.1 Limit

According to CFR47 section 2.1047(a), for Voice Modulation Communication Equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000Hz shall be measured.

According to FCC 95.575:
Each FRS transmitter type must be designed such that the peak frequency deviation does not exceed 2.5 kHz, and the highest audio frequency contributing substantially to modulation must not exceed 3.125 kHz.

5.3.2 Block Diagram of Test Setup



5.3.3 Test Procedure

According to ANSI/TIA-603-E-2016

5.3.4 Test Results

Temperature	23.3℃	Humidity	53.4%
Test Engineer	Paddi Chen	Test Voltage	Normal Voltage

Modulation Limit:

Channel 1: 462.5625MHz					
Modulation Level (dB)	Peak Freq. Deviation At 300Hz (KHz)	Peak Freq. Deviation At 1004Hz (KHz)	Peak Freq. Deviation At 1500Hz (KHz)	Peak Freq. Deviation At 2500Hz (KHz)	Peak Freq. Deviation At 3000Hz (KHz)
-20	0.20	0.32	0.45	0.61	0.58
-15	0.30	0.48	0.60	0.73	0.67
-10	0.48	0.59	0.84	0.90	0.88
-5	0.59	0.71	1.53	1.53	1.51
0	0.88	0.83	1.63	1.80	2.11
+5	0.99	1.19	1.96	1.87	2.15
+10	1.25	1.82	2.05	2.03	2.25
+15	1.65	1.92	2.12	2.12	2.25
+20	1.79	1.99	2.18	2.27	2.26



Audio Frequency Response:

Channel 1: 462.5625MHz			
Modulation Frequency (Hz)	Peak Freq. Deviation (KHz)	Audio Frequency Response (dB)	Limit (KHz)
100	0.52	-22.27	3.125
200	0.85	-21.30	3.125
300	0.46	-11.04	3.125
400	0.50	-10.13	3.125
500	0.56	-8.07	3.125
600	0.69	-6.05	3.125
700	0.82	-5.04	3.125
800	0.91	-3.07	3.125
900	0.61	-2.03	3.125
1000	1.23	-1.32	3.125
1200	1.51	0.47	3.125
1400	1.75	1.16	3.125
1600	1.87	2.49	3.125
1800	1.96	4.41	3.125
2000	2.14	5.50	3.125
2200	2.17	5.46	3.125
2400	2.32	6.44	3.125
2600	2.30	7.53	3.125
2700	2.37	7.83	3.125
2800	2.82	8.47	3.125
3000	1.80	8.47	3.125
3500	1.79	9.77	3.125
4000	0.84	-20.37	3.125
4500	0.62	-21.35	3.125
5000	0.33	-22.42	3.125





Note:

1. All the modes had been tested, but only the worst data recorded in the report.

2. Test only was performed at high power level

5.4. Frequency Stability

5.4.1 Limit

According to FCC 95.565

Each FRS transmitter type must be designed such that the carrier frequencies remain within ±2.5 parts-per-million of the channel center frequencies specified in §95.563 during normal operating conditions.

5.4.2 Block Diagram of Test Setup



5.4.3 Test Procedure

The EUT was set in the climate chamber and connected to an external DC power supply. The RF output was directly connected to Spectrum Analyzer. The coupling loss of the additional cables was recorded and taken in account for all the measurements. After temperature stabilization (approx. 20 min for each stage), the frequency for the lower, the middle and the highest frequency range was recorded. For Frequency stability Vs. Voltage the EUT was connected to a DC power supply and the voltage was adjusted in the required ranges. The result was recorded.

5.4.4 Test Results

Temperature	22.6℃	Humidity	52.9%
Test Engineer	Paddi Chen	Test Voltage	Normal Voltage

Reference Frequency: 462.5625MHz					
Voltage (V)	Temperature (℃)	Frequency error (Hz)	Frequency Tolerance (%)	Limit (%)	Result
NV	-30	329	0.000071	0.00025%	Pass
	-20	427	0.000092		
	-10	449	0.000097		
	0	283	0.000061		
	10	483	0.000104		
	20	263	0.000057		
	30	305	0.000066		
	40	376	0.000081		
	50	215	0.000047		
LV	25	274	0.000059		
HV	25	400	0.000087		

Note:
1. Test only was performed at high power level.
2. List the worst result in this item

5.5. Transmitter Radiated Spurious Emission

5.5.1 Limit

According to FCC section 95.579, At least 43 + 10 log (Transmit Power) dB on any frequency band removed from the channel center frequency by more than 31.25 kHz.

5.5.2 Block Diagram of Test Setup





5.5.3 Test Procedure

a. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization.
The radiated emission measurements of all test transmit frequencies were measured with peak detector.

b. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

c. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum 100 kHz below 1GHz and 1MHz above 1GHz, Sweep from 30MHz to the 10th harmonic of the fundamental frequency; and recorded the level of the concerned spurious emission point as (P_r).

d. The EUT then replaced by a substitution antenna. In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization. The measurement results are obtained as described below:
Power (EIRP) = P_{Mea} - P_{cl} + G_a
Where;
P_{Mea} is the recorded signal generator level
P_{cl} is the cable loss connect between instruments
G_a Substitution Antenna Gain

e. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dBi) and known input power.

f. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.

g. Test site anechoic chamber refer to ANSI C63.10.

5.5.4 Test Results

Temperature	24.6℃	Humidity	52.4%
Test Engineer	Paddi Chen	Test Voltage	Normal Voltage

Test Frequency (MHz)	Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Distance (m)	G_a Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Pol.
462.5625	935.43	-24.30	3.54	3.00	12.87	-14.97	-13.00	1.97	V
	1402.83	-34.13	4.21	3.00	15.48	-22.86	-13.00	9.86	V
	1870.35	-32.27	4.52	3.00	17.32	-19.47	-13.00	6.47	V
	2338.43	-48.11	5.24	3.00	18.76	-34.59	-13.00	21.59	V
462.5625	935.36	-26.31	3.54	3.00	12.87	-16.98	-13.00	3.98	H
	1402.85	-37.20	4.21	3.00	15.48	-25.93	-13.00	12.93	H
	1870.31	-39.16	4.52	3.00	17.32	-26.36	-13.00	13.36	H
	2338.37	-43.45	5.24	3.00	18.76	-29.93	-13.00	16.93	H

Remark:

1. *EIRP = P_{Mea}(dBm) - P_{cl}(dB) + G_a(dBi)*
2. *Margin = Limit - EIRP*
3. *The Report only recorded the worst result（462.5625MHz）.*
4. *The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency，and only recorded worst spurious emissions.*
5. *Test only was performed at high power level.*
6. *List the worst result in this item*

5.6. Antenna Requirements

Excerpt from§ 95.587 FRS additional requirements

5.6.1 Antenna Requirements

Antenna. The antenna of each FRS transmitter type must meet the following requirements.

(1) The antenna must be a non-removable integral part of the FRS transmitter type.

(2) The gain of the antenna must not exceed that of a half-wave dipole antenna.

(3) The antenna must be designed such that the electric field of the emitted waves is vertically polarized when the unit is operated in the normal orientation.

5.6.2 Result

Compliant

EUT has non-removable Spring Antenna arrangement and the antenna gain is -2.16dBi(-4.31dBd), fulfill the requirement of this section.Detail refer to the EUT photo and test report.

6. SUMMARY OF TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Power Meter	R&S	NRVS	100444	2024-06-06	2025-06-05
2	Power Sensor	R&S	NRV-Z81	100458	2024-06-06	2025-06-05
3	Power Sensor	R&S	NRV-Z32	10057	2024-06-06	2025-06-05
4	Test Software	Tonscend	JS1120-2	/	N/A	N/A
5	RF Control Unit	Tonscend	JS0806-2	N/A	2024-11-08	2025-11-07
6	MXA Signal Analyzer	Agilent	N9020A	MY50510140	2024-10-08	2025-10-07
7	DC Power Supply	Agilent	E3642A	N/A	2024-10-08	2025-10-07
8	EMI Test Software	AUDIX	E3	/	N/A	N/A
9	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2024-06-06	2025-06-05
10	Positioning Controller	Max-Full	MF7802BS	MF780208586	N/A	N/A
11	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2024-07-13	2027-07-12
12	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2024-08-03	2027-08-02
13	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2024-07-13	2027-07-12
14	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2024-07-13	2027-07-12
15	Broadband Preamplifier	SCHWARZBECK	BBV9719	9719-025	2024-07-30	2025-07-29
16	EMI Test Receiver	R&S	ESR 7	101181	2024-06-06	2025-06-05
17	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2024-06-06	2025-06-05
18	Low-frequency amplifier	SchwarzZBECK	BBV9745	00253	2024-10-08	2025-10-07
19	High-frequency amplifier	JS Denki Pte	PA0118-43	JSPA21009	2024-10-08	2025-10-07
20	6dB Attenuator	/	100W/6dB	1172040	2024-06-06	2025-06-05
21	3dB Attenuator	/	2N-3dB	/	2024-10-08	2025-10-07
22	EMI Test Receiver	R&S	ESPI	101940	2024-06-06	2025-06-05
23	Artificial Mains	R&S	ENV216	101288	2024-06-06	2025-06-05
24	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2024-06-06	2025-06-05
25	EMI Test Software	Farad	EZ	/	N/A	N/A
26	Antenna Mast	Max-Full	MFA-515BSN	1308572	N/A	N/A
27	Pulse Limiter	R&S	ESH3-Z2	102750-NB	2024-06-06	2025-06-05

7. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

8. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

9. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

----------THE END OF REPORT----------