TEST REPORT

Reference No.	:	WTX24X08181877W001
FCC ID	:	2BLJP-INAIO070A
Applicant	:	INSTORESCREEN LLC
Address	:	7955 Airport Pulling rd, Suite206 Naples,FL 34109 USA
Manufacturer	:	The same as Applicant
Address	:	The same as Applicant
Product Name	:	InTOUCH07A-AllyW
Model No.	:	InAIO070A
Standards	:	FCC Part 15.407
Date of Receipt sample	:	2024-08-01
Date of Test	:	2024-08-01 to 2024-09-11
Date of Issue	:	2024-09-11
Test Report Form No.	:	WTX_Part 15_407W
Test Result	:	**Pass**

Remarks:
The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:
Waltek Testing Group (Shenzhen) Co., Ltd.
Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Mike Shi

Approved by:

Jason Su

TABLE OF CONTENTS

1. GENERAL INFORMATION 4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
1.2 TEST STANDARDS 5
1.3 TEST METHODOLOGY 5
1.4 TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING 5
1.5 EUT OPERATING DURING TEST 6
1.6 TEST FACILITY 6
1.7 EUT SETUP AND TEST MODE 7
1.8 MEASUREMENT UNCERTAINTY 8
1.9 TEST EQUIPMENT LIST AND DETAILS 9
2. SUMMARY OF TEST RESULTS 13
3. ANTENNA REQUIREMENT 14
3.1 STANDARD APPLICABLE 14
3.2 EVALUATION INFORMATION 14
4. AUTOMATICALLY DISCONTINUE TRANSMISSION 15
4.1 STANDARD APPLICABLE 15
4.2 SUMMARY OF TEST RESULTS 15
5. POWER SPECTRAL DENSITY 16
5.1 STANDARD APPLICABLE 16
5.2 TEST PROCEDURE 16
5.3 SUMMARY OF TEST RESULTS/PLOTS 17
6. EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH 18
6.1 STANDARD APPLICABLE 18
6.2 TEST PROCEDURE 18
6.3 SUMMARY OF TEST RESULTS/PLOTS 20
7. MAXIMUM CONDUCTED OUTPUT POWER 21
7.1 STANDARD APPLICABLE 21
7.2 TEST PROCEDURE 21
7.3 SUMMARY OF TEST RESULTS/PLOTS 22
8. RADIATED SPURIOUS EMISSIONS 23
8.1 STANDARD APPLICABLE 23
8.2 TEST PROCEDURE 23
8.3 TEST RECEIVER SETUP 25
8.4 CORRECTED AMPLITUDE & MARGIN CALCULATION 25
8.5 SUMMARY OF TEST RESULTS/PLOTS 25
9. FREQUENCY STABILITY 73
9.1 STANDARD APPLICABLE 73
9.2 TEST PROCEDURE 73
9.3 SUMMARY OF TEST RESULTS/PLOTS 73
10. CONDUCTED EMISSIONS 74
10.1 TEST PROCEDURE 74
10.2 BASIC TEST SETUP BLOCK DIAGRAM 74
10.3 TEST RECEIVER SETUP 74
10.4 SUMMARY OF TEST RESULTS/PLOTS 74
APPENDIX PHOTOGRAPHS 77

Report version

Version No.	Date of issue	Description
Rev.00	2024-09-11	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	InTOUCH07A-AllyW
Trade Name:	/
Model No.:	InAIO070A
Adding Model(s):	/
Rated Voltage:	DC 5V
Battery Capacity:	/
Power Adapter:	MODEL: M050200E111U1 INPUT: AC 100-240V, 50/60Hz, 0.35A Max, OUTPUT: DC5.0V, 2.0A
Note: The test data is gathered from a production sample, provided by the manufacturer.	

Technical Characteristics of EUT	
Support Standards:	802.11a, 802.11n(HT20), 802.11n-HT40, 802.11ac-VHT20, 802.11ac-VHT40, 802.11ac-VHT80
Frequency Range:	5180-5240MHz, 5745-5825MHz
Max. RF Output Power:	Band 1: 15.13dBm (Conducted) Band 4: 14.99dBm (Conducted)
Type of Modulation:	QPSK, 16QAM, 64QAM,256QAM
Type of Antenna:	FPC Antenna
Antenna Gain:	Band 1: -0.68dBi Band 4: -1.56dBi
Note The Antenna Gain is provided by the customer and can affect the validity of results.	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.407: General technical requirements.
ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
KDB789033 D02 v02r01: Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-Nii) Devices Part 15, Subparte.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB789033 D02 v02r01
The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Table for parameters of Test Software setting

Enter engineering mode in settings, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Mode	Test Frequency (MHz)												
	NCB: 20MHz												
	5180	5200	5240	5260	5300	5320	5500	5580	5700	5720	5745	5785	5825
802.11a 6Mbps	17	17	17	/	/	/	/	/	/	17	17	17	17
802.11n-HT20 MCS0	17	17	17	/	/	/	/	/	/	17	17	17	17
802.11ac-VHT20 MCS0	17	17	17	/	/	/	/	/	/	17	17	17	17

Mode	NCB: 40MHz									
	5190	5230	5270	5310	5510	5550	5670	5710	5755	5795
802.11n-HT40 MCS0	16	16	/	/	/	/	/	/	16	16
802.11ac -VHT40 MCS0	16	16	/	/	/	/	/	/	16	16

Mode	NCB: 80MHz					
	5210	5290	5530	5610	5690	5775
802.11ac-VHT80 MCS0	16	/	/	/	/	16

1.5 EUT Operating during test

EUT was programmed to be in continuously transmitting mode. During the test, EUT operation to normal function and programs under Android were executed.

1.6 Test Facility

Address of the test laboratory
Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.
Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990
Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is mai ntained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A
The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.7 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11a	5180MHz,5200MHz,5240MHz,5745MHz, 5785MHz,5825MHz
TM2	802.11n-HT20	5180MHz,5200MHz,5240MHz,5745MHz, 5785MHz,5825MHz
TM3	802.11ac-VHT20	5180MHz,5200MHz,5240MHz,5745MHz, 5785MHz,5825MHz
TM4	802.11n-HT40	5190MHz,5230MHz, 5755MHz,5795MHz
TM5	802.11ac-VHTT40	5190MHz,5230MHz, 5755MHz,5795MHz
TM6	802.11ac-VHT80	5210MHz, 5775MHz
Note: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.		

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	45~75 %
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Type-C Cable	1.5	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.8 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.42dB
Occupied Bandwidth	Conducted	±1.5%
Power Spectral Density	Conducted	±1.8dB
Conducted Spurious Emission	Conducted	±2.17dB
Conducted Emissions	Conducted	9-150kHz ±3.74dB
		0.15-30MHz ±3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz ±4.52dB
		0.2-1GHz ±5.56dB
		1-6GHz ±3.84dB
		6-18GHz ±3.92dB

1.9 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2024-02-24	2025-02-23
WTXE1005A 1005	Spectrum Analyzer	Agilent	N9020A	US47140102	2024-03-19	2025-03-18
WTXE1084A 1001	Spectrum Analyzer	Agilent	N9020A	MY54320548	2024-02-24	2025-02-23
WTXE1004A 1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2024-02-27	2025-02-26
WTXE1103A 1003	Attenuator	Pasternack	PE4007-4	/	2024-02-24	2025-02-23
WTXE1003A 1-005	Coaxial Cable	/	0M4RFC	/	2024-07-03	2025-01-03
☐Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2024-02-24	2025-02-23
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
WTXE1007A 1001	Amplifier	HP	8447F	2805A03475	2024-02-24	2025-02-23
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2024-02-24	2025-02-23
WTXE1104A 1032-1	Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-15
WTXE1104A 1032-2	Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-15
WTXE1104A 1032-3	Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-15
☐Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2024-02-24	2025-02-23
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
WTXE1065A 1001	Amplifier	C&D	PAP-1G18	2002	2024-02-27	2025-02-26
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2024-02-26	2025-02-25

WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-15
WTXE1104A 1033-2	Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-15
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-15
☐Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2024-02-24	2025-02-23
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2024-02-24	2025-02-23
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2024-07-03	2025-07-03
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-03
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-03
☒Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1007A 1002	Amplifier	HP	8447F	2944A038 69	2024-02-24	2025-02-23
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-03
WTXE1104A 1034-2	Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-03
WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-03
☒Chamber C: Above 1GHz						
WTXE1093A	EMI Test	Rohde &	ESIB 26	100401	2024-02-27	2025-02-26

1001	Receiver	Schwarz				
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2023-03-10	2026-03-09
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2024-02-27	2025-02-26
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2024-07-03	2025-07-03
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2024-07-03	2025-07-03
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2024-07-03	2025-07-03
☐Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2023-12-12	2024-12-11
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2024-02-24	2025-02-23
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2024-02-24	2025-02-23
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-03
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2024-07-03	2025-07-03
☒Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2024-02-24	2025-02-23
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2024-02-24	2025-02-23
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-03

Software List			
Description	**Manufacturer**	**Model**	**Version**
EMI Test Software (Radiated Emission A)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission B)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission C)	Farad	EZ-EMC	RA-03A1-2 (1.1.4.2)
EMI Test Software (Conducted Emission Room 1#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3
EMI Test Software (Conducted Emission Room 2#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.405	Antenna Requirement	Compliant
15.407 (c)	Automatically Discontinue Transmission	Compliant
§15.207; §15.407(b)(6)	Conducted Emission	Compliant
§15.407(a)(1),(2)	Power Spectral Density	Compliant
§15.407(e)	Emission Bandwidth and Occupied Bandwidth	Compliant
§15.407(a)(1),(2)	Maximum Conducted Output Power	Compliant
§15.407(b)(1),(2),(3),(4)	Undesirable emission	Compliant
§15.205; §15.407(b)(1),(2),(3)	Radiated Emission	Compliant
§15.407(g)	Frequency Stability	Compliant
§15.407(h)	Dynamic Frequency Selection (DFS)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information

This product has an FPC antenna, fulfill the requirement of this section.

4. Automatically Discontinue Transmission

4.1 Standard Applicable

According to FCC Part 15.407(c), the device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

4.2 Summary of Test Results

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

5. Power Spectral Density

5.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.
(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or 11 dBm + 10 log B, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

5.2 Test Procedure

According to 789033 D02 v02r01 General UNII Test Procedures New Rules v02, the following is the measurement procedure.
For devices operating in the bands 5.15-5.25GHz, 5.25-5.35GHz, and 5.47-5.725GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85GHz, the rules specify a measurement bandwidth of 500kHz. Many spectrum analyzers do not have 500kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500kHz, “provided that the measured power is integrated over the full

reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1MHz, or 500kHz). If measurements are performed using a reduced resolution bandwidth (< 1MHz, or < 500kHz) and integrated over 1 MHz, or 500kHz bandwidth, the following adjustments to the procedures apply:

a) Set RBW ≥ 1/T, where T is defined in section II.B.I.a).
b) Set VBW ≥ 3 RBW.
c) If measurement bandwidth of Maximum PSD is specified in 500kHz, add 10log(500kHz/RBW) to the measured result, whereas RBW (< 500kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add 10log(1MHz/RBW) to the measured result, whereas RBW (< 1MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100kHz for the sections 5.c) and 5.d) above, since RBW=100kHZ is available on nearly all spectrum analyzers.

5.3 Summary of Test Results/Plots

Please refer to Appendix D

6. Emission Bandwidth and Occupied Bandwidth

6.1 Standard Applicable

According to 15.407(a) and (e):

(1) For the band 5.15-5.25GHz.
(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or 11dBm + 10 log B, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(e) Within the 5.725-5.85GHz band, the minimum 6dB bandwidth of U-NII devices shall be at least 500kHz.

6.2 Test Procedure

According to 789033 D02 v02r0r section C&D, the following is the measurement procedure.

1. Emission Bandwidth (EBW)
a) Set RBW = approximately 1% of the emission bandwidth.
b) Set the VBW > RBW.

c) Detector = Peak.
d) Trace mode = max hold.
e) Measure the maximum width of the emission that is 26dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85GHz Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:
a) Set RBW = 100kHz.
b) Set the video bandwidth (VBW) ≥ 3 × RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.
Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

D. 99 Percent Occupied Bandwidth
The 99-percent occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission. Measurement of the 99-percent occupied bandwidth is required only as a condition for using the optional band-edge measurement techniques described in section II.G.3.d). Measurements of 99-percent occupied bandwidth may also optionally be used in lieu of the EBW to 789033 D02 v02r01 General UNII Test Procedures New Rules v01 define the minimum frequency range over which the spectrum is integrated when measuring maximum conducted output power as described in section II.E. However, the EBW must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with 15.407(a).

The following procedure shall be used for measuring (99 %) power bandwidth:
1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW ≥ 3 * RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency.

The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6.3 Summary of Test Results/Plots

Please refer to Appendix A1&A2&A3

7. Maximum Conducted Output Power

7.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.
(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or 11dBm + 10 log B, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

7.2 Test Procedure

According to KDB789033 D02 v02r01 section E, the following is the measurement procedure.

(i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1MHz.

(iii) Set VBW ≥ 3MHz.

(iv) Number of points in sweep ≥ 2 Span / RBW. (This ensures that bin-to-bin spacing is ≤ RBW/2, so that

narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

7.3 Summary of Test Results/Plots

Please refer to Appendix B&C

8. Radiated Spurious Emissions

8.1 Standard Applicable

According to §15.407(b), undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of −27dBm/MHz.

(2) For transmitters operating in the 5.25-5.35GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of −27dBm/MHz.

(3) For transmitters operating in the 5.47-5.725GHz band: All emissions outside of the 5.47-5.725GHz band shall not exceed an e.i.r.p. of −27dBm/MHz.

(4) For transmitters operating in the 5.725-5.85GHz band:

(i) All emissions shall be limited to a level of −27dBm/MHz at 75MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6dBm/MHz at 5MHz above or below the band edge, and from 5MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

According to §15.407(b)(6), Unwanted emissions below 1GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

According to §15.407(b)(7), The provisions of §15.205 apply to intentional radiators operating under this section.

789033 D02 v02r01 General UNII Test Procedures New Rules v01

If radiated measurements are performed, field strength is then converted to EIRP as follows:

EIRP = ((E*d)^2) / 30

where:

• E is the field strength in V/m;

• d is the measurement distance in meters;

• EIRP is the equivalent isotropically radiated power in watts.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.407(b)(6) and FCC Part 15.209 Limit..

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



8.3 Test Receiver Setup

During the radiated emission test for above 1GHz, the test receiver was set with the following configurations:

For peak detector:
RBW = 1000kHz, VBW = 3000kHz, Sweep Time = Auto

For average detector:
RBW = 1000kHz, VBW = 10Hz, Sweep Time = Auto

8.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Ant. Factor + Cable Loss – Ampl. Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit for Class B. The equation for margin calculation is as follows:

Margin = Corr. Ampl. – FCC Part 15 Limit

8.5 Summary of Test Results/Plots

Note: *this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

- Spurious Emission From 30MHz to 1GHz
- 5150-5250MHz

802.11a			
Test Channel	5180MHz(Worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	48.7191	28.96	-7.68	21.28	40.00	-18.72	-	-	peak
2	89.1579	33.43	-12.58	20.85	43.50	-22.65	-	-	peak
3	162.0197	28.38	-8.10	20.28	43.50	-23.22	-	-	peak
4	363.5231	29.62	-6.81	22.81	46.00	-23.19	-	-	peak
5	546.4368	30.40	-3.65	26.75	46.00	-19.25	-	-	peak
6	765.6482	30.50	0.45	30.95	46.00	-15.05	-	-	peak

802.11a			
Test Channel	5180MHz(Worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	37.5648	33.87	-8.47	25.40	40.00	-14.60	-	-	peak
2	91.0574	39.58	-12.54	27.04	43.50	-16.46	-	-	peak
3	133.0809	34.57	-9.18	25.39	43.50	-18.11	-	-	peak
4	181.3000	39.32	-9.88	29.44	43.50	-14.06	-	-	peak
5	201.4539	39.66	-11.42	28.24	43.50	-15.26	-	-	peak
6	315.8601	38.66	-7.52	31.14	46.00	-14.86	-	-	peak

802.11n-HT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	38.9081	28.99	-8.19	20.80	40.00	-19.20	-	-	peak
2	88.5336	31.21	-12.58	18.63	43.50	-24.87	-	-	peak
3	153.1627	28.69	-8.05	20.64	43.50	-22.86	-	-	peak
4	300.6988	29.61	-7.85	21.76	46.00	-24.24	-	-	peak
5	665.2610	31.23	-1.45	29.78	46.00	-16.22	-	-	peak
6	945.3336	32.02	3.19	35.21	46.00	-10.79	-	-	peak

802.11n-HT20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	38.0965	33.79	-8.36	25.43	40.00	-14.57	-	-	peak
2	90.4198	42.35	-12.57	29.78	43.50	-13.72	-	-	peak
3	133.0809	36.88	-9.18	27.70	43.50	-15.80	-	-	peak
4	183.8660	39.77	-10.16	29.61	43.50	-13.89	-	-	peak
5	201.4539	40.41	-11.42	28.99	43.50	-14.51	-	-	peak
6	315.8601	38.35	-7.52	30.83	46.00	-15.17	-	-	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	38.6357	27.91	-8.25	19.66	40.00	-20.34	-	-	peak
2	50.1080	27.13	-7.59	19.54	40.00	-20.46	-	-	peak
3	88.5336	31.33	-12.58	18.75	43.50	-24.75	-	-	peak
4	162.0197	27.84	-8.10	19.74	43.50	-23.76	-	-	peak
5	371.2680	29.21	-6.67	22.54	46.00	-23.46	-	-	peak
6	815.6353	31.71	1.17	32.88	46.00	-13.12	-	-	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	37.5648	34.45	-8.47	25.98	40.00	-14.02	-	-	peak
2	91.0574	36.16	-12.54	23.62	43.50	-19.88	-	-	peak
3	135.9163	36.73	-9.07	27.66	43.50	-15.84	-	-	peak
4	176.2748	37.56	-9.21	28.35	43.50	-15.15	-	-	peak
5	201.4539	39.88	-11.42	28.46	43.50	-15.04	-	-	peak
6	315.8601	38.42	-7.52	30.90	46.00	-15.10	-	-	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	39.7371	27.64	-8.01	19.63	40.00	-20.37	-	-	peak
2	88.5336	31.24	-12.58	18.66	43.50	-24.84	-	-	peak
3	148.9175	28.13	-8.14	19.99	43.50	-23.51	-	-	peak
4	205.7459	30.34	-11.51	18.83	43.50	-24.67	-	-	peak
5	512.9478	29.25	-4.56	24.69	46.00	-21.31	-	-	peak
6	787.4749	29.38	0.80	30.18	46.00	-15.82	-	-	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	37.3017	33.86	-8.53	25.33	40.00	-14.67	-	-	peak
2	88.5336	43.37	-12.58	30.79	43.50	-12.71	-	-	peak
3	136.8747	36.94	-9.03	27.91	43.50	-15.59	-	-	peak
4	182.5785	41.41	-10.02	31.39	43.50	-12.11	-	-	peak
5	201.4539	41.12	-11.42	29.70	43.50	-13.80	-	-	peak
6	315.8601	38.97	-7.52	31.45	46.00	-14.55	-	-	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	42.0350	28.56	-7.95	20.61	40.00	-19.39	-	-	peak
2	89.7866	30.72	-12.59	18.13	43.50	-25.37	-	-	peak
3	158.6399	28.02	-8.05	19.97	43.50	-23.53	-	-	peak
4	307.1053	28.57	-7.71	20.86	46.00	-25.14	-	-	peak
5	464.8867	29.28	-5.06	24.22	46.00	-21.78	-	-	peak
6	833.0127	29.98	1.36	31.34	46.00	-14.66	-	-	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	38.3651	33.84	-8.30	25.54	40.00	-14.46	-	-	peak
2	69.7179	33.61	-10.20	23.41	40.00	-16.59	-	-	peak
3	91.6995	39.84	-12.49	27.35	43.50	-16.15	-	-	peak
4	182.5785	39.10	-10.02	29.08	43.50	-14.42	-	-	peak
5	201.4539	40.81	-11.42	29.39	43.50	-14.11	-	-	peak
6	315.8601	38.64	-7.52	31.12	46.00	-14.88	-	-	peak

802.11ac-VHT80			
Test Channel	5210MHz(worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	46.7077	27.76	-7.83	19.93	40.00	-20.07	-	-	peak
2	89.1579	32.14	-12.58	19.56	43.50	-23.94	-	-	peak
3	154.2428	29.14	-8.05	21.09	43.50	-22.41	-	-	peak
4	250.4859	30.25	-9.68	20.57	46.00	-25.43	-	-	peak
5	373.8862	29.34	-6.62	22.72	46.00	-23.28	-	-	peak
6	809.9238	30.42	1.11	31.53	46.00	-14.47	-	-	peak

802.11ac-VHT80			
Test Channel	5210MHz(worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	38.6357	34.07	-8.25	25.82	40.00	-14.18	-	-	peak
2	91.0574	37.41	-12.54	24.87	43.50	-18.63	-	-	peak
3	136.8747	37.59	-9.03	28.56	43.50	-14.94	-	-	peak
4	176.2748	38.88	-9.21	29.67	43.50	-13.83	-	-	peak
5	201.4539	39.79	-11.42	28.37	43.50	-15.13	-	-	peak
6	315.8601	38.40	-7.52	30.88	46.00	-15.12	-	-	peak

➢ 5725-5850MHz

802.11a			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	50.4614	28.04	-7.64	20.40	40.00	-19.60	-	-	peak
2	89.7866	31.35	-12.59	18.76	43.50	-24.74	-	-	peak
3	153.1627	28.70	-8.05	20.65	43.50	-22.85	-	-	peak
4	336.4817	28.65	-7.20	21.45	46.00	-24.55	-	-	peak
5	642.2923	29.78	-1.62	28.16	46.00	-17.84	-	-	peak
6	899.9577	30.69	2.09	32.78	46.00	-13.22	-	-	peak

802.11a			
Test Channel	5745MHz(worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	38.0965	34.49	-8.36	26.13	40.00	-13.87	-	-	peak
2	88.5336	36.17	-12.58	23.59	43.50	-19.91	-	-	peak
3	133.0809	36.69	-9.18	27.51	43.50	-15.99	-	-	peak
4	182.5785	38.93	-10.02	28.91	43.50	-14.59	-	-	peak
5	201.4539	39.70	-11.42	28.28	43.50	-15.22	-	-	peak
6	315.8601	38.80	-7.52	31.28	46.00	-14.72	-	-	peak

802.11n-HT20			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	37.8297	28.68	-8.41	20.27	40.00	-19.73	-	-	peak
2	89.1579	32.23	-12.58	19.65	43.50	-23.85	-	-	peak
3	159.7586	28.45	-8.05	20.40	43.50	-23.10	-	-	peak
4	350.9722	29.49	-7.05	22.44	46.00	-23.56	-	-	peak
5	565.9776	29.71	-3.10	26.61	46.00	-19.39	-	-	peak
6	827.1795	30.86	1.29	32.15	46.00	-13.85	-	-	peak

802.11n-HT20			
Test Channel	5745MHz(worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	37.5648	33.08	-8.47	24.61	40.00	-15.39	-	-	peak
2	89.1579	42.93	-12.58	30.35	43.50	-13.15	-	-	peak
3	137.8400	37.00	-8.98	28.02	43.50	-15.48	-	-	peak
4	178.7697	38.28	-9.57	28.71	43.50	-14.79	-	-	peak
5	201.4539	39.80	-11.42	28.38	43.50	-15.12	-	-	peak
6	315.8601	38.87	-7.52	31.35	46.00	-14.65	-	-	peak

802.11ac-VHT20			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	38.3651	29.84	-8.30	21.54	40.00	-18.46	-	-	peak
2	89.1579	30.69	-12.58	18.11	43.50	-25.39	-	-	peak
3	154.2428	28.24	-8.05	20.19	43.50	-23.31	-	-	peak
4	259.4434	29.55	-9.31	20.24	46.00	-25.76	-	-	peak
5	495.2379	29.77	-4.85	24.92	46.00	-21.08	-	-	peak
6	958.7135	30.92	3.34	34.26	46.00	-11.74	-	-	peak

802.11ac-VHT20			
Test Channel	5745MHz(worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	69.7179	32.95	-10.20	22.75	40.00	-17.25	-	-	peak
2	90.4198	36.38	-12.57	23.81	43.50	-19.69	-	-	peak
3	134.9645	36.46	-9.11	27.35	43.50	-16.15	-	-	peak
4	178.7697	39.88	-9.57	30.31	43.50	-13.19	-	-	peak
5	201.4539	40.11	-11.42	28.69	43.50	-14.81	-	-	peak
6	315.8601	39.38	-7.52	31.86	46.00	-14.14	-	-	peak

802.11n-HT40			
Test Channel	5755MHz(worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	49.7571	27.34	-7.59	19.75	40.00	-20.25	-	-	peak
2	89.1579	31.45	-12.58	18.87	43.50	-24.63	-	-	peak
3	156.4259	29.79	-8.05	21.74	43.50	-21.76	-	-	peak
4	439.4730	28.90	-5.42	23.48	46.00	-22.52	-	-	peak
5	633.3285	29.15	-1.70	27.45	46.00	-18.55	-	-	peak
6	965.4742	31.30	3.37	34.67	54.00	-19.33	-	-	peak

802.11n-HT40			
Test Channel	5755MHz(worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	38.0965	34.43	-8.36	26.07	40.00	-13.93	-	-	peak
2	88.5336	42.72	-12.58	30.14	43.50	-13.36	-	-	peak
3	135.9163	37.09	-9.07	28.02	43.50	-15.48	-	-	peak
4	182.5785	41.93	-10.02	31.91	43.50	-11.59	-	-	peak
5	201.4539	41.38	-11.42	29.96	43.50	-13.54	-	-	peak
6	315.8601	38.95	-7.52	31.43	46.00	-14.57	-	-	peak

802.11ac-VHT40			
Test Channel	5755MHz(worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	51.8999	27.48	-7.79	19.69	40.00	-20.31	-	-	peak
2	88.5336	30.74	-12.58	18.16	43.50	-25.34	-	-	peak
3	170.1888	28.92	-8.34	20.58	43.50	-22.92	-	-	peak
4	392.7376	29.41	-6.36	23.05	46.00	-22.95	-	-	peak
5	655.9766	30.57	-1.52	29.05	46.00	-16.95	-	-	peak
6	932.1405	30.72	2.87	33.59	46.00	-12.41	-	-	peak

802.11ac-VHT40			
Test Channel	5755MHz(worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	37.0405	34.18	-8.58	25.60	40.00	-14.40	-	-	peak
2	89.1579	37.56	-12.58	24.98	43.50	-18.52	-	-	peak
3	137.8400	37.22	-8.98	28.24	43.50	-15.26	-	-	peak
4	177.5179	40.00	-9.38	30.62	43.50	-12.88	-	-	peak
5	201.4539	40.07	-11.42	28.65	43.50	-14.85	-	-	peak
6	315.8601	38.72	-7.52	31.20	46.00	-14.80	-	-	peak

802.11ac-VHT80			
Test Channel	5775MHz(worst case)	Polarity:	Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	45.7333	28.03	-7.90	20.13	40.00	-19.87	-	-	peak
2	88.5336	30.66	-12.58	18.08	43.50	-25.42	-	-	peak
3	167.8136	28.26	-8.25	20.01	43.50	-23.49	-	-	peak
4	311.4519	28.84	-7.61	21.23	46.00	-24.77	-	-	peak
5	520.2079	29.63	-4.41	25.22	46.00	-20.78	-	-	peak
6	979.1392	30.57	3.42	33.99	54.00	-20.01	-	-	peak

802.11ac-VHT80			
Test Channel	5775MHz(worst case)	Polarity:	Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	39.4588	33.34	-8.07	25.27	40.00	-14.73	-	-	peak
2	88.5336	44.24	-12.58	31.66	43.50	-11.84	-	-	peak
3	135.9163	37.74	-9.07	28.67	43.50	-14.83	-	-	peak
4	182.5785	41.51	-10.02	31.49	43.50	-12.01	-	-	peak
5	201.4539	41.45	-11.42	30.03	43.50	-13.47	-	-	peak
6	315.8601	38.39	-7.52	30.87	46.00	-15.13	-	-	peak

Remark: '-'Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

➢ Spurious Emission above 1GHz

802.11a- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	65.65	-12.53	53.12	74.00	-20.88	-	-	peak

802.11a- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5142.184	47.17	-12.58	34.59	54.00	-19.41	-	-	AVG

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	66.60	-12.53	54.07	74.00	-19.93	-	-	peak

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	48.91	-12.53	36.38	54.00	-17.62	-	-	AVG

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5146.092	65.56	-12.55	53.01	74.00	-20.99	-	-	peak

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	48.74	-12.53	36.21	54.00	-17.79	-	-	AVG

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5148.697	74.73	-12.53	62.20	74.00	-11.80	-	-	peak

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	57.58	-12.53	45.05	54.00	-8.95	-	-	AVG

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5147.395	76.18	-12.54	63.64	74.00	-10.36	-	-	peak

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	59.02	-12.53	46.49	54.00	-7.51	-	-	AVG

802.11ac-VHT80- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5146.092	76.31	-12.55	63.76	74.00	-10.24	-	-	peak

802.11ac-VHT80- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	60.32	-12.53	47.79	54.00	-6.21	-	-	AVG

Note: The Restricted Bandedge was tested in Horizontal /Vertical and the worst case position data was reported.

Remark: '-'Means' the test Degree and Height is not recorded by the test software and only show the worst case in the test report.

- For the frequency band 5.15-5.25GHz, 5.725-5.850GHz (802.11a)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5180MHz)							
10360	52.82	7.11	59.93	74	-14.07	H	PK
10360	37.36	7.11	44.47	54	-9.53	H	AV
10360	48.94	7.11	56.05	74	-17.95	V	PK
10360	33.71	7.11	40.82	54	-13.18	V	AV
Middle Channel (5200MHz)							
10400	53.03	7.22	60.25	74	-13.75	H	PK
10400	37.03	7.22	44.25	54	-9.75	H	AV
10400	54.09	7.22	61.31	74	-12.69	V	PK
10400	39.12	7.22	46.34	54	-7.66	V	AV
High Channel (5240MHz)							
10480	53.27	7.69	60.96	74	-13.04	H	PK
10480	38.34	7.69	46.03	54	-7.97	H	AV
10480	49.54	7.69	57.23	74	-16.77	V	PK
10480	38.72	7.69	46.41	54	-7.59	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5745MHz)							
11490	52.86	9.45	62.31	74	-11.69	H	PK
11490	38.17	9.45	47.62	54	-6.38	H	AV
11490	53.69	9.45	63.14	74	-10.86	V	PK
11490	39.48	9.45	48.93	54	-5.07	V	AV
Middle Channel (5785MHz)							
11570	51.16	9.62	60.78	74	-13.22	H	PK
11570	39.25	9.62	48.87	54	-5.13	H	AV
11570	53.28	9.62	62.90	74	-11.10	V	PK
11570	35.50	9.62	45.12	54	-8.88	V	AV
High Channel (5825MHz)							
11650	52.50	9.84	62.34	74	-11.66	H	PK
11650	35.21	9.84	45.05	54	-8.95	H	AV
11650	48.87	9.84	58.71	74	-15.29	V	PK
11650	37.61	9.84	47.45	54	-6.55	V	AV

➢ Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-34.36	-27
Highest	Above 5350	-37.67	-27
Note: the data just list the worst cases			

➢ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-32.01	-27
	5650 to 5700	-31.64	-27 to -17
	5700 to 5720	-27.32	-17 to 15.6
	5720 to 5725	-16.58	15.6 to 27
Highest	5850 to 5855	-12.99	27 to 15.6
	5855 to 5875	-25.11	15.6 to -17
	5875 to 5925	-35.79	-17 to -27
	Above 5925	-39.29	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz, 5.725-5.850GHz (802.11n-HT20)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5180MHz)							
10360	51.76	7.11	58.87	74	-15.13	H	PK
10360	38.10	7.11	45.21	54	-8.79	H	AV
10360	53.90	7.11	61.01	74	-12.99	V	PK
10360	39.49	7.11	46.60	54	-7.40	V	AV
Middle Channel (5200MHz)							
10400	54.28	7.22	61.50	74	-12.50	H	PK
10400	38.22	7.22	45.44	54	-8.56	H	AV
10400	50.76	7.22	57.98	74	-16.02	V	PK
10400	37.38	7.22	44.60	54	-9.40	V	AV
High Channel (5240MHz)							
10480	52.54	7.69	60.23	74	-13.77	H	PK
10480	37.71	7.69	45.40	54	-8.60	H	AV
10480	54.13	7.69	61.82	74	-12.18	V	PK
10480	37.90	7.69	45.59	54	-8.41	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5745MHz)							
11490	50.06	9.45	59.51	74	-14.49	H	PK
11490	38.02	9.45	47.47	54	-6.53	H	AV
11490	52.12	9.45	61.57	74	-12.43	V	PK
11490	36.42	9.45	45.87	54	-8.13	V	AV
Middle Channel (5785MHz)							
11570	54.75	9.62	64.37	74	-9.63	H	PK
11570	39.51	9.62	49.13	54	-4.87	H	AV
11570	51.48	9.62	61.10	74	-12.90	V	PK
11570	39.32	9.62	48.94	54	-5.06	V	AV
High Channel (5825MHz)							
11650	55.12	9.84	64.96	74	-9.04	H	PK
11650	37.69	9.84	47.53	54	-6.47	H	AV
11650	52.22	9.84	62.06	74	-11.94	V	PK
11650	37.14	9.84	46.98	54	-7.02	V	AV

➢ Out of Band edge 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-33.48	-27
Highest	Above 5350	-36.30	-27
Note: the data just list the worst cases			

➢ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-34.01	-27
	5650 to 5700	-30.44	-27 to -17
	5700 to 5720	-28.26	-17 to 15.6
	5720 to 5725	-15.05	15.6 to 27
Highest	5850 to 5855	-13.57	27 to 15.6
	5855 to 5875	-23.70	15.6 to -17
	5875 to 5925	-34.85	-17 to -27
	Above 5925	-40.37	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz, 5.725-5.850GHz (802.11ac-VHT20)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5180MHz)							
10360	53.30	7.11	60.41	74	-13.59	H	PK
10360	37.08	7.11	44.19	54	-9.81	H	AV
10360	53.23	7.11	60.34	74	-13.66	V	PK
10360	39.05	7.11	46.16	54	-7.84	V	AV
Middle Channel (5200MHz)							
10400	53.62	7.22	60.84	74	-13.16	H	PK
10400	40.49	7.22	47.71	54	-6.29	H	AV
10400	50.76	7.22	57.98	74	-16.02	V	PK
10400	38.51	7.22	45.73	54	-8.27	V	AV
High Channel (5240MHz)							
10480	52.39	7.69	60.08	74	-13.92	H	PK
10480	38.20	7.69	45.89	54	-8.11	H	AV
10480	56.30	7.69	63.99	74	-10.01	V	PK
10480	37.37	7.69	45.06	54	-8.94	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5745MHz)							
11490	49.93	9.45	59.38	74	-14.62	H	PK
11490	36.83	9.45	46.28	54	-7.72	H	AV
11490	50.17	9.45	59.62	74	-14.38	V	PK
11490	38.74	9.45	48.19	54	-5.81	V	AV
Middle Channel (5785MHz)							
11570	49.48	9.62	59.10	74	-14.90	H	PK
11570	38.59	9.62	48.21	54	-5.79	H	AV
11570	50.46	9.62	60.08	74	-13.92	V	PK
11570	38.19	9.62	47.81	54	-6.19	V	AV
High Channel (5825MHz)							
11650	49.19	9.84	59.03	74	-14.97	H	PK
11650	35.97	9.84	45.81	54	-8.19	H	AV
11650	51.10	9.84	60.94	74	-13.06	V	PK
11650	37.76	9.84	47.60	54	-6.40	V	AV

➢ Out of Band edge 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-33.57	-27
Highest	Above 5350	-37.24	-27
Note: the data just list the worst cases			

➢ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-33.39	-27
	5650 to 5700	-31.63	-27 to -17
	5700 to 5720	-27.87	-17 to 15.6
	5720 to 5725	-15.42	15.6 to 27
Highest	5850 to 5855	-14.60	27 to 15.6
	5855 to 5875	-25.32	15.6 to -17
	5875 to 5925	-33.39	-17 to -27
	Above 5925	-31.63	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz, 5.725-5.850GHz (802.11n-HT40)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5190MHz)							
10380	53.74	7.89	61.63	74	-12.37	H	PK
10380	38.81	7.89	46.70	54	-7.30	H	AV
10380	53.17	7.89	61.06	74	-12.94	V	PK
10380	40.68	7.89	48.57	54	-5.43	V	AV
High Channel (5230MHz)							
10460	-8.63	-8.63	-8.63	-8.63	-8.63	H	PK
10460	-8.63	-8.63	-8.63	-8.63	-8.63	H	AV
10460	-8.63	-8.63	-8.63	-8.63	-8.63	V	PK
10460	-8.63	-8.63	-8.63	-8.63	-8.63	V	AV

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5755MHz)							
11510	51.12	9.45	60.57	74	-13.43	H	PK
11510	37.60	9.45	47.05	54	-6.95	H	AV
11510	52.02	9.45	61.47	74	-12.53	V	PK
11510	37.95	9.45	47.40	54	-6.60	V	AV
High Channel (5795MHz)							
11590	49.96	9.27	59.23	74	-14.77	H	PK
11590	37.10	9.27	46.37	54	-7.63	H	AV
11590	51.20	9.27	60.47	74	-13.53	V	PK
11590	36.21	9.27	45.48	54	-8.52	V	AV

➢ Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-34.52	-27
Highest	Above 5350	-37.88	-27
Note: the data just list the worst cases			

➢ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-33.02	-27
	5650 to 5700	-31.56	-27 to -17
	5700 to 5720	-27.63	-17 to 15.6
	5720 to 5725	-17.32	15.6 to 27
Highest	5850 to 5855	-15.37	27 to 15.6
	5855 to 5875	-25.41	15.6 to -17
	5875 to 5925	-35.80	-17 to -27
	Above 5925	-37.88	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz, 5.725-5.850GHz (802.11ac-VHT40)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5190MHz)							
10380	51.79	7.89	59.68	74	-14.32	H	PK
10380	39.00	7.89	46.89	54	-7.11	H	AV
10380	52.15	7.89	60.04	74	-13.96	V	PK
10380	37.57	7.89	45.46	54	-8.54	V	AV
High Channel (5230MHz)							
10460	53.54	7.97	61.51	74	-12.49	H	PK
10460	39.73	7.97	47.70	54	-6.30	H	AV
10460	52.86	7.97	60.83	74	-13.17	V	PK
10460	37.38	7.97	45.35	54	-8.65	V	AV

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5755MHz)							
11510	50.03	9.45	59.48	74	-14.52	H	PK
11510	37.65	9.45	47.10	54	-6.90	H	AV
11510	48.60	9.45	58.05	74	-15.95	V	PK
11510	36.95	9.45	46.40	54	-7.60	V	AV
High Channel (5795MHz)							
11590	49.62	9.27	58.89	74	-15.11	H	PK
11590	37.78	9.27	47.05	54	-6.95	H	AV
11590	48.82	9.27	58.09	74	-15.91	V	PK
11590	38.91	9.27	48.18	54	-5.82	V	AV

➢ Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-31.81	-27
Highest	Above 5350	-36.33	-27
Note: the data just list the worst cases			

➢ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-32.13	-27
	5650 to 5700	-31.90	-27 to -17
	5700 to 5720	-27.22	-17 to 15.6
	5720 to 5725	-16.11	15.6 to 27
Highest	5850 to 5855	-14.15	27 to 15.6
	5855 to 5875	-23.95	15.6 to -17
	5875 to 5925	-34.58	-17 to -27
	Above 5925	-37.97	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz, 5.725-5.850GHz (802.11ac-VHT80)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
5210MHz							
10420	54.10	7.53	61.63	74	-12.37	H	PK
10420	36.85	7.53	44.38	54	-9.62	H	AV
10420	52.97	7.53	60.50	74	-13.50	H	PK
10420	39.68	7.53	47.21	54	-6.79	H	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
5775MHz							
11550	51.42	9.93	61.35	74	-12.65	H	PK
11550	37.31	9.93	47.24	54	-6.76	H	AV
11550	49.96	9.93	59.89	74	-14.11	V	PK
11550	35.45	9.93	45.38	54	-8.62	V	AV

- Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-32.35	-27
Highest	Above 5350	-36.90	-27
Note: the data just list the worst cases			

- Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-32.76	-27
	5650 to 5700	-30.88	-27 to -17
	5700 to 5720	-26.44	-17 to 15.6
	5720 to 5725	-15.12	15.6 to 27
Highest	5850 to 5855	-14.50	27 to 15.6
	5855 to 5875	-22.40	15.6 to -17
	5875 to 5925	-33.88	-17 to -27
	Above 5925	-38.15	-27
Note: the data just list the worst cases			

Note: Testing is carried out with frequency rang 9kHz to 40Ghz, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Frequency Stability

9.1 Standard Applicable

According to §15.407(g), manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

9.2 Test Procedure

According to §2.1055, the following test procedure was performed.
The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.
The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode.

9.3 Summary of Test Results/Plots

Please refer to Appendix E

10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.
The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

10.2 Basic Test Setup Block Diagram



10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150kHz
Stop Frequency 30MHz
Sweep Speed ..... Auto
IF Bandwidth..... 10kHz
Quasi-Peak Adapter Bandwidth 9kHz
Quasi-Peak Adapter Mode ..... Normal

10.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)	
1	0.1540	29.44	9.74	39.18	65.78	-26.60	QP
2	0.1700	16.06	9.68	25.74	54.96	-29.22	AVG
3	0.5380	30.36	9.73	40.09	56.00	-15.91	QP
4*	0.5380	21.20	9.73	30.93	46.00	-15.07	AVG
5	1.3580	14.08	9.65	23.73	46.00	-22.27	AVG
6	1.3820	25.32	9.65	34.97	56.00	-21.03	QP

Test Mode	Communication	AC120V 60Hz	Polarity:	Line



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)	
1	0.5380	37.88	9.73	47.61	56.00	-8.39	QP
2*	0.5420	29.44	9.73	39.17	46.00	-6.83	AVG
3	0.9580	19.45	9.68	29.13	46.00	-16.87	AVG
4	0.9740	28.98	9.67	38.65	56.00	-17.35	QP
5	1.3420	16.82	9.65	26.47	46.00	-19.53	AVG
6	1.3540	27.85	9.65	37.50	56.00	-18.50	QP

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

******* END OF REPORT *******